

Description

The present invention relates to a musical tone control apparatus, and more particularly to a musical tone generating apparatus to thereby generate a musical tone in response to a movement of player's hand, fingers or the like.

Conventionally, the music is performed by operating a keyboard and some switches in an electronic musical instrument, for example. However, in order to perform such electronic musical instrument, the player's movement must be always restricted, and it is impossible to perform the music with dancing. Meanwhile, the present applicant has proposed the musical tone control apparatus capable of controlling the musical tone based on the movement of player in prior, not prepublished EP-0264 782. Such musical tone control apparatus can be played with dancing. However, this proposed musical tone control apparatus can not control the musical tone delicately.

Meanwhile, another known electronic keyboard musical instrument detects the initial-touch and after-touch of keys to thereby vary the musical tone. Herein, the initial-touch is the touch response corresponding to the varying speed in depth or force of each key depression at the instant when the key is depressed. The after-touch is the touch response corresponding to the continuous variation degree of depressing pressure of each key in a period when the key is continuously depressed. As the method of detecting the initial-touch, each key provides a break contact which is "on" when the key is not depressed and a make contact which is "on" when the key is depressed. In this case, by counting the time interval between a first time when the key is depressed so that the break contact is off and a second time when the make contact is on, it is possible to obtain an initial-touch signal corresponding to the varying speed of depressing pressure at the instant when the key is depressed. As the method of detecting the after-touch, a pressure sensor for detecting the depressing pressure of key is provided. In this case, it is possible to obtain an after-touch signal corresponding to the continuous variation of depressing pressure based on the output of this pressure sensor.

In order to detect the initial-touch in the conventional electronic keyboard musical instrument, each key must provide all of the break contact, make contact and counting circuit for measuring the time. Further, in order to detect the after-touch, each key must provide the pressure sensor additionally. Since the initial-touch and after-touch are detected by the different detecting means independently, the constitution of electronic keyboard musical instrument must be complicated. Further,

since the key provides some contacts, there is a problem in that chattering must be occurred.

FR-A-2,224,061 relates to the features of the preamble of claim 1.

It is therefore a primary object of the present invention to provide a musical tone control apparatus which can be performed with freely moving player's hands or feet.

The present invention is directed to a musical tone control apparatus as set forth in the preamble of claim 1 and is characterized by the features of the characterizing part of claim 1.

Further objects and advantages of the present invention will be apparent from the following description, reference being had to the accompanying drawings wherein preferred embodiments of the present invention are clearly shown.

In the drawings:

Fig. 1 is a block diagram showing whole constitution of a musical tone control apparatus according to a first embodiment of the present invention;

Fig. 2 is a perspective side view showing appearances of right and left grip devices used in the first embodiment;

Fig. 3 is a front view showing an appearance of player who mounts the first embodiment;

Fig. 4 is a perspective side view showing a belt type main unit used in the first embodiment;

Fig. 5 is a graph showing characteristic of a piezoelectric element used in the first embodiment;

Figs. 6 and 7 are drawings each showing an example of functions assigned to the pressure sensors;

Fig. 8 is a block diagram showing a second embodiment;

Fig. 9 is a perspective side view showing appearances of grip devices and angle detectors according to the second embodiment;

Fig. 10 is a perspective side view showing an example for mounting the angle detector;

Fig. 11 is a front sectional view showing inner constitution of the angle detector;

Fig. 12 is a sectional view showing constitution of a mercury switch used in the angle detector; and

Fig. 13 is a view showing an example of functions assigned to the pressure sensors in the second embodiment.

Now, description will be given with respect to the preferred embodiments of the present invention in conjunction with the drawings, wherein like reference characters designate like or corresponding parts throughout several views.

[A] FIRST EMBODIMENT

Fig. 1 is a block diagram showing the whole constitution of a musical tone control apparatus according to the first embodiment of the present invention. Fig. 2 is a view showing appearances of grip devices 1R and 1L for player's right and left hands, and Fig. 3 is a front view showing the appearance of player who mounts the musical tone control apparatus according to the first embodiment.

First, description will be given with respect to the constitutions of the grip devices 1R and 1L for player's right and left hands in conjunction with Fig. 2. These grip devices 1R and 1L are constituted symmetrically. Hence, description of the left grip device 1L will be omitted, and description will be given with respect to the right grip device 1R only. The left grip device 1L is constituted by the parts corresponding to those of the right grip 1R, wherein these parts are labeled with the letter "L" instead of the letter "R".

In the right grip device 1R, 2R designates a case having the shape which can be held by the right hand. In other words, in order to fit the holding case 2R with the right hand, a curved face 2Ra which can be in close contact with the root portion between the thumb and index finger of right hand and another stopping portion 2Rb which is held between the third finger and middle finger of right hand are respectively formed at the holding case 2R (see Fig. 3). In addition, the holding case 2R has seven pressure sensors SR1 to SR7 each of which is constituted by a push button and piezoelectric element. This piezoelectric element has resistance which is varied in response to depressing pressure of the push button.

Next, description will be given with respect to the arrangement of these pressure sensors SR1 to SR7. Each of these pressure sensors SR1 to SR7 is arranged at the predetermined position such that each pressure sensor can be easily depressed by each of five fingers when the grip device 1R is held by the right hand. More specifically, the pressure sensors SR1 and SR2 are arranged laterally such that these pressure sensors SR1 and SR2 can be depressed by the thumb, the pressure sensors SR3 and SR4 are arranged vertically such that these pressure sensors SR3 and SR4 can be depressed by the index finger, and the pressure sensors SR5 to SR7 are arranged vertically such that these pressure sensors SR5 to SR7 can be respectively depressed by the middle finger, third finger and little finger. Because of such arrangement, these pressure sensors SR1 to SR7 can be smoothly depressed by five fingers of right hand without effort.

When each pressure sensor is depressed by each finger tip, the depressing pressure effects on its piezoelectric element whose resistance will be varied. These pressure sensors SR1 to SR7 are connected to a belt type main unit (i.e., musical tone control data generating means) 5 via a cable 3R and connector 4R. As shown in Fig. 3, this main unit 5 is mounted to the player's waist. Fig. 4 shows an appearance of this belt type main unit 5.

Next, in Fig. 1, one terminals of these pressure sensors SR1 to SR7 are connected in common to the main unit 5 via the cable 3R and then grounded. On the other hand, other terminals of these pressure sensors SR1 to SR7 are connected to the main unit 5 via the cable 3R and then pulled up respectively by pull-up resistors r . In addition, these other terminals are respectively connected to key-on/touch detecting circuits 6R1 to 6R7.

Each of these key-on/touch detecting circuits 6R1 to 6R7 outputs key-on signal KON, initial touch-data ITD and after-touch data ATD based on the detection voltage supplied from each of the pressure sensors SR1 to SR7. The key-on signal KON is outputted when the depressing pressure applied to each pressure sensor becomes larger than the predetermined pressure. In addition, the initial-touch data ITD are the data whose value corresponds to the varying speed of initial touch, i.e., the varying speed of depressing pressure at the instant when each pressure sensor is depressed. Further, the after-touch data ATD are the data whose value corresponds to the continuous variation of depressing pressure while each finger starts and then stops to depress each pressure sensor.

Each of these key-on/touch detecting circuits 6R1 to 6R7 has the same constitution, hence, description will be given with respect to the constitution of key-on/touch detecting circuit 6R1 only.

More specifically, the key-on/touch detecting circuit 6R1 is constituted by an analog-to-digital (A/D) converter 7, comparator circuit 8, delay circuit 9, AND gate 10 and register 11. The A/D converter 7 converts the detection voltage supplied from the pressure sensor SR1 into digital detection voltage data VD of predetermined bits. Such data VD are outputted as the after-touch data ATD. Then, the comparator circuit 8 compares the detection voltage data VD with the reference voltage data V_{ref} . In the case where $VD > V_{ref}$, the output level of comparator circuit 8 is turned to "H" level. This output signal of comparator circuit 8 is supplied to a first terminal of AND gate 10. In addition, this output signal is delayed by the predetermined time T in the delay circuit 9 and then supplied to a second terminal of AND gate 10. Therefore, when the predetermined time T has passed after $VD > V_{ref}$, the output level of AND gate 10 turns to "H"

level so that such output signal of AND gate 10 having the "H" level is outputted as the key-on signal KON. Meanwhile, the output signal of delay circuit 9 is also supplied to a load terminal L of register 11. When the output level of delay circuit 9 is turned to "H" level, the register 11 latches the detection voltage data VD, and then such latched data are outputted as the initial-touch data ITD.

Next, description will be given with respect to the reason why the data latched by the register 11 are outputted as the initial-touch data ITD when the predetermined time T is passed after $VD > V_{ref}$ in conjunction with Fig. 5.

Fig. 5 is a graph showing the relation between the depressing pressure applied to the pressure sensor and its resistance. In Fig. 5, it is supposed that the resistance of pressure sensor reaches at R_{ref} so that the detection voltage VD will be equal to the reference voltage V_{ref} when the depressing pressure reaches at P0. Then, in the case where the depressing pressure is applied to the pressure sensor with relatively weak touch (i.e., in the case where the varying speed of depressing pressure is relatively slow), the depressing pressure reaches at P1 so that the resistance will be equal to R_{init1} when the predetermined time T is passed away. On the contrary, in the case where the depressing pressure is applied to the pressure sensor with relatively strong touch (i.e., in the case where the varying speed of depressing pressure is relatively fast), the depressing pressure reaches at P2 ($> P1$) so that the resistance will be equal to R_{init2} ($< R_{init1}$). As described above, the resistance of pressure sensor when the predetermined time T is passed after the depressing pressure exceeds over P0 depends on the intensity of touch. The resistance will be R_{init2} when the touch is strong, while the resistance will be R_{init1} when the touch is weak. Since the detection voltage data VD outputted from the A/D converter 7 correspond to the resistance of piezoelectric element within the pressure sensor, it is possible to obtain the initial-touch data ITD by latching such detection voltage data VD in the register 11.

The above-mentioned key-on/touch detecting circuits 6R1 to 6R7 are respectively provided for the pressure sensors SR1 to SR7. Similarly, key-on/touch detecting circuits 6L1 to 6L7 are provided for the pressure sensors SL1 to SL7 of the left grip device 1L. The key-on signal KON, initial-touch data ITD and after-touch data ATD outputted from each of the key-on/touch detecting circuits 6R1 to 6R7 and 6L1 to 6L7 are supplied to a multiplexer 12.

Based on a channel select signal CS supplied to its select terminal, the multiplexer 12 selects and outputs the key-on signal KON, initial-touch data ITD and after-touch data ATD outputted from one

of the key-on/touch detecting circuits 6R1 to 6R7 and 6L1 to 6L7. Meanwhile, 14 designates a central processing unit (CPU), 16 designates a read only memory (ROM) for storing programs used in the CPU 14, and 17 designates a random access memory (RAM) which is used as a work area. The CPU 14 sequentially changes the channel select signal CS to thereby scan the output data of key-on/touch detecting circuits with high speed. Then, the CPU 14 transmits the selected output data to the RAM 17. Based on such selected output data, the CPU 14 generates key code data KC for designating the tone pitch, tone volume data VOL for designating the tone volume and tone color designating data TD for designating the tone color. Incidentally, these key-on signal KON, key code data KC, tone volume data VOL and tone color designating data TD are called as musical tone control data MCD.

In addition, 18 designates a console panel including push switches (see Fig. 4) and encoder which encodes and outputs the outputs of push switches to the CPU 14. Further, 19 designates a liquid crystal display (LCD) indicator (see Fig. 4), and 20 designates a transmitter which modulates the musical tone control data MCD with the carrier wave to thereby output the modulated data from an antenna 20a by wireless. A MIDI circuit 21 converts the musical tone control data MCD into the data of MIDI (musical instrument digital interface) standard, and such data of MIDI standard will be outputted to an external device (not shown) via an output terminal 21a.

Next, description will be given with respect to the operation of the musical tone control apparatus according to the first embodiment.

In order to perform the music, the player mounts the belt type main unit 5 at his waist as shown in Fig. 3. Then, the connectors 4R and 4L at the tip edges of cables 3R and 3L which are stretched from the grip device 1R and 1L are respectively connected to connectors 5R and 5L of the main unit 5 (see Fig. 4). Further, in the case where the musical tone generating apparatus is driven by use of wire, the connection cable is connected between the output terminal 21a and musical tone generating apparatus. Thereafter, the power is applied to the main unit 5 mounted at the player's waist and the musical tone generating apparatus. Next, the push switches of console panel 18 are operated so that wire-transmission or wireless-transmission (i.e., the method for transmitting the data to the musical tone generating apparatus) is designated. In addition, functions are assigned to each pressure sensor of the grip devices 1R and 1L.

In the first embodiment, one of first to fourth octaves is designated based on the outputs of

pressure sensors SR1 to SR4 in the right grip device 1R. In addition, based on the combination of the outputs of pressure sensors SR5 to SR7, one of musical scales Cⁿ, Dⁿ, ..., Bⁿ and Cⁿ⁺¹ is designated. In this case, the value "1" corresponds to the key-on and the value "0" corresponds to the key-off in the outputs of pressure sensors SR5 to SR7. Further, based on the outputs of pressure sensors SL1 to SL4 in the left grip device 1L, the key-on and touch intensity are designated. Furthermore, based on the outputs of pressure sensors SL5 to SL7, the tone color is designated.

Next, the player holds the grip devices 1R and 1L by his right and left hands respectively. Then, the player operates the push button in the console panel 18 for commanding the start timing to thereby start the performance. Thereafter, the CPU 14 sequentially transmits the key-on signal KON, initialtouch data ITD and after-touch data ATD to the RAM 18, wherein these data are obtained from one of the key-on/touch detecting circuits 6R1 to 6R7 and 6L1 to 6L7. Based on the transmitted data, the CPU 14 generates the musical tone control data MCD, which are then outputted to the MIDI circuit 21. The MIDI circuit 21 converts the supplied musical tone control data MCD into the data of MIDI standard, which are then outputted to the external musical tone generating apparatus via the output terminal 21a and connection cable. Thus, the musical tone generating circuit generates the musical tone from its speaker based on the data of MIDI standard.

In this case, the functions as shown in Fig. 6 are assigned to the pressure sensors of the grip devices 1R and 1L. For example, the right thumb depresses the pressure sensor SR1 to thereby designate the first octave, the right middle finger depresses the pressure sensor SR5 to thereby designate musical scale Gⁿ, and the left little finger depresses the pressure sensor SL7 to thereby designate the flute. In such state, when the left thumb depresses the pressure sensor SL1, the musical tone generating apparatus generates the musical tone having the touch corresponding to its depressing intensity, the tone color of flute and the musical scale G¹. Thereafter, when the left index finger depresses the pressure sensor SL3, the musical tone generating apparatus generates the musical tone having the touch corresponding to its depressing intensity and the tone pitch which is higher than the scale G¹ by half-tone. On the other hand, when the left index finger depresses the pressure sensor SL4, the musical tone generating apparatus generates the musical tone having the touch corresponding to its depressing intensity and the tone pitch which is lower than the scale G¹ by half-tone.

In the period when the pressure sensors SR1 to SR4 for designating the octave and the pressure

sensors SL5 to SL7 for designating the tone color are depressed, the CPU 14 judges the designation of the depressed pressure sensor valid. Incidentally, it is possible to maintain the designations of these pressure sensors SR1 to SR4 and SL5 to SL7. As shown in Fig. 7, it is possible to assign some musical effects such as the tone volume, vibrato and wow based on the outputs of pressure sensors SL5 to SL7 of the left grip device 1L. These musical effects can be arbitrarily set by the player who operates the push switches of the console panel 18.

In the case where "wireless" is selected as the method of transmitting the data to the musical tone generating apparatus, the musical tone control data MCD are supplied to the transmitter 20. Then, the LCD indicator 19 displays the operation contents and the like of the console panel 18.

In the first embodiment described heretofore, the thumb and index finger capable of moving delicately operate two of four pressure sensors SR1 to SR4 (or SL1 to SL4), while the remaining middle finger, third finger and little finger operate one of the pressure sensors SR5 to SR7 (or SL5 to SL7). Hence, the ten fingers can operate the total fourteen pressure sensors without effort.

In addition, in the first embodiment, it is possible to detect both of the initial-touch and after-touch based on the output signal of single pressure sensor (i.e., SR1 to SR7 and SL1 to SL7).

Incidentally, it is possible to apply this musical tone control apparatus to the normal electronic keyboard musical instrument such that the initial-touch and after-touch of key can be detected. In addition, it is possible to re-design the first embodiment so that the analog detection voltage of each pressure sensor will be directly used without converting such analog detection voltage into the digital detection voltage data VD in the A/D converter 7.

[B] SECOND EMBODIMENT

Next, description will be given with respect to the second embodiment. This second embodiment as shown in Figs. 8 and 9 is characterized by further comprising angle detectors 30R and 30L for player's right and left arms as compared to the first embodiment shown in Fig. 1. In Fig. 8, parts corresponding to those of first embodiment shown in Fig. 1 are designated by the same numerals, hence, description thereof will be omitted.

In Fig. 8, similar to the grip devices 1R and 1L described before, the angle detectors 30R and 30L are constituted symmetrically. Therefore, hereinafter, description will be given with respect to the right angle detector 30R only, and description of the left angle detector 30L will be omitted.

As shown in Fig. 10, the angle detector 30R is mounted to a supporter 33 via plane fasteners 31 and 32, and this supporter 33 is mounted to the player's right arm. More specifically, the positive plane fastener 31 is attached to the angle detector 30R, while the negative plane fastener 32 is attached to the supporter 33. Therefore, the angle detector 30R can be freely mounted to and removed from the supporter 33. As shown in Fig. 11, the angle detector 30R is constituted by a case 35 and two mercury switches Ra and Rb. These mercury switches Ra and Rb is arranged such that angle of 45 degrees is formed between a reference line SL and each of these mercury switches. As shown in Fig. 12, in each mercury switch, mercury liquid 37 is enclosed in a glass tube 36 and one part of electrodes 38a and 38b are inserted into the inside of this glass tube 36. In the state as shown in Fig. 12, the electrodes 38a and 38b are not conducted. However, when the mercury switch is revolved in a direction C, the electrodes 38a and 38b are conducted by the mercury liquid 37. Of course, similar to the mercury switches Ra and Rb, the left angle detector 30L provides mercury switches La and Lb.

In Fig. 11, when the angle detector 30R is revolved around a reference point O in a direction A or B, each of the mercury switches Ra and Rb is independently turned on or off. More specifically, in the state where the reference line SL is in parallel with the ground (or earth) as shown in Fig. 11, the mercury switch Ra is turned on but the mercury switch Rb is turned off. Then, when the angle detector 30R is revolved around the reference point O in the direction A by more than 45 degrees, both of the mercury switches Ra and Rb are turned on. On the contrary, when the angle detector 30R is revolved in the direction B by more than 45 degrees, both of the mercury switches Ra and Rb are turned off. Such on/off signals of the mercury switches Ra and Rb are guided into the grip device 1R via a cable 39R and then further guided into the main unit 5 via the cable 3R.

In Fig. 8, first terminals of the mercury switches Ra and Rb are connected in common and then guided into the grip device 1R via the cable 39R wherein this common line is further connected to first terminals of the pressure sensors SR1 to SR7 in common and then guided into the main unit 5 via the cable 3R. Then, such common line is grounded in the main unit 5. On the other hand, the second terminals of the pressure sensors SR1 to SR7 are guided into the main unit 5 via the cable 3R and then pulled up by pull-up resistors r. In addition, each of these second terminals are connected to each of the key-on/touch detecting circuits 6R1 to 6R7. Further, second terminals of the mercury switches Ra and Rb are guided into the

grip device 1R via the cable 39R. Then, these second terminals are pulled up by the pull-up resistors r and then connected to the multiplexer 12 respectively.

Based on the channel select signal CS, the multiplexer 12 selects one group of the key-on signal KON, initial-touch data ITD and after-touch data ATD outputted from the key-on/touch detecting circuits or the multiplexer 12 selects one of the on/off signals (hereinafter, referred to as angle data) outputted from the mercury switches Ra, Rb, La and Lb. Therefore, the CPU 14 scans the output data of key-on/touch detecting circuits and angle data outputted from the mercury switches with high speed to thereby obtain the key-on signal KON, initial-touch data ITD, after-touch data ATD and angle data, which are then sequentially transmitted to the RAM 17. Based on such transmitted data, the CPU 14 generates the key code data KC, tone volume data VOL, tone color designating data TD and the key-on signal KON, all of which are called the musical tone control data MCD.

As shown in Fig. 13, the functions are assigned to each of the pressure sensors in the second embodiment. More specifically, the key-on and touch intensity is designated based on the outputs of pressure sensors SR1 to SR4; the tone volume, vibrato and wow are respectively designated based on the outputs of pressure sensors SR5 to SR7; first to fourth octaves are respectively designated based on the outputs of pressure sensors SL1 to SL4; the tone color is designated based on each of the outputs of pressure sensors SL5 to SL7; and musical scales Cⁿ, Dⁿ, ..., Bⁿ, Cⁿ⁺¹, Dⁿ⁺¹ are designated based on combination of on/off states of the mercury switches Ra, Rb, La and Lb. Such assignment of functions can be arbitrarily set by operating the push switches of the console panel 18.

In the second embodiment, the player mounts the angle detectors 30R and 30L at his right and left arms respectively by use of the supporter 33, and then the player holds the grip devices 1R and 1L by his right and left hands respectively. Thereafter, the push switch for commanding the start in the console panel 18 is operated so that the performance will be started.

For example, in the state where the player stretches his both arms horizontally (so that the mercury switches Ra and La are turned on), the musical scale "G" is designated; the left thumb depresses the pressure sensor SL1 so that the "first octave" is designated; and the left little finger depresses the pressure sensor SL7 so that the tone color of "saxophone" is designated. In such state, when the right thumb further depresses the pressure sensor SR1, the musical tone generating apparatus generates the musical tone having the

touch response corresponding to the depressing intensity of such pressure sensor SR1, the tone color of saxophone and musical scale G¹. Next, when the right index finger depresses the pressure sensor SR3, the musical tone generating apparatus generates the musical tone having the touch response corresponding to the depressing intensity thereof and the tone pitch which is higher than the musical scale G¹ by half-tone. On the other hand, when the right index finger depresses the pressure sensor SL4, the musical tone generating apparatus generates the musical tone having the touch response corresponding to the depressing intensity thereof and the tone pitch which is lower than the musical scale G¹ by half-tone. In addition, when the right middle finger depresses the pressure sensor SR5, the tone volume is varied in response to its depressing intensity. When the right third finger depresses the pressure sensor SR6, the vibrato intensity is varied. Further, when the right little finger depresses the pressure sensor SR7, the wow effect is applied to the musical tone.

Above is the whole description of the preferred embodiments of the present invention. This invention may be practiced or embodied in still other ways without departing from the spirit or essential character thereof. Therefore, the preferred embodiments described herein are illustrative and not restrictive, the scope of the invention being indicated by the appended claims and all variations which come within the meaning of the claims are intended to be embraced therein.

Claims

1. A musical tone control apparatus comprising detecting means (1R, 1L) having the shape of a grip on which a plurality of pressure sensors are mounted, said detecting means outputting a detection signal corresponding to depressing pressure applied thereto by corresponding fingers of an operator holding the said detecting means in his hand, characterized in that it further comprises musical tone control means (5) for mounting on the operator's waist and connected to said detecting means for outputting musical tone control data (MCD) based on said detection signal outputted from said detecting means, and a remote musical tone generating apparatus controlled by said musical tone control data in order to generate a musical tone which is controlled in response to said depressing pressure of corresponding finger.
2. A musical tone control apparatus according to claim 1, wherein each of said pressure sensors having a piezoelectric element whose resis-

tance is varied in response to said depressing pressure of corresponding finger applied thereto.

3. A musical tone control apparatus according to claim 2 wherein said musical tone control means comprises:
 - (a) plural detecting circuits (6R1 to 6R7; 6L1 to 6L7) each outputting first data based on said depressing pressure of corresponding finger;
 - (b) selecting means (12) for selecting one of said plural detecting circuits; and
 - (c) means (14, 16, 17) for generating musical tone control data based on said first data of selected detecting circuit.
4. A musical tone control apparatus according to claim 3 wherein said first data include a key-on signal (KON), initial-touch data (ITD) representing a degree of key depression at the instant when the key is depressed and after-touch data (ATD) representing a degree of key depression strength when key is continuously depressed, said musical tone control data (MCD) including at least one of said key-on signal, key code data (KC) for designating a tone pitch, tone volume data (VOL) and tone color designating data (TD).
5. A musical tone control apparatus according to claim 3 wherein said detecting circuit comprises:
 - (a) converting means (7) for converting detected variation of said depressing pressure of corresponding finger into detection data, said detection data being outputted as after-touch data;
 - (b) comparator means (8) for comparing value of said detection data with a predetermined value, said comparator means outputting an output signal when the value of said detection data becomes larger than said predetermined value; and
 - (c) means (9 to 11) for generating a key-on signal based on the output signal of said comparator means, said means also outputting said detection data corresponding to timing of said key-on signal as initial-touch data.
6. A musical tone control apparatus according to claim 2 wherein one of predetermined musical effects is designated by depressing at least one of said pressure sensors.
7. A musical tone control apparatus according to any of claims 1 or 2, wherein said detecting



touch response corresponding to the depressing intensity of such pressure sensor SR1, the tone color of saxophone and musical scale G¹. Next, when the right index finger depresses the pressure sensor SR3, the musical tone generating apparatus generates the musical tone having the touch response corresponding to the depressing intensity thereof and the tone pitch which is higher than the musical scale G¹ by half-tone. On the other hand, when the right index finger depresses the pressure sensor SL4, the musical tone generating apparatus generates the musical tone having the touch response corresponding to the depressing intensity thereof and the tone pitch which is lower than the musical scale G¹ by half-tone. In addition, when the right middle finger depresses the pressure sensor SR5, the tone volume is varied in response to its depressing intensity. When the right third finger depresses the pressure sensor SR6, the vibrato intensity is varied. Further, when the right little finger depresses the pressure sensor SR7, the wow effect is applied to the musical tone.

Above is the whole description of the preferred embodiments of the present invention. This invention may be practiced or embodied in still other ways without departing from the spirit or essential character thereof. Therefore, the preferred embodiments described herein are illustrative and not restrictive, the scope of the invention being indicated by the appended claims and all variations which come within the meaning of the claims are intended to be embraced therein.

Claims

1. A musical tone control apparatus comprising detecting means (1R, 1L) having the shape of a grip on which a plurality of pressure sensors are mounted, said detecting means outputting a detection signal corresponding to depressing pressure applied thereto by corresponding fingers of an operator holding the said detecting means in his hand.
characterized in that it further comprises musical tone control means (5) for mounting on the operator's waist and connected to said detecting means for outputting musical tone control data (MCD) based on said detection signal outputted from said detecting means, and a remote musical tone generating apparatus controlled by said musical tone control data in order to generate a musical tone which is controlled in response to said depressing pressure of corresponding finger.
2. A musical tone control apparatus according to claim 1, wherein each of said pressure sensors having a piezoelectric element whose resis-

tance is varied in response to said depressing pressure of corresponding finger applied thereto.

3. A musical tone control apparatus according to claim 2 wherein said musical tone control means comprises:
 - (a) plural detecting circuits (6R1 to 6R7; 6L1 to 6L7) each outputting first data based on said depressing pressure of corresponding finger;
 - (b) selecting means (12) for selecting one of said plural detecting circuits; and
 - (c) means (14, 16, 17) for generating musical tone control data based on said first data of selected detecting circuit.
4. A musical tone control apparatus according to claim 3 wherein said first data include a key-on signal (KON), initial-touch data (ITD) representing a degree of key depression at the instant when the key is depressed and after-touch data (ATD) representing a degree of key depression strength when key is continuously depressed, said musical tone control data (MCD) including at least one of said key-on signal, key code data (KC) for designating a tone pitch, tone volume data (VOL) and tone color designating data (TD).
5. A musical tone control apparatus according to claim 3 wherein said detecting circuit comprises:
 - (a) converting means (7) for converting detected variation of said depressing pressure of corresponding finger into detection data, said detection data being outputted as after-touch data;
 - (b) comparator means (8) for comparing value of said detection data with a predetermined value, said comparator means outputting an output signal when the value of said detection data becomes larger than said predetermined value; and
 - (c) means (9 to 11) for generating a key-on signal based on the output signal of said comparator means, said means also outputting said detection data corresponding to timing of said key-on signal as initial-touch data.
6. A musical tone control apparatus according to claim 2 wherein one of predetermined musical effects is designated by depressing at least one of said pressure sensors.
7. A musical tone control apparatus according to any of claims 1 or 2, wherein said detecting



means comprises:

(a-1) timing generating means (7 or 10) for generating a timing signal when a predetermined time is passed after value of said detection signal exceeds a reference value; and

(a-2) storing means (11) for inputting and storing said detecting signal value at every time when said timing signal is supplied hereto, said storing means outputting its stored data as a first signal corresponding to an initial touch of each key, said detecting signal being outputted as a second signal corresponding to an after-touch of each key; and wherein said musical tone control means comprises:

(b-1) plural detecting circuits (6R1 to 6R7; 6L1 to 6L7) each outputting first data based on said depressing pressure of corresponding finger.

8. A musical tone control apparatus according to any of the preceding claims, comprising angle detecting means (30R, 30L) for detecting a swing angle of player's arm to thereby generate an angle signal corresponding to detected swing angle for controlling the remote musical tone generating apparatus.

9. A musical tone control apparatus according to claim 8 wherein said angle detecting means is attached to a supporter (33) by use of plane fasteners (31, 32), said supporter being mounted to the player's arm, whereby said angle detecting means is easily mounted to and removed from the player's arm.

10. A musical tone control apparatus according to claim 8 wherein said angle detecting means includes a mercury switch (Ra, Rb; La, Lb) which is turned on or off in response to inclination applied thereto when player mounts said angle detecting means at his arm and then swings his arm up or down.

11. A musical tone control apparatus as claimed in claim 7 comprising:

(b-2) selecting means (12) for selecting one of said plural detecting circuits; and

(b-3) means (14, 16, 17) for generating musical tone control data based on said first data of selected detecting circuit.

Patentansprüche

1. Eine musikalische Tonsteuervorrichtung, die Detektiermittel (1R, 1L) mit der Form eines Griffes aufweist, an dem eine Vielzahl von

Drucksensoren angebracht sind, wobei die Drucksensoren ein Detektiersignal abgeben, entsprechend des Herunterdrückdruckes, der daran angelegt wird durch entsprechende Finger eines Bedieners, der die Detektiermittel in seiner Hand hält,

dadurch gekennzeichnet, daß sie weiterhin folgendes aufweist:

musikalische Tonsteuermittel (5) zur Anbringung an der Hüfte des Bedieners und verbunden mit den Detektiermitteln zum Ausgeben von musikalischen Tonsteuerdaten (MCD), basierend auf dem Detektiersignal, das von den Detektiermitteln abgegeben wurde, und eine entfernt gelegene musikalische Tonerzeugungsvorrichtung, die gesteuert wird durch die musikalischen Tonsteuerdaten, um einen musikalischen Ton zu erzeugen, der gesteuert wird ansprechend auf den Herunterdrückdruck entsprechender Finger.

2. Musikalische Tonsteuervorrichtung nach Anspruch 1, wobei jeder der Drucksensoren ein piezoelektrisches Element besitzt, dessen Widerstand variiert wird, ansprechend auf den Herunterdrückdruck eines entsprechenden Fingers, der daran angelegt wird.

3. Musikalische Tonsteuervorrichtung nach Anspruch 2, wobei die musikalischen Tonsteuermittel folgendes aufweisen:

(a) eine Vielzahl von Detektierschaltungen (6R1 bis 6R7; 6L1 bis 6L7), die jeweils erste Daten ausgeben, basierend auf den Herunterdrückdruck entsprechender Finger;

(b) Auswahlmittel (12) zum Auswählen einer der Vielzahl von Detektierschaltungen; und

(c) Mittel (14, 16, 17) zum Erzeugen musikalischer Tonsteuerdaten, basierend auf den ersten Daten einer ausgewählten Detektierschaltung.

4. Musikalische Tonsteuervorrichtung nach Anspruch 3, wobei die ersten Daten folgendes aufweisen: ein Tastaten-Ein-Signal (KON), anfängliche Berührungsdaten (ITD), die einen Grad des Tastatenherunterdrückens darstellt zu dem Zeitpunkt, wenn die Tastate heruntergedrückt wird, und Nachberührungsdaten (ATD), die einen Grad der Tastatenherunterdrückstärke darstellen, wenn die Tastate kontinuierlich heruntergedrückt wird, wobei die musikalischen Tonsteuerdaten (MCD) mindestens eines der folgenden aufweist: das Tastaten-Ein-Signal, die Tastatencode- oder Schlüssel-daten (KC) zum Designieren einer Tonhöhe, Tonvolumendaten (VOL) oder Klangfarbendesignierdaten (TD).



5. Musikalische Tonsteuervorrichtung nach Anspruch 3, wobei die Detektierschaltung folgendes aufweist:

(a) Konvertier- oder Wandlerrmittel (7) zum Wandeln einer detektierten Variierung des Herunterdrückdruckes eines entsprechenden Fingers in Detektierdaten, wobei die Detektierdaten als Nachberührungsdaten ausgegeben werden;

(b) Vergleichermittel (8) zum Vergleichen des Werts der Detektierdaten mit einem vorbestimmten Wert, wobei die Vergleichsmittel ein Ausgangssignal abgeben, wenn der Wert der Detektierdaten größer wird als der vorbestimmte Wert; und

(c) Mittel (9 bis 11) zum Erzeugen eines Tastaten-Ein-Signals, basierend auf dem Ausgangssignal der Vergleichermittel, wobei die Mittel auch die Detektierdaten entsprechend dem Timing des Tastaten-Ein-Signals als anfängliche Berührungsdaten ausgeben.

6. Musikalische Tonsteuervorrichtung nach Anspruch 2, wobei einer der vorbestimmten musikalischen Effekte designiert wird durch Herunterdrücken von mindestens einem der Drucksensoren.

7. Musikalische Tonsteuervorrichtung nach einem der Ansprüche 1 oder 2, wobei die Detektiermittel folgendes aufweisen:

(a-1) Timingerzeugungsmittel (7 oder 10) zum Erzeugen eines Timingsignals, wenn eine vorbestimmte Zeit abgelaufen ist, nachdem der Wert des Detektiersignals einen Bezugswert übersteigt; und

(a-2) Speichermittel (11) zur Eingabe und zum Speichern des Detektiersignalwertes zu jeder Zeit, wenn das Timingsignal daran geliefert wird, wobei die Speichermittel ihre gespeicherten Daten als ein erstes Signal entsprechend einer anfänglichen Berührung jeder Taste abgeben, wobei das Detektiersignal als ein zweites Signal entsprechend einer Nachberührung jeder Taste abgegeben wird; und wobei die musikalischen Tonsteuermittel folgendes aufweisen:

(b-1) eine Vielzahl von Detektierschaltungen (6R1, bis 6A7; 6L1 bis 6L7), die jeweils erste Daten abgeben, basierend auf dem Herunterdrückdruck eines entsprechenden Fingers.

8. Musikalische Tonsteuervorrichtung nach einem der vorhergehenden Ansprüche, die Winkeldetektiermittel (30R, 30L) aufweist, zum Detektieren eines Schwing- oder Schwenkwinkels des Arms eines Spielers, um dadurch ein Winkelsi-

gnal entsprechend dem detektierten Schwenkwinkel zum Steuern der entfernt gelegenen musikalischen Tonerzeugungsvorrichtung zu erzeugen.

9. Musikalische Tonsteuervorrichtung nach Anspruch 8, wobei die Winkeldetektiermittel an einem Träger (33) durch die Verwendung flächiger Befestiger (31, 32) angebracht sind, wobei der Träger an dem Arm des Spielers angebracht ist, wodurch die Winkeldetektiermittel leicht an den Arm des Spielers angebracht werden können und von diesem abgenommen werden können.

10. Musikalische Tonsteuervorrichtung nach Anspruch 8, wobei die Winkeldetektiermittel einen Quecksilberschalter (Ra, Rb; La, Lb) aufweisen, der ein- oder ausgeschaltet wird, ansprechend auf die Neigung, die daran angelegt wird, wenn der Spieler die Winkeldetektiermittel an seinem Arm anbringt und dann den Arm nach oben oder nach unten schwenkt.

11. Musikalische Tonsteuervorrichtung nach Anspruch 7, die folgendes aufweist:

(b-2) Auswahlmittel (12) zum Auswählen einer aus einer Vielzahl von Detektierschaltungen; und

(b-3) Mittel (14, 16, 17) zum Erzeugen musikalischer Tonsteuerdaten, basierend auf den ersten Daten einer ausgewählten Detektierschaltung.

Revendications

1. Appareil de commande de sons musicaux comportant des moyens détecteurs (1R, 1L) en forme de poignée sur lesquels sont fixés une pluralité de capteurs de pression, lesdits moyens détecteurs émettant un signal de détection correspondant à la pression exercée sur eux par les doigts correspondants d'un opérateur tenant dans les mains lesdits moyens détecteurs,

caractérisé en ce qu'il comporte en outre un moyen de commande de sons musicaux (5) destiné à être fixé à la taille de l'opérateur et relié auxdits moyens détecteurs afin d'émettre des données de commande de sons musicaux (MCD) fondées sur ledit signal de détection émis à partir desdits moyens détecteurs, et un appareil générateur de sons musicaux à distance commandé par lesdites données de commande de sons musicaux afin d'émettre un son musical qui soit commandé en réponse à ladite pression exercée par le doigt correspondant.



2. Appareil de commande de sons musicaux conforme à la revendication 1, dans lequel chacun desdits capteurs de pression est muni d'un élément piézoélectrique dont la résistance varie en réponse à ladite pression exercée par le doigt correspondant lui étant appliquée. 5

3. Appareil de commande de sons musicaux conforme à la revendication 2, dans lequel ledit moyen de commande de sons musicaux comprend: 10
 - (a) une pluralité de circuits détecteurs (6R1 à 6R7; 6L1 à 6L7) émettant chacun des premières données fondées sur ladite pression exercée par le doigt correspondant; 15
 - (b) un moyen sélecteur (12) destiné à sélectionner un desdits circuits de la pluralité de circuits détecteurs; et
 - (c) des moyens (14, 16, 17) destinés à générer des données de commande de sons musicaux fondées sur lesdites premières données du circuit détecteur sélectionné. 20

4. Appareil de commande de sons musicaux conforme à la revendication 3, dans lequel lesdites premières données incluent un signal de frappe de touche (KON) des données de frappe initiale (LTD) représentant un degré de pression sur la touche à l'instant où la touche est enfoncée, et des données de "suite de frappe" (ATD) représentant un degré de force de pression sur la touche quand la touche est enfoncée en continu, lesdites données de commande de sons musicaux (MCD) comportant au moins un desdits signaux de frappe de touche, les données de code de touche (KC), afin d'indiquer une hauteur de son, des données de volume de son (VOL) et des données indiquant le timbre acoustique (TD). 25 30 35 40

5. Appareil de commande de sons musicaux conforme à la revendication 3, dans lequel ledit circuit détecteur comprend: 45
 - (a) un moyen convertisseur (7) destiné à convertir la variation détectée de ladite pression exercée par le doigt correspondant en données de détection, lesdites données de détection étant émises comme données de "suite de frappe"; 50
 - (b) un moyen comparateur (8) destiné à comparer la valeur desdites données de détection avec une valeur prédéterminée, ledit moyen comparateur émettant un signal de sortie quand la valeur desdites données de détection devient supérieure à ladite valeur prédéterminée; et 55

- (c) des moyens (9 à 11) destinés à émettre un signal de frappe de touche fondé sur le signal de sortie dudit moyen comparateur, lesdits moyens émettant également lesdites données de détection correspondant au cadencement dudit signal de frappe de touche comme données de frappe initiale.

6. Appareil de commande de sons musicaux conforme à la revendication 2, dans lequel on indique l'un des effets musicaux prédéterminés en appuyant sur au moins un desdits capteurs de pression.

7. Appareil de commande de sons musicaux conforme à l'une quelconque des revendications 1 ou 2, dans lequel ledit moyen détecteur comporte:
 - (a-1) un moyen générateur de signaux d'horloge (7 ou 10) destiné à générer un signal de synchronisation quand un temps prédéterminé s'est écoulé après que la valeur dudit signal de détection excède une valeur de référence; et
 - (a-2) un moyen de stockage (11) destiné à entrer et à stocker la valeur dudit signal de détection à chaque fois que ledit signal de synchronisation lui est envoyé, ledit moyen de stockage émettant ses données stockées comme premier signal correspondant à une frappe initiale de chaque touche, ledit signal de détection étant émis comme deuxième signal correspondant à une "suite de frappe" de chaque touche; et dans lequel ledit moyen de commande de sons musicaux comprend:
 - (b-1) une pluralité de circuits détecteurs (6R1 à 6R7; 6L1 à 6L7) émettant chacun des premières données fondées sur ladite pression exercée par le doigt correspondant.

8. Appareil de commande de sons musicaux conforme à l'une quelconque des revendications précédentes, comprenant des moyens détecteurs d'angle (3OR, 3OL) destinés à détecter l'angle d'orientation du bras du joueur pour, par là-même, générer un signal d'angle correspondant à l'angle d'orientation détecté afin de commander l'appareil générateur de sons musicaux à distance.

9. Appareil de commande de sons musicaux conforme à la revendication 8, dans lequel ledit moyen détecteur d'angle est fixé à un brassard (33) au moyen d'attaches plates (31, 32), ledit brassard étant fixé au bras du joueur, ce par quoi il est facile de fixer ledit moyen



détecteur d'angle d'orientation sur le bras du joueur, ou de l'en retirer.

10. Appareil de commande de sons musicaux conforme à la revendication 8, dans lequel ledit moyen détecteur d'angle inclut un commutateur à mercure (Ra, Rb; La, Lb) qui est mis en fonction ou hors fonction en réponse à l'inclinaison qui lui est appliquée quand le joueur fixe ledit moyen détecteur d'angle à son bras, puis déplace son bras vers le haut ou vers le bas.

11. Appareil de commande de sons musicaux conforme à la revendication 7, comprenant:
- (b-2) un moyen de sélection (12) destiné à sélectionner un circuit de ladite pluralité de circuits détecteurs; et
 - (b-3) des moyens (14, 16, 17) destinés à générer des données de commande de sons musicaux fondées sur lesdites premières données du circuit détecteur sélectionné.

25

30

35

40

45

50

55

11