

(12) 按照专利合作条约所公布的国际申请

(19) 世界知识产权组织
国际局



(10) 国际公布号
WO 2025/044840 A1

(43) 国际公布日
2025 年 3 月 6 日 (06.03.2025)

(51) 国际专利分类号:
D06F 33/69 (2020.01)

(72) 发明人:薛磊(XUE, Lei); 中国江苏省南京市雨花台区凤汇大道21号3幢808室, Jiangsu 210039 (CN)。

(21) 国际申请号: PCT/CN2024/113398

(74) 代理人:北京中强智尚知识产权代理有限公司 (BEIJING STRONG WISDOM INTELLECTUAL PROPERTY AGENCY LTD.); 中国北京市朝阳区东三环中路7号财富中心写字楼A座509室, Beijing 100020 (CN)。

(22) 国际申请日: 2024 年 8 月 20 日 (20.08.2024)

(25) 申请语言: 中文

(26) 公布语言: 中文

(30) 优先权:
202311129993.8 2023年8月31日 (31.08.2023) CN

(81) 指定国(除另有指明, 要求每一种可提供的国家保护): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CV, CZ, DE, DJ, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IQ, IR, IS, IT, JM, JO, JP, KE, KG, KH, KN, KP, KR, KW, KZ, LA, LC, LK, LR, LS, LU, LY, MA, MD, MG, MK, MN, MU, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SA, SC, SD,

(71) 申请人: 南京石头创新科技有限公司 (NANJING ROBOROCK INNOVATION TECHNOLOGY CO., LTD.) [CN/CN]; 中国江苏省南京市雨花台区凤汇大道21号3幢808室, Jiangsu 210039 (CN)。

(54) **Title:** WATER LOADING CONTROL METHOD AND APPARATUS, CLOTHES TREATMENT DEVICE, AND STORAGE MEDIUM

(54) 发明名称: 供水控制方法及装置、衣物处理设备和存储介质

基于衣物处理指令, 执行第一供水处理和第二供水处理, 所述第一供水处理位于所述第二供水处理之前和/或之后, 其中, 所述第一供水处理包括通过第一供水管路向衣物处理设备的衣物容纳装置供水, 所述第一供水管路经所述衣物处理设备的出风通道与所述衣物容纳装置连通, 所述出风通道内设置有用于在烘干处理中过滤气流的过滤网; 所述第二供水处理包括通过第二供水管路向所述衣物容纳装置供水, 所述第二供水管路经所述衣物处理设备的衣物处理剂盒与所述衣物容纳装置连通

图 7

702 Execute a first water loading process and a second water loading process on the basis of a clothes treatment instruction, wherein the first water loading process is executed before and/or after the second water loading process, the first water loading process comprises loading water into a clothes accommodating apparatus of a clothes treatment device by means of a first water supply pipeline, the first water supply pipeline is in communication with the clothes accommodating apparatus by means of an air outlet channel of the clothes treatment device, a filter screen for filtering air flow during drying is arranged in the air outlet channel, the second water loading process comprises loading water into the clothes accommodating apparatus by means of a second water supply pipeline, and the second water supply pipeline is in communication with the clothes accommodating apparatus by means of a detergent box of the clothes treatment device

(57) **Abstract:** A water loading control method and apparatus, a clothes treatment device (100), and a storage medium. The method comprises: executing a first water loading process and a second water loading process on the basis of a clothes treatment instruction, wherein the first water loading process is executed before and/or after the second water loading process, the first water loading process comprises loading water into a clothes accommodating apparatus (101) of the clothes treatment device (100) by means of a first water supply pipeline (103), the first water supply pipeline (103) is in communication with the clothes accommodating apparatus (101) by means of an air outlet channel (105) of the clothes treatment device (100), a filter screen (106) for filtering air flow during drying is arranged in the air outlet channel (105), the second water loading process comprises loading water into the clothes accommodating apparatus (101) by means of a second water supply pipeline (107), and the second water supply pipeline (107) is in communication with the clothes accommodating apparatus (101) by means of a detergent box (102) of the clothes treatment device (100). Cleaning

[见续页]

WO 2025/044840 A1

SE, SG, SK, SL, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ,
UA, UG, US, UZ, VC, VN, WS, ZA, ZM, ZW。

(84) 指定国(除另有指明, 要求每一种可提供的地区
保护): ARIPO (BW, CV, GH, GM, KE, LR, LS, MW, MZ,
NA, RW, SC, SD, SL, ST, SZ, TZ, UG, ZM, ZW), 欧亚
(AM, AZ, BY, KG, KZ, RU, TJ, TM), 欧洲 (AL, AT, BE,
BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR,
HU, IE, IS, IT, LT, LU, LV, MC, ME, MK, MT, NL, NO,
PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF,
CG, CI, CM, GA, GN, GQ, GW, KM, ML, MR, NE, SN,
TD, TG)。

本国际公布:

— 包括国际检索报告(条约第21条(3))。

the filter screen (106) before and/or after clothes treatment indicated by the clothes treatment instruction is executed can increase the ventilation area of the filter screen (106) to improve the ventilation performance of the filter screen (106) during the execution of the clothes treatment instruction, thereby improving the drying effect.

(57) 摘要: 一种供水控制方法及装置、衣物处理设备(100)和存储介质, 该方法包括: 基于衣物处理指令, 执行第一供水处理和第二供水处理, 第一供水处理位于第二供水处理之前和/或之后, 其中, 第一供水处理包括通过第一供水管路(103)向衣物处理设备(100)的衣物容纳装置(101)供水, 第一供水管路(103)经衣物处理设备(100)的出风通道(105)与衣物容纳装置(101)连通, 出风通道(105)内设置有用于在烘干处理中过滤气流的过滤网(106); 第二供水处理包括通过第二供水管路(107)向衣物容纳装置(101)供水, 第二供水管路(107)经衣物处理设备(100)的衣物处理剂盒(102)与衣物容纳装置(101)连通。在执行衣物处理指令所指示的衣物处理之前对过滤网(106)进行清洗, 和/或在执行衣物处理指令所指示的衣物处理之后对过滤网(106)进行清洗, 均可增大过滤网(106)的通风面积, 提升执行衣物处理指令过程中过滤网(106)的通风性能, 有利于提升烘干效果。