

GSM MOBILE WATCH PHONE

TECHNICAL FIELD

The present invention relates to a wrist watch kind mobile phone and in particular a wrist watch phone design for use in GSM telephone network that may operate over
5 several frequency bands.

BACKGROUND ART

Wrist watches are commonly known to provide the basic function of time keeping. Modern wrist watches have a number of extra functions that make them more than just a time piece.

10 It has long been desired to make a wrist watch that provides a two-way communication function, but it is difficult to build one in practice.

One of the challenges involved in producing such a wrist watch is the difficulty of reducing the size of the electronic components to fit them within a housing that is wearable by a person on the wrist. Typically the dimension of a wearable wrist watch is
15 50 x 60 x 15 mm which is much smaller than that of a typical mobile phone which is around 100 x 60 x 15 mm, or larger.

It is known to provide a wrist mounted mobile telephone watch, such as that shown in US 6567523 which describes a wrist mounted telephone device having a watch unit and telephone unit. However, this device has the telephone unit separate
20 from the time unit, where each of the units has its own housing. As a result, there are many different parts in the watch and it is not convenient to use, or to wear.

It would also be desirable to provide a wrist watch phone that ameliorates or overcomes one or more of the disadvantages of such devices or that may provide a useful alternative to these devices.

DISCLOSURE OF THE INVENTION

According to the invention there is provided a wrist watch phone wearable by a person comprising:

5 a communication module adapted to operate under Global System of Mobile (GSM) telephone networks, to operate with at least one GSM frequency bands, and to send audio data across said GSM telephone networks;

an antenna connecting to said communication module, wherein said antenna is adapted to transmit signals to and receive signals from said GSM telephone networks;

10 a display adapted to at least display time, and to provide a graphic interface for showing a status of said communication module;

a power supply connecting to said communication module, wherein said power supply is adapted to provide power to said wrist watch mobile phone; and

a housing means adapted to enclose said display, said antenna, said communication module and said power supply

15 In a preferred embodiment, said wrist watch phone comprises a retaining means adapted to secure said retaining means around a wrist.

In a preferred embodiment, said communication module adapted to operate with at least three GSM frequency bands.

Preferably, said communication module adapted to operate in quad bands mode.

20 In a preferred embodiment, said GSM frequency bands include any one or more of 800Mhz, 850MHz, 900MHz, 1800MHz, 1900MHz, 2100Mhz.

In a preferred embodiment, said communication module adapted to operate under Voice Over IP (VOIP), Wi-Fi, InfraRed, Worldwide interoperability Microwave Access (WiMAX).

25 In a preferred embodiment, said antenna is an internal antenna enclosed entirely inside said housing means.

In a preferred embodiment, said antenna is enclosed within or retained upon said retaining means.

In a preferred embodiment, said power supply includes a rechargeable battery adapted to provide power to said communication module and said display module.

In a preferred embodiment, said communication module has a charger interface for recharging said rechargeable battery.

5 Preferably, said display is any one of Organic Light-Emitting Diode (OLED) display, Thin Film Transistor Liquid Crystal Display (TFTLCD) or Liquid Crystal Display (LCD).

In a preferred embodiment, said display is made of any one of plastic or glass.

In a preferred embodiment, said display is a touch screen.

10 In a preferred embodiment, said display is adapted to display 256 colours.

Preferably, said communication module is adapted to communicate via IP Packets Exchange network.

In a preferred embodiment, said wrist watch is adapted to operate with a Subscriber Identity Module (SIM) card.

15 In a preferred embodiment, said wrist watch includes a Global Positioning System (GPS) module connecting to said communication module, wherein said GPS module determines at least one coordinate data of said wrist watch phone and displays said coordinate data on said display.

20 Preferably, said communication module has a baseband module adapted to process, send and receive digital data.

In a preferred embodiment, said digital data include emails, telephone calls, text messages, multimedia messages, files, videos, sounds, voices, music, pictures and games.

25 In a preferred embodiment, said wrist watch is adapted to send an email when said GPS has detected that said wrist watch phone is outside a predetermined geographical area.

In a preferred embodiment, said wrist watch has a Bluetooth communication module to connect to a Bluetooth compatible device.

Preferably, said retaining means includes a security encryption device for securely locking said wrist watch around a wrist.

5 In a preferred embodiment, said security encryption device is adapted to receive wireless signals for locking and unlocking said security encryption device.

In a preferred embodiment, said communication module includes a customized Printed Circuit Board (PCB).

In a preferred embodiment, said PCB includes
10 a Radio Frequency (RF) module adapted to send and receive digital signals through GSM telephone networks using one of said three multiply frequency bands , and

a baseband module adapted to convert data from at least one input to said digital signals and to convert said digital signals from said RF module to data for output
15 devices.

In a preferred embodiment, said baseband module is adapted to send and receive data from at least one of the devices including: a USB device, an I/O device, a keypad, a Bluetooth device, a Real Time Clock (RTC), a Time Stamp Counter (TSC), a Microphone, a headset, a system clock, a display and a camera.

20 In a preferred embodiment, said baseband module is adapted to collect status information from said rechargeable battery module and display said status information on said display.

In a preferred embodiment, there is provided a software module for use in the wrist watch phone of any one of the preceding claims, said software comprising:

25 a protocol stack adapted to provide application programming interface (API) for said communication module; and

a man to machine interface adapted to accept input from a user and pass said input to said communication module using said API, and to display output from said communication module using said API.

In a preferred embodiment, said API in a format compatible with at least one high
5 level computer languages.

In a preferred embodiment, said API in a format compatible with wireless application protocol.

In a preferred embodiment, said protocol stack has a battery control module for minimizing battery usage by optimizing the use of graphics

10 In a preferred embodiment, said protocol stack is adapted to handle IP Exchange packets.

In this specification, unless the context clearly indicates otherwise, the term “comprising” has the non-exclusive meaning of the word, in the sense of “including at least” rather than the exclusive meaning in the sense of “consisting only of”. The same
15 applies with corresponding grammatical changes to other forms of the word such as “comprise”, “comprises” and so on.

BRIEF DESCRIPTION OF DRAWINGS

The invention is now discussed with reference to drawings, where:

Figure 1 is a front view of GSM watch phone according to one embodiment of the
20 present invention;

Figure 2 is a view showing the internal components of the watch phone of Figure 1;

Figure 3 is a back view of Figure 2;

Figure 4 is an expanded view of the circuit board shown in Figure 3;

Figure 5 is a view of the reverse side of the circuit board of 4;

25 Figure 6 is a block diagram of the RF module of watch phone of Figure 1;

Figure 7 is a block diagram of the baseband module of watch phone of Figure 1;

Figure 9 is a schematic diagram of the software architecture of watch phone of figure 1;

Figure 10 is a schematic diagram of the circuit board of figure 4; and
Figure 11 is a schematic diagram of the circuit board of figure 5;
Figure 12 is the first layer of circuit board of Figure 4;
Figure 13 is the second layer of circuit board of Figure 4;
5 Figure 14 is the third layer of circuit board of Figure 4;
Figure 15 is the forth layer of circuit board of Figure 4;
Figure 16 is the fifth layer of circuit board of Figure 4;
Figure 17 is the sixth layer of circuit board of Figure 4;
Figure 18 is the seventh layer of circuit board of Figure 4;
10 Figure 19 is the eighth layer of circuit board of Figure 4;
Figure 20 is the ninth layer of circuit board of Figure 4;
Figure 21 is the tenth layer of circuit board of Figure 4.

BEST MODES FOR CARRYING OUT THE INVENTION

Referring to Figures 1 to 21, the invention provides a wrist watch phone (9)
15 wearable by a person. Preferably, the wrist watch has a size of about 50 x 60 x 15 mm
which is smaller than that of a typical mobile phone.

Referring to Figures 1 to 3 the wrist watch phone has a housing (10) that includes
a display (16) that is connected to a communication module (18). The front shell (12)
of the housing (10) and the back shell (14) of the housing enclose the display (16) and
20 the communication module (18). The wrist watch phone has straps (11) or some other
suitable form of watch band for fastening around a wrist of a person. Preferably, the
watch phone includes some sort of watch band, but it may be provided or sold without
one, so that the users can add their own watch band later.

The communication module (18) is able to operate under the Global System for
25 Mobile communications (GSM) telephone networks. The GSM telephone network is
commonly used for mobile telephone communication and normally operates over one or
more of four frequency ranges, such as the frequency bands of 850MHz, 900MHz,

1800MHz and 1900MHz, depending on the system adopted by a particular country. Different countries may have different operation bands.

Traditionally, mobile phones only support one frequency band for communication. However, some countries use two frequency bands to provide a better coverage of the mobile networks, and therefore some mobile phones are designed to support two bands. This type of mobile phones is known as a “dual band” mobile phone. Mobile phones that support three bands are known as “tri band” mobile phones and mobile phones that support four bands are known as “quad band” mobile phones.

The communication module (18) has a customized Printed Circuit Board (PCB) (19) to accommodate all the electronics for supporting four or more different GSM frequency bands communication as well as a number of 3G frequency bands including 806 to 890 MHz, 1710 to 1885 MHz and 1901 to 2200MHz. Below is a table showing an example of the operational GSM frequency bands of a watch phone.

Table 1 – Operational GSM frequency bands of GSM Watch Phone

System	Band	Uplink	Downlink	Channel Number
GSM 400	450	450.4 - 457.6	460.4 - 467.6	259 - 293
GSM 400	480	478.8 - 486.0	488.8 - 496.0	306 - 340
GSM 850	850	824.0 - 849.0	869.0 - 894.0	128 - 251
GSM 900 (P-GSM)	900	890.0 - 915.0	935.0 - 960.0	1 - 124
GSM 900 (E-GSM)	900	880.0 - 915.0	925.0 - 960.0	975 - 1023, (0, 1-124)
GSM-R (R-GSM)	900	876.0 - 915.0	921.0 - 960.0	955 - 973, (0, 1-124, 975 - 1023)
DCS 1800	1800	1710.0 - 1785.0	1805.0 - 1880.0	512 - 885
PCS 1900	1900	1850.0 - 1910.0	1930.0 - 1990.0	512 - 810

In addition to those GSM frequency bands, the PCB of the watch phone may also accommodate all the electronics for supporting a number of different communication

systems including Voice Over IP (VOIP), Wi-Fi, InfraRed, Worldwide interoperability Microwave Access (WiMAX) for sending audio data. The PCB contains multiply layers of circuits and in a preferred embodiment, may have ten different layers of circuit etched on the PCB. As a result, it is possible to share the components between the
5 different standards for supporting all different bands.

Figures 12 to 21 show the circuit layouts of all the layers of the circuit board. The electronic components of the watch phone utilises all these ten layers of circuit board such that the communication module (18) may work across all the different frequency bands.

10 Referring to figures 9 and 10, which are schematic diagrams of the communication module (18), the PCB includes a Radio Frequency (RF) module and a baseband module (30). As shown in figure 7, the RF module consists of a transmitter / receiver (T/R) assembly (22), RF Surface acoustic wave (SAW) filters (23), a transceiver (24), an amplifier (25).

15 In receiving mode, the T/R assembly has an antenna and a T/R switch for receiving signals from the GSM network. The signals are then passed to the SAW filter (23), and the transceiver (24) for down-converting. The transceiver converts the signals to data for further processing in the baseband module (30).

In transmitting mode, the data is passed to the transceiver (24) to generate the
20 necessary R/F signals. The R/F signals are then passed to the amplifier (25) which magnifies the signals to the power level within the burst ramping mask. The magnified signals are then transmitted to the GSM network through the antenna.

The baseband module (30) controls all the functions of the watch except for the transmitting and receiving signals, which is controlled by the RF module. It accepts the
25 data down-converted from the transceiver and further processes it and distributes it to the designated devices of the watch. It is also responsible for receiving input from those devices, processing them and pushing the data to the RF module for sending.

In this embodiment, the baseband module, as shown in figure 8, is designed to send data to and receive data from: a USB device (34), an I/O device (35), a keypad

(36), a Bluetooth device (37), a Real Time Clock (RTC) (38), a Time Stamp Counter (TSC) (39), a microphone (53), a headset receiver (54), a headset microphone (55), a system clock (56), a display interface (57) and a camera (58). Other devices known to be used in typical digital watches may also be incorporated in this watch phone. These
5 devices are included to enhance the functions of the watch phone.

A Subscriber Identity Mobile (SIM) Card, if there is one needed, may be inserted into the watch through the SIM card interface (72). The baseband module also connects to a controller (31) for interfacing with the SIM card (32). The SIM card stores the information for connecting to the GSM or 3G telephone networks. It is also able to
10 store other information of the user such as telephone numbers or text messages depending on the size of the memory of the SIM card.

The baseband module also controls the memory for storing data in the watch. The memory in this preferred embodiment may be a NorFlash memory (33). The memory is used for storing firmware and drivers for the watch.

15 The baseband module is also responsible for collecting status information from a power supply system (40). The power supply system may have a rechargeable battery (42), which may connect to a charger (43), a LED (44) for indicating the power status and preferably a vibrator (41). The power supply system is controlled by a controller (41). It determines and indicates the power on/off status, the charging status and the
20 power level. It also controls the vibrating function of the watch. In the embodiment the controller (31) for the SIM card and the controller (41) for the power supply system are integrated in one single chip.

Referring to figure 10, the watch may also have a number of interfaces for connecting external devices. Those interfaces include USB interface (72), a power
25 supply socket (76), a microphone socket (75) and a headphone socket (75).

The wrist watch phone includes a display (16) for interfacing with the user. The display is typically a 16bit OLED display having enough capacity to display around 65K of different colours. The display may be in the form of Thin Film Transistor Liquid Crystal Display (TFTLCD), touch screen or LCD made of glass or plastic.

The display is the main visual output of the wrist watch mobile phone. It provides various graphic user interfaces (GUI) to show the time as well as the mobile phone interface, including, for example, a dialling keypad display, an address book, an email client, etc. The display is preferably in the form of a touch screen, such that it can be used to accept input from the user. The display is used to show all of the functions typically used with a mobile telephone, and wrist watch. Preferably, these functions are accessible by the users through the GUI presented on the display of the watch phone. Typically only a subset of these functions appears on the display at any one time. A user may navigate through the GUI such as menu or icons to switch to different functions.

The housing (10) of the watch, also known as the watch "shell", encloses all the electronic components of the communication module and the time piece. As mentioned above, the size of the housing is generally smaller than that of a typical mobile phone such that it is suitable to be worn on the wrist. There may be one or more buttons located on the housing, preferably at the front or side of the housing for a user to activate certain functions of the watch.

The wrist watch phone may have watch straps (11) for fastening the watch around the wrist. The watch straps can be made of different variety of materials, such as, leather, metal, sponge, plastic or other materials, or mixtures of those known to be used with watch bands. The strap may be expendable to fit over the hand or else, it may have an fastening capable of opening and closing for wearing.

The wrist watch phone may also include an internal antenna. Typical antennas for GSM telephone networks are relatively large and cumbersome compared to the size of a wrist watch. In one preferred embodiment, the size of the internal antenna is reduced to fit inside the housing of the watch. The internal antenna of one preferred embodiment is embedded entirely inside the housing and it supports the transmission and reception of the GSM frequency bands mentioned above.

As another preferred embodiment, the antenna may extend along part or all of the watch band. A combination of having some of the antenna located within the housing, and the remainder situated within or along the watchband, may also be utilised. Also, it

may be permitted, according to the invention, to provide an antenna as a separate and removable component. This may ideally operate when the user needs to receive a weak signal, and the separate antenna may then be attached to the watch phone, either to enhance the attached antenna or to replace it.

5 A rechargeable battery may be installed inside the wrist watch phone to provide power to the watch. The battery module may provide power to support the communication module with 200 minutes talk time, or 80 hours standby time, for instance. In one preferred embodiment, the entire battery module is embedded inside the housing. The housing normally has a small opening for used in order to recharge
10 the battery.

The communication module may provide a Voice over IP (VoIP) facility. In other words, the wrist watch phone of a preferred embodiment supports communication using IP packets. The wrist watch mobile may directly connect to an IP number for communication, in this situation.

15 The wrist watch phone may have any one of the functions of an advanced mobile phone. It may provide the functions of sending and receiving digital data, emails, telephone calls, text messages, multimedia messages, files, videos, sounds, voices, music, pictures and games. The wrist watch phone may provide other wireless connection for other wireless electronic devices, and such wireless connection may be
20 an infra-red connection, Bluetooth connection, etc. New or improved such functions may be installed into the wrist watch phone by downloading new programs and upgrades through the communication module, if desired.

In another embodiment, the wrist watch phone may include a Global Positioning System (GPS) module. The GPS may be used to determine the location of the wearer
25 and this may also be used for tracking the location of the wearer. For example, a child may wear this watch with the GPS function enabled. If the child wanders outside school or home, the watch may be able to detect that and then send an email or SMS to the parent to notify them of the child's whereabouts. The parent may then telephone the child via the wrist watch mobile phone.

When the wrist watch phone is used for tracking a person, it may be desirable to lock the watch around a person's wrist such a way that it is not easy to remove the watch. One way to lock the watch to a person is provide a security encryption device for securely locking the wrist watch around a wrist. The security encryption device may
5 only then be unlocked by sending a digital key to the watch via the communication device. In this way, it is possible to unlock or re-lock the watch remotely. A remote signalling device may be used for sending out the key to lock or unlock the security encryption device through the GSM network.

Referring to figure 9, which shows the software architecture (60) of the watch, the
10 wrist watch phone may has a software operating system to interface with the hardware. The operating system has a Nucleus OS (61) for supporting the basic functions of an embedded system, these functions include file I/O, bus I/O, etc.

In addition to the Nucleus OS, there may be a number of protocol stack layers (62 and 64) for handing digital signals processing of the mobile communications. Each of
15 the stack layers may have one or more processing functions to control or map the data between logical and physical channels. There are also a number of device drivers (63), each of which is designed to provide control for one or more hardware components. There may be device drivers for the SIM module, Real Time Clock (RTC), Keypad, etc. With the device drivers, it is possible to create a program to control the devices
20 connecting to the baseband module.

The protocol stack layers and device drivers only provide basic programming interfaces controlling a hardware component and these basic programming interfaces provide very limited functions. Typically, so as to make the software programming more user friendly, there may be a Man to Machine Interface (MMI) layer (65)
25 centralising all the functions provide by the protocol stack layers and device drivers. Then MMI provides a set of Application Programming Interfaces (API) that are compatible to a high level computer languages such as JAVA (67), WAP (68), etc, such that developers may able to create new applications or update existing applications for the wrist watch mobile phone. The watch may then download new applications and
30 updates and run them. As a result, the functions of the watch may be enriched as more applications become available. The manufacturer may also provide updates to the

firmware to the watch. With the API provided, the wrist watch phone may optimise its performance with new application updates.

In another embodiment, the battery usage is minimised by reducing the display of unnecessary graphics.

5 In the drawings, the list of parts is shown in the following table, for one preferred embodiment of the wrist watch phone.

Table 2 – Parts Included in a GSM Watch Phone.

number	name	Figure
10	watch	1
11	straps	1
12	watch shell front	3
14	watch shell back	3
16	display	3
18	communication module	3
20	R/F module	7
22	T/R ASM	7
23	SAW filter	7
24	Transceiver	7
25	PA	7
30	baseband	7
31	controller	8
32	SIM	8
33	NorFlash	8
34	USB	8
35	I/O	8
36	Keypad	8
37	Bluetooth	8
38	RTC	8
39	TSC	8
40	power supply	8
41	controller	8
42	battery	8
43	charger	8
44	LED	8

45	vibrator	8
52	Receiver	8
53	MIC	8
54	Headset Receiver	8
55	Headset MIC	8
56	System Clock	8
57	RF Interface	8
58	LCD	8
59	Camera	8
60	software architecture	9
61	Nucleus OS	9
62	L1 Protocol Stack	9
63	Drivers	9
64	L2/L3 Protocol Stack	9
65	MMI	9
66	WAP	9
67	JAVA	9
68	META	9
69	Catcher	9
72	USB	10
73	SIM Interface	11
74	Mic Connector	11
75	Audio Jack	11
76	charger interface	11

INDUSTRIAL APPLICATION

As described above, the present invention is applicable to a mobile watch phone wearable on a wrist. According to the present invention, the mobile watch phone is adapted to connect to a variety of GSM telephone networks for communication of voice, video and data. The mobile watch phone also provides a variety of functions to facility mobile phone communication such as SMS, address book and email.

The mobile watch phone described above may also have a GPS device for tracking the location of the mobile watch phone. It can be used for tracking the location of the user wearing it.

CLAIMS:

1. A wrist watch phone wearable by a person comprising

a communication module adapted to operate under Global System of Mobile (GSM) telephone networks, to operate with at least one GSM frequency bands, and to send audio data across said GSM telephone networks;

an antenna connecting to said communication module, wherein said antenna is adapted to transmit signals to and receive signals from said GSM telephone networks;

a display adapted to at least display time, and to provide a graphic interface for showing a status of said communication module;

a power supply connecting to said communication module, wherein said power supply is adapted to provide power to said wrist watch mobile phone; and

a housing means adapted to enclose said display, said antenna, said communication module and said power supply.

2. The wrist watch phone of claim 1 comprising a retaining means adapted to secure said retaining means around a wrist.
3. The wrist watch phone of claim 1 wherein said communication module adapted to operate with at least three GSM frequency bands.
4. The wrist watch phone of claim 1 wherein said communication module adapted to operate in quad bands mode.
5. The wrist watch phone of any one of the preceding claims, wherein said GSM frequency bands include any one or more of 800Mhz, 850MHz, 900MHz, 1800MHz, 1900MHz, 2100Mhz.
6. The wrist watch phone of any one of the preceding claims, wherein said communication module adapted to operate under Voice Over IP (VOIP), Wi-Fi, InfraRed, Worldwide interoperability Microwave Access (WiMAX).

7. The wrist watch phone of any one of the preceding claims wherein said antenna is an internal antenna enclosed entirely inside said housing means.
8. The wrist watch phone of claim 2 wherein said antenna is enclosed within or retained upon said retaining means.
- 5 9. The wrist watch phone of any one of the preceding claims wherein said power supply includes a rechargeable battery adapted to provide power to said communication module and said display module.
10. The wrist watch phone of claim 9, wherein said communication module has a charger interface for recharging said rechargeable battery.
- 10 11. The wrist watch phone of any one of the preceding claims, wherein said display is any one of Organic Light-Emitting Diode (OLED) display, Thin Film Transistor Liquid Crystal Display (TFTLCD) or Liquid Crystal Display (LCD).
12. The wrist watch phone of any one of the preceding claims, wherein said display is made of any one of plastic or glass.
- 15 13. The wrist watch phone of any one of the preceding claims, wherein said display is a touch screen.
14. The wrist watch phone of any one of the preceding claims, wherein said display is adapted to display 256 colours.
15. The wrist watch phone of any one of the preceding claims, wherein said
20 communication module is adapted to communicate via IP Packets Exchange network.
16. The wrist watch phone of any one of the preceding claims, wherein said wrist watch is adapted to operate with a Subscriber Identity Module (SIM) card.
17. The wrist watch phone of any one of the preceding claims, wherein said wrist
25 watch includes a Global Positioning System (GPS) module connecting to said communication module, wherein said GPS module determines at least one

coordinate data of said wrist watch phone and displays said coordinate data on said display.

- 5 18. The wrist watch phone of any one of the preceding claims, wherein said communication module has a baseband module adapted to process, send and receive digital data.
19. The wrist watch phone of any one of the preceding claims, wherein said digital data include emails, telephone calls, text messages, multimedia messages, files, videos, sounds, voices, music, pictures and games.
- 10 20. The wrist watch phone of claim 18 and 19, wherein said wrist watch is adapted to send an email when said GPS has detected that said wrist watch phone is outside a predetermined geographical area.
21. The wrist watch phone of any one of the preceding claims, wherein said wrist watch has a Bluetooth communication module to connect to a Bluetooth compatible device.
- 15 22. The wrist watch phone of any one of the preceding claims, wherein said retaining means includes a security encryption device for securely locking said wrist watch around a wrist.
23. The wrist watch phone of claim 22, wherein said security encryption device is adapted to receive wireless signals for locking and unlocking said security encryption device.
- 20 24. The wrist watch phone of any one of the preceding claims, wherein said communication module includes a customized Printed Circuit Board (PCB).
25. The wrist watch phone of claim 24, wherein said PCB includes
- 25 a Radio Frequency (RF) module adapted to send and receive digital signals through GSM telephone networks using one of said three multiply frequency bands , and

a baseband module adapted to convert data from at least one input to said digital signals and to convert said digital signals from said RF module to data for output devices.

26. The wrist watch phone of claim 25, wherein said baseband module is adapted to send and receive data from at least one of the devices including: a USB device, an I/O device, a keypad, a Bluetooth device, a Real Time Clock (RTC), a Time Stamp Counter (TSC), a Microphone, a headset, a system clock, a display and a camera.
27. The wrist watch phone of claims 25 or 26, wherein said baseband module is adapted to collect status information from said rechargeable battery module and display said status information on said display.
28. A software module for use in the wrist watch phone of any one of the preceding claims, said software comprising:
- a protocol stack adapted to provide application programming interface (API) for said communication module; and
- a man to machine interface adapted to accept input from a user and pass said input to said communication module using said API, and to display output from said communication module using said API.
29. The software module of claim 28, wherein said API in a format compatible with at least one high level computer languages.
30. The software module of claim 29, wherein said API in a format compatible with wireless application protocol.
31. A software module of any one claims of 28 to 30, wherein said protocol stack has a battery control module for minimizing battery usage by optimizing the use of graphics
32. A software module of any one claims of 28 to 31 wherein said protocol stack is adapted to handle IP Exchange packets.