Description

This invention relates to a developing device which can be applied to an image-forming machine such as an electrostatic copying machine and an electrostatic printing machine.

Image-forming machines such as an electrostatic copying machine are equipped with a developing device for developing the resulting latent electrostatic image to a toner image.

It is conventional practice to use developing devices of the toner supply type which comprise a main body equipped with developer applicator means and a toner cartridge detachably mounted on the main body. The toner cartridge in the developing devices of this type include a cartridge body and a cover member for closing a toner supply opening formed in it. The cover member is attached to the toner supply opening when the cartridge body is to be detached from the main body of the developing device. This prevents scattering of the toner remaining in the cartridge body at the time of detaching. In the conventional developing device, the cartridge body can be detached from the main body of the developing device even when the cover member is not attached to the toner supply opening. If, therefore, the cartridge body is detached from the developing device by error, the toner inside it scatters through the toner supply opening.

It is also known (EP-A-0101303) for a developing device of the aforegoing type to use a toner cartridge comprising a hopper part for storing toner particles and a base plate which is mounted for limited sliding movement on the hopper part. The toner part and the base part each contain a respective plurality of spaced apertures. In one relative position of the hopper part and base plate, their apertures are aligned to enable toner to drop through to the developing device but in another relative position the apertures are not so aligned whereby passage of the toner particles is prevented. The base plate is an integral part of the toner cartridge and remains in place at all times, both when the toner cartridge is in use to dispense toner to the developing device and when the cartridge is detached from the developing device. One practical problem with the latter arrangement is that the toner is discharged through the aligned apertures in the toner hopper and the base plate which are arranged at spaced intervals in the longitudinal direction of the cartridge whereby no toner is dispensed in the regions between the latter apertures. Therefore, toner cannot be discharged uniformly across the entire length of the cartridge, as is desirable.

An object of the present invention is to provide an improved developing device in which when a cartridge body is to be detached from the main body of the developing device, scattering of a toner from it can be reliably prevented.

In accordance with a first aspect of the present invention, there is provided a developing device for developing an image in an image forming machine, said developing device comprising a main body including an applicator means for applying a developer to a latent electrostatic image, said main body having a toner inlet opening; a toner cartridge adapted to contain toner and having a toner discharge opening; said toner cartridge being selectively detachably mountable on said main body with said toner discharge and inlet openings aligned such that toner may be supplied from said cartridge into said main body; means for preventing detachment of the cartridge from said main body, and a cover member which is not part of the detachment preventing means and which is selectively removably mountable on the cartridge to block the toner discharge opening and to release said detachment preventing means to enable the cartridge to be detached from said main body.

Preferably, said cartridge detachment preventing means comprises a receiving portion defined in said cartridge, and an engaging member detachably receivable in said receiving portion and provided on said main body such that, when said cartridge is mounted on said main body, said engaging member is received in said receiving portion of said cartridge to thereby render substantially impossible the detachment of the cartridge from the main body, unless the cover member is mounted on the cartridge to remove the engaging member from the receiving portion of the cartridge and thereby permit detachment of the cartridge from the main body.

Advantageously, the engaging member is vertically, movably mounted on the main body of the developing device; a biasing means for biasing the engaging member upwardly is provided; the upper end of the engaging member is inclined upwardly in the mounting direction of the cover member; when the main body of the cartridge is detachably loaded into the main body of the developing device, the engaging member is received in the receiving portion of the main body of the cartridge by the action of the biasing means; and when the cover member is mounted on the main body of the cartridge, the engaging member is detached from the receiving portion of the main body of the cartridge as a result of the movement of the cover member in the mounting direction against the biassing action of the biassing means.

Preferably, a detaching movement hampering means is provided on said cartridge and said cover member for preventing detachment of the cover member from the cartridge, after the cover mem-

ber has been mounted on the main body of the cartridge.

The invention is described further hereinafter, by way of example, with reference to the accompanying drawings, in which:-

Fig. 1 is a sectional view showing one embodiment of a developing device for an electrostatic copying machine;

Fig. 2 is a perspective view, partly exploded, showing the main body of the developing device shown in Fig. 1;

Fig. 3 is an exploded perspective view showing the construction of an image-forming machine on which the main body shown in Fig. 2 is to be detachably mounted;

Fig. 4 is a perspective view showing the principal parts of the main body of the developing device shown in Fig. 2 and part of an image-forming machine on which the main body of the developing device is to be mounted;

Fig. 5 is a side view showing, partly in section, of the main body of the developing device shown in Figure 2 as it is detachably mounted on the main body of the image-forming device.

Figure 6 is a front view showing a changeover mechanism and positioning means in the developing device shown in Figure 1.

Figures 7-A and 7-B are each a front view showing a first cam of the changeover mechanism as it is held at a second angular position, and a front view showing a first cam of the changeover mechanism as it is held at a first angular position.

Figures 8-A, 8-B and 8-C show the state of pressing members in positioning means when an elevating-lowering member of the changeover mechanism is at an elevated position, and the movement of the pressing members when the main body of the developing device is detached while the elevating lowering member is at a lowered position.

Figures 9-A and 9-B respectively show, partly in section, the main body of the developing device as it is moved in the mounting direction and the detaching direction when the elevating-lowering member is at the elevated position.

Figures 10-A and 10-B respectively show the main body of the developing device as it is moved in the mounting direction and the detaching direction when the elevating-lowering member is at the lowered position.

Figure 11 is a perspective view showing a toner cartridge of the present invention which is adapted to be detachably loaded into the main body of the developing device.

Figure 12 is a partial front view showing a cartridge body and a cover member as they are mounted on a cartridge loading portion of the main body of the developing device.

Figures 13-A and 13-B are rough views for explaining the movement of discharge facilitating means attached to the main body of the developing device.

Figures 14-A to 14-C are rough sectional views for explaining the operation of loading the cartridge body on the main body of the developing device and the operation of detaching it from the main body of the developing device.

The outline of the illustrated developing device will be described with reference mainly to Figure 1.

The illustrated developing device comprises a main body 6 including a supporting section 2 and a developing section 4 extending from the supporting section 2 (see Figures 2 and 4 also). The main body 6 of the developing device is detachably mounted on an image-forming machine such as an electrostatic copying machine. In the so-mounted state, the developing section 4 of the main body 6 is free to pivot between a non-operating position shown by a solid line in Figure 1 and an operating position shown by a two-dot chain line in Figure 1.

The developing section 4 is provided with a development housing 8 defining a developing chamber 10. An opening 11 is formed in the left-hand surface of the development housing 8 in Figure 1 (that surface which faces a photosensitive material to be described). A magnetic brush mechanism 12 constituting an applicator means is disposed in the left-hand part of the developing chamber 10, and an agitating means 14 is disposed in the right-hand part of the developing chamber 10. The magnetic brush mechanism 12 is comprised of a combination of a hollow sleeve member 18 to be rotated in the direction shown by an arrow 16 and a stationary permanent magnet 20 disposed within the sleeve member 18. A developer is held on the peripheral surface of the hollow sleeve member 18 and carried in the direction of arrow 16. The agitating means 14 comprises a supporting shaft 22 and an agitating member 24 mounted on the supporting shaft 22. Outwardly projecting vanes 26 are provided on the peripheral surface of the agitating member 24. The agitating means 14 is rotated in the direction shown by an arrow 28 to agitate and mix the developer in the developing chamber 10 and triboelectrically charge the toner in the developer. A guide member 30 is provided above the hollow sleeve member 18 and the agitating member 24. A toner transfer chamber 32 is defined in the upper part of the developing chamber 10 (in other words, above the guide member 30), and a toner transfer means 34 is disposed in the toner transfer chamber 32. A toner supply opening 36 is formed in the bottom of the toner transfer chamber 32.

In the developing device of the above structure, the toner supplied from a toner cartridge (to be described hereinafter) is transferred in a direction perpendicular to the sheet surface in Figure 1 by the action of the toner transfer means 34. The transferred toner is supplied onto the guide member 30 through the toner supply opening 36, and allowed to flow down onto the agitating member 24 along the upper surface of the guide member 30. The agitating member 24 mixes the developer flowing down from the guide member 30 (containing the fresh toner supplied as stated above) and the developer present in the developing chamber 10, and feeds the mixture to the magnetic brush mechanism 12. The magnetic brush mechanism 12 magnetically holds the resulting mixed developer onto the peripheral surface of the hollow sleeve member 18 and transfers it in the direction of arrow 16. On the other hand, a brush length adjusting portion 38 projecting toward the peripheral surface of the sleeve member 18 is provided as a one-piece unit with part of the development housing 8. Hence, the excess of the developer held on the hollow sleeve member 18 is removed from it by the action of the brush length adjusting portion 38. The removed developer is conducted upwardly and then allowed to flow down toward the agitating member 24 over the upper surface of the guide member 30. A toner concentration detector 40 is disposed in proximity to the brush length adjusting portion 38. The toner concentration detector 40 detects the toner concentration of the developer which has been removed from the hollow sleeve member 18 and conducted upwardly. The developer whose brush length has been adjusted by the action of the brush length adjusting portion 38 is further transferred in the direction of arrow 16 by the rotation of the hollow sleeve member 18 and acts on the surface of image-bearing means such as a rotating drum 42 having a photosensitive material disposed on its peripheral surface. A latent electrostatic image is formed on the surface of the photosensitive material on the rotating drum 42 by means known per se. Hence, when the developer held by the magnetic brush mechanism 12 acts on the surface of the photosensitive material on the rotating drum 42 in a developing zone shown at 44, the latent electrostatic image is developed to a toner image.

Structure of the main body of the developing device

With reference to Figures 2, 4 and 5, the structure of the main body 6 of the developing device will be described. In the illustrated main body 6 of the developing device, the supporting section 2 exists at one end portion (the right-hand bottom portion in Figures 2 and 4, and the left-hand end portion in Figure 5), and the developing section 4 extends from the supporting section 2 to the other end portion (to the left-hand top in Figure 2, and to the right in Figure 4).

The supporting section 2 has a supporting main body 46, and a gripping member 48 which is provided as a one-piece unit with the front surface of the supporting main body 46. A pair of protruding portions 50 spaced from each other in the left-right direction are provided in the rear surface of the supporting main body 46, and a cylindrical receiving depressed portion 52 (Figures 4 and 5)is defined in each protruding portion 50. In the supporting main body 46, a supporting wall 54 extending substantially perpendicularly and upwardly is provided. A connecting terminal 56 constituting electrical connecting means is mounted on the supporting wall 54. An engaging member 60 having a claw portion 58 is pivotably mounted on the supporting main body 46, and a biasing spring 62 is attached to the engaging member 60. By depressing an operating portion 64 of the engaging member 60, the engaging member 60 can be pivoted against the biasing force of the biasing spring 62.

The development housing 8 of the developing section 4 has a pair of end walls 66 and 68 spaced from each other in the width direction of the housing 8, i.e. the front-rear direction of the image-forming machine (a direction perpendicular to the sheet surface in Figure 1, a direction from right-hand bottom to left-hand top in Figure 2, and the left-right direction in Figure 5) and a bottom wall 70, a side wall 72 and an upper wall 74 (Figure 1) disposed between the end walls 66 and 68, and these walls 66, 68, 79, 72 and 74 define the developing chamber 10. It will be understood from Figures 1 and 2 that in the illustrated embodiment, shaft portions (not shown) provided at opposite end portions of the hollow sleeve member 18 in the magnetic brush mechanism 12 are supported rotatably on the end walls 66 and 68, and supported on the end wall 66 via a supporting member 76 mounted on the end wall 66. In the illustrated embodiment, one end of a wire 78 for applying a development bias voltage to the hollow sleeve member 18 is connected to the supporting member 76 by means of a screw member 79. The other end of the wire 78 is connected to the connecting terminal 56 of the supporting section 2. The supporting shaft 22 of the agitating means 14 is also rotatably supported on the end walls 66 and 68.

With reference mainly to Figure 2, in the illustrated embodiment, an auxiliary housing 80 is mounted on the upper wall 74 of the development housing 8, and the auxiliary housing 80 is provided with a cartridge loading portion 82 and a toner

transfer portion 84. The cartridge loading portion 82 defines a toner discharge chamber 86, and its upper surface is opened.

A toner cartridge 88 (Figure 10) is detachably loaded above the toner discharge chamber 86, and the toner in the toner cartridge 88 is discharged into the toner discharge chamber 86. The toner cartridge 88 and the cartridge loading portion 82 will be described hereinafter in detail. The toner transfer portion 84 is constructed of a hollow cylindrical wall 90 and extends from the cartridge mounting portion 82 to the left-hand top in Figure 2. A pair of protrusions 92 are provided opposite to the peripheral surface of the cylindrical wall 90, and the auxiliary housing 80 is mounted in position on the development housing 8 by securing the protrusions 92 to the upper wall 74 of the housing 8 by screws 94. The toner transfer chamber 32 defined by the cylindrical wall 90 is allowed to communicate with the toner discharge chamber 86, and the toner supply opening 36 formed at its bottom has a progressively increasing width in the toner transfer direction shown by an arrow 96. A helical member 98 constituting the toner transfer means 34 is rotatably mounted in the toner transfer chamber 32. One end portion of the helical member 98 extends from the toner transfer chamber 32 to the toner discharge chamber 86, and its other end portion extends to the left-hand top in Figure 2 in the developing chamber 10. Accordingly, the toner discharged into the toner discharge chamber 86 from the toner cartridge 88 (Figure 10) is transferred in the direction of arrow 96 in the toner transfer chamber 32 by the action of the helical member 98. In the upstream portion of the toner transfer chamber 32 in the transfer direction shown by arrow 96, the width of the toner supply opening 36 is relatively small. Thus, in spite of the relatively large amount of the toner transferred, the proportion of the toner supplied through the toner supply opening 36 is relatively small. Since the width of the toner supply opening 36 is relatively large in the downstream portion of the toner transfer chamber 32 in the transfer direction shown by arrow 96, the proportion of the toner supplied through the toner supply opening 36 is relatively large in spite of the relatively small amount of the toner transferred. Hence, the toner from the toner discharge chamber 86 is supplied substantially uniformly over the entire width direction of the developing chamber 10 through the toner supply opening 36.

The supporting section 2 and the developing section 4 are connected as described below. Mainly with reference to Figures 2 and 4, a circular hole 100 and an arcuate guide hole 102 are formed in the supporting wall 54 in the supporting section 2. On the other hand, in the developing section 4, a supporting shaft portion 104 and a guide shaft portion 106 to be guided are provided on the outside of the end wall 66. The developing section 4 is attached to the supporting section 2 by inserting the supporting shaft portion 104 into the hole 100 and the guide shaft portion 106 into the guide hole 102. In the illustrated embodiment, the supporting shaft portion 104 and the guide shaft portion 106 slightly project through the supporting wall 54 of the supporting section 2, and a linking plate piece 110 is attached to the end surfaces of the supporting shaft portion 104 and the guide shaft portion 106 by screws 108. By the action of the linking plate piece 110, detachment of the developing section 4 from the supporting section 2 is reliably prevented. A biassing coil spring 112 (constituting biasing means) is fitted over the supporting shaft portion 104. One end portion of the biasing coil spring 112 is anchored at part of the supporting wall 54, and the other end portion is anchored at the guide shaft portion 106. The biasing coil spring 112 resiliently biases the developing section 4 in the direction shown by an arrow 114 (see Figure 1) toward the operating position shown by the two-dot chain line in Figure 1.

With reference to Figures 3 to 5, the structure of the main body of an image-forming machine on which the main body 6 of the developing device is detachably mounted is now described.

The main body of the image-forming machine, such as an electrostatic copying machine, has a front base plate 116 and a rear base plate 118 (Figure 5) spaced from each other in the front-rear direction (the left-right direction in Figure 5). An opening 117 (Figure 4) having a shape nearly corresponding to the shape of the developing section 4 of the developing device 6 is formed in the front base plate 116, and the developing section 4 is positioned in the required manner between the front base plate 116 and the rear base plate 118 as shown in Figure 5 through the opening 117. In the illustrated embodiment shown in Figure 4, a plate-like supporting guide member 284 having a shape corresponding to the shape of the lower portion of the developing section 4 is provided at a site which defines the lower edge of the opening 117. As shown in Figure 4, one end portion of the supporting guide member 284 projects slightly ourwardly from the front base plate 116, and its other end portion projects slightly inwardly from the front base plate 116. The supporting guide member 284 has a predetermined width in the front-rear direction (see Figures 9-A and 9-B). The supporting guide member 284 guides and supports the developing section 4 at the time of mounting and detaching the main body 6 of the developing device. In the front surface (outside surface) of the front base plate 116, a pair of supporting pins 120 (Figure 4) spaced from each other in the left-right

direction are implanted. The pair of supporting pins 120 are disposed corresponding to the pair of receiving depressed portions 52 defined in the supporting section 2. A connecting terminal 119 (constituting electrical connecting means) corresponding to the connecting terminal 56 of the supporting section 2 is provided in the front surface of the front base plate 116. Hence, when the main body 6 of the developing device is detachably mounted on the main body of the image-forming machine as shown in Figure 5, the supporting pins 120 in the front base plate 116 are received in the receiveing depressed portions 52 of the supporting section 2. As a result, the supporting section 2 is mounted on the front base plate 116, and the connecting terminal 56 of the supporting section 2 is electrically connected to the connecting terminal 119 of the front base plate 116. Thus, the hollow sleeve member 18 and the toner concentration detector 40 are connected to a bias power supply and control means (both of which are not shown) provided in the main body of the image-forming machine via the connecting terminals 56 and 119. The connecting terminal 56 may be of a convex shape, for example, and the other connecting terminal 119 may be of a concave shape conforming to the convex shape.

In the illustrated embodiment, a sleeve 121 (Figure 5) made of a metalic material is fitted in the inside of one protruding portion 50 (the one on the right top in Figures 2 and 3). The front base plate 116 and the supporting pins 120 are also formed of a metallic material. A grounding wire 124 of an electric motor 122 is fixed to the above one protruding portion 50 in order to rotate the helical member 98, and connected to a sleeve member 121 via a fixing screw. Hence, when the main body 6 of the developing device is mounted in the required manner, the grounding wire 124 of the electric motor 122 is ground to the front base plate 116 via the fixing screw, the sleeve member 112 and the supporting pin 120.

With reference mainly to Figure 3, a supporting plate 126 extending in the front-rear direction is disposed between the front base plate 116 and the rear base plate 118. An upwardly opened channel-like guide portion 128 is provided in the upper end portion of the supporting plate 126, and extends in a straight line from one end of the supporting plate 126 toward its rear end portion. In the illustrated embodiment, a greater portion of the guide portion 128 extends substantially horizontally, and only its other end portion 128a is inclined downwardly toward the other end (the right end in Figure 5). On the other hand, the upper part of the right end (in Figure 1) of the development housing 8 has provided therein a rightwardly projecting protruding portion 130 to be supported, and a downwardly projecting piece 132 is formed integrally in the under surface of the protruding portion 130. Furthermore, as shown in Figure 5, a protruding portion 134 is formed in the outside surface of the end wall 68 of the developing section 4, and a shaft member 136 is mounted on the rear base plate 118. A receiving depressed portion 140 extending to the left in Figure 5 is defined in the end surface of the protruding portion 134. On the other hand, a fixing portion 142 is provided in one end portion of the shaft member 136, and the other end portion of the shaft member 136 projects inwardly through the rear base plate 118. A gear 144 is attached to this projecting portion of the shaft member 136 so as to be movable in the front-rear direction shown by an arrow 138. The other end of the shaft member 136 projects inwardly from the gear 144. Between the gear 144 and the rear base plate 118 is interposed a biasing spring member 146 for elastically biasing the gear 144 inwardly. The gear 144 is drivingly connected to a driving source for the image-forming machine although it is not shown in the accompanying drawings. In mounting the main body 6 of the developing device on the main body of the image-forming machine, the protruding piece 132 provided in the development housing 8 is guided by the guide portion 128 of the supporting plate 126 and moved in the mounting direction shown by an arrow 148. When the main body 6 of the development device is mounted in the required manner, the projecting end portion of the shaft member 136 is positioned in the receiving depressed portion 140 of the protruding portion 134 provided in the end wall 68 of the developing section 4. Hence, in the as-mounted state, one end portion of the developing section 4 is rotatably supported by the supporting portion 2 via the supporting shaft portion 104, and the other end portion of the developing section 4 is rotatably supported on the rear base plate 118 via the shaft member 136. The developing section 4 is thus free to rotate between the aforesaid non-operating and operating positions about the supporting shaft portion 104 and the shaft member 136 as a center (more specifically about a central axis of the supporting shaft portion 104 and the shaft member 136 which constitutes a rotating central axis extending in the widthwise direction of the main body 6 of the developing device). When the main body 6 of the developing device is so mounted, a gear for rotating the hollow sleeve member 18 of the magnetic brush mechanism 12 and a gear for rotating the supporting shaft 24 of the agitating means 14 are drivingly connected to the gear 144 although these non-numbered gears are not shown in the drawings.

Changeover mechanism

In the illustrated embodiment, a changeover mechanism 150 is provided which selectively brings the developing section 4 to the non-operating position shown by the solid line in Figure 1 and the operating position shown by the two-dot chain line in Figure 1 when the main body 6 of the developing device is set on the main body of the image-forming machine. With reference to Figure 6 as well as Figure 3, the illustrated changeover mechanism 150 is provided with cam means 152 and an elevating-lowering member 154 adapted to be elevated or lowered by the action of the cam means 152. The elevating-lowering member 154 has a main body portion 156, an acting portion 158 provided in an intermediate portion in the main body portion 156, a bent portion 160 at the upper end of the main body portion 156, and a cam follower portion 162 extending downwardly from the bent portion 160. A vertically extending elongate hole 164 is formed in the main body portion 156. The elevating-lowering member 154 is mounted vertically movably on the other end portion of the supporting frame 126 in the manner mentioned below. A guide member 166 is disposed in the hole 164 of the main body portion 156 of the elevating-lowering member 154 (more specifically, a guide projecting portion 166a of the guide member 166 is positioned in the hole 164). On the other hand, mounting pins 170 spaced from each other in the vertical direction are provided in a mounting member 168. By inserting the mounting pins 170 into openings 174 provided in the supporting plate 126 through holes 172 formed in the guide member 166, the elevating-lowering member 154 is mounted on the guide member 166 attached to the supporting plate 126. In the illustrated embodiment, a fixing screw 176 is threadedly secured to the supporting plate 126 through the mounting member 168 and the guide member 166. Hence, the elevating-lowering member 154 is free to move between an elevated position (the position shown in Figure 7-B) at which the lower end of the hole 164 abuts against the lower end of the guide protruding portion 166a and a lowered position (the position shown in Figures 6 and 7-A) at which the upper end of the hole 164 abuts against the upper end of the guide protruding portion 166a). The acting portion 158 of the elevating-lowering member 154 is constructed such that it can act on the protruding portion 132 provided in the development housing 8. A biasing spring 178 is also attached to the elevating-lowering member 154. One end portion of the biasing spring 178 is engaged with an engaging protruding piece 156a provided in the main body portion 156 of the elevating-lowering member 154 and its other end portion is engaged with an engaging piece 179 provided in the lower end portion of the supporting plate 126. The biasing spring 178 elastically biases the elevating-lowering member 154 downwardly toward the aforesaid lowered position.

The illustrated cam means 152 is provided with a fan-like first cam 180 and a circular second cam 182. In the illustrated embodiment, an auxiliary plate 186 is secured to the rear end portion of the upper part of the supporting plate 126 by means of a fixing screw 184. An electric motor 188 is mounted on the auxiliary plate 186, and the first cam 180 and the second cam 182 are mounted on an output shaft 190 which projects from the electric motor 188 through the auxiliary plate 186. The first cam 180 and the second cam 182 are formed as a one-piece unit. The first cam 180 is disposed so that its peripheral surface acts on the lower edge of the cam follower portion 162 of the elevating-lowering member 154, and the second cam 182 is disposed so as to be positioned between the main body portion 156 and the cam follower portion 162 of the elevating-lowering member 154. Switch means 192 such as a microswitch is attached to the second cam 182. The switch means 192 has a detecting arm 192a, and is adapted to be on when the large-diameter portion 194 of the second cam 182 acts on the detecting arm 192a and to be off when the small-diameter portion 196 of the second cam 182 acts on the detecting arm 192a (or does not substantially act on the detecting arm 192a).

When a changeover switch (not shown) provided in an operating panel in the image-forming machine in order to set the developing section 4 in operation, the electric motor 188 is rotated in the direction shown by an arrow 198 (Figures 7-A and 7-B), and with it, the first cam 180 and the second cam 182 are rotated. When by this rotation, the large-diameter portion 194 of the second cam 182 acts on the detecting arm 192a of the switch means 192, the electric motor 188 is de-energized on the basis of a detection signal from the switch means 192, and the elevating-lowering member 154 and elements relating to it are held in the state shown in Figures 6 and 7-A. In the state shown in Figure 7-A, the first cam 180 is held at a second angular position displaced substantially by an angle of 180 degrees from a first angular position. At the second angular position, the small-diameter portion 200 of the first cam 180 acts on the lower edge of the cam follower portion 162 of the elevating-lowering member 154 and the elevating-lowering member 154 is moved to the lowered position by the action of the biasing spring 178. It will be easily understood by comparing Figure 7-A with Figure 7-B that at the lowered position, the developing section 4 is permitted to rotate in the direction shown by an arrow 114 (Figure 1) with respect to the

supporting section 2, and the developing section 4 is brought to the operating position shown by the two-dot chain line in Figure 1 by its own weight and the biasing coil spring 112 attached to the developing section 4. In the operating position, part of the development housing 8 abuts against supporting means (not shown) supporting the rotating drum 42, and therefore, the turning of the developing section 4 beyond the operating position is exactly hampered by the action of the supporting means. When the developing section 4 is thus held at the operating position, the magnetic brush mechanism 12 is positioned in proximity to the peripheral surface of the rotating drum 42 and the developer held on the hollow sleeve member 18 acts on the surface of the photosensitive material on the rotating drum 42 in the developing zone 44. As a result, a latent electrostatic image formed on the surface of the photosensitive material is developed to a toner image. As shown in Figure 7-A, when the elevating-lowering member 154 is held at the lowered position, the acting portion 158 abuts aginst, or is away downwardly from, the under surface of the protruding piece 132 of the development housing 8. Therefore, the acting portion 158 does not substantially act on the protruding piece 132. On the other hand, when the changeover switch (not shown) provided in the operating panel is operated in order to set the developing section 4 out of operation, the electric motor 188 is rotated in the direction of arrow 198, and with it, the first cam 180 and the second cam 182 are rotated. When by this rotation, the small-diameter portion 196 of the second cam 182 acts on the detecting arm 192a of the switch means 192, the electric motor 188 is deenergized on the basis of a detection signal from the switch means 192, and the elevating-lowering member 154 and elements relating to it are held in the state shown in Figure 7-B. In the state shown in Figure 7-B, the first cam 180 is held at the first angular position by being substantially moved away from the second angular position. Since at the first angular position, the large-diameter portion 202 of the first cam 180 acts on the lower edge of the cam follower portion 162 of the elevating-lowering member 154, the elevating-lowering member 154 is held at the elevated position against the action of the biasing spring 178. At the elevated position, the acting portion 158 of the elevating-lowering member 154 acts on the protruding piece 132 of the development housing 8 to elevate it as shown in Figures 1 and 7-B. Consequently, the developing section 4 is turned in a direction opposite to the direction of arrow 114 and brought to the non-operating position shown by a solid line in Figure 1. At the non-operating position, the magnetic brush mechanism 12 is positioned apart from the peripheral surface of the rotating drum 42, and the developer held on the hollow sleeve member 18 does not substantially act on the surface of the photosensitive material on the rotating drum 42.

Positioning means

The illustrated developing device is provided with positioning means for holding the developing section 4 of its main body 6 exactly at the aforesaid operating position. With reference to Figures 3 and 6, the illustrated positioning means 204 is equipped with a pair of pressing members 206 spaced from each other in the widthwise direction of the main body 6 of the developing device (the direction from right bottom to left top in Figure 3, and the left-right direction in Figure 6). In the illustrated embodiment, an upwardly extending projecting portion 208a is provided at one end portion of the supporting plate 126, and one pressing member 206 is pivotably mounted on a pin 210 implanted in the projecting portion 208a. An upwardly extending projecting portion 208b is provided at the other end portion of the supporting plate 126, and the other pressing member 206 is pivotably mounted on a pin 210 implanted in the projecting portion 208b. An engaging member 211 for preventing detachment of the press member 206 is attached to the end of each pin 210. Each of the press members 206 is nearly in an inverted L-shape, and has a downwardly extending arm portion 212 and a pressing arm portion 214 extending to the left in Figures 3 and 6. A nearly triangular pressing block piece 216 is attached to the end of the pressing arm portion 214 by means of a fixing screw 218. Each of the pressng members 206 is free to pivot between a first position shown in Figures 6 and 7-A and a second position shown in Figure 7-B. A biasing coil spring 220 constituting elastic biasing means is attached to each of the pressing members 206. The biasing coil spring 220 is fitted over the pin 210 and its one end portion is engaged with a hole 222 (Figure 3) formed in the supporting plate 126. Its other end portion is engaged with the pressing arm portion 214 of the pressing member 206. Thus, the biasing coil spring 220 elastically biases each pressing member 206 toward the aforesaid first position, namely counterclockwise in Figures 3 and 6.

The illustrated positioning means 204 is further equipped with a moving member 224 for pivoting the pressing members 206. The moving member 224 has a relatively long first member 226 and a relatively short second member 228, and the first member 226 is mounted on the supporting plate 126 so that it can move in the widthwise direction of the main body 6 of the developing device. In the illustrated embodiment, a pair of supporting screws 230 spaced from each other in the widthwise direc-

tion of the main body 6 of the developing device are threadedly secured to the supporting plate 126, and a sleeve member 232 is rotatably mounted on each of the supporting screws 230. On the other hand, a pair of elongate holes 234 are formed in the opposite end portions of the first member 226 corresponding to the pair of supporting screws 230. By positioning the sleeve members 232 in the elongate holes 234, the first member 226 is mounted on the supporting plate 126. Hence, as shown in Figures 7-A and 7-B, the first member 226 is free to move between a position at which each supporting screw 230 is positioned at one end portion of each elongate hole 234 and a position at which each supporting screw 230 is positioned at the other end portion of each elongate hole 234. Acting sleeve members 236 are mounted on the opposite end portions of the first member 226 corresponding to the pressing members 206. In the illustrated embodiment, supporting screws 238 are threadedly secured to both end portions of the first member 226, and the acting sleeve members 236 are rotatably mounted on the supporting screws 238. Hence, by the abutment of the arm portions 212 of the pressing members 206 against the acting sleeve members 236, the pressing members 206 are reliably prevented from turning counterclockwise in Figures 6, 7-A and 7-B. To permit the aforesaid movement of the first member 226, long holes 240 for the acting sleeve members 236 are formed in the supporting plate 126. Furthermore, in order to permit mounting of the first member 226, a large-diameter portion 240a for permitting insertion of each acting sleeve member 236 is formed in one end of each long hole 240 in the supporting plate 126. The second member 228 is interposed between the cam means 152 and the first member 226. One end portion of the second member 228 is rotatably connected to the first member 226 via a connecting screw 242 threadedly secured to the left end of the first member 226 in Figures 3 and 6 and a sleeve member 244 attached to the connecting screw 242. A disc-like portion 246 is integrally formed in the second cam 182, and the other end portion of the second member 228 is rotatably connected to the second cam 182 via a connecting screw 248 threadedly secured to the disc-like portion 246 in eccentric relationship and a sleeve member 250 attached to the connecting screw 248.

In operation, the positioning means 204 is held in an operating state shown in Figure 7-A when the first cam 180 is at the second angular position. Specifically, the connecting screw 248 secured to the second cam 182 is positioned in proximity to the first member 226 and therefore, the first member 226 is moved in the direction shown by an arrow 252 (Figure 7-A) via the second member 228 and held at the position shown in Figure 7-A (the position at which the supporting screw 230 is positioned at one end portion of the long hole 234 of the first member 226). As a result, with the movement of the first member 226, the supporting screws 238 are also moved to permit pivoting of the pressing members 206 in the direction shown by an arrow 254 (Figure 7-A). The pressing members 206 are pivoted in the direction of arrow 254 by the action of the biasing coil springs 220. Consequently, as shown in Figure 7-A, the pressing block piece 216 provided in the pressing arm portion 214 of each pressing member 206 acts on the upper surface of the right end portion of the developing section 4 in Figure 1 [more specifically the upper surface of one protrusion 92 (the right protrusion in Figures 1 and 3) provided in the auxiliary housing 80]. As a result, the developing section 4 is turned in the direction of arrow 114 (Figure 1) by its one weight and by the biasing force of the biasing coil spring 112 and surely held at the operating position. Since in this operating state of the positioning means 204 each of the pressing members 206 is elastically biased in the direction of arrow 254 (Figure 7-A) by the action of the biasing coil spring 220, the developing section 4 is elastically held exactly at the operating position by the action of the biasing coil springs 220 and the pressing members 206 (and therefore, the pressing members 206 are held elastically at the first position). On the other hand; when the first cam 180 is at the first angular position, the positioning means 204 is held in a non-operating state shown in Figure 7-B. Specifically, the connecting screw 248 secured to the second cam 182 is positioned away from the first member 226, and therefore, the first member 226 is moved in the direction of arrow 256 (Figure 7-B) via the second member 228 and held at the position shown in Figure 7-B (the position at which the supporting screw 230 is held at the other end portion of the long hole 234 of the first member 226). As a result, the supporting screws 238 are moved with the movement of the first member 226, and the supporting screws 230 act on the arm portions 212 of the pressing members 206 via the acting sleeve members 236 to pivot the arm portions 212 in the direction shown by an arrow 258 (Figure 7-B). Thus, the pressing members 206 are held at the second position shown in Figure 7-B. Thus, since the first cam 180 is at the first angular position, the developing section 4 is held at the non-operating position. Furthermore, since the pressing members 206 are held at the second position, the pressing block pieces 216 abut against, or positioned slightly upwardly from, the developing section 4. Hence, the pressing members 206 do not substantially act on the developing section 4, and the developing section 4 is exactly held at the non-operating position by the action of

the elevating-lowering member 154.

In relation to the positioning means 204, for easy elevating of the elevating-lowering member 154 the above embodiment is preferably constructed such that the elevating-lowering member 154 is elevated by the first cam 180 after the pressing by the pressing members 206 is cancelled by moving the first member 226 in the direction of arrow 256.

The above developing device has the following features in relation to the positioning means 204.

With reference to Figures 8-A to 8-C in conjunction with Figures 7-A and 7-B, when the elevating-lowering member 154 is at the elevated position, the acting portion 158 of the elevating-lowering member 154 is substantially on the same level as the guide portion 128 provided in the supporting plate 126 (see Figures 7-B and 8-A). Hence, when the elevating-lowering member 154 is held at the elevated position at the time of detaching the main body 6 of the developing device from the main body of the image-forming machine, the developing section 4 is held at the non-operating position. Consequently, the pressing members 206 of the positioning means 204 are held at the second position, and the acting portion 158 of the elevating-lowering member 154 is held on the same level as the guide portion 128 of the supporting plate 126. Accordingly, the main body 6 of the developing device can be detached from the main body of the image-forming machine by moving it in the detaching direction shown by arrow 260 (Figure 5). At the time of detaching, the protruding piece 132 provided in the development housing 8 is moved while being guided by the guide portion 128 of the supporting plate 126 and the acting portion 158 of the elevating-lowering member 154 at the elevated position. The developing section 4 is therefore kept at the non-operating position during detachment, and the developer held by the magnetic brush mechanism 12 does not substantially act on the surface of the photosensitive material on the rotating drum 42. Damage of the photosensitive material during detachment can therefore be prevented. At the same time, scattering of the developer which occurs upon its acting on the photosensitive material can be reliably prevented. Furthermore, the pressing members 206 are held at the second position and do not substantially act on the developing section 4. Moreover, since the acting portion 158 and the guide portion 128 are maintained on the same level, the main body 6 of the developing device can be easily moved in the detaching direction shown by arrow 260. For the detachment of the main body 6 of the developing device in the aforesaid state, see Figures 9-A and 9-B also.

When the elevating-lowering member 154 is held at the lowered position, the acting position 158 of the elevating-lowering member 154 is substantially on the same level as the lower end of the other end portion 128a of the guide portion 128 provided in the supporting plate 126 (see Figures 7-A, 8-B and 8-C). The developing section 4 is reliably held at the opening position as a result of the positioning means 204 being held in the operating state. In the illustrated embodiment, when the positioning means 204 is in the operating state, the pressing members 206 are biased toward the first position by the biasing coil springs 220, but can be pivoted to the second position against the biasing action of the biasing coil springs 220. In this connection, the main body 6 of the developing device can be detached from the main body of the image-forming machine even when the elevating-lowering member 154 is at the lowered position. With reference to Figures 9-A, 8-B and 8-C, when the main body 6 of the developing device is moved in the detaching direction of arrow 252 while the elevating-lowering member 154 is at the lowered position the developing section 4 is at the operating position, the protruding piece 132 provided in the development housing 8 first moves inclinedly upwardly by the guidance of the inclined surface of the other end portion 128a of the guide portion 128 in the supporting plate 126. Thereafter, the protruding piece 132 is guided by a substantially horizontal part of the guide portion 128 (Figure 8-C). (Incidentally, that part of the protruding piece 132 which comes into contact with the other end portion 128a of the guide portion 128 is preferably inclined correspondingly to the other end portion 128a in order to make the upward movement of the protruding piece 132 smooth.) When the main body 6 of the developing device is thus moved in the direction of arrow 252, the developing section 4 is turned from the operating position toward the non-operating position since the protruding piece 132 is moved upwardly. With this movement, the pressing members 206 are pivoted from the first position toward the second position in the direction of arrow 250. When as shown in Figure 8-C, the protruding piece 132 is moved along the substantially horizontal part of the guide portion 128, the developing section 4 is held at the non-operating position and the pressing members 206 are held substantially at the second position. (Incidentally, when the main body 6 of the developing device is detached in the required manner, the pressing members 206 are brought to the first position shown by a solid line in Figure 8-C by the returning force of the biasing coil springs 220). Accordingly, in relation to the fact that the pressing members 206 can be pivoted between the first and second positions even when the positioning means 204 is in the operating state, the main body 6 of the developing device can be detached in the required manner from the main body of the image-forming machine by moving it in

the detaching direction shown by arrow 260. When the main body 6 of the developing device is moved in the detaching direction of arrow 260 while the developing section 4 is at the operating position, the developing section 4 is held at the non-operating position by the action of the inclined other end portion 128a of the guide portion 128 and the protruding piece 132 provided in the development housing 8. Thus, the developing section 4 is moved while being held at the non-operating position. In this case, too, the developer held on the magnetic brush mechanism 12 does not substantially act on the surface of the photosensitive material on the rotating drum 42, and the damage of the photosensitive material during detachment can be reliaby prevented. In addition, scattering of the developer can be reliably prevented. See Figures 10-A and 10-B also with regard to the detachment of the main body 6 of the developing device when the elevating-lowering member 154 is at the lowered position.

In the illustrated embodiment, as shown in Figure 8-A, the protruding piece 132 in the development housing 8 is preferably constructed as to be substantially astride the substantially horizontal part of the guide portion 128 and the acting portion 148 of the elevating-lowering member 154. This arrangement permits easier mounting and detachment of the main body 6 of the developing device.

Non-operating position holding means

The illustrated developing device is further provided with means for holding the developing section 4 at a non-operating position. With reference mainly to Figures 2 and 5, the non-operating position holding means 262 has a holding member 264 movable in the mounting and detaching directions of the main body 6 of the developing device. The holding member 264 has a main body portion 266 extending in the mounting direction shown by the arrow 148 (Figure 5), a suspending piece 268 provided in the right end portion in Figure 5 of the main body portion 266 (the front end portion in the mounting direction of arrow 148) and a turn hampering portion 270 provided in the left end portion in Figure 5 of the main body portion 266 (the rear end portion in the mounting direction of arrow 148). On the other hand, a guide groove 274 (Figure 2) having a nearly T-shaped vertical sectional shape is provided in a protruding portion 272 extending outwardly from the end wall 66 of the development housing 8. The main body portion 266 of the holding member 264 is fitted in the guide groove 274 so as to be free to move in the directions shown by arrows 148 and 260. In the illustrated embodiment, the suspending piece 268 and the turn hampering portion 270 of the holding member 264 project downwardly through downwardly extending opening formed in the guide groove 274, as shown in Figure 5.

The turn hampering portion 270 of the holding member 264 is constructed such that it engages part of the supporting section 2 when it is at an engaging position shown in Figures 9-A and 10-A. In the illustrated embodiment, the under surface of the turn hampering portion 270 defines a substantially horizontal hampering surface 270a, and the upper surface of part of the supporting main body 46 in the supporting section 2 defines a substantially horizontal engaging surface 276 adapted to cooperate with the hampering surface 270a. At the aforesaid engaging position, the hampering surface 270a of the turn hampering portion 270 comes into engagement with the engaging surface 276 of the supporting section 2. In the illustrated embodiment, biasing means is attached to the holding member 264. The biasing means is constructed of a biasing spring 278. Its one end portion is engaged with an engaging piece 280 provided in the development housing 8 and its other end portion is engaged with the suspending piece 268 of the holding member 264 (see Figures 9-A and 10-A). The biasing spring 278 biases the holding member 264 toward the above engaging position. In relation to the holding member 264, a hampering member 282 is provided in the development housing 8. The hampering member 282 abuts against the suspending piece 268 of the holding member 264 and reliably hampers the movement of the holding member 264 beyond the engaging position.

The operation and effect of the non-operating position holding means 262 will now be described.

In the above developing device, the holding member 264 is usually held at the engaging position when its main body 6 is detached from the image-forming machine. The suspending piece 268 of the holding member 264 abuts against the hampering member 282 provided in the development housing 8, and the hampering surface 270a of the turn hampering member 270 is kept in engagement with the engaging surface 276 defined in the supporting main body 46 of the supporting section 2. Hence, in spite of the biasing action of the biasing coil spring 278, turning of the developing section 4 in the direction of arrow 113 (Figure 1) with respect to the supporting section 2 is reliably hampered by the action of the hampering surface 270a and the engaging surface 276, and as can be seen from Figures 9-A and 10-A, the developing section 4 is held at the non-operating position with respect to the supporting section 2.

When the main body 6 of the developing device in this condition is mounted detachably on the main body of the image-forming machine, the holding member 264 is disengaged as described be-

low. As shown in Figures 9-A and 9-B which show the elevating-lowering member 154 at the elevated position and Figures 10-A and 10-B which show the elevating-lowering member 154 at the lowered position, when the main body 6 of the developing device is slightly inserted into the opening formed in the front base plate 116 and the protruding piece 132 provided in the development housing 8 is positioned in the guide portion 128 of the supporting plate 126 and moved in the mounting direction shown by arrow 148, the front end portions of the pair of supporting pins 120 provided in the front base plate 116 are received in the pair of receiving depressed portions 52 defined in the supporting section 2 as shown in Figures 9-A and 10-A at a point of time when a greater portion of the developing section has been inserted into the main body of the image-forming machine. At this point of time, it is preferred that the protruding piece 132 provided in the development housing 8 be positioned at a substantially horizontally extending part of the guide portion 128, and the holding member 264 be held at the engaging position. By this arrangement, the pair of supporting pins 120 can easily be inserted into the receiving depressed portions 52 of the supporting section 2. When the main body 6 of the developing device is further moved in the direction of arrow 148, the suspending piece 268 of the holding member 264 abuts against a supporting guide member 284 provided in the opening formed in the front base plate 116 (Figures 10-A and 10-B). With the movement of the main body 6 in the direction of arrow 148, the holding member 264 is moved in the direction of arrow 260 relative to the developing section 4 against the biasing force of the biasing spring 278. As a result, the engagement between the hampering surface 270a of the holding member 264 and the engaging surface 276 of the supporting section 2 is cancelled, and the developing section 4 is permitted to turn toward the operating position. Preferably, even when the engagement between the hampering surface 270a and the engaging surface 276 is cancelled, the protruding piece 132 of the development housing 8 is positioned at the substantially horizontal part of the guide member 128 and by moving the main body 6 of the developing device further slightly in the direction of arrow 148, the lower end of the protruding piece 132 moves away from the substantially horizontal part of the guide portion 128. When the main body 6 of the developing device is further moved, the front end portion of the shaft member 136 mounted on the rear base plate 118 is received in the receiving depressed portion 140 formed in the protruding portion 134 provided in the end wall 68 (Figure 2) of the development housing 8, and the main body 6 is detachably mounted on the main body of the image-forming machine. In this mounted position, one end portion of the main body 6 of the developing device is supported by the front base plate 116 as a result of the supporting pin 120 being positioned in the receiving depressed portion 52, and the other end portion of the main body 6 is supported by the rear base plate 118 as a result of the front end portion of the shaft member 136 being positioned within the receiving depressed portion 140. The protruding piece 132 in the development housing 8 is positioned above the acting portion 158 of the elevating-lowering member 154 substantially away from the substantially horizontal part of the guide portion 128. Furthermore, when the developing device is thus mounted, the claw portion 58 of the engaging member 60 mounted on the supporting section 2 engages part of the front base plate 116, and the movement of the main body 6 of the developing device in the detaching direction of arrow 280 is hampered. It will be easily appreciated by comparing Figures 9-A and 9-B with Figures 10-A and 10-B that the main body 6 of the developing device can be detachably mounted on the main body of the image-forming machine when the elevating-lowering member 154 is at the elevated position and the lowered position, but that when the main body 6 of the developing device is mounted while the elevating-lowering member 154 is at the elevated position, the developing section 4 is held at the non-operating position and when the main body 6 of the developing device is mounted while the elevating-lowering member 154 is at the lowered position, the developing section 4 is held at the operating position. When the elevating-lowering member 154 is at the elevated position, the acting portion 158 of the elevating-lowering member 154 is on the same level as the substantially horizontal part of the guide portion 128 as shown in Figures 10-A and 10-B. Accordingly, when the main body 6 of the developing device is mounted in position, the developing section 4 is kept at the non-operating position by the action of the acting portion 158. Thus, to bring the developing section 4 to the operating position, the elevating-lowering member 154 should be held at the lowered position. On the other hand, when the elevating-lowering member 154 is at the lowered position, the acting portion 158 of the elevating-lowering member 154 is substantially on the same level as the lower end of the inclined other end portion 128a of the guide member 128. Hence, the protruding piece 132 of the development housing 8 is moved downwardly along the other end portion 128a of the guide portion 128 just prior to mounting the main body 6 in position. When by this movement, the main body 6 is mounted in position, the developing section 4 is held at the operating position. The developing device further has the following feature.

The developing section 4 is held at the non-operating position when the main body 6 of the developing device is to be mounted in position or more specifically the protruding piece 132 moves the substantially horizontal part of the guide portion 128 while the elevating-lowering member 154 is at the elevated or lowered position. Accordingly, the developer held on the magnetic brush mechanism 12 does not substantially act on the photosensitive material provided on the rotating drum 42, and damage of the photosensitive material during mounting of the developing device 6 can be reliably prevented.

In the illustrated embodiment, when the main body 6 of the developing device is detached from the main body of the image-forming machine, the holding member 264 is held at the engaging position in the manner to be described below. When the engagement of the engaging member 60 is cancelled and the main body 6 of the developing device is moved in the detaching direction, the holding member 264 is moved in the direction of arrow 148 relative to the development housing 8 by the action of the biasing spring 278. When the main body 6 of the developing device is moved slightly in the direction of arrow 260, the hampering surface 270a of the holding member 264 and the engaging surface 276 of the supporting section 2 come into engagement with each other because the developing section 4 is at the non-operating position (as shown in Figures 9-A and 10-B), (when the elevating-lowering member 154 is at the elevated position, the developing section 4 is kept at the non-operating position, and as shown in Figures 10-A and 10-B, when the elevating-lowering member 154 is at the lowered position, the developing section 4 is brought from the operating position to the non-operating position incident to the movement of the main body 6 of the developing device in the direction of arrow 260). Then, the holding member 264 abuts against the hampering member 282 provided in the development housing 8 and is thus held at the engaging position as shown in Figure 9-A or 10-A. Accordingly, even when the main body 6 of the developing device is detached from the main body of the image-forming machine, the holding member 264 is held at the engaging position and the developing section 4 continues to be held at the non-operating position. When the main body 6 of the developing device is further moved, the pair of supporting pins 120 get out of the receiving depressed portions 52 of the supporting section 2. In the illustrated embodiment, after one connecting terminal 56 mounted on the supporting section gets out of the other connecting terminal 119 mounted on the front base plate 116, the supporting pins 120 come out of the receiving depressed portions 52. This ensures disconnecting of the grounding of the electric motor 122 after the power supply for the main body 6 of the developing device is turned off. In this regard, when the main body 6 of the developing device is to be mounted, the connecting terminals 56 and 116 are connected to each other after the supporting pins 120 have been received in the depressions 52. Hence, by moving the supporting section 2 in the axial direction of the supporting pins 120, the two connecting terminals 56 and 116 are reliably connected to each other. When thereafter the main body 6 of the developing device is further moved in the direction of arrow 260, the main body 6 of the developing device is detached exactly from the main body of the image-forming machine.

Toner cartridge and related elements

Now, with reference to Figures 11 and 12 in conjunction with Figure 2, the toner cartridge and related elements will be described.

Mainly with reference to Figure 11, the illustrated toner cartridge 88 has a square-columnar main body 288. The main body 288 has an upper wall 290 having a toner supply opening 292 (Figures 14-A to 14-C) defined therein. After filling with toner, the toner supply opening 292 is closed by a closure 294. The lower end portion of the main body 288 is funnel-shaped and a toner discharge opening 296 (Figures 14-A to 14-C) is defined at its lower end. In the illustrated embodiment, a rectangular flange 298 is integrally provided at the lower end (the opening part of the toner discharge opening 296) of the main body 288. By applying a flexible sheet material 300 to the under surface of the flange 298, the toner discharge opening 296 of the main body 288 is substantially sealed up. To make detachment of the sheet material 300 easy, its one end portion is bent upwardly and bonded to the upper surface of the flange 298. Accordingly, the sheet material 300 can be easily stripped from the flange 298 by removing its one end portion bonded to the upper surface of the flange 298 and pulling it in the direction shown by an arrow 302.

The toner cartridge 88 further includes a cover member 304 for closing the toner discharge opening 296 at the time of detaching the main body 288 of the toner cartridge from the main body 6 of the developing device. The illustrated cover member 304 is nearly rectangular corresponding to the shape of the flange 298 and recessed portions 306 for receiving the two side end portions of the flange 298 are defined at both side ends of the cover member 304. Hence, the toner discharge opening 296 of the main body 288 can be closed by positioning the two side end portions of the flange 298 in the recessed portions 306 of the cover member 304 and moving the cover member 304 relatively in

the direction shown by an arrow 308 (Figure 14-B) as shown in Figure 14-C. As shown in Figures 11 and 14-C, a stop piece 310 for reliably hampering the movement of the cover member 304 in the direction of arrow 308 when the cover member 304 has been mounted in position on the flange 298 is preferably provided in the cover member 304.

In the illustrated embodiment, the toner cartridge is constructed such that the cover member 304 cannot be substantially moved in the detaching direction when it has been mounted on the flange 298 of the main body 288 of the toner cartridge. Specifically, as shown in Figures 11 and 14-C, detaching movement hampering means 312 is provided in the flange 298 and the cover member 304. The illustrated detaching movement hampering member 312 is comprised of a combination of a hole 314 (constituting a depressed portion) formed in the flange 298 and an engaging projecting portion 316 formed in the cover member 304. The engaging projecting portion 316 is inclined downwardly in the mounting direction of arrow 308 at its forward part in the mounting direction, but substantially projects vertically at its rear end in the mounting direction. Hence, when the cover member 304 is moved in the direction of arrow 308, the hole 314 and the engaging projecting portion 316 are engaged with each other by the elastic deformation of the flange 298 and the engaging projecting portion 316. After the hole 314 and the engaging projecting portion 316 have come into engagement, it is substantially impossible to move the engaging projecting portion 316 and therefore, the cover member 304, in a direction opposite to the direction mentioned above. If desired, it is possible to provide the engaging protruding portion in the flange 298 and the receiving depressed portion in the cover member 304 contrary to the above embodiment.

In the illustrated embodiment, the cover member 304 is constructed such that when it is not used, it is detachably mounted on one side wall 318 (the rear side wall as viewed in the mounting direction of the cartridge main body 288 shown by an arrow 320 in Figure 14-A) of the main body 288 of the toner cartridge. A pair of L-shaped supporting protrusions 322 spaced from each other are provided in the side wall 318 of the main body 288. Each of the supporting protrusions 322 extends vertically and has a projecting portion adapted to be positioned in the recessed portion 306 of the cover member 304. A stop piece 324 is provided in the lower end portion of the side wall 318. Hence, as shown in Figures 11 and 14-A, the cover member 304 is detachably mounted on the side wall 318 of the main body 288 by positioning the projecting portions of the supporting protrusions 322 in the recessed portion 306 of the cover member 304 and moving the cover member 304 downwardly. Upon mounting, the lower edge of the cover member 304 in Figure 14-A abuts against the stop piece 324 and is held in the state shown in Figure 14-A. In this mounted state, the upper end portion of the cover member 304 projects slightly upwardly from the upper wall 290 of the main body 288 of the toner cartridge. By holding the projecting upper end portion and moving it upwardly, the cover member 304 can be easily detached from the side wall 318. It will be readily appreciated that the cover member 304 may be adapted to be mounted on the flange 298 of the main body 288 instead of the side wall 318 and, in this arrangement, it is necessary to store the cover member 304 when the cartridge 88 is in use. (Furthermore, in this arrangement, to prevent substantial engagement between the hole 314 of the flange 298 and the engaging projecting portion 316 of the cover member 304, it is necessary to cover the hole 314 substantially by applying the sheet material 300 to at least the under surface of the flange 298).

Mainly with reference to Figures 2 and 12, the cartridge loading portion 82 of the main body 6 of the developing device into which the cartridge main body 288 is loaded detachably has four side walls and is nearly cylindrical, and a nearly rectangular flange 326 is provided at its upper end. A seal member 328, such as a sponge, capable of being elastically deformed is bonded to the inner circumferential part of the flange 326. A guide cover 332 is attached to the outer circumferential part of the flange 326 by means of securing screws 330. The guide cover 332 defines a pair of guide grooves 334 extending in the loading direction of the cartridge main body 288 in cooperation with the flange 326 at both side portions. At nearly the central portion of the guide cover 332 is formed a nearly semicircular opening 336 opened at one end (on the loading side of the main body 288). In order to permit easy loading of the cartridge main body 288, it is preferred to enlarge the openings of the guide grooves 334 by upwardly inclining one end portion of the guide cover 332 at both its side portions in a direction opposite to the loading direction of the cartridge main body 288 shown by arrow 320. A rotating shaft 340 is rotatably mounted on one side wall 338 (the side wall located at right bottom in Figure 2) of the cartridge loading portion 82. One end portion of the rotating shaft 340 projects outwardly through the side wall 338, and this projecting end portion is drivingly connected to an output shaft 342 of the electric motor 122. In the illustrated embodiment, a receiving depressed portion 344 is provided in one end portion of the rotating shaft 340 and an engaging pin 346 is provided in the output shaft 342. By inserting the engaging pin 346 into the depressed portion 344, the rotating shaft 340 is drivingly connected to the

output shaft 342. The other end portion of the rotating shaft 340 projects inwardly through the side wall 338 and the helical member 98 of the toner transfer means 34 is connected to this inwardly projecting end portion of the rotating shaft 340 (see Figures 13-A and 13-B). In relation to the rotating shaft 340, discharge facilitating means 348 is provided in order to increase the dischargeability of the toner in the cartridge main body 288. With reference to Figure 13-A also, the illustrated discharge facilitating means 348 is equipped with a supporting shaft 350 (which extends substantially vertically with respect to the rotating shaft 340) supported rotatably between the facing end walls of the cartridge loading portion 82. An actuating piece 352 is attached to an intermediate part of the supporting shaft 350 by means of a securing screw 354, and an oscillating member 356 is attached to its one end portion located within the toner discharge chamber 86. The oscillating member 356 projects outwardly through an opening 357 formed in the side wall 338 and a projecting portion 356a extending upwardly of the rotating shaft 340 is provided at the free end portion of the oscillating member 356. On the other hand, an actuating protrusion extending radially outwardly is provided on the peripheral surface of the rotating shaft 340, and this actuating protrusion 358 is adapted to act on the projecting portion 356a of the oscillating member 356. In the illustrated embodiment, a biasing spring 360 is attached to the oscillating member 356. One end portion of the biasing spring 360 is engaged with the oscillating member 356 and its other end portion is engaged with part of the cartridge loading portion 82. The biasing spring 360 biases the oscillating member 356 in the direction shown by an arrow 362 (Figure 13-A), whereby the oscillating member 356 is usually held at an angular position shown in Figure 13-A at which the front end portion of the actuating piece 352 abuts at the under surface of the flange 298 of the cartridge main body 288. Accordingly, when the electric motor 122 is rotated in a predetermined direction, the helical member 98 is similarly rotated via the rotating shaft 340, and the toner discharged into the toner discharge chamber 86 is transferred in the direction of arrow 96 (Figure 2) in the toner transfer chamber 32 (Figure 1) by the action of the helical member 98. Furthermore, when the rotating shaft 340 thus rotates, the actuating protrusion 358 provided in the rotating shaft 340 acts on the projecting portion 356a of the oscillating member 356 to oscillate the oscillating member 356 in the directions shown by arrows 362 and 364. Specifically, when with the rotation of the rotating shaft 340 in the direction of arrow 366 (Figure 2), the actuating protrusion 358 acts on the projecting portion 356a and elevates it, the oscillating member 356 is pivoted in the direction of arrow 364 against the biasing force of the biasing spring 360 (Figure 13-B). When the rotating shaft 340 further rotates and the actuating protrusion 358 comes out of the projecting portion 356a, the oscillating member 356 is pivoted in the direction of arrow 362 by the biasing action of the biasing spring 360, and the front end portion of the actuating piece 352 provided in the supporting shaft 350 collides with the flange 298 of the main body 288 (Figure 13-A). The collision of the actuating piece 352 results in an impact on the cartridge main body 288, whereby the blocking of the toner in the carridge main body 288 is eliminated and the toner is precisely released. Furthermore, the toner remaining on the inner surface of the main body 288 is also released. Thus, the discharge of the toner within the cartridge main body 288 is facilitated, and the toner is reliably discharged.

The developing device is also constructed such that unless the cover member 304 is mounted on the main body 288 of the cartridge, it is substantially impossible for the cartridge to be detached from the cartridge loading portion 82 of the main body 6 of the developing device. Again, with reference to Figures 2 and 12, a pair of supporting protrusions 368 extending downwardly are provided in the under surface of the flange 326 provided in the cartridge loading portion 82 in the illustrated embodiment. An engaging member 370 is mounted vertically movably between the pair of supporting protrusions 368. The engaging member 370 has a main body portion 372 mounted movably on the supporting protrusions 368 and a pair of engaging claw portions 374 provided respectively in the opposite ends of the main body portion 372. A biasing spring member 378 is interposed between an engaging member 376 attached to the lower end of each supporting protrusion 368 and the main body portion 372. The biasing spring member 378 resiliantly biases the engaging member 370 upwardly. If desired, instead of the above arrangement, it is also possible to provide the engaging member 370 integrally in the flange 326 and form a slit in the joining part between the flange 326 and the engaging member 370, and thus permit the pair of engaging claw portions 374 to move vertically by the elastic deformation of the main body portion 372 of the engaging member 370. On the other hand, a pair of notches 380 corresponding to the pair of engaging claw portions 374 of the engaging member 370 are provided in the two side end portions of the flange 298 in the cartridge main body 288. The pair of notches 380 extend inwardly from both side ends of the flange 289 and define receiving portions for receiving the engaging claw portions 374. As shown in Figure 2, notches 382 through which the engaging claw portions 374 of

the engaging member 370 can pass are formed in the flange 326 of the cartridge loading portion 82.

Now, with reference to Figures 14-A to 14-C, the operations of loading and detaching the cartridge main body 288 will be described.

In loading the main body 288 on the cartridge loading portion 82, both side end portions of the flange 298 are positioned in the pair of guide grooves 334 defined in the cartridge loading portion 82 and moved in the loading direction shown by arrow 320 (Figure 14-A). As a result, the two side end portions of the flange 298 are guided by the pair of guide grooves 334 and the main body 288 is positioned at the loaded position shown in Figure 14-A (by the abutting of the left-hand end in Figure 14-A of the flange 298 against the end wall 332a of the guide cover 332, the movement of the main body 288 beyond the loaded position is prevented). As a result, as shown in Figure 14-A, the pair of engaging claw portions 374 of the engaging member 370 pass through the notches 382 formed in the flange 326 and project into the notches 380 formed in the flange 298 of the cartridge main body 288, and are reliably engaged with part of the flange 298. As shown in Figure 14-A, the engaging claw portions 374 are substantially vertical at the front end and inclined downwardly toward their rear end when viewed in the loading direction of arrow 320. Hence, when the engaging claw portions 374 come into engagement with part of the flange 298, the movement of the cartridge main body 288 in the detaching direction of arrow 384 (Figure 14-B) is prevented, and unless the cover member 304 is mounted, the cartridge main body 288 cannot be detached.

Then, part of the sheet material 300 bonded to the flange 298 in the cartridge main body 288 is peeled and pulled to detach it completely from the flange 298. As a result, the toner discharge opening 298 of the cartridge main body 288 is exposed, and the toner in the cartridge main body 288 is discharged into the toner discharge chamber 86 through the toner discharge opening 296.

On the other hand, to detach the cartridge main body 288 from the cartridge loading portion 82, the cover member 304 is detached from the side wall 318 (Figure 11) of the cartridge main body 288 and is inserted between the flange 326 of the cartridge loading portion 82 and the flange 298 of the main body 288 and moved in the direction of arrow 308 as far as the position shown in Figure 14-B. (The movement of the cover member 304 beyond this position can be prevented by the abutting of the stop piece 310 provided in the cover member 304 against the right end of the flange 298 in Figure 14-B). Since the engaging claw portions 374 are inclined upwardly in the loading direction shown by arrow 308, the insertion of the cover member 304 is permitted. With the movement of the cover member 304 in the loading direction, the engaging member 370 is moved downwardly against the biasing force of the biasing spring 378. When the cover member 304 covers the under surface of the flange 298, the pair of engaging claw portions 374 is moved from the notches 380 to permit movement of the cartridge main body 288 in the detaching direction shown by arrow 384. When the cover member 304 is so mounted, the toner discharge opening 296 of the cartridge main body 288 is closed by the cover member 304, and its engaging projecting portion 316 is positioned in the hole 314 formed in the flange 298. Thus, the movement of the cover member 304 in the detaching direction with respect to the cartridge main body 288 can be prevented.

Thereafter, the cartridge main body 288 is moved in the detaching direction of arrow 384 together with the cover member 304. As a result, as shown in Figure 14-C, the cartridge main body 288 can be detached while its toner discharge opening 296 is covered by the cover member 304. Even when the toner is present in some amount within the cartridge main body 288, it does not scatter outside.

Modified embodiments

While the invention has been described with regard to one embodiment of the developing device constructed in accordance with this invention, it should be understood that the invention is not limited to this specific embodiment, and various changes and modifications are possible without departing from the scope of the invention as described and claimed herein.

For example, in the illustrated embodiment, the mechanisms relating to the cover member 304 are described with regard to an embodiment in which the cartridge main body 288 is loaded into one end portion of the developing section 4 of the developing device 6. This is not limitative, however. They can be equally applied to an embodiment in which the cartridge main body is loaded detachably in the toner holding chamber of the developing device.

Furthermore, in the illustrated embodiment, one developing device is detachably mounted around the rotating drum 42. If desired, for monocolor copying of a multiplicity of colors, two or more developing devices may be detachably mounted around the rotating drum 42, as described, for example, in the specification and drawings of Japanese Patent Application No. 235929/1986.

Claims

1. A developing device for developing an image in an image forming machine, said developing device comprising:

a main body (6) including an applicator means (12) for applying a developer to a latent electrostatic image, said main body (6) having a toner inlet opening;

a toner cartridge (88) adapted to contain toner and having a toner discharge opening (296);

said toner cartridge (88) being selectively detachably mountable on said main body (6) with said toner discharge (296) and inlet openings aligned such that toner may be supplied from said cartridge into said main body; and

means (368,374,380) for preventing detachment of the cartridge (88) from the main body (6);

characterised by:

a cover member (304) which is not part of the detachment preventing means and which is selectively removably mountable on the cartridge (88) to block the toner discharge opening (296) and to release said detachment preventing means to enable the cartridge to be detached from said main body (6).

2. A developing device according to claim 1, wherein said cartridge detachment preventing means comprises a receiving portion (380) defined in said cartridge, and an engaging member (372) detachably receivable in said receiving portion (380) and provided on said main body (6) such that, when said cartridge (88) is mounted on said main body (6), said engaging member (372) is received in said receiving portion (380) of said cartridge to thereby render substantially impossible the detachment of the cartridge from the main body, unless the cover member (304) is mounted on the cartridge to remove the engaging member (372) from the receiving portion of the cartridge and thereby permit detachment of the cartridge from the main body.

3. A developing device according to claim 2, wherein the engaging member (372) is vertically movably mounted on the main body (6) of the developing device; a biasing means (378) for biasing the engaging member (372) upwardly is provided; the upper end of the engaging member (372) is inclined upwardly in the mounting direction of the cover member (304); when the main body of the cartridge is detachably loaded into the main body of the developing device, the engaging member (372) is received in the receiving portion (380) of the main body of the cartridge by the action of the biasing means (378); and when the cover member (304) is mounted on the main body of the cartridge, the engaging member (372) is detached from the receiving portion of the main body of the cartridge as a result of the movement of the cover member in the mounting direction against the biasing action of the biasing means.

4. A developing device as claimed in claim 1, 2 or 3, wherein a detaching movement hampering means is provided on the main body of the cartridge and the cover member (304) which prevents movement of the cover member (304) from the cartridge in the detaching direction after the cover member (304) has been mounted on the main body of the cartridge.

5. A developing device as claimed in claim 4, wherein the detaching movement hampering means is comprised of a combination of a receiving recessed portion (314) provided in one of the main body of the cartridge and the cover member and an engaging projecting portion (316) provided in the other of the main body of the cartridge and the cover member and adapted to be received in the receiving depressed portion (314).

6. A developing device as claimed in claim 4 or 5, wherein the cover member (304) is adapted to be detachably mounted on the side wall of the main body of the cartridge when it is not in use.

7. A developing device as claimed in any of claims 1 to 6, wherein the toner discharge opening (296) of the main body of the cartridge is sealed by a flexible sheet material (300); and by loading the main body of the cartridge on the main body of the developing device and thereafter peeling the flexible sheet material (300), the toner discharge opening is exposed, and the toner in the cartridge is supplied.

Patentansprüche

1. Ein Entwicklungsgerät zur Entwicklung eines Bildes in einer Bildformierungsmaschine, wobei das besagte Entwicklungsgerät umfaßt:

einen Hauptbestandteil (6), der eine Auftragungsvorrichtung (12) für die Auftragung eines Entwicklers auf ein latentes elektrostatisches Bild einschließt, wobei der besagte Hauptbestandteil (6) eine Tonereinlaßöffnung besitzt;

* C L M S *

eine Tonerkartusche (88), die angepaßt ist, Toner zu enthalten und die eine Tonerausstoßöffnung (296) besitzt;

wobei die besagte Tonerkartusche (88) selektiv loslösbar an dem besagten Hauptbestandteil (6) montierbar ist und wobei die besagten Tonerausstoß- (296) und Einlaßöffnungen so ausgerichtet sind, das der Toner von der besagten Kartusche dem besagten Hauptbestandteil zugeführt werden kann; und

Vorrichtungen (368, 374, 380), um die Loslösung der Kartusche (88) von dem Hauptbestandteil (6) zu verhindern;

gekennzeichnet durch:

ein Abdeckungsteil (304), welches kein Teil der Vorrichtung zur Verhinderung der Loslösung ist und welches selektiv entfernbar an der Kartusche (88) montierbar ist, um die Tonerausstoßöffnung (296) zu blockieren und um die besagte Vorrichtung zu der Verhinderung der Loslösung frei zu machen, so daß es möglich ist, die Kartusche von dem besagten Hauptbestandteil (6) zu entfernen.

2. Ein Entwicklungsgerät nach Anspruch 1, in dem die besagte Vorrichtung zur Verhinderung der Loslösung der Kartusche ein Aufnahmeteil (380), das in der besagten Kartusche definiert ist, und ein Bindeglied (372) umfaßt, das loslösbar in dem besagten Aufnahmeteil (380) aufnehmbar ist und das an dem besagten Hauptbestandteil (6) zur Verfügung gestellt worden ist, so daß das besagte Bindeglied (372), wenn die besagte Kartusche (88) an dem besagten Hauptbestandteil (6) montiert ist, in dem besagten Aufnahmeteil (380) der besagten Kartusche aufgenommen wird, um dadurch die Loslösung der Kartusche von dem Hauptbestandteil im wesentlichen unmöglich zu machen, außer wenn das Abdeckungsteil (304) an der Kartusche montiert ist, um das Bindeglied (372) von dem Aufnahmeteil der Kartusche zu entfernen und um dadurch die Loslösung der Kartusche von dem Hauptbestandteil zu erlauben.

3. Ein Entwicklungsgerät nach Anspruch 2, in dem das Bindeglied (372) an dem Hauptbestandteil (6) des Entwicklungsgerätes montiert ist, so daß es senkrecht bewegbar ist; in dem eine Ausrichtungsvorrichtung (378) zur Verfügung gestellt worden ist, um das Bindeglied (372) nach oben auszurichten; in dem das obere Ende des Bindeglieds (372) in der Montagerichtung des Abdeckungsteiles (304) nach oben geneigt ist; in dem das Bindeglied (372), wenn der Hauptbestandteil der Kartusche loslösbar in dem Hauptbestandteil des Entwicklungsgerätes geladen ist, in das Aufnahmeteil (380) des Hauptbestandteiles der Kartusche durch die Aktion der Ausrichtungsvorrichtung (378) aufgenommen wird; und wenn das Abdeckungsteil (304) an dem Hauptbestandteil der Kartusche montiert ist, ist das Bindeglied (372) von dem Aufnahmeteil des Hauptbestandteiles der Kartusche losgelöst als ein Ergebnis der Bewegung des Abdeckungsteiles in der Montagerichtung gegen die Ausrichteaktion der Ausrichtungsvorrichtung.

4. Ein Entwicklungsgerät nach Anspruch 1,2 oder 3, in dem eine Loslösungshinderungsvorrichtung an dem Hauptbestandteil der Kartusche und an dem Abdeckungsteil (304) zur Verfügung gestellt worden ist, die die Bewegung des Abdeckungsteiles (304) von der Kartusche in der Loslösungsrichtung verhindert, nachdem das Abdeckungsteil (304) an dem Hauptbestandteil der Kartusche montiert worden ist.

5. Ein Entwicklungsgerät nach Anspruch 4, in dem die Loslösungshinderungsvorrichtung eine Kombination eines Aufnahmevertiefungsteiles (314), das entweder in dem Hauptbestandteil der Kartusche oder in dem Abdeckungsteil zur Verfügung gestellt worden ist, und eines herausragenden Bindungsteiles (316) umfaßt, das dementsprechend umgekehrterweise entweder in dem Hauptbestandteil der Kartusche oder dem Abdeckungsteil zur Verfügung gestellt worden ist und so angepaßt ist, daß es in das Aufnahmevertiefungsteil (314) aufgenommen werden kann.

6. Ein Entwicklungsgerät nach Anspruch 4 oder 5, in dem das Abdeckungsteil (304) so angepaßt ist, daß es loslösbar an der Seitenwand des Hauptbestandteiles der Kartusche montiert werden kann, wenn es nicht in Gebrauch ist.

7. Ein Entwicklungsgerät nach einem der vorhergehenden Ansprüche 1 bis 6, in dem die Tonerausstoßöffnung (296) des Hauptbestandteiles der Kartusche durch ein flexibles Folienmaterial (300) versiegelt ist; und in dem die Tonerausstoßöffnung durch das Laden des Hauptbestandteiles der Kartusche an den Hauptbestandteil des Entwicklungsgerätes und durch die darauffolgende Ablösung des flexiblen Folienmaterials (300) freigelegt wird und der Toner in der Kartusche abgegeben wird.

Revendications

1. Dispositif de développement pour développer une image dans un appareil imageur, le dit

* C L M S *

dispositif de développement comprenant:

un corps principal (6) comportant un moyen applicateur (12) pour appliquer un révélateur à une image électrostatique latente, le dit corps principal (6) ayant une ouverture d'admission du toner;

une cartouche de toner (88) adaptée pour contenir le toner et ayant une ouverture de décharge du toner (296);

la dite cartouche de toner (88) pouvant être sélectivement montée de façon amovible sur le dit corps principal (6) les dites ouvertures de décharge (296) et d'admission de toner étant alignées de sorte que le toner puisse être fourni de la dite cartouche dans le dit corps principal; et

des moyens (368,374,380) visant à éviter le décollement de la cartouche (88) par rapport au corps principal (6);

caractérisé par:

un élément couvercle (304) qui ne fait pas partie des moyens de prévention du décollement et qui peut être sélectivement monté de façon amovible sur la cartouche (88) pour bloquer l'ouverture de décharge de toner (296) et pour dégager les dits moyens de prévention du décollement de sorte à permettre le décollement de la cartouche par rapport au dit corps principal (6).

2. Dispositif de développement selon la revendication 1, où le dit moyen de prévention du décollement de cartouche comporte une partie de réception (380) délimitée dans la dite cartouche, et un élément d'engrènement (372) susceptible d'être reçu de façon amovible dans la dite portion de réception (380) et monté sur le dit corps principal (6) de sorte que, lorsque la dite cartouche (88) est montée sur le dit corps principal (6), le dit élément d'engrènement (372) est reçu dans la dite portion de réception (380) de la dite cartouche afin de rendre ainsi sensiblement impossible le décollement de la cartouche par rapport au corps principal, à moins que l'élément couvercle (304) ne soit monté sut la cartouche pour retirer l'élément d'engrènement (372) de la portion de réception de la cartouche et pour permettre par là même le décollement de la cartouche par rapport au corps principal.

3. Dispositif de développement selon la revendication 2, où l'élément d'engrènement (372) est verticalement monté de façon amovible sur le corps principal (6) du dispositif de développement; un moyen redresseur (378) est fourni pour dévier l'élément d'engrènement (372) vers le haut; l'extrémité supérieure de l'élément d'engrènement (372) est inclinée vers le haut dans la direction de montage de l'élément couvercle (304); lorsque le corps principal de la cartouche est chargé de façon amovible dans le corps principal du dispositif de développement, l'élément d'engrènement (372) est reçu dans la portion de réception (380) du corps principal de la cartouche sous l'action du moyen redresseur (378); et lorsque l'élément couvercle (304) est monté sur le corps principal de la cartouche, l'élément d'engrènement (372) est détaché de la portion de réception du corps principal de la cartouche du fait du mouvement de l'élément couvercle dans la direction de montage contre l'effet de déviation du moyen redresseur.

4. Dispositif de développement selon la revendication 1, 2 ou 3, où un moyen entraveur du mouvement de décollement est fourni sur le corps principal de la cartouche et l'élément couvercle (304) qui empêche le mouvement de l'élément couvercle (304) par rapport à la cartouche dans la direction de décollement après que l'élément couvercle (304) ait été monté sur le corps principal de la cartouche.

5. Dispositif de développement selon la revendication 4, où le moyen entraveur du mouvement de décollement comprend une combinaison d'une portion renfoncée de réception (314) prévue dans l'un de corps principal de la cartouche et d'élément couvercle et d'une portion saillante d'engrènement (316) prévue dans l'autre de corps principal de la cartouche et de l'élément couvercle et adaptée pour être reçue dans la portion renfoncée de réception (314).

6. Dispositif de développement selon la revendication 4 ou 5, où l'élément couvercle (304) est adapté pour être monté de façon amovible sur la paroi latérale du corps principal de la cartouche lorsqu'il n'est pas utilisé.

7. Dispositif de développement selon l'une quelconque des revendications 1 à 6, où l'ouverture de décharge de toner (296) du corps principal de la cartouche est scellée par une feuille de matériau souple (300); et par le chargement du corps principal de la cartouche sur le corps principal du dispositif de développement et par le décollement ultérieur de la feuille de matériau souple (300), l'ouverture de décharge de toner est exposée et le toner dans la cartouche est introduit.

* C L M S *