

CLAIMS

[Claim 1]

5 A client-side communication control device connectable to a gateway, which is provided between a client device and a network communication grid, and the client device, the client-side communication control device comprising:

an authentication unit; and

10 a control unit that is configured to request the authentication unit to perform at least a mutual authentication process among the mutual authentication process and an encryption/decryption process, the mutual authentication process performing mutual authentication in communication with a server-side communication control device using a client secret key and a client certificate, the client secret key and the client certificate being issued by a private authentication authority, transmitted to the client-side communication control device by the private authentication authority, and stored in the authentication unit, the private authentication authority transmitting to the server-side communication control device a server secret key and a server certificate to be used for a server device, the server device being a communication destination of the client device, the private authentication authority being separated from the server device, the server-side communication control device being connected to the server device and the network communication grid, the encryption/decryption process encrypting information, that is transmitted to the server device by the client device, using a common key determined for communication between the client-side communication control device and the server-side communication control device, the encryption/decryption process decrypting information, that is transmitted to the client device by the server device, using the common key,

25 wherein

the client-side communication control device communicates by wire with the client device in plaintext, and

30 the client-side communication control device communicates by wire with the gateway,

wherein the control unit requests the authentication unit to perform a firmware verification process of performing verification of whether or not details of information

about firmware of the client device transmitted to the client device are correct using a key issued by the private authentication authority.

[Claim 2]

- 5 The client-side communication control device according to claim 1, wherein the authentication unit determines whether or not to permit communication with the client device for a communication device transmitting information to the client device on the basis of a transmission destination list indicating information about communication equipment for which communication with the client device is permitted.

10