What is claimed is:

1. A lubricant composition comprising:

(a) an oil of lubricating viscosity;

(b) 0.1 to 2 percent by weight of an ashless Mannich dispersant prepared by reacting a hydrocarbyl-substituted phenol, formaldehyde and dimethylamine;

(c) 0.1 to 2 percent by weight of an ashless succinimide dispersant; and

(d) a metal-containing detergent comprising an overbased calcium phenate detergent, in an amount to deliver 0.01 to 0.12 percent sulfated ash to the lubricant composition,

wherein the succinimide dispersant provides at least 40 parts per million by weight of nitrogen atoms to the lubricant composition.

2. The lubricant composition of claim 1 wherein the Mannich dispersant comprises the reaction product of a polyisobutene-substituted phenol, formaldehyde ~~or a reactive equivalent of formaldehyde,~~ and dimethylamine.

3. The lubricant composition of claim 1 or claim 2 wherein the succinimide dispersant is a condensation product of hydrocarbyl-substituted succinic anhydride or a reactive equivalent thereof, with a polyethylene polyamine.

4. The lubricant composition of any one of claims 1 through 3 wherein the succinimide dispersant has a total base number of at least 70 on an oil-free basis.

5. The lubricant composition of any one of claims 1 through 4 wherein the succinimide dispersant has a nitrogen content of at least 3 percent by weight on an oil-free basis.

6. The lubricant composition of any one of claims 1 through 5 wherein the weight ratio of the Mannich dispersant to the succinimide dispersant is 80:20 to 20:80.

7. The lubricant composition of any one of claims 1 through 6 wherein the weight ratio of the Mannich dispersant to the succinimide dispersant is 70:30 to 30:70.~~the metal-containing detergent is an overbased sulfonate, phenate, salicylate, or salixarate detergent.~~

~~8. The lubricant composition of any one of claims 1 through 7 wherein the metal containing detergent comprises an overbased calcium phenate detergent~~.

~~9~~8. The lubricant composition of any one of claims 1 through ~~8~~7 wherein the metal containing detergent contributes at least 0.1 total base number to the lubricant composition.

~~10~~9. The lubricant composition of any one of claims 1 through ~~9~~8 wherein the metal containing detergent is present in an amount of 0.1 to 3 weight percent. ~~an amount of phosphorus contained therein is 0 to 0.05 weight percent.~~

~~11. The lubricant composition of claim 10 wherein the amount of phosphorus is provided by one or more zinc dialkyldithiophosphates~~.

1~~2~~0. A method of lubricating an internal combustion engine, comprising supplying thereto the lubricant composition of any one of claims 1 through ~~11~~9.

1~~3~~1. The method of claim 1~~2~~0 wherein the internal combustion engine is a two-stroke cycle engine.

1~~4~~2. The method of claim 1~~2~~0 or claim 1~~3~~1 wherein the internal combustion engine has a power output of less than 150 kW (201 horsepower).

1~~5~~3. The method of any one of claims 1~~2~~0 through 1~~4~~2 wherein the lubricant composition is provided as a mixture with a liquid fuel.