

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
31 October 2002 (31.10.2002)

PCT

(10) International Publication Number
WO 02/086036 A1

(51) International Patent Classification⁷: **C10M 157/00**,
157/04 // (C10M 157/00, 143:10, 145:14, 145:16) (C10M
157/04, 145:14, 145:16, 149:04, 149:06, 149:10), C10N
20:04, 40:08

(74) Agents: **SHOLD, David, M.** et al.; The Lubrizol Corpo-
ration, 29400 Lakeland Boulevard, Wickliffe, OH 44092
(US).

(21) International Application Number: PCT/US02/10906

(22) International Filing Date: 4 April 2002 (04.04.2002)

(25) Filing Language: English

(26) Publication Language: English

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI,
SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU,
ZA, ZW.

(30) Priority Data:
60/285,377 20 April 2001 (20.04.2001) US

(84) Designated States (*regional*): European patent (AT, BE,
CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC,
NL, PT, SE, TR).

(71) Applicant (*for all designated States except US*): **THE LU-
BRIZOL CORPORATION** [US/US]; 29400 Lakeland
Boulevard, Wickliffe, OH 44092 (US).

Published:
— with international search report

(72) Inventor; and

(75) Inventor/Applicant (*for US only*): **GAPINSKI, Richard,
E.** [US/US]; 7316 Hopkins Road, Mentor, OH 44060 (US).

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: ALL-WEATHER TRACTOR HYDRAULIC FLUID USING A MIXTURE OF VISCOSITY MODIFIER TYPES TO MEET SHEAR-STABLE MULTIGRADE VISCOSITY REQUIREMENTS

(57) Abstract: A composition of the following components: an oil of lubricating viscosity; a polymethacrylate viscosity modifier; an ester of a maleic acid/styrene copolymer; and optionally, an additive package that imparts to the fluid the capacity to meet bench and dynamometer tests specified by an equipment manufacturer, is suitable for use as a functional fluid such as a tractor hydraulic fluid, under a wide variety of climatic conditions.



WO 02/086036 A1