



159159

- 1 -



G00002

DESCRIPTION

LIQUID CRYSTAL DISPLAY DEVICE, METHOD FOR DRIVING SAME, AND
PORTABLE TERMINAL

5

Technical Field

The present invention relates to a liquid crystal display device, a method for driving the same, and a portable terminal. In particular, the present invention
10 relates to an active matrix liquid crystal display device using a pre-charge system, a method for driving the same, and a portable terminal having such a liquid crystal display device at an output display section.

15 Background Art

Portable terminals such as portable telephones have become increasingly popular in recent years. Such portable terminals typically use a liquid crystal display device for an output display section. These portable terminals are
20 frequently used outdoors, and therefore, are required to ensure stable operation over a wide temperature range. The lower limit of the guaranteed operating temperature range is set to an extremely low level such as about -30° C.

At low temperature, a liquid crystal display device is
25 disadvantageous in that the frequency characteristics of the

liquid crystal dielectric constant are degraded, causing the contrast at low temperature to become low. In more detail, referring to Fig. 3 showing an equivalent circuit for a unit pixel, the resistance component R of the liquid crystal

5 material increases at low temperature, thus preventing the pixel electrode, with a liquid crystal capacitance C_{lc} , from being sufficiently charged within a predetermined period of time. Consequently, a desired signal voltage cannot be written to the pixel, causing the contrast to become low.

10 This problem of low contrast at low temperature is notable particularly in a liquid crystal display device operated at a low voltage to reduce power consumption, in which a lower voltage is applied to the liquid crystal capacitance C_{lc} . In order to overcome the problem described
15 above, a higher voltage may be applied to the liquid crystal capacitance C_{lc} ; however, this approach produces another problem in that the output circuit of the data driver for driving the data lines requires a high current capacity, thus consuming more power and occupying a larger circuit
20 area.

A selector drive system, employed in a color liquid crystal display device, is a well-known system that allows three color signals corresponding to three horizontally arranged colors to be time-sequentially sampled within one
25 horizontal period and then written to the data lines in the

display area, thus reducing the number of outputs of the data driver to one-third. In such a liquid crystal display device employing the selector drive system, three color signals are sequentially sampled within one horizontal
5 period, and therefore, a shorter period of time is allocated, in particular, for the third sampled color. This problem is more noticeable at low temperature for the reasons described above. Thus, a desired signal voltage cannot be written to the pixel of the third sampled color. As a result, the
10 contrast of the third sampled color becomes significantly low, causing a chromaticity shift (chromaticity deterioration).

In view of the above-described problem, it is an object of the present invention to provide a liquid crystal display
15 device that increases the contrast characteristics at low temperature while still suppressing power consumption and that reduces a chromaticity shift if the selector drive system is employed; a method for driving such a liquid crystal display device; and a portable terminal having such
20 a liquid crystal display device at an output display section.

Disclosure of Invention

In order to achieve the object described above, according to the present invention, a pre-charge signal
25 level is written to each data line in the display area

before the display signal is written to each data line, that is, the pre-charge signal level which is equivalent to the gray-scale level as obtained when no voltage is applied to the liquid crystal. The gray-scale level as obtained when
5 no voltage is applied to the liquid crystal is the white level for normally-white liquid crystal display devices or the black level for normally-black liquid crystal display devices.

In the liquid crystal display device, the resistance
10 component of the liquid crystal material increases at low temperature to degrade the frequency characteristics of the liquid crystal dielectric constant. This results in failure to write a desired signal voltage to the pixel electrode with a liquid crystal capacitance within a predetermined
15 period of time. To overcome the abovementioned problem, a liquid crystal display device according to the present invention writes the gray-scale level as obtained when no voltage is applied to the liquid crystal to the data lines, prior to writing display signals to the data lines, where
20 the gray-scale level functions as a pre-charge signal level. Thus, driving of the data lines can be started with the gray-scale signal level; in other words, a desired signal voltage can be written to the data lines within a shorter period of time. For the reason described above, even if the
25 frequency characteristics of the liquid crystal dielectric

constant are degraded at low temperature, a desired signal voltage can be written to the pixel electrode with a liquid crystal capacitance within a predetermined period of time, thereby increasing the contrast at low temperature.

5

Brief Description of the Drawings

Fig. 1 is a circuit diagram of an active matrix liquid crystal display device according to an embodiment of the present invention.

10

Fig. 2 is a timing chart illustrating the timing of writing a black signal to a G pixel when the B, G, and R signals are sampled in that order in a normally-white liquid crystal display device.

15

Fig. 3 is a circuit diagram showing an equivalent circuit for a unit pixel.

Fig. 4 is a block diagram illustrating a typical structure of a liquid crystal panel according to an embodiment of the present invention.

20

Fig. 5 is a schematic drawing illustrating the outline of a portable telephone according to the present invention.

Fig. 6 shows a typical appearance of an output display section.

Best Mode for Carrying Out the Invention

25

Embodiments according to the present invention will now

be described in detail with reference to the attached drawings. Fig. 1 is a circuit diagram of an active matrix liquid crystal display device according to an embodiment of the present invention. For convenience, the embodiment will
5 be described by way of an example in which a pixel array has four rows by six columns.

Referring to Fig. 1, gate lines 11-1 to 11-4 and data lines 12-1 to 12-6 are wired in a matrix. A pixel 13 is formed at each of the intersections of the gate lines and
10 data lines described above, all the pixels 13 together thus forming a display area 14. Each of the pixels 13 includes a pixel transistor TFT (thin film transistor) having its gate electrode connected to the corresponding gate line (one of the gate lines 11-1 to 11-4) and its source electrode (or
15 drain electrode) connected to the corresponding data line (one of the data lines 12-1 to 12-6); a liquid crystal cell LC whose pixel electrode is connected to the drain electrode (or source electrode) of the pixel transistor TFT; and a
20 storage capacitor Cs connected in parallel with the liquid crystal cell LC.

In the pixel structure described above, the counter electrodes of the liquid crystal cells LC are commonly connected among all pixels. A common voltage VCOM is applied to the counter electrodes of the liquid crystal
25 cells LC. For 1H (H represents a horizontal period) reverse

driving or 1F (F represents a period equivalent to one field) reverse driving described below, the display signals to be written to the data lines 12-1 to 12-6 are polarity-reversed with respect to this common voltage VCOM.

5 In the liquid crystal display device according to the embodiment, VCOM reverse driving is also employed in which the common voltage VCOM is polarity-reversed every 1H period or 1F period. When this VCOM reverse driving is used together with 1H reverse driving or 1F reverse driving, the
10 operating power voltage of the output circuit of the data driver described below can be half of that when VCOM reverse driving is not used, thus allowing the data driver to be operated at a lower voltage.

 The common voltage VCOM is supplied as an alternate
15 voltage with an amplitude substantially equal to that of the display signals used: 0 to 3.3 V, for example. When signals are written to the pixel electrodes of the liquid crystal cells LC through the pixel transistors TFT from the data lines 12-1 to 12-6, factors such as parasitic capacitance
20 cause a voltage drop at the pixel transistors TFT. For this reason, in practice, an alternate voltage with an amplitude shifted by the voltage drop is practically used for the common voltage VCOM. Along with this VCOM reverse driving, a voltage which has the same amplitude as the common voltage
25 VCOM and which is polarity-reversed in synchronization with

the common voltage VCOM is applied to the electrodes of the storage capacitors Cs adjacent to the counter electrodes via the Cs lines 15 (the adjacent lines to the counter electrodes).

5 A scan driver 16 serving as vertical driving means is disposed, for example, to the left of the display area 14. The scan driver 16 sequentially drives the gate lines 11-1 to 11-4 every one field period to select each row of pixels 13 at a time. A data driver 17 is disposed, for example,
10 above the display area 14. A selector switch 18 is disposed between the data driver 17 and the display area 14. A pre-charge switch 19 is disposed, for example, below the display area 14.

 The data driver 17 repeatedly outputs the display
15 signals for the three colors, that is, blue (B), green (G), and red (R), in a predetermined order such as B, G, and R. In this case, the display signals are output for each group of three columns of the pixel array in the display area 14. This repetition period is usually the 1H period. In short,
20 each of the B, G, and R signals is time-sequentially output within the 1H period. At this time, the polarities of these color signals are reversed every 1H with respect to the common voltage VCOM. In this manner, 1H reverse driving is performed wherein the polarity of the display signal to be
25 applied to each pixel 13 is reversed every 1H.

In a power-saving mode, the data driver 17 repeatedly outputs the B, G, and R color signals every one field period (1F). At this time, the polarities of these color signals are reversed every 1F with respect to the common voltage VCOM. Thus, 1F reverse driving is performed wherein the polarity of the display signal to be applied to each pixel 13 is reversed every 1F. With 1F reverse driving, polarity reversal of the color signals is required much less frequently than with 1H reverse driving, thereby suppressing power consumption of the output circuit of the data driver 17. This means 1F reverse driving is effective in reducing power consumption (that is, contributing to power saving).

As described above, the data driver 17 outputs display signals Sig1, Sig2, and so on. These display signals are each a time-sequence signal of B, G, and R color signal components, and are supplied to the selector switch 18, one for each group of two or more adjacent pixels (three pixels, for example) in the same row of the pixel array in the display area 14. The selector switch 18 enables the selector drive system, where the display signals for the pixels corresponding to the three colors horizontally arranged in the display area 14 are time-sequentially sampled into the data lines 12-1 to 12-6 within one horizontal period.

More specifically, the selector switch 18 has a group

of three analog switches SWsB-1, SWsG-1, and SWsR-1 for the display signal Sig1, a group of three analog switches SWsB-2, SWsG-2, and SWsR-2 for the display signal Sig2, and so on. The input terminals of the analog switches in each group are
5 connected to one common line. The output terminals of the analog switches are connected to the respective data lines 12-1 to 12-6 in the display area 14.

In the selector switch 18, the analog switches for the same color are turned ON/OFF in synchronization with the
10 corresponding external select pulse SEL-B, SEL-G, or SEL-R applied time-sequentially. More specifically, the analog switches SWsB-1 and SWsB-2 are turned ON/OFF in synchronization with the select pulse SEL-B for color B, the analog switches SWsG-1 and SWsG-2 are turned ON/OFF in
15 synchronization with the select pulse SEL-G for color G, and the analog switches SWsR-1 and SWsR-2 are turned ON/OFF in synchronization with the select pulse SEL-R for color R.

The selector drive system achieved with this selector switch 18 allows the display signals Sig1 and Sig2 for the
20 pixels arranged horizontally in each row to be time-sequentially sampled and supplied to the data lines 12-1 to 12-6 in the display area 14 within one horizontal period, and hence is advantages in that it allows the number of outputs from the data driver 17 to be reduced to one-third
25 of the number of data lines 12-1 to 12-6 in the display area

14.

The pre-charge switch 19 is used for the pre-charge system, where a pre-charge signal P_{sig} is written to the data lines 12-1 to 12-6 just before writing to the data lines 12-1 to 12-6 the display signals Sig1 and Sig2 sampled using the selector switch 18.

In more detail, the pre-charge switch 19 includes as many analog switches (SW_p-1 to SW_p-6) as the number of columns of the pixel array in the display area 14. One end of each of these analog switches SW_p-1 to SW_p-6 is connected to one common line serving as the input terminal of the pre-charge signal P_{sig}, whereas the other end of each of the same analog switches is connected to the corresponding data line, that is, one of the data lines 12-1 to 12-6 in the display area 14. The analog switches SW_p-1 to SW_p-6 are turned ON/OFF in synchronization with the pre-charge pulse PCG, which is applied externally prior to the first select pulse SEL-B.

Now, let us see what happens if pre-charging is not performed in a liquid crystal display device employing the analog point-at-a-time driving system. If the pre-charge signal P_{sig} is not written to the data lines 12-1 to 12-6 in such a liquid crystal panel before the display signals Sig1 and Sig2 are written, a large charge/discharge current resulting from signals being written to the data lines 12-1

to 12-6 during 1H reverse driving described above generates noise, such as vertical streaks, on the display screen. On the other hand, writing the pre-charge signal P_{sig} (typically gray or black level for a normally-white liquid crystal panel) to the data lines 12-1 to 12-6 suppresses a charge/discharge current caused by signal writing, thereby reducing noise.

Unfortunately, pre-charging of a signal similar to the pre-charge signal P_{sig} for improving the low temperature characteristics leads to an increase in power consumption. In order to suppress power consumption caused by this pre-charging, the liquid crystal display device according to the embodiment uses the pre-charge signal P_{sig} which is the gray-scale level as obtained when no voltage is applied to the liquid crystal, that is, the gray-scale level equivalent to the white level for a normally-white liquid crystal display device or the black level for a normally-black liquid crystal display device. More specifically, the common voltage V_{COM} is equivalent to the gray-scale level as obtained when no voltage is applied to the liquid crystal, i.e., the white-level for a normally-white liquid crystal display device, for example. The liquid crystal display device according to the embodiment, therefore, uses the common voltage V_{COM} for the pre-charge signal P_{sig} .

As described above, the active matrix liquid crystal

display device employing the pre-charge system may allocate the gray-scale level as obtained when no voltage is applied to the liquid crystal, such as the common voltage VCOM, for the pre-charge signal Psig; turn ON/OFF the pre-charge

5 switch 19 in synchronization with the pre-charge pulse PCG just before sampling, with the selector switch 18, the desired display signals Sig1, Sig2, and so on supplied from the data driver 17 to pre-charge the data lines 12-1 to 12-6 with the common voltage VCOM; and then sequentially turn
10 ON/OFF the selector switch 18 in synchronization with the select pulses SEL-B, SEL-G, and SEL-R to write the desired signal into the corresponding pixel 13 through the data lines 12-1 to 12-6. The advantages of these features will become apparent in the following description.

15 Fig. 2 illustrates the timing of writing the black signal to a G pixel when the B, G, and R signals are sampled in that order in a liquid crystal display device such as a normally-white liquid crystal display device. For VCOM reverse driving, the common voltage VCOM has a phase-
20 reversed relationship with the output signals Sig from the data driver 17.

Without pre-charging, the potential Sig-G of the data line for G before being written, as shown by the dotted lines in Fig. 2, drops from the original voltage level: that
25 is, it is adversely affected by this phase-reversed common

voltage VCOM. Referring now to Fig. 3 showing an equivalent circuit for a unit pixel, the potential V_p of the pixel electrode with the liquid crystal capacitance C_{lc} also drops, as shown by the dotted lines in Fig. 2. An increase in the resistance component R of the liquid crystal material at low temperature prevents a desired signal voltage from being sufficiently written to the pixel within a predetermined period of time, thus causing a low contrast.

In contrast, pre-charging the data lines of the pre-charge pulse PCG (active at the low level) with the gray-scale signal as obtained when no voltage is applied to the liquid crystal, i.e., the common voltage VCOM in the embodiment serving as the pre-charge signal P_{sig} , prior to writing the black signal, causes the potential $Sig-G$ of the data line for G to come to the middle level, as shown by the solid line in Fig. 2, thus causing the potential V_p of the pixel electrode with the liquid crystal capacitance C_{lc} to come to the middle level. Thereafter, the selector pulse SEL-G for G turns ON the selector switch $SWsG$, thus allowing the signal $Sig-G$ to rise from the middle level. Hence, despite an increase in the resistance component R of the liquid crystal material at low temperature, the pixel electrode with the liquid crystal capacitance C_{lc} can be charged sufficiently within a predetermined period of time and a desired signal voltage can be written to the pixel,

thus increasing the contrast even at low temperature.

Another disadvantage without pre-charging is that, as shown by the dotted lines in Fig. 2, the potential V_p of the pixel electrode with the liquid crystal capacitance C_{lc} cannot reach the desired signal level within a predetermined period of time. This disadvantage is noticeable, particularly with the signal for R, which is sampled last during B, G, and R sampling in that order. Thus, the contrast for R is greatly degraded at low temperature. On the other hand, pre-charging as described above brings the potential V_p of the pixel electrode with the liquid crystal capacitance C_{ls} to the middle level, and thereby the potential V_p of the pixel electrode with the liquid crystal capacitance C_{ls} can reach the desired signal level well within a predetermined period of time. Consequently, a chromaticity shift at low temperature can be greatly reduced.

In the embodiment described above, the common voltage V_{COM} applied to the counter electrodes of the liquid crystal cells LC is used for the gray-scale level as obtained when no voltage is applied to the liquid crystal. A reference voltage other than the common voltage V_{COM} can also be used: a voltage applied to the electrodes of the storage capacitors C_s adjacent to the C_s lines, for example. This voltage has a level substantially equivalent to that of the common voltage V_{COM} and can be used for the gray-scale level

as obtained when no voltage is applied to the liquid crystal, namely, the pre-charge signal P_{sig} .

If a voltage applied to the electrodes of the storage capacitors C_s adjacent to the C_s lines is used for the pre-charge signal P_{sig} , the C_s driver (not shown in the figures) for driving the C_s lines 15 can be used for the pre-charge switch (pre-charge driver) 19. In this case, the C_s driver can normally be composed of a CMOS inverter, and therefore does not allow much direct current to flow in the circuit thereof. Pre-charging is also advantageous in that the pre-charge driver (C_s driver) accounts for half the charging/discharging required in the output circuit (analog circuit) of the data driver 17, thus reducing the current consumption in the output circuit. This advantage greatly contributes to the low power-consumption design of the liquid crystal display device.

The forgoing embodiment has been described with reference to, but not limited to, a liquid crystal display device employing the VCOM reverse driving system. In other words, the present invention is not limited to VCOM reverse driving but is also applicable to a common voltage VCOM fixed to a particular DC voltage. In this case, the voltage applied to the electrodes of the storage capacitors C_s adjacent to the C_s lines, that is, the potential of the C_s lines 15, is also fixed to the common voltage VCOM or

another DC level.

The embodiment described above has been described by way of an example of a liquid crystal display device employing the selector drive system. The present invention
5 is also applicable to techniques other than the selector drive system. Some of these other techniques are the line-at-a-time driving system, in which the display signals for each row of pixels in the display area 14 are sampled all at once within one horizontal period to supply the display
10 signals to the data lines, and the point-at-a-time driving system, in which the display signals for each row of pixels in the display area 14 are sequentially sampled within one horizontal period to supply the display signals to the data lines. If the present invention is applied particularly to
15 the point-at-a-time driving system, the period of time for writing the signal for the pixel to be sampled last is reduced, thus exhibiting an advantage in that shading at low temperature is reduced.

Fig. 4 is a block diagram illustrating a typical
20 structure of the liquid crystal panel according to the embodiment described above. The same symbols in Fig. 4 as those in Fig. 1 refer to the same components.

In the above structure, the data driver 17 is implemented as an IC on a glass substrate 21 by COG (Chip On
25 Glass). The positional relationships among the display area

14, the data driver 17, the selector switch 18, and the pre-charge switch 19 on the glass substrate 21 are same as in Fig. 1. In Fig. 4, however, the scan driver 16 is not shown. The data driver 17 receives external setting signals PRM1, 2, and 3 via a flexible printed circuit board 22, where the setting signals PRM1, 2, and 3 determine how a control signal PRS described below is output.

In a 1F reverse driving mode or during non-display period in a partial mode, the data driver 17 outputs the control signal PRS that defines whether or not to make the pre-charge switch 19 active during the horizontal blanking interval. The data driver 17 further outputs the gray-scale signal as obtained when no voltage is applied to the liquid crystal, namely, the gray-scale signal serving as the pre-charge signal P_{sig}. For this gray-scale signal as obtained when no voltage is applied to the liquid crystal, the common voltage VCOM is used in the embodiment described above.

The output terminal for the control signal PRS on the data driver 17, the PRS terminal on the test pad 23, and a level shift circuit 24 on the glass substrate 21 are electrically connected to one another by wiring 25. The control signal PRS output from the data driver 17 is supplied to the level shift circuit 24 through the wiring 25.

The level shift circuit 24 shifts the control signal PRS from a first voltage level, such as 3.3 V, to a higher

second voltage level, such as 7.0 V. The control signal PRS which has undergone level shift is given to a pulse generating circuit 26 for generating the pre-charge pulse PCG to control whether or not to generate the pre-charge pulse PCG. The pre-charge pulse PCG generated by the pulse generating circuit 26 is given to the pre-charge switch 19.

The output terminal for the pre-charge signal Psig on the data driver 17, the Tsig terminal on a test pad 27, and the pre-charge switch 19 are electrically connected to one another by wiring 28. The pre-charge signal Psig output from the data driver 17 is supplied to the pre-charge switch 19 via the wiring 28.

Furthermore, the TMS terminal of the flexible printed circuit board 22, the TMS terminal of the test pad 27, and the pre-charge switch 19 are electrically connected to one another by wiring 29. An external control signal TMS is input to the TMS terminal of the flexible printed circuit board 22 and is supplied to the pre-charge switch 19 via the wiring 29. This control signal TMS sets the pre-charge switch 19 to a test mode or a pre-charge driving mode.

In the liquid crystal display device according to the embodiment having the structure described above, setting the pre-charge switch 19 to the test mode using the control signal TMS input via the TMS terminal of the flexible printed circuit board 22 causes a test signal Tsig to be

input via the Tsig terminal on the test pad 27 and to be given to the pre-charge switch 19 via the wiring 28, thus allowing a panel display test to be performed without the driver IC (data driver 17). In this case, the pre-charge
5 switch 19 functions as a test switch.

With the data driver 17 implemented, the control signal PRS output from the data driver 17 makes the pre-charge switch 19 active during the horizontal blanking interval, thus allowing pre-charging, where the pre-charge switch 19
10 writes the pre-charge signal Psig before the data driver 17 writes the signal to the data line for each pixel in the display area 14, as described in the foregoing embodiment.

On the other hand, in the 1F driving reverse mode or during the non-display period in the partial mode, the
15 control signal PRS output from the data driver 17 makes the pre-charge switch 19 inactive during the horizontal blanking interval, thus disabling pre-charging in the 1F reverse driving mode or during the non-display period in the partial mode. This approach further reduces power consumption in
20 the liquid crystal display device.

In more detail, the 1F reverse driving mode can allocate a longer period of time for writing signals to pixels, and hence suffers from less low contrast at low temperature than with the 1H reverse driving mode. This
25 advantage of the 1F reverse driving mode allows pre-charging

to be disabled, thus contributing to a reduction in power consumption by as much as the power required for driving the pre-charge switch 19.

During the non-display period in the partial mode for a normally-white liquid crystal display device, for example, the white signal is written to the data lines so that the non-display area appears white. This operation is equivalent to writing the common voltage VCOM serving as the pre-charge signal Psig to the data lines, eliminating the need for pre-charging. This also allows pre-charging to be disabled to reduce power consumption.

Fig. 5 is a schematic drawing illustrating the outline of a portable terminal such as a portable telephone according to the present invention.

The portable telephone according to the embodiment includes a speaker section 42, an output display section 43, an operating section 44, and a microphone section 45 in that order from top to bottom of the front surface of a device casing 41. In the portable telephone structured as described above, the liquid crystal display device according to the foregoing embodiment or the example is used at the output display section 43.

The output display section 43 of such a portable telephone is provided with a partial display mode: a display function in a standby mode in which images are displayed in

part of the screen in the vertical direction. In the standby mode, for example, information about the remaining battery power, receiver sensitivity, or time is always displayed in part of the screen, as shown in Fig. 6. The non-display area other than the display area appears white for a normally-white liquid crystal display device or black for a normally-black liquid crystal display device.

Thus, the portable telephone provided with the output display section 43, i.e., the liquid crystal display device according to the foregoing embodiment or modification may perform pre-charging prior to writing the display signals to the pixels in order to enhance the contrast characteristics over a wide guaranteed operating temperature range, particularly at low temperature, thereby exhibiting superior image display in an environment at any temperature.

Another advantage is that pre-charging is disabled in the non-display area for partial display in the standby mode to reduce power consumption in the output display section 43 by as much power as consumed by the pre-charge driver, thus allowing long-term operation with one battery charge of the main power supply.

The foregoing embodiment has been described by way of an example of a portable telephone, but not limited to this. The present invention is applicable to other portable terminals such as PDA (personal digital assistants).

Industrial Applicability

As described above, the present invention allows pre-charging before the display signals are written to the
5 pixels, where the pre-charge signal is the gray-scale level as obtained when no voltage is applied to the liquid crystal to ensure that a desired signal voltage is written to the pixel despite the increased resistance component of the liquid crystal material at low temperature, thus enhancing
10 the contrast characteristics at low temperature while still suppressing power consumption.

CLAIMS

1. A liquid crystal display device comprising:

signal writing means for writing display signals to
data lines in a display area comprising a matrix of pixels;

5 and

pre-charging means for writing a gray-scale level to
the data lines before the signal writing means writes the
display signals to the data lines, the gray scale level
being obtained when no voltage is applied to liquid crystal

10 and serving as a pre-charge signal level.

2. The liquid crystal display device according to claim 1,

wherein the signal writing means time-sequentially
samples display signals, each corresponding to a group of
adjacent pixels in the same row of the display area, during
15 one horizontal period, and supplies the display signals to
the data lines, and

wherein the pre-charging means writes the pre-charge
signal to the data lines before the signal writing means
samples the display signals.

20 3. The liquid crystal display device according to claim 1,

wherein the signal writing means sequentially samples
display signals corresponding to the pixels in each row of
the display area during one horizontal period and supplies
the display signals to the data lines, and

25 wherein the pre-charging means writes the pre-charge

signal to the data lines before the signal writing means samples the display signals.

4. The liquid crystal display device according to claim 1, wherein the signal writing means simultaneously samples

5 all display signals corresponding to the pixels in each row of the display area during one horizontal period and supplies the display signals to the data lines, and

wherein the pre-charging means writes the pre-charge signal to the data lines before the signal writing means

10 samples the display signals.

5. The liquid crystal display device according to claim 1, wherein the gray-scale signal is a common voltage applied to counter electrodes of liquid crystal cells constituting the pixels.

15 6. The liquid crystal display device according to claim 1, wherein the gray-scale signal is a voltage applied to first ends of storage capacitors, the first ends being connected to respective counter electrodes of liquid crystal cells constituting the pixels and second ends of the storage
20 capacitors being connected to respective pixel electrodes of the liquid crystal cells.

7. The liquid crystal display device according to claim 1, wherein the pre-charging means does not perform the pre-charging in one field reverse driving mode in which the
25 polarity of the display signal to be written to each pixel

is reversed during one field period every one field period.

8. The liquid crystal display device according to claim 1,
wherein the pre-charging means does not perform the pre-
charging during a non-display period in a partial mode that
5 drives only part of the display area.

9. The liquid crystal display device according to claim 1,
wherein the pre-charging means writes an external test
signal to the data lines in place of the pre-charge signal.

10. A method for driving a liquid crystal display device,
10 comprising writing a gray-scale level to data lines in a
display area comprising a matrix of pixels before writing
display signals to the data lines, the gray-scale level
being obtained when no voltage is applied to liquid crystal
and serving as a pre-charge signal level.

15 11. A portable terminal including an output display section
which is a liquid crystal display device,

wherein the liquid crystal display device comprises:

signal writing means for writing display signals to
data lines in a display area comprising a matrix of pixels;

20 and

pre-charging means for writing a gray-scale level to
the data lines before the signal writing means writes the
display signals to the data lines, the gray-scale level
being obtained when no voltage is applied to liquid crystal
25 and serving as a pre-charge signal level.

12. The portable terminal according to claim 11,
wherein the output display section is capable of
setting a partial mode for driving only part of the display
area, and

5 wherein the pre-charging means does not perform the
pre-charging during a non-display period in the partial mode.