

Description

The present invention relates to an apparatus for severing and joining a joint piece. The invention is applicable for example to an apparatus for automatically severing a joint piece from an elongate product such as a surface fastener or a pressure-sensitive adhesive tape and joining the joint piece to the trailing end of a length cut off from another elongate product such as a surface fastener, a slide fastener chain, a film, an ornamental tape, or the like, so that the joint piece can be applied to a coil of the cut-off length on a reel to prevent the coil from being loosened off the reel, or the joint piece and the cut-off piece, if they are severed from surface fastener products, can be used as an adjustable band such as on a hat.

It has been customary to employ independent processes for severing an elongate product to a desired length, and making a joint piece to be applied to a coil of such a severed length to prevent the coil from being loosened off a reel (see for example EP-A-0106167), or making a joint piece for use as an adjustable band to be attached to a hat, for example. Before the joint piece is applied to the coil, it is manually attached to the trailing end of the severed length. These independent processes and manual procedure have however been tedious and time-consuming.

The present invention seeks to provide an apparatus for automatically severing a joint piece from an elongate product and joining such a joint piece to a desired length severed from another elongate product.

According to the present invention, there is provided an apparatus for severing and joining a joint piece, comprising: first feed means for feeding a first elongate product along a substantially horizontal path; second feed means for feeding a second elongate product for a predetermined interval along an inclined path extending obliquely to said horizontal path; a first fixed cutter disposed adjacent to said horizontal path; a second fixed cutter disposed adjacent to said inclined path; a movable cutter movable for transversely cutting off the first elongate product on said first fixed cutter into a product length and then for obliquely cutting off the second elongate product on said second fixed cutter into a joint piece, said movable cutter having a slanted surface for carrying a trailing end of the product length thereon with the joint piece partly overlapping said trailing end; and joining means for joining overlapping portions of the joint piece and the product length to each other thereby to produce a product with the joint piece having a free end exposed beyond said trailing end.

Many other advantages and features of the present invention will become manifest to those versed in the art upon making reference to the detailed description and the accompanying sheets of drawings in which preferred structural embodiments incorporating the principles of the present invention are shown by way of illustrative example.

Figure 1 is a side elevational view, partly in cross section, of an apparatus embodying the present invention;

Figure 2 is a fragmentary exploded perspective view of the apparatus shown in Figure 1;

Figure 3 is a side elevational view of the apparatus of Figure 1, also showing arrangements for feeding elongate products and a take-up reel;

Figures 4A and 4B are perspective views showing the manner in which a severed joint piece is applied to an elongate surface fastener product wound on a take-up reel;

Figures 5A through 5D are fragmentary cross-sectional views of the apparatus, illustrating a succession of steps of operation thereof;

Figures 6A and 6B are fragmentary cross-sectional views showing successive steps of operation of an apparatus according to another embodiment of the present invention;

Figures 7A through 7C are fragmentary cross-sectional views showing successive steps of operation of an apparatus according to still another embodiment of the present invention;

Figures 8A and 8B are perspective views showing the manner in which a severed joint piece is applied to an slide fastener chain wound on a take-up reel;

Figure 9A is a perspective view of an adjustable band including a joint piece produced by the apparatus shown in Figures 7A through 7C;

Figure 9B is a perspective view of the adjustable band of Figure 9A which is sewn to a fabric piece; and

Figure 10 is a perspective view of a hat to which the adjustable band is attached.

Like or corresponding parts are denoted by like or corresponding reference numerals throughout several views.

The principles of the present invention are particularly useful when embodied in an apparatus for severing and jointing a joint piece, such as shown in Figure 1, generally designated by the reference numeral 10.

The apparatus 10 includes a pair of vertically stacked horizontal feed rollers 11 rotatably mounted on horizontal shafts 12, respectively, on one side of the apparatus 10. The feed rollers 11 have their confronting portions disposed in a recess 13 defined in a horizontal feed guide 14 having a horizontal slot 15. A first elongate product L (Figure 1) such as a surface fastener, a slide fastener chain, a film, an ornamental tape, or the like is supplied into the apparatus 10 by the feed rollers 11 along a horizontal feed path through the slot 15. A second elongate product S such as a surface fastener, a pressure-sensitive tape, or the like, which is to be severed and joined as a joint piece to a cut end of the first elongate product L, is also supplied by a feed gripper 16 positioned above the feed rollers 11 and directed obliquely downwardly. The feed rollers 11 are rotated intermittently by a step motor (not shown) for feeding the first elongate product L intermittently so that a certain desired length thereof will be supplied to

the apparatus 10 and then stopped in each operation cycle. The feed gripper 16 is operated in timed relation to the feed rollers 11 to supply a desired length of the second elongate product S to the apparatus 10.

The apparatus 10 also includes a pair of vertically stacked horizontal auxiliary rollers 17 rotatably mounted on respective vertically movable horizontal shafts 18 on the opposite side of the apparatus 10. The auxiliary rollers 17 have confronting portions disposed in a recess 19 defined in a horizontal discharge guide 20 having a horizontal slot 21. The auxiliary rollers 17 are rotatable intermittently in synchronism with the feed rollers 11 to assist the first elongate product L in being fed through the apparatus 10. A finished product N is a combination of the cut length of the first elongate product L and a joint piece M (Figures 4A and 4B) applied to the cut end of the first elongate product L. When the finished product N is discharged from the apparatus 10, the auxiliary rollers 17 are vertically moved away from each other to allow smooth movement of the product N out of the apparatus 10.

The apparatus 10 includes a housing 22 having a lower support 23 on which the inner end of the feed guide 14 is fixedly mounted. A first fixed cutter 24 is mounted on the inner end of the feed guide 14, the first fixed cutter 24 having a lower cutting edge 25 (Figure 2) vertically aligned with the inner edge of the feed guide 14. A second fixed cutter 26 is mounted on the first fixed cutter 24. The first and second cutters 24, 26 have respective confronting slanted surfaces which jointly define therebetween an inclined slot 27 through which the second elongate product S can be fed along an inclined feed path which extends from above, obliquely and downwardly to the horizontal feed path for the first elongate product L, converging therewith in the directions of feed of both products L and S. The second fixed cutter 26 has a lower cutting edge 28 (Figure 2) positioned above the exit end of the slot 27 and vertically aligned with the cutting edge 25 of the first fixed cutter 24.

The housing 22 also has lower and upper supports 29, 30 wherein which are horizontally spaced from the support 23 and the first and second fixed cutters 24, 26. The discharge guide 20 is fixedly mounted on the lower support 29. A joining block 31 is attached to the lower end of the upper support 30 in vertically spaced relation to the discharge guide 20.

The apparatus 10 also includes a movable cutter 32 positioned between the feed guide 14 and the discharge guide 20 and vertically movable in a direction substantially normal to the direction in which the first elongate product L travels from the feed guide 14 to the discharge guide 20. The movable cutter 32 has a through-hole 33 defined between an upper slanted surface 34 and a lower slanted surface 35 spaced downwardly from and parallel to the upper slanted surface 34. The upper and lower slanted surfaces 34, 35 are inclined progressively downwardly

toward the discharge guide 20. Before the movable cutter 32 is moved upwardly, the through-hole 33 is positioned in communication with the horizontal slots, 15, 21 and the inclined slot 27, and the upper slanted surface 34 lies continuously flush with the slanted surface of the second fixed cutter 26 which defines the inclined slot 27. Therefore, the portion of the movable cutter 32 above the through-hole 33 serves as a guide 36 for guiding the second elongate product S along a downwardly inclined guide path into the movable cutter 32. The lower slanted surface 35 has an upper edge 37 (Figure 2) serving as a cutting edge which will coact with the cutting edges 25, 28 to cut off the first and second elongate products L, S, respectively. The movable cutter 32 can be actuated by an air cylinder 38 coupled thereto and disposed below the housing 22. The movable cutter 32 may be operated by any of other suitable actuators such as a hydraulic cylinder, a solenoid, a crank mechanism, and the like.

The second elongate product S can be adhered to the first elongate product L under pressure. Where the first elongate product L is a surface fastener having loops or hooks on its one surface, the second elongate product S is a surface fastener having hooks or loops on its surface facing the first elongate product L. Where the first elongate product L is a slide fastener chain, a film, an ornamental tape, or the like, the second elongate product S is a pressure-sensitive adhesive tape with a pressure-sensitive adhesive layer coated on its back. As shown in Figure 2, the joining block 31 has a vertical surface 39 facing the movable cutter 32, and the movable cutter 32 has a vertical surface 40 lying below the through-hole 33 and confronting the vertical surface 39 of the joining block 31.

As shown in Figure 3, a pivotable discharge tray 41 is positioned downstream of the auxiliary rollers 17 with respect to the direction of travel of the product N from the apparatus 10, the discharge tray 41 being inclined downwardly toward a take-up reel 32. The take-up reel 42 is removably mounted on a rotatable shaft 42a for winding the product N thereon. The discharge tray 42 has a lower end that is located in the take-up reel 42 for direct delivery of the product N onto the take-up reel 42. As the number of turns of the product N on the take-up reel 42 is increased, the discharge tray 41 is progressively raised to allow the product N to be smoothly wound on the take-up reel 42. While the first elongate product L is being supplied into the apparatus 10, it is tensioned by a tension roller 43 which is rollingly placed on the first elongate product L between idler rollers 44. The second elongate product S is delivered over an idler roller 45 into the feed gripper 16.

Operation of the apparatus 10 will be described with reference to Figures 5A through 5D. In Figures 5A through 5D, the first elongate product L is shown as a surface fastener having hooks or loops, and the second elongate product S is shown as a surface fastener having loops or hooks for face-to-face mating engagement with

the first elongate product L. The first elongate product L is fed through the apparatus 10 and is stopped when its leading end portion of a pre-determined length is wound on the take-up reel 42 (Figure 3). As shown in Figure 5A, the second elongate product S is supplied obliquely through the inclined slot 27 toward the first elongate product L by the feed gripper 16 which moves obliquely toward the inclined slot 27. The supply of the second elongate product S is stopped when its leading end is just about to reach the first elongate product L. Then, the movable cutter 32 is moved upwardly, as shown in Figure 5B, to cause the cutting edge 37 thereof to cut off the first elongate product L on the cutting edge 25 of the first fixed cutter 24, thereby producing a severed length T of the first elongate product L. The movable cutter 32 is continuously lifted to carry the trailing end portion of the product length T on the lower slanted surface 35, and to cause the cutting edge 37 to cut off the second elongate product S on the cutting edge 28 into a joint piece M, which is partly placed over the trailing end portion of the product length T. The joint piece M has a length m which is substantially equal to the length of the lower slanted surface 35 and which is larger than the thickness n of the movable cutter 32. Since the movable cutter 32 has substantially been raised above the horizontal path of the first elongate product L, the trailing end of the product length T is positioned approximately halfway on the lower slanted surface 35. Therefore, when the joint piece M overlies the trailing end of the product length T on the lower slanted surface 35, a near portion f of the joint piece M does not overlap the trailing end of the product length T and is positioned as a free exposed end over the lower slanted surface 35, as illustrated in Figure 5B. The free end f of the joint piece M will be applied to the final layer of the product length T on the reel 42 to prevent the wound product N from being loosened off the reel 42, as shown in Figure 4B. The length of the free end f is dependent on the angle at which the second elongate product S is fed into the apparatus 10.

Upon continued ascent of the movable cutter 32, the trailing end of the product length T with the joint piece M thereon is slid off the lower slanted surface 35, as shown in Figure 5C, and pinched between the confronting vertical surfaces 39, 40 of the joining block 31 and the movable cutter 32. The joint piece M is therefore firmly attached to the product length T. Then, the movable cutter 32 is lowered to release the joint piece M and the trailing end of the product length T into the through-hole 33, as shown in Figure 5D. The shaft 42a (Figure 4A) is rotated to enable the reel 42 to wind the product length T as the product N. At this time, the auxiliary rollers 17 (Figure 1) are moved apart from each other to allow smooth travel of the product length T through the tray 41 toward the reel 42. Finally, the free end f of the joint piece M is pressed against the outermost final layer of the wound product length T to secure the coil of the product N against the

danger of loosening off the reel 42, as shown in Figure 4B.

Figures 6A and 6B illustrate an apparatus according to another embodiment of the present invention. A cutter 50 is vertically movably disposed between the feed and discharge guides 14, 20 and has a slanted surface 51 on its upper end, the slanted surface 51 having an upper cutting edge 52 for cutting off the first and second elongate products L, S. A guide/joining block 53 is disposed separately above the movable cutter 50 and has a slanted surface 54 extending parallel to and spaced from the slanted surface 51 in confronting relation. The slanted surfaces 51, 54 jointly define a hole 55 therebetween for passage of the first and second elongate products L, S. The guide/joining block 53 is normally urged by a compression coil spring 56 to move downwardly toward the movable cutter 50. After the first and second elongate products L, S are cut off by the movable cutter 50, as shown in Figure 6B, the joint piece M and the trailing end of the product length T are securely applied to each other by being sandwiched between the slanted surfaces 51, 54 of the movable cutter 50 and the guide/joining block 53. The guide/joining block 53 therefore serves to both guide the second elongate product S along the slanted surface 54 and join the joint piece M to the trailing end of the product length T.

According to still another embodiment shown in Figures 7A through 7C, a pair of presser rollers 57, 58 is disposed downstream of the movable cutter 32, the presser rollers 57, 58 being rotatably mounted respectively on shafts 59, 60 supported on upper and lower supports 61, 62 disposed in the apparatus housing. As illustrated in Figures 7B and 7C, the presser rollers 57, 58 press a joint piece Mb (Figure 7C), which is severed by the movable cutter from the second elongate product S, against a product length Tb cut off the first elongate product L, thus producing a product Nb. The joint piece Mb may be increased in length by increasing the thickness of the movable cutter 32 (Figures 7A through 7C) and feeding the first and second elongate products L, S over an increased interval, before they are cut off by the movable cutter 32. The second elongate product S can then continuously be applied to the first elongate product L by the presser rollers 57, 58 over the increased length, as shown in Figure 7B.

In Figures 8A and 8B, the first elongate product is a slide fastener chain, which is severed by the apparatus of the invention into a slide fastener chain length Ta. The second elongate product is a pressure-sensitive adhesive tape, which is severed into a pressure-sensitive joint piece Ma. The joint piece Ma is applied to the trailing end of the slide fastener chain length Ta wound on the reel 42, as shown in Figure 8A, and is adhered to the final layer of the slide fastener chain length Ta on the reel 42, as shown in Figure 8B.

The product Nb manufactured by the apparatus shown in Figures 7A through 7C is particularly suitable for use as an adjustable band as shown in

Figures 9A, 9B, and 10, since the product Nb may be of an increased length. The product Nb can be attached to the rear of a hat 65 (Figure 10) by joining the opposite exposed free ends of the joint piece Mb and the product length Tb, which have been joined to each other in staggered relation, to respective confronting fabric edges 63, 64 of the hat 65, as shown in Figure 9B. In Figures 9A and 9B, the product length Tb is shown as having loops, and the joint piece Mb is shown as having hooks engaging the loops.

Claims

1. An apparatus (10) for severing and joining a joint piece (M; Ma; Mb), comprising: first feed means (11) for feeding a first elongate product (L) along a substantially horizontal path; second feed means (16) for feeding a second elongate product (S) for a predetermined interval along an inclined path extending obliquely to said horizontal path; a first fixed cutter (24) disposed adjacent to said horizontal path; a second fixed cutter (26) disposed adjacent to said inclined path; a movable cutter (32; 50) movable for transversely cutting off the first elongate product (L) on said first fixed cutter (24) into a product length (T; Ta; Tb) and then for obliquely cutting off the second elongate product (S) on said second fixed cutter (26) into a joint piece (M; Ma; Mb), said movable cutter (32; 50) having a slanted surface (35; 51) for carrying a trailing end of the product length (T; Ta; Tb) thereon with the joint piece (M; Ma; Mb) partly overlapping said trailing end; and joining means (31; 53; 57, 58) for joining overlapping portions of the joint piece (M; Ma; Mb) and the product length (T; Ta; Tb) to each other thereby to produce a product (N; Na; Nb) with the joint piece (M; Ma; Mb) having a free end (f) exposed beyond said trailing end.

2. An apparatus (10) according to claim 1, said first and second fixed cutters (24, 26) jointly defining an inclined slot (27) extending along said inclined path for passage therethrough of the second elongate product (S).

3. An apparatus (10) according to claim 1 or 2, said movable cutter (32) having a through-hole (33) for passage of the first and second elongate products (L, S) from said first and second feed means (11, 16), said through-hole (33) being defined by said slanted surface (35) and a second slanted surface (34) spaced from and parallel to said first-mentioned slanted surface (35).

4. An apparatus (10) according to claim 3, said movable cutter (32) including a guide (36) having said second slanted surface (34) for guiding the second elongate product (S) along said inclined path before the second elongate product (S) is cut off by said movable cutter (32) and said second fixed cutter (26).

5. An apparatus (10) according to claim 4, said joining means (31) comprising a joining block (31) disposed downstream of said guide (36) in said horizontal path for coacting with said movable cutter (32) to sandwich the joint piece (M)

and said product length (N) to join them to each other.

6. An apparatus (10) according to claim 1 or 2, further including a guide/joining block (53) having a second slanted surface (54) spaced from and parallel to said first-mentioned slanted surface (51) for guiding the second elongate product (S) along said inclined path before the second elongate product (S) is cut off by said movable cutter (50) and said second fixed cutter (26), and a spring (56) acting on said guide/joining block (53) for normally urging the latter toward said movable cutter (50) to sandwich the joint piece (M) and said product length (N) to join them to each other.

7. An apparatus (10) according to claim 1, said joining means (57, 58) comprises a pair of rollers (57, 58) rotatably disposed downstream of said movable cutter (32) in said horizontal path for sandwiching the joint piece (M) and said product length (N) therebetween to join them to each other.

8. An apparatus (10) according to any preceding claim wherein the inclined path of the second elongate product (S) is above the horizontal path of the first elongate product (L), and is inclined downwardly toward said horizontal path in the directions of feed of both products (L, S).

Patentansprüche

1. Vorrichtung (10) zum Abtrennen und Anbringen eines Verbindungsstücks (M; Ma; Mb), umfassend: erste Zuführrmittel (11) zum Zuführen eines ersten langgestreckten Produktes (L) längs einer im wesentlichen horizontalen Bahn; zweite Zuführrmittel (16) zum Zuführen eines zweiten langgestreckten Produktes (S) mit einer bestimmten Schrittlänge längs einer geneigten Bahn, die sich schräg zu der horizontalen Bahn erstreckt; eine erste ortsfeste Schneideinrichtung (24), die neben der besagten horizontalen Bahn angeordnet ist; eine zweite ortsfeste Schneideinrichtung (26), die neben der besagten geneigten Bahn angeordnet ist; eine bewegliche Schneideinrichtung (32; 50), die bewegbar ist, um das erste langgestreckte Produkt (L) auf der besagten ersten ortsfesten Schneideinrichtung (24) in eine Produktlänge (T; Ta; Tb) quer abzuschneiden, und um sodann das zweite langgestreckte Produkt (S) auf der besagten zweiten ortsfesten Schneideinrichtung (26) in ein Verbindungsstück (M; Ma; Mb) schräg abzuschneiden, wobei die bewegliche Schneideinrichtung (32; 50) eine geneigte Fläche (35; 51) zum Abstützen eines hinteren Endes der Produktlänge (T; Ta; Tb) hat, wobei das Verbindungsstück (M; Ma; Mb) dieses hintere Ende teilweise überlappt; und Zusammenfügemittel (31; 53; 57, 58), um überlappende Bereiche des Verbindungsstücks (M; Ma; Mb) und der Produktlänge (T; Ta; Tb) zusammenzufügen, um dadurch ein Produkt (N; Na; Nb) zu schaffen, wobei das Verbindungsstück (M; Ma; Mb) ein über das besagte hintere Ende hinausragendes freies Ende (f) hat.

Figures 9A, 9B, and 10, since the product Nb may be of an increased length. The product Nb can be attached to the rear of a hat 65 (Figure 10) by joining the opposite exposed free ends of the joint piece Mb and the product length Tb, which have been joined to each other in staggered relation, to respective confronting fabric edges 63, 64 of the hat 65, as shown in Figure 9B. In Figures 9A and 9B, the product length Tb is shown as having loops, and the joint piece Mb is shown as having hooks engaging the loops.

Claims

1. An apparatus (10) for severing and joining a joint piece (M; Ma; Mb), comprising: first feed means (11) for feeding a first elongate product (L) along a substantially horizontal path; second feed means (16) for feeding a second elongate product (S) for a predetermined interval along an inclined path extending obliquely to said horizontal path; a first fixed cutter (24) disposed adjacent to said horizontal path; a second fixed cutter (26) disposed adjacent to said inclined path; a movable cutter (32; 50) movable for transversely cutting off the first elongate product (L) on said first fixed cutter (24) into a product length (T; Ta; Tb) and then for obliquely cutting off the second elongate product (S) on said second fixed cutter (26) into a joint piece (M; Ma; Mb), said movable cutter (32; 50) having a slanted surface (35; 51) for carrying a trailing end of the product length (T; Ta; Tb) thereon with the joint piece (M; Ma; Mb) partly overlapping said trailing end; and joining means (31; 53; 57, 58) for joining overlapping portions of the joint piece (M; Ma; Mb) and the product length (T; Ta; Tb) to each other thereby to produce a product (N; Na; Nb) with the joint piece (M; Ma; Mb) having a free end (f) exposed beyond said trailing end.

2. An apparatus (10) according to claim 1, said first and second fixed cutters (24, 26) jointly defining an inclined slot (27) extending along said inclined path for passage therethrough of the second elongate product (S).

3. An apparatus (10) according to claim 1 or 2, said movable cutter (32) having a through-hole (33) for passage of the first and second elongate products (L, S) from said first and second feed means (11, 16), said through-hole (33) being defined by said slanted surface (35) and a second slanted surface (34) spaced from and parallel to said first-mentioned slanted surface (35).

4. An apparatus (10) according to claim 3, said movable cutter (32) including a guide (36) having said second slanted surface (34) for guiding the second elongate product (S) along said inclined path before the second elongate product (S) is cut off by said movable cutter (32) and said second fixed cutter (26).

5. An apparatus (10) according to claim 4, said joining means (31) comprising a joining block (31) disposed downstream of said guide (36) in said horizontal path for coacting with said movable cutter (32) to sandwich the joint piece (M)

and said product length (N) to join them to each other.

6. An apparatus (10) according to claim 1 or 2, further including a guide/joining block (53) having a second slanted surface (54) spaced from and parallel to said first-mentioned slanted surface (51) for guiding the second elongate product (S) along said inclined path before the second elongate product (S) is cut off by said movable cutter (50) and said second fixed cutter (26), and a spring (56) acting on said guide/joining block (53) for normally urging the latter toward said movable cutter (50) to sandwich the joint piece (M) and said product length (N) to join them to each other.

7. An apparatus (10) according to claim 1, said joining means (57, 58) comprises a pair of rollers (57, 58) rotatably disposed downstream of said movable cutter (32) in said horizontal path for sandwiching the joint piece (M) and said product length (N) therebetween to join them to each other.

8. An apparatus (10) according to any preceding claim wherein the inclined path of the second elongate product (S) is above the horizontal path of the first elongate product (L), and is inclined downwardly toward said horizontal path in the directions of feed of both products (L, S).

Patentansprüche

1. Vorrichtung (10) zum Abtrennen und Anbringen eines Verbindungsstücks (M; Ma; Mb), umfassend: erste Zuführrmittel (11) zum Zuführen eines ersten langgestreckten Produktes (L) längs einer im wesentlichen horizontalen Bahn; zweite Zuführrmittel (16) zum Zuführen eines zweiten langgestreckten Produktes (S) mit einer bestimmten Schrittlänge längs einer geneigten Bahn, die sich schräg zu der horizontalen Bahn erstreckt; eine erste ortsfeste Schneideinrichtung (24), die neben der besagten horizontalen Bahn angeordnet ist; eine zweite ortsfeste Schneideinrichtung (26), die neben der besagten geneigten Bahn angeordnet ist; eine bewegliche Schneideinrichtung (32; 50), die bewegbar ist, um das erste langgestreckte Produkt (L) auf der besagten ersten ortsfesten Schneideinrichtung (24) in eine Produktlänge (T; Ta; Tb) quer abzuschneiden, und um sodann das zweite langgestreckte Produkt (S) auf der besagten zweiten ortsfesten Schneideinrichtung (26) in ein Verbindungsstück (M; Ma; Mb) schräg abzuschneiden, wobei die bewegliche Schneideinrichtung (32; 50) eine geneigte Fläche (35; 51) zum Abstützen eines hinteren Endes der Produktlänge (T; Ta; Tb) hat, wobei das Verbindungsstück (M; Ma; Mb) dieses hintere Ende teilweise überlappt; und Zusammenfügemittel (31; 53; 57, 58), um überlappende Bereiche des Verbindungsstücks (M; Ma; Mb) und der Produktlänge (T; Ta; Tb) zusammenzufügen, um dadurch ein Produkt (N; Na; Nb) zu schaffen, wobei das Verbindungsstück (M; Ma; Mb) ein über das besagte hintere Ende hinausragendes freies Ende (f) hat.



2. Vorrichtung nach Anspruch 1, wobei die besagte erste und zweite ortsfeste Schneideinrichtung (24, 26) gemeinsam einen geneigten Schlitz (27) begrenzen, der sich längs der besagten geneigten Bahn für den Durchtritt des zweiten langgestreckten Produktes (S) erstreckt.

3. Vorrichtung (10) nach Anspruch 1 oder 2, wobei die bewegliche Schneideinrichtung (32) eine durchgehende Öffnung (33) für den Durchgang des ersten und zweiten langgestreckten Produktes (L, S) von den besagten ersten und zweiten Zuführungsmitteln (11, 16) aufweist, wobei die durchgehende Öffnung (33) von der besagten geneigten Fläche (35) und einer zweiten geneigten Flächen (34) begrenzt ist, die zu der erstgenannten geneigten Fläche (35) im Abstand parallel angeordnet ist.

4. Vorrichtung (10) nach Anspruch 3, wobei die bewegliche Schneideinrichtung (32) eine Führung (36) umfaßt, welche die besagte zweite geneigte Fläche (34) aufweist, um das zweite langgestreckte Produkt (S) längs der besagten geneigten Bahn zu führen, bevor das zweite langgestreckte Produkt (S) durch die bewegliche Schneideinrichtung (32) und die zweite ortsfeste Schneideinrichtung (26) abgeschnitten wird.

5. Vorrichtung (10) nach Anspruch 4, wobei die Zusammenfügemittel (31) einen Zusammenfügeblock (31) umfassen, der in der besagten horizontalen Bahn stromabwärts von der besagten Führung (36) angeordnet ist und mit der beweglichen Schneideinrichtung (32) zusammenwirkt, um das Verbindungsstück (M) und die besagte Produktlänge (N) zum Zusammenfügen übereinander anzuordnen.

6. Vorrichtung (10) nach Anspruch 1 oder 2, ferner umfassend einen Führungs/Zusammenfügeblock (53), der eine zweite geneigte Fläche (54) aufweist, die im Abstand parallel zu der erstgenannten geneigten Fläche (51) angeordnet ist, um das zweite langgestreckte Produkt (S) längs der besagten geneigten Bahn zu führen, bevor das zweite langgestreckte Produkt (S) durch die bewegliche Schneideinrichtung (50) und durch die zweite ortsfeste Schneideinrichtung (26) abgeschnitten wird, und eine Feder (56), die den Führungs/Zusammenfügeblock (53) normalerweise zu der beweglichen Schneideinrichtung (50) hin belastet, um das Verbindungsstück (M) und die besagte Produktlänge (N) zum Zusammenfügen übereinander anzuordnen.

7. Vorrichtung (10) nach Anspruch 1, wobei die Zusammenfügemittel (57, 58) zwei Rollen (57, 58) umfassen, die stromabwärts von der beweglichen Schneideinrichtung (32) in der besagten horizontalen Bahn angeordnet sind, um das Verbindungsstück (M) und die besagte Produktlänge (N) zum Zusammenfügen übereinander anzuordnen.

8. Vorrichtung (10) nach einem der vorhergehenden Ansprüche, wobei die geneigte Bahn des zweiten langgestreckten Produktes (S) über der horizontalen Bahn des ersten langgestreckten Produktes (L) angeordnet und nach unten zu der besagten horizontalen Bahn in Zuführrichtung der beiden Produkte (L, S) geneigt ist.

Revendications

1. Appareil (10) pour couper et réunir une pièce de raccordement (M; Ma; Mb), comportant: des premiers moyens de délivrance (11) pour délivrer un premier produit allongé (L) le long d'un chemin substantiellement horizontal; des deuxièmes moyens de délivrance (16) pour délivrer un deuxième produit allongé (S) dans un intervalle prédéterminé le long d'un chemin incliné s'étendant oblique par rapport audit chemin horizontal; un premier dispositif de coupe fixe (24) disposé au voisinage dudit chemin horizontal; un deuxième dispositif de coupe fixe (26) disposé au voisinage dudit chemin incliné; un dispositif de coupe mobile (32; 50) pouvant se déplacer pour couper transversalement le premier produit allongé (L) sur ledit premier dispositif de coupe fixe (24) en une longueur de produit (T; Ta; Tb), puis pour couper ensuite en oblique le deuxième produit allongé (S) sur ledit deuxième dispositif de coupe fixe (26) en une pièce de raccordement (M; Ma; Mb), ledit dispositif de coupe mobile (32; 50) ayant une surface inclinée (35; 51) pour porter une extrémité arrière de la longueur de produit (T; Ta; Tb) sur celle-ci, avec la pièce de raccordement (M; Ma; Mb) de façon à chevaucher partiellement ladite extrémité arrière; et des moyens de raccordement (31; 53; 57; 58) pour réunir des parties se chevauchant de la pièce de raccordement (M; Ma; Mb) et de la longueur de produit (T; Ta; Tb) les unes aux autres, afin de produire par conséquent un produit (N; Na; Nb), avec la pièce de raccordement (M; Ma; Mb) ayant une extrémité libre (f) exposée au-delà de ladite extrémité arrière.

2. Appareil (10) selon la revendication 1, lesdits premier et deuxième dispositifs de coupe fixes (24, 26) définissant conjointement une fente inclinée (27) s'étendant le long dudit chemin incliné pour le passage à travers celle-ci du deuxième produit allongé (S).

3. Appareil (10) selon la revendication 1 ou 2, ledit dispositif de coupe mobile (32) ayant un trou traversant (33) pour le passage des premier et deuxième produits allongés (L, S) depuis lesdits premier et deuxième moyens de délivrance (11, 16), ledit trou traversant (33) étant défini par ladite surface inclinée (35) et une deuxième surface inclinée (34) espacée de ladite surface inclinée (35) premièrement mentionnée et parallèle à celle-ci.

4. Appareil (10) selon la revendication 3, ledit dispositif de coupe mobile (32) comportant un guide (36) ayant ladite deuxième surface inclinée (34) pour guider le deuxième produit allongé (S) le long dudit chemin incliné avant que le deuxième produit allongé (S) soit coupé par ledit dispositif de coupe mobile (32) et ledit deuxième dispositif de coupe fixe (26).

5. Appareil (10) selon la revendication 4, lesdits moyens de raccordement (31) comportant un bloc de raccordement (31) disposé en aval dudit guide (36) dans ledit chemin horizontal pour interagir avec ledit dispositif de coupe mobile (32) afin de



prendre en sandwich la pièce de raccordement (M) et ladite longueur (N) de produit de façon à les réunir l'une à l'autre.

6. Appareil (10) selon la revendication 1 ou 2, comportant de plus un bloc de guidage/raccordement (53) ayant une deuxième surface inclinée (54) espacée de ladite surface inclinée (51) mentionnée en premier et parallèle à celle-ci pour guider le deuxième produit allongé (S) le long dudit chemin incliné avant que le deuxième produit allongé (S) ne soit coupé par ledit dispositif de coupe mobile (50) et ledit deuxième dispositif de coupe fixe (26), et un ressort (56) agissant sur ledit bloc de guidage/raccordement (53) de façon à pousser normalement ce dernier vers ledit dispositif de coupe mobile (50) afin de prendre en sandwich la pièce de raccordement (M) et ladite

longueur de produit (N) pour les réunir l'une à l'autre.

7. Appareil (10) selon la revendication 1, lesdits moyens de raccordement (57, 58) comportant une paire de rouleaux (57, 58) disposés de façon à pouvoir tourner en aval dudit dispositif de coupe mobile (32) dans ledit chemin horizontal pour prendre en sandwich la pièce de raccordement (M) et ladite longueur de produit (N) entre ceux-ci pour les réunir l'une à l'autre.

8. Appareil (10) selon l'une quelconque des revendications précédentes, dans lequel le chemin incliné du deuxième produit allongé (S) se situe au-dessus du chemin horizontal du premier produit allongé (L), et est incliné vers le bas en direction dudit chemin horizontal dans les directions de délivrance des deux produits (L, S).

20

25

30

35

40

45

50

55

60

65

7

