

THREE DIMENSIONAL PRINTING OF PARTS

BACKGROUND INFORMATION

5

Background

Modern aircraft contain a plurality of different parts. Aircraft manufacturers have each part design certified under airworthiness standards and other requirements of the Federal Aviation Administration (FAA). A certification for a part is specific to that part's specifications such as dimensions, shape, and material specifications.

During the lifetime of an aircraft, parts may be replaced. In order to meet demand for replacement parts, aircraft manufacturers may keep an inventory of parts on hand. A client may request parts from the aircraft manufacturer when a replacement part is desired. However, receiving requested parts from the aircraft manufacturer may take an undesirable amount of time for a client. Some clients may keep an inventory of parts on hand to avoid waiting an undesirable amount of time. However, storing an inventory of extra parts either at an aircraft manufacturer or at a client may use an undesirable amount of resources.

20

Three dimensional printing is a process of making a solid object of virtually any shape from a part definition file. Three dimensional printing is an additive process where successive layers of material are laid down. Three dimensional printing may be performed with a variety of different materials such as polymers, plasters, metals, and metal alloys. Three dimensional printing may allow on-demand manufacture of desired parts.

25

Therefore, it would be desirable to have a method and apparatus that take into account at least some of the issues discussed above, as well as other possible issues.

30

SUMMARY

In an illustrative embodiment, an apparatus is provided. The apparatus comprises a parts library, a database, and a parts management system. The parts library is configured to store a plurality of part definition files. The database is configured to store entries identifying a printing of parts using the plurality of part definition files. The parts management system is configured to receive a request for a part definition file in the parts library, identify the part definition file in the plurality of part definition files in the parts library, receive an indication of a printing of a part using the part definition file, and store an entry identifying the printing of the part using the part definition file in the database.

In another illustrative embodiment, a method is provided. The method comprises receiving a request for a part definition file in a parts library; identifying the part definition file in a plurality of part definition files in the parts library; receiving an indication of a printing of a part using the part definition file; and storing an entry identifying the printing of the part using the part definition file in a database.

In yet another illustrative embodiment, a system is presented. The system comprises a parts library, a database, a parts management system, and a three dimensional printing system. The parts library is configured to store a plurality of part definition files. The database is configured to store entries identifying a printing of parts using the plurality of part definition files. The parts management system is configured to receive a request for a part definition file in the parts library from the three dimensional printing system. The three dimensional printing system is configured to print parts using the plurality of part definition files.

The features and functions can be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

30

BRIEF DESCRIPTION OF THE DRAWINGS

The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode
5 of use, further objectives and features thereof, will best be understood by reference to the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

Figure 1 is an illustration of an aircraft in accordance with an illustrative embodiment;

10 **Figure 2** is an illustration of a block diagram of a parts environment in accordance with an illustrative embodiment;

Figure 3 is an illustration of a database in accordance with an illustrative embodiment;

Figure 4 is an illustration of a data flow in accordance with an illustrative embodiment;

15 **Figure 5** is another illustration of a data flow in accordance with an illustrative embodiment;

Figure 6 is an illustration of a flowchart of a process for the three dimensional printing of a part in accordance with an illustrative embodiment;

Figure 7 is another illustration of a flowchart of a process for the three dimensional printing of a part in accordance with an illustrative embodiment;

20 **Figure 8** is an illustration of a flowchart of a process for authorizing the three dimensional printing of a part in accordance with an illustrative embodiment;

Figure 9 is another illustration of a flowchart of a process for authorizing the three dimensional printing of a part in accordance with an illustrative embodiment;

25 **Figure 10** is an illustration of a block diagram of a data processing system in accordance with an illustrative embodiment;

Figure 11 is an illustration of a block diagram of an aircraft manufacturing and service method in accordance with an illustrative embodiment; and

Figure 12 is an illustration of a block diagram of an aircraft in which an illustrative embodiment may be implemented.

30

DETAILED DESCRIPTION

The different illustrative embodiments recognize and take into account a number of different considerations. For example, the illustrative embodiments recognize and take into account that clients may prefer to three dimensionally print parts when desired rather than hold parts in inventory. Accordingly, the different illustrative embodiments recognize and take into account that a client three dimensionally printing parts may reduce the cost of storing parts. Further, the different illustrative embodiments recognize and take into account that a client three dimensionally printing parts may reduce the time to receive the parts.

The different illustrative embodiments recognize and take into account that an aircraft manufacturer may wish to limit access to intellectual property such as part definition files. Further, the different illustrative embodiments recognize and take into account that an aircraft manufacturer may desire payment upon each three dimensional printing of a part. Yet further, the different illustrative embodiments recognize and take into account that an aircraft manufacturer may wish to verify information from a three dimensional printing system so that printed parts meet certification requirements.

With reference now to the figures, and in particular, with reference to **Figure 1**, an illustration of an aircraft is depicted in accordance with an illustrative embodiment. In this illustrative example, aircraft **100** has wing **102** and wing **104** attached to body **106**. Aircraft **100** includes engine **108** attached to wing **102** and engine **110** attached to wing **104**.

Body **106** has tail section **112**. Horizontal stabilizer **114**, horizontal stabilizer **116**, and vertical stabilizer **118** are attached to tail section **112** of body **106**.

Aircraft **100** is an example of an aircraft in which parts manufactured using three dimensional printing may be implemented in accordance with an illustrative embodiment. In some illustrative examples, portions of the passenger cabin in body **106** may be formed using a three dimensional printed part. For example, a handle of a luggage bin in the passenger cabin of aircraft **100** may use a three dimensional printed part.

The illustration of aircraft **100** in **Figure 1** is not meant to imply physical or architectural limitations to the manner in which an illustrative configuration may be implemented. For example, although aircraft **100** is a commercial aircraft, aircraft **100** may be a military aircraft, a rotorcraft, helicopter, unmanned aerial vehicle, or any other
5 suitable aircraft.

Although the illustrative examples for an illustrative embodiment are described with respect to an aircraft, an illustrative embodiment may be applied to other types of platforms. The platform may be, for example, a mobile platform, a stationary platform, a
10 land-based structure, an aquatic-based structure, and a space-based structure. More specifically, the platform, may be a surface ship, a tank, a personnel carrier, a train, a spacecraft, a space station, a satellite, a submarine, an automobile, a power plant, a bridge, a dam, a house, a windmill, a manufacturing facility, a building, and other suitable platforms.

15 With reference now to **Figure 2**, an illustration of a block diagram of a parts environment is depicted in accordance with an illustrative embodiment. In this illustrative example, parts environment **200** in **Figure 2** is depicted in a block form to illustrate different components for one or more illustrative embodiments. In this
20 illustrative example, parts environment **200** includes authorization system **202** and three dimensional printing system **204** which are in communication via data connection **206**. Data connection **206** may be at least one of a wired connection or a wireless connection.

Authorization system **202** is configured to authorize printing of parts by three
25 dimensional printing system **204**. Authorization system **202** includes parts library **208**, database **210**, and parts management system **212**.

Parts library **208** stores plurality of part definition files **214**. As depicted, plurality of part definition files **214** includes part definition file **216** and part definition file **218**.
30 As depicted, two part definition files are depicted in plurality of part definition files **214**. However, plurality of part definition files **214** may have any desirable number of part definition files.

Part definition file **216** is a file which may be used by three dimensional printing system **204** to create first part **217**. Part definition file **216** includes part specifications **220**, printer specifications **222**, and material specifications **224**. Part specifications **220** include physical specifications for first part **217**. Part specifications **220** may include at least one of a three dimensional shape and dimensions.

As used herein, the phrase “at least one of,” when used with a list of items, means different combinations of one or more of the listed items may be used and only one of each item in the list may be needed. For example, “at least one of item A, item B, or item C” may include, without limitation, item A or item A and item B. This example also may include item A, item B, and item C or item B and item C. The item may be a particular object, thing, or a category. In other words, at least one of means any combination of items and number of items may be used from the list but not all of the items in the list are required.

15

Printer specifications **222** include desired properties for a printer to create first part **217** using part definition file **216**. In one illustrative example, printer specifications **222** may include a printer resolution. In another illustrative example, printer specifications **222** may include a current printer health. Material specifications **224** include identified materials which may be used to form first part **217** using part definition file **216**. Material specifications **224** may be limited by certification of first part **217**.

Part definition file **218** is a file which may be used by three dimensional printing system **204** to create second part **219**. Part definition file **218** includes part specifications **226**, printer specifications **228**, and material specifications **230**. Part specifications **226** include physical specifications for second part **219**. Part specifications **226** may include at least one of a three dimensional shape and dimensions. Printer specifications **228** include desired properties for a printer to create second part **219** using part definition file **218**. In one illustrative example, printer specifications **228** may include a printer resolution. In another illustrative example, printer specifications **228** may include a current printer health. Material specifications **230** include identified materials which may be used to form second part **219** using part definition file **218**. Material specifications **230** may be limited by certification of second part **219**.

30

Database **210** is configured to store entries identifying the printing of parts using plurality of part definition files **214**. In some illustrative examples, database **210** may store an entry for each printing of a part. In some illustrative examples, database **210** may store an entry for each part printed by a customer. In this illustrative example, the entry
5 may contain a field for a number of times the part has been printed by the customer. In some illustrative examples, database **210** may store an entry for each part printed by a three dimensional printer. In this illustrative example, the entry may contain a field for a number of times the part has been printed by the three dimensional printer.

10 Parts management system **212** is configured to facilitate authorization of three dimensional printing of parts. Parts management system **212** is configured to receive a request for a part definition file, such as part definition file **216**, in parts library **208**. Parts management system **212** may receive the request from three dimensional printing system **204** via data connection **206**. Parts management system **212** is also configured to identify
15 the part definition file, such as part definition file **216**, in plurality of part definition files **214** in parts library **208**. After identifying part definition file **216**, parts management system **212** may encrypt and send part definition file **216** to three dimensional printing system **204**. Parts management system **212** may send part definition file **216** via data connection **206** after encryption.

20 Parts management system **212** is further configured to receive an indication of a printing of a part using the part definition file. In one illustrative example, this indication may be an indication of printing first part **217** using part definition file **216** by three dimensional printing system **204**. Parts management system **212** is also configured to
25 store an entry identifying a printing of the part using the part definition file in the database. Additionally, parts management system **212** is configured to request payment in response to an event. In some illustrative examples, the event may be receiving the indication of the printing of the part using the part definition file. In some other illustrative examples, the event may be receiving a message from three dimensional
30 printing system **402** that a desired number of parts has been printed using the part definition file.

As depicted, three dimensional printing system **204** has three dimensional printer **232**, three dimensional printer **234**, and data processing system **236**. As depicted, three dimensional printing system contains two three dimensional printers. However, three dimensional printing system **204** may contain any desirable number of three dimensional printers. Likewise, three dimensional printing system **204** may contain any desirable number of data processing systems.

Three dimensional printer **232** has parts library **238**, number of materials **240**, and diagnostic information **242**. In some illustrative examples, parts library **238** may not initially contain any part definition files. In these illustrative examples, a part definition file may be loaded to parts library **238** prior to printing a part using three dimensional printer **232**. In these illustrative examples, the part definition file may be deleted following printing a part using the part definition file.

In some other illustrative examples, parts library **238** may contain a plurality of part definition files. In these illustrative examples, authorization system **202** may update parts library **238** as desired. For example, authorization system **202** may add a number of part definition files to parts library **238**. Part definition files may be added to parts library **238** after the client purchases a new type of aircraft. Part definition files may be added to parts library **238** after new part definition files are created by the aircraft manufacturer. As another example, authorization system **202** may update specifications for a number of part definition files of parts library **238** to keep parts library **238** up to date. Specifications for a number of part definition files of parts library **238** may be updated as changes are made to parts by the aircraft manufacturer.

Three dimensional printer **232** may manufacture parts using number of materials **240**. Number of materials **240** may be selected from at least one of metals, metal alloys, polymers, or other desirable materials.

Diagnostic information **242** may include printer resolution, printer health information, or any other printer information. In some illustrative examples, parts management system **212** may verify that diagnostic information **242** conforms to at least one of printer specifications **222** or material specifications **224** of part definition file **216**.

In some illustrative examples, parts management system **212** may verify that diagnostic information **242** conforms to at least one of printer specifications **228** or material specifications **230** of part definition file **218**.

5 As depicted, three dimensional printer **232** receives input **250**. Input **250** may be at least one of part number **252** and part illustration **254**. In some illustrative examples, three dimensional printer **232** may identify a part definition file for a part using input **250**. In some illustrative examples, data processing system **236** may be in communication with three dimensional printer **232** and may identify a part definition file for a part using input
10 **250**. After identifying the part definition file, three dimensional printing system **204** sends a request for the part definition file to authorization system **202**.

 In some illustrative examples, after sending a request, three dimensional printing system **204** receives the part definition file, such as part definition file **216**. In some
15 illustrative examples, after sending a request, three dimensional printing system **204** receives authorization to print a part using a part definition file on three dimensional printer **232** or three dimensional printer **234**. After receiving a part definition file or authorization to print a part, three dimensional printer **232** may print part **256**. Part **256** may be printed using a part definition file from plurality of part definition files **214** or
20 from parts library **238**. In some illustrative examples, part **256** may be an implementation of first part **217**. In some illustrative examples, part **256** may be an implementation of second part **219**.

 Three dimensional printer **234** has parts library **244**, number of materials **246**, and
25 diagnostic information **248**. In some illustrative examples, parts library **244** may not initially contain any part definition files. In these illustrative examples, a part definition file may be loaded to parts library **244** prior to printing a part using three dimensional printer **234**. In these illustrative examples, the part definition file may be deleted following printing a part using the part definition file.

30

 In some other illustrative examples, parts library **244** may contain a plurality of part definition files. In these illustrative examples, authorization system **202** may update parts library **244** as desired. For example, authorization system **202** may add a number of

part definition files to parts library **244**. Part definition files may be added to parts library **244** after the client purchases a new type of aircraft. Part definition files may be added to parts library **244** after new part definition files are created by the aircraft manufacturer. As another example, authorization system **202** may update specifications for a number of part definition files of parts library **244** to keep parts library **244** up to date. Specifications for a number of part definition files of parts library **244** may be updated as changes are made to parts by the aircraft manufacturer.

Three dimensional printer **234** may manufacture parts using number of materials **246**. Number of materials **246** may be selected from at least one of metals, metal alloys, polymers, or other desirable materials.

Diagnostic information **248** may include printer resolution, printer health information, or any other printer information. In some illustrative examples, parts management system **212** may verify that diagnostic information **248** conforms to at least one of printer specifications **222** or material specifications **224** of part definition file **216**. In some illustrative examples, parts management system **212** may verify that diagnostic information **248** conforms to at least one of printer specifications **228** or material specifications **230** of part definition file **218**.

By having authorization system **202** authorize the three dimensional printing of parts, the owner of part definition files may control who accesses the part definition files. In some illustrative examples, the owner may be an aircraft manufacturer. Further, by having authorization system **202** authorize the three dimensional printing of parts, the owner of part definition files may track the number of times a specific part is printed. Additionally, by having authorization system **202** authorize the three dimensional printing of parts, the owner of part definition files may request payment for each printing of a part. By verifying diagnostic information of a three dimensional printing system, the authorization system may verify a three dimensional printing of a part may meet certification standards.

The illustration of parts environment **200** in **Figure 2** is not meant to imply physical or architectural limitations to the manner in which an illustrative embodiment

may be implemented. Other components in addition to or in place of the ones illustrated may be used. Some components may be unnecessary. Also, the blocks are presented to illustrate some functional components. One or more of these blocks may be combined, divided, or combined and divided into different blocks when implemented in an illustrative embodiment.

For example, as depicted, two part definition files are depicted in plurality of part definition files **214**. However, plurality of part definition files **214** may have any desirable number of part definition files.

Turning now to **Figure 3**, an illustration of a database is depicted in accordance with an illustrative embodiment. Database **300** is an implementation of database **210** of **Figure 2**.

Database **300** stores entries **302**. As depicted, entries **302** have identifiers **304**. Identifiers **304** comprise transaction number **306**, client number **308**, printer number **310**, part number **312**, part definition file location **314**, and print time **316**. Transaction number **306** is a unique identifier for the respective printing of the part. Client number **308** is an identifier for the client that printed the part. The client is the owner of the three dimensional printing system which printed the part. Printer number **310** is an identifier for the three dimensional printer that printed the part. Part number **312** is an identifier for the particular part that was printed. Part definition file location **314** identifies whether the part was printed using a part definition file from the authorization system or the three dimensional printing system. Print time **316** is an identifier of the date and time the indication of the printing was received.

As depicted, entries **302** comprise one entry for each printing of a part. In some illustrative examples, entries **302** may comprise one entry for each part. In these illustrative examples, each entry may have an additional identifier for the number of times the part has been printed.

With reference now to **Figure 4**, an illustration of a data flow is depicted in accordance with an illustrative embodiment. Data flow **400** is an example of an

implementation of communications between authorization system **202** and three dimensional printing system **204** via data connection **206** in **Figure 2**. Three dimensional printing system **402** is an example of an implementation of three dimensional printing system **204** of **Figure 2**. Authorization system **404** is an example of an implementation
5 of authorization system **202** of **Figure 2**.

In data flow **400**, each request and information may be a message. In some illustrative examples, a message may be sent within three dimensional printing system **402** or authorization system **404**. In some illustrative examples, a message may be sent
10 between three dimensional printing system **402** and authorization system **404**. In data flow **400**, three dimensional printing system **402** requests a part definition file from authorization system **404**. In response to receiving the request for the part definition file, authorization system **404** requests diagnostic information. Three dimensional printing system **402** then sends diagnostic information to authorization system **404**.

15 Authorization system **404** identifies the part definition file. After identifying the part definition file, authorization system **404** verifies that the diagnostic information conforms to at least one of printer specifications and material specifications of the part definition file. After verifying that the diagnostic information is desirable, authorization
20 system **404** encrypts the part definition file. Authorization system **404** then sends the encrypted part definition file to three dimensional printing system **402**. Three dimensional printing system **402** decrypts the encrypted part definition file. Three dimensional printing system **402** then prints a part using the decrypted part definition file. After printing the part, three dimensional printing system **402** sends an indication of
25 printing to authorization system **404**. In response to the indication of printing, authorization system **404** stores an entry identifying the printing in a database.

Authorization system **404** may then send a delete command to three dimensional printing system **402**. In response to the delete command, three dimensional printing
30 system **402** deletes the part definition file. Authorization system **404** requests payment for the printing of the part.

Turning now to **Figure 5**, another illustration of a data flow is depicted in accordance with an illustrative embodiment. Data flow **500** is an example of an implementation of communications between authorization system **202** and three dimensional printing system **204** via data connection **206** in **Figure 2**. Three dimensional printing system **502** is an example of an implementation of three dimensional printing system **204** of **Figure 2**. Authorization system **504** is an example of an implementation of authorization system **202** of **Figure 2**.

In data flow **500**, each request and information may be a message. In some illustrative examples, a message may be sent within three dimensional printing system **502** or authorization system **504**. In some illustrative examples, a message may be sent between three dimensional printing system **502** and authorization system **504**. In data flow **500**, three dimensional printing system **502** requests a part definition file from authorization system **504** (message m1). In response to receiving the request for the part definition file, authorization system **504** requests diagnostic information (message m2). Three dimensional printing system **502** then sends diagnostic information to authorization system **504** (message m3).

Authorization system **504** identifies the part definition file (message m4). After identifying the part definition file, authorization system **504** verifies that the diagnostic information conforms to at least one of printer specifications and material specifications of the part definition file (message m5). After verifying that the diagnostic information is desirable, authorization system **504** sends authorization to print the part to three dimensional printing system **502** (message m6).

After receiving authorization to print the part, three dimensional printing system **502** retrieves the part definition file (message m7). In some illustrative examples, a three dimensional printer of three dimensional printing system **502** may retrieve the part definition file from a part library on the three dimensional printer. Three dimensional printing system **502** then prints a part using the part definition file (message m8). Afterwards, three dimensional printing system **502** sends an indication of printing to authorization system **504** (message m9).

In response to the indication of printing, authorization system **504** stores an entry identifying the printing in a database (message m10). Authorization system **504** requests payment for the printing of the part from three dimensional printing system **502** (message m11).

5

With reference now to **Figure 6**, an illustration of a flowchart of a process for the three dimensional printing of a part is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 6** may be implemented to print a part using three dimensional printing system **204** of **Figure 2**.

10

The process begins by sending a request for a part definition file (operation **602**). In some illustrative examples, the three dimensional printing system may send the request. The three dimensional printing system may be three dimensional printing system **204** of **Figure 2**. In some illustrative examples, the part definition file may be selected by a part number to be printed.

15

The process then receives an encrypted part definition file (operation **604**). The process next decrypts the encrypted part definition file to form a decrypted part definition file (operation **606**). The process may then print a part using the decrypted part definition file (operation **608**). The process terminates thereafter.

20

Turning now to **Figure 7**, another illustration of a flowchart of a process for the three dimensional printing of a part is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 7** may be implemented to print a part using a three dimensional printing system such as three dimensional printing system **204** of **Figure 2**.

25

The process begins by sending a request for a part definition file (operation **702**). The process then receives an authorization to print a part using the part definition file (operation **704**). Next, the process retrieves the part definition file (operation **706**). In some illustrative examples, the part definition file may be retrieved from a data processing system of the three dimensional printing system. This data processing system may be data processing system **236** of three dimensional printing system **204** of **Figure 2**.

30

In some illustrative examples, the part definition file may be retrieved from a three dimensional printer, such as three dimensional printer 232 of **Figure 2**. The process then prints the part using the part definition file (operation 708). The process terminates thereafter.

5

With reference now to **Figure 8**, an illustration of a flowchart of a process for authorizing the three dimensional printing of a part is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 8** may be implemented to authorize the three dimensional printing of a part. The process illustrated in **Figure 8** may be implemented using an authorization system such as authorization system 202 of **Figure 2**.

The process begins by receiving a request for a part definition file in a parts library (operation 802). The request may be received by an authorization system from a three dimensional printing system. The authorization system may be authorization system 202 of **Figure 2**. The three dimensional printing system may be three dimensional printing system 204 of **Figure 2**. The process then identifies the part definition file in a plurality of part definition files in the parts library (operation 804). The process next receives an indication of a printing of a part using the part definition file (operation 806). The process then stores an entry identifying the printing of the part using the part definition file in a database (operation 808). The process then requests payment in response to receiving the indication of the printing of the part using the part definition file (operation 810). Afterwards the process terminates.

Turning now to **Figure 9**, another illustration of a flowchart of a process for authorizing three dimensional printing of a part is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 9** may be implemented to authorize the three dimensional printing of a part. The process illustrated in **Figure 9** may be implemented using an authorization system such as authorization system 202 of **Figure 2**.

30

The process begins by receiving a request for a part definition file in a parts library (operation 902). The process then requests diagnostic information for a three

dimensional printing system (operation 904). The process then receives the diagnostic information for the three dimensional printing system (operation 906). The process then identifies the part definition file in a plurality of part definition files in the parts library (operation 908). The process then verifies that the three dimensional printing system has
5 the diagnostic information conforming to at least one of printer specifications and material specifications of the part definition file of the plurality of part definition files in the parts library (operation 910). The process next encrypts the part definition file to form an encrypted part definition file (operation 912). The process then transmits the encrypted part definition file to the three dimensional printing system (operation 914).
10 The process next receives an indication of a printing of a part using the part definition file (operation 916). The process then stores an entry identifying the printing of the part using the part definition file in the database (operation 918). The process then requests payment in response to receiving the indication of the printing of the part using the part definition file (operation 920). The process terminates thereafter.

15

With reference now to **Figure 10**, an illustration of a block diagram of a data processing system is depicted in accordance with an illustrative embodiment. Data processing system **1000** may be used to implement one or more computers in authorization system **202** in **Figure 2**. Further, data processing system **1000** may be an
20 implementation of data processing system **236** of **Figure 2**. As depicted, data processing system **1000** includes communications framework **1002**, which provides communications between processor unit **1004**, storage devices **1006**, communications unit **1008**, input/output unit **1010**, and display **1012**. In some cases, communications framework **1002** may be implemented as a bus system.

25

Processor unit **1004** is configured to execute instructions for software to perform a number of operations. Processor unit **1004** may comprise a number of processors, a multi-processor core, and/or some other type of processor, depending on the implementation. In some cases, processor unit **1004** may take the form of a hardware
30 unit, such as a circuit system, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware unit.

Instructions for the operating system, applications, and/or programs run by processor unit **1004** may be located in storage devices **1006**. Storage devices **1006** may be in communication with processor unit **1004** through communications framework **1002**. As used herein, a storage device, also referred to as a computer readable storage device, is any piece of hardware capable of storing information on a temporary and/or permanent basis. This information may include, but is not limited to, data, program code, and/or other information.

Memory **1014** and persistent storage **1016** are examples of storage devices **1006**. Memory **1014** may take the form of, for example, a random access memory or some type of volatile or non-volatile storage device. Persistent storage **1016** may comprise any number of components or devices. For example, persistent storage **1016** may comprise a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. The media used by persistent storage **1016** may or may not be removable.

Communications unit **1008** allows data processing system **1000** to communicate with other data processing systems and/or devices. Communications unit **1008** may provide communications using physical and/or wireless communications links.

20

Input/output unit **1010** allows input to be received from and output to be sent to other devices connected to data processing system **1000**. For example, input/output unit **1010** may allow user input to be received through a keyboard, a mouse, and/or some other type of input device. As another example, input/output unit **1010** may allow output to be sent to a printer connected to data processing system **1000**.

25

Display **1012** is configured to display information to a user. Display **1012** may comprise, for example, without limitation, a monitor, a touch screen, a laser display, a holographic display, a virtual display device, and/or some other type of display device.

30

In this illustrative example, the processes of the different illustrative embodiments may be performed by processor unit **1004** using computer-implemented instructions. These instructions may be referred to as program code, computer usable program code, or

computer readable program code and may be read and executed by one or more processors in processor unit **1004**.

In these examples, program code **1018** is located in a functional form on computer readable media **1020**, which is selectively removable, and may be loaded onto or transferred to data processing system **1000** for execution by processor unit **1004**. Program code **1018** and computer readable media **1020** together form computer program product **1022**. In this illustrative example, computer readable media **1020** may be computer readable storage media **1024** or computer readable signal media **1026**.

Computer readable storage media **1024** is a physical or tangible storage device used to store program code **1018** rather than a medium that propagates or transmits program code **1018**. Computer readable storage media **1024** may be, for example, without limitation, an optical or magnetic disk or a persistent storage device that is connected to data processing system **1000**.

Alternatively, program code **1018** may be transferred to data processing system **1000** using computer readable signal media **1026**. Computer readable signal media **1026** may be, for example, a propagated data signal containing program code **1018**. This data signal may be an electromagnetic signal, an optical signal, and/or some other type of signal that can be transmitted over physical and/or wireless communications links.

The illustration of data processing system **1000** in **Figure 10** is not meant to provide architectural limitations to the manner in which the illustrative embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system that includes components in addition to or in place of those illustrated for data processing system **1000**. Further, components shown in **Figure 10** may be varied from the illustrative examples shown.

Illustrative embodiments of the disclosure may be described in the context of aircraft manufacturing and service method **1100** as shown in **Figure 11** and aircraft **1200** as shown in **Figure 12**. Turning first to **Figure 11**, an illustration of a block diagram of an aircraft manufacturing and service method is depicted in accordance with an

illustrative embodiment. During pre-production, aircraft manufacturing and service method **1100** may include specification and design **1102** of aircraft **1200** in **Figure 12** and material procurement **1104**.

5 During production, component and subassembly manufacturing **1106** and system integration **1108** of aircraft **1200** in **Figure 12** takes place. Thereafter, aircraft **1200** in **Figure 12** may go through certification and delivery **1110** in order to be placed in service **1112**. While in service **1112** by a customer, aircraft **1200** in **Figure 12** is scheduled for routine maintenance and service **1114**, which may include modification, reconfiguration,
10 refurbishment, and other maintenance or service.

Each of the processes of aircraft manufacturing and service method **1100** may be performed or carried out by a system integrator, a third party, and/or an operator. In these examples, the operator may be a customer. For the purposes of this description, a system
15 integrator may include, without limitation, any number of aircraft manufacturers and major-system subcontractors; a third party may include, without limitation, any number of vendors, subcontractors, and suppliers; and an operator may be an airline, a leasing company, a military entity, a service organization, and so on.

20 With reference now to **Figure 12**, an illustration of a block diagram of an aircraft is depicted in which an illustrative embodiment may be implemented. In this example, aircraft **1200** is produced by aircraft manufacturing and service method **1100** in **Figure 11** and may include airframe **1202** with plurality of systems **1204** and interior **1206**. Examples of systems **1204** include one or more of propulsion system **1208**, electrical
25 system **1210**, hydraulic system **1212**, and environmental system **1214**. Any number of other systems may be included. Although an aerospace example is shown, different illustrative embodiments may be applied to other industries, such as the automotive industry.

30 Apparatuses and methods embodied herein may be employed during at least one of the stages of aircraft manufacturing and service method **1100** in **Figure 11**. One or more illustrative embodiments may be used during maintenance and service **1114**. For example, three dimensional printing system **204** may also be used to print parts to

perform replacements during maintenance and service **1114**. Parts for aircraft **1200** may be three dimensionally printed during scheduled maintenance for aircraft **1200**.

Thus, the illustrative embodiments provide a method and apparatus for
5 authorizing the three dimensional printing of parts. By having authorization system **202** authorize the three dimensional printing of parts, the owner of part definition files may control who accesses the part definition files. In some illustrative examples, the owner may be an aircraft manufacturer. Further, by having authorization system **202** authorize the three dimensional printing of parts, the owner of part definition files may track the
10 number of times a specific part is printed. Additionally, by having authorization system **202** authorize the three dimensional printing of parts, the owner of part definition files may request payment for each printing of a part. By verifying diagnostic information of a three dimensional printing system, the authorization system may verify that a three dimensional printing of a part may meet certification standards.

15

By providing a mechanism for authorizing the three dimensional printing of parts, a client may three dimensionally print replacement parts instead of ordering replacement parts from a manufacturer. By three dimensionally printing parts, a client may reduce the time prior to installation of a replacement part. By three dimensionally printing parts, a
20 client may reduce the resources allocated to storage of replacement parts.

The flowcharts and block diagrams in the different depicted embodiments illustrate the architecture, functionality, and operation of some possible implementations of apparatuses and methods in an illustrative embodiment. In this regard, each block in
25 the flowcharts or block diagrams may represent a module, a segment, a function, and/or a portion of an operation or step.

In some alternative implementations of an illustrative embodiment, the function or functions noted in the blocks may occur out of the order noted in the figures. For
30 example, in some cases, two blocks shown in succession may be executed substantially concurrently, or the blocks may sometimes be performed in the reverse order, depending upon the functionality involved. Also, other blocks may be added in addition to the illustrated blocks in a flowchart or block diagram.

The description of the different illustrative embodiments has been presented for purposes of illustration and description, and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different illustrative embodiments
5 may provide different features as compared to other illustrative embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

10

CLAIMS:

What is claimed is:

- 5 1. An apparatus comprising:
 - a parts library (208) configured to store a plurality of part definition files (214);
 - a database (210) configured to store entries (302) identifying a printing of parts using the plurality of part definition files (214); and
 - 10 a parts management system (212) configured to receive a request for a part definition file (216) in the parts library (208), identify the part definition file (216) in the plurality of part definition files (214) in the parts library (208), receive an indication of a printing of a part using the part definition file (216), and store an entry identifying the printing of the part using the part definition file (216) in the database (210).
- 15 2. The apparatus of claim 1, wherein the parts management system (212) is further configured to:
 - request payment in response to receiving the indication of the printing of the part using the part definition file (216).
- 20 3. The apparatus of any of claims 1-2, wherein the parts management system (212) is further configured to:
 - transmit the part definition file (216) to a three dimensional printing system (204).
- 25 4. The apparatus of claim 3, wherein the parts management system (212) is further configured to encrypt the part definition file (216) to form an encrypted part definition file, and wherein in being configured to transmit the part definition file (216) to the three dimensional printing system (204), the parts management system (212) is configured to transmit the encrypted part definition file to the three dimensional printing system (204).
- 30 5. The apparatus of any of claims 1-4, wherein the parts management system (212) is further configured to verify that a three dimensional printing system (204) has diagnostic information (242) conforming to at least one of printer specifications (222) and material

specifications (224) of the part definition file (216) of the plurality of part definition files (214) in the parts library (208).

6. The apparatus of any of claims 1-5, wherein the parts library (208) is a first parts library (208), and wherein the parts management system (212) is further configured to update a second parts library (238) in a three dimensional printing system (204) using the plurality of part definition files (214) in the first parts library (208).

7. A method comprising:
10 receiving (802) a request for a part definition file (216) in a parts library (208);
identifying (804) the part definition file (216) in a plurality of part definition files (214) in the parts library (208);
receiving (806) an indication of a printing of a part using the part definition file (216); and
15 storing (808) an entry identifying the printing of the part using the part definition file (216) in a database (210).

8. The method of claim 7, further comprising:
requesting (810) payment in response to receiving the indication of the printing of
20 the part using the part definition file (216).

9. The method of any of claims 7-8, further comprising:
sending the part definition file (216) in the plurality of part definition files (214) to a three dimensional printing system (204).

25 10. The method of any of claims 7-9, further comprising:
verifying that diagnostic information (242) of a three dimensional printing system (204) conforms to at least one of printer specifications (222) and material specifications (224) of the part definition file (216) in the plurality of part definition files (214).

30 11. The method of any of claims 7-10, further comprising:
sending a delete command to delete the part definition file (216) to a three dimensional printing system (204) in response to an event.

12. The method of any of claim 7-11, further comprising:
encrypting the part definition file (216) before sending the part definition file
(216) in the plurality of part definition files (214) to a three dimensional printing system
5 (204).
13. A system comprising:
a parts library (208) configured to store a plurality of part definition files (214);
a database (210) configured to store entries (302) identifying a printing of parts
10 using the plurality of part definition files (214);
a parts management system (212) configured to receive a request for a part
definition file (216) in the parts library (208) from a three dimensional printing system
(204); and
the three dimensional printing system (204) configured to print parts using the
15 plurality of part definition files (214).
14. The system of claim 13, wherein the parts library (238) is located in the three
dimensional printing system (204).
- 20 15. The system of any of claims 13-14, wherein the database (210) and the parts
management system (212) are located in an authorization system (202), and wherein the
authorization system (202) is configured to update the parts library (208) by adding a
number of part definition files to the parts library (208).
- 25 16. The system of any of claim 13-14, wherein the database (210) and the parts
management system (212) are located in an authorization system (202), and wherein the
authorization system (202) is configured to update specifications for a number of part
definition files of the parts library (208) to keep the parts library (208) up to date.
- 30 17. The system of any of claims 13-14, wherein the database (210) and the parts
management system (212) are located in an authorization system (202).

18. The system of claim 17, wherein the authorization system (202) and the three dimensional printing system (204) are connected by a data connection (206).

19. The system of any of claim 13-18, wherein the three dimensional printing system
5 (204) comprises a number of three dimensional printers.

20. The system of any of claims 13-19, wherein the three dimensional printing system
(204) further comprises a data processing system (236).

10