

VEHICLE SEAT FOR A DISABLED PERSON

TECHNICAL FIELD

The present invention relates to removable vehicle seats and in particular to removable bus seats for disabled people.

BACKGROUND

Typically, when a disabled person in a wheelchair travels in a bus, the person remains in their regular wheelchair during the trip. The wheelchair is loaded into the bus whilst the disabled person remains seated in it, and it is then strapped down to prevent it from moving whilst the bus is in motion. A disadvantage of this method of travel is that a conventional wheelchair occupies considerable space in a bus, reducing the number of conventional seats in the bus and also limiting the number of disabled people that can travel at once. For example, a conventional wheelchair may occupy the space of four conventional bus seats. There are known methods of removing seats from a bus when it is necessary to make space for conventional wheelchairs, but this still reduces the seating capacity of the bus when transporting a wheelchair and the removed bus seats must be stored outside of the bus.

In some instances, such as in some of the public transport "low floor" Sydney Buses, a designated space is provided on each bus for disabled passengers in wheelchairs. This designated space is normally occupied by four inwardly facing foldable seats near the front of the bus to be used normally by passengers. However, should a disabled person in a wheelchair board the bus, the foldable seats are folded out of the way, so that the disabled person in the wheelchair may be secured by their wheelchair brakes in a forward facing direction. One of the disadvantages of such arrangement is that the wheelchair takes up the space of the four foldable seats, primarily because of the size and shape of conventional wheelchairs.

Typically, when a disabled person in a wheelchair travels in a long distance bus, commonly referred to as a "coach", the person remains in their regular wheelchair during the trip. The wheelchair is loaded into the coach whilst the disabled person remains seated in it, and it is then strapped down to prevent it from moving whilst the coach is in motion. A disadvantage of this method of travel is that a conventional wheelchair occupies considerable space in a coach, reducing the number of conventional seats in the coach and also limiting the number of disabled people that can travel at once. A conventional wheelchair may occupy the space of

four conventional coach seats. There are known methods of removing seats from a bus when it is necessary to make space for conventional wheelchairs, but this still reduces the seating capacity of the bus when transporting a wheelchair and the removed bus seats must be stored outside of the bus or in the luggage compartment. A disadvantage is that some coaches require considerable time to remove and store their conventional seats, so that a disabled person in a wheelchair may use the coach. Another disadvantage, is that it is not always convenient to remove seats and leave them behind at a the location where they were removed, as according to varying circumstances a coach may need to take its removed seats with it, as it may be necessary for those removed seats to be reinstalled for a future journey, once the disabled person in a wheelchair disembarks. Where the coach is substantially full of passengers, the stowage of removed seats compromises the available luggage space.

There are also situations where coaches are engaged for a group of passengers, such as for tourism or sports club trips for a number of days or weeks. In such situation a passenger, may incur illness or injury during the coach trip which is not so bad to prevent travel, but makes boarding and alighting coach difficult. The prior art method of removing seats to allow for strapping down of wheelchairs, is usually not feasible in such situations.

WO 03/026548 (Baribunma Holdings) discloses an improved apparatus for securing a self-propelled wheelchair to the floor of a vehicle for transport. Whilst this method is preferable to strapping down a conventional wheelchair, the self-propelled wheelchair still occupies considerable space within the vehicle. Also, this method requires the disabled person's own wheelchair to have an anchoring mechanism that matches the anchoring element in the vehicle. Generally this method is intended for use in specially modified smaller vans, where the disabled person is either a passenger or the driver of the van. Due to the considerable space occupied by the self-propelled wheelchair, it cannot be used in a multi-seat larger bus without comprising the space that could otherwise be used for regular seating within the bus.

The term "bus" as used herein includes, but is not limited to, mini-buses, public buses and coaches.

The present invention seeks to overcome at least one of the disadvantages of the prior art.

SUMMARY OF INVENTION

The invention is defined in the independent claims. Some optional features of the invention are defined in the dependent claims. In a first example, there is a seat for a vehicle, said seat having an anchoring mechanism for releasably anchoring same to an anchoring element disposed on the

interior floor of said vehicle, said seat having wheels to enable it to be rolled within said vehicle when not anchored to the floor of the vehicle, the seat being temporarily removable from the vehicle for the purpose of seating a person in the seat whilst it is outside of the vehicle, before moving the seat back into the vehicle whilst the person remains seated in it, said wheels are retractable from a lowered position to a raised position, wherein in use when said wheels are in said lowered position and a person sitting in the seat is placed in the vehicle, said seat may be rolled to a position over said anchoring element, and then said wheels are raised thereby causing said seat to lower so that said anchoring mechanism may anchor to said anchoring element.

Preferably when said wheels are in said raised position they are stowed substantially below the base of said seat, and when they are in the lowered position they are extended so as to be disposed outwardly away from the base of the seat.

Preferably the wheels comprise two front wheels and two rear caster wheels, the front wheels being attached to a footrest that pivots upwards to retract the front wheels, and the rear caster wheels being attached to arms that pivot upwards to retract the rear caster wheels.

Preferably said anchoring mechanism comprises at least one anchoring projection that fits into a corresponding hook on the anchoring element, and at least one retractable pin that fits into a corresponding hole in the anchoring element.

Preferably in one embodiment a lever is operated to manually retract the wheels into the raised position, and to extend the wheels into the lowered position. Preferably in another embodiment electromechanical actuator is used to retract the wheels into the raised position, and to extend the wheels into the lowered position.

Preferably said vehicle is a bus, and said person is a disabled person.

In a second example, there is a method of transporting a person in a vehicle, said vehicle comprising a seat that is releasably anchored to an anchoring element disposed on the interior floor of said vehicle by an anchoring mechanism, said seat having wheels to enable it to be rolled inside said vehicle when not anchored to the interior floor of the vehicle, said wheels are retractable from a lowered rolling configuration to a raised anchoring configuration which allows said seat to be anchored to the interior floor of said vehicle, the said method comprising releasing the anchoring mechanism from said anchoring element and lowering said wheels to said lowered rolling configuration to thereby allow rolling of said seat

within said vehicle to allow removal from same, seating said person in said seat whilst it is outside said vehicle, moving said seat back into said vehicle whilst said person remains seated in it, rolling said seat to a position over said anchoring element, retracting said wheels to said raised anchoring configuration and anchoring said seat via said anchoring mechanism to said anchoring element.

In a third example, there is a seat for a bus, said seat having an anchoring mechanism for releasably anchoring same to an anchoring element disposed on the interior floor of said bus, said seat having wheels to enable it to be rolled within said bus when not anchored to the interior floor of the bus, said seat being temporarily removable from the bus for the purpose of seating a person in said seat whilst it is outside of the vehicle, before moving said seat back into said bus whilst the person remains seated in it, wherein said wheels are retractable between a lowered rolling configuration and a raised anchoring configuration, wherein in use when said wheels are in said lowered rolling configuration and a person sitting in said seat is placed in said bus, said seat may be rolled to a position over said anchoring element, and then said wheels are retracted to said anchoring configuration thereby allowing said seat to lower so that said anchoring mechanism may be anchored to said anchoring element.

Preferably said wheels are retracted into the raised anchoring configuration they are stowed substantially below the base of said seat, and when they are in the lowered rolling configuration they are extended so as to be disposed outwardly away from the base of said seat.

Preferably said seat is of a similar size and shape to other regular seats in said bus, and when said seat has its wheels retracted to said anchoring configuration and said seat is anchored to said anchoring element, said seat occupies a same amount of space as to said other regular seats.

Preferably the wheels comprise two front wheels and two rear caster wheels, said front wheels being attached to a footrest that pivots upwards to retract the front wheels, and the rear caster wheels being attached to arms that pivot upwards to retract the rear caster wheels, when the wheels are being moved from the lowered rolling configuration to the raised anchoring configuration.

Preferably in one embodiment a lever is operated to manually retract the wheels into said raised anchoring configuration, and to extend the wheels into said lowered rolling configuration. Preferably in another embodiment an electromechanical actuator is used to retract the wheels into said raised anchoring configuration, and to extend the wheels into said lowered rolling configuration.

In a fourth example there is a method of transporting a person in a bus, the bus comprising a plurality of regular seats and at least one rolling seat that is releasably anchored to anchoring element disposed on the interior of the bus by an anchoring mechanism, said rolling seat having wheels to enable it to be rolled when not anchored to the interior of the bus, said wheels are retractable from a lowered rolling configuration to a raised anchoring configuration which allows said rolling seat to be anchored to the interior floor of said bus, said method comprising releasing the anchoring mechanism from said anchoring element and lowering said wheels to said lowered rolling configuration to thereby allow rolling of said rolling seat within said bus to allow removal from same, seating said person in said rolling seat whilst it is outside said bus, moving said rolling seat back into said bus whilst said person remains seated in it, rolling said rolling seat to a position over said anchoring element, retracting said wheels to said raised anchoring configuration and anchoring said rolling seat via said anchoring mechanism to said anchoring element.

Preferably said rolling seat is of a similar size and shape to the regular seats in the bus, and when the rolling seat is in said raised anchoring configuration and said rolling seat is anchored to the interior of the bus, the rolling seat occupies the same amount of space as the other regular seats in the bus.

In a fifth example there is a bus comprising a plurality of regular seats and at least one rolling seat, said rolling seat having an anchoring mechanism for releasably anchoring same to an anchoring element disposed on the interior floor of said bus, said rolling seat having wheels to enable it to be rolled within said bus when not anchored to the interior floor of the bus, said rolling seat being temporarily removable from the bus for the purpose of seating a person in said rolling seat whilst it is outside of said bus, before moving said seat back into said bus whilst the person remains seated in it, wherein said wheels are retractable between a lowered rolling configuration and a raised anchoring configuration, wherein in use when said wheels are in said lowered rolling configuration and a person sitting in said rolling seat is placed in said bus, said rolling seat may be rolled to a position over said anchoring

element, and then said wheels are retracted to said anchoring configuration thereby allowing said rolling seat to lower so that said anchoring mechanism may be anchored to said anchoring element.

Preferably said rolling seat is of a similar size and shape to the plurality of regular seats in the bus, and when said rolling seat is in said raised anchoring configuration and said rolling seat is anchored to anchoring element, said rolling seat occupies a similar space to the other regular seats in the bus.

BRIEF DESCRIPTION OF DRAWINGS

Fig. 1 is a side view of a vehicle seat for a disabled person, with its wheels in a lowered rolling configuration.

Fig. 2 is a side view of the seat shown in Fig. 1, with its wheels lowered for rolling the seat, showing some hidden detail of the mechanism that retracts the wheels.

Fig. 3 is a side view of the seat shown in Fig. 1, with its wheels raised for anchoring the seat, showing some hidden detail of the mechanism that retracts the wheels.

Fig. 4 is a side view of the seat shown in Fig. 1, anchored to the floor of a bus.

Fig. 5 is a rear view of the seat shown in Fig. 1, anchored to the floor of a bus.

Fig. 6 is a perspective view of an anchor element for anchoring the seat shown in Fig. 1.

Fig. 7 is a front perspective view of the seat shown in Fig. 1, but with the wheels in a retracted configuration.

Fig. 8 is a front perspective view of the seat shown in Fig. 1.

Fig. 9 is a front perspective view of the seat shown in Fig. 1 with the wheels in a retracted configuration and anchored to the anchoring element.

Fig. 10 is a rear perspective view of the seat shown in Fig. 9.

DESCRIPTION OF PREFERRED EMBODIMENTS

Figs. 1 to 5, 7 and 8 show a vehicle seat 1 for a disabled person. Seat 1 comprises a base 4 that supports a lower cushion 3, a back rest 2, and a pair of arm rests 5. In this embodiment, seat 1 is for use in coach type buses. Seat 1 is of similar size and shape to the other regular seats (not shown) in the coach in that its lower cushion 3

and back rest 2 are similar to those of the regular seats, and the height of lower cushion 3 is also similar to that of the regular seats. Seat 1 may be constructed by modifying a regular seat.

Base 4 has two parallel vertical sides 18, on either side of seat 1, extending from the bottom of seat 1 up to the underside of lower cushion 3. A pair of free rolling front wheels 6 is attached to a pivoting footrest 8, and a pair of rear caster wheels 7 is pivotally attached to a pair of pivoting rear arms 9 that extend from the rear of base 4. As can be seen in Fig. 5, front wheels 6 are spaced outside of sides 18 of base 4, and rear caster wheels 7 are spaced apart within sides 18, such that front wheels 6 are spaced apart wider than rear wheels 7. Figs. 1, 2 and 8 show wheels 6 and 7 in a "lowered rolling configuration" to enable seat 1 to be rolled along the ground, or inside a bus, using handles 10 attached to backrest 2. In this lowered rolling configuration, wheels 6 and 7 support the weight of seat 1, and base 4 is clear of the ground by a distance that is adequate to not scrape the bottom of base 4 as seat 1 is rolled.

Fig. 3, 4 and 7 shows wheels 6 and 7 retracted to a "raised anchoring configuration" for anchoring seat 1 to the floor of a bus. To achieve this configuration, footrest 8 pivots upwards about its pivot 11 until front wheels 7 are substantially tucked under the front of lower cushion 3, and rear arms 9 pivot upwards about their pivot 12 until rear caster wheels 7 are substantially tucked under the rear of lower cushion 3. In this raised anchoring configuration, seat 1 is compacted such that it occupies approximately the same space as a regular seat.

Footrest 8 and rear arms 9 are connected by a linkage 13, as shown in hidden detail in Figs. 2 and 3, such that they raise and lower together. A lever 14 at the back of seat 1 is manually swung downwards and upwards, as shown in Fig. 3, to retract and extend wheels 6 and 7 to their raised and lowered positions by operating a mechanism (not shown) connected to footrest 8 and rear arms 9. Lever 14 is biased upwards by a spring (not shown). In other not shown embodiments, lever 14 may be extendable to provide additional leverage.

Seat 1 has an anchoring mechanism comprising two front anchoring projections 15, two rear anchoring projections 16, and two retractable pins 17. Anchoring projections 15 and 16 are short solid rods attached to the bottom of base 4. Front anchoring projections 15 are positioned at the front of each of the two sides 18 of base 4, and extend a short distance inwards from each side 18. Rear anchoring projections 16 are positioned at the back of each of the two sides 18, and extend a short distance outwards from each side 18.

One retractable pin 17 is positioned on each side 18 of base 4, between front and rear projections 15, 16, a short distance from the bottom of base 4. Retractable pins 17 slide in corresponding holes in sides 18 and are biased by springs (not shown) such that they normally protrude outwardly from each side 18. A handle 19 is attached to the top of a sliding rod 20 at the back of seat 1. A cable mechanism 21, shown in hidden details in Figs. 2 and 3, connects the bottom of rod 20 to retractable pins 17 to retract pins 17 flush with sides 18 when handle 19 is manually lifted.

Figs. 4 and 5 show seat 1 releasably anchored to the floor 23 of the bus by means of its anchoring mechanism 15, 16, 17 engaging an anchoring element 22 attached to the floor 23. Referring to Fig. 6, anchoring element 22 comprises a horizontal base plate 24 that bolts to floor 23, and two vertical side plates 25 parallel to the sides 18 of seat base 4, spaced apart slightly wider than base 4. Two rear hooks 26 are formed in the rear end of side plates 25, each with an opening facing the rear of anchoring element 22. Two front hooks 27 are attached near the front of anchoring element 22, spaced apart inside side plates 25, and each with an opening facing the rear of anchoring element 22. Each side plate 25 has a hole 28 through it. Seat 1 engages anchor plate 22 by front anchoring projections 15 fitting into front hooks 27, rear anchoring projections 16 fitting into rear hooks 26, and retractable pins 17 fitting into holes 28.

The method of operation of seat 1 will now be described. Starting with an empty seat 1 anchored to the bus floor 23 as shown in Figs. 4 and 5, seat 1 is released from anchor element 22 by lifting handle 19 to retract pins 17 clear of side plates 25 and pulling seat 1 a short distance backwards until projections 15 and 16 are clear of hooks 26 and 27. Lever 14 is then operated to lower wheels 6 and 7, which raises seat 1 and enables it to be rolled using handle 10. Seat 1 is then temporarily removed from the bus, and rolled on the ground outside of the bus to position it as required.

A disabled person is then seated in seat 1 whilst it is outside of the bus. Typically the disabled person will initially be seated in a conventional wheelchair. The person is then transferred to seat 1 with aid of other people or a lifting means. If required, the conventional wheelchair can be collapsed and stowed in the luggage compartment of the bus. Seat 1 is then moved back into the bus, by rolling and lifting. It is then anchored back into anchor element 22 using the reverse of the procedure for releasing it, as follows. Seat 1 is rolled over anchor element 22 and lowered by raising wheels 6 and 7 with handle 19 lifted to retract pins 17. Seat 1 is then

pushed forward such that projections 15 and 16 fit into hooks 26 and 27, and pins 17 will spring out into holes 28 when they align.

The advantage of using seat 1 over the prior art method of placing a conventional wheelchair inside of the bus is that seat 1 only occupies the same amount of space as a regular bus seat, enabling more passengers, disabled or otherwise, to travel in the bus. Furthermore, as the seatings portions 2, 3 of seat 1 are similar in size and shape to a regular seat when it is anchored to the floor of the bus, it can be used by non-disabled people when not required for disabled people.

Whilst the abovementioned embodiment utilises an actuator mechanism that is manually actuated via handle 19 and cable mechanism 21, it should be understood that in another not shown embodiment the actuator mechanism may employ an electromechanical actuator. Such an electromechanical actuator may be triggered by a switch or button, and powered by either a rechargeable battery or by power provided from the electrical power supply of the bus. For instance a "power supply contact" (not shown) may be associated with anchoring element 22 fitted to the bus. When seat 1 is brought into engagement with anchoring element 22 and pins 17 locked into place, power may be supplied from the bus to recharge a rechargeable battery or directly power a electromechanical actuator for raising the wheels 6 and 7.

Whilst the embodiment of the seat described above is intended for buses, the invention is equally applicable to disabled seating in other types of passenger vehicles.

The terms "comprising" and "including" (and their grammatical variations) as used herein are used in an inclusive sense and not in the exclusive sense of "consisting only of".

CLAIMS:

1. A seat for a vehicle, said seat having an anchoring mechanism for releasably anchoring same to an anchoring element disposed on the interior floor of said vehicle, said seat having wheels to enable it to be rolled within said vehicle when not anchored to the floor of the vehicle, the seat being temporarily removable from the vehicle for the purpose of seating a person in the seat whilst it is outside of the vehicle, before moving the seat back into the vehicle whilst the person remains seated in it, said wheels are retractable from a lowered position to a raised position , wherein in use when said wheels are in said lowered position and a person sitting in the seat is placed in the vehicle, said seat is configured to be rolled to a position over said anchoring element, and then for said wheels to be raised thereby for said seat to lower so that said anchoring mechanism may anchor to said anchoring element.
2. A seat for a vehicle as claimed in claim 1, configured so that when said wheels are in said raised position they are stowed substantially below the base of said seat, and when they are in the lowered position they are extended so as to be disposed outwardly away from the base of the seat.
3. A seat for a vehicle as claimed in claim 1, wherein the wheels comprise two front wheels and two rear caster wheels, the front wheels being attached to a footrest that pivots upwards to retract the front wheels, and the rear caster wheels being attached to arms that pivot upwards to retract the rear caster wheels.
4. A seat for a vehicle as claimed in claim 1, wherein said anchoring mechanism comprises at least one anchoring projection for fitting into a corresponding hook on the anchoring element, and at least one retractable pin for fitting into a corresponding hole in the anchoring element.
5. A seat for a vehicle as claimed in claim 1, wherein a lever is operable to manually retract the wheels into the raised position, and to extend the wheels into the lowered position.
6. A seat for a vehicle as claimed in claim 1, wherein an electromechanical actuator is configured to retract the wheels into the raised position, and to extend the wheels into the lowered position.

7. A seat for a vehicle as claimed in claim 1, wherein said vehicle is a bus.
8. A seat for a vehicle as claimed in claim 1, wherein said person is a disabled person.
9. A method of transporting a person in a vehicle, said vehicle comprising a seat that is releasably anchored to an anchoring element disposed on the interior floor of said vehicle by an anchoring mechanism, said seat having wheels to enable it to be rolled inside said vehicle when not anchored to the interior floor of the vehicle, said wheels are retractable from a lowered rolling configuration to a raised anchoring configuration which allows said seat to be anchored to the interior floor of said vehicle, the said method comprising releasing the anchoring mechanism from said anchoring element and lowering said wheels to said lowered rolling configuration to thereby allow rolling of said seat within said vehicle to allow removal from same, seating said person in said seat whilst it is outside said vehicle, moving said seat back into said vehicle whilst said person remains seated in it, rolling said seat to a position over said anchoring element, retracting said wheels to said raised anchoring configuration and anchoring said seat via said anchoring mechanism to said anchoring element.
10. A seat for a bus, said seat having an anchoring mechanism for releasably anchoring same to an anchoring element disposed on the interior floor of said bus, said seat having wheels to enable it to be rolled within said bus when not anchored to the interior floor of the bus, said seat being temporarily removable from the bus for the purpose of seating a person in said seat whilst it is outside of the vehicle, before moving said seat back into said bus whilst the person remains seated in it, wherein said wheels are retractable between a lowered rolling configuration and a raised anchoring configuration, wherein in use when said wheels are in said lowered rolling configuration and a person sitting in said seat is placed in said bus, said seat is configured to be rolled to a position over said anchoring element, and then for said wheels to be retracted to said anchoring configuration thereby allowing said seat to lower so that said anchoring mechanism may be anchored to said anchoring element.
11. A seat for a bus as claimed in claim 10, configured so that when said wheels are retracted into the raised anchoring configuration they are stowed substantially below the base of said seat, and when they are in the lowered rolling configuration they are extended so as to be disposed outwardly away from the base of said seat.

12. A seat for a bus as claimed in claim 10, wherein said seat is of a similar size and shape to other regular seats in said bus, and configured so that when said seat has its wheels retracted to said anchoring configuration and said seat is anchored to said anchoring element, said seat occupies a same amount of space as to said other regular seats.
13. A seat for a bus as claimed in claim 10, wherein the wheels comprise two front wheels and two rear caster wheels, said front wheels being attached to a footrest that pivots upwards to retract the front wheels, and the rear caster wheels being attached to arms that pivot upwards to retract the rear caster wheels, when the wheels are being moved from the lowered rolling configuration to the raised anchoring configuration.
14. A seat for a bus as claimed in claim 13, wherein a lever is operable to manually retract the wheels into said raised anchoring configuration, and to extend the wheels into said lowered rolling configuration.
15. A seat for a bus as claimed in claim 13, wherein an electromechanical actuator is configured to retract the wheels into said raised anchoring configuration, and to extend the wheels into said lowered rolling configuration.
16. A method of transporting a person in a bus, the bus comprising a plurality of regular seats and at least one rolling seat that is releasably anchored to anchoring element disposed on the interior floor of the bus by an anchoring mechanism, said rolling seat having wheels to enable it to be rolled when not anchored to the interior of the bus, said wheels are retractable from a lowered rolling configuration to a raised anchoring configuration which allows said rolling seat to be anchored to the interior floor of said bus, said method comprising releasing the anchoring mechanism from said anchoring element and lowering said wheels to said lowered rolling configuration to thereby allow rolling of said rolling seat within said bus to allow removal from same, seating said person in said rolling seat whilst it is outside said bus, moving said rolling seat back into said bus whilst said person remains seated in it, rolling said rolling seat to a position over said anchoring element, retracting said wheels to said raised anchoring configuration and anchoring said rolling seat via said anchoring mechanism to said anchoring element.

17. A method of transporting a person in a bus as claimed in claim 16, wherein said rolling seat is of a similar size and shape to the regular seats in the bus, and when the rolling seat is in said raised anchoring configuration and said rolling seat is anchored to the interior of the bus, the rolling seat occupies the same amount of space as the other regular seats in the bus.
18. A bus comprising a plurality of regular seats and at least one rolling seat, said rolling seat having an anchoring mechanism for releasably anchoring same to an anchoring element disposed on the interior floor of said bus, said rolling seat having wheels to enable it to be rolled within said bus when not anchored to the interior floor of the bus, said rolling seat being temporarily removable from the bus for the purpose of seating a person in said rolling seat whilst it is outside of said bus, before moving said seat back into said bus whilst the person remains seated in it, wherein said wheels are retractable between a lowered rolling configuration and a raised anchoring configuration, wherein in use when said wheels are in said lowered rolling configuration and a person sitting in said rolling seat is placed in said bus, said rolling seat is configured to be rolled to a position over said anchoring element, and then for said wheels to be retracted to said anchoring configuration thereby allowing said rolling seat to lower so that said anchoring mechanism may be anchored to said anchoring element.
19. A bus as claimed in claim 18, wherein said rolling seat is of a similar size and shape to the plurality of regular seats in the bus, and configured so that when said rolling seat is in said raised anchoring configuration and said rolling seat is anchored to anchoring element, said rolling seat occupies a similar space to the other regular seats in the bus.