

DESCRIPTION

Title of Invention: TRANSPORT VEHICLE SYSTEM

Technical Field

5 [0001] One aspect of the present invention relates to a transport vehicle system.

Background Art

[0002] There is known an overhead transport vehicle in which a traveling part configured to travel on a track installed on a ceiling and the like and a lifting part including a gripping part configured to transfer
10 an article to a transfer part such as a shelf or a load port are provided. The lifting part is suspended and held by a plurality of suspending members such as a belt, and configured to be lifted and lowered by winding or paying out the suspending members. In such an overhead transport vehicle, the lifting part is required to be maintained in parallel
15 with the transfer part (in a case in which the transfer part is horizontal, the lifting part is required to be horizontal) during lifting or lowering.

[0003] For example, Patent Document 1 discloses an overhead transport vehicle in which fixed end positions of suspending members with respect to a drum and an unwinding angle of both suspending members
20 extending from a winding surface of the drum are set so that accumulation of winding differences per rotation of the drum caused by deviation of timing when the two suspending members (lifting belts) that are double wound shift to winding of the next layer is smaller than a predetermined value with which the lifting part (placement table) can be
25 held at a required horizontal degree. With this overhead transport vehicle, the winding difference between the two suspending members

can be suppressed to fall within a permissible range, and the article can be horizontally gripped irrespective of a lifting position.

Citation List

Patent Literature

- 5 [0004] [Patent Document 1] Japanese Unexamined Patent Publication No. H10-194410

Summary of Invention

Technical Problem

- 10 [0005] However, even if the winding difference between the two suspension members is kept within the permissible range by the above-described conventional method, the characteristics of each overhead transport vehicle (that is, machine differences) may possibly prevent the state of the lifting part from being appropriately adjusted during lifting and lowering.

- 15 [0006] Accordingly, an object of one aspect of the present invention is to provide a transport vehicle system in which the state of the lifting part can be appropriately adjusted for each overhead transport vehicle without human intervention.

Solution to Problem

- 20 [0007] A transport vehicle system according to one aspect of the present invention is a transport vehicle system equipped with an overhead transport vehicle in which a lifting part having a gripping part for gripping an article is lifted and lowered by a plurality of suspending members, the transport vehicle including a measuring part configured to
- 25 measure a measurement target portion, a measured part on which the measurement target portion is formed, and a control part configured to

cause the lifting part to be lifted and lowered according to a predetermined set value, and the control part controls lifting and lowering of the lifting part so that the measuring part is able to measure the measured part by one of the measuring part and the measured part gripped by the gripping part and by the other of the measuring part formed or placed at a predetermined position and the measured part formed or placed on a predetermined position, and corrects the set value based on a result of measurement of the measured part made by the measuring part.

[0008] In the overhead transport vehicle, the lifting part is controlled based on a predetermined set value when lifted or lowered, but in the transport vehicle system of the present invention, the set value is appropriately corrected based on the measurement result acquired by the measured part and the measuring part (that is, information considered to be indicative of the current state of the lifting part when the lifting part is lifted and lowered to a transfer part). This makes it possible to appropriately adjust the state of the lifting part for each overhead transport vehicle without human intervention.

[0009] In the transport vehicle system according to one aspect of the present invention, one of the measuring part and the measured part may be formed as a first unit member grippable by the gripping part, the other of the measuring part and the measured part may be formed as a second unit member placeable at the predetermined position, and one of the first unit member and the second unit member may be placed at the predetermined position in a state of being supported by the other of the first unit member and the second unit member. With this

configuration, automatic measurement by the measuring part and the measured part can be executed rapidly.

5 [0010] The transport vehicle system according to one aspect of the present invention may further include a communication unit configured to transmit the result of measurement of the measured part made by the measuring part to a control device provided in the overhead transport vehicle, and the measured part may be used in a state of being gripped by the gripping part and the measuring part may be used in a state of being placed at the predetermined position. With this configuration,
10 automatic measurement by the measuring part and the measured part is feasible without significantly changing the configuration of the overhead transport vehicle.

[0011] The transport vehicle system according to one aspect of the present invention may further include a maintenance trestle that is
15 provided in a traveling area of the overhead transport vehicle and on which a placement table to be the predetermined position is formed. With this configuration, separately from a placement part, a position where automatic measurement by the measuring part and the measured part is enabled is provided, so that the overhead transport vehicle can be
20 measured efficiently.

[0012] In the overhead transport vehicle system according to one aspect of the present invention, the overhead transport vehicle may have a body part, the lifting part provided in a manner of being able to be lifted and lowered with respect to the body part by the suspending members
25 being wound and unwound, and a sliding part configured to move the lifting part in a direction orthogonal to both a transport direction of the

overhead transport vehicle and the vertical direction, and the maintenance trestle may include a first placement table provided at a position where the article is placeable by lowering the lifting part without activating the sliding part, a second placement table provided
5 above the first placement table in the vertical direction and provided to be retractable in a horizontal direction from an area above the first placement table in the vertical direction, and a third placement table provided at a position where the article is placeable by activating at least the sliding part. With this configuration, in each of the placement part
10 provided at a relatively low position with respect to the traveling position of the overhead transport vehicle, the placement part provided at a relatively high position, and the placement part on which placing is performed by activating the sliding part, the inclination of the lifting part for each overhead transport vehicle can be appropriately adjusted.

15 [0013] In the transport vehicle system according to one aspect of the present invention, the control part may cause the overhead transport vehicle to periodically move to the maintenance trestle and cause the measuring part to measure the measured part. With this configuration, periodic adjustments to the set value can be made.

20 [0014] In the transport vehicle system according to one aspect of the present invention, the set value may be set for each placement part for the article, one of the measuring part and the measured part may be used in a state of being gripped by the gripping part, and the other of the measuring part and the measured part may be used in a state of being
25 formed or placed on the placement part to be a measurement target. With this configuration, an adjustment of the optimal set value for each

placement part can be made.

[0015] In the transport vehicle system according to one aspect of the present invention, the overhead transport vehicle may include a winding drum configured to lift and lower the lifting part by winding and unwinding the suspending members, at least one guide roller around which the suspending members unwound from the winding drum are wound, a body part supporting the winding drum and the guide roller, at least one position adjustment part configured to move a connection portion of the suspending members with the lifting part in a lifting-and-lowering direction by moving a relative position of the guide roller with respect to the body part, and a control device configured to control a movement of the guide roller by the position adjustment part based on information about inclination of the lifting part, and the set value may include the information about inclination. With this configuration, the inclination of the lifting part can be adjusted with a simple configuration.

Advantageous Effects of Invention

[0016] According to one aspect of the present invention, it is possible to appropriately adjust the state of the lifting part for each overhead transport vehicle without human intervention.

Brief Description of Drawings

[0017] FIG. 1 is a side view of an overhead transport vehicle according to an embodiment.

FIG. 2 is a front view of a holding unit.

FIG. 3 is a perspective view of a first buffering mechanism and a second buffering mechanism.

FIG. 4 is a front view of a lifting drive unit.

FIG. 5 is a side view of the lifting drive unit.

FIG. 6(A) and FIG. 6(B) are front views illustrating the operation of the lifting drive unit.

5 FIG. 7(A) and FIG. 7(B) are side views illustrating the operation of the lifting drive unit.

FIG. 8 is a perspective view of a measuring unit and a measured unit.

10 FIG. 9 is a schematic diagram illustrating measurement targets of each distance sensor when the measuring unit measures the measured unit.

FIG. 10(A) to FIG. 10(C) are schematic diagrams illustrating a method in which a unit controller calculates the state of the overhead transport vehicle.

15 FIG. 11 is a block diagram illustrating a functional configuration of a transport vehicle system.

FIG. 12(A) is a side view illustrating a maintenance trestle and FIG. 12(B) is a plan view illustrating the maintenance trestle viewed from direction B in FIG. 12(A).

20 FIG. 13(A) and FIG. 13(B) are diagrams for explaining the procedure for acquiring the state of the overhead transport vehicle using the maintenance trestle.

FIG. 14(A) and FIG. 14(B) are diagrams for explaining the procedure for acquiring the state of the overhead transport vehicle using the maintenance trestle.

25

FIG. 15 is a diagram for explaining the procedure for acquiring

the state of the overhead transport vehicle using the maintenance trestle.

Description of Embodiments

[0018] A preferred embodiment of one aspect of the present invention will be described in detail below with reference to the accompanying drawings. In the description of the drawings, the same elements are denoted by the same reference signs, and redundant descriptions are omitted.

[0019] A transport vehicle system 100 of one embodiment includes a plurality of overhead transport vehicles 1 (see FIG. 1), a track 20 (see FIG. 1) forming a travel path for the overhead transport vehicles 1, an area controller 110 (see FIG. 11), a measuring unit (measuring part) 80 (see FIG. 11), and a measured unit (measured part) 90 (see FIG. 8). At least one of the overhead transport vehicles 1 includes a linear motion mechanism (position adjustment part) 67 (see FIG. 4) configured to adjust the inclination of a holding unit (lifting part) 7 with respect to the horizontal plane.

[0020] As illustrated in FIG. 1, an overhead transport vehicle 1 according to the embodiment travels along the track 20 installed in the vicinity of a ceiling of a clean room in which semiconductor devices are manufactured. The overhead transport vehicle 1 according to the embodiment carries a front opening unified pod (FOUP) (article) 200 housing a plurality of semiconductor wafers, and transfers the FOUP 200 to a load port (transfer part) 300 and the like provided on a processing device configured to perform various kinds of processing on the semiconductor wafers.

[0021] As illustrated in FIG. 1 and FIG. 11, the overhead transport

vehicle 1 includes a frame unit 2, a traveling unit 3, a lateral unit 4, a theta unit 5, a lifting drive unit 6, a holding unit 7, a transport vehicle controller (control part) 8, a storage unit 8A, and a communication unit 9. The frame unit 2 includes a center frame 15, a front frame 16, and a rear frame 17. The front frame 16 extends downward from an end part on a front side of the center frame 15 (front side in a traveling direction of the overhead transport vehicle 1). The rear frame 17 extends downward from an end part on a rear side of the center frame 15 (rear side in the traveling direction of the overhead transport vehicle 1).

[0022] The traveling unit 3 is disposed on an upper side of the center frame 15. For example, the traveling unit 3 travels along the track 20 by receiving electric power supplied from a high-frequency current line installed along the track 20 in a non-contact manner. The lateral unit 4 is disposed on a lower side of the center frame 15. The lateral unit 4 causes the theta unit 5, the lifting drive unit 6, and the holding unit 7 to move in a lateral direction (a lateral side in the traveling direction of the overhead transport vehicle 1). The theta unit 5 is disposed on a lower side of the lateral unit 4. The theta unit 5 turns the lifting drive unit 6 and the holding unit 7 in a horizontal plane.

[0023] The lifting drive unit 6 is disposed on a lower side of the theta unit 5. The lifting drive unit 6 causes the holding unit 7 to be lifted and lowered. The holding unit 7 is disposed on a lower side of the lifting drive unit 6. The holding unit 7 holds a flange 201 of the FOUP 200.

[0024] The transport vehicle controller (control part) 8 is disposed in the center frame 15. The transport vehicle controller 8 is an electronic

control unit including a central processing unit (CPU), read-only memory (ROM), random access memory (RAM), and the like. The transport vehicle controller 8 controls respective parts of the overhead transport vehicle 1.

5 [0025] By way of example, the overhead transport vehicle 1 configured as described above operates as follows. In a case of transferring the FOUP 200 to the overhead transport vehicle 1 from the load port 300, the overhead transport vehicle 1 not holding the FOUP 200 stops at a predetermined position above the load port 300. If the position of the
10 holding unit 7 that lowers at the stop position deviates from a predetermined position with respect to the load port 300 (FOUP 200 placed on the load port 300), the horizontal position and the horizontal angle of the holding unit 7 are adjusted by driving the lateral unit 4 and the theta unit 5. If the holding unit 7 lowered by paying out the belts
15 (suspending members) B is inclined with respect to the horizontal plane, the inclination of the holding unit 7 is adjusted by activating the linear motion mechanism 67 (see FIG. 4).

[0026] The transport vehicle controller 8 performs, based on the set values stored in the storage unit 8A, adjustments of the horizontal
20 position and horizontal angle of the holding unit 7 and the inclination of the holding unit 7. Subsequently, the lifting drive unit 6 lowers the holding unit 7, and the holding unit 7 holds the flange 201 of the FOUP 200 placed on the load port 300. Then, the lifting drive unit 6 lifts the holding unit 7 up to a lifting end, and disposes the FOUP 200 between
25 the front frame 16 and the rear frame 17. Subsequently, the overhead transport vehicle 1 holding the FOUP 200 starts to travel.

[0027] Meanwhile, in a case of transferring the FOUP 200 from the overhead transport vehicle 1 to the load port 300, the overhead transport vehicle 1 holding the FOUP 200 stops at a predetermined position above the load port 300. If the position of the holding unit 7 (FOUP 200) to be lowered at the stop position deviates from the predetermined position with respect to the load port 300, the horizontal position and horizontal angle of the holding unit are adjusted by driving the lateral unit 4 and the theta unit 5. If the holding unit 7 lowered by paying out the belts B is inclined with respect to the horizontal plane, the inclination of the holding unit 7 is adjusted by activating the linear motion mechanism 67 (see FIG. 4).

[0028] The transport vehicle controller 8 performs, based on the set values stored in the storage unit 8A, adjustments of the horizontal position and horizontal angle of the holding unit 7 and the inclination of the holding unit 7. Subsequently, the lifting drive unit 6 lowers the holding unit 7, the FOUP 200 is placed on the load port 300, and the holding unit 7 releases the flange 201 of the FOUP 200. Then, the lifting drive unit 6 lifts the holding unit 7 up to the lifting end. Subsequently, the overhead transport vehicle 1 not holding the FOUP 200 starts to travel.

[0029] Next, the following describes a configuration of the holding unit 7 in detail. As illustrated in FIG. 1 and FIG. 2, the holding unit 7 has a base 11, a pair of grippers (gripping parts) 12 and 12, and a housing 13. The pair of grippers 12, 12 is supported by the base 11 so as to be openable and closeable along the horizontal direction. The pair of grippers 12, 12 is opened or closed by a driving motor (not illustrated)

and a link mechanism (not illustrated). In the present embodiment, the height position of the holding unit 7 is adjusted so that the holding surfaces of the grippers 12 are lower than the height of the lower surface of the flange 201 when the pair of grippers 12, 12 is in an opened state.

5 In this state, as the pair of grippers 12, 12 is then in a closed state, the holding surfaces of the grippers 12 advance toward the lower surface of the flange 201, and as the lifting drive unit 6 is lifted in this state, the flange 201 is held (gripped) by the pair of grippers 12, 12 and the FOUP 200 is supported. In the holding unit 7, the base 11 constitutes a
10 bottom wall of the housing 13, and the position thereof with respect to the housing 13 is fixed.

[0030] As illustrated in FIG. 3, in the holding unit 7 of the present embodiment, one ends of the belts B are connected via a first buffering mechanism 50 and a second buffering mechanism 40. The following
15 describes the first buffering mechanism 50 and the second buffering mechanism 40 in detail. The first buffering mechanism 50 and the second buffering mechanism 40 are mechanisms configured to couple the belts B to the holding unit 7 (see FIG. 1), and are mechanisms configured to prevent vibration, which is caused when the traveling unit
20 3 travels or the holding unit 7 is lifted or lowered, from being transmitted to the FOUP 200.

[0031] The first buffering mechanism 50 has elastic members 58 that support the base 11 to be movable vertically from below in the vertical direction, and is disposed on one side in the width direction orthogonal
25 to the traveling direction of the overhead transport vehicle 1 in a plan view seen from the vertical direction. In the present embodiment, the

first buffering mechanism 50 is provided on the right side of the holding unit 7 in the left-and-right direction. The first buffering mechanism 50 has connection members 51, swing members 53, first body members 54, a second body member 56, and a pair of the elastic members 58, 58.

5 The left-and-right direction in the present embodiment means the left-and-right direction when the overhead transport vehicle 1 is viewed from the front in the traveling direction.

[0032] The connection member 51 is a member attached to the belt B. The swing member 53 is a member coupled to the connection member 51. The swing member 53 is coupled to the connection member 51 to be rotatable bidirectionally via a pin member 52. The first body member 54 is a substantially L-shaped member, and the bottom part thereof is formed to be flat. The upper end of the first body member 54 is connected to the swing member 53. The bottom part of the first body member 54 is connected to the second body member 56 by a bolt and the like. The second body member 56 supports the elastic members 58 from below and also supports the bottom parts of the first body members 54.

[0033] The pair of elastic members 58, 58 are coil springs each having a predetermined spring constant. The pair of elastic members 58, 58 are supported by the second body member 56 and support the base 11 from below. The lower end of the elastic member 58 is fixed to the second body member 56. The upper end of the elastic member 58 is not fixed to the base 11, but supports the base 11 in contact. That is, each of the pair of elastic members 58, 58 urges the second body member 56 and the base 11 in a direction to be away from each other

when in a contracted state being in contact with both the second body member 56 and the base 11. The elastic member 58 has the role of reducing vibration transmitted between the members being in contact with each other. It may be fixed to the base 11 and provided to be
5 separable from and contactable to the second body member 56.

[0034] The second buffering mechanism 40 has elastic members 48 that support the base 11 to be movable vertically from below in the vertical direction, and is disposed on the other side in the width direction (opposite side to the first buffering mechanism 50 in the width
10 direction) that is orthogonal to the traveling direction of the overhead transport vehicle 1 in a plan view seen from the vertical direction. In the present embodiment, the second buffering mechanism 40 is provided on the left side of the holding unit 7 in the left-and-right direction. The second buffering mechanism 40 has connection
15 members 41, 41, swing members 43, a third body member 45, a fourth body member 46, a restriction member 47, and a pair of elastic members 48, 48.

[0035] The connection members 41, 41 are members to which belts B, B are respectively attached. The swing member 43 is a member
20 configured to couple the pair of connection members 41, 41 to the third body member 45. The pair of connection members 41, 41 and the swing members 43 are coupled to be bidirectionally rotatable and are coupled via a pair of pin members 42, 42. The swing members 43 and the third body member 45 are coupled to be bidirectionally rotatable via
25 a pin member 44. The fourth body member 46 supports the elastic members 48, 48 from below.

[0036] The pair of elastic members 48, 48 are coil springs each having a predetermined spring constant. The pair of elastic members 48, 48 are supported by the fourth body member 46 and also support the base 11 from below. The lower end of the elastic member 48 is fixed to the fourth body member 46. The restriction member 47 restricts the base 11 from being separated from the fourth body member 46 by more than a predetermined distance. In more detail, the restriction member 47 locks the top surface of the base 11 that tries to go away from the fourth body member 46 by more than the predetermined distance. The upper end of the elastic member 48 is not fixed to the base 11, but supports the base 11 in contact. That is, each of the pair of elastic members 48, 48 urges the fourth body member 46 and the base 11 in the direction to be away from each other, when in a contracted state being in contact with both the fourth body member 46 and the base 11. The elastic member 48 has the role of reducing vibration transmitted between the members being in contact with each other. The elastic member 48 may be fixed to the base 11 and provided to be separable from and contactable to the fourth body member 46.

[0037] Although not illustrated, the holding unit 7 may be provided with a link mechanism that couples the first buffering mechanism 50 and the second buffering mechanism 40 and operates to make each of the distance between the first buffering mechanism 50 and the base 11 in the vertical direction and the distance between the second buffering mechanism 40 and the base 11 in the vertical direction closer together.

[0038] Next, the following describes a configuration of the lifting drive unit 6 in detail. As illustrated in FIG. 4 and FIG. 5, the lifting drive

unit 6 has a base (body part) 61, a supporting part 62, four (a plurality of) winding drums 63, a driving motor (winding drive part) 63A, first idler rollers (guide rollers) 65A, second idler rollers (guide rollers) 65B, third idler rollers (guide rollers) 64, linear motion mechanisms (position adjustment parts) 67, swing members 68, and four (a plurality of) belts B.

[0039] The base 61 supports the winding drums 63, the first idler rollers 65A, and the third idler rollers 64 via the supporting part 62. The supporting part 62 supports the four winding drums 63 in a rotatable manner. The four winding drums 63 are arranged in the front and rear direction, and winds or pays out each of the four belts B by being driven by the driving motor 63A. The supporting part 62 supports the first idler roller 65A and one end part 68A of the swing member 68 in a swingable manner.

[0040] Each of the winding drums 63 is attached to the base 61 via the supporting part 62 in a rotatable manner. The driving motor 63A is a driving source for rotating each of the winding drums 63, and fixed to the base 61. The four winding drums 63 are driven by the one driving motor 63A by being attached to a common rotating shaft (not illustrated), or by being coupled to each other via an interlocking mechanism (not illustrated).

[0041] One end of each belt B is connected to the holding unit 7, and the other end of each belt B is connected to each winding drum 63. In the present embodiment, the four belts B are provided to suspend three points of the holding unit 7. More specifically, the holding unit 7 is suspended by the four belts B. Two of the four belts B are connected

to the one swing member 43 (refer to FIG. 3) that is provided in a swingable manner with respect to the holding unit 7 via the connection members 41, and the remaining two of the four belts are respectively connected to swing members 53 that are provided in a swingable manner with respect to the holding unit 7 via connection members 51.

[0042] The first idler roller 65A and the second idler roller 65B guide movement of the belt B connected to the first buffering mechanism 50. The two belts B are connected to the first buffering mechanism 50, and the first idler roller 65A and the second idler roller 65B are provided corresponding to each of the belts B. The first idler roller 65A is provided on the supporting part 62, and does not move relatively to the base 61. The second idler roller 65B is provided on the swing member 68 (described later), and moves relatively to the base 61. The configuration in which the second idler roller 65B moves relatively to the base 61 will be described at a latter stage. The third idler roller 64 guides movement of the belt B connected to the second buffering mechanism 40. The two belts B are connected to the second buffering mechanism 40, and the third idler roller 64 is provided corresponding to each of the belts B.

[0043] The linear motion mechanism 67 is a known mechanism mainly including a driving motor 67A, a screw shaft 67B, and a ball nut 67C, and configured to convert a rotational motion of the driving motor 67A into a linear motion. The linear motion mechanism 67 is fixed to the base 61 via a bracket 66. Another end part 68B of the swing member 68 is connected to the ball nut 67C in a swingable manner, the ball nut 67C configured to move along the screw shaft 67B by being driven by

the driving motor 67A. In the present embodiment, the swing member 68 swings when the ball nut 67C moves along the screw shaft 67B, and the second idler roller 65B moves relatively to the base 61 along with the swing of the swing member 68. In this way, the linear motion mechanism 67 moves the position of the second idler roller 65B so that a connection portion of the belt B (one end of the belt B) to the holding unit 7 (first buffering mechanism 50) moves in the lifting-and-lowering direction. The swing member 68 may be changed to a vertically movable member that is cantilevered by the linear motion mechanism 67, and by moving this member vertically, the position of the second idler roller 65B may be moved linearly.

[0044] For example, as illustrated in FIG. 6(A), when both the linear motion mechanisms 67 are activated and the second idler rollers 65B are moved upward (to be closer to the base 61), the right side of the holding unit 7 can be inclined upward. For example, as illustrated in FIG. 6(B), when both the linear motion mechanisms 67 are activated and the second idler rollers 65B are moved downward (to be away from the base 61), the right side of the holding unit 7 can be inclined downward.

[0045] For example, as illustrated in FIG. 7(A), when one linear motion mechanism 67 (on the front side) of the two linear motion mechanisms 67 is activated and the second idler roller 65B is moved upward (to be closer to the base 61), the front side of the holding unit 7 can be inclined upward. In a case in which the front side of the holding unit 7 is desired to be inclined upward, the other linear motion mechanism 67 (on the rear side) of the two linear motion mechanisms 67 may be

activated, and the second idler roller 65B may be moved downward (to be away from the base 61).

[0046] For example, as illustrated in FIG. 7(B), when the other linear motion mechanism 67 (on the rear side) of the two linear motion mechanisms 67 is activated and the second idler roller 65B is moved upward (to be closer to the base 61), the rear side of the holding unit 7 can be inclined upward. In a case in which the rear side of the holding unit 7 is desired to be inclined upward, one linear motion mechanism 67 (on the front side) of the two linear motion mechanisms 67 may be activated, and the second idler roller 65B may be moved downward (to be away from the base 61).

[0047] As in the foregoing, the overhead transport vehicle 1 of the present embodiment can adjust, by activating both or one of the two linear motion mechanisms 67, the inclination of the holding unit 7 with respect to the horizontal plane. Furthermore, in the overhead transport vehicle 1 of the present embodiment, the operation of the linear motion mechanism 67 is controlled based on the state of the overhead transport vehicle 1 (information on inclination of the lifting part). The state of the overhead transport vehicle 1 is stored, for example, in the storage unit 8A provided in the center frame 15. The state of the overhead transport vehicle 1 includes the state of the overhead transport vehicle 1 acquired during teaching and the state of the overhead transport vehicle 1 acquired by the measuring unit 80 and the measured unit 90.

[0048] On each of the overhead transport vehicles 1, teaching is performed before the transport vehicle system 100 is put into operation. The teaching is making the overhead transport vehicle 1 store the

operation to be performed such that, in order for the overhead transport vehicle 1 to transfer the FOUP 200 at the load port 300, the state of the overhead transport vehicle 1 is acquired in a state in which the overhead transfer transport 1 is stopped at a predetermined position on the track

5 20 and the holding unit 7 is lowered by a predetermined distance to know an amount of deviation of the position of the holding unit 7 (more precisely, the position of the grippers 12) from a target position, and based on the state of the relevant overhead transport vehicle 1, the deviation from the target position falls within an allowable range when

10 the transport vehicle system 100 is in operation. Examples of the state of the overhead transport vehicle 1 include information such as the actual position (X coordinate, Y coordinate, Z coordinate) of the grippers 12 with the reference position of the load port 300 as the origin, the angle θ , the angle α_x , the angle α_y , and the like.

15 [0049] The measuring unit 80 and the measured unit 90 are described in detail. As illustrated in FIG. 8 and FIG. 9, the measuring unit 80 and the measured unit 90 are units for acquiring the state of the overhead transport vehicle 1 without human intervention. FIG. 8 is a perspective view of the measuring unit 80 and the measured unit 90, and

20 FIG. 9 is a schematic diagram illustrating the measurement target of each distance sensor 83X1, 83Y1, 83Y2, 83Z1, 83Z2, 83Z3 when the measuring unit 80 measures the measured unit 90. The solid line arrows and broken line arrows illustrated in FIG. 8 and FIG. 9 indicate the output directions of the laser at each distance sensor 83X1, 83Y1,

25 83Y2, 83Z1, 83Z2, and 83Z3.

[0050] In the transport vehicle system 100 of the present embodiment,

when acquiring the state of the overhead transport vehicle 1, the measured unit 90 is mounted on the overhead transport vehicle 1 and the measuring unit 80 is mounted on the load port 300. That is, the measured unit (first unit member) 90 is used by being gripped by the pair of grippers 12, 12 and the measuring unit (second unit member) 80 is used by being placed on the load port 300. In a state in which the overhead transport vehicle 1 is stopped at a predetermined position on the track 20, the holding unit 7 is lowered by a predetermined distance, and the measured unit 90 is separated from the measuring unit 80 above the load port 300, the state of the overhead transport vehicle 1 is acquired.

[0051] The measuring unit 80 includes a body part 81, a unit controller 82 (see FIG. 11), a plurality of distance sensors 83X1, 83Y1, 83Y2, 83Z1, 83Z2, and 83Z3, mounting parts 84, support parts 85, and guide parts 86. The body part 81 is a flat plate-like member that supports the unit controller 82, the mounting parts 84, and the guide parts 86. The unit controller 82 is provided in a state of being supported by the body part 81 and performs various electrical processes in the measuring unit 80.

[0052] Each of the distance sensors 83X1, 83Y1, 83Y2, 83Z1, 83Z2, and 83Z3 is a laser-type distance sensor, for example, and is attached to the mounting parts 84. The distance sensor 83X1 measures the distance to an object by emitting a laser beam toward the inside of the body part 81 along the X-axis direction. The distance sensors 83Y1 and 83Y2 measure the distances to an object by emitting laser beams toward the inside of the body part 81 along the Y-axis direction. The

distance sensors 83Z1, 83Z2, and 83Z3 measure the distances to an object by emitting laser beams upward along the Z-axis direction.

[0053] The mounting parts 84 are the portions on which each of the distance sensors 83X1, 83Y1, 83Y2, 83Z1, 83Z2, and 83Z3 is mounted, and are provided to stand on the body part 81. The support parts 85 are the portions that support the measured unit 90 and are provided to stand on the body part 81. The guide parts 86 are the portions that guide so that the measured unit 90 is positioned in a predetermined position when the measured unit 90 is supported on the support parts 85.

The guide parts 86 are provided to stand on the body part 81.

[0054] The measured unit 90 has a flange 91, a base plate 92, a plurality of target plates 93, 94, and 95, and legs 97. The flange 91 is the portion provided grippable by the gripper 12. The base plate 92 is connected to the flange 91, and the target plates 93, 94, and 95 are provided to stand thereon. The base plate 92 and the target plates 93, 94, and 95 are the portions forming the target surfaces to be measured by the respective distance sensors 83X1, 83Y1, 83Y2, 83Z1, 83Z2, and 83Z3.

[0055] Each target plate 93, 94, and 95 is fixed in a predetermined place on the base plate 92. A surface 93a facing the distance sensor 83X1 in the target plate 93 is a plane perpendicular to the X-axis direction and has a predetermined positional relation with the reference position of the load port 300 (center position of the placement surface of the load port 300). A surface 94a facing the distance sensor 83Y1 in the target plate 94 and a surface 95a facing the distance sensor 83Y2 in the target plate 95 are planes perpendicular to the Y-axis direction and have a

predetermined positional relation with the reference position of the load port 300. The legs 97 are provided at the bottom of each of the target plates 93, 94, and 95, and come into contact with the body part 81 of the measuring unit 80 when the measured unit 90 is supported by the measuring unit 80.

[0056] As in the foregoing, the unit controller 82 of the measuring unit 80 can acquire the measurement distance X1 by the distance sensor 83X1, the measurement distance Y1 by the distance sensor 83Y1, the measurement distance Y2 by the distance sensor 83Y2, the measurement distance Z1 by the distance sensor 83Z1, the measurement distance Z2 by the distance sensor 83Z2, and the measurement distance Z3 by the distance sensor 83Z3. Then, the unit controller 82 can, based on a plurality of measurement distances X1, Y1, Y2, Z1, Z2, and Z3, calculate the actual position (X coordinate, Y coordinate, Z coordinate) of the grippers 12 with the reference position of the load port 300 as the origin, and the angle θ , the angle α_x , and the angle α_y .

[0057] In this case, as illustrated in FIG. 10(A), the angle θ is the rotation angle of the measuring unit 80 rotating about the Z-axis with respect to the measured unit 90 (that is, the rotation angle of the gripper 12 rotating about the Z-axis with respect to the load port 300).

Assuming that the distance between the distance sensor 83Y1 and the distance sensor 83Y2 is L1, the angle θ is expressed as $\theta = \tan^{-1} [(Y1 - Y2)/L1]$. In FIG. 10(A), depiction of the distance sensors 83X1, 83Z1, 83Z2, 83Z3, and the like is omitted.

[0058] The angle α_x , as illustrated in FIG. 10(B), is the tilt angle of the measuring unit 80 inclined about the Y-axis with respect to a surface 92a

of the base plate 92 of the measured unit 90 (that is, the tilt angle of the gripper 12 inclined about the Y-axis with respect to the reference plane of the load port 300). Assuming that the distance between the distance sensor 83Z1 and the distance sensor 83Z3 is L2, the angle α_x is expressed as $\alpha_x = \tan^{-1} [(Z3-Z1)/L2]$. In FIG. 10(B), depiction of the distance sensors 83X1, 83Y1, and 83Y2 and the target plates 93, 94, 95, and the like is omitted.

[0059] The angle α_y , as illustrated in FIG. 10(C), is the tilt angle of the measuring unit 80 inclined about the X-axis with respect to the surface 92a of the base plate 92 of the measured unit 90 (that is, the tilt angle of the gripper 12 inclined about the X-axis with respect to the reference plane of the load port 300). Assuming that the average value of the distance Z1 measured by the distance sensor 83Z1 and the distance Z3 measured by the distance sensor 83Z3 (that is, $(Z1+Z3)/2$) is Z13 and that the distance between the line connecting the distance sensor 83Z1 and the distance sensor 83Z3 and the distance sensor 83Z2 is L3, the angle α_y is expressed as $\alpha_y = \tan^{-1} [(Z2-Z13)/L3]$. In FIG. 10(C), depiction of the distance sensors 83X1, 83Y1, and 83Y2 and the target plates 93, 94, 95, and the like is omitted.

[0060] In the transport vehicle system 100 of the present embodiment, at a predetermined load port 300, in place of acquiring the actual position (X coordinate, Y coordinate, Z coordinate) of the grippers 12 with the reference position of the load port 300 as the origin, the angle θ , the angle α_x , and the angle α_y (hereinafter, also referred to simply as the "state of the overhead transport vehicle 1"), the state of the overhead transport vehicle 1 is acquired using the measuring units 80 placed on a

first placement table 151, a second placement table 152, and a pair of third placement tables 153, 153 provided on a maintenance trestle 150 illustrated in FIG. 12(A) and FIG. 12(B) and using at least one measured unit 90.

5 [0061] Next, the maintenance trestle 150 is described in detail. As illustrated in FIG. 12(A), the maintenance trestle 150 is provided at a predetermined position along the track 20. The first placement table 151, the second placement table 152, and the pair of third placement tables 153, 153 are supported by a frame 154. The first placement
10 table 151 is provided below the track 20 and at a relatively low position with respect to the second placement table 152 (in other words, at a position where the unwound amount of belts B for placing the FOUP 200 is relatively large).

[0062] The second placement table 152 is provided below the track 20
15 and at a relatively high position with respect to the first placement table 151 (in other words, at a position where the unwound amount of belts B for placing the FOUP 200 is relatively small). The second placement table 152 is provided at a position displaced from the first placement table 151 (in the present embodiment, at a position displaced toward the
20 rear) in a plan view seen from above in the vertical direction. The second placement table 152 is provided to be slidable in the front-and-rear direction and is provided to be movable between an advanced position at which it is located in the area above the first placement table 151 and a retracted position at which it is not located in the area above
25 the first placement table 151. When the state of the overhead transport vehicle 1 is acquired using the second placement table 152, the second

placement table 152 is moved to the advanced position.

[0063] The pair of third placement tables 153, 153 are disposed so as to sandwich the track 20 in a plan view seen from above. The pair of third placement tables 153, 153 are provided at a position where the FOUP 200 cannot be transferred without activating the lateral unit 4. The pair of third placement tables 153, 153 are fixed immovably, unlike the second placement table 152.

[0064] As in the foregoing, with the maintenance trestle 150 having the first placement table 151, the second placement table 152, and the pair of third placement tables 153, 153, the state of the overhead transport vehicle 1 can be acquired for each of the first placement table 151, the second placement table 152, and the pair of third placement tables 153, 153. That is, on the maintenance trestle 150, the state of the overhead transport vehicle 1 when the unwound amount of belts B is relatively large can be acquired using the first placement table 151, the state of the overhead transport vehicle 1 when the unwound amount of belts B is relatively small can be acquired using the second placement table 152, and the state of the overhead transport vehicle 1 when the belts B are unwound by activating the lateral unit 4 can be acquired using the pair of third placement tables 153, 153.

[0065] Next, using the maintenance trestle 150, a flow of acquiring the state of the overhead transport vehicle 1 is described. As illustrated in FIG. 13(A), the area controller 110 causes the overhead transport vehicle 1 to move to the maintenance trestle 150 with predetermined timing. The area controller 110 (see FIG. 11) causes the overhead transport vehicle 1 to move to the maintenance trestle 150 according to

a predetermined schedule (periodically). On the first placement table 151 of the maintenance trestle 150, the measured unit 90 is placed in a state of being supported by the measuring unit 80 (see FIG. 8).

[0066] As illustrated in FIG. 13(B), the overhead transport vehicle 1 unwinds the belts B in a state of stopping above the first placement table 151 and lowers the holding unit 7. After unwinding the belts B by a predetermined amount, the overhead transport vehicle 1 activates the grippers 12 to grip the flange 91 of the measured unit 90. Thereafter, a predetermined amount of belts B is rewound and the measured unit 90 supported by the measuring unit 80 is separated from the measuring unit 80. The measuring unit 80 placed on the first placement table 151 measures, in this state, the distances X1, Y1, Y2, Z1, Z2, and Z3 to the base plate 92 and the target plates 93, 94, and 95 of the measured unit 90.

[0067] After the measurement by the measuring unit 80 placed on the first placement table 151, the overhead transport vehicle 1 winds the belts B in a state of gripping the measured unit 90, and moves the holding unit 7 to a height position higher than the second placement table 152. Next, as illustrated in FIG. 14 (A), the second placement table 152 is slid and moved to the advanced position above the first placement table 151. The overhead transport vehicle 1 unwinds the belts B and lowers the holding unit 7 holding the measured unit 90. The overhead transport vehicle 1 unwinds the belts B by a predetermined amount and positions the measured unit 90 so as to be in a state of being separated by a predetermined amount from the measuring unit 80 placed on the second placement table 152. The

measuring unit 80 placed on the second placement table 152 measures, in this state, the distances X1, Y1, Y2, Z1, Z2, and Z3 to the base plate 92 and the target plates 93, 94, and 95 of the measured unit 90.

[0068] After the measurement by the measuring unit 80 placed on the second placement table 152, the overhead transport vehicle 1 winds the belts B in a state of gripping the measured unit 90, and then, activates the lateral unit 4 to move the holding unit 7 above one of the pair of third placement tables 153. The overhead transport vehicle 1 unwinds the belts B and lowers the holding unit 7 holding the measured unit 90.

The overhead transport vehicle 1 unwinds the belt B by a predetermined amount and positions the measured unit 90 so as to be in a state of being separated by a predetermined amount from the measuring unit 80 placed on the one of the pair of third placement tables 153. The measuring unit 80 placed on the one of the pair of third placement tables 153 measures, in this state, the distances X1, Y1, Y2, Z1, Z2, and Z3 to the base plate 92 and the target plates 93, 94, and 95 of the measured unit 90.

[0069] After the measurement by the measuring unit 80 placed on the one of the pair of third placement tables 153, the overhead transport vehicle 1 winds the belts B in a state of gripping the measured unit 90, activates the lateral unit 4, and this time, moves the holding unit 7 above the other of the pair of third placement tables 153. The overhead transport vehicle 1 unwinds the belts B and lowers the holding unit 7 holding the measured unit 90. The overhead transport vehicle 1 unwinds the belts B by a predetermined amount and positions the measured unit 90 so as to be in a state of being separated by a

predetermined amount from the measuring unit 80 placed on the other of the pair of third placement tables 153. The measuring unit 80 placed on the other of the pair of third placement tables 153 measures, in this state, the distances X1, Y1, Y2, Z1, Z2, and Z3 to the base plate 92 and the target plates 93, 94, and 95 of the measured unit 90.

[0070] After the measurement by the measuring unit 80 placed on the other of the pair of third placement tables 153, the overhead transport vehicle 1 winds the belts B in a state of gripping the measured unit 90, activates the lateral unit 4, and this time, moves the holding unit 7 above the first placement table 151. Next, as illustrated in FIG. 14(B), the second placement table 152 moves to the retracted position retracted from above the first placement table 151. The move to the retracted position of the second placement table 152 may be performed at an appropriate timing after the measurement by the measuring unit 80 placed on the second placement table 152.

[0071] The overhead transport vehicle 1 unwinds the belts B in a state of stopping above the first placement table 151 and lowers the holding unit 7 holding the measured unit 90. As illustrated in FIG. 15, the overhead transport vehicle 1 unwinds the belts B until the measured unit 90 is in a state of being supported by the measuring unit 80 placed on the first placement table 151, then activates the grippers 12 to release the gripping of the flange 91 of the measured unit 90. The measured unit 90 is in a state of being supported by the measuring unit 80 placed on the first placement table 151. Thereafter, the overhead transport vehicle 1 winds the belts B until the holding unit 7 is ready to travel. The area controller 110 causes the overhead transport vehicle 1 to leave

from the maintenance trestle 150.

[0072] By the foregoing flow, on each of the measured unit 90 placed on each of the first placement table 151, the second placement table 152, and the pair of third placement tables 153, 153 at which the distances X1, Y1, Y2, Z1, Z2, and Z3 to the base plate 92 and the target plates 93, 94, and 95 have been measured, information such as the actual position (X coordinate, Y coordinate, Z coordinate) of the grippers 12 with the reference position of each of the placement tables as the origin, the angle θ , the angle α_x , and the angle α_y is calculated based on the distances X1, Y1, Y2, Z1, Z2, and Z3. These pieces of information are transmitted to the communication unit 9 of the overhead transport vehicle 1 via a communication unit 88 provided in the maintenance trestle 150. The communication unit 88 of the maintenance trestle 150 and the communication unit 9 of the overhead transport vehicle 1 can perform communication by appropriate means such as optical communication, wireless communication, and the like.

[0073] The transport vehicle controller 8 causes the storage unit 8A (see FIG. 11) to store the information received via the communication unit 9 such as the actual position (X coordinate, Y coordinate, Z coordinate) of the grippers 12 with the reference position of each placement table as the origin, the angle θ , the angle α_x , and the angle α_y . That is, the transport vehicle controller 8 causes the storage unit 8A to store (update) the latest state of the overhead transport vehicle 1 acquired by the measuring unit 80 and the measured unit 90. The transport vehicle controller 8 controls the operation of the linear motion mechanisms 67 based on the state of the overhead transport vehicle 1 stored in this

storage unit 8A.

[0074] The action and effect in the transport vehicle system 100 of the above-described embodiment are described. In such a transport vehicle system 100, the holding unit 7 is controlled based on
5 predetermined set values when lifted or lowered, but in the transport vehicle system 100 of the above-described embodiment, the set values are appropriately corrected based on the measurement result acquired by the measuring unit 80 and the measured unit 90, that is, the information that is considered to be indicative of the current state of the holding unit
10 7 when the holding unit 7 is lifted or lowered to the transfer part, for example, the load port 300. This makes it possible to appropriately adjust the inclination of the holding unit 7 for each overhead transport vehicle 1 without human intervention

[0075] In the transport vehicle system 100 of the above-described
15 embodiment, the measured unit 90 is formed as a unit member grippable by the grippers 12, and the measuring unit 80 is formed as a unit member placeable on each of the placement tables of the maintenance trestle 150. When the overhead transport vehicle 1 is about to start acquiring the state of the overhead transport vehicle 1, the measured
20 unit 90 is placed on the first placement table 151 in a state of being supported by the measuring unit 80. This makes it possible to rapidly execute automatic measurement by the measuring unit 80 and the measured unit 90.

[0076] In the transport vehicle system 100 of the above-described
25 embodiment, the measured unit 90 is used in a state of being gripped by the grippers 12, and the measuring unit 80 is used in a state of being

placed on each of the placement tables of the maintenance trestle 150.

This makes it possible to perform automatic measurement by the measuring unit 80 and the measured unit 90 without significantly changing the configuration of the overhead transport vehicle 1.

5 [0077] In the transport vehicle system 100 of the above-described embodiment, the maintenance trestle 150 is provided in the traveling area of the overhead transport vehicle 1 separately from the load port 300, so that the overhead transport vehicle 1 can be measured efficiently without stopping the operation by the transport vehicle system 100.

10 [0078] In the transport vehicle system 100 of the above-described embodiment, the maintenance trestle 150 including the first placement table 151, the second placement table 152, and the third placement tables 153 is provided, so that, on each of the load port 300 provided at a relatively low position with respect to the traveling position of the
15 overhead transport vehicle 1, the load port 300 provided at a relatively high position, and the load port 300 on which placing is performed by operating the sliding part, it is possible to appropriately adjust the inclination of the holding unit 7 for each overhead transport vehicle 1.

[0079] In the transport vehicle system 100 of the above-described
20 embodiment, the overhead transport vehicle 1 is periodically moved to the maintenance trestle 150 and the measuring unit 80 is made to measure the measured unit 90, so that periodic adjustment of the set values can be made.

[0080] In the overhead transport vehicle 1 of the above-described
25 embodiment, by activating the linear motion mechanisms 67, the inclination of the holding unit 7 with respect to the horizontal plane can

be adjusted. The amount of operation of the linear motion mechanisms
67 (amount of movement of the guide rollers) is automatically adjusted
based on the information about the inclination on the holding unit 7
(information such as the angle α_x and the angle α_y) that is the state of
5 the overhead transport vehicle 1, so that the holding unit 7 can be
adjusted to the desired tilt. That is, the overhead transport vehicle 1 of
the present embodiment can appropriately adjust the inclination of the
holding unit 7 without human intervention.

[0081] The embodiment has been described above, but one aspect of
10 the present invention is not limited to the embodiment described above.
Various modifications can be made without departing from the gist of
one aspect of the invention.

[0082] First Modification

In the overhead transport vehicle 1 of the above-described
15 embodiment, it has been described with an example of acquiring the
state of the overhead transport vehicle 1 by causing the overhead
transport vehicle 1 to enter the maintenance trestle 150, but the state of
the overhead transport vehicle 1 may be acquired for each load port 300
constituting the transport vehicle system 100. With this configuration,
20 the holding unit 7 can be adjusted to the optimum inclination for each
load port 300 on which the FOUP 200 is actually placed.

[0083] Second Modification

In the overhead transport vehicle 1 of the above-described
embodiment and the above-described modification, it has been
25 described with an example of acquiring the state of the overhead
transport vehicle 1 from the measuring unit 80 and the measured unit 90

when the holding unit 7 grips the measured unit 90, but the state of the overhead transport vehicle 1 may be acquired by moving the holding unit 7, which is gripping the measuring unit (first unit member) 80, away from or closer to the measured unit (second unit member) 90 placed on each of the placement tables. With this configuration, the measured unit 90, which is inexpensive relative to the measuring unit 80, is placed on each of the placement tables of the maintenance trestle 150, so that the maintenance trestle 150 can be constructed at a low cost.

10 [0084] Third Modification

In the overhead transport vehicle 1 of the above-described embodiment and the above-described modifications, it has been described, as the state of the overhead transport vehicle 1 to be stored in the storage unit 8A, with an example of the information such as the actual position (X coordinate, Y coordinate, Z coordinate) of the grippers 12 with a predetermined reference position as the origin, the angle θ , the angle α_x , the angle α_y , and the like, but it may be set values of the amount of operation of the linear motion mechanisms 67 (amount of movement of the guide rollers) determined based on such information on the actual position (X coordinate, Y coordinate, Z coordinate), the angle θ , the angle α_x , the angle α_y , and the like.

[0085] Fourth Modification

In the above-described embodiment and some of the above-described modifications, it has been described with an example in which the measured unit 90 having the target plates 93, 94, and 95, which are measurement targets by the measuring unit 80, is disposed on each of

the placement tables of the maintenance trestle 150, but in a case of the load port 300, for example, positioning pins or the like formed on a portion where the FOUP 200 is placed may be used, in place of the measured unit 90, as the measurement target of the measuring unit 80, or targets to be the measurement targets may be formed directly on each of the placement tables of the maintenance trestle 150.

[0086] Other Modifications

In the overhead transport vehicle 1 of the above-described embodiment, in place of the linear motion mechanism 67 having the function of moving the position of at least one of the second idler rollers 65B in order to move one end of the belt B in the lifting-and-lowering direction, a cam mechanism (position adjustment part) having a similar function may be provided.

[0087] In the overhead transport vehicle 1 of the above-described embodiment, it has been described with an example of moving one end of the belt B in the lifting-and-lowering direction by moving the position of at least one of the second idler rollers 65B, but it may be configured such that one end of the belt B is moved in the lifting-and-lowering direction by moving the position of the first idler roller 65A in place of the second idler roller 65B.

[0088] In the above-described embodiment and the modifications, it has been described with an example of employing the ball screw as the linear motion mechanisms 67, but a cylinder, a linear guide, and the like may be employed.

[0089] The holding unit 7 of the above-described embodiment and the modifications has been described with an example in which one ends of

the belts B are connected via the first buffering mechanism 50 and the second buffering mechanism 40, but it may be directly connected to the holding unit 7. The four belts B may be directly connected to the holding unit 7 as is. Alternatively, the three belts B may be connected to the holding unit 7.

[0090] In the above-described embodiment and the modifications, it has been described with an example of direct exchange between the overhead transport vehicle 1 and the measuring unit 80 via the communication units, but various pieces of information may be exchanged via the area controller 110.

[0091] In addition to the configuration of the measuring unit 80 of the above-described embodiment and the above-described modifications, a measuring unit including a battery and a communication unit, which are integrally configured, may be used.

Reference Signs List

[0092] 1 ... overhead transport vehicle

7 ... holding unit

8 ... transport vehicle controller (control part)

61 ... base (body part)

64 ... third idler roller (guide roller)

65A ... first idler roller (guide roller)

65B ... second idler roller (guide roller)

67 ... linear motion mechanism (position adjusting part)

80 ... measurement unit (measuring part)

82 ... unit controller

83X1, 83Y1, 83Y2, 83Z1, 83Z2, 83Z3 ... distance sensor

	88 ... communication unit
	90 ... measured unit (acquisition part)
	93, 94, 95 ... target plate
	100 ... transport vehicle system
5	110 ... area controller (control device)

CLAIMS

1. A transport vehicle system equipped with an overhead transport vehicle in which a lifting part having a gripping part
5 for gripping an article is lifted and lowered by a plurality of suspending members, the transport vehicle system comprising:

a measuring part configured to measure a measurement target portion;

10 a measured part on which the measurement target portion is formed;

a control part configured to cause the lifting part to be lifted and lowered according to a predetermined set value;

15 a maintenance trestle provided in a traveling area of the overhead transport vehicle and on which a placement table of the measuring part is formed; and

a communication unit configured to transmit a result of measurement of the measured part made by the measuring part to the control part provided in the overhead transport vehicle in a wireless manner, wherein

20 the measured part is formed as a first unit member grippable by the gripping part,

the measuring part is formed as a second unit member placeable on the placement table,

25 the first unit member is placed on the maintenance trestle in a state of being supported by the second unit member placed on the placement table, and

30 the control part is configured to cause the gripping part to grip the first unit member in a state of being supported by the second unit member at the placement table of the maintenance trestle and causes the lifting part to lift so that the second unit member in a state of being placed on the placement table is able to measure the first unit member gripped by the gripping part, and corrects the set value based on a measurement result of the first unit member transmitted via the communication unit
35 from the second unit member in a state of being placed on the placement table.

2. The transport vehicle system according to claim 1, wherein
the overhead transport vehicle has a body part, the lifting
part provided in a manner of being able to be lifted and lowered
with respect to the body part by the suspending members being
wound and unwound, and a sliding part configured to move the
lifting part in a direction orthogonal to both a transport
direction of the overhead transport vehicle and a vertical
direction, and

the maintenance trestle includes a first placement table
provided at a position where the article is placeable by
lowering the lifting part without the overhead transport vehicle
activating the sliding part, a second placement table provided
above the first placement table in the vertical direction and
provided to be retractable in a horizontal direction from an
area above the first placement table in the vertical direction,
and a third placement table provided at a position where the
article is placeable by at least the overhead transport vehicle
activating the sliding part.

3. The transport vehicle system according to claim 1, further
comprising an area controller configured to cause the overhead
transport vehicle to periodically move to the maintenance
trestle.