



-1-

METALLIC INNER ENCLOSURE FOR AN ELECTRICAL
CABLE CONNECTION

Background of the Invention

1. Field of the Invention

5 The invention refers to a metallic inner enclosure for an electrical cable connection according to the preamble of patent claim 1.

2. Background of the Prior Art

10 The German patent specification 36 43 249 discloses an inner enclosure for an electrical cable connection comprising a tubular central section surrounding the connection area and two tubular end sections which extend taperingly from the central section to shield layers of the cables. All three sections are of metallic material. One end section is introducible, with its smaller end ahead, through the other end of the central section into the central section, a first mechanical plug connection being provided at the larger end of the one end section effective in the direction of introduction. At the larger end of the other end part and at the other end of the central section, a second mechanical plug connection is provided. By this, the complete enclosure is installed by an axial interplugging of only three structural parts. Since with the manufacturing of the parts tolerances cannot be avoided, the danger exists that the plug connections are not tight enough to keep the liquid insulation mass enclosed. Further, the known enclosure requires a so-called parking position during the insulation work. The enclosure parts are to be pushed onto one of the cables to be connected before the conductors are interconnected. Therefore, sufficient space must be available in the manhole.

35 From the German patent specification 31 00 221, a transition sleeve has become known for the connection of a paper-insulated cable with a plastic-insulated cable wherein a tubular portion surrounds the connection area at a radial distance. Sealing elements of metallic material



-2-

are shaped as a lid or a flange wherein an outer axial flange engages the outer surface of the tubular portion while an inner axial flange through which the cable extends sealingly engages the outer conducting layer. The sealing elements are attached to the tubular portion either by a boot clamp or by soldering. Considerable difficulties are encountered to achieve a satisfactory sealing between the metallic sealing elements and the tubular portion by means of a boot clamp. On the other side, the soldering is work-expensive and necessitates educated workers. Also this known enclosure requires a parking position which the tubular portion first has to attain as long as the interconnection of the conductors is not established.

From the German patent specification 29 02 041, it has become known to provide a tubular housing with variable volume for connection sleeves of electrical cables such that the housing consists of two tubular portions of different diameter which are coaxially and overlappingly arranged. A piston-like sealing element is placed between the housing portions. Such an enclosure also necessitates educated workers for its installation and requires a relatively large manhole or ditch.

It is the object of the invention to provide a metallic inner enclosure of an electrical cable connection which consists of parts which can be installed by non-educated or semi-educated workers within a short time and which requires only a small manhole.

This object is attained by the features of the characterizing portion of patent claim 1.

Summary of the Invention

Similar to the case described above (DE-OS 31 00 221), the invention provides a tubular portion, however, this tubular portion is parted in the longitudinal direction. The parted envelope for example consists of a suitable approximately cylindrically formed sheet, e.g. zinc or of galvanized steel sheet and can be laterally placed on the cable connection by simply moving the



-3-

longitudinal edges at a seam away from each other. A parking position which is required with cylindrical enclosures is not necessary.

5 In an enclosure according to the invention the sealing elements which concurrently serve as spacers for the envelope are made of elastically deformable material. By means of the longitudinal cover which engages the longitudinal edges of the envelope and biases the edges toward each other, the sealing elements are subjected to a
10 radial pressure so that a sealing is effected at the ends of the envelope which seals prevent a leakage of impregnating liquid or insulating mass.

The cover is also made of metallic material to provide a complete screening in the area of the envelope.
15 However, with the envelope according to the invention it is refrained from providing a geometrically closed screening system wherein as for example with the sleeve of the German patent specification 31 00 221 the spacer and sealing elements are made of metallic material. It has
20 been recognized with the invention that it is sufficient for the control of the electrical field if the outer shield layer of the cable extends into the envelope. If for example a paper-insulated cable is used and the lead sheath is funnel-like or expanded at its free end as known per se and introduced into the metallic envelope a certain length
25 the sealing elements must not be made electrically conductive. In connection with plastic insulated cable a conical field controlling sleeve (refractor sleeve) of semi-conductive material can be advantageously used. Such
30 refractor sleeves are known. In the enclosure according to the invention, the end of the sleeve having the smaller diameter is brought into engagement with the primary insulation, and the end having the larger diameter is brought into engagement with the screen while the center
35 portion is brought into engagement with the semi-conductive layer. Besides its field controlling properties, such sleeve which is made of resilient material also contributes



to a sealing effect.

5 In a presently preferred embodiment of the invention, a rail having approximately C-shape in cross section coacts with the outwardly bent longitudinal edges of the envelope in order to hold them against each other under tension. The rail and bent longitudinal edges can define a kind of dove-tail connection. In case the envelope is relatively long, it can be advantageous if the rail consists of a plurality of separate portions, for
10 example of two.

The sealing elements preferably consist of foamed plastic which is suited to be compressed a certain amount. The sealing elements can be provided with a radially outwardly extending portion which extends into the gap
15 between the longitudinal edges of the envelope to provide a sealed connection in the area of the gap. The sealing elements are formed with a radial cut and may include locking portions adapted to engage each other to hold the ends in locking engagement. According to an embodiment of
20 the invention, they may consist of an inner core having one or a plurality of circular recesses for the receipt of cables or cable conductors, around which an outer collar is wrapped. In the known enclosure described above, the short circuit current or earthconnection is established by
25 the enclosure itself. This can be critical if the engagement between the outer and the tubular center sections is only spotwise. In case of high currents, these areas are strongly heated and can even melt. Also with the envelope according to the German patent specification 31 00
30 221, the metallic sleeve is connected to the respective cables through a screen wire connection and a ground braid, respectively. According to an embodiment of the invention, the outer conducting layers of the cables to be interconnected are electrically interconnected by a
35 separate braid which, additionally, can be electrically connected with the parted envelope for example by means of a sheet screw. The braid can be clamped by means of



-5-

suitable clamping means, e.g. a constant force spring. If one of the cables to be connected is a plastic insulated cable including a wire screen, a braid can be formed of the wire if the plastic insulated cable is sufficiently shortened.

5

In case a three-conductor cable is to be connected with three individual cables or the like, a spacer element of electrically insulating material can be placed between the cables or the conductors, respectively. In order to achieve a stability against short circuit current forces, a spacer wrapper can be located between the cable and the parted envelope, e.g. of relatively stiff non-woven material.

10

Description of the Drawing

15

The invention will be subsequently described in connection with the drawing.

Figure 1 is a view on a plastic insulated cable and a three conductor paper insulated cable prepared for a connection therebetween.

20

Figure 2 is a perspective view, partially broken of a cable connection including an enclosure according to the invention.

Figure 3 is a front view of a sealing element for an enclosure according to the invention.

25

Figure 4 is a front view of another sealing element for an enclosure according to the invention.

Figure 5 is a cross section of Figure 2 along line 5-5.

Figure 6 is a lateral view of a modified envelope of the invention.

30

Figure 7 is a partial end view of the envelope in Figure 6 if looking in the direction of arrow 7.

Figure 8 is a view of larger scale of one end portion of the envelope of Figure 6.

35

Figure 9 is a cross section through the end of a cable connection including an alternate embodiment of the sealing element.



-6-

Figure 10 is a perspective view of a sealing element similar to that of Figure 9.

Detailed Description of the Invention

5 In Figure 1 a plastic insulated cable 10 and a three conductor paper insulated cable 11 can be seen. In total three plastic insulated cables are connected with the paper insulated cable 11 as illustrated in Figure 2. The cable 10 includes a conductor 12, a plastic insulation 14 on the conductor 12, an outer conducting layer 15 placed on the insulation 14, a copper wire shield or screen 16 on the outer conducting layer 15 and a cable sheath 17. With the removed cable sheath 17, the cable 10 is shortened a predetermined length so that the wires of the screen 16 extend beyond the cable end. A braid 18 is formed of the wires 16. The outer conducting layer 15 is removed a predetermined length so that the insulation 14 is exposed. The insulation 14 is removed a certain length corresponding substantially to one half of the standard crimp connector length.

20 As can be seen in Figure 1, the rearwardly bent wires 16 of the screen are fixed to the cable sheath 17 by means of a constant force spring 19. A refractor sleeve 20 of semiconducting field controlling material is pushed onto the cable from the free end thereof. The sleeve is conically formed, and its larger diameter end engages the cable sheath or the screen 16 thereon. The center portion of sleeve 20 engages the outer conducting layer 15 while the smaller diameter portion engages the insulation 14. A protection tape is placed on the conductor end which is removed prior to the connecting of the conductors 12, 30.

30 The paper insulated cable 11 includes three conductors 30, each wrapped with a paper insulation 31, a protection tape 30a being applied to the free end of the conductors 30. A so-called belt insulation 32 is wrapped around the conductors, a lead sheath 33 is around the belt insulation, and an armor 34 being wrapped around the lead sheath 33. The cable oversheath 35 is made for example of



-7-

jute. The structure of cables 10 and 11 is conventional.

As can be seen, the jute oversheath 35 and the armor 34 are removed such that the armor 34 slightly extends beyond oversheath 35. The removed lead sheath 33 extends beyond armor 34. The lead sheath is funnel-like expanded at its free end as shown at 36. The removed belt insulation 32 extending beyond the lead sheath 33 is fixed by a cord 37. The paper insulation 31 is removed about one half of the standard crimp connector length as can be seen in Figure 1.

Figure 2 shows the connection of three plastic insulated cables 10a, 10b, 10c having a structure like cable 10 of Figure 1 with an oil paper insulated cable 11. The connection of the conductors is not shown since it is of conventional kind. Shrink sleeves 40a, 40b, 40c are placed on the electrical connection of the conductors in a manner as know per se. A perforated spacer tube 41 of suitable plastic material is positioned between the conductors or the shrink sleeves 40a, 40b, 40c, respectively, in order to establish a desired distance between the cables.

An envelope 42, preferable zinc or, alternatively, of galvanized steel sheet is wrapped around the illustrated cable connection. The envelope 42 is divided in longitudinal direction while the longitudinal edges 42a are bend outwardly. Two rail portions 43, 44 are U- or C-shaped in cross section and have legs inclined inwardly. The legs grip behind the bend longitudinal edges 42a of envelope 42 and define a kind of dove-tail connection.

Sealing elements 45, 46 are placed on the cables 10a, 10b, 10c and the lead sheath 33 of cable 11, respectively, at the ends of envelope 42. The structure of the sealing elements 45, 46 can be seen in Figures 3 and 4. The sealing elements 45, 46 consist of resilient closed cellular foamed plastic material. The sealing element 46 is annular and includes a radial extension 47 dove-tailed



-8-

shaped in cross section which is adapted to the cross-sectional contour of the gap defined between the outwardly bend edges 42a of envelope 42. The sealing element 46 has a central circular opening 48. The sealing element is also cut or split along an arcuate line 49. By this, the sealing element 46 can be opened and laid around the lead sheath 33 like a collar. The sealing element 46 is placed such that the funnel-like expansion 36 is within opening 48.

The sealing element 45 consists of a star-like core 50 having circular recesses, 51, 52, 53 to receive the plastic insulated cables in the area of the refractor sleeves 20. An annular collar 54 is wrapped around core 50 which has a radial extension 55 similar to extension 47. The collar 54 is cut along an arcuate line 56 so that it can be easily wrapped around core 50. It consists of the same material as sealing element 46.

The dimensions of the sealing elements 45, 46 are such that upon a sliding of the rail portions 43, 44 on the longitudinal edges 42a of envelope 42 the sealing elements are slightly radially compressed to establish a satisfactory sealing. The sealing elements 45, 46 also serve as spacers to keep the envelope 42 at a uniform distance from the cables and the connection area, respectively.

Spacer material in the form of a non-woven material 58 preferably of polypropylene is wrapped around the connection area which serves for the support of envelope 42.

The braids 18a, 18b, and 18c made of the screen of the plastic insulated cables 10a, 10b, and 10c are led outside of the envelope 42 and can be electrically connected with the envelope 42 by means of a sheet screw 59. The ends of the braids 18a, 18b, 18c are brought into electrical engagement with the lead sheath 33 by means of a constant force spring 60 so that a short circuit connection is established between the cables 10, 10b, 10c



-9-

on the one side and the cable 11 on the other side.

5 The rail portion 44 receives an adapter 61 of plastic material within an opening, and opening of the adapter can be closed by a cap 42. The adapter 51 serves for receiving a pouring spout of a bag for a casting mass indicated at 64. The casting mass is poured into and completely fills out the cavity formed. For this purpose, the rail portions 43, 44 can have a certain distance from each other in order to vent the air and to observe the liquid level in the cavity. After the filling of the cavity, the rail portions 43, 44 are pushed against one another. The opening of the adapter 41 is closed by cap 62. The insulation mass first is liquid, however, solidifies after some time. For this, a suitable casting resin can be used. Thereafter, an outer protective sleeve is laid around the envelope which, however, is not to be described.

10

15

20 In the embodiment described, a plastic insulated cable is connected with an oil paper insulated cable. It is understood that also two oil paper insulated cables or two plastic insulated cables can be interconnected transit sleeve).

25 As can be seen further, an electrical screening is only given in radial direction through envelope 42 while no metallic material is provided in the axial direction. By the introduction of the outer conducting layers of the cables into envelope 42 and the use of field controlling refractor sleeves 20a, 20b, and 20c and by the special shape of the lead sheath 33 a metallic end closure of envelope 22 is not necessary.

30

35 The enclosure according to the invention can be used for arbitrary cable connections, particularly, however, for electrical cables in the medium voltage range. The installation of an enclosure according to the invention requires less work load and can be carried out by semi-educated workers. The individual parts used are of less expensive material. Particularly, the installation work



-10-

requires a relatively small manhole or ditch since a so-called parking position to be attained first by the enclosure before the electrical connection is established can be omitted.

5 The envelope shown in Figure 6 deviates from envelope 42 of Figure 2 insofar as barbs 170, 171 extend beyond the end of the longitudinal edges 142a, the barbs 170, 171 being formed by axial, circumferentially spaced extensions 172 rounded at the free ends thereof. As can
10 be seen in Figure 7, the extensions 172 are bent radially inwardly after the installation of envelope 142 whereby the associated sealing elements 45 or 46, respectively, are axially outwardly limited. The extensions 172 overlap each other at the free ends thereof.

15 Adjacent the outwardly bend longitudinal edges 142a extensions 172a, 172b are provided which are broader than the extensions 172. Through a circumferential cut, the area of the extensions 172a, 172b facing the gap between the longitudinal edges 142a is free. The width of
20 the extensions 172a, 172b is such that they also overlap each other after being bend radially inwardly.

 The barbs 170, 171 above all are provided to establish earth potential if the cable connection is touched at one end.

25 As can be seen in Figures 5 and 7, the longitudinal edges 142a are bent radially outwardly such that the gap formed therebetween enlarges radially outwardly. A radius 42b or 142b, respectively, is formed at the bending area.


30 Figures 9 and 10 illustrate alternative embodiments 45', 46' of the sealing elements 45, 46 of Figures 3 and 4, respectively. Referring to Figure 9, the sealing element 46' is approximately cylindrical and consists of a resilient, foamed, closed-cell cellular
35 plastic material. The sealing element 46' has a radial extension 47' forming a dove tail in cross section, the cross-sectional contour thereof corresponding to the gap



-11-

between the outwardly bent edges 42a' of sleeve 42'. The sealing element 46' has a central circular opening 48'. It includes further a radial cut along a line 49'. The cut 49' includes a first portion 202 extending from opening 48' toward extension 47' along a curve, the curve leading from the central opening 48' toward the outer periphery as a spiral. A second relatively short portion 203 having an opposite curvature than portion 202 extending approximately radially backwards toward opening 48' whereby a relatively small acute angle is formed between portions 202 and 203. A third portion 204 joins to the second or medium portion 203 which extends along a second circular curve or spiral up to the outer periphery and as illustrated to one side of the extension element 47'. The portions 203 and 204 include a small acute angle. Due to the described course of the cut line 49', the adjacent ends of the portions 202, 203, 204 form a projection and a recess on both opposing end faces of the sealing element, each having a small acute angle, the projections and the recesses being adapted to positively interengage, whereby a locking is achieved automatically retaining the ends of the cut sealing element 46' together unless it is unfolded by a manual operation. This is for example the case if the collar-like sealing element 46 is to be placed around the sheath 33 of a cable 11 as shown in Figure 9.

For an unfolding and relocking of the ends of the sealing element 46', the radial extension 47' can be manually gripped in order to bring the ends out of engagement. After the locking of both sealing elements for a sleeve 42 has taken place, the sleeve can be wrapped around the sealing elements. The sizes of the sealing elements are such that they are somewhat radially compressed as rail 44 is slid along the longitudinal edges 42a of sleeve 42 in order to achieve a satisfactory sealing effect. Furthermore, the sealing element 46 serves as a spacer by which sleeve 42 can be held at a uniform radial distance from the cables or their connection area,



respectively.

The reference number 59 designates the aforementioned screw by which a strand 18c forming a cable screen is electrically connected to sleeve 42.

5 In Figure 10, a sealing element 45' can be seen which resembles that of Figure 4, with the ends of the element generally corresponding to the ends of element 46'. It is to be seen that the portions 202' and 203' of the parting line 49'' extend farther into the radial extension
10 47'' than in the embodiment of Figure 9. The ring-cylindrical sealing element 45' surrounds a star-like sealing core 50 having circular recesses 51, 52, 53 for the receipt of plastic cables 10a, 10d and 10c which, for example, could be connected with the cores of the oil paper
15 cable 11 of Figure 1. The total connection being surrounded by the sleeve 42 as illustrated in Figure 9, including end sealing element 45' and the sealing core 50 as well as sealing extension 47'' in the area of the gap, to seal the plastic cable while the oil paper cable
20 connected thereto is being sealed against the sleeve by sealing element 46'.

Having described the present invention with reference to a preferred embodiment, including alternative portions thereof, it is to be appreciated that other
25 changes may be made without departing from the invention as claimed in the appended claims.

-1-


CLAIMS:

1. Metallic inner enclosure of an electrical cable connection, comprising a metallic tubular portion, surrounding the connection area and having a larger diameter than the cables, annular sealing elements located between the ends of said tubular portion and the associated cables, said sealing elements holding said tubular portion at a uniform radial distance from said connection area and defining a sealed cavity with said tubular portion for receiving liquid insulation mass, the outer conducting layer of said cables extending through said associated sealing element into said tubular portion and being electrically connected to said tubular portion through an electrically conducting connection means, characterized in that the tubular portion is defined by an envelope (42) parted in longitudinal direction and defining a pair of spaced longitudinal edges (42a), metallic cover means cooperate with said longitudinal edges (42a) to cover and seal the space formed by said longitudinal edges (42a) and to bias said longitudinal edges (42a) toward each other and in that said sealing elements (45, 46) are made of non-metallic resilient sealing material.

2. The enclosure according to claim 1, wherein the longitudinal edges (42a) of envelope (42) are bent outwardly, and a rail (43, 44) approximately C-shaped or U-shaped in cross section is slid over both bent longitudinal edges 42a, the legs of the rail (43, 44) engaging behind the longitudinal edges (42a).

3. The enclosure according to claim 2, wherein the rail (43, 44) and the outwardly bent longitudinal edges (42a) form a kind of dove-tail connection.

4. The enclosure according to claim 2 or 3, wherein the rail is divided into a plurality of separate portions, preferably two.



5. The enclosure according to one of the claims 1 to 4, wherein the sealing elements (45, 46) consist of closed cellular foamed plastic material.

5 6. The enclosure according to claim 2 or 3, wherein the sealing elements (45, 46) have a radial portion (47, 55) extending into the gap between the outwardly bent longitudinal edges (42a).

10 7. The enclosure according to claim 6, wherein the radial portion (47, 55) is adapted to the cross-sectional configuration in the gap between the longitudinal edges (42a).

8. The enclosure according to one of the claims 1 to 7, wherein the annular sealing elements (45, 46) are splitted and collapsible.

15 9. The enclosure according to claim 8, wherein the sealing elements (45) are comprised of an inner core (50) having one or a plurality of circular recesses (51, 52, 53) to receive cables, and of an annular splitted collar (54) adapted to be wrapped
20 around the core.

10. The enclosure according to one of the claims 1 to 9, wherein in case of plastic insulated cables (10, 10a, 10c) a field controlling conical sleeve (20, 20a, 20b, 20c) of semi-conductive
25 resilient material is pushed onto the exposed portion of the outer conducting layer (14, 14a, 14b, 14c), the end having the greater diameter engaging the screen (16, 16a, 16b, 16c) and the end having the smaller diameter engaging the plastic insulation (14, 14a,
30 14b, 14c).

11. The enclosure according to one of the claims 1 to 10, wherein the outer conducting layers (15, 15a, 15b or 33, respectively) of the cables (10, 10a, 10b, 10c or 11, respectively), a electrically
35 interconnected by a braid (18, 18a, 18b, 18c) which is brought into engagement with the associated conducting layer by suitable clamping means (19, 19a, 19b, 19c or



60, respectively).

12. The enclosure according to claim 11, wherein the braid (18, 18a, 18b, 18c) is made of the screen of the plastic insulated cable (10, 10a, 10b, 10c) which is shortened about the necessary length.

13. The enclosure according to one of the claims 1 to 12, wherein in case of a paper insulated cable (11) the lead sheath (33) is expanded at the free end thereof.

14. The enclosure according to one of the claims 1 to 13, wherein the envelope (42) includes at least one bore for the receipt of a sheet screw (59).

15. The enclosure according to one of the claims 1 to 14, wherein the cover means (44) include a closable pouring opening (61) for a liquid insulation mass.

16. The enclosure according to one of the claims 1 to 15, wherein in case of a connection between a three conductor cable with three individual cables a spacer element (41) of electrically insulating material is placed between the individual cables or the conductors, respectively.


17. The enclosure according to one of the claims 1 to 16, wherein a spacer wrapper (58), preferably of relatively stiff non-woven material or a grid or net like web of resilient plastic material, is placed within the envelope (42).

18. The enclosure according to one of the claims 1 to 17, wherein barbs (170, 171) are provided at the ends of the envelope (142) formed by a plurality of circumferentially spaced extensions (172, 172a, 172b) which are bent radially inwardly after the placement of the envelope on the connection area, the extensions axially limiting the associated sealing element (45, 46).

19. The enclosure according to claim 18, wherein the extensions (172a, 172b) of the barb (170,



This Sheet Has Been Replaced



-4-

171) adjacent the outwardly bent longitudinal edges (142a) of envelope (142) have a larger width than the remaining extensions (172) such that they are also overlapping after being bent radially inwardly.