

DISC DEVICE

BACKGROUND OF THE PRESENT INVENTION

The present invention relates to a disc device which rotates a disc-like replaceable recording medium at a high speed so as to carry out at least reproduction of data, such as, a disc removable
5 type disc device for CD-ROM, DVD, MO, removable HDD or the like, and in particular to a disc device which is effective at a high rotational speed.

A conventional CD-ROM device is composed of a spindle motor system for rotating a disc, and a pick-up system for reading data
10 from the disc. On the disc, spiral or concentric recording pits are formed, onto which laser is projected from the pick-up system which is driven radially of the disc, and data are read through the reflection thereupon. The radial recording pitches of these recording pits are very fine, that is, 1.6 μm , and highly precise
15 positioning is required between the disc and the pick-up.

The following two problems are main factors which cause hindrance to positioning accuracy.

- (1) Vibration caused by the spindle drive system and the pick-up drive system; and
- 20 (2) External disturbance exerted from the outside.

The typical those of the problems stated in (1) are unbalance vibration of a rotary system, electromagnetic vibration of a motor or drive reaction of a pick-up drive system. It is most important to ensure a required degree of positioning accuracy under the
25 presence of these factors when designing the device. In particular, the unbalance vibration of the rotary system have been being materialized since the speed of rotation of a disc has been rapidly increased due to requirement of high speed data transfer.



Accordingly, as disclosed in Japanese Laid-Open Patent No. H3-86968, balance correction using fluid has been proposed.

It has been desired to increase the data transfer speed of the disc device due to the materialization of multi-media which
5 concerns a large volume of data of image or motion picture. The higher the rotational speed of a disc in a disc device, the higher the data transfer speed. Accordingly, these years, the rotational speed of an optical disc has been being rapidly increased.

The most serious problem which should be overcome for
10 increasing the rotational speed of a disc, is an increase in unbalance vibration. Different from a hard disc device, an optical disc device for CD-ROM or the like is essential in view of the compatibility of a disc as a recording medium used therein. Since the disc is mass-producible by pressing, the manufacturing accuracy
15 cannot be enhanced greatly, and accordingly, unevenness in thickness and eccentricity between the outer periphery and the inner periphery of a disc are large. Further, unbalance in weight caused by printing letters and a pattern on the disc is not negligible.

20 If a system having such a large unbalance is rotated, unbalance vibration would occur due to a cause such that the center of gravity of the rotary system does not precisely align with the rotating center thereof. The force causing unbalance vibration is exhibited by the following formula (1):

25
$$F = m \times \varepsilon \times \omega^2 \quad (1)$$

Where ε is a distance between the center of gravity and the rotating center of the rotary system, m is a mass of a rotary body, and ω is a rotational speed (rotational frequency).



As understood from formula (1), the unbalance vibration is proportional to the square of the rotational speed, and accordingly, it becomes serious rapidly if the rotational speed increases. The unbalance vibration not only vibrates the pick-up system so as to
5 hinder the read/write of signals and to cause noise, but also vibrates the system itself to which the device is attached, thereby remarkably lowering the reliability of the system itself.

This is because of the higher speed rotation of a disc due to the higher speed data transfer. For example, in the case of an 8-X
10 CD-ROM drive, the rotational speed is 4,200 r.p.m, and accordingly, the problem of unbalance vibration of a disc, as mentioned above, has been being materialized.

OBJECT AND SUMMARY OF THE INVENTION

One object of the present invention is to provide a highly
15 reliable disc device which incorporates in its drive system composed of a disc and a drive system, a mechanism for automatically correcting unbalance of the rotary system so as to restrain generation of vibration at a high rotational speed in order to carry out high speed data transfer.

20 In order to achieve the above-mentioned object, a rotary system having a natural frequency ω_n and a rotational frequency ω is set so that ω_n is lower than ω , that is, $\omega_n < \omega$, and an unbalance correcting mechanism including a mass system which can smoothly rotate about a rotary shaft, is provided, thereby it is
25 possible to correct unbalance of a rotary body itself through self-aligning action inherent to the rotary system during rotation.

Further, in addition to the above-mentioned unbalance correcting mechanism, an intermediate holding member which carries thereon a rotary drive system and an optical head is supported to a



casing or a unit mechanism base through resilient elements (vibration proof legs). It is noted that the natural frequency of the support system composed of the intermediate member and the resilient elements is set to be higher than 30 Hz but lower than 70 Hz, and a lift value of the transmission characteristic thereof is set to be higher than 8 dB at a resonance point. Thus, the above-mentioned resilient elements are made of silicon group rubber or fluorine group rubber, and the intermediate holding member is supported by the resilient elements at three or four points around the outer periphery thereof.

Further, in the unbalance correcting system, a ring-like groove around the rotary shaft as a center, is formed in a clamper for fixing a disc, a disk holding part (turntable) for fixing a disc, the rotor side surface of a motor or the interior of the motor, and more than two spherical correcting bodies are inserted in this groove.

BRIEF DESCRIPTION OF THE DRAWINGS:

Fig. 1 is an outside view illustrating a disc device in an embodiment of the present invention;

Fig. 2 is an outside view illustrating a unit mechanical part shown in Fig. 1;

Fig. 3 is a sectional view illustrating the disc device in which an unbalance correcting mechanism is provided in a clamper;

Figs. 4a and 4b are detailed sectional views illustrating the unbalance correcting mechanism;

Fig. 5 is a view illustrating unbalance correcting members and a rolling groove in an embodiment of the present invention;

Fig. 6a is a schematic view illustrating a disc and a motor shaft in a balanced state;



Fig. 6b is a schematic view similar to Fig. 6a, showing an unbalanced condition in which the natural frequency ω_n is higher than the rotational frequency ω ;

Fig. 6c is a schematic view similar to Fig. 6a, showing an unbalanced condition in which the natural frequency ω_n of the rotary system is lower than the rotational frequency ω thereof;

Fig. 7a is a view showing a positional relationship among correcting members, the rotational center, the center of gravity and the like in an unbalanced condition;

Fig. 7b is a view showing a condition during balance correction;

Fig. 7c is a view showing a condition after balance correction;

Fig. 8 is a sectional view illustrating the unbalance correcting mechanism incorporated in a turntable in an embodiment of the present invention;

Fig. 9 is a view showing displacement response and phase relationship of a support system;

Fig. 10 is a view showing an arrangement of the correcting members in the unbalance correcting mechanism;

Fig. 11 is a view showing a relationship between the frequency, the amplitude ratio and the like of vibration of a viscous damping system;

Fig. 12 is a view showing transmission characteristics of the resilient elements, which are different from one another due to natures of materials;

Fig. 13 is a sectional view illustrating a vibration proof leg in an embodiment of the present invention;



Fig. 14 is a view illustrating another embodiment of the present invention in which an unbalance correcting mechanism is incorporated in a clamper;

Fig. 15 is a view illustrating further another embodiment of the present invention in which an unbalance correcting mechanism is
5 incorporated in the rotor of a motor; and

Fig. 16 is a view illustrating an embodiment of the present invention in which a holding member for the correcting bodies are incorporated.

10 DESCRIPTION OF THE PREFERRED EMBODIMENTS

Fig. 1 is an outside view which shows an optical disc (CD-ROM) device in which an embodiment of the present invention is incorporated. Explanation will be hereinbelow made of basic operation of the optical disc device.

15 At first, a disc tray 31 for loading a disc 2 into the disc device (or unloading the disc 2 from the disc device) is extended from an entrance slot formed in a front panel 1. The disc tray 31 is extended and retracted by a disc loading mechanism which is not shown. Then, the disc is set on the extended disc tray 31.
20 Thereafter, the disc tray 31 is retracted into the disc device by means of the loading mechanism, and then, the disc 2 is shifted onto a turntable 15 as a disc carrying part provided to the shaft of a motor (spindle motor). The disc 2 carried on the turntable 15 is held between a disc clamper 3 attached to a clamper holder 4 and
25 the turntable under magnetic attraction effected by the disc clamper 3.

It is noted that a rotary drive mechanism such as the spindle motor, an optical head for reading and writing data from and onto the disc, and a drive mechanism for the latter are provided on a

unit mechanical chassis 11 serving as an intermediate holding member.

Next, the disc 2 is rotated at a predetermined rotational speed by the spindle motor, and data are written onto or read from
5 the disc 2 by the optical head which is not shown, carried on the unit mechanical chassis 11 located below the disc 2. The optical head incorporates an objective lens drive mechanism and a shift means by which the optical head can be moved radially of the disc 2. The unit mechanism chassis 11 is supported on a unit mechanical
10 holder 12 secured to a unit mechanical base 18 through the intermediary of vibration proof legs 13a, 13b, 13c formed of resilient elements. Alternatively, it is supported directly to the base of a casing (unit mechanical housing) through the intermediary of the vibration proof legs without the unit mechanical holder 12
15 intervening therebetween.

According to the present invention, an unbalance correcting mechanism for automatically correcting unbalance of the disc 2 is provided in the optical disc device in order to enhance the vibration-proof function of the optical disc device. Further, the
20 natural frequency of a vibration system including the above-mentioned vibration proof legs is set to a predetermined value.

The disc 2 used in a CD-ROM device or a DVD device is a removable. Since the disc 2 is mass-produced by pressing or the like, the manufacturing accuracy thereof cannot be made to be so
25 high, that is, the unevenness of the thickness of the disc, and the unevenness of concentricity between the outer and inner peripheries of the disc are relative large. Unbalance of the disc 2 caused by letters and a pattern printed on the disc 2 and caused by a sorting label or the like stuck to the disc by the user is not negligible.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

That is, the disc 2 itself is unbalanced in weight by usually 1 gcm at maximum. Thus, if such a disc 2 is rotated at a high speed, unbalanced load which is greatly increased by the rotation of the disc 2 is exerted to the spindle motor 2 for carrying the disc 2.

- 5 Vibration of rotational primary component of the disc 2 caused by the unbalance load is transmitted to the unit mechanical chassis through the intermediary of the spindle motor, resulting in the vibration of the device itself and interference contact between the components or the like, which are caused by the transmitted
10 vibration, and accordingly, noise is produced.

Next, the principle of the unbalance correcting mechanism will be explained, referring to Figs. 6 and 7.

- Figs. 6a to 6c are schematic views which show a motor and a disc attached to the motor, in which reference numeral 0 denotes
15 the rotational center of a bearing, S denotes the rotational center of the disc at the surface thereof, and G denotes the center of gravity of the disc. In an ideal rotary body with no unbalance, O, S and G are completely coincident with one another as shown in Fig. 6a, but in an unbalanced rotary body, the shaft is drawn outward by
20 the centrifugal force of the unbalance, causing deflection or deformation of the shaft.

- The phases of the points S, G, relative to the point O, vary, depending upon the relationship between the natural frequency ω_n and the rotational frequency ω of the rotary system. This
25 condition is shown in Figs. 6b and 6c. If ω_n is greater than ω (Fig. 6b), the point G is positioned outside of the point S. If ω_n is equal to ω (critical), the points S, G are positioned on one and the same straight line. If ω is greater than ω_n (Fig. 6c, overcritical), this relationship is reversed so that the point S is

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

positioned outside of the point G. In order to correct the unbalancing, this overcritical condition is used.

Fig. 7 is a schematic view which shows the relationship among unbalance correction members (spherical bodies) provided in the rotary body, and the rotational center, the center of gravity and the like.

Two balance weights M1, M2 are provided so as to smoothly rotationally move in such a way that their centers move depict a locus S. It is estimated that the balance weights M1, M2 are secured in a condition as shown in Fig. 7a, until the overcritical condition occurs. The rotational speed increases to a constant rotational speed in the overcritical condition. In this condition, the positions of centrifugal forces F1, F2 exerted to the balance weights M1, M2 and the points O, S, G are shown in Fig. 7a in which the center G of gravity is that of the entire rotary system including the balance weights M1, M2. In this condition, if the fixing of the balance weights M1, M2 is released, the balance weights M1, M2 are shifted from the condition shown in Fig. 7a into a condition shown in Fig. 7b by the circumferential components of the centrifugal forces F1, F2. The shifting of the balance weights M1, M2 causes the center G of gravity to be shifted in an upward direction as viewed in the figure, that is, the direction toward S, and accordingly, the difference between the points S, G which approach each other becomes less. That is, the points S, G, O are coincident with one another in a direction in which the unbalancing is decreased due to the shifting of the balance weights M1, M2. That is, it continues until a condition in which the unbalancing is completely eliminated, occurs. Thus, the unbalance of the rotary

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

system which exists in the initial stage can be automatically corrected by the balance weights M1, M2.

Due to the provision of the above-mentioned automatic unbalance correcting mechanism for the rotary body, a disc having a large unbalance can be rotated at a high speed without generation of vibration, thereby it is possible to transmit data at a high speed with no deterioration of reliability.

Fig. 2 shows the external appearance of the unit mechanical part of the disc device (Fig. 1) incorporating the above-mentioned unbalance correcting mechanism.

In this embodiment, the unbalance correcting mechanism has a such an arrangement that a plurality of correcting balls (balance balls) 7 are provided in a groove formed in the disc carrying part (turn table) of the spindle motor. The optical head 8 incorporating the objective lens can be moved radially of the disc along a guide rail 16. The unit mechanical chassis 11 having a substantially rectangular shape in this embodiment is attached to the unit mechanical holder 12 by means of the vibration proof legs 13a, 13b, 13c and 13d.

Next, a specific embodiment of the automatic balance correcting mechanism will be explained.

Fig. 3 is a sectional view which shows a CD-ROM device provided with the unbalance correcting mechanism on the disc clamper side.

The disc 2 as a recording medium, is inserted into the device from the front panel 1 side by means of a tray of a loading device. At this time, a unit mechanical system composed of the spindle motor 14, the pick-up 9 and the drive system therefor, is retracted in order to hinder the loading of the disc 2. When the disc 2 is

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

completely inserted into the device, the unit mechanical system initiates its movement, and when the height of the turntable 15 attached to the spindle motor 14 becomes equal to the height of the disc 2, it stops the movement. Simultaneously, the disc 2 is
5 clamped by attracting forces of a magnet 27 on the turntable 15 and a magnetic member 6 provided to the clamper 3, and is secured by the clamp holder 4 and the clamp retainer 5. Thus, the disc 2 can be rotated by the spindle motor 14, and simultaneously, optical data on the disc 2 can be read by the optical head 8 attached to
10 the unit mechanical system. It is noted that the unit mechanical system is incorporated in a unit mechanical housing 10, and is covered with a top cover 9.

The unit mechanical base 18 is supported to the unit mechanical chassis 11 by means of vibration proof legs 13 made of
15 soft rubber or formed of springs. The purpose of the provision of the vibration proof legs 13 is to prevent unbalancing oscillation of the disc 2 from being transmitted outside of the device, to prevent vibration outside of the device from being transmitted to the unit mechanical base 18, and to effectively operate the
20 unbalance correcting mechanism.

Fig. 5 shows an example of the unbalance correcting mechanism. In this example, two rolling grooves are formed, each incorporating therein with a correcting member 1. However, it is natural that a single groove can incorporate two correcting bodies. The
25 explanation will be hereinbelow made with such an estimation that the single groove is used.

The first essential feature of the present invention is the provision of an unbalance correcting mechanism integrally with the above-mentioned clamper 3. This unbalance correcting mechanism is

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

composed of a ball guide having an arcuate rolling groove 17, and two correcting members (balance balls) 7a, 7b used in the groove 17.

The rolling groove 17 which is formed in the ball guide, extending circumferentially of the latter, has a width which is slightly larger than the diameter of the correcting members 7a, 7b, and is inserted therein with the two correcting members 7a, 7b. The side surfaces and the bottom surface of the rolling groove 17, and as well the outer surface of the correcting members 7 are finished so as to be smooth in order to allow the correcting members 7 to freely move in the rolling groove 17.

The material of the correcting members 7 should be selected so that it is nonmagnetic, and has a high density, and it can hardly cause occurrence of aging effect such as occurrence of abrasion or corrosion at the outer surfaces of the correcting members. If it is magnetic, it is magnetized by a clamping magnet 27 provided in the clamber 3 so as to cause such a problem that the two correcting members are attracted. If it has a low density, the degree of unbalance correction becomes small. The aging effect of the outer surface increases the frictional force which hinders the movement of the correcting members. In view of these problems, the correcting members are suitably made of nonmagnetic stainless steel or glass.

The maximum degree of unbalance which can be corrected is exhibited by the following formula in such a condition that the two balls assemble together in an unit body:

$$W = 2 \times mb \times r$$

Where mb is a weight of each of the correcting members 7, r is the rolling radius of the same. The maximum degree w of unbalance of the disc 2 can be considered by experience to be 1 gcm at maximum.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

If the rolling radius is $r = 1.75$ cm which is substantially equal to the outer diameter of the clasper 3, a required weight m_d of each of the correcting members 7 can be determined from the following formula;

5
$$m_b = w / (2 \times r) = 1 / (2 \times 1.75) = 0.28 \text{ g}$$

The weight of a stainless balls having a diameter of 4 mm is 0.27 g, and accordingly, the this ball can be used to cope with the above-mentioned maximum of unbalance of the disc 2.

The second essential feature of this embodiment is the provision of such an arrangement that the natural frequency ω_n which is exhibited by the following formula;

$$\omega_n = \sqrt{(m/K)}$$

where K is a rigidity of the above-mentioned vibration proof legs and M is a mass of the above-mentioned unit mechanical base 18, is set to be smaller than the rated rotational speed ω of the device, and the device is operated in an overcritical condition. Operation is made with the unbalance correcting mechanism having a configuration as mentioned above, and through the overcritical condition, the correcting members 7 are shifted in a direction reverse to that of the unbalance of the disc 2 since the phases of the center of gravity and the rotational center are reversed, and accordingly, the unbalance can be automatically corrected.

In the case of a CD-ROM device, the rotational speed of the spindle motor 14 is controlled so that the peripheral speed is constant. That is, when the pick-up 8 is located at the inner peripheral side, the rotational speed is high, but when it is located at the outer peripheral side, the rotational speed is low. The rotational speed at which an audio CD is reproduced, is called as a standard speed which is in a range between 3.8 Hz at its outer



periphery and 8.3 Hz at its inner periphery. Due to the demand of increasing the speed of data transmission speed, these days, the rotational speed of the CD-ROM device is planned to be 12 times as high as the standard speed (that is, 45 Hz at the outer periphery and 100 Hz at the inner periphery). The natural frequency ω_n is set to be higher than the rotational frequency of the standard speed at the inner periphery but is lower than the rotational frequency of the used speed at the outer periphery. If the natural frequency ω_n is set to a value lower than the standard rotational speed, the rigidity of the vibration proof legs has to be extremely small, and accordingly, the vibration proof legs would be greatly deformed when an external force is exerted thereto. Thus, it is anticipated that the disc 2 or the like cannot be stably supported, and accordingly, it is not practical. On the other hand, a rotational speed substantially equal to the standard speed does not cause a problem even though the unbalance vibration is not corrected since the unbalance vibration is small.

Attention has to be taken for the damping rate of the vibration when the natural frequency ω_n is set. In view of the vibration-proof, it is effective to use a material having a large damping rate in order to decrease the amplification factor of vibration peak. However, in this embodiment, the vibration proof legs made of such a material having a high damping rate causes a problem. Since the material having a high damping rate delays the reversing of the phase. As mentioned above, since the reversing of the phases of the rotational center and the center of gravity during overcritical operation is used in the unbalance correcting mechanism according to the present invention, the phases cannot be completely reversed if a the material having a high damping rate is

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

used, and accordingly, the effect of the correction is low. In the case of a damping rate which is 25 %, even though ω_n is set to one-third ($1/3$) of ω , the phase does not shift, exceeding an angle of 160 deg. in this condition, the effect of correction for
5 unbalance is low. In this embodiment, the damping rate is set to 5 % while ω_n is set to $1/2$ of ω , the reversing of the phases of about an angle of about 180 deg. can be obtained, thereby sufficient unbalance correction can be expected.

Fig. 4 is an embodiment in which the unbalance correcting
10 mechanism is provided in the disc clamp part.

The essential feature of this embodiment is the provision of a first clamp 19 on which the unbalance correcting mechanism composed of the correcting members 7 is provided, and a second clamp 20 incorporating a ball fixing mechanism which can be
15 vertically moved, coaxial with the first clamp 19 is provided. In the case of a CD-ROM device, since the rotation of the disc 2 is made in such a condition that the peripheral speed is constant, the spindle motor 14 is accelerated and decelerated in accordance with a position of the pick-up 8 in order to change the rotational speed.
20 In the case of no fixing mechanism for the correcting members 7, since the correcting members 7 would turn at a constant rotational speed upon such acceleration and deceleration, relative rotation occurs between the correcting members 7 and the disc 2. With a design such that full attention is made to the ranges of both
25 natural frequency ω_n and rotational speed ω , the correcting members 7 can be finally stabilized to their original correcting positions even though the rotational speed varies. However, since the frictional force between the rolling surface of the rolling groove 17 and the correcting members 7 is set to be low in order to



reduce the affection of the friction exerted to the correcting members 7, a time is required more or less until the correcting members are stabilized. If the period from the time when the rolling of the correcting members 7 is initiated due to
5 acceleration and deceleration to the time when it is stabilized, exceeds a seek time by which the pick-up 8 moves, data has to be read in an unstable vibration condition, causing deterioration of the reliability of the device itself. Thus, the fixing mechanism for the correcting members 7 are provided so that the correction is
10 once made, and in this condition, the correcting members 7 are fixed in this condition, thereby it is possible to solve the above-mentioned problems.

The second clamp 20 is assembled in such a way that a protrusion 23 of the second clamp 20 is snugly fitted in a hollow
15 shaft 22 of the first clamp, which extends from the first clamp, which is hollow and which is formed on its outside with a first clamp groove 24 so that the second clamp 20 can be rotated simultaneously with the rotation of the first clamp 19 while it can be vertically moved. Further, a spring 26 is provided between the
20 first clamp 19 and the second clamp 20 so that the first clamp 19 and the second clamp 20 are held to be opened if no vertical force is exerted thereto. The second clamp 20 is formed therein with several teeth 21 having a width which is narrower than the rolling groove 17, at a position just facing the rolling groove 17 for the
25 correcting members 7, formed in the first camp 19, the several teeth 21 being adapted to enter the ball rolling groove 17 of the first clamp 19 over the entire periphery thereof when the second clamp 20 lowers. The pitches of these teeth 21 is slightly larger than the diameter of the correcting member 7, but are equally

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

divided circumferentially. The height of the teeth 21 is set so that the gap between the bottoms of the rolling members 17 and the tip ends of the teeth 21 becomes smaller than the diameter of the correcting members 17 in such a condition that the first clamp 19
5 and the second clamp 20 are closed.

In such a condition that the first clamp 19 and the second clamp 20 are opened, the correcting members 7 can freely be moved in the rolling groove 17, but when they are closed, the correcting members 7 are clamped between the teeth 21 of the second clamp 20
10 so that they cannot be moved. In such a condition that the first clamp 19 and the second clamp 20 are opened, unbalance correction is carried out under overcritical condition, and after the correcting members 7 become stable, when the first and second clamps 19, 20 are closed, the corrected condition of the correcting
15 members 7 can be held. The opening and closing of the first and second clamps 19, 20 are carried out through the vertical motion of the unit mechanical base 18 upon ejection of the disc 2. In a conventional device, upon insertion of the disc 2, the unit mechanical base 18 is retracted downward in order to prevent the
20 spindle 14 from hindering the disc 2, and after the completion of insertion of the disc 2, the unit mechanical base 18 is raised up to an operating height so as to clamp the disc 2 with the use of the attracting forces of the magnet 27 provided in the spindle motor 14 and the magnetic member 6 provided to the clasper. This
25 operation is carried out by gear and cam mechanisms and a motor provided in the chassis 11 and the unit mechanical base 18. However, the essential feature of this embodiment in which the unit mechanical base 18 is raised upward from the retracted condition, and the first clamp 19 is attracted by the magnet 29 of the spindle

motor 14 so as to secure the disc 2 which can be therefore rotated, is the provision of such an arrangement that there are established a condition in which the first clamp 19 and the second clamp 20 are opened so that the correcting members 7 can be moved freely (which will be hereinbelow mentioned as "correcting mode"), and a condition in which the unit mechanical base 18 is further moved so as to close the first clamp 19 and the second clamp 20 in order to secure the correcting members 7 (which will be mentioned as "rated mode", Fig. 5b).

Explanation will be hereinbelow made of the operation. When the disc 2 is inserted, the unit mechanical base 18 takes the lowest position. As the disc is inserted, the unit mechanical base 18 is moved upward, and comes to a stop once in the correcting mode. In this condition, the first clamp 19 is operated so as to clamp the disc 2. In this phase, the first clamp 19 and the second clamp 20 are held to be opened, as shown in Fig. 4a, and accordingly, the correcting members 7 can freely move in the rolling groove 17. The positional relationship between the pick-up 8 and the disc 2 has been established. After starting of the rotation of the disc 2 by the spindle motor 14, the disc 2 is rotated at a constant rotational speed in an overcritical condition, exceeding the natural frequency ω_n of the rotary system. This rotational speed is determined in consideration with the damping characteristic of the above-mentioned vibration proof legs 13, but can be determined, irrespective of the rated rotational speed of the device itself. At the time when the correcting members 7 become stable at their correcting positions, the unit mechanical base 18 is further moved upward while the rotational speed being held, and comes to a stop in the rated mode. The first clamp 19 and the second clamp 20 are

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

gradually closed through the movement of the unit mechanism 18, and accordingly, the correcting members 7 are secured by the teeth 21 formed in the second clamp 20 in the rated mode, at the correcting positions. By securing the correcting members 7 at the positions
5 where the balance correction is made, the correcting body 7 is not moved even though the rotational speed is changed in association with a position of the pick-up 8 in order to make the line speed constant, and accordingly, it is possible to prevent deterioration of the seek performance.

10 In this embodiment, with the use of a vibration sensor such as an acceleration sensor, the manipulatability can be improved. For example, a vibration sensor is attached to the unit mechanical base 18. Explanation will be made of the operation of this embodiment in the case of the provision of the vibration sensor.
15 When the disc 2 is inserted, the unit mechanical base 18 is moved to a rated position, and the correcting members 7 are secured at arbitrary positions. Thereafter, the rotation of the motor is started. In this condition, the measurement of vibration is carried out. If it is determined that the level of vibration is low, the
20 data are read soon, but it is determined that the level of vibration is high, the unit mechanical base 18 is lowered down to the correcting mode position. Thereafter, the unbalance correction is carried out in a procedure similar to that made in the case of no provision of the vibration sensor. In the case of the presence
25 of the vibration sensor, no unbalance correction is required for every disc 2, and accordingly, it is possible to promote the operation steps from the insertion of the disc 2 to the stating of the reading of data.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

Next, explanation will be hereinbelow made of the arrangement in which two rolling grooves 17a, 17b are formed, and the correcting members 7a, 7b are incorporated in these grooves, respectively.

5 Should a plurality of correcting members 7 are incorporated in a single groove 17, the correcting members 7 impinge upon each other during unbalance correction, and cause occurrence of an unstable phenomenon. Further, in the case of using magnetic
10 correcting members 7, since it is magnetized, the correcting members 7 are attracted to each other. Thus, in this embodiment, the plurality of rolling grooves 17 are formed, and the correcting members 7 are incorporated in these rolling grooves 17, respectively. Thereby it is possible to enhance the reliability of the balance correction.

15 Next, explanation will be made of an arrangement in which the unbalance correcting mechanism is provided to the turntable of the spindle motor with reference to Fig. 8.

A disc rotating system for an optical disc, is composed of a spindle motor, a disc 2 serving as a recording medium, a disc
20 clamper 3 for securing the disc 2 onto the turntable 15, a rubber element 39 for preventing the disc from slipping, and the like. The spindle motor is composed of the turntable 15 for carrying the disc 2, a shaft 37 press-fitted in the turntable 15, and a rotor 36 press-fitted onto the shaft 37. A magnetic circuit for generating a
25 rotary drive power for the spindle motor 37 is formed in the rotor 36, and the rotor 36 serving as a rotary part is attached thereto with a cylindrical magnet multi-polarized. In the rotor 36, a core serving as a stationary part, and a coil are attached to a stator substrate 38.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

The shaft 37 is rotatably supported to the stationary side by means of a bearing 43 such as a ball bearing or a slide bearing. Further, the stationary part is secured onto the stator substrate 38 to which a spindle motor control substrate is applied. Detailed
5 explanation will be made of the turntable 15 incorporating the unbalance correcting mechanism as shown in the figure.

The turntable 15 is formed therein with a ring-like groove in which a disc securing magnet 41 is provided. A disc 2 carried on the turntable 15 is clamped by the disc clamper 3 from above so
10 that the disc 2 is secured. This is caused by the magnetic attracting force applied by an attracting iron plate 34 in the disc clamper 3, facing the disc securing magnet 41. A ring-like groove (rolling groove) is also formed in the turntable outside of the former ring-like groove, and is incorporated therein with
15 correcting members (balance balls) 7 for correcting unbalance. The groove in which the correcting members 7 are incorporated, is completely covered with a dust protecting cover 35 for preventing dust from entering therein from the outside.

As mentioned above, unbalance vibration caused by unbalance
20 of the disc 2 is exerted radially of the disc due to deflection and rotation of the shaft. If the unbalance correcting mechanism is incorporated in the turntable 15, the above-mentioned correcting members 7 also centrifugally act upon the rotary shaft. These two forces can be effected substantially in the same plane so as to
25 correct unbalance without exerting an angular moment to the shaft 3. Further, the ring-like groove formed in the turntable 15 is completely fixed to the shaft 37 as a rotary shaft, and accordingly, it can be easily formed, concentric with the rotary shaft, thereby

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

it is possible to reduce the rotational eccentricity of the ring-like groove.

Next, explanation will be made of the operation of the correcting members 7 with reference to Fig. 10.

5 Fig. 10 shows the configuration of the correcting members 7 set in the ring-like groove formed in the turntable 15.

 The correcting members 7 are used by at least two in the unbalance correcting mechanism in the present invention. Further, each of the correcting members 7 is formed of a nonmagnetic true-
10 circular rigid ball in order to prevent affection by a magnetic field. For example, in the case of the presence of disc unbalance in the lower part of the figure, a force caused by this disc unbalance is effected in a centrifugal direction (indicated by the arrow). On the contrary, in an ideal corrected condition, the
15 correcting members 7 are located in the direction opposite to the direction of the disc unbalance. The unbalance correcting force at this time is effected in the direction of a component of a centrifugal force exerted to the correcting members 7, opposite to the direction of the unbalance. In the case of the presence of a
20 plurality of the correcting members 7, the sum of the components of centrifugal forces exerted to the correcting members 7 gives an unbalance correcting force. Accordingly, the correcting members 7 located in the ring-like groove make contact with the pathway surface to which they cling under a centrifugal force while they
25 are arranged, adjacent to one another, and in this condition, the positions of correcting members 7a, 7b at opposite ends of them, are located in directions which are directed from the rotational center, right angles to the disc unbalance so that the components of the centrifugal force becomes zero. That is, in the case of the

This Sheet Has Been Replaced


THIS SHEET HAS BEEN
REPLACED

arrangement of the plurality of correcting members in the correcting direction, the shape and the number of the correcting members should be determined in such a way that the correcting members at the opposite ends are set within an angular range of less than 180 deg. In this embodiment, estimating that the degree of unbalance is 1 gcm in the worst case in view of a degree of a disc unbalance in a CD-ROM device in general, stainless rigid balls having a diameter of about 2 to 3 mm are used by a number of 8 to 15 as the correcting members 7 which can be set in a groove having a shape that can be formed in the turntable for a spindle motor available at present (the outer diameter of the balance ball pathway is about 25 mm). The effect of correction by these correcting members is 0.5 to 0.8 gcm, and accordingly, even in the case of the disc unbalance of 1 gcm, vibration can be restrained below a degree corresponding to an unbalance load of 0.5 to 0.2 gcm. Further, by making the correcting members from a material having a heavy density and by using a correcting pathway having a large diameter, the correcting force can be further increased. Although the explanation has been made such that spherical bodies such as the balance balls are used as the correcting members 7 for correction of unbalance, it goes without saying that not only the spherical bodies but also those which can move through the correcting grooves with a small frictional force, or fluid may be also used.

Further, in such a case that the frequency of replacement of discs is less, the correcting members may be secured after correction of unbalance, similar to the arrangement in which the unbalance correcting mechanism is incorporated in the clamp part, as mentioned above.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

In the device in this embodiment, the unit mechanical chassis 11 shown in Fig. 2, is supported to the unit mechanical holder 12 by means of four vibration proof legs 13a, 13b, 13c, 13d. The correcting members 7 is shifted toward the disc unbalance side in a range of $\omega_n > \omega$ where ω_n is the natural frequency of this support system, and ω the rotational frequency of the spindle motor at a start of rotation, that is, before the rotational frequency exceeds the natural frequency. The support system is a primary vibration system, and accordingly, the phase is inverted by an angle of 180 deg. when it exceeds an eigenvalue. Thus, if the rotational frequency ω exceeds the natural frequency ω_n , a force in a direction opposite to the direction of unbalance acts upon the correcting members. Accordingly, when the spindle motor is rotated at a rotational speed in a range of $\omega_n < \omega$, the correcting members are shifted in a direction of correction of unbalance. For the unbalance correction in this embodiment using this principle, the setting of a natural frequency of the support system, in particular, the vibration proof legs 13, the way of the direction of the shift of the phase in a frequency range exceeding the natural frequency, and so forth are important.

Fig. 9 shows a vibration transmitting characteristic of the vibration proof leg as mentioned above. The correcting members 7 located in the ring-like groove shown in Fig. 8, act in the direction of unbalance as shown in a range in which the rotational frequency ω of the spindle motor is less than the natural frequency ω_n exhibited by the vibration proof legs 13, due to a centrifugal force given by a disc unbalance. If it exceeds the natural frequency ω_n , the phase is inverted, exceeding an angle of 180 deg, the above-mentioned centrifugal force acts in a direction



opposite to the direction of unbalance so that the correcting members act in the direction of correction of unbalance.

Next, explanation will be made of the setting of the natural frequency. As mentioned as to the action of the unbalance
5 correcting mechanism, the natural frequency of the support system should be set to be lower than the rotational frequency of a disc. An objective lens actuator used in a CD-ROM device, a DVD device or the like, has two axial freedoms in order to allow its objective lens to follow a surface deflection (surface oscillation) or
10 eccentric motion of the disc. Specifically, it is in general supported by a suspension having freedoms in the above-mentioned directions.

The natural frequency of the suspension system is set to about 30 Hz for determining a d.c. sensibility of the actuator in
15 order to follow rotational primary components of surface deflection of $\pm 500 \mu\text{m}$ and an eccentricity of $\pm 70 \mu\text{m}$. Further, in order to carry out the correction of unbalance at the rotational speed higher than that of a 8x CD-ROM device which has remarkably exhibited unbalance frequency these days, the rotational speed of
20 8x is set to be lower than 70 Hz.

Next, explanation will be made of the damping characteristic of the support system. In the case of making the vibration proof
legs 13 of a material having a high degree of damping, the phase rotation is slow in a condition in which the rotational frequency
25 exceeds the natural frequency of the support system, due to the damping effect, and accordingly, a characteristic indicted by the chain line is exhibited. That is, the correcting members 7 are unstable around ideal positions by a degree corresponding to that the phase cannot be shifted toward the unbalance direction, that is,



a sufficient effect of correction cannot be obtained. Accordingly, in the correction of unbalance using the correcting members 7, the support by resilient members having a damping which is less than that of conventional support legs is preferable. With the resilient member having a small damping, when the rotational frequency exceeds the natural frequency, the phase shift is fast in comparison with vibration proof legs having a large damping, and accordingly, the correcting members 7 are shifted to positions which are substantially ideal.

10 Accordingly, the explanation will be made of the characteristics of the vibration proof legs 13 which are required for the correction of unbalance according to the present invention, with reference to Fig. 11, as to a vibration ratio (rotational frequency ω /natural frequency ω_n), an amplitude amplification factor and a phase characteristic.

For example, estimation is made such that the natural frequency of the support system given by the vibration proof legs 13, is 30 Hz, and the disc rotational speed of 5,500 revolution per minute (about 900 Hz) corresponding to that of a 10x CD-ROM. The vibration ratio should be three times, $90/30 = 3$, and the damping ratio ζ should be less than 0.2 in view of a phase shift of an angle larger than 170 deg. The amplitude amplification factor is about 2.5 when the damping ratio ζ is 0.2. Accordingly, in the above-mentioned condition, the degree of lift-up of the characteristic at the resonant point of the vibration proof legs 13 should be set to be greater than 2.5 times (8 dB).

Fig. 12 shows transmission ratios of materials of the resilient members used for the specific vibration proof legs at a resonant point. In general, butyl group rubber is used as the

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

material of the resilient members for the vibration proof legs in a CD-ROM drive or a DVD drive. As mentioned above, this is because of using the vibration legs having a high damping rate for preventing exciting force from being transmitted from the exterior to the interior. As to the vibration proof legs made of butyl group rubber having a rubber hardness of 30 degrees, and incorporated in, for example, an actual device, the amplitude amplification factor (transmission rate) is about 2 times at the resonant point as indicated by the solid line in the figure. In this case, estimating that the damping ratio ζ is about 0.25 and the vibration ratio is 3 times, the phase is not shifted, exceeding an angle of about 160 deg. and accordingly, ideal correction of balance cannot be made by the correcting members 7.

On the contrary, in the case of using silicon group rubber having a hardness of about 20 degrees, the amplitude amplification factor is about 7 times (when damping rate is obtained in the bandwise direction from the characteristics shown in Fig. 11, it becomes $\zeta = 0.06$). Further, in the case of using silicon group rubber having a hardness of 30 degrees, the amplification factor is about 20 times (when the damping rate is obtained from the characteristics shown in Fig. 11, it becomes $\zeta = 0.03$) as indicated by the one-dot chain line. As mentioned above, with the use of the vibration proof legs made of silicon group rubber, the damping rate ζ can be easily reduced from 0.06 to 0.03, and accordingly, if the vibration proof legs made of silicon group rubber is used, the phase is shifted by an angle of about 180 deg. under the same condition as mentioned above, the correcting members are shifted to ideal correcting positions. With the vibration proof legs having a usual shape, butyl group rubber can hardly increase the amplitude

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

amplification factor up to about 2.5 times at a resonant point, and accordingly, it is found that silicon group rubber is preferable. Further, the silicon group rubber is excellent in its temperature characteristic, and accordingly, it is possible to provide a disc
5 device having a high degree of reliability. It is noted that, in addition to the silicon group rubber, fluoro rubber having a small damping rate may be used in order to obtain similar effects.

Fig. 13 shows a sectional shape of the vibration proof legs in an embodiment. The vibration proof legs 13 has a structure in
10 which a shoulder is formed in the center part thereof. Thus, the shoulder of the vibration proof leg is supported by the unit mechanical chassis 11, and then the vibration proof leg 13 is fastened onto a boss part 44 provided on the unit mechanical holder 12 by a retaining screw 40. A gap is defined between the retaining
15 screw 40 and the inner surface side of the vibration proof leg 13. With this arrangement, the unit mechanical chassis 11 and the unit mechanical holder 12 are resiliently supported by the vibration proof leg 13. By using silicon group rubber or fluoro rubber as a material of the vibration proof leg, the unbalance correcting
20 mechanism as mentioned above, is operated so as to effect the correction of unbalance with a high degree of accuracy.

As mentioned above, with the use of the arrangement in which the unbalance correcting mechanism is incorporated in the turntable 15, the correction of unbalance can be made without great
25 improvement in the drive mechanism. Further, since the groove is formed in the turntable 15, the grooving process can be carried out so as to easily form a true-circular groove with no eccentricity with respect to the rotational center. Since nonmagnetic rigid balls are used for the correcting members 7, the degree of

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

correction is given by the sum of mass systems of the correcting members, thus it is possible to obtain a large degree of correction. Further, since the correcting members 7 are nonmagnetic, the correcting members can be prevented from being magnetically
5 attracted, and accordingly, the reliability of rolling thereof is high. Further, since silicon group rubber or fluoro rubber having a low damping, is used, the calculation of an eigenvalue of the support system is easy, and the damping effect in a high frequency range is great. Further, by using silicon group rubber or fluoro
10 rubber, the temperature characteristic is stable, and further, the aging effect is low, thereby it is possible to enhance the use life and the reliability.

Fig. 14 shows another embodiment of the unbalance correcting mechanism. In this embodiment, it is provided in the disc clasper 3,
15 similar to the embodiment shown in Fig. 3.

This embodiment is the same as the embodiment shown in Fig. 3, except that teeth 21 for securing the correcting balls (balance balls) are not formed on the calmpers holder 4 side, that is, this arrangement corrects the unbalance by using such a principle that
20 the unbalance balls are shifted so that the phase thereof is reversed by an angle of 180 deg, with the use of vibration of the support system through the vibration proof legs, similar to the afore-mentioned embodiment.

The effect and the like obtained thereby are similar to those
25 as mentioned above. However, this embodiment exhibits such a disadvantage that a true-circular groove in which the correcting members are set cannot be easily formed with respect to the rotational center.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

Fig. 15 is an embodiment in which the unbalance correcting mechanism is provided at a side surface of the rotor 36 of the motor. That is, a ring-like member formed in a groove in which the correcting members are set, is fitted in the rotor 36. Specifically,
5 the member 42 having a ring-like groove and the correcting members set in the ring-like groove are incorporated in the rotor 36.

In this case, since a bearing 43 for supporting the shaft 37 is present within the rotor 36, the moment exerted to the shaft 37 can be made to be small, and accordingly, the use life of the
10 bearing 43 can be enhanced. In the case of using fluid as the correcting members 7, the vertical dimensions can be increased so as to increase the cubage of the correcting member, and accordingly, it is possible to enhance the effect of correction. Further, the above-mentioned unbalance correcting mechanism may be provided to
15 the shaft 37 which is extended downward from the bearing 43, although it is not shown.

Fig. 16 is a sectional view which shows another embodiment of the present invention. This embodiment is substantially the same as that shown in Fig. 8, except that the unbalance correcting
20 mechanism is incorporated in the turntable 15, including a holding member 45 for holding the correcting members 7. Explanation will be hereinbelow made of the operation and the effect of the holding member 45. The condition shown in this figure, the rotational speed of a disc does not yet reach a resonant point of the rotational
25 support system.

In this embodiment, the holding member 45 is formed of a leaf spring which made of a resilient material, being bent at their outer peripheral part (forward end part). In the range of the rotational speed up to the resonant point, the correcting members 7

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

are pressed against the rolling groove by means of the leaf spring so as to be held, being prevented from shifting. This pressing force can be about a value which is slightly greater than the rolling resistance between the correcting members and the pathway surface, that is, the contact frictional force.

When the rotational speed of the disc exceeds the resonant point, the centrifugal force caused by the rotation acts upon the forward end of the leaf spring, the bent forward end part thereof starts its deformation in a horizontal direction. Accordingly, the pressing force exerted to the correcting members 7 is eliminated, and accordingly, the correcting members 7 can be freely moved. When the rotational speed exceeds the resonant point, the correcting members 7 is shifted in a direction reverse to the direction of unbalance by an angle of 180 deg., thereby it is possible to correct the unbalance.

Thus, the reason why the correcting members are held before the resonant point, is such that vibration caused by the rolling of the correcting members, which generates when passing the resonant point of the rotary support system in the case of a disc speed changing control system (For example, a CD-ROM drive or a DVD-ROM drive using a constant linear speed system) should be restrained. In the case of the constant disc speed control system (for example, an MO drive or a high speed CD-ROM system using an angularly constant system), the rotational speed rapidly rises up since the vibration which is caused by rolling of the correcting members when passing the resonant point of the rotary support system is restrained, similar to that mentioned above. Further, since the correcting members 7 can be released after completely passing the resonant point, and since a force can be prevented from being

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

effected in an unbalance direction but can be effected in only a correcting direction, unbalance of the disc can be stably corrected.

As mentioned above, the disc device according to the present invention, can automatically correct unbalance of the rotary system
5 including unbalance of the disc, and can reduce unbalance vibration caused by the rotary system. With this arrangement, focus errors and tracking errors caused by the unbalance vibration can be restrained, and vibration and noise can also be decreased. Further, a disc device using the unbalance correcting mechanism according to
10 the present invention can aim at increasing the rotational speed of a disc for high speed transmission of data, and at enhancing the degree of accuracy which is required when the density of data is increased to a high value.



WHAT IS CLAIMED IS:

1. A disc device incorporating a motor for rotating a replaceable disc-like recording medium, characterized in that an unbalance correcting mechanism for restraining vibration caused by
5 rotation of said motor, is incorporated in a means for holding said recording medium.

2. A disc device as set forth in claim 1, characterized in that said unbalance correcting mechanism is incorporated in a disc clamper constituting said recording medium holding means.

10 3. A disc device as set forth in claim 1, characterized in that said unbalance correcting mechanism is provided in a disc holding bed constituting said recording medium holding means.

4. A disc device as set forth in claim 4, wherein said unbalance correcting mechanism is incorporated in a rotor in the
15 lower part of a disc holding bed for holding said recording medium.

5. A disc device as set forth in claim 1, characterized in that said unbalance correcting mechanism is composed of a rotary point pathway concentric with the rotational center of the motor, and more than one of correcting members which can move in the
20 rotary point pathway.

6. A disc device as set forth in claim 1, characterized in that said unbalance correcting mechanism is composed of a plurality of rotary path ways concentric with the rotating center of said motor, and at least one of movable correcting members set
25 respectively in said plurality of rotary pathways.

7. A disc device as set forth in claim 5 or 6, wherein said correcting members are more than two in number, and said correcting members are set in such a way that when said more than two of correcting members are arranged adjacent to one another at a

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



side wall of the rotary pathway during rotation, the correcting members at opposite ends make an angle less than 180 deg. with respect to the rotating center.

8. A disc device incorporating a motor for rotating a
5 replaceable rotary disc-like medium, characterized in that
an unbalance correcting mechanism for restraining vibration caused by rotation of said motor is incorporated in a means for holding a recording medium; and

said unbalance correcting mechanism is composed of a pathway
10 concentric with the rotating center of said motor, a plurality of correcting members adapted to move in said path way, and a securing means for securing said correcting members at arbitrary positions.

9. A disc device incorporating a rotary drive mechanism
for rotating a replaceable disc-like recording medium
15 characterized in that,
an unbalance correcting mechanism for correcting unbalance is incorporated in a rotary body rotating means in said rotary drive mechanism, and comprises a holding member for holding said rotary drive mechanism and a head having at least a reproducing function,
20 and a support member composed of resilient members, for supporting a casing and a unit holder to each other.

10. A disc device as set forth in claim 9, characterized
in that
said unbalance correcting mechanism is adapted to be operated
25 at a frequency higher than a frequency of vibration determined by a holding member holding a rotary drive mechanism including said recording medium, and a head having at least a reproducing function, and a resilient member of a support member holding said holding member to a casing or a unit holder.

This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED



11. A disc device as set forth in claim 9, characterized in that a holding system composed of said holding member and said supporting member has a natural frequency higher than 30 Hz but lower than 70 Hz, and exhibits a transmission characteristic having
5 a lift-up degree of higher than 8 dB at a resonant point.

12. A disc device as set forth in claim 9, characterized in that said support member supports said holding member at three or four points in the outer peripheral part of the latter, and said resilient member is made of silicon group rubber.

10 13. A disc device as set forth in claim 9, characterized in that said support member supports said holding member at three or four points in the outer peripheral part of the latter, and said resilient member is made of fluoro rubber.

14. A device as set forth in claim 9, characterized in that
15 said rotary body moving means incorporating said unbalance correcting mechanism is a rotary part which is nearer to a motor coil side than the recording medium holding means for holding said recording medium.

15. A disc device as set forth in claim 9, characterized in
20 that said rotary body moving means incorporating said unbalance correcting mechanism is a disc clamper or a turntable in the recording medium holding part for holding said recording medium.

16. A disc device incorporating a rotary drive mechanism for rotating a replaceable disc-like recording medium, and a head
25 having at least a function of reproducing data, characterized in that

said rotary drive mechanism incorporates an unbalance correcting mechanism which is composed of a groove formed in a turntable for carrying thereon said recording medium or a clamper



for securing said recording medium, and a plurality of spherical bodies adapted to move in said groove, and

said rotary drive mechanism and a holding means for holding said head are supported to a casing or a mechanical base by a
5 support means composed of a resilient members.

ABSTRACT OF DISCLOSURE

DISC DEVICE

In order to solve such a problem that primary rotational vibration which is caused by unbalance of the weight of a disc and which has been rapidly increased due to high speed rotation at present, vibrates a pick-up system, causing hindrance to reproduction signals, and produces noise and vibration of the device itself while deteriorates the reliability of the disc device, an unbalance correcting mechanism composed of a rotary pathway having a rotating center coincident with the rotating center of the disc and correcting members movable in the rotary pathway is provided in a holding means for holding the disc, and a support member for holding the rotary system and the pick-up system, and a casing are supported to each other by vibration proof legs having its natural frequency which is set to be higher than 30 Hz but lower than 70 Hz, and its amplitude amplification which is set to be higher than 80 dB at a resonant point, thereby it is possible to correct unbalance and restrain generation of vibration.

(Figure 3)

FIG. 1




FIG. 2




FIG. 3




FIG. 4A




FIG. 4B




FIG. 5




FIG. 6A




FIG. 6B




FIG. 6C




FIG. 7A





FIG. 7B




O: BEARING
ROTATING
CENTER

S: DISC
ROTATING
CENTER

G: CENTER OF
GRAVITY

FIG. 7C



This Sheet Has Been Replaced

THIS SHEET HAS BEEN
REPLACED

FIG. 8




FIG. 9





FIG. 10

LESS THAN 180 DEGREES



This Sheet Has Been Replaced

THIS SHEET HAS BEEN
REPLACED

FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15





FIG. 16



This Sheet Has Been Replaced



THIS SHEET HAS BEEN
REPLACED

REPLACEMENT SHEET

09 DEC 1997

DISC DEVICE

BACKGROUND OF THE PRESENT INVENTION

The present invention relates to a disc device which rotates a disc-like replaceable recording medium at a high speed so as to carry out at least reproduction of data, such as, a disc removable
5 type disc device for CD-ROM, DVD, MO, removable HDD or the like, and in particular to a disc device which is effective at a high rotational speed.

A conventional CD-ROM device is composed of a ^{rotary} ~~spindle~~-motor system for rotating a disc, and a pick-up system for reading data
10 from the disc. On the disc, spiral or concentric recording pits are formed, onto which laser is projected from the pick-up system which is driven radially of the disc, and data are read through the reflection thereupon. The radial recording pitches of these recording pits are very fine, that is, 1.6 μm , and highly precise
15 positioning is required between the disc and the pick-up.

The following two problems are main factors which cause hindrance to positioning accuracy.

- (1) Vibration caused by the ^{rotary} ~~spindle~~-drive system and the
pick-up drive system; and
- 20 (2) External disturbance exerted from the outside.

The typical those of the problems stated in (1) are unbalance vibration of a rotary system, electromagnetic vibration of a motor or drive reaction of a pick-up drive system. It is most important to ensure a required degree of positioning accuracy under the
25 presence of these factors when designing the device. In particular, the unbalance vibration of the rotary system have been being materialized since the speed of rotation of a disc has been rapidly increased due to requirement of high speed data transfer.

Accordingly, as disclosed in Japanese Laid-Open Patent No. H3-86968, balance correction using fluid has been proposed.

It has been desired to increase the data transfer speed of the disc device due to the materialization of multi-media which
 5 concerns a large ~~volume~~^{capacity} of data of image or motion picture. The higher the rotational speed of a disc in a disc device, the higher the data transfer speed. Accordingly, these years, the rotational speed of ~~an optical~~^{the} disc has been being rapidly increased.

The most serious problem which should be overcome for
 10 increasing the rotational speed of a disc, is an increase in unbalance vibration. Different from a hard disc device, an optical disc device for CD-ROM or the like is essential in view of the compatibility of a disc as a recording medium used therein. Since the disc is mass-producible by pressing, the manufacturing accuracy
 15 cannot be enhanced greatly, and accordingly, unevenness in thickness and eccentricity between the outer periphery and the inner periphery of a disc are large. Further, unbalance in weight caused by printing letters and a pattern on the disc is not negligible.

20 If a system having such a large unbalance is rotated, unbalance vibration would occur due to a cause such that the center of gravity of the rotary system does not precisely align with the rotating center thereof. The force causing unbalance vibration is exhibited by the following formula (1):

25
$$F = m \times \varepsilon \times \omega^2 \quad (1)$$

Where: ε is a distance between the center of gravity and the rotating center of the rotary system, m is a mass of a rotary body, and ω is a rotational speed (rotational frequency).

REPLACEMENT SHEET

09 DEC 1997

As understood from formula (1), the unbalance vibration is proportional to the square of the rotational speed, and accordingly, it becomes serious rapidly if the rotational speed increases. The unbalance vibration not only vibrates the pick-up system so as to hinder the read/write of signals and to cause noise, but also vibrates the system itself to which the device is attached, thereby remarkably lowering the reliability of the ^{computer} system itself.

This is because of the higher speed rotation of a disc due to the higher speed data transfer. For example, in the case of an 8-X CD-ROM drive, the rotational speed is 4,200 r.p.m, and accordingly, the problem of unbalance vibration of a disc, as mentioned above, has been being materialized.

OBJECT AND SUMMARY OF THE INVENTION

One object of the present invention is to provide a highly reliable disc device which incorporates in its drive system composed of a disc and a drive system, a mechanism for automatically correcting unbalance of the rotary system so as to restrain generation of vibration at a high rotational speed in order to carry out high speed data transfer.

In ^{order} ~~order~~ to achieve the above-mentioned object, a rotary system having a natural frequency ω_n and a rotational frequency ω is set so that ω_n is lower than ω , that is, $\omega_n < \omega$, and an unbalance correcting mechanism including a mass system which can smoothly rotate about a rotary shaft, is provided, thereby it is possible to correct unbalance of a rotary body itself through self-aligning action inherent to the rotary system during rotation.

Further, in addition to the above-mentioned unbalance correcting mechanism, an intermediate holding member which carries thereon a rotary drive system and an optical head is supported to a

REPLACEMENT SHEET

09 DEC 1997

casing or a unit mechanism base through resilient elements (vibration proof legs). It is noted that the natural frequency of the support system composed of the intermediate member and the resilient elements is set to be higher than 30 Hz but lower than 70 Hz, and a lift value of the transmission characteristic thereof is set to be higher than 8 dB at a resonance point. Thus, the above-mentioned resilient elements are made of silicon group rubber or fluorine group rubber, and the intermediate holding member is supported by the resilient elements at three or four points around the outer periphery thereof.

Further, in the unbalance correcting system, a ring-like groove around the rotary shaft as a center, is formed in a clamper for fixing a disc, a disk holding part (turntable) for fixing a disc, the rotor side surface of a motor or the interior of the motor, and more than two spherical correcting ^{members} bodies are inserted in this groove.

BRIEF DESCRIPTION OF THE DRAWINGS:

Fig. 1 is an outside view illustrating a disc device in an embodiment of the present invention;

Fig. 2 is an outside view illustrating a unit mechanical part shown in Fig. 1;

Fig. 3 is a sectional view illustrating the disc device in which an unbalance correcting mechanism is provided in a clamper;

Figs. ^{4A} 4a and ^{4B} 4b are detailed sectional views illustrating the unbalance correcting mechanism;

Fig. 5 is a view illustrating unbalance correcting members and a rolling groove in an embodiment of the present invention;

Fig. ^{6A} 6a is a schematic view illustrating a disc and a motor shaft in a balanced state;

REPLACEMENT SHEET

09 DEC 1997

Fig. ~~6a~~^{6B} is a schematic view similar to Fig. ~~6a~~^{6A}, showing an unbalanced condition in which the natural frequency ω_n is higher than the rotational frequency ω ;

Fig. ~~6c~~^{6C} is a schematic view similar to Fig. ~~6a~~^{6A}, showing an unbalanced condition in which the natural frequency ω_n of the rotary system is lower than the rotational frequency ω thereof;

Fig. ~~7a~~^{7A} is a view showing a positional relationship among correcting members, the rotational center, the center of gravity and the like in an unbalanced condition;

Fig. ~~7b~~^{7B} is a view showing a condition during balance correction;

Fig. ~~7c~~^{7C} is a view showing a condition after balance correction;

Fig. 8 is a sectional view illustrating the unbalance correcting mechanism incorporated in a turntable in an embodiment of the present invention;


Fig. 9 is a view showing displacement response and phase relationship of a support system;

Fig. 10 is a view showing an arrangement of the correcting members in the unbalance correcting mechanism;

Fig. 11 is a view showing a relationship between the frequency, the amplitude ratio and the like of vibration of a viscous damping system;

Fig. 12 is a view showing transmission characteristics of the resilient elements, which are different from one another due to natures of materials;

Fig. 13 is a sectional view illustrating a vibration proof leg in an embodiment of the present invention;



unit mechanical chassis 11 serving as an intermediate holding member.

Next, the disc 2 is rotated at a predetermined rotational speed by the spindle motor¹⁴, and data are written onto or read from the disc 2 by the optical head which is not shown, carried on the unit mechanical chassis 11 located below the disc 2. The optical head incorporates an objective lens drive mechanism and a shift means by which the optical head can be moved radially of the disc 2. The unit mechanism chassis 11 is supported on a unit mechanical holder 12 secured to a unit mechanical base 18 through the intermediary of vibration proof legs 13a, 13b, 13c formed of resilient elements. Alternatively, it is supported directly to the base of a casing (unit mechanical housing) through the intermediary of the vibration proof legs without the unit mechanical holder 12 intervening therebetween.

According to the present invention, an unbalance correcting mechanism for automatically correcting unbalance of the disc 2 is provided in the optical disc device in order to enhance the vibration-proof function of the optical disc device. Further, the natural frequency of a vibration system including the above-mentioned vibration proof legs¹³ is set to a predetermined value.

The disc 2 used in a CD-ROM device or a DVD device is a removable. Since the disc 2 is mass-produced by pressing or the like, the manufacturing accuracy thereof cannot be made to be so high, that is, the unevenness of the thickness of the disc, and the unevenness of concentricity between the outer and inner peripheries of the disc are relative large. Unbalance of the disc 2 caused by letters and a pattern printed on the disc 2 and caused by a sorting label or the like stuck to the disc² by the user is not negligible.

REPLACEMENT SHEET

09 DEC 1997

That is, the disc 2 itself is unbalanced in weight by usually 1 ^{g/cm} ~~g/cm~~ at maximum. Thus, if such a disc 2 is rotated at a high speed, unbalanced load which is greatly increased by the rotation of the disc 2 is exerted to the spindle motor ¹⁴ 2 for carrying the disc 2.

5 Vibration of rotational primary component of the disc 2 caused by the unbalance load is transmitted to the unit mechanical chassis through the intermediary of the spindle motor ¹⁴ resulting in the vibration of the device itself and interference contact between the components or the like, which are caused by the transmitted

10 vibration, and accordingly, noise is produced.

Next, the principle of the unbalance correcting mechanism will be explained, referring to Figs. 6 and 7.

^{6A} ^{6C}
Figs. 6a to 6e are schematic views which show a motor and a disc attached to the motor, in which reference numeral 0 denotes

15 the rotational center of a bearing, S denotes the rotational center of the disc at the surface thereof, and G denotes the center of gravity of the disc. In an ideal rotary body with no unbalance, O, S and G are completely coincident with one another as shown in Fig. ^{6A} 6a, but in an unbalanced rotary body, the shaft is drawn outward by

20 the centrifugal force of the unbalance, causing deflection or deformation of the shaft.

The phases of the points S, G, relative to the point O, vary, depending upon the relationship between the natural frequency ω_n and the rotational frequency ω of the rotary system. This

25 condition is shown in Figs. ^{6B} ^{6C} 6b and 6c. If ω_n is greater than ω (Fig. ^{6B} 6b), the point G is positioned outside of the point S. If ω_n is equal to ω (critical), the points S, G are positioned on one and the same straight line. If ω is greater than ω_n (Fig. ^{6C} 6c, overcritical), this relationship is reversed so that the point S is

REPLACEMENT SHEET

09 DEC 1997

positioned outside of the point G. In order to correct the unbalancing, this overcritical condition is used.

Fig. 7 is a schematic view which shows the relationship among ~~unbalance correction~~ ^{correcting} members ~~7a, 7b~~ (spherical bodies) provided in the rotary body, and the rotational center, the center of gravity and the like.

- ~~Two balance weights M1, M2~~ ^{correcting members 7a, 7b} are provided so as to smoothly rotationally move in such a way that their centers move ~~depict~~ ^{correcting members 7a, 7b} a locus S. It is estimated that the ~~balance weights M1, M2~~ ^{7A} are secured in a condition as shown in Fig. 7a, until the overcritical condition occurs. The rotational speed increases to a constant rotational speed in the overcritical condition. In this condition, the positions of centrifugal forces F1, F2 exerted to the ~~balance weights M1, M2~~ ^{correcting members 7a, 7b} and the points O, S, G are shown in Fig. 7a in which
- 15 the center G of gravity is that of the entire rotary system including the ~~balance weights M1, M2~~ ^{correcting members 7a, 7b}. In this condition, if the ~~fixing of the balance weights M1, M2~~ ^{correcting members 7a, 7b} is released, the ~~balance weights M1, M2~~ ^{correcting members 7a, 7b} are shifted from the condition shown in Fig. 7a into a condition shown in Fig. 7b by the circumferential components of
- 20 the centrifugal forces F1, F2. The shifting of the ~~balance weights M1, M2~~ ^{correcting members 7a, 7b} causes the center G of gravity to be shifted in an upward direction as viewed in the figure, that is, the direction toward S, and accordingly, the difference between the points S, G which approach each other becomes less. That is, the points S, G, O are
- 25 coincident with one another in a direction in which the unbalancing ~~is decreased~~ ^{correcting members 7a, 7b} due to the shifting of the ~~balance weights M1, M2~~. That is, it continues until a condition in which the unbalancing is completely eliminated, occurs. Thus, the unbalance of the rotary

REPLACEMENT SHEET

09 DEC 1997

system which exists in the initial stage can be automatically corrected by the ~~balance weights M1, M2.~~ ^{correcting members 7a, 7b.}

Due to the provision of the above-mentioned automatic unbalance correcting mechanism for the rotary body, a disc² having a large unbalance can be rotated at a high speed without generation of vibration, thereby it is possible to transmit data at a high speed with no deterioration of reliability.

Fig. 2 shows the external appearance of the unit mechanical part of the disc device (Fig. 1) incorporating the above-mentioned unbalance correcting mechanism.

In this embodiment, the unbalance correcting mechanism has a such an arrangement that a plurality of correcting ^{members} balls (balance balls) ^{7a, 7b} 7 are provided in a groove¹⁷ formed in the disc carrying part (turn table) of the spindle motor¹⁴. The optical head 8 incorporating the objective lens can be moved radially of the disc along a guide rail 16. The unit mechanical chassis 11 having a substantially rectangular shape in this embodiment is attached to the unit mechanical holder 12 by means of the vibration proof legs 13a, 13b, 13c and 13d.

Next, a specific embodiment of the automatic balance correcting mechanism will be explained.

Fig. 3 is a sectional view which shows a CD-ROM device provided with the unbalance correcting mechanism on the disc clamping³ side.

The disc 2 as a recording medium, is inserted into the device from the front panel 1 side by means of a tray of a loading device. At this time, a unit mechanical system composed of the spindle motor 14, the pick-up 9 and the drive system therefor, is retracted in order to hinder the loading of the disc 2. When the disc 2 is

REPLACEMENT SHEET

09 DEC 1997

completely inserted into the device, the unit mechanical system initiates its movement, and when the height of the turntable 15 attached to the spindle motor 14 becomes equal to the height of the disc 2, it stops the movement. Simultaneously, the disc 2 is
 5 clamped by attracting forces of a magnet 27 on the turntable 15 and a magnetic member 6 provided to the clamper 3, and is secured by the clamp holder 4 and the clamp retainer 5. Thus, the disc 2 can be rotated by the spindle motor 14, and simultaneously, optical data on the disc 2 can be read by the optical head 8 attached to
 10 the unit mechanical system. It is noted that the unit mechanical system is incorporated in a unit mechanical housing 10, and is covered with a top cover 9.

The unit mechanical base 18 is supported to the unit mechanical chassis 11 by means of vibration proof legs 13 made of
 15 soft rubber or formed of springs. The purpose of the provision of the vibration proof legs 13 is to prevent unbalancing oscillation of the disc 2 from being transmitted outside of the device, to prevent vibration outside of the device from being transmitted to the unit mechanical base 18, and to effectively operate the
 20 unbalance correcting mechanism.

Fig. 5 shows an example of the unbalance correcting mechanism. ^{17a, 17b}
 In this example, two rolling grooves_{17a, 17b} are formed, each incorporating therein with a correcting member 1. However, it is natural that a
 25 single groove can incorporate two correcting ^{members} bodies. The explanation will be hereinbelow made with such an estimation that the single groove is used.

The first essential feature of the present invention is the provision of an unbalance correcting mechanism integrally with the above-mentioned clamper 3. This unbalance correcting mechanism is

REPLACEMENT SHEET

09 DEC 1997

composed of a ball guide having an arcuate rolling groove 17, and two correcting members (balance balls) 7a, 7b used in the groove 17.

The rolling groove 17 which is formed in the ball guide, extending circumferentially of the latter, has a width which is slightly larger than the diameter of the correcting members 7a, 7b, and is inserted therein with the two correcting members 7a, 7b. The side surfaces and the bottom surface of the rolling groove 17, and as well the outer surface of the correcting members ^{7a, 7b}7 are finished so as to be smooth in order to allow the correcting members ^{7a, 7b}7 to freely move in the rolling groove 17.

The material of the correcting members 7 should be selected so that it is nonmagnetic, and has a high density, and it can hardly cause occurrence of aging effect such as occurrence of abrasion or corrosion at the outer surfaces of the correcting members. If it is magnetic, it is magnetized by a clamping magnet 27 provided in the clamping member 3 so as to cause such a problem that the two correcting members ^{7a, 7b}7 are attracted. If it has a low density, the degree of unbalance correction becomes small. The aging effect of the outer surface increases the frictional force which hinders the movement of the correcting members ^{7a, 7b}7. In view of these problems, the correcting members are suitably made of nonmagnetic stainless steel or glass.

The maximum degree of unbalance which can be corrected is exhibited by the following formula in such a condition that the two balls assemble together in an unit body:

$$W = 2 \times mb \times r$$

Where mb is a weight of each of the correcting members ^{7a, 7b}7, r is the rolling radius of the same. The maximum degree w of unbalance of the disc 2 can be considered by experience to be 1 ^{g.cm}g at maximum.

REPLACEMENT SHEET

09 DEC 1997

If the rolling radius is $r = 1.75$ cm which is substantially equal to the outer diameter of the clasper 3, a required weight m_d of each of the correcting members 7 can be determined from the following formula;

$$5 \quad m_b = w / (2 \times r) = 1 / (2 \times 1.75) = 0.28 \frac{\text{gf}}{\text{g}}$$

The weight of a stainless balls having a diameter of 4 mm is $0.27 \frac{\text{gf}}{\text{g}}$, and accordingly, the this ball can be used to cope with the above-mentioned maximum of unbalance of the disc 2.

The second essential feature of this embodiment is the provision of such an arrangement that the natural frequency ω_n which is exhibited by the following formula;

$$\omega_n = \sqrt{(m/K)}$$

where K is a rigidity of the above-mentioned vibration proof legs¹³, and M is a mass of the above-mentioned unit mechanical base 18, is set to be smaller than the rated rotational speed ω of the device, and the device is operated in an overcritical condition. Operation is made with the unbalance correcting mechanism having a configuration as mentioned above, and through the overcritical condition, the correcting members 7 are shifted in a direction reverse to that of the unbalance of the disc 2 since the phases of the center of gravity and the rotational center are reversed, and accordingly, the unbalance can be automatically corrected.

In the case of a CD-ROM device, the rotational speed of the spindle motor 14 is controlled so that the peripheral speed is constant. That is, when the pick-up 8 is located at the inner peripheral side, the rotational speed is high, but when it is located at the outer peripheral side, the rotational speed is low. The rotational speed at which an audio CD is reproduced, is called as a standard speed which is in a range between 3.8 Hz at its outer

REPLACEMENT SHEET

09 DEC 1997

periphery and 8.3 Hz at its inner periphery. Due to the demand of increasing the speed of data transmission speed, these days, the rotational speed of the CD-ROM device is planned to be 12 times as high as the standard speed (that is, 45 Hz at the outer periphery and 100 Hz at the inner periphery). The natural frequency ω_n is set to be higher than the rotational frequency of the standard speed at the inner periphery but is lower than the rotational frequency of the used speed at the outer periphery. If the natural frequency ω_n is set to a value lower than the standard rotational speed, the rigidity of the vibration proof legs¹³ has to be extremely small, and accordingly, the vibration proof legs¹³ would be greatly deformed when an external force is exerted thereto. Thus, it is anticipated that the disc 2 or the like cannot be stably supported, and accordingly, it is not practical. On the other hand, a rotational speed substantially equal to the standard speed⁽²⁾ does not cause a problem even though the unbalance vibration is not corrected since the unbalance vibration is small.

Attention has to be taken for the damping rate of the vibration when the natural frequency ω_n is set. In view of the vibration-proof, it is effective to use a material having a large damping rate in order to decrease the amplification factor of vibration peak. However, in this embodiment, the vibration proof legs¹³ made of such a material having a high damping rate causes a problem. Since the material having a high damping rate delays the reversing of the phase. As mentioned above, since the reversing of the phases of the rotational center and the center of gravity during overcritical operation is used in the unbalance correcting mechanism according to the present invention, the phases cannot be completely reversed if a the material having a high damping rate is


REPLACEMENT SHEET

09 DEC 1997

used, and accordingly, the effect of the correction is low. In the case of a damping rate which is 25 %, even though ω_n is set to one-third ($1/3$) of ω , the phase does not shift, exceeding an angle of 160 deg. in this condition, the effect of correction for
 5 unbalance is low. In this embodiment, the damping rate is set to 5 % while ω_n is set to $1/2$ of ω , the reversing of the phases of about an angle of about 180 deg. can be obtained, thereby sufficient unbalance correction can be expected.

Fig. 4 is an embodiment in which the unbalance correcting
 10 mechanism is provided in the disc clamp³ part.

The essential feature of this embodiment is the provision of a first clamp 19 on which the unbalance correcting mechanism composed of the correcting members 7 is provided, and a second clamp 20 incorporating a ball fixing mechanism which can be
 15 vertically moved, coaxial with the first clamp 19 is provided. In the case of a CD-ROM device, since the rotation of the disc 2 is made in such a condition that the peripheral speed is constant, the spindle motor 14 is accelerated and decelerated in accordance with a position of the pick-up 8 in order to change the rotational speed.
 20 In the case of no fixing mechanism for the correcting members 7, since the correcting members 7 would turn at a constant rotational speed upon such acceleration and deceleration, relative rotation occurs between the correcting members 7 and the disc 2. With a design such that full attention is made to the ranges of both
 25 natural frequency ω_n and rotational speed ω , the correcting members 7 can be finally stabilized to their original correcting positions even though the rotational speed_A ^{ω} varies. However, since the frictional force between the rolling surface of the rolling groove 17 and the correcting members 7 is set to be low in order to



reduce the affection of the friction exerted to the correcting members 7, a time is required more or less until the correcting members ⁷ are stabilized. If the period from the time when the rolling of the correcting members 7 is initiated due to acceleration and deceleration to the time when it is stabilized, exceeds a seek time by which the pick-up 8 moves, data has to be read in an unstable vibration condition, causing deterioration of the reliability of the device itself. Thus, the fixing mechanism for the correcting members 7 are provided so that the correction is once made, and in this condition, the correcting members 7 are fixed in this condition, thereby it is possible to solve the above-mentioned problems.

The second clamp 20 is assembled in such a way that a protrusion 23 of the second clamp 20 is snugly fitted in a hollow shaft 22 of the first clamp ¹⁹, which extends from the first clamp ¹⁹, which is hollow and which is formed on its outside with a first clamp groove 24 so that the second clamp 20 can be rotated simultaneously with the rotation of the first clamp 19 while it can be vertically moved. Further, a spring 26 is provided between the first clamp 19 and the second clamp 20 so that the first clamp 19 and the second clamp 20 are held to be opened if no vertical force is exerted thereto. The second clamp 20 is formed therein with several teeth 21 having a width which is narrower than the rolling groove 17, at a position just facing the rolling groove 17 for the correcting members 7, formed in the first camp 19, the several teeth 21 being adapted to enter the ball rolling groove 17 of the first clamp 19 over the entire periphery thereof when the second clamp 20 lowers. The pitches of these teeth 21 is slightly larger than the diameter of the correcting member 7, but are equally

REPLACEMENT SHEET

09 DEC 1997

motor 14 so as to secure the disc 2 which can be therefore rotated,
is the provision of such an arrangement that there are established
a condition in which the first clamp 19 and the second clamp 20 are
opened so that the correcting members 7 can be moved freely (which
5 will be hereinbelow mentioned as "correcting mode"), and a
condition in which the unit mechanical base 18 is further moved so
as to close the first clamp 19 and the second clamp 20 in order to
secure the correcting members 7 (which will be mentioned as "rated
mode", Fig. ^{5B}5b).

10 Explanation will be hereinbelow made of the operation. When
the disc 2 is inserted, the unit mechanical base 18 takes the
lowest position. As the disc ²_A is inserted, the unit mechanical base
18 is moved upward, and comes to a stop once in the correcting mode.
In this condition, the first clamp 19 is operated so as to clamp
15 the disc 2. In this phase, the first clamp 19 and the second clamp
20 are held to be opened, as shown in Fig. 4a, and accordingly, the
correcting members 7 can freely move in the rolling groove 17. The
positional relationship between the pick-up 8 and the disc 2 has
been established. After starting of the rotation of the disc 2 by
20 the spindle motor 14, the disc 2 is rotated at a constant
rotational speed in an overcritical condition, exceeding the
natural frequency ω_n of the rotary system. This rotational speed
is determined in consideration with the damping characteristic of
the above-mentioned vibration proof legs 13, but can be determined,
25 irrespective of the rated rotational speed of the device itself. At
the time when the correcting members 7 become stable at their
correcting positions, the unit mechanical base 18 is further moved
upward while the rotational speed being held, and comes to a stop
in the rated mode. The first clamp 19 and the second clamp 20 are

REPLACEMENT SHEET

09 DEC 1997

gradually closed through the movement of the unit mechanism 18, and accordingly, the correcting members 7 are secured by the teeth 21 formed in the second clamp 20 in the rated mode, at the correcting positions. By securing the correcting members 7 at the positions where the balance correction is made, the correcting members 7 are ~~body 7~~ is not moved even though the rotational speed is changed in association with a position of the pick-up 8 in order to make the line speed constant, and accordingly, it is possible to prevent deterioration of the seek performance.

10 In this embodiment, with the use of a vibration sensor such as an acceleration sensor, the manipulatability can be improved. For example, a vibration sensor is attached to the unit mechanical base 18. Explanation will be made of the operation of this embodiment in the case of the provision of the vibration sensor.

15 When the disc 2 is inserted, the unit mechanical base 18 is moved to a rated position, and the correcting members 7 are secured at arbitrary positions. Thereafter, the rotation of the motor is started. In this condition, the measurement of vibration is carried out. If it is determined that the level of vibration is low, the data are read soon, but it is determined that the level of

20 vibration is high, the unit mechanical base 18 is lowered down to the correcting mode position. Thereafter, the unbalance correction is carried out in a procedure similar to that made in the case of no provision of the vibration sensor. In the case of the presence

25 of the vibration sensor, no unbalance correction is required for every disc 2, and accordingly, it is possible to promote the operation steps from the insertion of the disc 2 to the stating of the reading of data.

REPLACEMENT SHEET

09 DEC 1997

Next, explanation will be hereinbelow made of the arrangement in which two rolling grooves 17a, 17b are formed, and the correcting members 7a, 7b are incorporated in these grooves, respectively.

5 Should a plurality of correcting members 7 are incorporated in a single groove 17, the correcting members 7 impinge upon each other during unbalance correction, and cause occurrence of an unstable phenomenon. Further, in the case of using magnetic correcting members 7, since it is magnetized, the correcting
10 members 7 are attracted to each other. Thus, in this embodiment, the plurality of rolling grooves 17 are formed, and the correcting members 7 are incorporated in these rolling grooves 17, respectively. Thereby it is possible to enhance the reliability of the balance correction.

15 Next, explanation will be made of an arrangement in which the unbalance correcting mechanism is provided to the turntable of the spindle motor¹⁴, with reference to Fig. 8.

A disc rotating system for an optical disc, is composed of a spindle motor¹⁴, a disc 2 serving as a recording medium, a disc
20 clamper 3 for securing the disc 2 onto the turntable 15, a rubber element 39 for preventing the disc from slipping, and the like. The spindle motor is composed of the turntable 15 for carrying the disc 2, a shaft 37 press-fitted in the turntable 15, and a rotor 36 press-fitted onto the shaft 37. A magnetic circuit for generating a
25 rotary drive power for the spindle motor¹⁴ 37 is formed in the rotor 36, and the rotor 36 serving as a rotary part is attached thereto with a cylindrical magnet multi-polarized. In the rotor 36, a core serving as a stationary part, and a coil are attached to a stator substrate 38.

REPLACEMENT SHEET

09 DEC 1997

The shaft 37 is rotatably supported to the stationary side by means of a bearing 43 such as a ball bearing or a slide bearing. Further, the stationary part is secured onto the stator substrate 38 to which a spindle motor control substrate is applied. Detailed
 5 explanation will be made of the turntable 15 incorporating the unbalance correcting mechanism as shown in the figure.

The turntable 15 is formed therein with a ring-like groove¹⁷_Λ in which a disc securing magnet 41 is provided. A disc 2 carried on the turntable 15 is clamped by the disc clamper 3 from above so
 10 that the disc 2 is secured. This is caused by the magnetic attracting force applied by an attracting iron plate 34 in the disc clamper 3, facing the disc securing magnet 41. A ring-like groove¹⁷_Λ (rolling groove) is also formed in the turntable¹⁵_Λ outside of the former ring-like groove¹⁷_Λ and is incorporated therein with
 15 correcting members (balance balls) 7 for correcting unbalance. The groove¹⁷_Λ in which the correcting members 7 are incorporated, is completely covered with a dust protecting cover 35 for preventing dust from entering therein from the outside.

As mentioned above, unbalance vibration caused by unbalance
 20 of the disc 2 is exerted radially of the disc due to deflection and rotation of the shaft. If the unbalance correcting mechanism is incorporated in the turntable 15, the above-mentioned correcting members 7 also centrifugally act upon the rotary shaft. These two forces can be effected substantially in the same plane so as to
 25 correct unbalance without exerting an angular moment to the shaft 3. Further, the ring-like groove¹⁷_Λ formed in the turntable 15 is completely fixed to the shaft 37 as a rotary shaft, and accordingly, it can be easily formed, concentric with the rotary shaft, thereby

REPLACEMENT SHEET


09 DEC 1997

it is possible to reduce the rotational eccentricity of the ring-like groove¹⁷_A

Next, explanation will be made of the operation of the correcting members 7 with reference to Fig. 10.

5 Fig. 10 shows the configuration of the correcting members 7 set in the ring-like groove¹⁷_A formed in the turntable 15.

The correcting members 7 are used by at least two in the unbalance correcting mechanism in the present invention. Further, each of the correcting members 7 is formed of a nonmagnetic true-
10 circular rigid ball in order to prevent affection by a magnetic field. For example, in the case of the presence of disc unbalance in the lower part of the figure, a force caused by this disc unbalance is effected in a centrifugal direction (indicated by the arrow). On the contrary, in an ideal corrected condition, the
15 correcting members 7 are located in the direction opposite to the direction of the disc unbalance. The unbalance correcting force at this time is effected in the direction of a component of a centrifugal force exerted to the correcting members 7, opposite to the direction of the unbalance. In the case of the presence of a
20 plurality of the correcting members 7, the sum of the components of centrifugal forces exerted to the correcting members 7 gives an unbalance correcting force. Accordingly, the correcting members 7 located in the ring-like groove¹⁷_A make contact with the pathway surface to which they cling under a centrifugal force while they
25 are arranged, adjacent to one another, and in this condition, the positions of correcting members 7a, 7b at opposite ends of them, are located in directions which are directed from the rotational center, right angles to the disc unbalance so that the components of the centrifugal force becomes zero. That is, in the case of the



arrangement of the plurality of correcting members in the correcting direction, the shape and the number of the correcting members should be determined in such a way that the correcting members at the opposite ends are set within an angular range of less than 180 deg. In this embodiment, estimating that the degree of unbalance is $1 \frac{\text{g}\cdot\text{cm}}{\text{cm}}$ in the worst case in view of a degree of a disc unbalance in a CD-ROM device in general, stainless rigid balls having a diameter of about 2 to 3 mm are used by a number of 8 to 15 as the correcting members 7 which can be set in a groove¹⁷ having a shape that can be formed in the turntable¹⁵ for a spindle motor available at present (the outer diameter of the balance ball pathway is about 25 mm). The effect of correction by these correcting members is 0.5 to $0.8 \frac{\text{g}\cdot\text{cm}}{\text{cm}}$, and accordingly, even in the case of the disc unbalance of $1 \frac{\text{g}\cdot\text{cm}}{\text{cm}}$, vibration can be restrained below a degree corresponding to an unbalance load of 0.5 to $0.2 \frac{\text{g}\cdot\text{cm}}{\text{cm}}$. Further, by making the correcting members from a material having a heavy density and by using a correcting pathway having a large diameter, the correcting force can be further increased. Although the explanation has been made such that spherical bodies such as the balance balls are used as the correcting members 7 for correction of unbalance, it goes without saying that not only the spherical bodies but also those which can move through the correcting grooves¹⁷ with a small frictional force, or fluid may be also used.

Further, in such a case that the frequency of replacement of discs is less, the correcting members may be secured after correction of unbalance, similar to the arrangement in which the unbalance correcting mechanism is incorporated in the clamp part, as mentioned above.

REPLACEMENT SHEET

09 DEC 1997

In the device in this embodiment, the unit mechanical chassis 11 shown in Fig. 2, is supported to the unit mechanical holder 12 by means of four vibration proof legs 13a, 13b, 13c, 13d. The correcting members 7 is shifted toward the disc unbalance side in a range of $\omega_n > \omega$ where ω_n is the natural frequency of this support system, and ω the rotational frequency of the spindle motor at a start of rotation, that is, before the rotational frequency exceeds the natural frequency. The support system is a primary vibration system, and accordingly, the phase is inverted by an angle of 180 deg. when it exceeds an eigenvalue. Thus, if the rotational frequency ω exceeds the natural frequency ω_n , a force in a direction opposite to the direction of unbalance acts upon the correcting members ⁷. Accordingly, when the spindle motor is rotated at a rotational speed in a range of $\omega_n < \omega$, the correcting members ⁷ are shifted in a direction of correction of unbalance. For the unbalance correction in this embodiment using this principle, the setting of a natural frequency ^{ω_n} of the support system, in particular, the vibration proof legs 13, the way of the direction of the shift of the phase in a frequency range exceeding the natural frequency ^{ω_n} and so forth are important.

Fig. 9 shows a vibration transmitting characteristic of the vibration proof leg ¹³ as mentioned above. The correcting members 7 located in the ring-like groove ¹⁷ shown in Fig. 8, act in the direction of unbalance as shown in a range in which the rotational frequency ω of the spindle motor is less than the natural frequency ω_n exhibited by the vibration proof legs 13, due to a centrifugal force given by a disc unbalance. If it exceeds the natural frequency ω_n , the phase is inverted, exceeding an angle of 180 deg, the above-mentioned centrifugal force acts in a direction

REPLACEMENT SHEET

09 DEC 1997

opposite to the direction of unbalance so that the correcting members ⁷ act in the direction of correction of unbalance.

Next, explanation will be made of the setting of the natural frequency ω_n . As mentioned as to the action of the unbalance correcting mechanism, the natural frequency ω_n of the support system should be set to be lower than the rotational frequency ω of a disc. An objective lens actuator used in a CD-ROM device, a DVD device or the like, has two axial freedoms in order to allow its objective lens to follow a surface deflection (surface oscillation) or eccentric motion of the disc. Specifically, it is in general supported by a suspension having freedoms in the above-mentioned directions.

The natural frequency ω_n of the suspension system is set to about 30 Hz for determining a d.c. sensibility of the actuator in order to follow rotational primary components of surface deflection of $\pm 500 \mu\text{m}$ and an eccentricity of $\pm 70 \mu\text{m}$. Further, in order to carry out the correction of unbalance at the rotational speed higher than that of a 8x CD-ROM device which has remarkably exhibited unbalance frequency these days, the rotational speed of 8x is set to be lower than 70 Hz.

Next, explanation will be made of the damping characteristic of the support system. In the case of making the vibration proof legs 13 of a material having a high degree of damping, the phase rotation is slow in a condition in which the rotational frequency exceeds the natural frequency ω_n of the support system, due to the damping effect, and accordingly, a characteristic indicted by the chain line is exhibited. That is, the correcting members 7 are unstable around ideal positions by a degree corresponding to that the phase cannot be shifted toward the unbalance direction, that is,

REPLACEMENT SHEET

09 DEC 1997

a sufficient effect of correction cannot be obtained. Accordingly, in the correction of unbalance using the correcting members 7, the support by resilient members having a damping which is less than that of conventional support legs is preferable. With the resilient member having a small damping, when the rotational frequency exceeds the natural frequency ω_n , the phase shift is fast in comparison with vibration proof legs ¹³ having a large damping, and accordingly, the correcting members 7 are shifted to positions which are substantially ideal.

10 Accordingly, the explanation will be made of the characteristics of the vibration proof legs 13 which are required for the correction of unbalance according to the present invention, with reference to Fig. 11, as to a vibration ratio (rotational frequency ω /natural frequency ω_n), an amplitude amplification


15 factor and a phase characteristic.

For example, estimation is made such that the natural frequency of the support system given by the vibration proof legs 13, is 30 Hz, and the disc rotational speed of 5,500 revolution per minute (about ⁹⁰~~900~~ Hz) corresponding to that of a 10x CD-ROM. The

20 vibration ratio should be three times, $90/30 = 3$, and the damping ratio ζ should be less than 0.2 in view of a phase shift of an angle larger than 170 deg. The amplitude amplification factor is about 2.5 when the damping ratio ζ is 0.2. Accordingly, in the above-mentioned condition, the degree of lift-up of the

25 characteristic at the resonant point of the vibration proof legs 13 should be set to be greater than 2.5 times (8 dB).

Fig. 12 shows transmission ratios of materials of the resilient members used for the specific vibration proof legs at a resonant point. In general, butyl group rubber is used as the



material of the resilient members for the vibration proof legs¹³ in a CD-ROM drive or a DVD drive. As mentioned above, this is because of using the vibration legs having a high damping rate for preventing exciting force from being transmitted from the exterior to the interior. As to the vibration proof legs¹³ made of butyl group rubber having a rubber hardness of 30 degrees, and incorporated in, for example, an actual device, the amplitude amplification factor (transmission rate) is about 2 times at the resonant point as indicated by the solid line in the figure. In this case, estimating that the damping ratio ζ is about 0.25 and the vibration ratio is 3 times, the phase is not shifted, exceeding an angle of about 160 deg. and accordingly, ideal correction of balance cannot be made by the correcting members 7.

On the contrary, in the case of using silicon group rubber having a hardness of about 20 degrees, the amplitude amplification factor is about 7 times (when damping rate is obtained in the bandwise direction from the characteristics shown in Fig. 11, it becomes $\zeta = 0.06$). Further, in the case of using silicon group rubber having a hardness of 30 degrees, the amplification factor is about 20 times (when the damping rate is obtained from the characteristics shown in Fig. 11, it becomes $\zeta = 0.03$) as indicated by the one-dot chain line. As mentioned above, with the use of the vibration proof legs¹³ made of silicon group rubber, the damping rate ζ can be easily reduced from 0.06 to 0.03, and accordingly, if the vibration proof legs¹³ made of silicon group rubber is used, the phase is shifted by an angle of about 180 deg. under the same condition as mentioned above, the correcting members⁷ are shifted to ideal correcting positions. With the vibration proof legs¹³ having a usual shape, butyl group rubber can hardly increase the amplitude

REPLACEMENT SHEET

09 DEC 1997

amplification factor up to about 2.5 times at a resonant point, and accordingly, it is found that silicon group rubber is preferable. Further, the silicon group rubber is excellent in its temperature characteristic, and accordingly, it is possible to provide a disc
5 device having a high degree of reliability. It is noted that, in addition to the silicon group rubber, fluoro rubber having a small damping rate may be used in order to obtain similar effects.

Fig. 13 shows a sectional shape of the vibration proof legs in an embodiment. The vibration proof legs 13 has a structure in
10 which a shoulder is formed in the center part thereof. Thus, the shoulder of the vibration proof leg ¹³ is supported by the unit mechanical chassis 11, and then the vibration proof leg 13 is fastened onto a boss part 44 provided on the unit mechanical holder 12 by a retaining screw 40. A gap is defined between the retaining
15 screw 40 and the inner surface side of the vibration proof leg 13. With this arrangement, the unit mechanical chassis 11 and the unit mechanical holder 12 are resiliently supported by the vibration proof leg 13. By using silicon group rubber or fluoro rubber as a material of the vibration proof leg ¹³, the unbalance correcting
20 mechanism as mentioned above, is operated so as to effect the correction of unbalance with a high degree of accuracy.

As mentioned above, with the use of the arrangement in which the unbalance correcting mechanism is incorporated in the turntable 15, the correction of unbalance can be made without great
25 improvement in the drive mechanism. Further, since the groove ¹⁷ is formed in the turntable 15, the grooving process can be carried out so as to easily form a true-circular groove ¹⁷ with no eccentricity with respect to the rotational center. Since nonmagnetic rigid balls are used for the correcting members 7, the degree of

REPLACEMENT SHEET

09 DEC 1997

correction is given by the sum of mass systems of the correcting members⁷, thus it is possible to obtain a large degree of correction. Further, since the correcting members 7 are nonmagnetic, the correcting members⁷ can be prevented from being magnetically
 5 attracted, and accordingly, the reliability of rolling thereof is high. Further, since silicon group rubber or fluoro rubber having a low damping, is used, the calculation of an eigenvalue of the support system is easy, and the damping effect in a high frequency range is great. Further, by using silicon group rubber or fluoro
 10 rubber, the temperature characteristic is stable, and further, the aging effect is low, thereby it is possible to enhance the use life and the reliability.

Fig. 14 shows another embodiment of the unbalance correcting mechanism. In this embodiment, it is provided in the disc clamper 3,
 15 similar to the embodiment shown in Fig. 3.

This embodiment is the same as the embodiment shown in Fig. 3, except that teeth 21 for securing the correcting ^{members} balls (balance balls) are not formed on the clamper holder 4 side, that is, this arrangement corrects the unbalance by using such a principle that
 20 correcting members⁷ the ~~unbalance balls~~ are shifted so that the phase thereof is reversed by an angle of 180 deg, with the use of vibration of the support system through the vibration proof legs¹³, similar to the afore-mentioned embodiment.

The effect and the like obtained thereby are similar to those
 25 as mentioned above. However, this embodiment exhibits such a disadvantage that a true-circular groove¹⁷ in which the correcting members⁷ are set cannot be easily formed with respect to the rotational center.




Fig. 15 is an embodiment in which the unbalance correcting mechanism is provided at a side surface of the rotor 36 of the motor. That is, a ring-like member ^{therein with} ¹⁷ formed in a groove ⁷ in which the correcting members are set, is fitted in the rotor 36. Specifically,
 5 the member 42 having a ring-like groove ¹⁷ and the correcting members set in the ring-like groove are incorporated in the rotor 36.

In this case, since a bearing 43 for supporting the shaft 37 is present within the rotor 36, the moment exerted to the shaft 37 can be made to be small, and accordingly, the use life of the
 10 bearing 43 can be enhanced. In the case of using fluid as the correcting members 7, the vertical dimensions can be increased so as to increase the cubage of the correcting member ⁷ and accordingly, it is possible to enhance the effect of correction. Further, the above-mentioned unbalance correcting mechanism may be provided to
 15 the shaft 37 which is extended downward from the bearing 43, although it is not shown.

Fig. 16 is a sectional view which shows another embodiment of the present invention. This embodiment is substantially the same as that shown in Fig. 8, except that the unbalance correcting
 20 mechanism is incorporated in the turntable 15, including a holding member 45 for holding the correcting members 7. Explanation will be hereinbelow made of the operation and the effect of the holding member 45. The condition shown in this figure, the rotational speed of a disc ² does not yet reach a resonant point of the rotational
 25 support system.

In this embodiment, the holding member 45 is formed of a leaf spring which made of a resilient material, being bent at their outer peripheral part (forward end part). In the range of the rotational speed up to the resonant point, the correcting members 7

REPLACEMENT SHEET

09 DEC 1997

are pressed against the rolling groove¹⁷ by means of the leaf spring so as to be held, being prevented from shifting. This pressing force can be about a value which is slightly greater than the rolling resistance between the correcting members⁷ and the pathway surface, that is, the contact frictional force.

When the rotational speed of the disc exceeds the resonant point, the centrifugal force caused by the rotation acts upon the forward end of the leaf spring, the bent forward end part thereof starts its deformation in a horizontal direction. Accordingly, the pressing force exerted to the correcting members 7 is eliminated, and accordingly, the correcting members 7 can be freely moved. When the rotational speed exceeds the resonant point, the correcting members 7 is shifted in a direction reverse to the direction of unbalance by an angle of 180 deg., thereby it is possible to correct the unbalance.

Thus, the reason why the correcting members are held before the resonant point, is such that vibration caused by the rolling of the correcting members⁷ which generates when passing the resonant point of the rotary support system in the case of a disc speed changing control system (For example, a CD-ROM drive or a DVD-ROM drive using a constant linear speed system) should be restrained. In the case of the constant disc speed control system (for example, an MO drive or a high speed CD-ROM system using an angularly constant system), the rotational speed rapidly rises up since the vibration which is caused by rolling of the correcting members⁷ when passing the resonant point of the rotary support system is restrained, similar to that mentioned above. Further, since the correcting members 7 can be released after completely passing the resonant point, and since a force can be prevented from being

REPLACEMENT SHEET

09 DEC 1997



WHAT IS CLAIMED IS:

1. A disc device incorporating a motor for rotating a replaceable disc-like recording medium, characterized in that an unbalance correcting mechanism for restraining vibration caused by rotation of said motor, is incorporated in a means for holding said recording medium.

2. A disc device as set forth in claim 1, characterized in that said unbalance correcting mechanism is incorporated in a disc clamper constituting said recording medium holding means.

3. A disc device as set forth in claim 1, characterized in that said unbalance correcting mechanism is provided in a disc holding bed constituting said recording medium holding means.

4. A disc device as set forth in claim ¹/₄, wherein said unbalance correcting mechanism is incorporated in a rotor in the lower part of a disc holding bed for holding said recording medium.

5. A disc device as set forth in claim 1, characterized in that said unbalance correcting mechanism is composed of a rotary point pathway concentric with the rotational center of the motor, and more than one of correcting members which can move in the rotary point pathway.

6. A disc device as set forth in claim 1, characterized in that said unbalance correcting mechanism is composed of a plurality of rotary path ways concentric with the rotating center of said motor, and at least one of movable correcting members set respectively in said plurality of rotary pathways.

7. A disc device as set forth in claim 5 or 6, wherein said correcting members are more than two in number, and said correcting members are set in such a way that when said more than two of correcting members are arranged adjacent to one another at a

REPLACEMENT SHEET

09 DEC 1997



side wall of the rotary pathway during rotation, the correcting members at opposite ends make an angle less than 180 deg. with respect to the rotating center.

8. A disc device incorporating a motor for rotating a
5 replaceable rotary disc-like medium, characterized in that
an unbalance correcting mechanism for restraining vibration caused by rotation of said motor is incorporated in a means for holding a recording medium; and
said unbalance correcting mechanism is composed of a pathway
10 concentric with the rotating center of said motor, a plurality of correcting members adapted to move in said path way, and a securing means for securing said correcting members at arbitrary positions.

9. A disc device incorporating a rotary drive mechanism
for rotating a replaceable disc-like recording medium
15 characterized in that,
an unbalance correcting mechanism for correcting unbalance is incorporated in a rotary body rotating means in said rotary drive mechanism, and comprises a holding member for holding said rotary drive mechanism and a head having at least a reproducing function,
20 and a support member composed of resilient members, for supporting a casing and a unit holder to each other.

10. A disc device as set forth in claim 9, characterized
in that
said unbalance correcting mechanism is adapted to be operated
25 at a frequency ^{of rotation} higher than a frequency of vibration determined by a holding member holding a rotary drive mechanism including said recording medium, and a head having at least a reproducing function, and a resilient member of a support member holding said holding member to a casing or a unit holder.

REPLACEMENT SHEET

09 DEC 1997

FIG. 7A





FIG. 7B




O: BEARING
ROTATING
CENTER

S: DISC
ROTATING
CENTER

G: CENTER OF
GRAVITY

FIG. 7C



REPLACEMENT SHEET

09 DEC 1997

FIG. 9





FIG. 10

LESS THAN 180 DEGREES



REPLACEMENT SHEET

09 DEC 1997

FIG. 15





FIG. 16



REPLACEMENT SHEET

09 DEC 1997