

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
17 November 2005 (17.11.2005)

PCT

(10) International Publication Number
WO 2005/107528 A2

(51) International Patent Classification⁷: **A47B 91/00**

(21) International Application Number:
PCT/US2004/043761

(22) International Filing Date:
22 December 2004 (22.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/565,715 27 April 2004 (27.04.2004) US

(71) Applicant and

(72) Inventor: **KEMENY, Zoltan, A.** [US/US]; 1809 East La
Vieve Lane, Tempe, AZ 85284 (US).

(74) Agent: **GOLTRY, Michael, W**; 340 East Palm Lane, Ste
260, Phoenix, AZ 85004 (US).

(81) Designated States (*unless otherwise indicated, for every
kind of national protection available*): AE, AG, AL, AM,

AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA,
ZM, ZW.

(84) Designated States (*unless otherwise indicated, for every
kind of regional protection available*): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM,
ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI,
FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO,
SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN,
GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— *without international search report and to be republished
upon receipt of that report*

*For two-letter codes and other abbreviations, refer to the "Guid-
ance Notes on Codes and Abbreviations" appearing at the begin-
ning of each regular issue of the PCT Gazette.*

(54) Title: DYNAMIC KINEMATIC MOUNT

(57) Abstract: A dynamic kinematic mount includes three balls, a first plate, and an opposing second plate. The first plate contacts the three balls at six contact points constraining translational and rotational movement of the first plate, and the second plate contacts the three balls at six contact points constraining translational and rotational movement of the second plate. Also provided is a spacer having opposing first and second faces and three bores extending therethrough from the first face to the second face. The three balls are each disposed in one of the three bores for rotation relative to the spacer, in which the three ball project outboard of the first and second faces. The first plate is in juxtaposition to the first face, and the second plate in juxtaposition to the second face.



WO 2005/107528 A2