

PROCESSING MATERIALS

[0001] This application incorporates by reference the full disclosure of the following co-pending provisional applications: USSN 61/711,801 and USSN 61/711,807 filed both filed October 10, 2012; the co-pending provisionals filed March 8, 2013: USSN 61/774,684; USSN 61/774,773; USSN 61/774,731; USSN 61/774,735; USSN 61/774,740; USSN 61/774,744; USSN 61/774,746; USSN 61/774,750; USSN 61/774,752; USSN 61/774,754; USSN 61/774,775; USSN 61/774,780; USSN 61/774,761; USSN 61/774,723; and USSN 61/793,336, filed March 15, 2013.

BACKGROUND OF THE INVENTION

[0002] Many potential lignocellulosic feedstocks are available today, including agricultural residues, woody biomass, municipal waste, oilseeds/cakes and seaweed, to name a few. At present, these materials are often under-utilized, being used, for example, as animal feed, biocompost materials, burned in a co-generation facility or even landfilled.

[0003] Lignocellulosic biomass includes crystalline cellulose fibrils embedded in a hemicellulose matrix, surrounded by lignin. This produces a compact matrix that is difficult to access by enzymes and other chemical, biochemical and/or biological processes. Cellulosic biomass materials (e.g., biomass material from which the lignin has been removed) is more accessible to enzymes and other conversion processes, but even so, naturally-occurring cellulosic materials often have low yields (relative to theoretical yields) when contacted with hydrolyzing enzymes. Lignocellulosic biomass is even more recalcitrant to enzyme attack. Furthermore, each type of lignocellulosic biomass has its own specific composition of cellulose, hemicellulose and lignin.

SUMMARY

[0004] This invention relates to systems, methods and processing equipment used for producing products from materials, such as biomass material. Generally, the method includes treating a recalcitrant biomass with electron beams while conveying the material using one or more conveyor and then biochemically and chemically processing the

reduced recalcitrance material to make, for example, ethanol, xylitol and/or other products. The processes and equipment include methods and systems for cooling while conveying and irradiating a material, such as a biomass.

[0005] In one aspect the invention relates to a method of conveying a material under
5 an electron beam including exposing a material, e.g., biomass material, to an electron
beam while conveying the material on a cooled surface (e.g., at least partially cooled
trough) of a conveyor. For example, conveying can include supporting the material (e.g.
biomass) on a first surface of the trough, and the method can include cooling a second
surface of the trough. The distance between the first and second surface of the trough can
10 be between about 1/64 "-2" (e.g., 1/64 "-1", 1/64 "-1/2", 1/32 "-1", 1/32 "-1/2", 1/32 "-
1/4", 1/16 "-1", 1/64 "-1/2", 1/64 "-1/4", 1/64 "-1/8", 1"-2"). The first and second
surfaces of the trough can be in thermal communication. Optionally, the electron beam
has at least 100 kW of power (e.g., at least 250 kW, at least 1000KW).

[0006] In another aspect the conveyor is vibrated. Optionally, the vibratory
15 conveyor has a trough and is oscillated in a direction parallel to the direction of
conveying and perpendicular to the electron beam. In some implementations, the trough
comprises a metal (e.g., aluminum, stainless steel number 316/316 L or any other alloys
of metals).

[0007] In some implementations, wherein there is a first and second surface in
20 thermal communication, the second surface can be cooled by contacting the surface with
an enclosure containing a cooling fluid. This trough configuration can be for both the
conveyor and the vibratory conveyor and the two configurations are denoted by
conveyor trough and a vibratory conveyor trough, respectively. Optionally, the second
surface of the conveyor forms a part of the enclosure. The method can further include
25 flowing fluid through the enclosure by flowing the cooling fluid into the enclosure
through an inlet to the enclosure and flowing the fluid out of the enclosure through an
outlet from the enclosure. Optionally, the enclosure comprises channels configured to
allow the flow of the cooling agent from the inlet to the outlet. Optionally, a difference in
the temperature of the cooling agent at the inlet of the enclosure to the temperature at the
30 outlet of the enclosure of between about 2 to 120 ° C can be maintained (e.g., between
about 2 to 30 ° C, between about 10 to 50 ° C, between about 20 to 70 ° C, between
about 30 to 90 ° C, between about 40 to 110 ° C, between about 50 to 120 ° C).
Optionally a flow rate of cooling fluid through the enclosure of between 0.5 and 150
gallons/min can be maintained.

[0008] In another aspect, the invention relates to an apparatus for irradiating a material. The apparatus can include an electron beam irradiation device and a vibratory conveying system. The conveying system can include a cooled trough. The trough can be configured to convey a material (e.g. a biomass material), for example, while the trough is being cooled. The trough can include a first surface configured to support and convey a biomass material, and a second surface that is in thermal communication with the first surface and is configured to contact a cooling system. The distance between the first and second surface of the trough can be between about 1/64"-2" (e.g. 1/64"-1", 1/64"-1/2", 1/32"-1", 1/32"-1/2", 1/32"-1/4", 1/16"-1", 1/64"-1/2", 1/64"-1/4", 1/64"-1/8", 1"-2"). Optionally, the cooling system comprises a cooling enclosure configured to contain a cooling fluid and positioned in thermal communication with the second surface. The cooling enclosure can include an inlet for the cooling fluid and an outlet for the cooling fluid. In addition, the enclosure can further include channels configured to allow flow of the cooling fluid through the enclosure from the inlet to the outlet. In some implementations, the apparatus includes an electron irradiation device that can have a relatively high total electron beam power of at least 25 kW (e.g., at least 100 kW at least 250 kW, at least 1000 kW). Optionally, the trough comprises a metal (e.g., aluminum, stainless steel number 316/316 L or any other alloys of metals). Alternatively, the trough comprises corrosion resistant metals such as Hastelloy, Inconel, Ultimet, Monel. Also the trough may be coated with corrosive resistant coating.

[0009] In yet another aspect, the invention relates to a method of conveying a material through a field of accelerated electrons, the electrons impinging upon a treatment zone of a conveyor, wherein the treatment zone includes a beam dump in thermal communication with the treatment zone. The beam dump can be optionally positioned on a side of the conveyor opposite impinging electrons. Optionally, the beam dump is integral with the treatment zone. The method can further include removing heat from the beam dump at a rate of between about 10 kW to 700 kW (e.g., about 25 kW to 500 kW, about 50kW to about 400 kW, about 75 kW to about 250 kW). For example, heat can be removed from the beam dump by flowing a cooling fluid through channels disposed within the beam dump. Optionally, the fluid enters the channels through an inlet and exits the channels through an outlet at a temperature less than about 140 ° C (e.g., less than about, 120 ° C, less than about 110 ° C, less than about 105 ° C, less than about, 100 ° C, or even less than about 80 ° C).

[0010] Optionally, both a cooling enclosure and a beam dump may be present.

These may both be located near or at the treatment zone. The cooling fluid used for the cooling enclosure may also be used in the beam dump in any convenient arrangement.

That is, the cooling fluid can flow sequentially and be put through the cooling enclosure first and the beam dump second or vice versa. Alternately, the fluid flow can be in parallel. Control systems can be used to optimize the use of the cooling fluid.

[0011] Cooling the conveyor during conveyance of materials, such as biomass, during irradiation is advantageous as this prevents overheating and possible destruction or degradation of the conveying equipment. Also, the overheating of the biomass can be minimized; the charring or burning of the biomass can be minimized.

[0012] Implementations of the invention can optionally include one or more of the following summarized features. In some implementations, the selected features can be applied or utilized in any order while in others implementations a specific selected sequence is applied or utilized. Individual features can be applied or utilized more than once in any sequence. In addition, an entire sequence, or a portion of a sequence, of applied or utilized features can be applied or utilized once or repeatedly in any order. In some optional implementations, the features can be applied or utilized with different, or where applicable the same, set or varied, quantitative or qualitative parameters as determined by a person skilled in the art. For example, parameters of the features such as size, individual dimensions (e.g., length, width, height), location of, degree (e.g., to what extent such as the degree of recalcitrance), duration, frequency of use, density, concentration, intensity and speed can be varied or set, where applicable as determined by a person of skill in the art.

[0013] Features, for example, include a method conveying a material under an electron beam, the method comprising: exposing a biomass material to an electron beam while conveying the biomass material, on a trough of a conveyor. The conveyor vibrates to move the biomass and the trough of the conveyor is cooled and is made of metals, alloys or coated metals. The trough consists of two surfaces which are in thermal communication and have a 1/64 to 2 inch separation between the two surfaces. The second surface can be cooled with a cooling fluid. The cooling fluid can flow through a cooling enclosure which is in contact with the second surface. The cooling enclosure has inlets and outlets for the cooling fluid and the temperature difference between the inlet and outlets is 2 to 120°C with a flow rate of cooling liquid of 0.5 to 150 gallons per minute. The total electron beam power is at least 50kW.

[0014] Furthermore, an embodiment of the invention is an apparatus which has an electron beam irradiating device where the beam is directed at a vibratory conveying device which has cooled trough. The trough has two surfaces, one to support and convey the biomass and the second in contact with a cooling enclosure through which cooling fluid flows from an inlet to an outlet. The cooling enclosure can have channels through which the cooling fluid flows. The trough can be made of metals, alloys of metals and coated metals. A factor in choosing the materials of the trough is there corrosion resistance. The distance between the first and second surfaces of the trough is 1/64 to 2 inches.

10 [0015] An additional embodiment is a method conveying a material through a field of accelerated electrons, the electrons impinging upon a treatment zone of a vibratory conveyor, wherein the treatment zone includes a beam dump in thermal communication with the treatment zone and can be positioned on a side of the vibratory conveyor opposite the side of the impinging electrons. Heat is removed from the beam dump at a rate of 10 kW to 700 kW. The heat removal from the beam dump can be by a cooling fluid flowing through channels within the beam dump. The cooling fluid for the channels of the beam dump flows through the channels and has an outlet temperature of less than about 140°C.

15 [0016] An alternate embodiment is a method of conveying a material through a field of accelerated electrons, the electrons impinging upon the treatment zone of a vibratory conveyor, wherein the treatment zone includes both a beam dump in thermal communication and a cooling enclosure in thermal communication with the treatment zone.

20 [0017] Other features and advantages of the invention will be apparent from the following detailed description, and from the claims.

25

DESCRIPTION OF THE DRAWINGS

[0018] The foregoing will be apparent from the following more particular description of example embodiments of the invention, as illustrated in the accompanying drawings in which like reference characters refer to the same parts throughout the different views. The drawings are not necessarily to scale, emphasis instead being placed upon illustrating embodiments of the present invention.

30 [0019] Fig. 1 is a side view of a system for irradiating a material with a cooled conveyor.

[0020] Fig. 2 is a perspective view of the optionally trough for the conveyor trough for conveying biomass taken from above and shown in outline.

[0021] Fig. 3 is a perspective view of the conveyor taken from below.

[0022] Fig. 4A is a perspective view of the cooling exchanger taken from below.

5 [0023] Fig. 4B is a cross-sectional view of the cooling exchanger taken along line 4B in Fig. 4A.

[0024] Fig. 5 is a perspective view of an enclosure that can be attached beneath the trough to cool the conveyors as they receive either direct or indirect radiation.

10

DETAILED DESCRIPTION

[0025] Using the methods and systems described herein materials, such as, cellulosic and lignocellulosic feedstock materials, for example, that can be sourced from biomass (e.g., plant biomass, animal biomass, paper, and municipal waste biomass) and that are often readily available but difficult to process, can be turned into useful products (e.g.,
15 sugars such as xylose and glucose, and alcohols such as ethanol and butanol). Included are methods and systems for cooling conveyors, or portions thereof, and/or the biomass while they are being heated as a result of irradiation.

[0026] Processes for manufacturing sugar solutions and products derived therefrom are described herein. These processes may include, for example, optionally mechanically
20 treating a cellulosic and/or lignocellulosic feedstock. Before and/or after this treatment, the feedstock can be treated with another physical treatment, for example irradiation, steam explosion, pyrolysis, sonication and/or oxidation to reduce, or further reduce its recalcitrance. A sugar solution is formed by saccharifying the feedstock by, for example, the addition of one or more enzymes. A product can be derived from the sugar solution,
25 for example, by fermentation to an alcohol. Further processing can include purifying the solution, for example by distillation. If desired, the steps of measuring lignin content and setting or adjusting process parameters (e.g., irradiation dosage) based on this measurement can be performed at various stages of the process, for example, as
described in U.S. Application Serial Number 12/704,519, filed on February 11, 2011, the
30 complete disclosure of which is incorporated herein by reference.

[0027] Several processes can occur in biomass when electrons from an electron beam interact with matter in inelastic collisions, for example, ionization of the material, chain scission of polymers in the material, cross linking of polymers in the material, oxidation of the material, generation of X-rays ("Bremsstrahlung") and vibrational excitation of

molecules (e.g., phonon generation). Without being bound to a particular mechanism, the reduction in recalcitrance of the biomass can be due to several of these inelastic collision effects, for example ionization, chain scission of polymers, oxidation and phonon generation. Some of the effects (e.g., especially X-ray generation), necessitate shielding and engineering barriers, for example, enclosing the irradiation processes in a concrete (or other radiation opaque material) vault. Another effect of irradiation, vibrational excitation, is equivalent to heating up the sample. Heating the sample by irradiation can help in recalcitrance reduction, but excessive heating can destroy the material, as will be explained below.

10 **[0028]** The adiabatic temperature rise (ΔT) from adsorption of ionizing radiation is given by the equation: $\Delta T = D/C_p$: where D is the average dose in kGy, C_p is the heat capacity in J/g $^{\circ}\text{C}$, and ΔT is the change in temperature in $^{\circ}\text{C}$. A typical dry biomass material will have a heat capacity close to 2. Wet biomass will have a higher heat capacity dependent on the amount of water since the heat capacity of water is very high (15 4.19 J/g $^{\circ}\text{C}$). Metals have much lower heat capacities, for example 304 stainless steel has a heat capacity of 0.5 J/g $^{\circ}\text{C}$. The adiabatic temperature rise from adsorption of ionizing radiation in a dry biomass and in stainless steel for various doses of radiation is shown in Table 1.

20 Table 1: Calculated Temperature increase for biomass and stainless steel.

Dose (Mrad)	Biomass ΔT ($^{\circ}\text{C}$)	Steel ΔT ($^{\circ}\text{C}$)
10	50	200
50	250	1000
100	500	2000
150	750	3000
200	1000	4000

[0029] High temperatures can destroy and/or modify the biopolymers in biomass so that the polymers (e.g., cellulose) are unsuitable for further processing. A biomass subjected to high temperatures can become dark, sticky and give off odors indicating decomposition. The stickiness can even make the material hard to convey. The odors can be unpleasant and be a safety issue. As a result, keeping the biomass below about 200 $^{\circ}\text{C}$ has been found to be beneficial in the processes described herein (e.g., below about 190 $^{\circ}\text{C}$, below about 180 $^{\circ}\text{C}$, below about 170 $^{\circ}\text{C}$, below about 160 $^{\circ}\text{C}$, below about 150 $^{\circ}\text{C}$,

below about 140°C, below about 130°C, below about 120°C, below about 110°C,
between about 60°C and 180°C, between about 60°C and 160°C, between about 60°C
and 150°C, between about 60°C and 140°C, between about 60°C and 130°C, between
about 60°C and 120°C, between about 80°C and 180°C, between about 100°C and
5 180°C, between about 120°C and 180°C, between about 140°C and 180°C, between
about 160°C and 180°C, between about 100°C and 140°C, between about 80°C and
120°C).

[0030] It has been found that irradiation above about 10 Mrad is desirable for the
processes described herein (e.g., reduction of recalcitrance). A high throughput is also
10 desirable so that the irradiation does not become a bottle neck in processing the biomass.
The treatment is governed by a Dose rate equation: $M = FP/D * \text{time}$, where M is the
mass of irradiated material (kg), F is the fraction of power that is adsorbed, P is the
emitted power (kW=Voltage in MeV * Current in mA), time is the treatment time (sec)
and D is the adsorbed dose (kGy). In an exemplary process where the fraction of
15 adsorbed power is fixed, the Power emitted is constant and a set dosage is desired, the
throughput (e.g., M, the biomass processed or any other material described herein) can
be increased by increasing the irradiation time. However, increasing the irradiation time
without allowing the material to cool can excessively heat the material, as exemplified
by the calculations shown above. Since biomass has a low thermal conductivity (less
20 than about 0.1 Wm-1K-1), heat dissipation is slow, unlike, for example metals (greater
than about 10 Wm-1K-1), which can dissipate energy quickly as long as there is a heat
sink to transfer the energy to. A solution to the aforementioned contrasting issues, the
need for a high radiation dose and rapid processing, without excessively heating the
irradiated material, is to cool the biomass as it is being irradiated and conveyed.

25 **[0031]** FIG. 1 shows a side view of a system for irradiating biomass with a cooled
conveyor with the vibratory conveyor configuration shown. The system includes an
electron beam irradiation device 110, which is supported by a thick concrete and H-bar
ceiling 120, for example as disclosed in U.S. Provisional Application 61/774,744, filed
March 8, 2013, the full disclosure of which is incorporated herein by reference. The
30 electron beam irradiation device includes an electron accelerator 112 and scan horn 114.
The scan horn is disposed above a vibratory conveyor 130 that conveys material under
the scan horn from the left to the right in the figure, as the conveyor oscillates generally
in the direction shown by the two headed arrows (some vibration also in and out of the
page and up and down occur). The vibratory conveyor 130 is preferably enclosed (e.g.,

includes a trough as will be discussed in detail below) and has windows, or cutouts, disposed to allow irradiation of the material. Conveyors and extraction windows are discussed in U.S. Provisional Application 61/711,801 U.S. Provisional Application 61/711,807 both filed October 10, 2012 the full disclosures of which are incorporated
5 herein by reference. A cooling system including an enclosure (e.g., a beam dump) 140 for flowing a cooling agent, e.g., a fluid or gas, beneath and in thermal contact (e.g., providing heat exchange) with the conveyor and conveyed material. The cooling agent can be a gas or a liquid; preferably, the cooling agent includes water. Glycols such as ethylene glycol or propylene glycol can also be used. For example, the cooling agent
10 may be an aqueous solution of a glycol, with glycol concentrations from 5 to 100% (at least 5%, at least 10%, at least 15%, at least 20%, at least 25%, between 25- 50%, between 50-75%, between 75-100%).

[0032] The flow rate of the cooling agent through the enclosure can be, for example, between about 0.5 to 150 gallons/minute (e.g., about 1 to 10, 10 to 30, 10 to 50, 50 to
15 100, 70 to 150, at least 20, at least 30, less than 100, less than 150 etc.). The cooling system is situated at a location so as to cool the area of the conveyor that receives the highest dose of radiation, either via irradiated biomass or direct irradiation of the conveyor. Generally, this location is underneath the trough directly below the scan horn. The dimensions of the cooling enclosure can be about 16 inches in length, 66 inches in
20 width and 3.5 inches in height where the length is measured in the direction of conveying material on the trough. The enclosure can hold up to about 550 cubic inches of cooling fluid. The dimensions of the trough above the cooling enclosure can be, e.g., 156 inches in length, 22.25 inches in width and 9.25 inches in height.

[0033] In some cases, for example as shown in FIG. 2, the cooling enclosure is
25 positioned adjacent to the trough portion of the conveyor. FIG. 2 is a top perspective view of a trough for conveying biomass shown in outline. The trough 210 is part of the vibratory conveyor discussed above, and, due to coupling to the oscillating systems of the conveyor, the trough generally oscillates in the direction indicated by the double-headed arrow. The trough can be made, for example, from aluminum or any alloys of
30 steel including steel 316/316 L. Biomass 220 can be dropped onto the trough surface 212, for example using a bias cut vibratory conveyor, at one end (the proximal end). Due to the oscillations of the trough, the biomass is conveyed on surface 212 and under the electron beam as shown by 230. The irradiated biomass 222 continues to the other end of the trough (the distal end) and drops off of the conveyor through a rectangular opening

214 in the trough. Alternative openings include circular, elliptical, slits (e.g., rectangular slits), an array of holes (e.g., circular holes, a mesh). Although not shown in Fig 2, the conveyor can be a surface without sides and not have a trough configuration.

5 **[0034]** A funnel 322 (FIG. 3) is disposed beneath the opening to direct the treated biomass to a collecting hopper and/or conveyor. The funnel can be attached to the conveyor trough. A cooling enclosure 140 (e.g., jacket and/or beam dump) is attached to the underside of the trough. As discussed above, a cooling agent flows through the cooling enclosure to cool the biomass and conveyor. Cooling enclosure 140 (e.g., jacket and/or beam dump) has an inlet 224 through which fluid enters the enclosure (not shown
10 in figure), and an outlet 226 through which cooling fluid exits the enclosure as shown in FIG. 2.

[0035] In some embodiments, the enclosure is configured to remove heat at a rate of 10 kW to about 700, e.g., between about 25 kW to about 500 kW, from about 50 kW to about 400 kW or between about 75 kW to about 250 kW.

15 **[0036]** FIG. 3 is a bottom perspective view of the optional vibratory conveyor. A 2-headed arrow indicates the general direction of oscillation of the conveyor. The figure shows the cooling enclosure 140 with arrows indicating the direction of the flow of the cooling agent inside the enclosure. Liquid or cooling gas enters from inlets located at 224 and exits from outlets located at 226. This view also shows the collection funnel 322
20 where the cooled and irradiated biomass is conveyed and subsequently collected.

[0037] FIG. 4A is a bottom perspective view of the cooling enclosure, e.g., a dimpled jacket heat exchanger plate, which can be made, for example of aluminum, stainless steel 316/316 L, or other metal alloys with thickness range of about between 1/64 "-2", 1/64 "-1", 1/64 "-1/2", 1/32 "-1", 1/32 "-1/2", 1/32 "-1/4", 1/16 "-1", 1/64 "-
25 1/2", 1/64 "-1/4", 1/64 "-1/8", 1"-2". Arrows indicate the direction of the flow of the cooling agent inside the enclosure. The cooling agent, which could be a liquid or chilled gas, enters from inlets located at 224 and exits from outlets located at 226. The cooling enclosure is in thermal contact with the conveyor, e.g., underneath, and conveyed biomass so that heat exchange can occur. Referring to FIGS. 4A and 4B, the heat
30 exchanger 416 can have dimples 414 (or welded points) which allow for increased surface area and provide a torturous path to the cooling fluid which can lead to a more efficient heat transfer from the conveyor to the cooling fluid.

[0038] FIG. 5 shows another embodiment of the cooling enclosure. In this case, the cooling agent flows through a tortuous cooling channel, rather than simply flowing

through an open enclosure. As shown in FIG. 5, liquid enters from inlet 224, flows through the cooling channel 226, which is supported on a planar substrate, and exits from outlet 512.

[0039] The difference in temperature of the cooling fluid near the inlet of the enclosure to the temperature near the outlet of the enclosure is between about 2 to 120 ° C, (e.g., between about 2 to 30 ° C, between about 10 to 50 ° C, between about 20 to 70 ° C, between about 30 to 90 ° C, between about 40 to 110 ° C, between about 50 to 120 ° C). The thermal gradient of the cooling system is also shown diagrammatically by the circled numbers in FIG. 5 (1 being the coolest and 5 the warmest temperature). Preferably, fluid, such as water glycol mixtures, exiting the jacket, is less than 140 ° C, such as less than about 120 ° C, less than about 110 ° C, less than about 105 ° C, less than about 100 ° C or even less than about 80 ° C. The temperature of the area of the trough facing (e.g., interior and/or surface temperatures) the irradiating electrons (e.g., in the irradiation zone) should remain below about 1000 ° C e.g., below about 500 ° C, below about 400 ° C, below about 300 ° C, below about 200 ° C, below about 150 ° C to avoid damaging the trough e.g., through warping, oxidation, sintering, grain growth. High temperatures can occur any time there is no work piece e.g., material such as biomass on the trough that is being irradiated, for example during startup, shutdowns and disruptions in the flow of biomass. Lower temperatures, for example below about 200 ° C e.g., below about 150 ° C, below about 140 ° C, below about 130 ° C, below about 120 ° C, below about 110 ° C, below about 100 ° C, below about 90 ° C, below about 80 ° C are preferable when a biomass material is being conveyed across the irradiated zone (e.g., to avoid decomposition, charring). Other embodiments of the cooling channel could be a U-tube exchanger or a straight tube exchanger with at least a one or two tube pass sides.

The conveyors (e.g., vibratory conveyor) can be made of corrosion resistant materials. The conveyors can utilize structural materials that include stainless steel (e.g., 304, 316 stainless steel, HASTELLOY® ALLOYS and INCONEL® Alloys). For example, HASTELLOY® Corrosion-Resistant alloys from Hynes (Kokomo, Indiana, USA) such as HASTELLOY® B-3® ALLOY, HASTELLOY® HYBRID-BC1® ALLOY, HASTELLOY® C-4 ALLOY, HASTELLOY® C-22® ALLOY, HASTELLOY® C-22IS® ALLOY, HASTELLOY® C-276 ALLOY, HASTELLOY® C-2000® ALLOY, HASTELLOY® G-30® ALLOY, HASTELLOY® G-35® ALLOY, HASTELLOY® N ALLOY and HASTELLOY® ULTIMET® alloy.

- [0040] The vibratory conveyors can include non-stick release coatings, for example, TUF-LON™ (Dupont, Delaware, USA). The vibratory conveyors can also include corrosion resistant coatings. For example coatings that can be supplied from Metal Coatings Corp (Houston, Texas, USA) and others such as Fluoropolymer, XYLAN®, Molybdenum Disulfide, Epoxy Phenolic, Phosphate- ferrous metal coating, Polyurethane- high gloss topcoat for epoxy, inorganic zinc, Poly Tetrafluoro ethylene, PPS/Ryton®, fluorinated ethylene propylene, PVDF/DYKOR®, ECTFE/HALAR® and Ceramic Epoxy Coating. The coatings can improve resistance to process gases (e.g., ozone), chemical corrosion, pitting corrosion, galling corrosion and oxidation.
- 10 [0041] The cooling jacket could also consist of a thermo electric system. Thermoelectric coolers operate by the Peltier effect or thermoelectric effect. The device has two sides, and when DC current flows through the device, it brings heat from one side to the other, so that one side gets cooler while the other gets hotter. The "hot" side is attached to a heat sink so that it remains at ambient temperature, while the cool side goes
- 15 below room temperature. In some applications, multiple coolers can be cascaded together for lower temperature.
- [0042] The cooling component can be equipped with temperature and flow rate detectors to maintain the desired range of temperature and flow rate of the cooling agent. The cooling fluid can also be recycled through a chilling loop attached to the outlets and
- 20 inlets of the cooling enclosure. The cooling enclosure could be welded/molded to the conveyor or be a removable unit, for example be mounted on rails or hinges and attached with fasteners.
- [0043] In some embodiments, the cooling fluid is cooled by utilizing a geothermal loop, for example a closed geothermal loop or an open geothermal loop. In addition, or
- 25 alternatively, fluid (e.g., water) from a cooling tower can be utilized. Additionally, or alternatively, a chiller, for example driven by a compressor (electric powered, gas powered) can be utilized to chill down cooling fluid. Cooling systems can be centralized and/or local systems, for example, a central cooling tower/geothermal loop can be combined with a smaller gas powered chiller. Some cooling methods that can be utilized,
- 30 for example, geothermal loops are described in US Provisional Application Serial No. 61/774,735 the entire disclosure of which is herein incorporated by reference.
- [0044] These cooling systems may be incorporated into the vibratory conveyor disclosed in US. Provisional Application 61/711,801 filed Oct. 10, 2012, the entire disclosure of which is herein incorporated by reference.

RADIATION TREATMENT

5 **[0045]** The feedstock may be treated with electron bombardment to modify its structure and thereby reduce its recalcitrance. Such treatment may, for example, reduce the average molecular weight of the feedstock, change the crystalline structure of the feedstock, and/or increase the surface area and/or porosity of the feedstock.

10 **[0046]** Electron bombardment via an electron beam is generally preferred, because it provides very high throughput and because the use of a relatively low voltage/high power electron beam device reduces the need or thickness of expensive concrete vault shielding, as such devices are “self-shielded” and provide a safe, efficient process. Electron beam accelerators are available, for example, from IBA, Belgium, and NHV Corporation, Japan.

15 **[0047]** Electron bombardment may be performed using an electron beam device that has a nominal energy of less than 10 MeV, e.g., less than 7 MeV, less than 5 MeV, or less than 2 MeV, e.g., from about 0.5 to 1.5 MeV, from about 0.8 to 1.8 MeV, or from about 0.7 to 1 MeV. In some implementations the nominal energy is about 500 to 800 keV.

20 **[0048]** The electron beam may have a relatively high total beam power (the combined beam power of all accelerating heads, or, if multiple accelerators are used, of all accelerators and all heads), e.g., at least 25 kW, e.g., at least 30, 40, 50, 60, 65, 70, 80, 100, 125, or 150 kW. In some cases, the power is even as high as 500 kW, 750 kW, or even 1000 kW or more. In some cases the electron beam has a beam power of 1200 kW or more. Alternately, the total beam power can be at least 50 kW, at least 100, at least 25 250 kW or at least 500kW.

30 **[0049]** This high total beam power is usually achieved by utilizing multiple accelerating heads. For example, the electron beam device may include two, four, or more accelerating heads. The use of multiple heads, each of which has a relatively low beam power, prevents excessive temperature rise in the material, thereby preventing burning of the material, and also increases the uniformity of the dose through the thickness of the layer of material.

[0050] It is generally preferred that the bed of biomass material has a relatively uniform thickness. In some embodiments the thickness is less than about 1 inch (e.g.,

less than about 0.75 inches, less than about 0.5 inches, less than about 0.25 inches, less than about 0.1 inches, between about 0.1 and 1 inch, between about 0.2 and 0.3 inches).

[0051] In some implementations, it is desirable to cool the material during and between dosing the material with electron bombardment. For example, the material can be cooled while it is conveyed, for example by a screw extruder, vibratory conveyor or other conveying equipment. For example, cooling while conveying is described in US Provisional Application No. 61/774,735 and 61/774,752 both filed on March 8, 2013 the entire description therein is herein incorporated by reference.

[0052] To reduce the energy required by the recalcitrance-reducing process, it is desirable to treat the material as quickly as possible. In general, it is preferred that treatment be performed at a dose rate of greater than about 0.25 Mrad per second, e.g., greater than about 0.5, 0.75, 1, 1.5, 2, 5, 7, 10, 12, 15, or even greater than about 20 Mrad per second, e.g., about 0.25 to 2 Mrad per second. Higher dose rates allow a higher throughput for a target (e.g., the desired) dose. Higher dose rates generally require higher line speeds, to avoid thermal decomposition of the material. In one implementation, the accelerator is set for 3 MeV, 50 mA beam current, and the line speed is 24 feet/minute, for a sample thickness of about 20 mm (e.g., comminuted corn cob material with a bulk density of 0.5 g/cm³).

[0053] In some embodiments, electron bombardment is performed until the material receives a total dose of at least 5 Mrad, e.g., at least 10, 20, 30 or at least 40 Mrad. In some embodiments, the treatment is performed until the material receives a dose of from about 10 Mrad to about 50 Mrad, e.g., from about 20 Mrad to about 40 Mrad, or from about 25 Mrad to about 30 Mrad. In some implementations, a total dose of 25 to 35 Mrad is preferred, applied ideally over a couple of seconds, e.g., at 5 Mrad/pass with each pass being applied for about one second. Applying a dose of greater than 7 to 8 Mrad/pass can in some cases cause thermal degradation of the feedstock material. Cooling can be applied before, after, or during irradiation. For example, the cooling methods, systems and equipment as described in the following applications can be utilized: US Provisional Application No. 61/774,735 and 61/774,754, both filed March 8, 2013, the entire disclosures of which are herein incorporated by reference.

[0054] Using multiple heads as discussed above, the material can be treated in multiple passes, for example, two passes at 10 to 20 Mrad/pass, e.g., 12 to 18 Mrad/pass, separated by a few seconds of cool-down, or three passes of 7 to 12 Mrad/pass, e.g., 9 to 11 Mrad/pass. As discussed herein, treating the material with several relatively low

doses, rather than one high dose, tends to prevent overheating of the material and also increases dose uniformity through the thickness of the material. In some implementations, the material is stirred or otherwise mixed during or after each pass and then smoothed into a uniform layer again before the next pass, to further enhance treatment uniformity.

[0055] In some embodiments, electrons are accelerated to, for example, a speed of greater than 75 percent of the speed of light, e.g., greater than 85, 90, 95, or 99 percent of the speed of light.

[0056] In some embodiments, any processing described herein occurs on lignocellulosic material that remains dry as acquired or that has been dried, e.g., using heat and/or reduced pressure. For example, in some embodiments, the cellulosic and/or lignocellulosic material has less than about 25 wt. % retained water, measured at 25°C and at fifty percent relative humidity (e.g., less than about 20 wt.%, less than about 15 wt.%, less than about 10 wt.%, less than about 5 wt.%).

[0057] Electron bombardment can be applied while the cellulosic and/or lignocellulosic material is exposed to air, oxygen-enriched air, or even oxygen itself, or blanketed by an inert gas such as nitrogen, argon, or helium. When maximum oxidation is desired, an oxidizing environment is utilized, such as air or oxygen and the distance from the beam source is optimized to maximize reactive gas formation, e.g., ozone and/or oxides of nitrogen.

[0058] In some embodiments, two or more electron sources are used, such as two or more ionizing sources. For example, samples can be treated, in any order, with a beam of electrons, followed by gamma radiation and UV light having wavelengths from about 100 nm to about 280 nm. In some embodiments, samples are treated with three ionizing radiation sources, such as a beam of electrons, gamma radiation, and energetic UV light. The biomass is conveyed through the treatment zone where it can be bombarded with electrons.

[0059] It may be advantageous to repeat the treatment to more thoroughly reduce the recalcitrance of the biomass and/or further modify the biomass. In particular the process parameters can be adjusted after a first (e.g., second, third, fourth or more) pass depending on the recalcitrance of the material. In some embodiments, a conveyor can be used which includes a circular system where the biomass is conveyed multiple times through the various processes described above. In some other embodiments, multiple treatment devices (e.g., electron beam generators) are used to treat the biomass multiple

(e.g., 2, 3, 4 or more) times. In yet other embodiments, a single electron beam generator may be the source of multiple beams (e.g., 2, 3, 4 or more beams) that can be used for treatment of the biomass.

5 **[0060]** The effectiveness in changing the molecular/supramolecular structure and/or reducing the recalcitrance of the carbohydrate-containing biomass depends on the electron energy used and the dose applied, while exposure time depends on the power and dose. The dose rate and total dose must be carefully controlled so as not to destroy (e.g., char or burn) the biomass material. For example, the carbohydrates should not be damaged in the processing so that they can be released from the biomass intact, e.g. as
10 monomeric sugars.

[0061] In some embodiments, the treatment (with any electron source or a combination of sources) is performed until the material receives a dose of at least about 0.05 Mrad, e.g., at least about 0.1, 0.25, 0.5, 0.75, 1.0, 2.5, 5.0, 7.5, 10.0, 15, 20, 25, 30, 40, 50, 60, 70, 80, 90, 100, 125, 150, 175, or 200 Mrad. In some embodiments, the
15 treatment is performed until the material receives a dose of between 0.1-100 Mrad, 1-200, 5-200, 10-200, 5-150, 50-150 Mrad, 5-100, 5-50, 5-40, 10-50, 10-75, 15-50, 20-35 Mrad.

[0062] In some embodiments, the treatment is performed at a dose rate of between 5 and 1500 kilorads/hour, e.g., between 10 and 750 kilorads/hour or between 50 and 350
20 kilorads/hours. In other embodiments the treatment is performed at a dose rate of between 10 and 10000 kilorads/hr., between 100 and 1000 kilorads/hr., or between 500 and 1000 kilorads/hr.

[0063] In some embodiments, relatively low doses of radiation are utilized, e.g., to increase the molecular weight of a cellulosic or lignocellulosic material (with any
25 radiation source or a combination of sources described herein). For example, a dose of at least about 0.05 Mrad, e.g., at least about 0.1 Mrad or at least about 0.25, 0.5, 0.75, 1.0, 1.5, 2.0, 2.5, 3.0, 3.5, 4.0, or at least about 5.0 Mrad. In some embodiments, the irradiation is performed until the material receives a dose of between 0.1 Mrad and 2.0 Mrad, e.g., between 0.5 rad and 4.0 Mrad or between 1.0 Mrad and 3.0 Mrad.

30 **[0064]** It also can be desirable to irradiate from multiple directions, simultaneously or sequentially, in order to achieve a desired degree of penetration of radiation into the material. For example, depending on the density and moisture content of the material, such as wood, and the type of radiation source used (e.g., gamma or electron beam), the maximum penetration of radiation into the material may be only about 0.75 inch. In such

a cases, a thicker section (up to 1.5 inch) can be irradiated by first irradiating the material from one side, and then turning the material over and irradiating from the other side. Irradiation from multiple directions can be particularly useful with electron beam radiation, which irradiates faster than gamma radiation but typically does not achieve as great a penetration depth.

RADIATION OPAQUE MATERIALS

[0065] The invention can include processing the material in a vault and/or bunker that is constructed using radiation opaque materials. In some implementations, the radiation opaque materials are selected to be capable of shielding the components from X rays with high energy (short wavelength), which can penetrate many materials. One important factor in designing a radiation shielding enclosure is the attenuation length of the materials used, which will determine the required thickness for a particular material, blend of materials, or layered structure. The attenuation length is the penetration distance at which the radiation is reduced to approximately $1/e$ (e = Euler's number) times that of the incident radiation. Although virtually all materials are radiation opaque if thick enough, materials containing a high compositional percentage (e.g., density) of elements that have a high Z value (atomic number) have a shorter radiation attenuation length and thus if such materials are used a thinner, lighter shielding can be provided. Examples of high Z value materials that are used in radiation shielding are tantalum and lead. Another important parameter in radiation shielding is the halving distance, which is the thickness of a particular material that will reduce gamma ray intensity by 50%. As an example for X-ray radiation with an energy of 0.1 MeV the halving thickness is about 15.1 mm for concrete and about 0.27 mm for lead, while with an X-ray energy of 1 MeV the halving thickness for concrete is about 44.45 mm and for lead is about 7.9 mm. Radiation opaque materials can be materials that are thick or thin so long as they can reduce the radiation that passes through to the other side. Thus, if it is desired that a particular enclosure have a low wall thickness, e.g., for light weight or due to size constraints, the material chosen should have a sufficient Z value and/or attenuation length so that its halving length is less than or equal to the desired wall thickness of the enclosure.

[0066] In some cases, the radiation opaque material may be a layered material, for example having a layer of a higher Z value material, to provide good shielding, and a layer of a lower Z value material to provide other properties (e.g., structural integrity,

impact resistance, etc.). In some cases, the layered material may be a "graded-Z" laminate, e.g., including a laminate in which the layers provide a gradient from high-Z through successively lower-Z elements. In some cases the radiation opaque materials can be interlocking blocks, for example, lead and/or concrete blocks can be supplied by
5 NEI.CO Worldwide (Burlington, MA), and reconfigurable vaults can be utilized as described in US Provisional Application No. 61/774,744.

[0067] A radiation opaque material can reduce the radiation passing through a structure (e.g., a wall, door, ceiling, enclosure, a series of these or combinations of these) formed of the material by about at least about 10 %, (e.g., at least about 20%, at least
10 about 30%, at least about 40%, at least about 50%, at least about 60%, at least about 70%, at least about 80%, at least about 90%, at least about 95%, at least about 96%, at least about 97%, at least about 98%, at least about 99%, at least about 99.9%, at least about 99.99%, at least about 99.999%) as compared to the incident radiation. Therefore, an enclosure made of a radiation opaque material can reduce the exposure of
15 equipment/system/components by the same amount. Radiation opaque materials can include stainless steel, metals with Z values above 25 (e.g., lead, iron), concrete, dirt, sand and combinations thereof. Radiation opaque materials can include a barrier in the direction of the incident radiation of at least about 1mm (e.g., 5 mm, 10 mm, 5 cm, 10 cm, 100 cm, 1 m, 10 m).

RADIATION SOURCES

[0068] The type of radiation determines the kinds of radiation sources used as well as the radiation devices and associated equipment. The methods, systems and equipment described herein, for example for treating materials with radiation, can utilized sources as
25 described herein as well as any other useful source.

[0069] Sources of gamma rays include radioactive nuclei, such as isotopes of cobalt, calcium, technicium, chromium, gallium, indium, iodine, iron, krypton, samarium, selenium, sodium, thalium, and xenon.

[0070] Sources of X-rays include electron beam collision with metal targets, such as tungsten or molybdenum or alloys, or compact light sources, such as those produced
30 commercially by Lyncean.

[0071] Alpha particles are identical to the nucleus of a helium atom and are produced by the alpha decay of various radioactive nuclei, such as isotopes of bismuth, polonium,

astatine, radon, francium, radium, several actinides, such as actinium, thorium, uranium, neptunium, curium, californium, americium, and plutonium.

[0072] Sources for ultraviolet radiation include deuterium or cadmium lamps.

[0073] Sources for infrared radiation include sapphire, zinc, or selenide window

5 ceramic lamps.

[0074] Sources for microwaves include klystrons, Slevin type RF sources, or atom beam sources that employ hydrogen, oxygen, or nitrogen gases.

[0075] Accelerators used to accelerate the particles (e.g., electrons or ions) can be electrostatic DC, e. g., electrodynamic DC, RF linear, magnetic induction linear or
10 continuous wave. For example, various irradiating devices may be used in the methods disclosed herein, including field ionization sources, electrostatic ion separators, field ionization generators, thermionic emission sources, microwave discharge ion sources, recirculating or static accelerators, dynamic linear accelerators, van de Graaff accelerators, Cockroft Walton accelerators (e.g., PELLETRON® accelerators), LINACS,
15 Dynamitrons (e.g., DYNAMITRON® accelerators), cyclotrons, synchrotrons, betatrons, transformer-type accelerators, microtrons, plasma generators, cascade accelerators, and folded tandem accelerators. For example, cyclotron type accelerators are available from IBA, Belgium, such as the RHODOTRON™ system, while DC type accelerators are available from RDI, now IBA Industrial, such as the DYNAMITRON®. Other suitable
20 accelerator systems include, for example: DC insulated core transformer (ICT) type systems, available from Nissin High Voltage, Japan; S-band LINACs, available from L3-PSD (USA), Linac Systems (France), Mevex (Canada), and Mitsubishi Heavy Industries (Japan); L-band LINACs, available from Iotron Industries (Canada); and ILU-based accelerators, available from Budker Laboratories (Russia). Ions and ion accelerators are
25 discussed in Introductory Nuclear Physics, Kenneth S. Krane, John Wiley & Sons, Inc. (1988), Krsto Prelec, FIZIKA B 6 (1997) 4, 177–206, Chu, William T., “Overview of Light-Ion Beam Therapy”, Columbus-Ohio, ICRU-IAEA Meeting, 18-20 March 2006, Iwata, Y. et al., “Alternating-Phase-Focused IH-DTL for Heavy-Ion Medical Accelerators”, Proceedings of EPAC 2006, Edinburgh, Scotland, , and Leitner, C.M. et
30 al., “Status of the Superconducting ECR Ion Source Venus”, Proceedings of EPAC 2000, Vienna, Austria. Some particle accelerators and their uses are disclosed, for example, in U.S. Pat. No. 7,931,784 to Medoff, the complete disclosure of which is incorporated herein by reference.

- [0076] Electrons may be produced by radioactive nuclei that undergo beta decay, such as isotopes of iodine, cesium, technetium, and iridium. Alternatively, an electron gun can be used as an electron source via thermionic emission and accelerated through an accelerating potential. An electron gun generates electrons, which are then
- 5 accelerated through a large potential (e.g., greater than about 500 thousand, greater than about 1 million, greater than about 2 million, greater than about 5 million, greater than about 6 million, greater than about 7 million, greater than about 8 million, greater than about 9 million, or even greater than 10 million volts) and then scanned magnetically in the x-y plane, where the electrons are initially accelerated in the z direction down the
- 10 accelerator tube and extracted through a foil window. Scanning the electron beams is useful for increasing the irradiation surface when irradiating materials, e.g., a biomass, that is conveyed through the scanned beam. Scanning the electron beam also distributes the thermal load homogenously on the window and helps reduce the foil window rupture due to local heating by the electron beam. Window foil rupture is a cause of significant
- 15 down-time due to subsequent necessary repairs and re-starting the electron gun.
- [0077] A beam of electrons can be used as the radiation source. A beam of electrons has the advantages of high dose rates (e.g., 1, 5, or even 10 Mrad per second), high throughput, less containment, and less confinement equipment. Electron beams can also have high electrical efficiency (e.g., 80%), allowing for lower energy usage relative to
- 20 other radiation methods, which can translate into a lower cost of operation and lower greenhouse gas emissions corresponding to the smaller amount of energy used. Electron beams can be generated, e.g., by electrostatic generators, cascade generators, transformer generators, low energy accelerators with a scanning system, low energy accelerators with a linear cathode, linear accelerators, and pulsed accelerators.
- 25 [0078] Electrons can also be more efficient at causing changes in the molecular structure of carbohydrate-containing materials, for example, by the mechanism of chain scission. In addition, electrons having energies of 0.5-10 MeV can penetrate low density materials, such as the biomass materials described herein, e.g., materials having a bulk density of less than 0.5 g/cm³, and a depth of 0.3-10 cm. Electrons as an ionizing
- 30 radiation source can be useful, e.g., for relatively thin piles, layers or beds of materials, e.g., less than about 0.5 inch, e.g., less than about 0.4 inch, 0.3 inch, 0.25 inch, or less than about 0.1 inch. In some embodiments, the energy of each electron of the electron beam is from about 0.3 MeV to about 2.0 MeV (million electron volts), e.g., from about 0.5 MeV to about 1.5 MeV, or from about 0.7 MeV to about 1.25 MeV. Methods of

irradiating materials are discussed in U.S. Pat. App. Pub. 2012/0100577 A1, filed October 18, 2011, the entire disclosure of which is herein incorporated by reference.

[0079] Electron beam irradiation devices may be procured commercially or built. For example elements or components such inductors, capacitors, casings, power sources, cables, wiring, voltage control systems, current control elements, insulating material, microcontrollers and cooling equipment can be purchased and assembled into a device. Optionally, a commercial device can be modified and/or adapted. For example, devices and components can be purchased from any of the commercial sources described herein including Ion Beam Applications (Louvain-la-Neuve, Belgium), NHV Corporation (Japan), the Titan Corporation (San Diego, CA), Vivirad High Voltage Corp (Billeric, MA) and/or Budker Laboratories (Russia). Typical electron energies can be 0.5 MeV, 1 MeV, 2 MeV, 4.5 MeV, 7.5 MeV, or 10 MeV. Typical electron beam irradiation device power can be 1 kW, 5 kW, 10 kW, 20 kW, 50 kW, 60 kW, 70 kW, 80 kW, 90 kW, 100 kW, 125 kW, 150 kW, 175 kW, 200 kW, 250 kW, 300 kW, 350 kW, 400 kW, 450 kW, 500 kW, 600 kW, 700 kW, 800 kW, 900 kW or even 1000 kW. Accelerators that can be used include NHV irradiators medium energy series EPS-500 (e.g., 500 kV accelerator voltage and 65, 100 or 150 mA beam current), EPS-800 (e.g., 800 kV accelerator voltage and 65 or 100 mA beam current), or EPS-1000 (e.g., 1000 kV accelerator voltage and 65 or 100 mA beam current). Also, accelerators from NHV's high energy series can be used such as EPS-1500 (e.g., 1500 kV accelerator voltage and 65 mA beam current), EPS-2000 (e.g., 2000 kV accelerator voltage and 50 mA beam current), EPS-3000 (e.g., 3000 kV accelerator voltage and 50 mA beam current) and EPS-5000 (e.g., 5000 and 30 mA beam current).

[0080] Tradeoffs in considering electron beam irradiation device power specifications include cost to operate, capital costs, depreciation, and device footprint. Tradeoffs in considering exposure dose levels of electron beam irradiation would be energy costs and environment, safety, and health (ESH) concerns. Typically, generators are housed in a vault, e.g., of lead or concrete, especially for production from X-rays that are generated in the process. Tradeoffs in considering electron energies include energy costs.

[0081] The electron beam irradiation device can produce either a fixed beam or a scanning beam. A scanning beam may be advantageous with large scan sweep length and high scan speeds, as this would effectively replace a large, fixed beam width. Further, available sweep widths of 0.5 m, 1 m, 2 m or more are available. The scanning

beam is preferred in most embodiments describe herein because of the larger scan width and reduced possibility of local heating and failure of the windows.

ELECTRON GUNS – WINDOWS

5 [0082] The extraction system for an electron accelerator can include two window foils. Window foils are described in U.S. Provisional Application Serial No. 61/711,801 filed Oct 10, 2012 the complete disclosure of which is herein incorporated by reference. The cooling gas in the two foil window extraction system can be a purge gas or a mixture, for example air, or a pure gas. In one embodiment the gas is an inert gas such
10 as nitrogen, argon, helium and or carbon dioxide. It is preferred to use a gas rather than a liquid since energy losses to the electron beam are minimized. Mixtures of pure gas can also be used, either pre-mixed or mixed in line prior to impinging on the windows or in the space between the windows. The cooling gas can be cooled, for example, by using a heat exchange system (e.g., a chiller) and/or by using boil off from a condensed gas (e.g.,
15 liquid nitrogen, liquid helium).

[0083] When using an enclosure, the enclosed conveyor can also be purged with an inert gas so as to maintain an atmosphere at a reduced oxygen level. Keeping oxygen levels low avoids the formation of ozone, which in some instances is undesirable due to its reactive and toxic nature. For example, the oxygen can be less than about 20% (e.g.,
20 less than about 10%, less than about 1%, less than about 0.1%, less than about 0.01%, or even less than about 0.001% oxygen). Purging can be done with an inert gas including, but not limited to, nitrogen, argon, helium or carbon dioxide. This can be supplied, for example, from a boil off of a liquid source (e.g., liquid nitrogen or helium), generated or separated from air *in situ*, or supplied from tanks. The inert gas can be recirculated and
25 any residual oxygen can be removed using a catalyst, such as a copper catalyst bed. Alternatively, combinations of purging, recirculating and oxygen removal can be done to keep the oxygen levels low.

[0084] The enclosure can also be purged with a reactive gas that can react with the biomass. This can be done before, during or after the irradiation process. The reactive
30 gas can be, but is not limited to, nitrous oxide, ammonia, oxygen, ozone, hydrocarbons, aromatic compounds, amides, peroxides, azides, halides, oxyhalides, phosphides, phosphines, arsines, sulfides, thiols, boranes and/or hydrides. The reactive gas can be activated in the enclosure, e.g., by irradiation (e.g., electron beam, UV irradiation, microwave irradiation, heating, IR radiation), so that it reacts with the biomass. The

biomass itself can be activated, for example by irradiation. Preferably the biomass is activated by the electron beam, to produce radicals, which then react with the activated or unactivated reactive gas, *e.g.*, by radical coupling or quenching.

[0085] Purging gases supplied to an enclosed conveyor can also be cooled, for example below about 25°C, below about 0°C, below about -40°C, below about -80°C, below about -120°C. For example, the gas can be boiled off from a compressed gas such as liquid nitrogen or sublimed from solid carbon dioxide. As an alternative example, the gas can be cooled by a chiller or part of or the entire conveyor can be cooled.

10 ELECTRON GUNS – BEAM STOPS

[0086] In some embodiments the systems and methods include a beam stop (*e.g.*, a shutter). For example, the beam stop can be used to quickly stop or reduce the irradiation of material without powering down the electron beam device. Alternatively the beam stop can be used while powering up the electron beam, *e.g.*, the beam stop can stop the electron beam until a beam current of a desired level is achieved. The beam stop can be placed between the primary foil window and a secondary foil window. For example the beam stop can be mounted so that it is movable, that is, so that it can be moved into and out of the beam path. Even partial coverage of the beam can be used, for example, to control the dose of irradiation. The beam stop can be mounted to the floor, to a conveyor for the biomass, to a wall, to the radiation device (*e.g.*, at the scan horn), or to any structural support. Preferably, the beam stop is fixed in relation to the scan horn so that the beam can be effectively controlled by the beam stop. The beam stop can incorporate a hinge, a rail, wheels, slots, or other means allowing for its operation in moving into and out of the beam. The beam stop can be made of any material that will stop at least 5% of the electrons, *e.g.*, at least 10%, 20%, 30%, 40%, 50%, 60%, 70%, at least 80%, 85%, 90%, 91%, 92%, 93%, 94%, 95%, 96%, 97%, 98%, 99% or even about 100% of the electrons.

[0087] The beam stop can be made of a metal including, but not limited to, stainless steel, lead, iron, molybdenum, silver, gold, titanium, aluminum, tin, or alloys of these, or laminates (layered materials) made with such metals (*e.g.*, metal-coated ceramic, metal-coated polymer, metal-coated composite, multilayered metal materials).

[0088] The beam stop can be cooled, for example, with a cooling fluid such as an aqueous solution or a gas. The beam stop can be partially or completely hollow, for example with cavities. Interior spaces of the beam stop can be used for cooling fluids

and gases. The beam stop can be of any shape, including flat, curved, round, oval, square, rectangular, beveled and wedged shapes.

[0089] The beam stop can have perforations so as to allow some electrons through, thus controlling (e.g., reducing) the levels of radiation across the whole area of the window, or in specific regions of the window. The beam stop can be a mesh formed, for example, from fibers or wires. Multiple beam stops can be used, together or independently, to control the irradiation. The beam stop can be remotely controlled, e.g., by radio signal or hard wired to a motor or other device for moving the beam into or out of position.

BIOMASS MATERIALS

[0090] Lignocellulosic materials include, but are not limited to, wood, particle board, forestry wastes (e.g., sawdust, aspen wood, wood chips), grasses, (e.g., switchgrass, miscanthus, cord grass, reed canary grass), grain residues, (e.g., rice hulls, oat hulls, wheat chaff, barley hulls), agricultural waste (e.g., silage, canola straw, wheat straw, barley straw, oat straw, rice straw, jute, hemp, flax, bamboo, sisal, abaca, corn cobs, corn stover, soybean stover, corn fiber, alfalfa, hay, coconut hair), sugar processing residues (e.g., bagasse, beet pulp, agave bagasse), , algae, seaweed, manure, sewage, and mixtures of any of these.

[0091] In some cases, the lignocellulosic material includes corncobs. Ground or hammer milled corncobs can be spread in a layer of relatively uniform thickness for irradiation, and after irradiation are easy to disperse in the medium for further processing. To facilitate harvest and collection, in some cases the entire corn plant is used, including the corn stalk, corn kernels, and in some cases even the root system of the plant.

[0092] Advantageously, no additional nutrients (other than a nitrogen source, e.g., urea or ammonia) are required during fermentation of corncobs or cellulosic or lignocellulosic materials containing significant amounts of corncobs.

[0093] Corncobs, before and after comminution, are also easier to convey and disperse, and have a lesser tendency to form explosive mixtures in air than other cellulosic or lignocellulosic materials such as hay and grasses.

[0094] Cellulosic materials include, for example, paper, paper products, paper waste, paper pulp, pigmented papers, loaded papers, coated papers, filled papers, magazines, printed matter (e.g., books, catalogs, manuals, labels, calendars, greeting cards,

brochures, prospectuses, newsprint), printer paper, polycoated paper, card stock, cardboard, paperboard, materials having a high α -cellulose content such as cotton, and mixtures of any of these. For example, paper products as described in U.S. App. No. 13/396,365 ("Magazine Feedstocks" by Medoff et al., filed February 14, 2012), the full
5 disclosure of which is incorporated herein by reference.

[0095] Cellulosic materials can also include lignocellulosic materials, which have been partially or fully de-lignified.

[0096] In some instances other biomass materials can be utilized, for example starchy materials. Starchy materials include starch itself, e.g., cornstarch, wheat starch,
10 potato starch or rice starch, a derivative of starch, or a material that includes starch, such as an edible food product or a crop. For example, the starchy material can be arracacha, buckwheat, banana, barley, cassava, kudzu, oca, sago, sorghum, regular household potatoes, sweet potato, taro, yams, or one or more beans, such as favas, lentils or peas. Blends of any two or more starchy materials are also starchy materials. Mixtures of
15 starchy, cellulosic and or lignocellulosic materials can also be used. For example, a biomass can be an entire plant, a part of a plant or different parts of a plant, e.g., a wheat plant, cotton plant, a corn plant, rice plant or a tree. The starchy materials can be treated by any of the methods described herein.

[0097] Microbial materials include, but are not limited to, any naturally occurring or
20 genetically modified microorganism or organism that contains or is capable of providing a source of carbohydrates (e.g., cellulose), for example, protists, e.g., animal protists (e.g., protozoa such as flagellates, amoeboids, ciliates, and sporozoa) and plant protists (e.g., algae such as alveolates, chlorarachniophytes, cryptomonads, euglenids, glaucophytes, haptophytes, red algae, stramenopiles, and viridiaeplantae). Other
25 examples include seaweed, plankton (e.g., macroplankton, mesoplankton, microplankton, nanoplankton, picoplankton, and femtoplankton), phytoplankton, bacteria (e.g., gram positive bacteria, gram negative bacteria, and extremophiles), yeast and/or mixtures of these. In some instances, microbial biomass can be obtained from natural sources, e.g., the ocean, lakes, bodies of water, e.g., salt water or fresh water, or
30 on land. Alternatively or in addition, microbial biomass can be obtained from culture systems, e.g., large-scale dry and wet culture and fermentation systems.

[0098] In other embodiments, the biomass materials, such as cellulosic, starchy and lignocellulosic feedstock materials, can be obtained from transgenic microorganisms and plants that have been modified with respect to a wild type variety. Such modifications

may be, for example, through the iterative steps of selection and breeding to obtain desired traits in a plant. Furthermore, the plants can have had genetic material removed, modified, silenced and/or added with respect to the wild type variety. For example, genetically modified plants can be produced by recombinant DNA methods, where

5 genetic modifications include introducing or modifying specific genes from parental varieties, or, for example, by using transgenic breeding wherein a specific gene or genes are introduced to a plant from a different species of plant and/or bacteria. Another way to create genetic variation is through mutation breeding wherein new alleles are artificially created from endogenous genes. The artificial genes can be created by a

10 variety of ways including treating the plant or seeds with, for example, chemical mutagens (e.g., using alkylating agents, epoxides, alkaloids, peroxides, formaldehyde), irradiation (e.g., X-rays, gamma rays, neutrons, beta particles, alpha particles, protons, deuterons, UV radiation) and temperature shocking or other external stressing and subsequent selection techniques. Other methods of providing modified genes are

15 through error prone PCR and DNA shuffling followed by insertion of the desired modified DNA into the desired plant or seed. Methods of introducing the desired genetic variation in the seed or plant include, for example, the use of a bacterial carrier, biolistics, calcium phosphate precipitation, electroporation, gene splicing, gene silencing, lipofection, microinjection and viral carriers. Additional genetically modified materials

20 have been described in U.S. Application Serial No 13/396,369 filed February 14, 2012 the full disclosure of which is incorporated herein by reference.

[0099] Any of the methods described herein can be practiced with mixtures of any biomass materials described herein.

25 OTHER MATERIALS

[00100] Other materials (e.g., natural or synthetic materials), for example polymers, can be treated and/or made utilizing the methods, equipment and systems described herein. For example polyethylene (e.g., linear low density ethylene and high density polyethylene), polystyrenes, sulfonated polystyrenes, poly(vinyl chlorides), poly (vinyl

30 chloride), polyesters (e.g., nylons, Dacron™, Kodel™), polyalkylene esters, poly vinyl esters, polyamides (e.g., Kevlar™), polyethylene terephthalate, cellulose acetate, acetal, polyacrylonitrile, polycarbonates(Lexan™), acrylics [e.g., poly (methyl methacrylate), poly(methyl methacrylate), polyacrylnitriles], Poly urethanes, polypropylene, poly butadiene, polyisobutylene, polyacrylonitrile, polychloroprene (e.g. neoprene), poly(cis-

1,4-isoprene) [e.g., natural rubber], poly(trans-1,4-isoprene) [e.g., gutta percha], phenol formaldehyde, melamine formaldehyde, epoxides, polyesters, poly amines, polycarboxylic acids, polylactic acids, polyvinyl alcohols, polyanhydrides, poly fluoro carbons (e.g., Teflon™), silicones (e.g., silicone rubber), polysilanes, poly ethers (e.g.,
5 polyethylene oxide, polypropylene oxide), waxes, oils and mixtures of these. Also included are plastics, rubbers, elastomers, fibers, waxes, gels, oils, adhesives, thermoplastics, thermosets, biodegradable polymers, resins made with these polymers, other polymers, other materials and combinations thereof. The polymers can be made by any useful method including cationic polymerization, anionic polymerization, radical
10 polymerization, metathesis polymerization, ring opening polymerization, graft polymerization, addition polymerization. In some cases the treatments disclosed herein can be used, for example, for radically initiated graft polymerization and cross linking. Composites of polymers, for example with glass, metals, biomass (e.g., fibers, particles), ceramics can also be treated and/or made.

15 **[00101]** Other materials that can be treated by using the methods, systems and equipment disclosed herein are ceramic materials, minerals, metals, inorganic compounds. For example, silicon and germanium crystals, silicon nitrides, metal oxides, semiconductors, insulators, cements and or conductors.

[00102] In addition, manufactured multipart or shaped materials (e.g., molded,
20 extruded, welded, riveted, layered or combined in any way) can be treated, for example cables, pipes, boards, enclosures, integrated semiconductor chips, circuit boards, wires, tires, windows, laminated materials, gears, belts, machines, combinations of these. For example, treating a material by the methods described herein can modify the surfaces, for example, making them susceptible to further functionalization, combinations (e.g.,
25 welding) and/or treatment can cross link the materials.

BIOMASS MATERIAL PREPARATION – MECHANICAL TREATMENTS

[00103] The biomass can be in a dry form, for example with less than about 35% moisture content (e.g., less than about 20 %, less than about 15 %, less than about 10 %
30 less than about 5 %, less than about 4%, less than about 3 %, less than about 2 % or even less than about 1 %). The biomass can also be delivered in a wet state, for example as a wet solid, a slurry or a suspension with at least about 10 wt.% solids (e.g., at least about 20 wt.%, at least about 30 wt. %, at least about 40 wt.%, at least about 50 wt.%, at least about 60 wt.%, at least about 70 wt.%).

[00104] The processes disclosed herein can utilize low bulk density materials, for example cellulosic or lignocellulosic feedstocks that have been physically pretreated to have a bulk density of less than about 0.75 g/cm³, e.g., less than about 0.7, 0.65, 0.60, 0.50, 0.35, 0.25, 0.20, 0.15, 0.10, 0.05 or less, e.g., less than about 0.025 g/cm³. Bulk density is determined using ASTM D1895B. Briefly, the method involves filling a measuring cylinder of known volume with a sample and obtaining a weight of the sample. The bulk density is calculated by dividing the weight of the sample in grams by the known volume of the cylinder in cubic centimeters. If desired, low bulk density materials can be densified, for example, by methods described in US. Pat. No. 7,971,809 to Medoff, the full disclosure of which is hereby incorporated by reference.

[00105] In some cases, the pre-treatment processing includes screening of the biomass material. Screening can be through a mesh or perforated plate with a desired opening size, for example, less than about 6.35 mm (1/4 inch, 0.25 inch), (e.g., less than about 3.18 mm (1/8 inch, 0.125 inch), less than about 1.59 mm (1/16 inch, 0.0625 inch), is less than about 0.79 mm (1/32 inch, 0.03125 inch), e.g., less than about 0.51 mm (1/50 inch, 0.02000 inch), less than about 0.40 mm (1/64 inch, 0.015625 inch), less than about 0.23 mm (0.009 inch), less than about 0.20 mm (1/128 inch, 0.0078125 inch), less than about 0.18 mm (0.007 inch), less than about 0.13 mm (0.005 inch), or even less than about 0.10 mm (1/256 inch, 0.00390625 inch)). In one configuration the desired biomass falls through the perforations or screen and thus biomass larger than the perforations or screen are not irradiated. These larger materials can be re-processed, for example, by comminuting, or they can simply be removed from processing. In another configuration material that is larger than the perforations is irradiated and the smaller material is removed by the screening process or recycled. In this kind of a configuration, the conveyor itself (for example a part of the conveyor) can be perforated or made with a mesh. For example, in one particular embodiment the biomass material may be wet and the perforations or mesh allow water to drain away from the biomass before irradiation.

[00106] Screening of material can also be by a manual method, for example by an operator or mechanoid (e.g., a robot equipped with a color, reflectivity or other sensor) that removes unwanted material. Screening can also be by magnetic screening wherein a magnet is disposed near the conveyed material and the magnetic material is removed magnetically.

[00107] Optional pre-treatment processing can include heating the material. For example a portion of the conveyor can be sent through a heated zone. The heated zone

can be created, for example, by IR radiation, microwaves, combustion (e.g., gas, coal, oil, biomass), resistive heating and/or inductive coils. The heat can be applied from at least one side or more than one side, can be continuous or periodic and can be for only a portion of the material or all the material. For example, a portion of the conveying

5 trough can be heated by use of a heating jacket. Heating can be, for example, for the purpose of drying the material. In the case of drying the material, this can also be facilitated, with or without heating, by the movement of a gas (e.g., air, oxygen, nitrogen, He, CO₂, Argon) over and/or through the biomass as it is being conveyed.

[00108] Optionally, pre-treatment processing can include cooling the material.

10 Cooling material is described in US Pat. No. 7,900,857 to Medoff, the disclosure of which is incorporated herein by reference. For example, cooling can be by supplying a cooling fluid, for example water (e.g., with glycerol), or nitrogen (e.g., liquid nitrogen) to the bottom of the conveying trough. Alternatively, a cooling gas, for example, chilled nitrogen can be blown over the biomass materials or under the conveying system.

15 **[0109]** Another optional pre-treatment processing method can include adding a material to the biomass. The additional material can be added by, for example, by showering, sprinkling and or pouring the material onto the biomass as it is conveyed. Materials that can be added include, for example, metals, ceramics and/or ions as described in U.S. Pat. App. Pub. 2010/0105119 A1 (filed October 26, 2009) and U.S. Pat. App. Pub.

20 2010/0159569 A1 (filed December 16, 2009), the entire disclosures of which are incorporated herein by reference. Optional materials that can be added include acids and bases. Other materials that can be added are oxidants (e.g., peroxides, chlorates), polymers, polymerizable monomers (e.g., containing unsaturated bonds), water, catalysts, enzymes and/or organisms. Materials can be added, for example, in pure form,

25 as a solution in a solvent (e.g., water or an organic solvent) and/or as a solution. In some cases the solvent is volatile and can be made to evaporate e.g., by heating and/or blowing gas as previously described. The added material may form a uniform coating on the biomass or be a homogeneous mixture of different components (e.g., biomass and additional material). The added material can modulate the subsequent irradiation step by

30 increasing the efficiency of the irradiation, damping the irradiation or changing the effect of the irradiation (e.g., from electron beams to X-rays or heat). The method may have no impact on the irradiation but may be useful for further downstream processing. The added material may help in conveying the material, for example, by lowering dust levels.

- 5 **[0110]** Biomass can be delivered to the conveyor (e.g., the vibratory conveyors used in the vaults herein described) by a belt conveyor, a pneumatic conveyor, a screw conveyor, a hopper, a pipe, manually or by a combination of these. The biomass can, for example, be dropped, poured and/or placed onto the conveyor by any of these methods. In some
- 10 **[0111]** The material can be leveled to form a uniform thickness between about 0.0312 and 5 inches (e.g., between about 0.0625 and 2.000 inches, between about 0.125 and 1 inches, between about 0.125 and 0.5 inches, between about 0.3 and 0.9 inches, between about 0.2 and 0.5 inches between about 0.25 and 1.0 inches, between about 0.25 and 0.5 inches.
- 15 **[0112]** Generally, it is preferred to convey the material as quickly as possible through the electron beam to maximize throughput. For example, the material can be conveyed at rates of at least 1 ft./min, e.g., at least 2 ft./min, at least 3 ft./min, at least 4 ft./min, at least 5 ft./min, at least 10 ft./min, at least 15 ft./min, 20, 25, 30, 35, 40, 45, 50 ft./min. The rate of conveying is related to the beam current, for example, for a ¼ inch thick
- 20 biomass and 100 mA, the conveyor can move at about 20 ft./min to provide a useful irradiation dosage, at 50 mA the conveyor can move at about 10 ft./min to provide approximately the same irradiation dosage.
- 25 **[0113]** After the biomass material has been conveyed through the radiation zone, optional post-treatment processing can be done. The optional post-treatment processing can, for example, be a process described with respect to the pre-irradiation processing. For example, the biomass can be screened, heated, cooled, and/or combined with additives. Uniquely to post-irradiation, quenching of the radicals can occur, for example, quenching of radicals by the addition of fluids or gases (e.g., oxygen, nitrous oxide, ammonia, liquids), using pressure, heat, and/or the addition of radical scavengers. For
- 30 example, the biomass can be conveyed out of the enclosed conveyor and exposed to a gas (e.g., oxygen) where it is quenched, forming carboxylated groups. In one embodiment the biomass is exposed during irradiation to the reactive gas or fluid. Quenching of biomass that has been irradiated is described in U.S. Pat. No. 8,083,906 to Medoff, the entire disclosure of which is incorporate herein by reference.

[0114] If desired, one or more mechanical treatments can be used in addition to irradiation to further reduce the recalcitrance of the carbohydrate-containing material. These processes can be applied before, during and or after irradiation.

[0115] In some cases, the mechanical treatment may include an initial preparation of the feedstock as received, e.g., size reduction of materials, such as by comminution, e.g., cutting, grinding, shearing, pulverizing or chopping. For example, in some cases, loose feedstock (e.g., recycled paper, starchy materials, or switchgrass) is prepared by shearing or shredding. Mechanical treatment may reduce the bulk density of the carbohydrate-containing material, increase the surface area of the carbohydrate-containing material and/or decrease one or more dimensions of the carbohydrate-containing material.

[0116] Alternatively, or in addition, the feedstock material can be treated with another treatment, for example chemical treatments, such as with an acid (HCl, H₂SO₄, H₃PO₄), a base (e.g., KOH and NaOH), a chemical oxidant (e.g., peroxides, chlorates, ozone), irradiation, steam explosion, pyrolysis, sonication, oxidation, chemical treatment. The treatments can be in any order and in any sequence and combinations. For example, the feedstock material can first be physically treated by one or more treatment methods, e.g., chemical treatment including and in combination with acid hydrolysis (e.g., utilizing HCl, H₂SO₄, H₃PO₄), radiation, sonication, oxidation, pyrolysis or steam explosion, and then mechanically treated. This sequence can be advantageous since materials treated by one or more of the other treatments, e.g., irradiation or pyrolysis, tend to be more brittle and, therefore, it may be easier to further change the structure of the material by mechanical treatment. As another example, a feedstock material can be conveyed through ionizing radiation using a conveyor as described herein and then mechanically treated. Chemical treatment can remove some or all of the lignin (for example, chemical pulping) and can partially or completely hydrolyze the material. The methods also can be used with pre-hydrolyzed material. The methods also can be used with material that has not been pre hydrolyzed. The methods can be used with mixtures of hydrolyzed and non-hydrolyzed materials, for example, with about 50% or more non-hydrolyzed material, with about 60% or more non- hydrolyzed material, with about 70% or more non-hydrolyzed material, with about 80% or more non-hydrolyzed material or even with 90% or more non-hydrolyzed.

[0117] In addition to size reduction, which can be performed initially and/or later in processing, mechanical treatment can also be advantageous for “opening up,” “stressing,” breaking or shattering the carbohydrate-containing materials, making the

cellulose of the materials more susceptible to chain scission and/or disruption of crystalline structure during the physical treatment.

[0118] Methods of mechanically treating the carbohydrate-containing material include, for example, milling or grinding. Milling may be performed using, for example, a hammer mill, ball mill, colloid mill, conical or cone mill, disk mill, edge mill, Wiley mill, gristmill or other mill. Grinding may be performed using, for example, a cutting/impact type grinder. Some exemplary grinders include stone grinders, pin grinders, coffee grinders, and burr grinders. Grinding or milling may be provided, for example, by a reciprocating pin or other element, as is the case in a pin mill. Other mechanical treatment methods include mechanical ripping or tearing, other methods that apply pressure to the fibers, and air attrition milling. Suitable mechanical treatments further include any other technique that continues the disruption of the internal structure of the material that was initiated by the previous processing steps.

[0119] Mechanical feed preparation systems can be configured to produce streams with specific characteristics such as, for example, specific maximum sizes, specific length-to-width, or specific surface areas ratios. Physical preparation can increase the rate of reactions, improve the movement of material on a conveyor, improve the irradiation profile of the material, improve the radiation uniformity of the material, or reduce the processing time required by opening up the materials and making them more accessible to processes and/or reagents, such as reagents in a solution.

[0120] The bulk density of feedstocks can be controlled (e.g., increased). In some situations, it can be desirable to prepare a low bulk density material, e.g., by densifying the material (e.g., densification can make it easier and less costly to transport to another site) and then reverting the material to a lower bulk density state (e.g., after transport). The material can be densified, for example from less than about 0.2 g/cc to more than about 0.9 g/cc (e.g., less than about 0.3 to more than about 0.5 g/cc, less than about 0.3 to more than about 0.9 g/cc, less than about 0.5 to more than about 0.9 g/cc, less than about 0.3 to more than about 0.8 g/cc, less than about 0.2 to more than about 0.5 g/cc). For example, the material can be densified by the methods and equipment disclosed in U.S. Pat. No. 7,932,065 to Medoff and International Publication No. WO 2008/073186 (which was filed October 26, 2007, was published in English, and which designated the United States), the full disclosures of which are incorporated herein by reference. Densified materials can be processed by any of the methods described herein, or any

material processed by any of the methods described herein can be subsequently densified.

[0121] In some embodiments, the material to be processed is in the form of a fibrous material that includes fibers provided by shearing a fiber source. For example, the
5 shearing can be performed with a rotary knife cutter.

[0122] For example, a fiber source, e.g., that is recalcitrant or that has had its recalcitrance level reduced, can be sheared, e.g., in a rotary knife cutter, to provide a first fibrous material. The first fibrous material is passed through a first screen, e.g., having an average opening size of 1.59 mm or less (1/16 inch, 0.0625 inch), provide a second
10 fibrous material. If desired, the fiber source can be cut prior to the shearing, e.g., with a shredder. For example, when a paper is used as the fiber source, the paper can be first cut into strips that are, e.g., 1/4- to 1/2-inch wide, using a shredder, e.g., a counter-rotating screw shredder, such as those manufactured by Munson (Utica, N.Y.). As an alternative to shredding, the paper can be reduced in size by cutting to a desired size
15 using a guillotine cutter. For example, the guillotine cutter can be used to cut the paper into sheets that are, e.g., 10 inches wide by 12 inches long.

[0123] In some embodiments, the shearing of the fiber source and the passing of the resulting first fibrous material through a first screen are performed concurrently. The shearing and the passing can also be performed in a batch-type process.

20 [0124] For example, a rotary knife cutter can be used to concurrently shear the fiber source and screen the first fibrous material. A rotary knife cutter includes a hopper that can be loaded with a shredded fiber source prepared by shredding a fiber source.

[0125] In some implementations, the feedstock is physically treated prior to saccharification and/or fermentation. Physical treatment processes can include one or
25 more of any of those described herein, such as mechanical treatment, chemical treatment, irradiation, sonication, oxidation, pyrolysis or steam explosion. Treatment methods can be used in combinations of two, three, four, or even all of these technologies (in any order). When more than one treatment method is used, the methods can be applied at the same time or at different times. Other processes that change a molecular structure of a
30 biomass feedstock may also be used, alone or in combination with the processes disclosed herein.

[0126] Mechanical treatments that may be used, and the characteristics of the mechanically treated carbohydrate-containing materials, are described in further detail in

U.S. Pat. App. Pub. 2012/0100577 A1, filed October 18, 2011, the full disclosure of which is hereby incorporated herein by reference.

SONICATION, PYROLYSIS, OXIDATION, STEAM EXPLOSION

5 [0127] If desired, one or more sonication, pyrolysis, oxidative, or steam explosion processes can be used instead of or in addition to irradiation to reduce or further reduce the recalcitrance of the carbohydrate-containing material. For example, these processes can be applied before, during and or after irradiation. These processes are described in detail in U.S. Pat. No. 7,932,065 to Medoff, the full disclosure of which is incorporated
10 herein by reference.

USE OF TREATED BIOMASS MATERIAL

[0128] Using the methods described herein, a starting biomass material (e.g., plant biomass, animal biomass, paper, and municipal waste biomass) can be used as feedstock
15 to produce useful intermediates and products such as organic acids, salts of organic acids, anhydrides, esters of organic acids and fuels, e.g., fuels for internal combustion engines or feedstocks for fuel cells. Systems and processes are described herein that can use as feedstock cellulosic and/or lignocellulosic materials that are readily available, but often can be difficult to process, e.g., municipal waste streams and waste paper streams,
20 such as streams that include newspaper, kraft paper, corrugated paper or mixtures of these.

[0129] In order to convert the feedstock to a form that can be readily processed, the glucan- or xylan-containing cellulose in the feedstock can be hydrolyzed to low molecular weight carbohydrates, such as sugars, by a saccharifying agent, e.g., an
25 enzyme or acid, a process referred to as saccharification. The low molecular weight carbohydrates can then be used, for example, in an existing manufacturing plant, such as a single cell protein plant, an enzyme manufacturing plant, or a fuel plant, e.g., an ethanol manufacturing facility.

[0130] The feedstock can be hydrolyzed using an enzyme, e.g., by combining the
30 materials and the enzyme in a solvent, e.g., in an aqueous solution.

[0131] Alternatively, the enzymes can be supplied by organisms that break down biomass, such as the cellulose and/or the lignin portions of the biomass, contain or manufacture various cellulolytic enzymes (cellulases), ligninases or various small molecule biomass-degrading metabolites. These enzymes may be a complex of enzymes

that act synergistically to degrade crystalline cellulose or the lignin portions of biomass. Examples of cellulolytic enzymes include: endoglucanases, cellobiohydrolases, and cellobiases (beta-glucosidases).

[0132] During saccharification a cellulosic substrate can be initially hydrolyzed by
5 endoglucanases at random locations producing oligomeric intermediates. These intermediates are then substrates for exo-splitting glucanases such as cellobiohydrolase to produce cellobiose from the ends of the cellulose polymer. Cellobiose is a water-soluble 1,4-linked dimer of glucose. Finally, cellobiase cleaves cellobiose to yield glucose. The efficiency (e.g., time to hydrolyze and/or completeness of hydrolysis) of
10 this process depends on the recalcitrance of the cellulosic material.

INTERMEDIATES AND PRODUCTS

[0133] Using the processes described herein, the biomass material can be converted to one or more products, such as energy, fuels, foods and materials. Specific examples of
15 products include, but are not limited to, hydrogen, sugars (e.g., glucose, xylose, arabinose, mannose, galactose, fructose, disaccharides, oligosaccharides and polysaccharides), alcohols (e.g., monohydric alcohols or dihydric alcohols, such as ethanol, n-propanol, isobutanol, sec-butanol, tert-butanol or n-butanol), hydrated or hydrous alcohols (e.g., containing greater than 10%, 20%, 30% or even greater than 40%
20 water), biodiesel, organic acids, hydrocarbons (e.g., methane, ethane, propane, isobutene, pentane, n-hexane, biodiesel, bio-gasoline and mixtures thereof), co-products (e.g., proteins, such as cellulolytic proteins (enzymes) or single cell proteins), and mixtures of any of these in any combination or relative concentration, and optionally in combination with any additives (e.g., fuel additives). Other examples include carboxylic acids, salts
25 of a carboxylic acid, a mixture of carboxylic acids and salts of carboxylic acids and esters of carboxylic acids (e.g., methyl, ethyl and n-propyl esters), ketones (e.g., acetone), aldehydes (e.g., acetaldehyde), alpha and beta unsaturated acids (e.g., acrylic acid) and olefins (e.g., ethylene). Other alcohols and alcohol derivatives include propanol, propylene glycol, 1,4-butanediol, 1,3-propanediol, sugar alcohols (e.g.,
30 erythritol, glycol, glycerol, sorbitol, threitol, arabitol, ribitol, mannitol, dulcitol, fucitol, iditol, isomalt, maltitol, lactitol, xylitol and other polyols), and methyl or ethyl esters of any of these alcohols. Other products include methyl acrylate, methyl methacrylate, lactic acid, citric acid, formic acid, acetic acid, propionic acid, butyric acid, succinic acid, valeric acid, caproic acid, 3-hydroxypropionic acid, palmitic acid, stearic acid, oxalic

acid, malonic acid, glutaric acid, oleic acid, linoleic acid, glycolic acid, gamma-hydroxybutyric acid, and mixtures thereof, salts of any of these acids, mixtures of any of the acids and their respective salts.

5 [0134] Any combination of the above products with each other, and/or of the above products with other products, which other products may be made by the processes described herein or otherwise, may be packaged together and sold as products. The products may be combined, e.g., mixed, blended or co-dissolved, or may simply be packaged or sold together.

10 [0135] Any of the products or combinations of products described herein may be sanitized or sterilized prior to selling the products, e.g., after purification or isolation or even after packaging, to neutralize one or more potentially undesirable contaminants that could be present in the product(s). Such sanitation can be done with electron bombardment, for example, be at a dosage of less than about 20 Mrad, e.g., from about 0.1 to 15 Mrad, from about 0.5 to 7 Mrad, or from about 1 to 3 Mrad.

15 [0136] The processes described herein can produce various by-product streams useful for generating steam and electricity to be used in other parts of the plant (co-generation) or sold on the open market. For example, steam generated from burning by-product streams can be used in a distillation process. As another example, electricity generated from burning by-product streams can be used to power electron beam generators used in pretreatment.

20 [0137] The by-products used to generate steam and electricity are derived from a number of sources throughout the process. For example, anaerobic digestion of wastewater can produce a biogas high in methane and a small amount of waste biomass (sludge). As another example, post-saccharification and/or post-distillate solids (e.g., unconverted lignin, cellulose, and hemicellulose remaining from the pretreatment and primary processes) can be used, e.g., burned, as a fuel.

25 Other intermediates and products, including food and pharmaceutical products, are described in U.S. Pat. App. Pub. 2010/0124583 A1, published May 20, 2010, to Medoff, the full disclosure of which is hereby incorporated by reference herein,

30

LIGNIN DERIVED PRODUCTS

[0138] The spent biomass (e.g., spent lignocellulosic material) from lignocellulosic processing by the methods described are expected to have a high lignin content and in addition to being useful for producing energy through combustion in a Co-Generation

plant, may have uses as other valuable products. For example, the lignin can be used as captured as a plastic, or it can be synthetically upgraded to other plastics. In some instances, it can also be converted to lignosulfonates, which can be utilized as binders, dispersants, emulsifiers or as sequestrants.

5 **[0139]** When used as a binder, the lignin or a lignosulfonate can, e.g., be utilized in coal briquettes, in ceramics, for binding carbon black, for binding fertilizers and herbicides, as a dust suppressant, in the making of plywood and particle board, for binding animal feeds, as a binder for fiberglass, as a binder in linoleum paste and as a soil stabilizer.

10 **[0140]** As a dispersant, the lignin or lignosulfonates can be used, e.g., concrete mixes, clay and ceramics, dyes and pigments, leather tanning and in gypsum board.

[0141] As an emulsifier, the lignin or lignosulfonates can be used, e.g., in asphalt, pigments and dyes, pesticides and wax emulsions.

[0142] As a sequestrant, the lignin or lignosulfonates can be used, e.g., in micro-nutrient systems, cleaning compounds and water treatment systems, e.g., for boiler and cooling
15 systems.

[0143] For energy production lignin generally has a higher energy content than holocellulose (cellulose and hemicellulose) since it contains more carbon than holocellulose. For example, dry lignin can have an energy content of between about 11,000 and 12,500 BTU per pound, compared to 7,000 and 8,000 BTU per pound of
20 holocellulose. As such, lignin can be densified and converted into briquettes and pellets for burning. For example, the lignin can be converted into pellets by any method described herein. For a slower burning pellet or briquette, the lignin can be crosslinked, such as applying a radiation dose of between about 0.5 Mrad and 5 Mrad. Crosslinking can make a slower burning form factor. The form factor, such as a pellet or briquette,
25 can be converted to a “synthetic coal” or charcoal by pyrolyzing in the absence of air, e.g., at between 400 and 950 °C. Prior to pyrolyzing, it can be desirable to crosslink the lignin to maintain structural integrity.

[0144] Co-generation using spent biomass is described in U.S. Provisional Application No. 61/774,773 filed March 8, 2013 the entire disclosure therein is herein incorporated
30 by reference.

BIOMASS PROCESSING AFTER IRRADIATION

[0145] After irradiation the biomass may be transferred to a vessel for saccharification. Alternately, the biomass can be heated after the biomass is irradiated prior to the

saccharification step. The biomass can be, for example, by IR radiation, microwaves, combustion (e.g., gas, coal, oil, biomass), resistive heating and/or inductive coils. This heating can be in a liquid, for example, in water or other water-based solvents. The heat can be applied from at least one side or more than one side, can be continuous or
5 periodic and can be for only a portion of the material or all the material. The biomass may be heated to temperatures above 90°C in an aqueous liquid that may have an acid or a base present. For example, the aqueous biomass slurry may be heated to 90 to 150°C, alternatively, 105 to 145°C, optionally 110 to 140°C or further optionally from 115 to 135°C. The time that the aqueous biomass mixture is held at the peak temperature is 1 to
10 12 hours, alternately, 1 to 6 hours, optionally 1 to 4 hours at the peak temperature. In some instances, the aqueous biomass mixture is acidic, and the pH is between 1 and 5, optionally 1 to 4, or alternately, 2 to 3. In other instances, the aqueous biomass mixture is alkaline and the pH is between 6 and 13, alternately, 8 to 12, or optionally, 8 to 11.

15 **SACCHARIFICATION**

[0146] The treated biomass materials can be saccharified, generally by combining the material and a cellulase enzyme in a fluid medium, e.g., an aqueous solution. In some cases, the material is boiled, steeped, or cooked in hot water prior to saccharification, as described in U.S. Pat. App. Pub. 2012/0100577 A1 by Medoff and Masterman, published
20 on April 26, 2012, the entire contents of which are incorporated herein.

[0147] The saccharification process can be partially or completely performed in a tank (e.g., a tank having a volume of at least 4000, 40,000, or 500,000 L) in a manufacturing plant, and/or can be partially or completely performed in transit, e.g., in a rail car, tanker truck, or in a supertanker or the hold of a ship. The time required for complete
25 saccharification will depend on the process conditions and the carbohydrate-containing material and enzyme used. If saccharification is performed in a manufacturing plant under controlled conditions, the cellulose may be substantially entirely converted to sugar, e.g., glucose in about 12-96 hours. If saccharification is performed partially or completely in transit, saccharification may take longer.

30 [0148] It is generally preferred that the tank contents be mixed during saccharification, e.g., using jet mixing as described in International App. No. PCT/US2010/035331, filed May 18, 2010, which was published in English as WO 2010/135380 and designated the United States, the full disclosure of which is incorporated by reference herein.

[0149] The addition of surfactants can enhance the rate of saccharification. Examples of surfactants include non-ionic surfactants, such as a Tween® 20 or Tween® 80 polyethylene glycol surfactants, ionic surfactants, or amphoteric surfactants.

5 [0150] It is generally preferred that the concentration of the sugar solution resulting from saccharification be relatively high, e.g., greater than 40%, or greater than 50, 60, 70, 80, 90 or even greater than 95% by weight. Water may be removed, e.g., by evaporation, to increase the concentration of the sugar solution. This reduces the volume to be shipped, and also inhibits microbial growth in the solution.

10 [0151] Alternatively, sugar solutions of lower concentrations may be used, in which case it may be desirable to add an antimicrobial additive, e.g., a broad spectrum antibiotic, in a low concentration, e.g., 50 to 150 ppm. Other suitable antibiotics include amphotericin B, ampicillin, chloramphenicol, ciprofloxacin, gentamicin, hygromycin B, kanamycin, neomycin, penicillin, puromycin, streptomycin. Antibiotics will inhibit growth of microorganisms during transport and storage, and can be used at appropriate
15 concentrations, e.g., between 15 and 1000 ppm by weight, e.g., between 25 and 500 ppm, or between 50 and 150 ppm. If desired, an antibiotic can be included even if the sugar concentration is relatively high. Alternatively, other additives with anti-microbial or preservative properties may be used. Preferably the antimicrobial additive(s) are food-grade.

20 [0152] A relatively high concentration solution can be obtained by limiting the amount of water added to the carbohydrate-containing material with the enzyme. The concentration can be controlled, e.g., by controlling how much saccharification takes place. For example, concentration can be increased by adding more carbohydrate-containing material to the solution. In order to keep the sugar that is being produced in
25 solution, a surfactant can be added, e.g., one of those discussed above. Solubility can also be increased by increasing the temperature of the solution. For example, the solution can be maintained at a temperature of 40-50°C, 60-80°C, or even higher.

SACCHARIFYING AGENTS

30 [0153] Suitable cellulolytic enzymes include cellulases from species in the genera Bacillus, Coprinus, Myceliophthora, Cephalosporium, Scytalidium, Penicillium, Aspergillus, Pseudomonas, Humicola, Fusarium, Thielavia, Acremonium, Chrysosporium and Trichoderma, especially those produced by a strain selected from the species Aspergillus (see, e.g., EP Pub. No. 0 458 162), Humicola insolens (reclassified as

Scytalidium thermophilum, see, e.g., U.S. Pat. No. 4,435,307), Coprinus cinereus, Fusarium oxysporum, Myceliophthora thermophila, Meripilus giganteus, Thielavia terrestris, Acremonium sp. (including, but not limited to, A. persicinum, A. acremonium, A. brachyphenium, A. dichromosporum, A. obclavatum, A. pinkertoniae, A. roseogriseum, A. incoloratum, and A. furatum). Preferred strains include Humicola insolens DSM 1800, Fusarium oxysporum DSM 2672, Myceliophthora thermophila CBS 117.65, Cephalosporium sp. RYM-202, Acremonium sp. CBS 478.94, Acremonium sp. CBS 265.95, Acremonium persicinum CBS 169.65, Acremonium acremonium AHU 9519, Cephalosporium sp. CBS 535.71, Acremonium brachyphenium CBS 866.73, Acremonium dichromosporum CBS 683.73, Acremonium obclavatum CBS 311.74, Acremonium pinkertoniae CBS 157.70, Acremonium roseogriseum CBS 134.56, Acremonium incoloratum CBS 146.62, and Acremonium furatum CBS 299.70H. Cellulolytic enzymes may also be obtained from Chrysosporium, preferably a strain of Chrysosporium lucknowense. Additional strains that can be used include, but are not limited to, Trichoderma (particularly T. viride, T. reesei, and T. koningii), alkalophilic Bacillus (see, for example, U.S. Pat. No. 3,844,890 and EP Pub. No. 0 458 162), and Streptomyces (see, e.g., EP Pub. No. 0 458 162).

[0154] In addition to or in combination to enzymes, acids, bases and other chemicals (e.g., oxidants) can be utilized to saccharify lignocellulosic and cellulosic materials. These can be used in any combination or sequence (e.g., before, after and/or during addition of an enzyme). For example strong mineral acids can be utilized (e.g. HCl, H₂SO₄, H₃PO₄) and strong bases (e.g., NaOH, KOH).

SUGARS

[0155] In the processes described herein, for example after saccharification, sugars (e.g., glucose and xylose) can be isolated. For example, sugars can be isolated by precipitation, crystallization, chromatography (e.g., simulated moving bed chromatography, high pressure chromatography), centrifugation, extraction, any other isolation method known in the art, and combinations thereof.

HYDROGENATION AND OTHER CHEMICAL TRANSFORMATIONS

[0156] The processes described herein can include hydrogenation. For example, glucose and xylose can be hydrogenated to sorbitol and xylitol respectively. Hydrogenation can be accomplished by use of a catalyst (e.g., Pt/gamma-Al₂O₃, Ru/C, Raney Nickel, or

other catalysts know in the art) in combination with H₂ under high pressure (*e.g.*, 10 to 12000 psi). Other types of chemical transformation of the products from the processes described herein can be used, for example, production of organic sugar derived products such (*e.g.*, furfural and furfural-derived products). Chemical transformations of sugar
5 derived products are described in US. App. No. 13/934704, filed July 3, 2013, the disclosure of which is incorporated herein by reference in its entirety.

FERMENTATION

[0157] Yeast and Zymomonas bacteria, for example, can be used for fermentation or
10 conversion of sugar(s) to alcohol(s). Other microorganisms are discussed below. The optimum pH for fermentations is about pH 4 to 7. For example, the optimum pH for yeast is from about pH 4 to 5, while the optimum pH for Zymomonas is from about pH 5 to 6. Typical fermentation times are about 24 to 168 hours (*e.g.*, 24 to 96 hrs.) with temperatures in the range of 20°C to 40°C (*e.g.*, 26°C to 40°C), however thermophilic
15 microorganisms prefer higher temperatures.

[0158] In some embodiments, *e.g.*, when anaerobic organisms are used, at least a portion of the fermentation is conducted in the absence of oxygen, *e.g.*, under a blanket of an inert gas such as N₂, Ar, He, CO₂ or mixtures thereof. Additionally, the mixture may have a constant purge of an inert gas flowing through the tank during part of or all of the
20 fermentation. In some cases, anaerobic condition, can be achieved or maintained by carbon dioxide production during the fermentation and no additional inert gas is needed.

[0159] In some embodiments, all or a portion of the fermentation process can be interrupted before the low molecular weight sugar is completely converted to a product (*e.g.*, ethanol). The intermediate fermentation products include sugar and carbohydrates
25 in high concentrations. The sugars and carbohydrates can be isolated via any means known in the art. These intermediate fermentation products can be used in preparation of food for human or animal consumption. Additionally or alternatively, the intermediate fermentation products can be ground to a fine particle size in a stainless-steel laboratory mill to produce a flour-like substance. Jet mixing may be used during fermentation, and
30 in some cases saccharification and fermentation are performed in the same tank.

[0160] Nutrients for the microorganisms may be added during saccharification and/or fermentation, for example the food-based nutrient packages described in U.S. Pat. App. Pub. 2012/0052536, filed July 15, 2011, the complete disclosure of which is incorporated herein by reference.

[0161] "Fermentation" includes the methods and products that are disclosed in International Publication No. WO 2013/096700, published June 27, 2013, and International Publication No. WO 2013/096693, published June 27, 2013, the contents of both of which are incorporated by reference herein in their entirety.

- 5 [0162] Mobile fermenters can be utilized, as described in International App. No. PCT/US2007/074028 (which was filed July 20, 2007, was published in English as WO 2008/011598 and designated the United States) and has a US issued Patent No. 8,318,453, the contents of which are incorporated herein in its entirety. Similarly, the saccharification equipment can be mobile. Further, saccharification and/or fermentation
10 may be performed in part or entirely during transit.

FERMENTATION AGENTS

- [0163] The microorganism(s) used in fermentation can be naturally-occurring microorganisms and/or engineered microorganisms. For example, the microorganism
15 can be a bacterium (including, but not limited to, e.g., a cellulolytic bacterium), a fungus, (including, but not limited to, e.g., a yeast), a plant, a protist, e.g., a protozoa or a fungus-like protest (including, but not limited to, e.g., a slime mold), or an alga. When the organisms are compatible, mixtures of organisms can be utilized.

- [0164] Suitable fermenting microorganisms have the ability to convert carbohydrates,
20 such as glucose, fructose, xylose, arabinose, mannose, galactose, oligosaccharides or polysaccharides into fermentation products. Fermenting microorganisms include strains of the genus *Sacchromyces* spp. (including, but not limited to, *S. cerevisiae* (baker's yeast), *S. distaticus*, *S. uvarum*), the genus *Kluyveromyces*, (including, but not limited to, *K. marxianus*, *K. fragilis*), the genus *Candida* (including, but not limited to, *C. pseudotropicalis*, and *C. brassicae*), *Pichia stipitis* (a relative of *Candida shehatae*), the
25 genus *Clavispora* (including, but not limited to, *C. lusitaniae* and *C. opuntiae*), the genus *Pachysolen* (including, but not limited to, *P. tannophilus*), the genus *Bretannomyces* (including, but not limited to, e.g., *B. clausenii* (Philippidis, G. P., 1996, Cellulose bioconversion technology, in Handbook on Bioethanol: Production and Utilization, Wyman, C.E., ed., Taylor & Francis, Washington, DC, 179-212)). Other suitable
30 microorganisms include, for example, *Zymomonas mobilis*, *Clostridium* spp. (including, but not limited to, *C. thermocellum* (Philippidis, 1996, supra), *C. saccharobutylaceticum*, *C. tyrobutyricum*, *C. saccharobutylicum*, *C. Puniceum*, *C. beijerinckii*, and *C. acetobutylicum*), *Moniliella* spp. (including but not limited to *M.*

- pollinis, *M. tomentosa*, *M. madida*, *M. nigrescens*, *M. oedocephali*, *M. megachiliensis*), *Yarrowia lipolytica*, *Aureobasidium* sp., *Trichosporonoides* sp., *Trigonopsis variabilis*, *Trichosporon* sp., *Moniliellaacetobutans* sp., *Typhula variabilis*, *Candida magnoliae*, *Ustilaginomycetes* sp., *Pseudozyma tsukubaensis*, yeast species of genera
- 5 *Zygosaccharomyces*, *Debaryomyces*, *Hansenula* and *Pichia*, and fungi of the dematioid genus *Torula* (e.g., *T. corallina*).
- [0165] Many such microbial strains are publicly available, either commercially or through depositories such as the ATCC (American Type Culture Collection, Manassas, Virginia, USA), the NRRL (Agricultural Research Service Culture Collection, Peoria,
- 10 Illinois, USA), or the DSMZ (Deutsche Sammlung von Mikroorganismen und Zellkulturen GmbH, Braunschweig, Germany), to name a few.
- [0166] Commercially available yeasts include, for example, RED STAR®/Lesaffre Ethanol Red (available from Red Star/Lesaffre, USA), FALI® (available from Fleischmann's Yeast, a division of Burns Philip Food Inc., USA), SUPERSTART®
- 15 (Lallemand Biofuels and Distilled Spirits, Canada), EAGLE C6 FUEL™ or C6 FUEL™ (available from Lallemand Biofuels and Distilled Spirits, Canada), GERT STRAND® (available from Gert Strand AB, Sweden) and FERMOL® (available from DSM Specialties).

20 **DISTILLATION**

- [0167] After fermentation, the resulting fluids can be distilled using, for example, a “beer column” to separate ethanol and other alcohols from the majority of water and residual solids. The vapor exiting the beer column can be, e.g., 35% by weight ethanol and can be fed to a rectification column. A mixture of nearly azeotropic (92.5%) ethanol
- 25 and water from the rectification column can be purified to pure (99.5%) ethanol using vapor-phase molecular sieves. The beer column bottoms can be sent to the first effect of a three-effect evaporator. The rectification column reflux condenser can provide heat for this first effect. After the first effect, solids can be separated using a centrifuge and dried in a rotary dryer. A portion (25%) of the centrifuge effluent can be recycled to
- 30 fermentation and the rest sent to the second and third evaporator effects. Most of the evaporator condensate can be returned to the process as fairly clean condensate with a small portion split off to waste water treatment to prevent build-up of low-boiling compounds.

HYDROCARBON-CONTAINING MATERIALS

[0168] “Hydrocarbon-containing materials,” as used herein, is meant to include oil sands, oil shale, tar sands, coal dust, coal slurry, bitumen, various types of coal, and other naturally-occurring and synthetic materials that include both hydrocarbon components and solid matter. The solid matter can include rock, sand, clay, stone, silt, drilling slurry, or other solid organic and/or inorganic matter. The term can also include waste products such as drilling waste and by-products, refining waste and by-products, or other waste products containing hydrocarbon components, such as asphalt shingling and covering, asphalt pavement, etc.

CONVEYING SYSTEMS

[0169] Various conveying systems can be used to convey the biomass material, for example, to and from a vault. Exemplary conveyors and conveying systems belt conveyors, pneumatic conveyors, screw conveyors, carts, trains, trains or carts on rails, elevators, front loaders, backhoes, cranes, various scrapers and shovels, trucks, and throwing devices can be used.

OTHER EMBODIMENTS

[0170] Any material, processes or processed materials can be used to make products and/or intermediates such as composites, fillers, binders, plastic additives, adsorbents and controlled release agents. The methods can include densification, for example, by applying pressure and heat to the materials. For example composites can be made by combining fibrous materials with a resin or polymer. For example radiation cross-linkable resin, e.g., a thermoplastic resin can be combined with a fibrous material to provide a fibrous material/cross-linkable resin combination. Such materials can be, for example, useful as building materials, protective sheets, containers and other structural materials (e.g., molded and/or extruded products). Absorbents can be, for example, in the form of pellets, chips, fibers and/or sheets. Adsorbents can be used, for example, as pet bedding, packaging material or in pollution control systems. Controlled release matrices can also be the form of, for example, pellets, chips, fibers and or sheets. The controlled release matrices can, for example, be used to release drugs, biocides, fragrances. For example, composites, absorbents and control release agents and their uses are described in U.S. Serial No. PCT/US2006/010648, filed March 23, 2006, and US Patent No.

8,074,910 filed November 22, 2011, the entire disclosures of which are herein incorporated by reference.

[0171] In some instances the biomass material is treated at a first level to reduce recalcitrance, e.g., utilizing accelerated electrons, to selectively release one or more
5 sugars (e.g., xylose). The biomass can then be treated to a second level to release one or more other sugars (e.g., glucose). Optionally, the biomass can be dried between treatments. The treatments can include applying chemical and biochemical treatments to release the sugars. For example, a biomass material can be treated to a level of less than
10 about 20 Mrad (e.g., less than about 15 Mrad, less than about 10 Mrad, less than about 5 Mrad, less than about 2 Mrad) and then treated with a solution of sulfuric acid, containing less than 10% sulfuric acid (e.g., less than about 9%, less than about 8%, less than about 7%, less than about 6%, less than about 5%, less than about 4%, less than about 3%, less than about 2%, less than about 1%, less than about 0.75%, less than about
15 0.50 %, less than about 0.25%) to release xylose. Xylose, for example that is released into solution, can be separated from solids and optionally the solids washed with a solvent/solution (e.g., with water and/or acidified water). The solids can be dried, for example in air and/or under vacuum optionally with heating (e.g., below about 150° C, below about 120° C) to a water content below about 25 wt.% (below about 20 wt.%, below about 15 wt.%, below about 10 wt.%, below about 5 wt.%). The solids can then be
20 treated with a level of less than about 30 Mrad (e.g., less than about 25 Mrad, less than about 20 Mrad, less than about 15 Mrad, less than about 10 Mrad, less than about 5 Mrad, less than about 1 Mrad) and then treated with an enzyme (e.g., a cellulase) to release glucose. The glucose (e.g., glucose in solution) can be separated from the remaining solids. The solids can then be further processed, for example utilized to make
25 energy or other products (e.g., lignin derived products).

FLAVORS, FRAGRANCES AND COLORANTS

[0172] Any of the products and/or intermediates described herein, for example, produced by the processes, systems and/or equipment described herein, can be combined with
30 flavors, fragrances, colorants and/or mixtures of these. For example, any one or more of (optionally along with flavors, fragrances and/or colorants) sugars, organic acids, fuels, polyols, such as sugar alcohols, biomass, fibers and composites can be combined with (e.g., formulated, mixed or reacted) or used to make other products. For example, one or more such product can be used to make soaps, detergents, candies, drinks (e.g., cola,

wine, beer, liquors such as gin or vodka, sports drinks, coffees, teas), pharmaceuticals, adhesives, sheets (e.g., woven, none woven, filters, tissues) and/or composites (e.g., boards). For example, one or more such product can be combined with herbs, flowers, petals, spices, vitamins, potpourri, or candles. For example, the formulated, mixed or

5 reacted combinations can have flavors/fragrances of grapefruit, orange, apple, raspberry, banana, lettuce, celery, cinnamon, chocolate, vanilla, peppermint, mint, onion, garlic, pepper, saffron, ginger, milk, wine, beer, tea, lean beef, fish, clams, olive oil, coconut fat, pork fat, butter fat, beef bouillon, legume, potatoes, marmalade, ham, coffee and cheeses.

[0173] Flavors, fragrances and colorants can be added in any amount, such as between

10 about 0.001 wt.% to about 30 wt.%, e.g., between about 0.01 to about 20, between about 0.05 to about 10, or between about 0.1 wt.% to about 5 wt.%. These can be formulated, mixed and or reacted (e.g., with any one of more product or intermediate described herein) by any means and in any order or sequence (e.g., agitated, mixed, emulsified, gelled, infused, heated, sonicated, and/or suspended). Fillers, binders, emulsifier,

15 antioxidants can also be utilized, for example, protein gels, starches and silica.

[0174] In one embodiment the flavors, fragrances and colorants can be added to the biomass immediately after the biomass is irradiated such that the reactive sites created by the irradiation may react with reactive compatible sites of the flavors, fragrances, and colorants.

20 [0175] The flavors, fragrances and colorants can be natural and/or synthetic materials. These materials can be one or more of a compound, a composition or mixtures of these (e.g., a formulated or natural composition of several compounds). Optionally the flavors, fragrances, antioxidants and colorants can be derived biologically, for example, from a fermentation process (e.g., fermentation of saccharified materials as described herein).

25 Alternatively, or additionally these flavors, fragrances and colorants can be harvested from a whole organism (e.g., plant, fungus, animal, bacteria or yeast) or a part of an organism. The organism can be collected and or extracted to provide color, flavors, fragrances and/or antioxidant by any means including utilizing the methods, systems and equipment described herein, hot water extraction, supercritical fluid extraction, chemical

30 extraction (e.g., solvent or reactive extraction including acids and bases), mechanical extraction (e.g., pressing, comminuting, filtering), utilizing an enzyme, utilizing a bacteria such as to break down a starting material, and combinations of these methods. The compounds can be derived by a chemical reaction, for example, the combination of a sugar (e.g., as produced as described herein) with an amino acid (Maillard reaction). The

flavor, fragrance, antioxidant and/or colorant can be an intermediate and or product produced by the methods, equipment or systems described herein, for example and ester and a lignin derived product.

5 FLAVORS, FRAGRANCES, AND COLORANTS

[0176] Some examples of flavor, fragrances or colorants are polyphenols. Polyphenols are pigments responsible for the red, purple and blue colorants of many fruits, vegetables, cereal grains, and flowers. Polyphenols also can have antioxidant properties and often have a bitter taste. The antioxidant properties make these important
10 preservatives. One class of polyphenols are the flavonoids, such as Anthocyanidines, flavanones, flavan-3-ols, s, flavanones and flavanones. Other phenolic compounds that can be used include phenolic acids and their esters, such as chlorogenic acid and polymeric tannins.

[0177] Among the colorants inorganic compounds, minerals or organic compounds can
15 be used, for example titanium dioxide, zinc oxide, aluminum oxide, cadmium yellow (E.g., CdS), cadmium orange (e.g., CdS with some Se), alizarin crimson (e.g., synthetic or non-synthetic rose madder), ultramarine (e.g., synthetic ultramarine, natural ultramarine, synthetic ultramarine violet), cobalt blue, cobalt yellow, cobalt green, viridian (e.g., hydrated chromium(III)oxide), chalcophyllite, conicalcrite, cornubite,
20 cornwallite and licronite. Black pigments such as carbon black and self-dispersed blacks may be used.

[0178] Some flavors and fragrances that can be utilized include ACALEA TBHQ, ACET C-6, ALLYL AMYL GLYCOLATE, ALPHA TERPINEOL, AMBRETTOLIDE, AMBRINOL 95, ANDRANE, APHERMATE, APPLELIDE, BACDANOL®,
25 BERGAMAL, BETA IONONE EPOXIDE, BETA NAPIITHYL ISO-BUTYL ETHER, BICYCLONONALACTONE, BORNAFIX®, CANTHOXAL, CASHMERAN®, CASHMERAN® VELVET, CASSIFFIX®, CEDRAFIX, CEDRAMBER®, CEDRYL ACETATE, CELESTOLIDE, CINNAMALVA, CITRAL DIMETHYL ACETATE, CITROLATE™, CITRONELLOL 700, CITRONELLOL 950, CITRONELLOL
30 COEUR, CITRONELLYL ACETATE, CITRONELLYL ACETATE PURE, CITRONELLYL FORMATE, CLARYCET, CLONAL, CONIFERAN, CONIFERAN PURE, CORTEX ALDEHYDE 50% PEOMOSA, CYCLABUTE, CYCLACET®, CYCLAPROP®, CYCLEMAX™, CYCLOHEXYL ETHYL ACETATE, DAMASCOL, DELTA DAMASCONE, DIHYDRO CYCLACET, DIHYDRO MYRCENOL,

DIHYDRO TERPINEOL, DIHYDRO TERPINYL ACETATE, DIMETHYL
 CYCLORMOL, DIMETHYL OCTANOL PQ, DIMYRCETOL, DIOLA, DIPENTENE,
 DULCINYL® RECRYSTALLIZED, ETHYL-3-PHENYL GLYCIDATE,
 FLEURAMONE, FLEURANIL, FLORAL SUPER, FLORALOZONE, FLORIFFOL,
 5 FRAISTONE, FRUCTONE, GALAXOLIDE® 50, GALAXOLIDE® 50 BB,
 GALAXOLIDE® 50 IPM, GALAXOLIDE® UNDILUTED, GALBASCONÉ,
 GERALDEHYDE, GERANIOL 5020, GERANIOL 600 TYPE, GERANIOL 950,
 GERANIOL 980 (PURE), GERANIOL CFT COEUR, GERANIOL COEUR,
 GERANYL ACETATE COEUR, GERANYL ACETATE, PURE, GERANYL
 10 FORMATE, GRISALVA, GUAIYL ACETATE, HELIONAL™, HERBAC,
 HERBALIME™, HEXADECANOLIDE, HEXALON, HEXENYL SALICYLATE CIS
 3-, HYACINTH BODY, HYACINTH BODY NO. 3, HYDRATROPIC
 ALDEHYDE.DMA, HYDROXYOL, INDOLAROME, INTRELEVEN ALDEHYDE,
 INTRELEVEN ALDEHYDE SPECIAL, IONONE ALPHA, IONONE BETA, ISO
 15 CYCLO CITRAL, ISO CYCLO GERANIOL, ISO E SUPER®, ISOBUTYL
 QUINOLINE, JASMAI., JESSEMAL®, KHARISMAI®, KHARISMAI® SUPER,
 KHUSINIL, KOAVONE®, KOHINOOL®, LIFFAROME™, LIMOXAL,
 LINDENOL™, LYRAL®, LYRAME SUPER, MANDARIN ALD 10% TRI ETH,
 CITR, MARITIMA, MCK CHINESE, MEIJIFF™, MELAFLEUR, MELOZONE,
 20 METHYL ANTHIRANILATE, METHYL IONONE ALPHA EXTRA, METHYL
 IONONE GAMMA A, METHYL IONONE GAMMA COEUR, METHYL IONONE
 GAMMA PURE, METHYL LAVENDER KETONE, MONTAVERDI®, MUGUESIA,
 MUGUET ALDEHYDE 50, MUSK Z4, MYRAC ALDEHYDE, MYRCENYL
 ACETATE, NECTARATE™, NEROL 900, NERYL ACETATE, OCIMENE,
 25 OCTACETAL, ORANGE FLOWER ETHER, ORIVONE., ORRINIFF 25%,
 OXASPIRANE, OZOFLEUR, PAMPLEFLEUR®, PEOMOSA, PHENOXANOL®,
 PICONIA, PRECYCLEMONE B, PRENYL ACETATE, PRISMANTOL, RESEDA
 BODY, ROSALVA, ROSAMUSK, SANJINOL., SANTALIFF™, SYVERTAL,
 TERPINEOL, TERPINOLENE 20, TERPINOLENE 90 PQ, TERPINOLENE RECT.,
 30 TERPINYL ACETATE, TERPINYL ACETATE JAX, TETRAHYDRO, MUGUOL®,
 TETRAHYDRO MYRCENOL, TETRAMERAN, TIMBERSILK™, TOBACAROL,
 TRIMOFIX® O TT, TRIPLAL®, TRISAMBER®, VANORIS, VERDOX™,
 VERDOX™ HC, VERTENEX®, VERTENEX® HC, VERTOPIX® COEUR,
 VERTOLIFF, VERTOLIFF ISO, VIOLIFF, VIVALDIE, ZENOLIDE, ABS INDIA 75

PCT MIGLYOL, ABS MOROCCO 50 PCT DPG, ABS MOROCCO 50 PCT TEC,
 ABSOLUTE FRENCH, ABSOLUTE INDIA, ABSOLUTE MD 50 PCT BB,
 ABSOLUTE MOROCCO, CONCENTRATE PG, TINCTURE 20 PCT, AMBERGRIS,
 AMBRETTE ABSOLUTE, AMBRETTE SEED OIL, ARMOISE OIL 70 PCT
 5 THUYONE, BASIL ABSOLUTE GRAND VERT, BASIL GRAND VERT ABS MD,
 BASIL OIL GRAND VERT, BASIL OIL VERVEINA, BASIL OIL VIETNAM, BAY
 OIL TERPENELESS, BEESWAX ABS N G, BEESWAX ABSOLUTE, BENZOIN
 RESINOID SIAM, BENZOIN RESINOID SIAM 50 PCT DPG, BENZOIN RESINOID
 SIAM 50 PCT PG, BENZOIN RESINOID SIAM 70.5 PCT TEC, BLACKCURRANT
 10 BUD ABS 65 PCT PG, BLACKCURRANT BUD ABS MD 37 PCT TEC,
 BLACKCURRANT BUD ABS MIGLYOL, BLACKCURRANT BUD ABSOLUTE
 BURGUNDY, BOIS DE ROSE OIL, BRAN ABSOLUTE, BRAN RESINOID,
 BROOM ABSOLUTE ITALY, CARDAMOM GUATEMALA CO2 EXTRACT,
 CARDAMOM OIL GUATEMALA, CARDAMOM OIL INDIA, CARROT HEART,
 15 CASSIE ABSOLUTE EGYPT, CASSIE ABSOLUTE MD 50 PCT IPM, CASTOREUM
 ABS 90 PCT TEC, CASTOREUM ABS C 50 PCT MIGLYOL, CASTOREUM
 ABSOLUTE, CASTOREUM RESINOID, CASTOREUM RESINOID 50 PCT DPG,
 CEDROL CEDRENE, CEDRUS ATLANTICA OIL REDIST, CHAMOMILE OIL
 ROMAN, CHAMOMILE OIL WILD, CHAMOMILE OIL WILD LOW LIMONENE,
 20 CINNAMON BARK OIL CEYLAN, CISTE ABSOLUTE, CISTE ABSOLUTE
 COLORLESS, CITRONELLA OIL ASIA IRON FREE, CIVET ABS 75 PCT PG,
 CIVET ABSOLUTE, CIVET TINCTURE 10 PCT, CLARY SAGE ABS FRENCH
 DECOL, CLARY SAGE ABSOLUTE FRENCH, CLARY SAGE C'LESS 50 PCT PG,
 CLARY SAGE OIL FRENCH, COPAIBA BALSAM, COPAIBA BALSAM OIL,
 25 CORIANDER SEED OIL, CYPRESS OIL, CYPRESS OIL ORGANIC, DAVANA OIL,
 GALBANOL, GALBANUM ABSOLUTE COLORLESS, GALBANUM OIL,
 GALBANUM RESINOID, GALBANUM RESINOID 50 PCT DPG, GALBANUM
 RESINOID HERCOLYN BHT, GALBANUM RESINOID TEC BHT, GENTIANE
 ABSOLUTE MD 20 PCT BB, GENTIANE CONCRETE, GERANIUM ABS EGYPT
 30 MD, GERANIUM ABSOLUTE EGYPT, GERANIUM OIL CHINA, GERANIUM OIL
 EGYPT, GINGER OIL 624, GINGER OIL RECTIFIED SOLUBLE, GUAIAACWOOD
 HEART, HAY ABS MD 50 PCT BB, HAY ABSOLUTE, HAY ABSOLUTE MD 50
 PCT TEC, HEALINGWOOD, HYSSOP OIL ORGANIC, IMMORTELLE ABS YUGO
 MD 50 PCT TEC, IMMORTELLE ABSOLUTE SPAIN, IMMORTELLE ABSOLUTE

- YUGO, JASMIN ABS INDIA MD, JASMIN ABSOLUTE EGYPT, JASMIN
ABSOLUTE INDIA, ASMIN ABSOLUTE MOROCCO, JASMIN ABSOLUTE
SAMBAC, JONQUILLE ABS MD 20 PCT BB, JONQUILLE ABSOLUTE France,
JUNIPER BERRY OIL FLG, JUNIPER BERRY OIL RECTIFIED SOLUBLE,
- 5 LABDANUM RESINOID 50 PCT TEC, LABDANUM RESINOID BB, LABDANUM
RESINOID MD, LABDANUM RESINOID MD 50 PCT BB, LAVANDIN ABSOLUTE
H, LAVANDIN ABSOLUTE MD, LAVANDIN OIL ABRIAL ORGANIC,
LAVANDIN OIL GROSSO ORGANIC, LAVANDIN OIL SUPER, LAVENDER
ABSOLUTE H, LAVENDER ABSOLUTE MD, LAVENDER OIL COUMARIN
- 10 FREE, LAVENDER OIL COUMARIN FREE ORGANIC, LAVENDER OIL
MAILLETTE ORGANIC, LAVENDER OIL MT, MACE ABSOLUTE BB,
MAGNOLIA FLOWER OIL LOW METHYL EUGENOL, MAGNOLIA FLOWER
OIL, MAGNOLIA FLOWER OIL MD, MAGNOLIA LEAF OIL, MANDARIN OIL
MD, MANDARIN OIL MD BHT, MATE ABSOLUTE BB, MOSS TREE ABSOLUTE
- 15 MD TEX IFRA 43, MOSS-OAK ABS MD TEC IFRA 43, MOSS-OAK ABSOLUTE
IFRA 43, MOSS-TREE ABSOLUTE MD IPM IFRA 43, MYRRH RESINOID BB,
MYRRH RESINOID MD, MYRRH RESINOID TEC, MYRTLE OIL IRON FREE,
MYRTLE OIL TUNISIA RECTIFIED, NARCISSE ABS MD 20 PCT BB, NARCISSE
ABSOLUTE FRENCH, NEROLI OIL TUNISIA, NUTMEG OIL TERPENELESS,
- 20 OEILLET ABSOLUTE, OLIBANUM RESINOID, OLIBANUM RESINOID BB,
OLIBANUM RESINOID DPG, OLIBANUM RESINOID EXTRA 50 PCT DPG,
OLIBANUM RESINOID MD, OLIBANUM RESINOID MD 50 PCT DPG,
OLIBANUM RESINOID TEC, OPOPONAX RESINOID TEC, ORANGE BIGARADE
OIL MD BHT, ORANGE BIGARADE OIL MD SCFC, ORANGE FLOWER
- 25 ABSOLUTE TUNISIA, ORANGE FLOWER WATER ABSOLUTE TUNISIA,
ORANGE LEAF ABSOLUTE, ORANGE LEAF WATER ABSOLUTE TUNISIA,
ORRIS ABSOLUTE ITALY, ORRIS CONCRETE 15 PCT IRONE, ORRIS
CONCRETE 8 PCT IRONE, ORRIS NATURAL 15 PCT IRONE 4095C, ORRIS
NATURAL 8 PCT IRONE 2942C, ORRIS RESINOID, OSMANTHUS ABSOLUTE,
- 30 OSMANTHUS ABSOLUTE MD 50 PCT BB, PATCHOULI HEART N°3,
PATCHOULI OIL INDONESIA, PATCHOULI OIL INDONESIA IRON FREE,
PATCHOULI OIL INDONESIA MD, PATCHOULI OIL REDIST, PENNYROYAL
HEART, PEPPERMINT ABSOLUTE MD, PETITGRAIN BIGARADE OIL TUNISIA,
PETITGRAIN CITRONNIER OIL, PETITGRAIN OIL PARAGUAY TERPENELESS,

PETITGRAIN OIL TERPENELESS STAB, PIMENTO BERRY OIL, PIMENTO LEAF OIL, RHODINOL EX GERANIUM CHINA, ROSE ABS BULGARIAN LOW METHYL EUGENOL, ROSE ABS MOROCCO LOW METHYL EUGENOL, ROSE ABS TURKISH LOW METHYL EUGENOL, ROSE ABSOLUTE, ROSE ABSOLUTE

5 BULGARIAN, ROSE ABSOLUTE DAMASCENA, ROSE ABSOLUTE MD, ROSE ABSOLUTE MOROCCO, ROSE ABSOLUTE TURKISH, ROSE OIL BULGARIAN, ROSE OIL DAMASCENA LOW METHYL EUGENOL, ROSE OIL TURKISH, ROSEMARY OIL CAMPHOR ORGANIC, ROSEMARY OIL TUNISIA, SANDALWOOD OIL INDIA, SANDALWOOD OIL INDIA RECTIFIED,

10 SANTALOL, SCHINUS MOLLE OIL, ST JOHN BREAD TINCTURE 10 PCT, STYRAX RESINOID, STYRAX RESINOID, TAGETE OIL, TEA TREE HEART, TONKA BEAN ABS 50 PCT SOLVENTS, TONKA BEAN ABSOLUTE, TUBEROSE ABSOLUTE INDIA, VETIVER HEART EXTRA, VETIVER OIL HAITI, VETIVER OIL HAITI MD, VETIVER OIL JAVA, VETIVER OIL JAVA MD, VIOLET LEAF

15 ABSOLUTE EGYPT, VIOLET LEAF ABSOLUTE EGYPT DECOL, VIOLET LEAF ABSOLUTE FRENCH, VIOLET LEAF ABSOLUTE MD 50 PCT BB, WORMWOOD OIL TERPENELESS, YLANG EXTRA OIL, YLANG III OIL and combinations of these.

[0179] The colorants can be among those listed in the Colour Index International by the

20 Society of Dyers and Colourists. Colorants include dyes and pigments and include those commonly used for coloring textiles, paints, inks and inkjet inks. Some colorants that can be utilized include carotenoids, arylide yellows, diarylide yellows, β -naphthols, naphthols, benzimidazolones, diazo condensation pigments, pyrazolones, nickel azo yellow, phthalocyanines, quinacridones, perylenes and perinones, isoindolinone and

25 isoindoline pigments, triarylcarbonium pigments, diketopyrrolo-pyrrole pigments, thioindigoids. Carotenoids include, alpha-carotene, beta-carotene, gamma-carotene, lycopene, lutein and astaxanthin, Annatto extract, Dehydrated beets (beet powder), Canthaxanthin, Caramel, β -Apo-8'-carotenal, Cochineal extract, Carmine, Sodium copper chlorophyllin, Toasted partially defatted cooked cottonseed flour, Ferrous

30 gluconate, Ferrous lactate, Grape color extract, Grape skin extract (enocianina), Carrot oil, Paprika, Paprika oleoresin, Mica-based pearlescent pigments, Riboflavin, Saffron, Titanium dioxide, Tomato lycopene extract; tomato lycopene concentrate, Turmeric, Turmeric oleoresin, FD&C Blue No. 1, FD&C Blue No. 2, FD&C Green No. 3, Orange B, Citrus Red No. 2, FD&C Red No. 3, FD&C Red No. 40, FD&C Yellow No. 5, FD&C

Yellow No. 6, Alumina (dried aluminum hydroxide), Calcium carbonate, Potassium sodium copper chlorophyllin (chlorophyllin-copper complex), Dihydroxyacetone, Bismuth oxychloride, Ferric ammonium ferrocyanide, Ferric ferrocyanide, Chromium hydroxide green, Chromium oxide greens, Guanine, Pyrophyllite, Tale, Aluminum powder, Bronze powder, Copper powder, Zinc oxide, D&C Blue No. 4, D&C Green No. 5, D&C Green No. 6, D&C Green No. 8, D&C Orange No. 4, D&C Orange No. 5, D&C Orange No. 10, D&C Orange No. 11, FD&C Red No. 4, D&C Red No. 6, D&C Red No. 7, D&C Red No. 17, D&C Red No. 21, D&C Red No. 22, D&C Red No. 27, D&C Red No. 28, D&C Red No. 30, D&C Red No. 31, D&C Red No. 33, D&C Red No. 34, D&C Red No. 36, D&C Red No. 39, D&C Violet No. 2, D&C Yellow No. 7, Ext. D&C Yellow No. 7, D&C Yellow No. 8, D&C Yellow No. 10, D&C Yellow No. 11, D&C Black No. 2, D&C Black No. 3 (3), D&C Brown No. 1, Ext. D&C, Chromium-cobalt-aluminum oxide, Ferric ammonium citrate, Pyrogallol, Logwood extract, 1,4-Bis[(2-hydroxy-ethyl)amino]-9,10-anthracenedione bis(2-propenoic)ester copolymers, 1,4-Bis[(2-methylphenyl)amino]-9,10-anthracenedione, 1,4-Bis[4-(2-methacryloxyethyl)phenylamino] anthraquinone copolymers, Carbazole violet, Chlorophyllin-copper complex, Chromium-cobalt-aluminum oxide., C.I. Vat Orange 1, 2-[[2,5-Diethoxy-4-[(4-methylphenyl)thiol] phenyl]azo]-1,3,5-benzenetriol, 16,23-Dihydrodinaphtho [2,3-a:2',3'-i] naphth [2',3':6,7] indolo [2,3-c] carbazole- 5,10,15,17,22,24-hexone, N,N'-(9,10-Dihydro- 9,10-dioxo- 1,5-anthracenediyl) bisbenzamide, 7,16-Dichloro- 6,15-dihydro- 5,9,14,18-anthrazinetetrone, 16,17-Dimethoxydinaphtho (1,2,3-cd:3',2',1'-lm) perylene- 5,10-dione, Poly(hydroxyethyl methacrylate) -dye copolymers(3), Reactive Black 5, Reactive Blue 21, Reactive Orange 78, Reactive Yellow 15, Reactive Blue No. 19, Reactive Blue No. 4, C.I. Reactive Red 11, C.I. Reactive Yellow 86, C.I. Reactive Blue 163, C.I. Reactive Red 180, 4-[(2,4-dimethylphenyl)azo]- 2,4-dihydro- 5-methyl-2-phenyl- 3H-pyrazol-3-one (solvent Yellow 18), 6-Ethoxy-2- (6-ethoxy-3-oxobenzo[b]thien-2(3H)- ylidene) benzo[b]thiophen- 3(2H)-one, Phthalocyanine green, Vinyl alcohol/methyl methacrylate-dye reaction products, C.I. Reactive Red 180, C.I. Reactive Black 5, C.I. Reactive Orange 78, C.I. Reactive Yellow 15, C.I. Reactive Blue 21, Disodium 1-amino-4-[[4-[(2-bromo-1-oxoallyl)amino]-2-sulphonatophenyl]amino]-9,10-dihydro-9,10-dioxoanthracene-2-sulphonate (Reactive Blue 69), D&C Blue No. 9, [Phthalocyaninato(2-)] copper and mixtures of these.

[0180] Other than in the examples herein, or unless otherwise expressly specified, all of the numerical ranges, amounts, values and percentages, such as those for amounts of

materials, elemental contents, times and temperatures of reaction, ratios of amounts, and others, in the following portion of the specification and attached claims may be read as if prefaced by the word “about” even though the term “about” may not expressly appear with the value, amount, or range. Accordingly, unless indicated to the contrary, the numerical parameters set forth in the following specification and attached claims are approximations that may vary depending upon the desired properties sought to be obtained by the present invention. At the very least, and not as an attempt to limit the application of the doctrine of equivalents to the scope of the claims, each numerical parameter should at least be construed in light of the number of reported significant digits and by applying ordinary rounding techniques.

[0181] Notwithstanding that the numerical ranges and parameters setting forth the broad scope of the invention are approximations, the numerical values set forth in the specific examples are reported as precisely as possible. Any numerical value, however, inherently contains error necessarily resulting from the standard deviation found in its underlying respective testing measurements. Furthermore, when numerical ranges are set forth herein, these ranges are inclusive of the recited range end points (e.g., end points may be used). When percentages by weight are used herein, the numerical values reported are relative to the total weight.

[0182] Also, it should be understood that any numerical range recited herein is intended to include all sub-ranges subsumed therein. For example, a range of “1 to 10” is intended to include all sub-ranges between (and including) the recited minimum value of 1 and the recited maximum value of 10, that is, having a minimum value equal to or greater than 1 and a maximum value of equal to or less than 10. The terms “one,” “a,” or “an” as used herein are intended to include “at least one” or “one or more,” unless otherwise indicated.

[0183] Any patent, publication, or other disclosure material, in whole or in part, that is said to be incorporated by reference herein is incorporated herein only to the extent that the incorporated material does not conflict with existing definitions, statements, or other disclosure material set forth in this disclosure. As such, and to the extent necessary, the disclosure as explicitly set forth herein supersedes any conflicting material incorporated herein by reference. Any material, or portion thereof, that is said to be incorporated by reference herein, but which conflicts with existing definitions, statements, or other disclosure material set forth herein will only be incorporated to the extent that no conflict arises between that incorporated material and the existing disclosure material.

[0184] While this invention has been particularly shown and described with references to preferred embodiments thereof, it will be understood by those skilled in the art that various changes in form and details may be made therein without departing from the scope of the invention encompassed by the appended claims.

CLAIMS

1. A method of conveying a material under an electron beam, the method comprising:

5 exposing a biomass material to an electron beam while conveying the biomass material on a vibratory conveyor, wherein the vibratory conveyor comprises a vibratory conveyor trough having a first surface conveying the biomass, and

oscillating the vibratory conveyor in a direction parallel to the direction of conveying and perpendicular to the scan horn of the electron beam.

10

2. The method of claim 1, wherein the total electron beam power has at least 50 kW of power.

3. The method of claim 1, wherein the vibratory conveyor comprises a metal, alloys of metals or coated metals and alloys of metals.

15 4. The method of claim 1, wherein the vibratory conveyor trough comprises a first surface of the vibratory conveyor trough conveying the biomass, and the method further comprises cooling a second surface of the vibratory conveyor trough, wherein the first and second surfaces of the vibratory conveyor trough are in thermal communication, and wherein the distance between the first and second surface of the vibratory conveyor trough is between
20 about 1/64 and 2 inches.

5. The method of claim 1, wherein the vibratory conveyor trough comprises a first surface of the vibratory conveyor trough conveying the biomass, and the method further comprises cooling a second surface of the vibratory conveyor trough, wherein the first and second surfaces of the vibratory conveyor trough are in thermal communication, and further
25 comprising cooling the second surface by contacting the second surface with a cooling enclosure containing a cooling fluid.

6. The method of claim 5, wherein the second surface of the vibratory conveyor trough forms a part of the cooling enclosure.

7. The method of claim 5, further comprising flowing fluid through the cooling enclosure by flowing the cooling fluid into the cooling enclosure through an inlet to the enclosure and flowing the fluid out of the cooling enclosure through an outlet from the cooling enclosure.

8. The method of claim 7, wherein the cooling enclosure comprises channels configured to allow the flow of the cooling agent from the inlet to the outlet.

9. The method of claim 7, further comprising maintaining a difference in the temperature of the cooling agent at the inlet of the cooling enclosure to the temperature at the outlet of the enclosure of between about 2 to 120 ° C.

10. The method of claim 6, further comprising maintaining a flow rate of cooling fluid through the cooling enclosure of between 0.5 and 150 gallons/minute.