



(43) International Publication Date
22 November 2012 (22.11.2012)

- (51) International Patent Classification:
H02K 31/00 (2006.01)
- (21) International Application Number:
PCT/CZ2012/000039
- (22) International Filing Date:
11 May 2012 (11.05.2012)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
PV 2011-293 17 May 2011 (17.05.2011) CZ
- (71) Applicant (for all designated States except US): **COM-
INFO, A.S.** [CZ/CZ]; Nábřeží 695, 76001 Zlín Pršté
(CZ).
- (72) Inventor; and
- (75) Inventor/Applicant (for US only): **VÁCLAV, Konfršt**
[CZ/CZ]; Mostecká 3186, 27201 Kladno (CZ).
- (74) Agent: **ŽÁK, Vítězslav**; Ostopovická 4, 66441 Troubsko
(CZ).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report (Art. 21(3))

[Continued on next page]

(54) Title: DIRECT-CURRENT ELECTRIC MOTOR




Fig. 2

(57) Abstract: For applications standard d-c machines require gear-boxes, there is designed a d-c motor provided with a first basic element (1) made of magnetic conductive material and carrying a system of unipolar oriented magnets (3) and further provided with a second basic element (2) made of magnetic non-conductive material and carrying at least one coil (4) with leads for connection to a source of d-c current. The coil (4) is located on a core (5) made of a magnetic conductive material and arranged mutually spaced apart along the system of the magnets. The first and the second parts are mutually relatively movable. In a preferred application the magnets are made of permanent magnets (3).



-
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))* (88) **Date of publication of the international search report:**
3 April 2014