

9901474-8 IPOs

PCT

WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : A43B 7/16, 13/38		A1	(11) International Publication Number: WO 98/14083 ✓
			(43) International Publication Date: 9 April 1998 (09.04.98)
(21) International Application Number: PCT/US97/17652 ✓		(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, <u>SG</u> , SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, ML, MR, NE, SN, TD, TG).	
(22) International Filing Date: 30 September 1997 (30.09.97) ✓			
(30) Priority Data: ① 08/720,719 ✓ 2 October 1996 (02.10.96) ✓ US ✓ ② 08/883,553 ✓ 26 June 1997 (26.06.97) ✓ US ✓			
(71) Applicant: HBN SHOE, LLC [US/US]; 175 Canal Street, Manchester, NH 03101 (US). ✓			
(72) Inventor: DANANBERG, Howard, J.; 19 Beaver Lane, Bedford, NH 03110 (US). ✓			
(74) Agent: SOLOWAY, Norman, P.; Hayes, Soloway, Hennessey, Grossman & Hage, 175 Canal Street, Manchester, NH 03101 (US).		Published With international search report. / Before the expiration of the time limit for amending the claims and to be republished in the event of the receipt of amendments. 2 PD 1 appl^a 1 inv. IPC : A43B 7/16 ; A43B 13/38	
(54) Title: SHOE AND METHOD OF MAKING SAME ✓		IPER 24/7/98	
(57) Abstract			
A foot construction comprising a rigid molded device (116) comprising a heel cup (118) and an anatomically shaped arch appliance (120) extending forwardly from the heel cup to just proximal to the metatarsal heads, causes the foot of the wearer to assume an anatomically correct position in the shoe, provides torsional stability and contributes to shoe structure integrity.			