

TITLE OF THE INVENTION

APPARATUS FOR ROASTING SKEWERED FOOD

BACKGROUND OF THE INVENTION

Field of the Invention

[0001]

The present invention relates to an apparatus for roasting skewered food which can quickly cook a large amount of skewered roasted food such as skewered roasted chickens, skewered roasted giblets and the like prepared by heating pieces of meat, fish, vegetables and the like set on a skewer.

Description of Related Art

[0002]

There has been known the method of cooking skewered roasted food by setting pieces of meat, fish, vegetables and the like on a skewer and heating the materials, but for cooking skewered roasted food such as skewered roasted chickens, skewered roasted giblets and the like which can be provided and sold at pubs, restaurants, or other types of stores, persons hoping to engage in the job are required to work as apprentices at skilled persons for several years. In addition, because scales of the pubs, restaurants, and other stores have been increasingly larger, it is required to cook a large amount of skewered roasted food quickly within a short period of time.

[0003]

To satisfy the need as described above, there has been proposed the apparatus for roasting skewered food which can quickly cook a large amount of skewered roasted food within a short period of time without requiring the long time job training, in which a number of skewer holders are mounted on an endless rotary chain with a prescribed space in-between, raw materials of skewered food prepared by setting food materials on a skewer are held on the skewer holders in order, and the raw materials of skewered food are carried along heating devices for heating the raw materials of skewered food to prepare skewered roasted food (Refer to Japanese Patent Laid.-Open Publication No. 2004-57463; Patent document 1).

[0004]

In the apparatus for roasting skewered food mentioned in the patent document 1, when a raw material of skewered food is held on skewer holder, it is required to hold the raw material of skewered food in the substantially horizontal posture. However, it is difficult for an operator to hold the raw material of skewered food in the horizontal posture, and because it is required to hold the raw material of skewered food with the tip portion of the skewer facing against the operator, the food materials are touched by the operator's fingers, which is not desirable from the sanitary point of view.

[0005]

Furthermore, there is no step of immersing a raw material of skewered food in sauce during the process of carrying the raw material of skewered food along heating devices with an endless rotary chain for

heating, and therefore, after the raw material of skewered food is heated to roast, it is necessary to immerse the raw material of skewered food in sauce and heat the raw material of skewered food again, so that the work load is rather heavy and the period of time required for cooking skewered roasted food is disadvantageously long.

[0006]

In addition, because linking pins or the like are used for mounting the skewer holders on the endless rotary chain, when the number of skewer holders is to be changed or any skewer holder is exchanged with a new one because of a failure or for some other reasons, it is required to remove the endless rotary chain from sprockets and then dismount skewer-holders, and therefore, the work for dismounting skewer holders is laborious and requires a long period of time.

[0007]

Therefore, an inventor of this patent application developed an apparatus for roasting skewered food in which it is easy for an operator to hold a skewer holder, food materials are not touched by the operator's fingers which is desirable from the sanitary point of view, the work load is not heavy and the period of time required for cooking skewered roasted food, and also, the work for dismounting skewer holders is easy and requires not so a long period of time, to solve the problems as described above (Refer to Japanese Patent Laid.-Open Publication No. 2009-005880; Patent document 2).

[0008]

In the apparatus for roasting skewered food mentioned in the

patent document 2, the heating devices are fixed on the base through support members and the radiating faces of the heating devices are set at prescribed height. Therefore, according to the mounted position of food materials in the raw materials of skewered food, the food materials are at the position higher or lower than the position facing to the radiating faces and it is difficult to heat food materials uniformly.

[0009]

A net body for protection which protects the radiating face is set on the heating device and in case that a wire netting of the net body for protection was broken, skewer holders, an endless rotary chain, covers etc. are removed, a heating device is removed and the net body for protection is changed. Therefore, the working for changing the net body for protection is extremely troublesome and requires a long period of time.

[0010]

A skewer holder is supported to a support member rotatably in the vertical direction and when sauce is attached and stored to the connecting portion between the skewer holder and the support member, the skewer holder cannot be rotated smoothly. Therefore, the skewer holder cannot go down smoothly along the skewer holder lifting member, whereby raw materials of skewered food cannot be dipped into the sauce and there occurred the situation where skewer holders get tangled among themselves to interfere with operation of the apparatus.

[0011]

In case that the endless rotary chain cannot move by any cause during working time of the apparatus for roasting skewered food, the

endless rotary chain or driving sprocket is broken to scatter the broken pieces so that it is dangerous for a operator, and the driving motor is heated up to break out.

[0012]

In addition, in case that skewer holders are mounted and changed or the driving device is cleaned and repaired, the endless rotary chain, the driving sprocket, the driven sprocket and the like must be removed and support shafts and the like must be also removed. However, it is troublesome to remove the parts as described above and it requires a long period of time to mount and change skewer holders or clean and repair the driving device.

SUMMARY OF THE INVENTION

[0013]

The present invention was made to solve the problems in the conventional technology, and an object of the present invention is to provide an apparatus for roasting skewered food, in which food materials can be heated uniformly without the position of food materials mounted to a skewer in a raw material of roasting skewered. the working to change net body for protection is easy and requires not so a long time, raw materials for roasting skewered food are dipped into sauce certainly, skewer holders get entangled themselves to interfere the operation of the apparatus.

[0014]

Further, the other object of the present invention is to provide an apparatus for roasting skewered food, in which, in case that the endless

rotary chain cannot move, the endless rotary chain, the driving sprocket and driving motor are not broken, it is easy to remove parts of driving device, and it doesn't require a long time to mount and change the skewer holders and clean and repair the driving device.

[0015]

In order to achieve the object, the apparatus for roasting skewered food according to the present invention comprises a skewer holder carrying mechanism that carries a raw material of skewered food prepared by setting food materials on a skewer in the vertical posture with a skewer holder mounted on an endless rotary chain; heating devices which heat the raw material of skewered food from the both sides while the raw material of skewered food are being carried; a sauce storage tank in which the raw material of skewered food is immersed in sauce; and a control unit which actuates, stops, and controls a carrying speed of the skewer holder carrying mechanism, characterized in that the radiating face of the said heating device can be adjusted of its height.

[0016]

The apparatus for roasting skewered food according to the present invention is characterized in that the net body for protection of the heating device can be slid along the guide member and removed out from the front of the base. According to the structure, when the netting wire is broken, the net body for protection can be changed easily.

[0017]

The apparatus for roasting skewered food according to the present

invention is characterized in that a controlling member of skewer holders is arranged near the tank of sauce to go down skewer holders forcibly. According to the structure, raw materials of skewered food are dipped into the sauce certainly and skewer holders don't get entangled themselves to interfere the operation of the apparatus.

[0018]

If the driving sprocket is connected with the driving shaft through a key which is low strength, in case that the endless rotary chain can not move, the endless rotary chain, the driving sprocket and the driving motor are not broken.

[0019]

If the parts of the driving device can removed in a body, the parts of the driving device can easily removed and it does not require a long period of time to mount and change skewer holders and clean and repair the driving device.

[0020]

According to the apparatus for roasting skewered food of this invention, food materials can be heated uniformly irrespective of the position of food materials of the raw materials of skewer food and when a netting wire of the net body for protection is broken, the net body for protection can be changed easily.

[0021]

According to the apparatus for roasting skewered food of this invention, raw materials of skewered food can be dipped into sauce certainly and skewer holders do not get entangled themselves to interfere

the operation of the apparatus.

[0022]

Furthermore, according to the apparatus for roasting skewered food of this invention, in case that the endless rotary chain can not move, the endless rotary chain, the driving sprocket and the driving motor are not broken and it does not require a long period of time to mount and change the skewer holders and clean and repair the driving device.

BRIEF DESCRIPTION OF THE DRAWINGS

[0023]

FIG. 1 is a plan view of an apparatus for roasting skewered food according to the present invention.

[0024]

FIG. 2 is a left side view of the apparatus for roasting skewered food according to the present invention.

[0025]

FIG. 3 is a front view of the apparatus for roasting skewered food according to the present invention.

[0026]

FIG. 4 is a rear face view of the apparatus for roasting skewered food according to the present invention.

[0027]

FIG. 5 (A) is a plan view illustrating a driving device and FIG. 5 (B) is a cross-sectional view illustrating the driving device.

[0028]

FIG. 6 (A) is a plan view illustrating a driving sprocket mounting section and FIG. 6 (B) is a cross-sectional view illustrating the driving sprocket mounting section.

[0029]

FIG. 7 (A) is a plan view illustrating a driven sprocket mounting section and FIG. 7 (B) is a cross-sectional view illustrating the driven sprocket mounting section.

[0030]

FIG. 8 (A) is a plan view illustrating the heating device arranging section and FIG. 8 (B) is a side view illustrating the heating device arranging section.

[0031]

FIG. 9 (A) is a plan view illustrating a state where a skewer holder is mounted on a support member and FIG. 9 (B) is a side view illustrating the state.

[0032]

FIG. 10 (A) is a plan view illustrating a holder main body of a skewer holder and FIG. 10 (B) is a side view illustrating the holder main body.

[0033]

FIG. 11 is a view illustrating a method of mounting a skewer holder on a support member.

[0034]

FIG. 12 (A) is a plan view illustrating an action of a skewer releasing mechanism and FIG. 12 (B) is a side view illustrating the action.

[0035]

FIG. 13 (A) is a plan view illustrating a sauce adhesion preventing mechanism and FIG. 13 (B) is a side view illustrating the sauce adhesion preventing mechanism.

[0036]

FIG. 14 (A) is a plan view illustrating an operation of the skewer holder at a position adjacent to a sauce storage tank when a skewer holder support member is located at a lower position and FIG. 14 (B) is a side cross-sectional view illustrating the operation.

[0037]

FIG. 15 (A) is a plan view illustrating an operation of the skewer holder at a position adjacent to a sauce storage tank when a skewer holder support member is located at an upper position and FIG. 15 (B) is a side cross-sectional view illustrating the operation.

DETAILED DESCRIPTION OF THE INVENTION

[0038]

A preferable embodiment of the apparatus for roasting skewered food according to the present invention is described specifically in detail with reference to the drawings.

FIG. 1 is a plan view of the apparatus for roasting skewered food according to the present invention, FIG. 2 is a left side view of the apparatus, FIG. 3 is a front view of the apparatus, FIG. 4 is a rear view of the apparatus, and FIG. 5 (A) is a plan view of the driving device and . FIG. 5 (B) is a sectional view of the driving device.

[0039]

An apparatus for roasting skewered food 1 according to the present invention comprises a skewer holder carrying mechanism 2, heating devices 3, 4, a sauce storage tank 5, and a control unit 6 as shown in FIG. 1 to FIG. 5.

[0040]

The skewer holder carrying mechanism 2 comprises an endless rotary chain 7, a driving sprocket 8, a driven sprocket 9, and a driving motor 10.

[0041]

As shown in FIG. 5, a bottom 12A is provided on a top face of a base 11 and a support plate 12D is provided on the bottom plate 12A through brackets 12B, 12C. Column supports 13, 13 are provided on the support plate 12D with a prescribed space in-between in the longitudinal direction and a ceiling plate 14 is provided on the upper edge portion of the column supports 13, 13..

[0042]

A driving shaft 15 is provided in the upright state at the back of the base 11, and as shown in FIG. 5 and FIG. 6, the driving sprocket 8 is fixed to an upper edge portion of the driving shaft 15. A shaft 10a of the driving motor 10 is linked via a linking member 16 to a lower edge portion of the driving shaft 15.

[0043]

As shown in FIG. 6, a key groove 15a is provided in the driving shaft 15, while a key groove 8a is provided in the driving sprocket 8, and the driving sprocket 8 can easily be set in or dismounted from the driving

shaft 15 by manually engaging a key 17 in or removing the key 17 from each of the key grooves 15a and 8a.

A stepped portion 15b is provided in the driving shaft 15 for preventing the driving sprocket 8 from moving downward.

[0044]

A driven shaft 18 is provided in the upright state in front of the base 11, and as shown in FIG. 5 and FIG. 7, the driven sprocket 9 is fixed via a bearing 19 on a top edge portion of the driven shaft 18.

[0045]

As shown in FIG. 7, the bearing 19 is press-fit into an engagement hole 9a of the driven sprocket 9, while the bearing 19 is loosely engaged with the driven shaft 18. Therefore, when the driven sprocket 9 is pulled upward strongly, the driven sprocket 9 can relatively easily be disengaged from the driven shaft 18.

To prevent the driven sprocket 9 from moving downward, a stepped portion 18a is formed on the driven shaft 18.

[0046]

Furthermore, the endless rotary chain 7 is spanned over the driving sprocket 8 and the driven sprocket 9, and a plurality of skewer holders 20, 20 are mounted with a prescribed space on the endless rotary chain 7.

The driving sprocket 8 and the driven sprocket 9 may be provided either in front of or at the back of the base 11.

[0047]

The key 17 is formed into L-shape from metal material with low

strength such as aluminum, and in case that overload is applied between the driving shaft 15 and the driving sprocket 8, the key 17 is broken.

Therefore, in case that the endless rotary chain 7 became not to move by any reason, overload is applied between the driving shaft 15 and the driving sprocket 8 and the key 17 is broken. After that, as the driving shaft 15 runs idle, the endless rotary chain, the driving sprocket 8 and the driving motor 10 are not broken.

[0048]

As shown in FIG. 5, the skewer holder carrying mechanism 2 is integrated with the endless rotary chain 7, the driving sprocket 8, the driven sprocket 9 and the driving motor 10.

Therefore, components of the skewer holder carrying mechanism 2 can be easily removed as a unit so that it does not take so long time to mount and change skewer holders 20 and to clean and repair the components.

Furthermore, only the driving motor 10 can be easily separated by releasing coupling between the driving shaft 15 and the shaft 10a of the driving motor 10, so that it is convenient for changing, cleaning and repairing.

[0049]

The heating devices 3, 4 are provided at both sides of the skewer holder carrying mechanism 2, and comprise gas burners 21A, 21B facing against each other with a prescribed space.

As shown in FIG. 8, a setting plate 23 is provided on the upper face

of the base 11 through a support body 22 and the gas burners 21A, 21B are fixed to the setting plate 23.

[0050]

Insertion slots 22a are formed in the support body 22 in the direction of height and screw holes 23a are formed in the setting plate 23 so that radiation face of the gas burners 21A, 21B can be adjusted on the position of height suitably by adjusting the height of the setting plate 23 suitably and fastening the setting plate 23 to the support body 22 with screws.

Therefore, without the position of food materials to a skewer, food materials can be positioned as facing to the radiation face so that food materials can be heated uniformly.

[0051]

As shown in FIG. 8, a net body for protection 24 is mounted on the radiation face of the gas burner 21A, 21B in order to protect the radiation face.

The net body for protection 24 is fixed to the radiation face with screws. The upper edge portion and lower edge portion of the net body 24 are contacted with guide bodies 25A, 25B attached to the setting plate 23 and when the net body 24 is detached from setting plate 23, the net body 24 can be slid along the guide bodies 25A, 25B and can be removed from the front of the base 11.

Therefore, in case that net wire 24a of the net body for protection 24 is broken, the net body 24 is detached from setting plate 23, slid along the guide bodies 25A, 25B and can be removed from the front of the base

11. So, work for change net bodies 24 is easy and does not require so a long time..

[0052]

The gas burners 21A is covered by cover 26A which covers the skewer holder carrying mechanism 2 so that the radiation face of the gas burners 21A is positioned in the outer side, while the gas burners 21B is covered by cover 26B which covers the gas burners 21B itself so that the radiation face of the gas burners 21B is positioned in the inner side.

In this embodiment, the gas burners 21A, 21B are far-infrared ray gas burners, but the present invention is not limited to this configuration, and electric heaters may be used.

[0053]

Gas inlet holes of the gas burners 21A, 21B are communicated to a manifold 28 provided in front of a front face portion of the base 11 via piping 27, 27, ... Provided on the manifold 28 are a cock 29 for inletting a gas, and cocks 30, 30 for adjusting a fire power.

[0054]

The sauce storage tank 5 is provided on the base 11 at the rear edge portion, and can easily be mounted on or dismounted from the base 11.

[0055]

The control unit 6 is provided in the base 11, and controls a driving motor 10 to actuate and stop the skewer holder carrying mechanism 2 and to control a carrying speed.

An operation panel 31 is provided on the front face portion 11b of the base 11, and an operation dial 32 and an operation lamp 33 are provided on the operation panel 31.

[0056]

As shown in FIG. 8 and FIG. 9, a plurality of support members 34, 34, ... are fixed with a prescribed space there-between on the endless rotary chain 7, and the skewer holders 20 are supported by the support members 34 via supporting pins 35 respectively so that the skewer holders 20 can freely rotate in the vertical direction.

[0057]

The skewer holder 20 comprises a holder main body 36 and a movable clamping body 37 as shown in FIG. 9 and FIG. 10, and the movable clamping body 37 is linked to the holder main body 36 with a pivotal pin 38 so that the movable clamping body 37 can freely rotate in the horizontal direction. In the ordinary mode, the movable clamping body 37 is elastically energized by a spring 39 to clamp and hold a skewer A.

[0058]

The holder main body 36 is a metallic rectangular and lever-shaped body as shown in FIG. 9 and FIG. 10, and a groove 36a for clamping a skewer having a semicircular form is provided on a side face at a tip portion thereof, while a recessed portion 36b for setting a spring therein is provided on a side face at the intermediate portion. In addition, a pin insertion hole 36c is provided at the intermediate portion, and a pin insertion groove 36d inclined at a prescribed angle and

extending from the top face to the central portion is provided at the base edge portion.

The supporting pin 35 inserted into the pin insertion groove 36d is not easily disengaged from the pin insertion groove 36 because movement of a rear edge face of the holder main body 36 in the horizontal direction is restricted by an internal face 34a of the mounting section of the supporting member 34, but for making the disengagement further difficult, it is preferable to inflect the pin insertion groove 36d as shown in FIG. 10 (B).

[0059]

The movable clamping member 37 is prepared by bending the metal plate into a horse-shoe shape and has a top surface portion, a side surface portion, and a bottom surface portion as shown in FIG. 9. A skewer clamping groove 37a having a semicircular form is provided at a tip side portion of each of the top surface portion and the bottom surface portion, while a pin insertion hole 37b is provided at the intermediate portion. A release pin 40 is fixed to a base portion of the top surface portion in the upright state.

[0060]

The skewer holder 20 has the configuration as described above, and therefore by inclining the skewer holder 20 at a prescribed angle with the tip portion oriented upward and moving the skewer holder 20 in the upward direction as shown in FIG. 11 (A), the supporting pin 35 of the supporting member 34 can be inserted being guided through the pin insertion groove 36d of the holder main body 36 as shown in FIG. 11 (B).

Then by turning the skewer holder 20 in the downward direction, the skewer holder 20 can be supported by the supporting member 34 in the substantially horizontal direction as shown in FIG. 11(C).

Therefore, the skewer holder 20 can be supported by the supporting member 34 without the need of dismounting the supporting pin 35 each time the skewer holder 20 is to be supported by the supporting member 34.

[0061]

Provided in the skewer holder carrying mechanism 2 is a rail-formed skewer holder guide member 41 extending outward along the endless rotary chain 7 as shown in FIG. 1, and the holder main body 36 is placed on an upper edge face of the skewer holder guide member 41, so that the skewer holder 20 is carried in the substantially horizontal state in the normal operation.

[0062]

A skewer releasing mechanism 42 is provided in the front left side portion of the skewer holder carrying mechanism 2, and the skewer releasing mechanism 42 comprises a supporting plate 43 fixed to a ceiling plate 14, and a press roller 45 rotatably supported by the supporting plate 43 via a spindle 44 as shown in FIG. 1.

[0063]

When the skewer holder 20 having a heated product of skewered roasted food product D thereon moves to the press roller 45 and the press roller 45 presses the releasing pin 40 fixed on the movable clamping body 37 as shown in FIG. 12, the press roller 45 rotates the movable clamping

body 37 against a elastic force of a spring 39 to release the clamping state by the holder main body 36 and by the movable clamping body 37, so that the product of skewered roasted food is released and drops downward.

[0064]

Then the product of skewered roasted food D dropped from the skewer holder 20 slides along a shoot 46 formed in the front left portion of the base 11, and is discharged from a product outlet port 47 formed on a front surface of the base 11, and is inserted onto a plate 48.

[0065]

A skewer holder lifting member 49 with the upper edge face curved and capable of changing the height is provided at a position adjacent to the sauce storage tank 5 at a rear edge portion of the skewer holder carrying mechanism 2 as shown in FIG. 1 and FIG. 4. A beginning edge and a end edge of the skewer holder lifting member 49 are connected to the skewer holder guide member 41, and in this configuration, when the skewer holder 20 reaches side face portions 5a, 5b of the sauce storage tank 5, a height of the upper edge face is set at the uppermost position, and when the skewer holder 20 reaches a central portion of the sauce storage tank 5, the height of the upper edge face is set at the lowermost position.

[0066]

Therefore, as shown in FIG. 14, the skewer holder 20 placed on the skewer holder guide member 41 and carried in the horizontal posture is transferred to and placed on the skewer holder lifting member 49. Then the skewer holder 20 is placed on the skewer holder lifting member 49 and is turned upward. When the skewer holder 20 reaches the side face

portion 5a of the sauce storage tank 5, the skewer holder 20 is inclined most, and when the skewer holder 20 reaches a central portion of the sauce storage tank 5, the skewer holder 20 returns to the substantially horizontal posture. Furthermore, when the skewer holder 20 reaches the side face portion 5b of the sauce storage tank 5, the skewer holder 20 is again inclined most.

[0067]

As shown in FIG. 13, the apparatus for roasting skewered food 1 has a sauce adhesion preventing mechanism 50. The sauce adhesion preventing mechanism 50 comprises a skewer holder holding member 51 having a circular form, a holding member support lever 52 like a curved lever, a grasping member 53, a grasping member support lever 54 like a straight lever, and a linking member 55 for linkage between the holding member support lever 52 and the grasping member support lever 54. The linking member 55 can freely rotate in the vertical direction with a spindle 56.

The holding member support lever 52 is divided to a vertical lever portion 52a, a curved lever portion 52b, and a horizontal lever portion 52c according to the necessity, and male screw portions are formed at the divided portion, and by screwing length adjusting members 57, 57 each with a female screw portion formed thereof, the lengths in the vertical direction and the horizontal direction can be adjusted.

[0068]

The skewer holder holding member 51 is located at a position lower than an upper edge face of the skewer holder lifting member 49 during the

normal operation as shown in FIG. 2 and FIG. 3, and the holding member support lever 52 is provided under the covers 26A, 26A for the skewer holder carrying mechanism 2 and extends from a rear side to a front side of the base 11.

The grasping member support lever 54 protrudes from a support lever guide hole 58a provided on a cover 58 covering a front portion of the skewer holder carrying mechanism 2.

[0069]

Because of the configuration described above, when the grasping member 53 and the grasping member support lever 54 are located at an upper position of the support lever guide hole 58a during the normal operation as shown in FIG. 3, because the skewer holder holding member 51 is located at a position lower than the upper edge face of the skewer holder lifting member 49 as shown in FIG. 14, the skewer holder 20 is placed on the skewer holder lifting member 49 as described above and moves upward or downward.

[0070]

When an operator grasps and presses the grasping member 53 and positions the grasping member 53 and the grasping member support lever 54 at a lower position of the support lever guide hole 58a, the holding member support lever 52 rotates upwards and the skewer holder holding member 51 is located at the substantially same position of the upper edge face of the skewer holder lifting member 49 as shown in FIG. 15.

[0071]

Therefore, the skewer holder 20 is placed on the skewer holder

lifting member 49 and rotates upward and is set in the maximum inclined position. Then the skewer holder 20 is placed on the skewer holder holding member 51 and preserved at the maximum inclined state. Then, again the skewer holder 20 is placed on the skewer holder lifting member 49 and rotates downward, and is placed on the skewer holder guide member 41 to return to the horizontal posture.

[0072]

Because of the configuration, when the grasping member 53 and the grasping member support lever 54 are positioned at the upper position of the support lever guide hole 58a during the normal operation, a raw material of skewered food can be immersed in sauce in the sauce storage tank 5 by moving up and down the skewer holder 20, and on the other hand, when the grasping member 53 is pressed down and the grasping member 53 and the grasping member support lever 54 are positioned at the lower position of the support lever guide hole 58a, the skewer holder 20 can be held at an upper position for preventing the raw material of skewered food C from being immersed in the sauce.

[0073]

However, when sauce is adhered and stored in the connecting portion between the skewer holder 20 and the support member 34, the skewer holder 20 cannot be rotated smoothly. Therefore, the skewer holder 20 cannot go down smoothly along the skewer holder lifting member 49, whereby raw materials of skewered food C cannot be dipped into the sauce and there occurred the situation where skewer holders 20, 20 get tangled among themselves to interfere with operation of the apparatus.

So, as shown in FIG. 14, a skewer holder control member 59 is provided. The skewer holder control member 59 is attached with a skewer holder 20 from the upper side so that the skewer holder 20 is guided along the skewer holder lifting member 49 smoothly and goes down.

[0074]

The apparatus for roasting skewered food 1 according to the present invention has the configuration as described above, and is used as described below for roasting skewered food.

[0075]

An operator stands in front of the base 11, and rotates an operation dial 32 clockwise to turn on power for the apparatus for roasting skewered food 1. With this operation, the operation lamp 33 is lit, and operations of the apparatus for roasting skewered food 1 are actuated. Then the driving motor 10 drives and the endless rotary chain 7 moves.

[0076]

In front of the base 11, the operator pushes a base edge portion of a skewer A of a raw material of skewered food C, which is prepared by setting food materials B on a skewer A, into skewer clamping grooves 36a, 37a of a holder main body 36 and a movable clamping body 37, so that the skewer A is clamped by the holder main body 36 and by the movable clamping body 37 and the raw material of skewered food C is hung down from and supported by the skewer holder 20.

[0077]

The raw material of skewered food C held by the skewer holder 20 in the hung state reaches the position at which the heating device 3 is

provided as shown in FIG. 1 and FIG. 3, and is heated by the gas burners 21A, 21B while being carried by the endless rotary chain 7.

[0078]

As shown in FIG. 1 and FIG. 14, when the skewer holder 20 is guided by the skewer holder lifting member 49 and rotates upward, the raw material of skewered food C getting closer to the sauce storage tank 5 rotates upward and is inclined, and when the raw material of skewered food C reaches the side face portion 5a of the sauce storage tank 5, the raw material of skewered food C is inclined at the maximum and moves over the side face portion 5a.

Then, when the skewer holder 20 rotates downward, also the raw material of skewered food C rotates downward, and the raw material of skewered food C is immersed in sauce stored in the sauce storage tank 5.

Furthermore, when the skewer holder 20 is guided by the skewer holder lifting member 49 and again rotates upward, also the raw material of skewered food C rotates upward and is inclined, and when the raw material of skewered food C reaches the side face portion 5b of the sauce storage tank 5, the raw material of skewered food C is inclined at maximum and moves over the side face portion 5b.

[0079]

As shown in FIG. 1 and FIG. 3, the raw material of skewered food C immersed in sauce in the hung state again reaches the position where the heating device 4 is provided, and is heated by the gas burners 21A, 21B while being carried by the endless rotary chain 7.

[0080]

A product of skewered roasted food D completely heated reaches a position at which the skewer releasing mechanism 42 is provided, and when the press roller 45 presses the releasing pin 40 fixed to the movable clamping body 37 of the skewer holder 20, the movable clamping body 37 rotates to release the skewer A from the clamped state, so that the product of skewered roasted food D drops from the skewer holder 20.

[0081]

The dropped product of skewered roasted food D slides on and along the shoot 46, and is discharged from the product outlet port 47 and is placed on the plate 48. As described above, the product of skewered roasted food D can almost automatically be cooked excluding the work for setting the raw material of skewered food C on the skewer holder 20.

[0082]

When a skewered roasted food not immersed in sauce and roasted with salt is to be cooked, an operator is required only to press down the grasping member 53 to locate the grasping member 53 and the grasping member support lever 54 at the upper position of the support lever guide hole 58a.

[0083]

With the operation described above, the skewer holder holding member 51 moves upward and is located at the substantially same position as the upper edge face of the skewer holder lifting member 49 as shown in FIG. 15. In this state, the skewer holder 20 is placed on and guided by the skewer holder lifting member 49 and the skewer holder holding member 51 at a position adjacent to the sauce storage tank 5, and preserved the

utmost inclined state, so that the raw material of skewered food C is prevented from being immersed in the sauce.

[0084]

As described above, with the apparatus for roasting skewered food 1 according to the present invention, an operator is required only to grasp a base edge portion of a skewer A with fingers in the state where a raw material of skewered food C is hung down, and to insert the base edge portion of the skewer A into a tip portion between the holder main body 36 and the movable clamping body 37 while a skewer holder 20 is passing through the front portion of the base 11. Therefore, the raw material of skewered food C can easily be held by the skewer holder 20 without touching the food materials B with fingers, which is preferable from the sanitary point of view.

[0085]

There is provided the step of immersing the raw material of skewered food C in sauce while the raw material of skewered food C is carried by the endless rotary chain 7 along the heating devices 3, 4 and is heated, so that the product of skewered roasted food D can be cooked quickly within a short period of time.

[0086]

Because the pin insertion groove 36d inclining at a prescribed angle is provided on the holder main body 36, so that an operator can set the skewer holder 20 on the supporting member 34, namely on the endless rotary chain 7, only by moving the skewer holder 20 upward in the inclined state and rotating the skewer holder 20 downward.

Therefore, when the number of skewer holders 20 to be set is changed or any skewer holder 20 is exchanged with a new one because of a failure or the like, it is not necessary to remove the endless rotary chain 7 from the sprockets 8, 9, so that the work for dismantling the skewer holder 20 is quite easy and can be performed quickly.

[0087]

Furthermore, the driving sprocket 8 can be dismantled from the driving shaft 15 and the driven sprocket 9 can be dismantled from the driven shaft 18 without requiring any specific tool, so that the works for removing the endless rotary chain 7 and dismantling and exchanging a number of skewer holders 20 with new ones can easily be performed.

[0088]

In case that height of the setting plate 23 is adjusted suitably and the setting plate 23 is fastened to the support body 22 by screws, height of the radiating face of the gas burner 21A, 21B can be adjusted suitably. Therefore, food materials can be heated uniformly irrespective of the position of food materials mounted to a skewer.

[0089]

The upper end portion and the lower end portion of net body for protection 24 are touched to the guide body 25A, 25B, the net body for protection 24 is slid along the guide body 25A, 25B and can be removed from the front of the base 11. Therefore, work to change the net body for protection 24 is easy and does not take a long time.

[0090]

The control member of skewer holder 59 is provided and is in contact with the skewer holder 20 from upper side to go down the skewer holder 20. Therefore, there is not occur the situation in which the skewer holder 20 does not go down smoothly along the skewer holder lifting member 49 so that raw materials of skewered food can not be dipped into sauce or skewer holders get entangled themselves to interfere the operation of the apparatus.

[0091]

In case that the endless rotary chain 7 cannot move by any reason, the key 17 is broken because of overload so that the driving shaft 15 becomes to run idle. Therefore, the endless rotary chain, the driving sprocket and the driving motor are not broken.

[0092]

In addition, the skewer holder carrying mechanism 2 comprises the integration of the endless rotary chain 7, the driving sprocket 8, the driven sprocket and the like so that the skewer holder carrying mechanism 2 can be easily removed in a body and it does not require a long period of time to mount and change the sewer holders or clean and repair the parts.

WHAT IS CLAIMED IS:

1. An apparatus for roasting skewered food comprising:

a skewer holder carrying mechanism that carries a number of raw materials of skewered food prepared by setting food materials on a skewer in the vertical posture with a skewer holder mounted on an endless rotary chain;

heating devices that heat the raw materials of skewered food from the both sides while the raw materials of skewered food are being carried;

a sauce storage tank that immerses the raw materials of skewered food in sauce; and

a control unit that actuates, stops, and controls a carrying speed of the skewer holder carrying mechanism;

wherein radiating face of the heating device can be adjusted on the height suitably and a net body for protection of the heating device can be slid along guide bodies to remove from the front of the base.

2. The apparatus for roasting skewered food according to claim 1, wherein a controlling member of skewer holder is arranged near the sauce storage tank to go down skewer holders forcibly.

3. The apparatus for roasting skewered food according to claims 1 or 2, wherein a driving sprocket of the skewer holder carrying mechanism is connected with a driving shaft through a key which is low strength.

4. The apparatus for roasting skewered food according to any of claims 1 to 3, wherein parts of the skewer holder carrying mechanism can be removed as a unit to mount and change the skewer holders and clean and repair the parts.