99.024.13-G

IDS copy

PCT WORLD INTELLECTUAL PROPERTY ORGANIZATION
International Bureau

INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification 6 : G11B 23/03 — A2

(11) International Publication Number: **WO 99/17291**

(43) International Publication Date: 8 April 1999 (08.04.99)

(21) International Application Number: PCT/IB98/01450

(22) International Filing Date: 21 September 1998 (21.09.98)

(30) Priority Data:
97202965.6 26 September 1997 (26.09.97) EP

(71) Applicant: KONINKLIJKE PHILIPS ELECTRONICS N.V. [NL/NL]; Groenewoudseweg 1, NL–5621 BA Eindhoven (NL).

(71) Applicant *(for SE only)*: PHILIPS AB [SE/SE]; Kottbygatan 7, Kista, S–164 85 Stockholm (SE).

(72) Inventor: DOODSON, Peter, John; Prof. Holstlaan 6, NL–5656 AA Eindhoven (NL).

(74) Agent: SCHRIJNEMAEKERS, Hubert, J., M.; Internationaal Octrooibureau B.V., P.O. Box 220, NL–5600 AE Eindhoven (NL).

(81) Designated States: AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, CA, CH, CN, CU, CZ, DE, DK, EE, ES, FI, GB, GE, GH, HU, ID, IL, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MD, MG, MK, MN, MW, MX, NO, NZ, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, UA, UG, UZ, VN, YU, ZW, ARIPO patent (GH, GM, KE, LS, MW, SD, SZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GW, ML, MR, NE, SN, TD, TG).

Published
Without international search report and to be republished upon receipt of that report.

(54) Title: HOUSING FOR A DISC–SHAPED INFORMATION CARRIER

(57) Abstract

A housing for storing a disc–shaped information carrier, for example a DVD. The housing is provided with a bottom part (1) with a retaining device (7) for the information carrier and a lid part (3) which is connected with hinging possibility to the bottom part. Two corner hinges form the connection here, which corner hinges comprise two recessed hinge arms (30) of the hinge part and two matching recessed hinge walls (36). The lid part is provided with protection walls (42) which extend at the outside of the housing substantially parallel to the hinge arms so as to protect the hinge arms from external mechanical influences.

