



(43) International Publication Date
10 January 2013 (10.01.2013)

(10) International Publication Number
WO 2013/006303 A1

(51) International Patent Classification:

C10M 141/06 (2006.01) *C10N 40/26* (2006.01)
C10N 10/04 (2006.01) *C10N 30/04* (2006.01)

(21) International Application Number:

PCT/US2012/044118

(22) International Filing Date:

26 June 2012 (26.06.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/505,172 7 July 2011 (07.07.2011) US

(71) Applicant (for all designated States except US): **THE LUBRIZOL CORPORATION** [US/US]; 29400 Lakeland Blvd., Wickliffe, Ohio 44092-2298 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **DOHNER, Brent R.** [US/US]; 29400 Lakeland Blvd., Wickliffe, Ohio 44092-2298 (US).

(74) Agents: **SHOLD, David M.** et al.; 29400 Lakeland Blvd., Wickliffe, Ohio 44092-2298 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,

AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))

Published:

— with international search report (Art. 21(3))

(54) Title: LUBRICANT PROVIDING IMPROVED CLEANLINESS FOR TWO-STROKE CYCLE ENGINES

(57) Abstract: A lubricant composition comprising an oil of lubricating viscosity, 0.1 to 2 percent by weight of a Mannich dispersant, and 0.1 to 2 percent by weight of a succinimide dispersant, wherein the succinimide dispersant provides at least about 40 parts per million by weight of nitrogen atoms to the lubricant composition, provides cleanliness to a two-stroke cycle engine.



WO 2013/006303 A1