

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
10 May 2002 (10.05.2002)

PCT

(10) International Publication Number
WO 02/36037 A1

(51) International Patent Classification⁷: **A61C 7/14**

(21) International Application Number: PCT/AU01/01427

(22) International Filing Date:
5 November 2001 (05.11.2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
PR 1280 6 November 2000 (06.11.2000) AU

(71) Applicant (for all designated States except US): **GOLD-SCHMIED PTY LTD** [AU/AU]; 58 Gascoyne Street, Launceston, Tasmania 7250 (AU).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **GOLDSCHMIED, Felix** [AU/AU]; 58 Gascoyne Street, Launceston, Tasmania 7250 (AU).

(74) Agent: **PHILLIPS ORMONDE & FITZPATRICK**; 367 Collins Street, Melbourne, Victoria 3000 (AU).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

(54) Title: ORTHODONTIC APPLIANCE AND PIN



(57) Abstract: An orthodontic appliance including a bracket having a substantially flat base (15) for engaging a tooth and a securing member (23) having a terminal aspect, and a pin (1) having an appendage (5) having an active surface (3) wherein the base and the securing member form a channel adapted to receive the pin to secure the pin in a position to form a slot between the terminal aspect of the securing member and the active surface of the appendage of the pin, said pin having longitudinal movement within the channel, wherein said movement enable the dimensions of the slot formed between the terminal aspect of the securing member and the active surface (32) of the appendage of the pin to be variable.



WO 02/36037 A1