

Patent Application

of

Bryan Lee Hyncek,

Jarret Weis,

5 Stephen Reiger Myers

and

David Law

for

TITLE: One Piece Co-formed Exterior Hard Shell Case with an Elastomeric Liner for Mobile

10 Electronic Devices

FEDERALLY SPONSORED RESEARCH: Not Applicable

SEQUENCE LISTING OR PROGRAM: Not Applicable

CROSS REFERENCE TO RELATED APPLICATIONS: Not Applicable

15 TECHNICAL FIELD OF THE INVENTION

The present invention relates generally to handheld mobile electronic devices, such as a personal digital assistant, cellular telephone, laptop computers or portable digital media player. More specifically the present invention relates to a multiple-component protective

20 case for mobile electronic devices.

BACKGROUND OF THE INVENTION

There are many cases for handheld electronic devices. They fall into four main categories: Elastomeric/Rubber skins, hard plastic shells, cut and sew materials and combinations of these. In general the elastomeric cases are a single skin which, because of the flexible nature of the material, can easily be stretched over the device and then once installed conform closely to the shape of the device. The rubbery material can provide very good shock resistance. The downside of these types of cases is that the elastomeric material has a high surface friction coefficient. This makes this type of case difficult to place in and remove from pockets and other tight places. What is needed is a device that offers the very good shock resistance of an elastomeric case without the high surface friction coefficient making it more convenience for use.

Hard plastic shells normally are manufactured as more than one piece to allow the device to slide into the case before being closed in with a secondary piece. Additionally they will often have a liner of elastomeric material, which helps to cushion the device. This can be co-molded, permanently attached or floating with the assembly. Cut and Sew cases are normally made from flat stock material, which is cut into patterns and then sewn into a shape that the device can slide into. The device is then held in place, by friction or a strap of some form. The downside to these devices is that it can be difficult to attached a device to a rigid case, or where a case has a secondary piece for securing a device, it can add bulk to the combination of the device and case, making it impractical. Additionally, the manufacture of cases which are required to be cut and sewn together greatly increases cost. What is needed is a case that combines both hard shell cases and elastomeric materials that is easy to produce and requires minimal material in its production.

SUMMARY OF THE INVENTION

The present invention is an improvement over the existing cases because it combines the best features of both hard cases and the elastomeric cases while being only a single part, which is particularly useful from a consumer viewpoint. The present invention provides a hard protective exterior shell. This hard protective exterior shell allows the device maximum protection from impacts with sharp objects. The hard protective exterior shell mimics the finish of existing phones, MP3/4 players, and other mobile electronic devices. Many users like the feel of the original phone and would like to maintain that feel but still want protection for their device. The hard protective exterior shell of the present invention has a low coefficient of friction. This allows the device to easily be slipped in and out of pockets easily without becoming attached or without great resistance to clothing materials. A major complaint from current elastomeric case users.

The case taught by the present invention has an interior elastomeric portion that provides shock protection for the device from dropping, falls, or other impacts. The interior elastomeric portion also ensures the device and the case fit together with no gaps as the case is a single piece assembly. The case has a very solid connection to the phone and feels extremely high quality and lightweight.

What makes this case different is the geometry and manufacturing of the case. The exterior hard shell part is formed to fit the device closely with a small offset from the devices surface. The exterior hard shell raps around the edges of the device it is formed for. To allow the shell to be able to be mounted on the device the corners of the hard shell are cut open. This allows each sidewall to flex away when a device is inserted and snap back once it is in

place. The unique aspect of this case is that the elastomeric material is formed in addition to the exterior hard shell on the interior of the exterior hard shell. The elastomeric material fills in the gaps created at the corners of the exterior hard shell to allow the hard shell to flex for mounting. The elastomeric material is provided in this location because it has much greater
5 inherent flexibility than the plastic or metal of the exterior hard shell and it stretches sufficiently to allow the sidewalls of the exterior hard shell to still flex away on mounting. This creates a one-piece case that wraps around a phone or other mobile electronic device even on corners and prevents dirt and fluids from entering wherever possible. The elastomeric liner also can be formed over the buttons on the phone wherein a user simply presses the
10 elastomeric liner corresponding to the portion of the mobile electronic device input that is desired.

BRIEF DESCRIPTION OF THE DRAWINGS

15 The accompanying drawings, which are incorporated herein and form a part of the specification, illustrate the present invention and, together with the description, further serve to explain the principles of the invention and to enable a person skilled in the pertinent art to make and use the invention.

Fig. 1 is a perspective view of a handheld device protective case depicting the external
20 hard shell layer with cut corners and inner elastomeric layer of the protective carrying case where it fills in the cut corners of the external hard shell layer;

Figs. 2a and 2b are sectional views of the protective case of the present invention showing the detent created by the inner elastomeric layer for securing a device in the case;

Fig. 3 is a top orthogonal view of a handheld device protective case depicting the external hard shell layer with cut corners and inner elastomeric layer of the protective carrying case where is fills in the cut corners of the external hard shell layer and an additional large elastomeric overhand for securing a device;

5 Fig. 4 is sectional view of the protective case of the present invention showing the large elastomeric overhand for securing a device;

Fig. 5 is a perspective view of the protective case of the present invention before a device is secured therein;

Fig. 6 is a perspective view of the protective case attached to a sample device showing
10 the detent created by the inner elastomeric layer for securing a device in the case; and

Figs. 7a and 7b are perspective views of the present invention depicting the external hard shell layer with cut corners and inner elastomeric layer of the protective carrying case is a resting, securing position and in an expanded, device insertion position.

15 DETAILED DESCRIPTION OF THE INVENTION

In the following detailed description of the invention of exemplary embodiments of the invention, reference is made to the accompanying drawings (where like numbers represent like elements), which form a part hereof, and in which is shown by way of illustration specific
20 exemplary embodiments in which the invention may be practiced. These embodiments are described in sufficient detail to enable those skilled in the art to practice the invention, but other embodiments may be utilized and logical, mechanical, electrical, and other changes may be made without departing from the scope of the present invention. The following detailed

description is therefore, not to be taken in a limiting sense, and the scope of the present invention is defined only by the appended claims.

The invention will now be described with reference to Fig. 1, which is a perspective view of the protective case 10 depicting the outer layer of the protective case 11, comprising
5 two separate layers, an first external hard shell layer 12 and a second interior elastomeric layer 13. The first external hard shell layer 12 and a second interior elastomeric layer 13 are combined to independently attach to a handheld device 19 and incorporate at least one viewing window 14, input/output access ports 15, 16, and 17, and molded elastomeric covers over device buttons, accessible through holes in the hard shell 18 and 26. This hard protective
10 exterior shell 12 allows the device maximum protection from impacts with sharp objects. The external hard shell layer 12 mimics the finish of existing phones, MP3/4 players, and other mobile electronic devices. Many users like the feel of the original phone and would like to maintain that feel but still want protection for their device 19. The external hard shell layer 12 of the present invention has a low coefficient of friction. This allows the device to easily be
15 slipped in and out of pockets easily without becoming attached or without great resistance to clothing materials.

With further reference to Fig. 1, the external hard shell layer 12 is attached to the second interior elastomeric layer 13. The external hard shell layer 12 and the interior elastomeric layer 13 may be attached in several ways, such as glue, chemical bonding,
20 heating, heat treated chemicals or any other means known in the art which permanently attach the external hard shell layer 12 to the interior elastomeric layer 13. The interior elastomeric portion 13 provides shock protection for the device from dropping, falls, or other impacts. The interior elastomeric portion 13 also ensures the device 19 and the protective case 10 fit

together with no gaps as the protective case 10 is a single piece assembly. The protective case 10 has a very solid connection to a device 19 and feels extremely high quality and lightweight.

Depending on manufacturing methods other materials made be used to replace the
5 hard plastic used by the external hard shell layer 12 in a preferred embodiment of the present invention. For example, if it was desired to make a metal/elastomeric combo for the protective case 10 without overhangs in the hard material, in this example metal, a simple bending process could be considered for the metal manufacturing. An over molded interior elastomeric layer 13 would provide the undercuts to secure a device. The metal or hard
10 material would then simply provide a framework for the softer material interior layer and also provide the elastic stiffness to allow the device to be held in the opening. The undercut would be formed in the elastomeric material but the flexing to allow a device to be inserted into the protective case would come from the harder material, and again, cutting away the corners of the case allows the sides to easily flex.

15 Figs. 2a and 6 are sectional views of the protective case 10 of the present invention showing the detent 20 created by the inner elastomeric layer 13 for securing a device 19 in the case. The protective case 10 is fitted to clasp onto a device 19, and incorporates a detent 20 to ensure a snug and secure fit.

In an alternative embodiment as shown in Fig. 2b and 4, an additional large
20 elastomeric overhang 21 for securing a device 19 may be included in the protective case 10. This illustrates a possible alternative embodiment where rather than having an undercut in the external hard shell layer 13 and its corresponding sides of the protective case 10, the inner elastomeric layer 13 forms features that would secure the protective case to a device 19.

These features could be detents 20 as described along the side or top and bottom of the external hard shell layer 12 or it could be a large area like illustrated in Figs. 2b and 4 where an additional large elastomeric overhang 21 for securing a device 19 may be included in the protective case 10 so that a device would be slipped under and secured thereby with some
5 form of undercut on the opposite end whether molded into the external hard shell layer 12 or the inner elastomeric layer 13.

As shown in Figs. 3 and 5, the external hard shell layer 12 defines a fitted cavity 22 fitted to clasp onto a device 19 and incorporates a detent 20 to ensure a snug and secure fit. The handheld device 19 protective case depicts the external hard shell layer 12 with cut
10 corners 23 and inner elastomeric layer 13 of the protective carrying case where the inner elastomeric layer 13 fills in the cut corners 23 of the external hard shell layer 12.

What makes this case different is the geometry and manufacturing of the case. The external hard shell layer 12 is formed to fit a device 19 closely with a small offset from the devices surface. The external hard shell layer 12 raps around the edges of a device 19 it is
15 formed for. To allow the external hard shell layer 12 to be able to be mounted on a device 19 the corners 23 of the external hard shell layer 12 are cut open. This allows each sidewall of the external hard shell layer 12 to flex away when a device 19 is inserted and snap back once it is in place. The unique aspect of the protective case 10 is that an inner elastomeric layer 13 is formed in addition to the external hard shell layer 12 on the interior of the external hard
20 shell layer 12. The inner elastomeric layer 13 fills in the gaps created at the corners 23 of the external hard shell layer 12 to allow the external hard shell layer 12 to flex during mounting as shown in Figs. 7a and 7b.

The inner elastomeric layer 13 is provided in this location because it has much greater inherent flexibility than the plastic or metal of the external hard shell layer 12 and it stretches sufficiently to allow the sidewalls of the external hard shell layer 12 to still flex away on mounting as shown in Figs. 7a and 7b. This creates a one-piece protective case 10 that wraps
5 around a device even on corners and prevents dirt and fluids from entering wherever possible. The inner elastomeric layer 13 also can be formed over the buttons on a device 19 wherein a user simply presses the exposed inner elastomeric layer 13 corresponding to the portion of the mobile electronic device input that is desired as illustrated by the button 18 and 26 on Fig. 1.

Figs. 7a and 7b are perspective views of the present invention depicting the external
10 hard shell layer 12 with cut corners 23 and inner elastomeric layer 13 of the protective carrying case 10 is a resting, securing position 24 and in an expanded, device insertion position 25.

It is appreciated that the optimum dimensional relationships for the parts of the invention, to include variation in size, materials, shape, form, function, and manner of
15 operation, assembly and use, are deemed readily apparent and obvious to one of ordinary skill in the art, and all equivalent relationships to those illustrated in the drawings and described in the above description are intended to be encompassed by the present invention.

Furthermore, other areas of art may benefit from this method and adjustments to the design are anticipated. Thus, the scope of the invention should be determined by the
20 appended claims and their legal equivalents, rather than by the examples given.

CLAIMS

The embodiments of the invention in which an exclusive property or privilege is claimed are defined as follows:

5

1. A protective case for a handheld mobile electronic device comprising:

a first portion creating an exterior hard shell, including a fitted cavity formed therein for mounting a handheld mobile electronic device to the protective case;

10 a second portion, permanently affixed to the fitted cavity formed therein of the first portion;

said first and second portions made up of:

said first portion comprising a protective outer layer composed of a hardened plastic; and

15 said second portion comprising an elastomeric liner formed and permanently affixed on the interior of the exterior hard shell first portion.

2. The device as described in claim 1 wherein, the second portion further comprises a detent for mounting a handheld mobile electronic device to the protective case.

20 3. The device as described in claim 2 wherein, said detent on the second portion runs the length of the fitted cavity formed by the first portion.

4. The device as described in claim 1 wherein, the second portion further comprises large elastomeric overhang on one side of the fitted cavity for securing a handheld mobile electronic device to the protective case.

5 5. The device as described in claim 1 wherein, the second portion further comprises large elastomeric overhang on one or more sides of the fitted cavity for securing a handheld mobile electronic device to the protective case.

6. The device as described in claim 1 wherein,
10 the corners of the hard shell first portion are cut open; and
the elastomeric material of the second portion fills in the gaps created at the corners of the exterior hard shell first portion where it was cut open.

7. The device as described in claim 1 wherein, the exterior hard shell first portion is formed
15 to fit the device closely with a small offset from the devices surface.

8. The device as described in claim 1 wherein, the exterior hard shell first portion raps around the edges of the device.

20 9. The device as described in claim 1 wherein, the protective case has a window for providing exposure to at least a portion of one surface of the associated segment of the handheld mobile electronic device.

10. The device as described in claim 1 wherein, said protective case has at least one access port to allow access to functions found on the handheld mobile electronic device.

11. A protective case for a handheld device having two layers comprising:

5 a first hardened formed plastic or metal layer designed so as to cover and fit sufficiently tightly to the exterior of a handheld mobile electronic device so as to hold said handheld mobile electronic device in place covering the handheld mobile electronic device and to provide exterior protection and styling;

 the corners of the first layer are cut open;

10 a second flexible material layer, permanently affixed to said first hardened molded plastic layer so as to cover the interior of said first hardened molded plastic layer and to provide interior protection for said first layer; and

 the elastomeric material of the second layer fills in the gaps created at the corners of the exterior hard shell first portion where it was cut open.

15

12. The device as described in claim 11 wherein, the second layer further comprises a detent for mounting a handheld mobile electronic device to the protective case.

13. The device as described in claim 12 wherein, said detent on the second layer runs the

20 length of the fitted cavity formed by the first portion.

14. The device as described in claim 11 wherein, the second layer further comprises large elastomeric overhang on one side of the fitted cavity for securing a handheld mobile electronic device to the protective case.

5 15. The device as described in claim 11 wherein, the second layer further comprises large elastomeric overhang on one or more sides of the fitted cavity for securing a handheld mobile electronic device to the protective case.

10 16. The protective case as described in claim 11 wherein, the exterior hard shell first layer is formed to fit the device closely with a small offset from the devices surface.

17. The protective case as described in claim 11 wherein, the exterior layer portion raps around the edges of a device.

15 18. The protective case as described in claim 11, further comprising a window for providing exposure to at least a portion of one surface of a handheld mobile electronic device.

19. The protective case as described in claim 11, further comprising at least one access port to allow access to functions found on the handheld mobile electronic device.

20