

POLARIZER MODULE AND OPERATION METHOD THEREOF

TECHNICAL FIELD

[0001] The invention relates to an optical module and an operation method thereof, and more particularly, to a polarizer module and an operation method thereof.

5 BACKGROUND

[0002] In general, a liquid crystal display can be generally divided into a transmissive liquid crystal display, a reflective liquid crystal display, and a transflective liquid crystal display.

With the increasing use of displays, transparent displays have been gradually developed. A transparent display means that the display itself has a certain degree of transparency and can

10 clearly display the views behind a display panel. The transparent display is suitable for a variety of applications such as building windows, car windows and shop windows, and has the potential for future development as an information display in addition to the original transparent display function, which has attracted much attention from the market.

[0003] However, the transparency of transparent displays can be used to develop applications
15 that cannot be done by existing non-transparent displays, but with relative limitations. For instance, although the transparent display technology may achieve the transparent display function, but it is unable to switch between a transparent mode and a mirror mode; and although the transparent display technology of applying a polymer dispersed liquid crystal (PDLC) may achieve an anti-peep effect, but it is poor in shading and heat insulation.

20

SUMMARY

[0004] The invention provides a polarizer module and an operation method thereof that can

switch between the mirror mode and the transparent mode.

[0005] An embodiment of the invention provides a polarizer module, which includes a bifacial reflective polarizer, a first liquid crystal layer, a second liquid crystal layer, a first polarizer, and a second polarizer. The bifacial reflective polarizer has a first surface and a second surface opposite to each other. The first liquid crystal layer and the second liquid crystal layer are disposed on the first surface and the second surface respectively. The first polarizer and the second polarizer are disposed on the first liquid crystal layer and the second liquid crystal layer respectively.

[0006] An embodiment of the invention provides an operation method of polarizer module, which includes steps of: providing the polarizer module described above; and enabling the polarizer module to perform a dual mirror mode, a single mirror mode or a transparent mode. When light is reflected by the bifacial reflective polarizer and pass through the first polarizer and the second polarizer, respectively, the polarizer module is in the dual mirror mode. When the light is reflected by the bifacial reflective polarizer and pass through only one of the first polarizer and the second polarizer, the polarizer module is in the single mirror mode. When the light transmits through the bifacial reflective polarizer, the polarizer module is in the transparent mode.

[0007] Based on the above, due to the polarizer module of the invention includes the bifacial reflective polarizer, the first liquid crystal layer, the second liquid crystal layer, the first polarizer and the second polarizer configured as above, so the polarizer module of the invention can switch between the mirror mode (e.g. the dual mirror mode or the single mirror mode) and the transparent mode by operating the first liquid crystal layer and/or the second liquid crystal layer.

[0008] To make the above features and advantages of the disclosure more comprehensible, several embodiments accompanied with drawings are described in detail as follows.

BRIEF DESCRIPTION OF THE DRAWINGS

[0009] The accompanying drawings are included to provide a further understanding of the disclosure, and are incorporated in and constitute a part of this specification. The drawings illustrate embodiments of the disclosure and, together with the description, serve to explain the principles of the disclosure.

[0010] FIG. 1 is a cross-sectional view of the polarizer module in an embodiment of the invention.

[0011] FIG. 2A to FIG. 2C are schematic diagrams illustrating how the polarizer module switches between the mirror mode and the transparent mode by operating the first liquid crystal layer and/or the second liquid crystal layer in an embodiment of the invention.

[0012] FIG. 3A to FIG. 3D are schematic diagrams illustrating how the polarizer module switches between the mirror mode and the transparent mode by operating the first liquid crystal layer and/or the second liquid crystal layer in another embodiment of the invention.

[0013] FIG. 4A to FIG. 4C are schematic diagrams illustrating how the polarizer module switches between the mirror mode and the transparent mode by operating the first liquid crystal layer and/or the second liquid crystal layer in yet another embodiment of the invention.

[0014] FIG. 5 is a cross-sectional view of the polarizer module in another embodiment of the invention.

[0015] FIG. 6 is a cross-sectional view of the polarizer module in yet another embodiment of the invention.

[0016] FIG. 7 is a cross-sectional view of the polarizer module in still another embodiment of

the invention.

[0017] FIG. 8 is a cross-sectional view of the polarizer module in still yet another embodiment of the invention.

5

DETAILED DESCRIPTION

[0018] In the following detailed description, for purposes of explanation, numerous specific details are set forth in order to provide a thorough understanding of the disclosed embodiments.

It will be apparent, however, that one or more embodiments may be practiced without these specific details. In other instances, well-known structures and devices are schematically shown

10 in order to simplify the drawing.

[0019] The invention will be described more comprehensively below with reference to the drawings for the embodiments. However, the invention may also be implemented in different forms rather than being limited by the embodiments described in the invention. Thicknesses of layer and region in the drawings are enlarged for clarity. The same reference numbers are used

15 in the drawings and the description to indicate the same or like parts, which are not repeated in the following embodiments. Further, the language used to describe the directions such as up, down, left, right, front, back or the like in the reference drawings is regarded in an illustrative rather than in a restrictive sense. Thus, the language used to describe the directions is not intended to limit the scope of the invention.

20 **[0020]** FIG. 1 is a cross-sectional view of the polarizer module in an embodiment of the invention. FIG. 2A to FIG. 2C are schematic diagrams illustrating how the polarizer module

switches between the mirror mode and the transparent mode by operating the first liquid crystal layer and/or the second liquid crystal layer in an embodiment of the invention. FIG. 3A to FIG. 3D are schematic diagrams illustrating how the polarizer module switches between the mirror mode and the transparent mode by operating the first liquid crystal layer and/or the second liquid crystal layer in another embodiment of the invention. FIG. 4A to FIG. 4C are schematic diagrams illustrating how the polarizer module switches between the mirror mode and the transparent mode by operating the first liquid crystal layer and/or the second liquid crystal layer in yet another embodiment of the invention.

[0021] With reference to FIG. 1, a polarizer module 100 includes a bifacial reflective polarizer RP, a first liquid crystal layer LC1, a second liquid crystal layer LC2, a first polarizer P1, and a second polarizer P2. In this embodiment, due to the polarizer module 100 may switch between the mirror mode (including the dual mirror mode and the single mirror mode) and the transparent mode, so it is applicable to a transparent display, a smart window or a smart wall to further improve the applicability of the polarizer module 100.

[0022] The bifacial reflective polarizer RP has a first surface S1 and a second surface S2 opposite to each other. For instance, as shown in FIG. 1, the first surface S1 may be a lower surface of the bifacial reflective polarizer RP; and the second surface S2 may be an upper surface of the bifacial reflective polarizer RP, but the invention is not limited thereto. In this embodiment, the bifacial reflective polarizer RP may have a reflection axis for reflecting a polarized light parallel to the reflection axis. For instance, as shown in FIG. 2A, when polarization directions of light F1 and light F2 incident to opposite sides of the bifacial reflective

polarizer RP are parallel to the reflection axis of the bifacial reflective polarizer RP, the light F1 and light F2 will be reflected by the bifacial reflective polarizer RP. The bifacial reflective polarizer RP may have a transmission axis for allowing a polarized light parallel to the transmission axis to transmit through the bifacial reflective polarizer RP. For instance, as shown in FIG. 2C, when the polarization directions of the light F1 and light F2 incident to the opposite sides of the bifacial reflective polarizer RP are parallel to the transmission axis of the bifacial reflective polarizer RP, the light F1 and light F2 will pass through the bifacial reflective polarizer RP. In this embodiment, the reflection axis and the transmission axis of the bifacial reflective polarizer RP may be orthogonal to each other. In other words, when the polarization directions of the light F1 and light F2 are perpendicular to the reflection axis of the bifacial reflective polarizer RP, the light F1 and light F2 can transmit through the bifacial reflective polarizer RP. In this embodiment, the bifacial reflective polarizer RP may be a reflective polarizer mirror (RPM) or a wire grid polarizer (WGP).

[0023] The first liquid crystal layer LC1 and the second liquid crystal layer LC2 are disposed on the first surface S1 and the second surface S2 of the bifacial reflective polarizer RP respectively. In some embodiments, the first liquid crystal layer LC1 and the second liquid crystal layer LC2 may include in-plane-switching liquid crystal molecules that can be rotated or switched by a horizontal electric field or vertical switching liquid crystal molecules that can be rotated or switched by a vertical electric field, but the invention is not limited thereto. In other embodiments, the first liquid crystal layer LC1 and the second liquid crystal layer LC2 may include polymer dispersed liquid crystals (PDLC) or other suitable liquid crystals.

[0024] The first polarizer P1 and the second polarizer P2 are disposed on the first liquid crystal layer LC1 and the second liquid crystal layer LC2 respectively. In this embodiment, each of the first polarizer P1 and the second polarizer P2 may have an absorption axis for absorbing a polarized light parallel to the absorption axis. Each of the first polarizer P1 and the second polarizer P2 may have a transmission axis for allowing a polarized light parallel to the transmission axis to transmit through the first polarizer P1 and the second polarizer P2. In this embodiment, the absorption axis and the transmission axis of each of the first polarizer P1 and the second polarizer P2 may be orthogonal to each other. In other words, when the polarization directions of the light F1 and light F2 are perpendicular to the absorption axis of the first polarizer P1 or the second polarizer P2, the light F1 and light F2 can transmit through the first polarizer P1 or the second polarizer P2.

[0025] Based on the above, due to the polarizer module 100 includes the bifacial reflective polarizer RP, the first liquid crystal layer LC1, the second liquid crystal layer LC2, the first polarizer P1 and the second polarizer P2 configured as above, so the polarizer module 100 can switch between the mirror mode and the transparent mode by operating the first liquid crystal layer LC1 and/or the second liquid crystal layer LC2.

[0026] An operation method of the polarizer module 100 may include steps of: providing the polarizer module 100 described above; and enabling the polarizer module 100 to perform the dual mirror mode, the single mirror mode or the transparent mode.

[0027] In the following paragraphs, FIG. 2A to FIG. 2C, FIG. 3A to FIG. 3D and FIG. 4A to FIG. 4C will be used as examples to describe how the polarizer module switches between the

mirror mode (including the dual mirror mode and the single mirror mode) and the transparent mode by operating the first liquid crystal layer LC1 and/or the second liquid crystal layer LC2 according to different embodiments of the invention. In FIG. 2A to FIG. 2C, FIG. 3A to FIG. 3D and FIG. 4A to FIG. 4C, the first polarizer P1 and the second polarizer P2 are not illustrated so the examples regarding whether the light F1 and light F2 will transmit through the bifacial reflective polarizer RP or will be reflected by the bifacial reflective polarizer RP can be clearly expressed.

[0028] When the polarizer modules 100, 200 and 300 are in the dual mirror mode, the light F1 and the light F2 may be reflected by the bifacial reflective polarizer RP, so both sides of the polarizer modules 100, 200 and 300 are in a mirror state.

[0029] When the polarizer modules 100, 200, 300 are in the single mirror mode, one of the light F1 and the light F2 may be reflected by the bifacial reflective polarizer RP, so that one side of the polarizer modules 100, 200 and 300 is in the mirror state; and another one of the light F1 and the light F2 may pass through the bifacial reflective polarizer RP and may be absorbed by the first polarizer P1 or the second polarizer P2, so that another one side of the polarizer modules 100, 200 and 300 is in a black state.

[0030] When the polarizer modules 100, 200 and 300 are in the transparent mode, the light F1 may pass through the bifacial reflective polarizer RP and the second polarizer P2, so that one side of the polarizer modules 100, 200 and 300 is in a transparent state; and the light F2 may pass through the bifacial reflective polarizer RP and the first polarizer P1, so that another side of the polarizer modules 100, 200 and 300 is also in the transparent state.

[0031] In the following paragraphs, FIG. 2A to FIG. 2C are used to illustrate how the polarizer module 100 in an embodiment of the invention switches between the mirror mode and the transparent mode by operating the first liquid crystal layer LC1 and/or the second liquid crystal layer LC2. FIG. 2A to FIG. 2C illustrate the examples of enabling the polarizer module 100 to perform the dual mirror mode, the single mirror mode, and the transparent mode, respectively. In this embodiment, a reflection axis of the bifacial reflective polarizer RP is perpendicular to an absorption axis of the first polarizer P1 and an absorption axis of the second polarizer P2.

[0032] Referring to FIG. 2A, when the reflection axis of the bifacial reflective polarizer RP is perpendicular to the absorption axis of the first polarizer P1 and the absorption axis of the second polarizer P2, the dual mirror mode may be performed by not applying voltage to the first liquid crystal layer LC1 and the second liquid crystal layer LC2. For instance, a polarization direction of a polarized light passed through the first polarizer P1 and the first liquid crystal layer LC1 is parallel to the reflection axis of the bifacial reflective polarizer RP, therefore, the light F1 may be reflected by the bifacial reflective polarizer RP so that one side of the polarizer module 100 is in the mirror state. Similarly, a polarization direction of a polarized light passed through the second polarizer P2 is parallel to the reflection axis of the bifacial reflective polarizer RP, therefore, the light F2 may be reflected by the bifacial reflective polarizer RP so that another side of the polarizer module 100 is also in the mirror state.

[0033] Referring to FIG. 2B, when the reflection axis of the bifacial reflective polarizer RP is perpendicular to the absorption axis of the first polarizer P1 and the absorption axis of the second polarizer P2, the single mirror mode may be performed by applying voltage to only one

of the first liquid crystal layer LC1 and the second liquid crystal layer LC2. For instance, voltage can be applied to the second liquid crystal layer LC2 while no voltage is applied to the first liquid crystal layer LC1. In this way, a polarization direction of a polarized light passed through the second polarizer P2 and the second liquid crystal layer LC2 is perpendicular to the reflection axis of the bifacial reflective polarizer RP and parallel to the absorption axis of the first polarizer P1, therefore, the light F2 may transmit through the bifacial reflective polarizer RP and may be absorbed by the first polarizer P1, so that one side of the polarizer module 100 is in the black state (as shown by an arrow F2'). On the other hand, a polarization direction of a polarized light passed through the first polarizer P1 and the first liquid crystal layer LC1 is parallel to the reflection axis of the bifacial reflective polarizer RP, therefore, the light F1 may be reflected by the bifacial reflective polarizer RP so that another side of the polarizer module 100 is in the mirror state.

[0034] Referring to FIG. 2C, when the reflection axis of the bifacial reflective polarizer RP is perpendicular to the absorption axis of the first polarizer P1 and the absorption axis of the second polarizer P2, the transparent mode may be performed by simultaneously applying voltage to the first liquid crystal layer LC1 and the second liquid crystal layer LC2. For instance, a polarization direction of a polarized light passed through the first polarizer P1 and the first liquid crystal layer LC1 is perpendicular to the reflection axis of the bifacial reflective polarizer RP, therefore, the light may pass through the bifacial reflective polarizer RP. When the polarized light passed through the bifacial reflective polarizer RP further passes through the second liquid crystal layer LC2, the polarization direction of the polarized light is perpendicular to the

absorption axis of the second polarizer P2, therefore, the light may pass through the second polarizer P2 so that one side of the polarizer module 100 is in the transparent state. Similarly, a polarization direction of a polarized light passed through the second polarizer P2 and the second liquid crystal layer LC2 is perpendicular to the reflection axis of the bifacial reflective polarizer RP, therefore, the light may pass through the bifacial reflective polarizer RP. When the polarized light passed through the bifacial reflective polarizer RP further passes through the first liquid crystal layer LC1, the polarization direction of the polarized light is perpendicular to the absorption axis of the first polarizer P1, therefore, the light may pass through the first polarizer P1 so that another side of the polarizer module 100 is also in the transparent state.

[0035] In the following paragraphs, FIG. 3A to FIG. 3D are used to illustrate how a polarizer module 200 in another embodiment switches between the mirror mode and the transparent mode by operating the first liquid crystal layer LC1 and/or the second liquid crystal layer LC2. The polarizer module 200 is similar to the polarizer module 100 except that the reflection axis of the bifacial reflective polarizer RP in the polarizer module 200 is perpendicular to an absorption axis of one of the first polarizer P1 and the second polarizer P2. Therefore, the same or similar elements are given the same or similar reference numerals, and the connection relationship, the materials, and the processes of the remaining members have been described in detail in the foregoing paragraphs, which are not be repeated hereinafter.

[0036] FIG. 3A and FIG. 3D illustrate the examples of enabling the polarizer module 200 to perform the single mirror mode; FIG. 3B illustrates the example of enabling the polarizer module 200 to perform the dual mirror mode; FIG. 3C illustrates the example of enabling the

polarizer module 200 to perform the transparent mode. In this embodiment, the reflection axis of the bifacial reflective polarizer RP is perpendicular to the absorption axis of one of the first polarizer P1 and the second polarizer P2.

[0037] Referring to FIG. 3A and FIG. 3D together, when the reflection axis of the bifacial reflective polarizer RP is perpendicular to the absorption axis of one of the first polarizer P1 and the second polarizer P2, the single mirror mode may be performed by simultaneously applying voltage to the first liquid crystal layer LC1 and the second liquid crystal layer LC2 (as shown by FIG. 3D) or not applying voltage to the first liquid crystal layer LC1 and the second liquid crystal layer LC2 (as shown by FIG. 3A). In this embodiment, the reflection axis of the bifacial reflective polarizer RP may be perpendicular to the absorption axis of the first polarizer P1 and parallel to the absorption axis of the second polarizer P2, but the invention is not limited thereto. In other embodiments, the reflection axis of the bifacial reflective polarizer RP may be parallel to the absorption axis of the first polarizer P1 and perpendicular to the absorption axis of the second polarizer P2.

[0038] Referring to FIG. 3A, when the reflection axis of the bifacial reflective polarizer RP is perpendicular to the absorption axis of the first polarizer P1 and parallel to the absorption axis of the second polarizer P2, the single mirror mode may be performed by not applying voltage to the first liquid crystal layer LC1 and the second liquid crystal layer LC2. For instance, a polarization direction of a polarized light passed through the first polarizer P1 and the first liquid crystal layer LC1 is parallel to the reflection axis of the bifacial reflective polarizer RP, therefore, the light F1 may be reflected by the bifacial reflective polarizer RP so that one side of

the polarizer module 200 is in the mirror state. On the other hand, a polarization direction of a polarized light passed through the second polarizer P2 and the second liquid crystal layer LC2 is perpendicular to the reflection axis of the bifacial reflective polarizer RP and parallel to the absorption axis of the first polarizer P1, therefore, the light F2 may transmit through the bifacial reflective polarizer RP and may be absorbed by the first polarizer P1 so that another side of the polarizer module 200 is in the black state (as shown by the arrow F2').

[0039] Referring to FIG. 3D, when the reflection axis of the bifacial reflective polarizer RP is perpendicular to the absorption axis of the first polarizer P1 and parallel to the absorption axis of the second polarizer P2, the single mirror mode may be performed by simultaneously applying voltage to the first liquid crystal layer LC1 and the second liquid crystal layer LC2. For instance, a polarization direction of a polarized light passed through the first polarizer P1 and the first liquid crystal layer LC1 is perpendicular to the reflection axis of the bifacial reflective polarizer RP and parallel to the absorption axis of the second polarizer P2, therefore, the light F1 may transmit through the bifacial reflective polarizer RP and may be absorbed by the second polarizer P2 so that one side of the polarizer module 200 is in the black state (as shown by an arrow F1'). On the other hand, a polarization direction of a polarized light passed through the second polarizer P2 and the second liquid crystal layer LC2 is parallel to the reflection axis of the bifacial reflective polarizer RP, therefore, the light F2 may be reflected by the bifacial reflective polarizer RP so that another side of the polarizer module 200 is in the mirror state.

[0040] Referring to FIG. 3B and FIG. 3C together, when the reflection axis of the bifacial reflective polarizer RP is perpendicular to the absorption axis of one of the first polarizer P1 and

the second polarizer P2, the dual mirror mode (as shown in FIG. 3B) or the transparent mode (as shown in FIG. 3C) may be performed by applying voltage to only one of the first liquid crystal layer LC1 and the second liquid crystal layer LC2. In this embodiment, the reflection axis of the bifacial reflective polarizer RP may be perpendicular to the absorption axis of the first polarizer P1 and parallel to the absorption axis of the second polarizer P2. In other embodiments, the reflection axis of the bifacial reflective polarizer RP may be parallel to the absorption axis of the first polarizer P1 and perpendicular to the absorption axis of the second polarizer P2.

[0041] Referring to FIG. 3B, when the reflection axis of the bifacial reflective polarizer RP is perpendicular to the absorption axis of the first polarizer P1 and parallel to the absorption axis of the second polarizer P2, the dual mirror mode may be performed by applying voltage to the second liquid crystal layer LC2 and not applying voltage to the first liquid crystal layer LC1. For instance, a polarization direction of a polarized light passed through the first polarizer P1 and the first liquid crystal layer LC1 is parallel to the reflection axis of the bifacial reflective polarizer RP, therefore, the light F1 may be reflected by the bifacial reflective polarizer RP so that one side of the polarizer module 200 is in the mirror state. On the other hand, a polarization direction of a polarized light passed through the second polarizer P2 and the second liquid crystal layer LC2 is parallel to the reflection axis of the bifacial reflective polarizer RP, the light F2 may be reflected by the bifacial reflective polarizer RP so that another side of the polarizer module 200 is also in the mirror state.

[0042] Referring to FIG. 3C, when the reflection axis of the bifacial reflective polarizer RP is

perpendicular to the absorption axis of the first polarizer P1 and parallel to the absorption axis of the second polarizer P2, the transparent mode may be performed by applying voltage to the first liquid crystal layer LC1 and not applying voltage to the second liquid crystal layer LC2. For instance, a polarization direction of a polarized light passed through the first polarizer P1 and the first liquid crystal layer LC1 is perpendicular to the reflection axis of the bifacial reflective polarizer RP, therefore, the light may pass through the bifacial reflective polarizer RP. When the polarized light passed through the bifacial reflective polarizer RP further passes through the second liquid crystal layer LC2, the polarization direction of the polarized light is perpendicular to the absorption axis of the second polarizer P2, therefore, the light may pass through the second polarizer P2 so that one side of the polarizer module 100 is in the transparent state. On the other hand, a polarization direction of a polarized light passed through the second polarizer P2 and the second liquid crystal layer LC2 is perpendicular to the reflection axis of the bifacial reflective polarizer RP, therefore, the light may pass through the bifacial reflective polarizer RP. When the polarized light passed through the bifacial reflective polarizer RP further passes through the first liquid crystal layer LC1, the polarization direction of the polarized light is perpendicular to the absorption axis of the first polarizer P1, therefore, the light may pass through the first polarizer P1 so that another side of the polarizer module 200 is in the transparent state.

[0043] In the following paragraphs, FIG. 4A to FIG. 4C are used to illustrate how a polarizer module 300 in yet another embodiment of the invention switches between the mirror mode and the transparent mode by operating the first liquid crystal layer and/or the second liquid crystal

layer. The polarizer module 300 is similar to the polarizer module 100 except that the reflection axis of the bifacial reflective polarizer RP in the polarizer module 300 is parallel to the absorption axes of the first polarizer P1 and the second polarizer P2. Therefore, the same or similar elements are given the same or similar reference numerals, and the connection relationship, the materials, and the processes of the remaining members have been described in detail in the foregoing paragraphs, which are not be repeated hereinafter.

[0044] In this embodiment, FIG. 4A to FIG. 4C illustrate the examples of enabling the polarizer module 300 to perform the dual mirror mode, the single mirror mode, and the transparent mode respectively. In this embodiment, the reflection axis of the bifacial reflective polarizer RP is parallel to the absorption axis of the first polarizer P1 and the absorption axis of the second polarizer P2.

[0045] Referring to FIG. 4A, when the reflection axis of the bifacial reflective polarizer RP is parallel to the absorption axis of the first polarizer P1 and the absorption axis of the second polarizer P2, the transparent mode may be performed by not applying voltage to the first liquid crystal layer LC1 and the second liquid crystal layer LC2. For instance, a polarization direction of a polarized light passed through the first polarizer P1 and the first liquid crystal layer LC1 is perpendicular to the reflection axis of the bifacial reflective polarizer RP and the absorption axis of the second polarizer P2, therefore, the light may pass through the bifacial reflective polarizer RP and the second polarizer P2 so that one side of the polarizer module 300 is in the transparent state. Similarly, a polarization direction of a polarized light passed through the second polarizer P2 and the second liquid crystal layer LC2 is perpendicular to the reflection axis of the

bifacial reflective polarizer RP and the absorption axis of the first polarizer P1, therefore, the light may pass through the bifacial reflective polarizer RP and the first polarizer P1 so that another side of the polarizer module 300 is also in the transparent state.

[0046] Referring to FIG. 4B, when the reflection axis of the bifacial reflective polarizer RP is parallel to the absorption axis of the first polarizer P1 and the absorption axis of the second polarizer P2, the single mirror mode may be performed by applying voltage to only one of the first liquid crystal layer LC1 and the second liquid crystal layer LC2. For instance, voltage can be applied to the second liquid crystal layer LC2 while no voltage is applied to the first liquid crystal layer LC1. In this way, a polarization direction of a polarized light passed through the second polarizer P2 and the second liquid crystal layer LC2 is parallel to the reflection axis of the bifacial reflective polarizer RP, therefore, the light F2 may be reflected by the bifacial reflective polarizer RP so that one side of the polarizer module 300 is in the mirror state. On the other hand, a polarization direction of a polarized light passed through the first polarizer P1 and the first liquid crystal layer LC1 is perpendicular to the reflection axis of the bifacial reflective polarizer RP and parallel to the absorption axis of the second polarizer P2, therefore, the light F1 may transmit through the bifacial reflective polarizer RP and may be absorbed by the second polarizer P2 so that another side of the polarizer module 300 is in the black state (as shown by the arrow F1').

[0047] Referring to FIG. 4C, when the reflection axis of the bifacial reflective polarizer RP is parallel to the absorption axis of the first polarizer P1 and the absorption axis of the second polarizer P2, the dual mirror mode may be performed by simultaneously applying voltage to the

first liquid crystal layer LC1 and the second liquid crystal layer LC2. For instance, a polarization direction of a polarized light passed through the first polarizer P1 and the first liquid crystal layer LC1 is parallel to the reflection axis of the bifacial reflective polarizer RP, therefore, the light F1 may be reflected by the bifacial reflective polarizer RP so that one side of the polarizer module 300 is in the mirror state. Similarly, a polarization direction of a polarized light passed through the second polarizer P2 and the second liquid crystal layer LC2 is parallel to the reflection axis of the bifacial reflective polarizer RP, therefore, the light F2 may be reflected by the bifacial reflective polarizer RP so that another side of the polarizer module 300 is also in the mirror state.

[0048] FIG. 5 is a cross-sectional view of the polarizer module in another embodiment of the invention. FIG. 6 is a cross-sectional view of the polarizer module in yet another embodiment of the invention. FIG. 7 is a cross-sectional view of the polarizer module in still another embodiment of the invention.

[0049] Referring to FIG. 5, the polarizer module 100 may further include a first substrate SUB1, which is disposed between the first liquid crystal layer LC1 and the second liquid crystal layer LC2 so the first liquid crystal layer LC1 and the second liquid crystal layer LC2 can share the first substrate SUB1. In this embodiment, the bifacial reflective polarizer RP may be the wire grid polarizer (WGP). In this embodiment, another substrate SUB' may be further included between the first liquid crystal layer LC1 and the first polarizer P1 and between the second liquid crystal layer LC2 and the second polarizer P2. That is to say, the polarizing module 100 may be a three-substrate dual cell structure.

[0050] In some embodiments, as shown by FIG. 6, the polarizer module 100 may further include a second substrate SUB2, which is disposed between the bifacial reflective polarizer RP and the second liquid crystal layer LC2, wherein the first substrate SUB1 is disposed between the bifacial reflective polarizer RP and the first liquid crystal layer LC1. That is to say, the polarizing module 100 may be a four-substrate dual cell structure. In this embodiment, the bifacial reflective polarizer RP may be the reflective polarizer mirror (RPM). In other embodiments, as shown by FIG. 7, an air gap AG may be included between the first substrate SUB1 and the second substrate SUB2 to improve heat insulation efficiency for the polarizer module 100.

[0051] FIG. 8 is a cross-sectional view of the polarizer module in still yet another embodiment of the invention.

[0052] Referring to FIG. 8, the polarizer module 100 may optionally include a side light source LS and a light guide plate LG. The side light source LS is provided on one side of the bifacial reflective polarizer RP. The light guide plate LG is disposed between the bifacial reflective polarizer RP and at least one of the first liquid crystal layer LC1 and the second liquid crystal layer LC2. In this embodiment, the light guide plate LG is disposed between the bifacial reflective polarizer RP and the first liquid crystal layer LC1 and between the bifacial reflective polarizer RP and the second liquid crystal layer LC2. In this way, light of the side light source LS may incident to the opposite sides of the bifacial reflective polarizer RP through the light guide plate LG. Since the light of the side light source LS are not polarized, a part of the light incident to the opposite sides of the bifacial reflective polarizer RP may be reflected by

the bifacial reflective polarizer RP, whereas another part of the light incident to the opposite sides of the bifacial reflective polarizer RP may transmit through the bifacial reflective polarizer RP. In this way, the polarizer module can switch between the mirror mode and the transparent mode by the configuration of the absorption axes of the first polarizer P1 and/or the second polarizer P2 and the operation of the first liquid crystal layer LC1 and/or the second liquid crystal layer LC2.

[0053] In summary, due to the polarizer module of the invention includes the bifacial reflective polarizer, the first liquid crystal layer, the second liquid crystal layer, the first polarizer and the second polarizer configured as above, so the polarizer module can switch between the mirror mode (e.g. the dual mirror mode or the single mirror mode) and the transparent mode by operating the first liquid crystal layer and/or the second liquid crystal layer.

[0054] It will be apparent to those skilled in the art that various modifications and variations can be made to the disclosed embodiments. It is intended that the specification and examples be considered as exemplary only, with a true scope of the disclosure being indicated by the following claims and their equivalents.

CLAIM:

1. A polarizer module, comprising:

a bifacial reflective polarizer, having a first surface and a second surface opposite to each other;

5 a first liquid crystal layer and a second liquid crystal layer, disposed on the first surface and the second surface respectively; and

a first polarizer and a second polarizer, disposed on the first liquid crystal layer and the second liquid crystal layer respectively.

2. The polarizer module according to claim 1, wherein a reflection axis of the
10 bifacial reflective polarizer is perpendicular to an absorption axis of the first polarizer and an absorption axis of the second polarizer.

3. The polarizer module according to claim 1, wherein a reflection axis of the bifacial reflective polarizer is perpendicular to an absorption axis of one of the first polarizer and the second polarizer.

15 4. The polarizer module according to claim 3, wherein the reflection axis of the bifacial reflective polarizer is perpendicular to an absorption axis of another one of the first polarizer and the second polarizer.

5. The polarizer module according to claim 1, wherein a reflection axis of the bifacial reflective polarizer is parallel to an absorption axis of the first polarizer and an
20 absorption axis of the second polarizer.

6. The polarizer module according to claim 1, further comprising:

a first substrate, disposed between the first liquid crystal layer and the second liquid crystal layer.

7. The polarizer module according to claim 6, further comprising:

a second substrate, disposed between the bifacial reflective polarizer and the second liquid crystal layer, wherein the first substrate is disposed between the bifacial reflective polarizer and the first liquid crystal layer.

8. The polarizer module according to claim 7, wherein an air gap is provided between the first substrate and the second substrate.

9. The polarizer module according to claim 1, further comprising:

a side light source, provided on one side of the bifacial reflective polarizer; and
a light guide plate, disposed between the bifacial reflective polarizer and at least one of the first liquid crystal layer and the second liquid crystal layer.

10. An operation method of polarizer module, comprising:

providing the polarizer module of claim 1; and

enabling the polarizer module to perform a dual mirror mode, a single mirror mode or a transparent mode,

wherein when light is reflected by the bifacial reflective polarizer and pass through the first polarizer and the second polarizer, respectively, the polarizer module is in the dual mirror mode,

wherein when the light is reflected by the bifacial reflective polarizer and pass through only one of the first polarizer and the second polarizer, the polarizer module is in the

single mirror mode,

wherein when the light transmits through the bifacial reflective polarizer, the polarizer module is in the transparent mode.

11. The operation method of polarizer module according to claim 10, wherein when a
5 reflection axis of the bifacial reflective polarizer is perpendicular to an absorption axis of the first polarizer and an absorption axis of the second polarizer, the dual mirror mode is performed by not applying voltage to the first liquid crystal layer and the second liquid crystal layer.

12. The operation method of polarizer module according to claim 10, wherein when a
10 reflection axis of the bifacial reflective polarizer is perpendicular to an absorption axis of the first polarizer and an absorption axis of the second polarizer, the single mirror mode is performed by applying voltage to only one of the first liquid crystal layer and the second liquid crystal layer.

13. The operation method of polarizer module according to claim 10, wherein when a
15 reflection axis of the bifacial reflective polarizer is perpendicular to an absorption axis of the first polarizer and an absorption axis of the second polarizer, the transparent mode is performed by simultaneously applying voltage to the first liquid crystal layer and the second liquid crystal layer.

14. The operation method of polarizer module according to claim 10, wherein when a
20 reflection axis of the bifacial reflective polarizer is perpendicular to an absorption axis of one of the first polarizer and the second polarizer, the single mirror mode is performed by simultaneously applying voltage to the first liquid crystal layer and the second liquid crystal

layer or not applying voltage to the first liquid crystal layer and the second liquid crystal layer.

15. The operation method of polarizer module according to claim 10, wherein when a reflection axis of the bifacial reflective polarizer is perpendicular to an absorption axis of one of the first polarizer and the second polarizer, the dual mirror mode or the transparent mode is performed by applying voltage to only one of the first liquid crystal layer and the second liquid crystal layer.

16. The operation method of polarizer module according to claim 10, wherein when a reflection axis of the bifacial reflective polarizer is parallel to an absorption axis of the first polarizer and an absorption axis of the second polarizer, the transparent mode is performed by not applying voltage to the first liquid crystal layer and the second liquid crystal layer.

17. The operation method of polarizer module according to claim 10, wherein when a reflection axis of the bifacial reflective polarizer is parallel to an absorption axis of the first polarizer and an absorption axis of the second polarizer, the single mirror mode is performed by applying voltage to only one of the first liquid crystal layer and the second liquid crystal layer.

18. The operation method of polarizer module according to claim 10, wherein when a reflection axis of the bifacial reflective polarizer is parallel to an absorption axis of the first polarizer and an absorption axis of the second polarizer, the dual mirror mode is performed by simultaneously applying voltage to the first liquid crystal layer and the second liquid crystal layer.