

Coupling device

The invention relates to a coupling device having a first coupling part provided with at least one projecting region and a second coupling part provided with at least one elastic region.

European Patent Application EP 0 255 042 discloses a clamping device for a tool on a machine tool, in particular for a die-sinking electrical-discharge machine. Described is a clamping device for a tool on a machine tool, in particular a die-sinking electrical-discharge machine, having a chuck which has two strips which project from the underside of the chuck and are provided with bearing surfaces for orienting the tool in an x direction and a y direction which point transversely to the centre line of the chuck. Provision is made for a plurality of posts to project from the underside of the chuck, said posts having reference surfaces, extending in the x-y plane, at their free end faces, the strips being formed eccentrically and at an angle relative to one another, and for a tool holder for bearing against the posts to have a plane surface in which two pairs of grooves are cut which are aligned with the strips and have elastic lips intended for bearing against the strips, the tool holder having a centre bore with locking elements for receiving a draw bolt in a locking and releasable manner.

The object of the present invention is to propose a coupling device which can be produced automatically and cost-effectively in one operation. Furthermore, the coupling device is to have optimum rigidity, loading capacity, force distribution and a low overall height.

This object is achieved according to the invention in that the regions (2, 2') of the first coupling part (1, 1', 35, 42, 43, 44, 45, 46, 51) which project in the z

direction are arranged eccentrically or centrally, and the projecting regions (2, 2') have conical outer surfaces (6) formed with at least one angle (12, 12') relative to the z direction, in that the elastic regions (4) pointing in the direction of the centre are formed in a radially parallel manner within the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49), the projecting regions (2, 2') of the first coupling part (1, 1', 35, 42, 43, 44, 45, 46, 51) engaging in the elastic regions (4) of the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49) for the x-y orientation in the z direction, in that the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49) is of one-piece design, and in that the workpiece (16) or the tool, the first coupling part (1, 1', 35, 42, 43, 44, 45, 46, 51) and the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49) can be connected by means of a fastening device (53).

The second coupling part of the coupling device according to the invention proves to be capable of being produced in one operation. It can be produced in one step on a lathe or milling machine. The production costs of the coupling device according to the invention are thus considerably reduced compared with the production costs of the coupling devices of the prior art. The second coupling part has many uses, so that only a few embodiments are necessary. The storage costs are therefore reduced. The coupling device according to the invention permits high-load applications. The risk of fracture is minimized. The coupling device can be produced and also used in a simple manner with both off-centre and central reference features.

The second coupling part may be of square design with a circular or square opening.

Depending on the desired application, the outer circumference of the second coupling part is circular or rectangular, preferably square. Likewise, the inner region of the second coupling part may be circular or rectangular, preferably square.

According to a further embodiment, the first coupling part can have a conically shaped, projecting, centrally arranged region, and the elastic regions of the second coupling part can interact with the centrally projecting region of the first coupling part.

The elastic regions of the second coupling part are preferably designed as circular sector sections, as circular sector sections with tongues, or in a tongue shape. These circular and/or tongue-shaped elastic regions can be produced in a simple manner on a lathe or milling machine.

The coupling device according to the invention may be produced from conventional steel, the steel being hardened by a thermal ageing process.

Furthermore, coupling devices can be made of aluminium or plastic.

In a known manner, the coupling device according to the invention has a fastening device for fastening the second coupling part to the first coupling part. All fastening devices known in the prior art are conceivable, such as, for example, a bayonet fastener, screwing by means of a central screwed connection, etc.

According to a preferred embodiment, the elastic regions are profiled and may additionally have a recess in the radial direction opposed to the centre of the second coupling part. This feature results in higher strength and loading capacity in the clamped state.

In a corresponding manner, the elastic regions may have different thicknesses in the radial direction in order to increase the strength and the loading capacity of the coupling device.

The arrangement of a web at the elastic regions in the direction of the centre of the second coupling part can preferably increase the strength and loading capacity of the coupling device.

A further preferred embodiment of the coupling device consists in the fact that at least two second concentric coupling devices having different circumferential radii are arranged one inside the other. That is to say the coupling device can be used on two sizes. For example, the inner second coupling part may be provided with a central cone, and the outer second coupling part may be provided with four off-centre bars. Likewise, the inner second coupling part may have off-centre bars.

Apart from that, the coupling device according to the invention may be constructed the other way round, i.e. the first coupling part has the elastic regions which interact with the projecting regions on the second coupling part.

The coupling device according to the invention can be used in connection with pallets.

The advantages associated with the coupling device are achieved in particular by the elastic regions of the second coupling part being arranged within the annular body of the second coupling part and not above it as in the prior art.

The invention is described below with reference to exemplary embodiments. In the drawings:

Fig. 1 shows a three-dimensional illustration of the
5 second coupling part,
Figs 2a and b show the second coupling part in plan
view and sectional view A-A,
Figs 3 to 8 show various embodiments of the second
coupling part,
10 Figs 9a and b show a two-piece embodiment of the second
coupling part,
Figs 10a and 10b show the first coupling part matching
Fig. 9,
Figs 11a and b show sectional illustrations of the
15 first coupling part of Fig. 10,
Figs 12a, b and c show a coupling device of low overall
height,
Figs 13a and b show a second coupling part with bars
and cone,
20 Figs 14 to 15 show applications of the coupling device
in pallets.

A three-dimensional view of the second coupling part 3
produced in one piece is shown from above and below in
25 Figure 1. In this exemplary embodiment, the second
coupling part 3 is shown as a ring 5. A square
embodiment is likewise conceivable. The second coupling
part has elastic sector-shaped regions 4 which point
inwards with respect to the annular region 5. The
30 annular region 5 and the elastic regions 4 form a
surface 7 having the elastic lateral 10 and circular 11
marginal regions.

The second coupling part 3 is shown in plan view and
35 sectional view A-A in Figures 2a and 2b. It has elastic
regions 4. The elastic regions 4 are four segments
having lateral 10 and circular 11 marginal regions.

Two embodiments of the first coupling part 1 and 1' are shown in section in Figures 3a and 3b. Figure 3a has bars as projecting regions 2, and Figure 3b has a central cone as projecting region 2'.

5

The first coupling part 1 can be connected together with the second coupling part, for example, to the workpiece 16, tool 16, etc., by means of a fastening device (not shown). All known fastening devices are conceivable, for example by means of bayonet fastener, restraining by means of balls, etc. Shown in Figure 2b a tapped hole 18 is provided, into which a screw (not shown) can be screwed for restraining the second coupling part together with the first coupling part.

15

In the clamped state, the elastic lateral marginal regions 10 interact with the projecting bars 2 of the first coupling part 1 with respect to the x-y orientation. In the clamped state, the centrally arranged cone provided in the first coupling part 1' touches the elastic circular marginal regions 11 in an orienting manner in the x-y plane.

The z orientation is effected via the seating surfaces 6, which touch the surface 7 in the clamped state.

25

The first coupling part is shown once again in plan view and sectional view in two exemplary embodiments 1 and 1' in Figures 4a and 4b. The first coupling part 1 with the bars 8 can be seen in Figure 4a. A first coupling part 1' with a central cone 9 is shown in Figure 4b. Both first coupling parts 1, 1' have seatings 6 for the z orientation. The surfaces of the bars 8 and of the cone 9 having two bevels with different angles 12 of slope can be seen in the enlarged individual illustrations I and II.

35

Another embodiment of the first coupling part 1 or 1' shows the elastic region 4 with a profile. The profile has an inclination 13 and a recess 14, as can be seen in Figures 5b and c. Figures 5b and c represent enlargements of the detail III in Figure 5a, Figure 5b showing the coupling device in the relaxed state and Figure 5c showing it in the clamped state. The broken line is intended to represent a bar 8 or a seating surface 6. Before the coupling device is clamped, the inclined profile is in contact in a first step, the elastic element 4 orients the first coupling part 1, and the inclination 13 is oriented parallel to the bar surface or to the seating surface. A recess 14 is preferably incorporated in the elastic region 4. The recess 14 is provided above the contact surface. The advantage associated therewith means high rigidity, better loading and greater resistance to fracture. At higher loads, the elastic contact between the elastic regions 4 and the bar surfaces changes to firm contact with the recesses 14. Further bending of the elastic regions is thus prevented. Fracture is prevented as a result.

Figures 6a and b show a further embodiment of the first coupling part. The elastic regions 4 additionally have a web 15 at the region pointing towards the centre. The web 15 increases the rigidity. The web 15 forms a narrow gap 17 at the end pointing in the direction of the workpiece 16. This preferred embodiment can be used in particular for coupling devices made of materials different from steel, such as, for example, aluminium, plastic, etc.

Another embodiment of the elastic regions 4 can be seen in Figures 7a and 7b, Figure 7b showing a sectional illustration of Figure 7a in direction C-C. The elastic regions 4 have tongue-shaped regions 19. The advantage associated therewith consists in particular in an

increase in the elasticity. Each tongue 19 can be deformed more effectively on its own.

Figures 8a and 8b show a further configuration of the elastic regions. Figure 8b shows the section along line D-D. In contrast to the embodiment in Figures 7a and 7b, the annular part 5 has projections 20 below the elastic regions, and these projections 20 support the elastic regions, so that only the projecting tongue-shaped regions can be elastically deformed during the clamping, which results in greater accuracy.

In Figures 8c and 8d (section in direction D-D), the circular margin of the elastic regions 4 has a cutout 21, i.e. the region between the tongues 19 is fixed. The result is in an elastic restraint in the contact region 22 during average loads with high accuracy. There is thus no firm contact in the region of the recess 23. At an even higher load, the tongues 19 are bent further in the axial direction until firm contact with the surface 24 is obtained, whereby higher strength and resistance to fracture is obtained.

Figures 9 to 11 show a coupling device having a two-piece second coupling part 25 and 26 and the associated first coupling part 32 and 33. The second coupling part in Figure 9a and in the sectional illustration according to Figure 9b can consist of at least two second coupling parts 25 and 26, the inner coupling part 25 being arranged concentrically in the outer coupling part 26. Due to the two-piece configuration, various embodiments described above can be combined, depending on the existing boundary conditions. That is to say coupling devices are possible in which the elastic regions 4 with respect to the inner coupling part 25 may differ from the elastic regions 4 of the outer coupling part 26.

The coupling devices having the two second coupling parts 25 and 26 and the associated first coupling parts 32 and 33 are shown in Figures 9 to 11. They are of similar construction to the one-piece first coupling parts in the previous figures. Reference numerals 27
5 signify the outer bars, 28 the inner bars, 29 the central cone, 30 the inner z seatings and 31 the outer z seatings.

10 A coupling device of smaller diameter is shown in Figures 12a to 12c. The second coupling part 34 in Figure 12a and in the sectional drawing G-G in Figure 12b has recesses 38 between the elastic regions 4. The recesses 38 provide space for the z seatings 37 of the
15 first coupling part 35 in Figure 12c.

A combination of bars 39 and central cone 40 is shown in the second coupling part 41 in Figures 13a and 13b. This combination can be used in the case of pallets
20 with individual holders or multi-holders. The combination shown in Figures 13a and b can then be used advantageously in a space-saving manner.

An application for pallets is shown in Figures 14a and
25 b. Four first coupling parts 42 can be seen, the first coupling part 43 in Figure 14a being provided for x-y-z orientation, the first coupling part 44 being provided for x-z orientation, the first coupling part 45 being provided for y-z orientation and the first coupling
30 part 46 being provided for z orientation. For all applications, the second coupling part 47 is disclosed in a single embodiment in Figure 14b.

Figures 15a and b show a further application of the
35 coupling device. Here, in particular the low overall height of the coupling device is to be emphasized, which is required in wire electrical-discharge machines for example. The first coupling part 49 is fastened to

the base 48 of the wire electrical-discharge machine.
The second coupling part 51 is connected to the
workpiece 52, the bottom surface 54 of the workpiece 52
lying with the base surface 54 of the wire electrical-
5 discharge machine at the level of the 0 line 50.

Of course, the first coupling part and the second
coupling part can be used the other way round for all
the embodiments described above, i.e. the first
10 coupling part has elastic regions and the second
coupling part has projecting regions.

List of designations

	1, 1'	First coupling part
	2, 2'	Projecting region
5	3	Second coupling part
	4	Elastic regions
	5	Ring
	6	Seating surfaces
	7	Surface
10	8	Bars
	9	Cone
	10	Lateral marginal regions
	11	Circular marginal regions
	12, 12'	Angle
15	13	Inclination
	14	Recess
	15	Web
	16	Workpiece, tool
	17	Gap
20	18	Tapped hole
	19	Tongue-shaped regions
	20	Projections
	21	Cutout
	22	Contact region
25	23	Recess
	24	Contact surface
	25	Inner second coupling part
	26	Outer second coupling part
	27	Outer bars
30	28	Inner bars
	29	Central cone
	30	Inner z seatings
	31	Outer z seatings
	32	Second coupling part
35	33	Second coupling part
	34	Second coupling part
	35	First coupling part
	36	Bars

	37	Z seatings
	38	Recess
	39	Bars
	40	Central cone
5	41	Second coupling part
	42	First coupling part
	43	First coupling part for x-y-z
	44	First coupling part for x-z
	45	First coupling part for y-z
10	46	First coupling part z
	47	Second coupling part
	48	Base
	49	First coupling part
	50	0 line
15	51	Second coupling part
	52	Workpiece
	53	Fastening device
	54	Surface of the base

Patent claims

1. Coupling device having a first coupling part (1, 1', 35, 42, 43, 44, 45, 46, 51) provided with at least one projecting region (2, 2') and a second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49) provided with at least one elastic region (4), characterized in that the regions (2, 2') of the first coupling part (1, 1', 35, 42, 43, 44, 45, 46, 51) which project in the z direction are arranged eccentrically or centrally, and the projecting regions (2, 2') have conical outer surfaces (6) formed with at least one angle (12, 12') relative to the z direction, in that the elastic regions (4) pointing in the direction of the centre are formed in a radially parallel manner within the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49), the projecting regions (2, 2') of the first coupling part (1, 1', 35, 42, 43, 44, 45, 46, 51) engaging in the elastic regions (4) of the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49) for the x-y orientation in the z direction, in that the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49) is of one-piece design, and in that the workpiece (16) or the tool, the first coupling part (1, 1', 35, 42, 43, 44, 45, 46, 51) and the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49) can be connected by means of a fastening device (53).

2. Coupling device according to Claim 1, characterized in that the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49) is of annular or square design with a circular or square opening.

3. Coupling device according to Claim 1, characterized in that the first coupling part (1, 1', 35, 42, 43, 44, 45, 46, 51) has a conically shaped, projecting, centrally arranged region (9), and in that the elastic regions (4) of the second coupling part (3,

25, 26, 32, 33, 34, 41, 47, 49) interact with the centrally projecting region (9) of the first coupling part (1, 1', 35, 42, 43, 44, 45, 46, 51):

- 5 4. Coupling device according to Claim 1, 2 or 3, characterized in that the elastic regions (4) are designed as circular sector sections, as circular sector sections with tongues, or in a tongue shape.
- 10 5. Coupling device according to at least one of the preceding claims, characterized in that the coupling part/parts is/are produced from steel, the steel being hardened by a thermal ageing process.
- 15 6. Coupling device according to at least one of Claims 1 to 4, characterized in that the coupling part/parts is/are produced from aluminium.
- 20 7. Coupling device according to at least one of Claims 1 to 4, characterized in that the coupling part/parts is/are produced from plastic.
- 25 8. Coupling device according to at least one of the preceding claims, characterized in that the fastening device (53) for fastening the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49) to the first coupling part (1, 1', 35, 42, 43, 44, 45, 46, 51) is designed as a bayonet fastener, or in that the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49) has a stud bolt
30 which can be screwed into the first coupling part (1, 1', 35, 42, 43, 44, 45, 46, 51) provided with a thread (18).
- 35 9. Coupling device according to at least one of the preceding claims, characterized in that the elastic regions (4) have profiles at their marginal zones (10, 11).

10. Coupling device according to at least one of the preceding claims, characterized in that the thickness of the elastic regions (4) have recesses (14) in the radial direction of the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49).

11. Coupling device according to at least one of the preceding claims, characterized in that the elastic regions (4) have different thicknesses in the radial direction towards the centre of the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49).

12. Coupling device according to at least one of the preceding claims, characterized in that the elastic regions (4) have a web (15) at the margins in the radial direction towards the centre of the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49).

13. Coupling device according to at least one of the preceding claims, characterized in that the second coupling part (3, 32, 33, 34, 41, 47, 49) is composed of at least two parts (25, 26) of different size, the two parts (25, 26) being designed in the same way and being arranged so as to fit one inside the other.

14. Coupling device according to at least one of the preceding claims, characterized in that the coupling device is designed the other way round, the first coupling part (1, 1', 35, 42, 43, 44, 45, 46, 51) having at least one elastic region (4) and the second coupling part (3, 25, 26, 32, 33, 34, 41, 47, 49) having at least one projecting region (2, 2').

15. Coupling device according to at least one of the preceding claims, characterized in that it is used in pallets (52).

16. Coupling device according to at least one of the preceding claims, characterized in that, with increasing load, the elastic contact between the elastic regions (4) and the bars (8) changes to firm
5 contact with the surfaces of the recesses (14, 23).