

IPos.

9610312-2

CLADDING UNITS FOR BUILDING AND SEAL STRUCTURE FOR JOINT THEREOF

BACKGROUND OF THE INVENTION

1. Field of the Invention:

5 This invention relates to cladding units or facing units for forming the outer wall of a building and a structure for sealing a joint between adjoining cladding units.

2. Description of the Prior Art:

10 As one form of the outer wall of a building, the unit type curtain wall that is formed by joining curtain walls side by side vertically and laterally as attached to the skeleton frame of a building is known. Generally, the curtain wall units each comprise a framework, a panel or screen fitted to the framework, and a dry seal member fitted to the perimeter of the
15 framework.

20 When the curtain wall units mentioned above are attached as vertically and laterally adjoined to one another to the skeleton frame of a given building, the seal members of these adjoining curtain wall units are pressed against one another and the joints consequently formed therebetween are sealed. It is, however, very difficult to press the seal members correctly against one another. Even when they are correctly pressed, the joints are not always sealed fully effectively. Usually, therefore, the joints between the adjoining curtain wall units
25 are sealed by filling the joints with a wet sealing material. This work of filling the joints with the wet sealing material turns out to be very irksome.

SUMMARY OF THE INVENTION

- 2 -

It is, therefore, an object of the present invention to provide cladding units or facing units and a seal structure for the joints thereof which are liberated from the problems mentioned above.

5 In accordance with one aspect of the present invention, there is provided a cladding unit which comprises a cladding member comprised of a framework and a face member attached to one side face thereof and fastener stringers for a waterproof slide fastener attached one each to the outer lateral parts of
10 the cladding member. According to this structure, the joint between two adjoining cladding units can be simply and infallibly sealed by uniting the opposed fastener stringers of the cladding units.

In a preferred mode of this aspect of the invention, the
15 fastener stringers mentioned above each comprise a waterproof tape and an engaging part provided with a multiplicity of coupling elements attached to the waterproof tape as spaced at fixed intervals along one longitudinal edge thereof, with the engaging part so disposed that one end part thereof will
20 protrude from one end part of the waterproof tape in the direction of length thereof. When the opposed fastener stringers of the adjoining cladding units are to be united, therefore, the insertion thereof into a slider is facilitated because the relevant engaging parts protruding on one end side
25 thereof from the corresponding waterproof tapes can be drawn out from between the adjoining cladding units and inserted into the slide groove of the slider.

Another aspect of the present invention consists in

This Sheet Has Been Replaced



- 3 -

providing a seal structure for the joint to be formed between the opposed frameworks of the cladding units mutually adjoined and attached to the backing member of the building. In a basic mode of this aspect of the invention, the joint formed between the adjoining cladding units is sealed by uniting the engaging parts of the opposed fastener stringers of these cladding units and the gap between the end parts of the fastener stringers and the gap between these end parts and the backing member of the building are sealed by filling the gaps with a wet sealing material.

In a preferred mode of this aspect of the present invention, a boxlike backup member provided with projecting parts each having a cross section roughly in the shape of three sides of a square and adapted to thrust out between the end part of the fastener stringer and the backing member of the building is disposed between the end parts of the adjoining fastener stringers so that the opening part thereof will confront the rear sides of the end parts of the fastener stringers and the gap between the end parts of the fastener stringers is sealed by filling the empty space in the backup member with a wet sealing material. Appropriately, the framework of the cladding unit is provided on each of the outer lateral surfaces thereof with two parallel elongate ribs extended in the direction of length of the surfaces as raised therefrom so that the longitudinal edge part of the fastener stringer opposite the engaging part thereof will be press fit preferably with a linear retaining member into a groove which is formed by the two ribs. The face member of the cladding

This Sheet Has Been Replaced



unit is attached to the framework in such a manner that the edges thereof will protrude from the framework. The boundary between the framework and the face member is sealed by filling the gap arising between the edges of the face member and one of the ribs defining the groove with a wet sealing material.

As one mode of the seal structure for the joint between the edge parts of fastener stringers, a seal structure is provided which is capable of sealing a cruciform joint to be formed by four vertically and laterally adjoining cladding units with a wet sealing material. In this seal structure, the lateral joints between the vertically adjoining cladding units and the vertical joints between the laterally adjoining cladding units are sealed by uniting the engaging parts of the opposed fastener stringers of the relevant cladding units. At the cruciform joint resulting from the intersection between the lateral joints and the vertical joints, a backup member having a generally cruciform plan figure is disposed in such a manner that the projecting parts thereof will thrust out in the rear sides of the end parts of the relevant fastener stringers. The cruciform joint is sealed by filling the empty space of the cruciform backup member with a wet sealing material.

As another mode of the seal structure, there is provided a seal structure which is capable of sealing a T-shaped joint to be formed between a first and a second cladding unit which adjoin each other and a third cladding unit which adjoins the two cladding units with a wet sealing material. In this seal structure, the first joint between the first and second adjoining cladding units, the second joint between the first

and third adjoining cladding units, and the third joint between the second and third cladding units are sealed severally by uniting the engaging parts of the opposed fastener stringers of the relevant cladding units. At the T-shaped joint resulting from the intersection between the first, second, and third joints mentioned above, a backup member having a generally T-shaped plan figure is disposed in such a manner that the projecting parts thereof will thrust out in the rear sides of the end parts of the relevant fastener stringers. The T-shaped joint is sealed by filling the empty space of the T-shaped backup member with a wet sealing material.

As yet another mode of the seal structure, a seal structure is provided which is capable of sealing the end part joint between the end parts of a first and a second cladding unit which adjoin each other and a wall in an opening of a building with a wet sealing material. In this seal structure, the joint between the first and second cladding units is sealed by uniting the engaging parts of the opposed fastener stringers of the first and second cladding units. In the end part in which the joint between the first and second cladding units confronts the wall surface in the opening of the building, an end part backup member is disposed so as to thrust out in the rear sides of the relevant fastener stringers. The opening between the end parts of the first and second cladding units and the end parts of the fastener stringers is sealed by filling the empty space of the end part backup member with a wet sealing material. The gap between the first and the second cladding unit and the wall in the opening of the building is

sealed by filling this gap with a wet sealing material.

As still another mode of the seal structure, a seal structure is provided which is capable of sealing with a wet sealing material the joint to be formed where an obstacle thrusting out the boundary of a first and a second cladding unit which would otherwise adjoin each other borders on the first and second cladding units. In this seal structure, depressed parts adapted jointly to conform to the contour of the obstacle are formed in the first and second cladding units, with the relevant fastener stringers interrupted in continuity by the depressed parts. The joints bordering on the opposite boundaries of the obstacle are sealed by filling the gaps between the depressed parts of the cladding units and the obstacle with a wet sealing material and uniting the engaging parts of the opposed fastener stringers attached to the first and second cladding units. In each of the end parts in which the opposite joints border on the obstacle, a backup member is disposed so as to thrust out in the rear sides of the united fastener stringers. The empty spaces in the backup members are filled with a wet sealing material to connect the fastener stringers with the wet sealing material in the depressed parts of the cladding units. The gaps between the wet sealing materials and the obstacle are sealed by filling the opening with a wet sealing material.

25

BRIEF DESCRIPTION OF THE DRAWINGS

Other objects, features, and advantages of the invention will become apparent from the following description taken together with the drawings, in which:

Fig. 1 is a schematic front view showing the state in which cladding units are fixed to the skeleton frame of a building;

Fig. 2 is a front view of a cladding unit;

5 Fig. 3 is a cross section taken through Fig. 2 along the line III - III;

Fig. 4 is a cross section taken through Fig. 2 along the line IV - IV;

10 Fig. 5 is a cross-sectional view of a fixing part of the cladding unit;

Fig. 6 is a fragmentary longitudinal section of a cruciform joint;

Fig. 7 is a cross section taken through Fig. 6 along the line VII - VII;

15 Fig. 8 is a perspective view of a cruciform backup member;

Fig. 9 is a fragmentary longitudinal section of a T-shaped joint;

Fig. 10 is a cross section taken through Fig. 9 along the line X - X;

20 Fig. 11 is a perspective view of the T-shaped backup member;

Fig. 12 is a fragmentary longitudinal section of an end part joint;

25 Fig. 13 is a cross section taken through Fig. 12 along the line XIII - XIII;

Fig. 14 is a perspective view of a seal part for the end parts of vertically adjoining cladding units;

Fig. 15 is a fragmentary longitudinal section of a joint

circumscribing an obstacle;

Fig. 16 is a front view of a cladding unit having a face material thereof formed of a glass plate;

5 Fig. 17 is a cross section taken through Fig. 16 along the line XVII - XVII;

Fig. 18 is a cross section taken through Fig. 16 along the line XVIII - XVIII;

10 Fig. 19 and Fig. 20 are respectively a longitudinal section and a cross-sectional view showing a connecting part between a cladding unit having a face material thereof formed of a board material and a cladding unit having a face material thereof formed of a glass plate; and

15 Fig. 21 and Fig. 22 are respectively a longitudinal section and a cross-sectional view showing an embodiment having adjoining cladding units so united that their surfaces do not fall flush.

DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

20 A plurality of lateral backing members 3 made of steel and a plurality of vertical backing members 4 made of steel are fixed in an opening 2 in a skeleton frame of a building 1 and cladding units 5 are fixed to the outdoor sides of the upper and lower lateral backing members 3 and the left and right vertical backing members 4 as shown in Fig. 1. The end part joints between the cladding units 5 and vertical edge parts 6
25 and lateral edge parts 7 in the opening of the building and lateral joints and vertical joints between vertically and laterally adjoining cladding units 5 are severally sealed with a waterproof slide fastener and a wet sealing material which

will be specifically described hereinafter.

5 The cladding units 5 mentioned above, as shown in Fig. 2, each comprise a cladding member 15 having a face member 14 fixed to the outdoor side surface of a framework 13 formed by joining an upper frame member 10, a lower frame member 11, and laterally opposite vertical frame members 12 in the shape of a square and fastener stringers 16 attached to the frame members 10, 11, and 12. The fastener stringers 16 are severally paired with those of the cladding units 5 which are adjoined as
10 opposed thereto and, consequently, are enabled to form waterproof slide fasteners in cooperation therewith.

The fastener stringers 16 mentioned above, as shown in Fig. 3, each comprise a waterproof tape 17 and an engaging part 18 having a multiplicity of coupling elements 19 fixed to the
15 waterproof tape 17 as regularly spaced along one longitudinal edge part thereof. One end part 18a of the engaging part 18 protrudes from one end part 17a of the waterproof tape 17 in the longitudinal direction thereof so as to permit easy insertion thereof into a slide groove of a slider, as shown in
20 Fig. 2.

The substance of which the waterproof tape 17 is made is silicone rubber. The waterproof tape 17, therefore, excels in weatherability and durability and exhibits good fastness of adhesion to the wet sealing material, a silicone sealant which
25 will be specifically described hereinbelow.

In the embodiment described above, the face member 14 has been depicted as formed of a plate material. Optionally, it may be made of a glass material, a screen, or other

materials.

The frame members 10, 11, and 12 mentioned above, as shown in Fig. 3 and Fig. 4, each comprise an elongate inner wall part 20, an elongate outer wall part 22, and a connecting part 5 serving to connect the longitudinal edges of these wall parts, which are so joined as to form a cross section roughly in the shape of three sides of a square. On the outside of each of the outer wall parts 22, an outwardly open conduit 23 is formed continuously as extended in the longitudinal direction 10 thereof. Each of the conduits 23 includes a groove defined by two parallel elongate ribs 23a, 23b raised from the outer surface of each of the outer wall parts 22 of the frame members 10, 11, and 12, as clearly shown in Fig. 7. Each of the ribs has an inwardly projecting pawl portion formed integrally with 15 the free edge thereof so that a linear retaining member is securely fitted in the conduit 23. In the edge of each of the outer wall parts 22, a plurality of outwardly projecting fixing pieces 24 are integrally formed as spaced with prescribed intervals in the longitudinal direction thereof. The face 20 member 14 is fixed with securing devices or fasteners 25 to the connecting parts 21 of the frame members 10, 11, and 12. The fixing pieces 24 protrude outwardly from the face member 14.

The end parts of the frame members 10, 11, and 12 are cut at an angle of 45 degrees and abutted and connected by welding 25 or by the use of a corner block or coupling piece. The longitudinal edge part of each of the waterproof tapes 17 of the fastener stringers 16 is push fit with a linear retaining member 26 such as aluminum wire into the outwardly open conduit

23. The engaging part 18 of each of the fastener stringers 16 protrudes outwardly from the face member 14. The joined parts of the framework 13 and the face member 14 are sealed by filling the gaps between the face member 14 and the outer wall parts 22 with a wet sealing material 27 such as silicone rubber.

The cladding units 5 are assembled at a factory, for example, and then transported to a site for the fixation on a building. The fixing pieces 24 of the vertical frame members 12 of the laterally adjoining cladding units 5 are severally secured with a securing device or fastener 28 such as, for example, a screw to the vertical backing member 4 as shown in Fig. 5 and, at the same time, the fixing pieces 24 of the upper and lower frame members 10, 11 of the vertically adjoining cladding units 5 are severally secured with a securing device such as, for example, a screw to the lateral backing member 3. The fixing pieces 24 each have an oblong hole 24a formed therein (see Fig. 6 and Fig. 14). Since the oblong holes 24a are so adapted that the securing device 28 may be inserted therethrough, the cladding units 5 are allowed to move in the direction of plane.

In the laterally adjoining cladding units 5, the engaging parts 18 of the fastener stringers 16 attached to the vertical frame members 12 are opposed to each other. The outwardly projecting one-end parts 18a of the engaging parts 18 are drawn out from between the laterally adjoining cladding units 5 and are inserted in a slider 29. The slider 29 is moved in the direction of length of the engaging parts 18 to mesh the

coupling elements 19 of the engaging parts 18 of the paired fastener stringers 16. The slider 29 is eventually extracted through the other end parts of the engaging parts 18.

Since the waterproof tapes 17 of the pair of the fastener stringers 16 are airtightly and watertightly coupled as a result of the procedure described above, the vertical joint between the laterally adjoining cladding units 5 can be sealed infallibly. Since the slider 29 is engaged with the engaging parts 18 on the outer side than between the laterally adjoining cladding units 5, the work of coupling of the fastener stringers is easy to perform.

Since the lateral joint between the vertically adjoining cladding units 5 is sealed in the same manner as described above, it can be sealed infallibly.

The outwardly projecting one-end parts of the engaging parts 18 of the fastener stringers 16 may be either cut off or left per se after they have been coupled by means of the slider 29. In the illustrated examples, they are depicted in a cut state.

Now, the seal structure for the cruciform joint (the part indicated by A in Fig. 1) formed by the vertically and laterally adjoining cladding units 5 will be described below.

Since each of the fastener stringers 16 has the same length as that of the outwardly open conduit 23 of each of the frame members 10, 11, and 12, the fastener stringers 16 have their continuity interrupted in the cruciform joint resulting from the intersection of the lateral joint and the vertical joint and consequently allow the occurrence of an

opening S₁ of the shape of a square as shown in Fig. 6.

A cruciform backup member 30, therefore, is disposed so as to thrust out on the rear surface side severally of the fastener stringers 16 in the cruciform joint as shown in Fig. 6 and Fig. 7. The opening S₁ is closed by filling the cruciform joint with a wet sealing material 31 and, at the same time, the cruciform joint is sealed by continuing the fastener stringers 16 with the wet sealing material 31.

The cruciform backup member 30, as shown in Fig. 8, comprises a cruciform bottom plate 32 and upright plates 33 of a plan shape of three sides of a square disposed one each along the outer edges of the cruciform bottom plate 32 and connected end to end to form a cruciform depressed part 34. The bottom plate 32 is adapted to be fixed by adhesion to the vertical backing member 4. Since the pair of the fastener stringers 16 are coupled substantially in the shape of the letter V so as to absorb possible displacement of the adjoining cladding units 5 as shown in Fig. 7, a notch 35 substantially in the shape of the letter V is formed in the edge part of each of the upright plates 33. As a result, the protruding portions 36 of the cruciform backup member 30 can be easily inserted in the rear sides of the pairs of coupled fastener stringers 16.

Next, the seal structure for the T-shaped joint (the part indicated by B in Fig. 1) to be formed by adjoining one cladding unit 5 astraddle to two laterally adjoining cladding units 5 will be described below.

The left and right fastener stringers 16', 16'' severally attached to the upper frame members 10', 10'' of the laterally

adjoining cladding units 5', 5'' are severally coupled with the fastener stringer 16 attached to the lower frame member 11 of the upper cladding unit 5 as shown in Fig. 9. Since the left and right fastener stringers 16', 16'' are separated from each other, these fastener stringers 16', 16'' have the continuity thereof interrupted in the T-shaped joint resulting from the intersection of the lateral joint and the vertical joint and give rise to an opening S₂ of the shape of a square.

A T-shaped backup member 40, therefore, is disposed so as to thrust out on the rear surface sides of the fastener stringers 16, 16', and 16'' in the T-shaped joint as shown in Fig. 9 and Fig. 10. The opening S₂ is closed by filling the T-shaped backup member 40 with a wet sealing material 41 and, at the same time, the T-shaped joint is sealed by continuing the fastener stringers 16, 16', and 16'' with the wet sealing material 41.

The T-shaped backup member 40, as shown in Fig. 11, comprises a T-shaped bottom plate 42 and upright plates 43 of a plan shape of three sides of a square disposed one each along the outer edges of the T-shaped bottom plate 42 and connected end to end to form a T-shaped depressed part 44. The bottom plate 42 is adapted to be fixed by adhesion to the lateral backing member 3. Since the pair of the fastener stringers 16, 16' or 16, 16'' are coupled substantially in the shape of the letter V so as to absorb possible displacement of the adjoining cladding units 5 as shown in Fig. 10, a notch 45 substantially in the shape of the letter V is formed in the edge part of each of the upright plates 43. As a result, the protruding portions

46 of the backup member 40 can be easily inserted in the rear sides of the pairs of coupled fastener stringers.

The left and right fastener stringers 16', 16'' of the lower laterally adjoining cladding units 5', 5'' are severally coupled with the one fastener stringer 16 attached to the lower frame member 11 of the upper cladding unit 5 on the opposite longitudinal edge portions relative to the medial portion as the boundary as shown in Fig. 9. It is, therefore, permissible to divide the fastener stringer 16 attached to the lower frame member 11 of the upper cladding unit 5 into a first fastener stringer 16-1 and a second fastener stringer 16-2, bond the divided ends of the relevant waterproof tapes 17 thereof by thermal welding or adhesion, and allow the one-end parts 18a of the engaging parts 18 of the second fastener stringer 16-2 and the opposed fastener stringer 16'' to protrude from the waterproof tapes 17 in the longitudinal direction thereof as indicated by an imaginary line in Fig. 9.

In such an arrangement, the lower left fastener stringer 16' attached to the upper frame member 10' of the left cladding unit 5' and the upper first fastener stringer 16-1 attached to the lower frame member 11 of the upper cladding unit 5 are coupled with each other by engaging the slider with the left end parts respectively of these fastener stringers and moving the slider along the joint length of these fastener stringers. This slider is removed in the opening S_2 in the T-shaped joint. The lower right fastener stringer 16'' attached to the upper frame member 10'' of the right cladding unit 5'' and the upper second fastener stringer 16-2 are coupled with each other

by engaging the slider with the medial end parts (the one-end parts 18a of the longitudinal engaging parts 18) respectively of these fastener stringers and moving the slider along the joint length of the fastener stringers. Thus, the engagement
5 of the slider with fastener stringers is easily performed.

The T-shaped joint of the lower cladding unit 5 and the upper paired cladding units 5 indicated by C in Fig. 1 is sealed in the same manner as described above.

Now, the seal structure for the end part joint to be
10 formed between the vertically adjoining cladding units 5 and the vertical edge part 6 of the wall of the building 1 (the part indicated by D in Fig. 1) will be described below.

As shown in Fig. 12, a wet sealing material 50 is packed in the outwardly open conduit 23 of one of the vertical frame
15 members 12 of the cladding unit 5 to be opposed to the vertical edge part 6 of the wall in the opening of the building 1 in advance at a factory, for example, so that the sealing material is brought into contact with the ends of the fastener stringers 16 attached to the upper and lower frame members 10 and 11 of
20 the cladding unit 5 to form a continuous surface therewith. An end part backup member 51 is disposed on the rear surface side of the end parts of the pair of fastener stringers 16 intervening between the lower frame member 11 and the upper frame member 10 of the vertically adjoining cladding units 5 as
25 shown in Fig. 14. The gap between the end part backup member 51 and the rear surfaces of the pair of fastener stringers 16 and the gap between the upper and the lower cladding unit 5 are filled with a wet sealing material 52.

The fixing piece 24 of one of the vertical frame members 12 is fixed with a securing device 53 to the vertical end part backing member 4 secured to the skeleton frame of the building 1 as shown in Fig. 13. The vertical joint formed between the 5 vertical edge part 6 of the wall in the opening of the building 1 and one of the vertical frame members 12 is sealed by filling the vertical joint continuously to the upper and the lower cladding unit 5 with a wet sealing material 55 through the medium of a backup member 54 disposed on the fixing piece 10 24 along the vertical edge part of the wall. The backup member 54 is formed of a plastic foam such as a hard polyurethane foam.

The end part backup member 51, as shown in Fig. 14, comprises a bottom plate 56 of the shape of a rectangle and upright plates 57 of a plan figure of the shape of three sides 15 of a square integrally formed on the bottom plate 56. A notch 58 of the shape of the letter V is formed in the end part of the intermediate upright plate 57.

Incidentally, the end part joint between the lateral edge part 7 of the wall in the opening of the building 1 and the 20 lateral frame members of the cladding units 5, which is indicated by E in Fig. 1, is sealed in the same manner as described above.

Now, the structure for sealing the joint to be formed between the adjoining cladding units 5 and an obstacle 60 such 25 as the post for an arcade, which is indicated by F in Fig. 1, will be described below on the assumption that the obstacle 60 thrusts from between the adjoining cladding units 5.

The lower frame member 11 of the upper cladding unit 5 is

divided by the obstacle 60 as a boundary into a first and a second frame member, 11-1 and 11-2, as shown in Fig. 15 and the first and the second frame member, 11-1 and 11-2, are connected through the medium of an auxiliary frame member 61 of the shape
5 of three sides of a square to give rise to a depressed part 62 conforming to the contour of the obstacle 60.

The auxiliary frame member 61 is obtained by connecting three frame members having the same cross-sectional shape as the lower frame member 11 end to end in the shape of three
10 sides of a square with a lower open side. This auxiliary frame member 61 is provided with conduits including grooves 63 continuing into the grooves 23c of the outwardly open conduits of the first and the second frame member, 11-1 and 11-2. The end parts of the left and right fastener stringers 16 are
15 sealed by filling the grooves 63 with a wet sealing material 64.

Meanwhile, the upper frame member 10 of the lower cladding unit 5 is also divided by the obstacle 60 as a boundary into a first and a second frame member, 10-1 and 10-2, as shown in Fig. 15 and the first and the second frame member, 10-1 and
20 10-2, are connected through the medium of an auxiliary frame member 65 of the shape of three sides of a square to give rise to a depressed part 66 conforming to the contour of the obstacle 60.

The auxiliary frame member 65 is obtained by connecting
25 three frame members having the same cross-sectional shape as the upper frame member 10 end to end in the shape of three sides of a square with an upper open side. This auxiliary frame member 65 is provided with conduits including grooves 67

continuing into the grooves 23c of the outwardly open conduits of the first and the second frame member, 10-1 and 10-2. The end parts of the left and right fastener stringers 16 are sealed by filling the grooves 67 with a wet sealing material 68.

5 Backup members 69 are disposed one each in the end parts of the upper and lower fastener stringers 16 opposed to the obstacle 60 so as to thrust on the rear surface sides of these fastener stringers 16. The end parts are sealed by filling the gap between the backup member 69 and the rear surfaces of the
10 upper and lower fastener stringers 16 and the gap between the wet sealing materials 64 and 68 packed in the upper and the lower auxiliary frame member, 61 and 65, with a wet sealing material 70. This backup member 69 is formed in the same shape as the end part backup member 51 shown in Fig. 14.

15 Then, the joints between the obstacle 60 and the upper and lower cladding units 5 are sealed by filling the gap between the upper and lower auxiliary frame members, 61 and 65, connected by the wet sealing material 70 and a peripheral surface 60a of the obstacle 60 with a wet sealing material 71.

20 A platelike backup member is attached to the peripheral surface 60a of the obstacle 60 or to the lateral backing member 3 or the vertical backing member 4 so as to permit the packing of the wet sealing material 71.

25 Now, an embodiment of the cladding unit 5 using the face member made of glass will be described below.

 The framework 13 is formed, as shown in Fig. 16, by abutting and connecting the opposite ends of the upper frame member 10 to the upper parts of the left and right vertical

frame members 12 and the opposite ends of the lower frame member 11 to the lower parts of the left and right vertical frame members 12.

Attachments 80 are fixed one each closely to the outdoor
5 sides in the out-face direction in the outer surfaces 10a, 11a, and 12a in the in-face direction of the frame members 10, 11, and 12 mentioned above. The attachments 80, as shown in Fig. 17 and Fig. 18, are each an elongate of the cross-sectional shape consisting of a fixing piece 81, an outwardly bent piece
10 82, and a hooked piece 83. The outwardly bent piece 82 and the hooked piece 83 defines an outwardly open groove 84. The fixing pieces 81 are fixed one each to the outer surfaces 10a, 11a, 12a respectively of the frame members 10, 11, and 12 by means of a screw 85. Depressed parts 86 opened on the outdoor
15 side are formed one each between the hooked pieces 83 and the outer surfaces 10a, 11a, and 12a of the frame members 10, 11, and 12.

The opposite end parts of the attachments 80 are cut at an angle of 45 degrees and butt joined. The depressed parts 86
20 are filled throughout their combined length with a wet sealing material 87 to seal the gaps between the framework 13 and the attachments 80.

The face member 14 is formed of a glass plate and, as shown in Fig. 17 and Fig. 18, is attached through the medium of
25 a sealing member 90 to inwardly open groove 89 of the upper frame member 10, the lower frame member 11, and the left and right vertical frame members 12. The cladding unit 5 is an ordinary fixed fit sash.

The longitudinal free edge parts of the waterproof tapes 17 of the fastener stringers 16 serving to form the waterproof slide fasteners are press attached by means of a linear retaining member 88 such as aluminum wire to the outwardly open grooves 84 of the attachments 80.

A frame material intended to form an ordinary fixed fit sash can be applied for the frame members 10, 11, and 12. It suffices specifically to fix the attachments 80 one each to the outer surfaces 10a, 11a, and 12a of the frame members 10, 11, and 12 and attach the waterproof tapes 17 of the fastener stringers 16 to the attachments 80.

For the purpose of adjoining the cladding unit 5 having the face member 14 formed of a glass plate to the cladding unit 5 of the first embodiment having the face member 14 formed of a board as shown in Fig. 2, it suffices to join the fixing pieces 24 of the frame members 10, 11, and 12 through the medium of fasteners 93 to the edge parts of an opening 92 of a skeleton frame 91 of a building by means of bolts 94, oppose the cladding units 5 to the opening 92 and fix the cladding units 5 in one plane, and unite the engaging parts 18 of the adjoining fastener stringers 16 by means of the slider 29 as shown in Fig. 19 and Fig. 20. The cladding unit 5 having the face member 14 formed of a glass plate is fixed by causing flange parts 99 of the frame members 10, 11, and 12 to be nipped between a retaining member 97 and a bracket 96 secured to the skeleton frame 91 of the building so as to thrust out from the opening 92 and tying them with screws 98.

Optionally, the attachments 80 may be integrally formed on

the outer faces 10a, 11a, and 12a of the frame members 10, 11, and 12. In other words, the outwardly open conduits including grooves may be integrally formed on the outer surfaces 10a, 11a, and 12a of the frame members 10, 11, and 12 serving to
5 form an ordinary sash.

Now, an embodiment of fixing adjoining cladding units 5 in such a manner that their surfaces will not fall flush.

The fixing pieces 24 of the frame members 10, 11, and 12 of the cladding unit 5 having the face member 14 formed of a
10 board are severally coupled to the fasteners 93 and fixed so as to thrust further on the outdoor side than the skeleton frame 91 of the building as shown in Fig. 21 and Fig. 22.

An ordinary cladding member 15 such as, for example, a fixed fitting sash or an open-close sash is disposed inside the
15 opening 92 of the skeleton frame 91 of the building. Outer frames 100 are fixed one each through the medium of an L-shaped piece 101 to outdoor surfaces 10b, 11b, and 12b in the out-face direction respectively of the frame members 10, 11, and 12 of the cladding member 15 and the fixing parts thereof are sealed
20 with a wet sealing material 102. The L-shaped pieces 101 are integrally formed on the lower frame members 11.

The outer frames 100 each comprise a first plate 103 extended in the out-face direction and a second plate 104 extended in the in-face direction and assume a substantially
25 hook-shaped cross section. An attachment 105 is fixed jointly to the first plate 103 and the second plate 104 by means of bolts 106. The attachment 105 is provided with a fixing piece 107 and a projecting piece 108. An outwardly open conduit

109 including groove is formed on the projecting piece 108. The fastener stringer 16 is fixed as mentioned above to the groove of the outwardly open conduit 109. A wet sealing material 110 is filled in the gap between the projecting piece
5 108 and the second plate 104.

As the fixing piece 107 of the attachment 105 is fixed to the fastener 93, the second plate 104 falls flush with the face member 14 and the adjoining fastener stringers 16 are opposed to each other. The engaging parts 18 of the adjoining fastener
10 stringers 16 are meshed with each other by means of the slider.

Owing to the structure described above, the gaps between the ordinary cladding member 15 and four cladding units 5 can be sealed with the waterproof slide fasteners when the ordinary cladding member 15 is fixed in the opening 92 of the skeleton
15 frame 91 of the building and fixing the cladding units 5 having the face member 14 thereof formed of a board one each to the vertical and lateral edge parts of the opening 92.

While certain specific embodiments have been disclosed herein, the invention may be embodied in other specific forms
20 without departing from the spirit or essential characteristics thereof. The described embodiments are therefore to be considered in all respects as illustrative and not restrictive, the scope of the invention being indicated by the appended claims rather than by the foregoing description and all changes
25 which come within the meaning and range of equivalency of the claims are, therefore, intended to be embraced therein.



THIS SHEET HAS BEEN
REPLACED

- 24 -

WHAT IS CLAIMED IS:

1. A cladding unit for a building, comprising a cladding member comprised of a framework and a face member attached to one side face of the framework and fastener stringers of a waterproof slide fastener attached severally to the outer lateral parts of said cladding member.

2. The cladding unit according to claim 1, wherein said fastener stringer comprises a waterproof tape and an engaging part having a plurality of coupling elements attached to the waterproof tape as spaced at fixed intervals along one longitudinal edge of the tape, one-end part of said engaging part protruding from one-end part of said waterproof tape in the longitudinal direction of the tape.

3. A seal structure for joints between adjoining cladding units attached to a backing member of a building,

said cladding units each comprising a cladding member comprised of a framework and a face member attached to one side face of the framework and fastener stringers of a waterproof slide fastener attached severally to outer lateral parts of said cladding member, said fastener stringers each comprising a waterproof tape and an engaging part having a plurality of coupling elements attached to said waterproof tape as spaced at fixed intervals along one longitudinal edge of the tape;

said joints being sealed by the coupling of said engaging parts of opposed fastener stringers of said adjoining cladding units; and

gaps between end parts of said fastener stringers and/or gaps between said end parts of the fastener stringers and said

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

- 25 -

backing member of said building being sealed by filling said gaps with a wet sealing material.

4. The seal structure according to claim 3, which further comprises a boxlike backup member disposed between the end parts of said fastener stringers and said backing member of the building, and the gaps between the end parts of said fastener strings and said backing member being sealed with a wet sealing material packed in an empty space of said backup member.

5. The seal structure according to claim 4, wherein said backup member is provided with projecting parts thrusting out between the end parts of said fastener stringers and said backing member of the building, assuming a cross section substantially of the shape of three sides of a square, and having an opening disposed so as to confront the rear sides of the end parts of the relevant fastener stringers.

6. The seal structure according to claim 4 or 5, wherein said backup member has a notch substantially in the shape of letter V formed in an upper edge thereof.

7. The seal structure according to any one of claims 3 to 6, wherein said cladding unit comprises two parallel elongate ribs raised from each of outer lateral surfaces of said framework and extended in the direction of length thereof and the longitudinal edge part of each of said fastener stringers opposite the engaging part thereof is fixed in a groove formed by said two ribs by means of a linear retaining member.

8. The seal structure according to claim 7, wherein said face member of said cladding unit is attached to said framework so as to have edges thereof protruding from said framework

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

- 26 -

and gaps between said framework and said face member are sealed with a wet sealing material packed in the gaps formed severally between said edges and one of said ribs.

5 9. The seal structure according to any one of claims 3 to 8, wherein one-end part of said engaging part of the fastener stringer protrudes from one-end part of said waterproof tape in the longitudinal direction of the tape.

10. A seal structure for a cruciform joint formed by four vertically and laterally adjoining cladding units,

10 said cladding units each comprising a cladding member comprised of a framework and a face member attached to one side face of the framework and fastener stringers of a waterproof slide fastener attached severally to outer lateral parts of said cladding member, said fastener stringers each comprising a
15 waterproof tape and an engaging part having a plurality of coupling elements attached to said waterproof tape as spaced at fixed intervals along one longitudinal edge of the tape;

a lateral joint being sealed by coupling the engaging parts of opposed fastener stringers of said vertically
20 adjoining cladding units and a vertical joint being sealed by coupling the engaging parts of opposed fastener stringers of said laterally adjoining cladding units;

a cruciform backup member being disposed in said cruciform joint resulting from the intersection of said lateral joint and
25 said vertical joint so as to protrude into the rear surfaces closely to end parts of said fastener stringers; and

the end parts of said fastener stringers being continuously sealed with a wet sealing material packed in said

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

- 27 -

cruciform backup member.

11. The seal structure according to claim 10, wherein one-end part of said engaging part of the fastener stringer protrudes from one-end part of said waterproof tape in the longitudinal direction of the tape.

12. A seal structure for a T-shaped joint formed by a first and a second cladding unit arranged in an adjoining state and a third cladding unit arranged astraddle said two adjoining cladding units,

10 said cladding units each comprising a cladding member comprised of a framework and a face member attached to one side face of the framework and fastener stringers of a waterproof slide fastener attached severally to outer lateral parts of said cladding member, said fastener stringers each comprising a waterproof tape and an engaging part having a plurality of coupling elements attached to said waterproof tape as spaced at fixed intervals along one longitudinal edge of the tape;

15 a first joint between said first and second cladding units being sealed by coupling the engaging parts of opposed fastener stringers of said first and second cladding units in the adjoining state;

20 a second joint between said first and third cladding units and a third joint between said second and third cladding units being severally sealed by coupling said engaging parts of said fastener stringers of said first and second cladding units with the opposite engaging part of said fastener stringer of said third cladding unit;

25 a T-shaped backup member being disposed in a T-shaped

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

- 28 -

joint resulting from the intersection of said first, second, and third joints so as to protrude in the rear surfaces closely to end parts of said fastener stringers; and

the end parts of said fastener stringers being
5 continuously sealed with a wet sealing material packed in said T-shaped backup member.

13. The seal structure according to claim 12, wherein one-end part of said engaging part of the fastener stringer protrudes from one-end part of said waterproof tape in the
10 longitudinal direction of the tape.

14. A seal structure for an end part joint between end parts of a first and a second cladding unit arranged in an adjoining state and a wall in an opening of a building,

said cladding units each comprising a cladding member
15 comprised of a framework and a face member attached to one side face of the framework and fastener stringers of a waterproof slide fastener attached severally to outer lateral parts of said cladding member, said fastener stringers each comprising a waterproof tape and an engaging part having a plurality of
20 coupling elements attached to said waterproof tape as spaced at fixed intervals along one longitudinal edge of the tape;

a joint between said first and second cladding units being sealed by coupling the engaging parts of opposed fastener stringers of said first and second cladding units;

25 an end part backup member being disposed closely to end parts of said first and second cladding units opposed to said wall in the opening of the building so as to protrude in the rear surfaces closely to end parts of said fastener stringers;

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

- 29 -

gaps between the end parts of said first and second cladding units and gaps in the end parts of said fastener stringers being severally sealed with a wet sealing material packed in said end part backup member; and

5 a joint between said first and second cladding units and said wall of the building is sealed with a wet sealing material packed in said joint.

15 15. The seal structure according to claim 14, wherein said cladding unit has a waterproof tape at a lateral part of said framework opposed to the wall in the opening of the building.

15 16. The seal structure according to claim 14, wherein said cladding unit has no fastener stringer at a lateral part of said framework opposed to the wall in the opening of the building.

17. The seal structure according to any one of claims 14 to 16, wherein one-end part of said engaging part of the fastener stringer protrudes from one-end part of said waterproof tape in the longitudinal direction of the tape.

20 18. A seal structure for a joint formed between a first and a second cladding unit in the adjoining state and an obstacle thrust from between said adjoining cladding units,

25 said cladding units each comprising a cladding member comprised of a framework and a face member attached to one side face of the framework and fastener stringers of a waterproof slide fastener attached severally to outer lateral parts of said cladding member, said fastener stringers each comprising a waterproof tape and an engaging part having a plurality of

This Sheet Has Been Replaced





THIS SHEET HAS BEEN
REPLACED

- 30 -

coupling elements attached to said waterproof tape as spaced at fixed intervals along one longitudinal edge of the tape;

5 said first and second cladding units each having a depressed part conforming to the contour of said obstacle so formed as to interrupt the continuity of the fastener stringers of said cladding units;

a wet sealing material being packed along the depressed parts;

10 joints formed on the opposite sides relative to said obstacle as the boundary being severally sealed by coupling the engaging parts of opposed fastener stringers attached to said first and second cladding units;

15 backup members being disposed one each closely to end parts of said coupled fastener stringers opposed to said obstacle at said joints so as to protrude in the rear surfaces of said coupled fastener stringers;

said backup members being filled with a wet sealing material so as to connect said fastener stringers with said wet sealing material packed in said depressed parts; and

20 gaps between said wet sealing materials and said obstacle being sealed by filling said gaps with a wet sealing material.

19. The seal structure according to claim 18, wherein one-end part of said engaging part of the fastener stringer protrudes from one-end part of said waterproof tape in the
25 longitudinal direction of the tape.

This Sheet Has Been Replaced



- 31 -

ABSTRACT OF THE DISCLOSURE

Cladding units (5) for a building and a seal structure for the joints thereof are disclosed. A cladding unit (5) comprises a cladding member (15) consisting of a framework (13) and a face member (14) attached to one side face thereof and fastener stringers (16) for waterproof slide fasteners attached one each to the outer lateral parts of the cladding member (15). In a seal structure for the joint to be formed between the opposed frameworks (13) of the cladding units (5) mutually adjoined and attached to the backing member (3, 4) on the building (1), the joint formed between the adjoining cladding units (5) is sealed by uniting the engaging parts (18) of the opposed fastener stringers (16) of these cladding units (5) and the gap between the end parts of the fastener stringers and the gap between these end parts and the backing member of the building are sealed by filling the gaps with a wet sealing material (31, 41, 52, 70).

(Fig. 2)

This Sheet Has Been Replaced



FIG. 1




FIG. 2




FIG. 3




FIG. 4




FIG. 5




FIG. 6




FIG. 7




FIG. 8




FIG. 10




FIG. 11




FIG. 12




FIG. 13




FIG. 14




FIG. 15




FIG. 16




FIG. 17




FIG. 18




FIG. 19





FIG. 20



(21/22)

FIG. 21





FIG. 22



11 DEC 1996

CLADDING UNITS FOR BUILDING AND SEAL STRUCTURE FOR JOINT THEREOFABSTRACT OF THE DISCLOSURE

Cladding units (5) for a building and a seal structure for the joints thereof are disclosed. A cladding unit (5) comprises a cladding member (15) consisting of a framework (13) and a face member (14) attached to one side face thereof and fastener stringers (16) for waterproof slide fasteners attached one each to the outer lateral parts of the cladding member (15). In a seal structure for the joint to be formed between the opposed frameworks (13) of the cladding units (5) mutually adjoined and attached to the backing member (3, 4) on the building (1), the joint formed between the adjoining cladding units (5) is sealed by uniting the engaging parts (18) of the opposed fastener stringers (16) of these cladding units (5) and the gap between the end parts of the fastener stringers and the gap between these end parts and the backing member of the building are sealed by filling the gaps with a wet sealing material (31, 41, 52, 70).

(Fig. 2)

S-27204 30

13 OCT 1997

- 2 -

It is, therefore, an object of the present invention to provide seal structures for the joints between adjoining cladding units or facing units, which are liberated from the problems mentioned above.

5 A cladding unit to be used in the present invention comprises a cladding member comprised of a framework and a face member attached to one side face thereof and fastener stringers for a waterproof slide fastener attached one each to the outer lateral parts of the cladding member. According to this
10 structure, the joint between two adjoining cladding units can be simply and infallibly sealed by uniting the opposed fastener stringers of the cladding units.

In a preferred mode of the cladding unit, the fastener stringers mentioned above each comprise a waterproof
15 tape and an engaging part provided with a multiplicity of coupling elements attached to the waterproof tape and spaced at fixed intervals along one longitudinal edge thereof, with the engaging part so disposed that one end part thereof will protrude from one end part of the waterproof tape in the
20 direction of length thereof. When the opposed fastener stringers of the adjoining cladding units are to be united, therefore, the insertion thereof into a slider is facilitated because the relevant engaging parts protruding on one end side thereof from the corresponding waterproof tapes can be drawn
25 out from between the adjoining cladding units and inserted into the slide groove of the slider.

As a basic mode of the present invention, there is

13 OCT 1997

- 3 -

provided a seal structure for the joint to be formed between the opposed frameworks of the cladding units mutually adjoined and attached to the backing member of the building.

The joint formed between the adjoining cladding units is sealed by uniting the engaging parts of the opposed fastener stringers of these cladding units and the gap between the end parts of the fastener stringers and the gap between these end parts and the backing member of the building are sealed by filling the gaps with a wet sealing material.

A boxlike backup member provided with projecting parts each having a cross section roughly in the shape of three sides of a square and adapted to thrust out between the end part of the fastener stringer and the backing member of the building is disposed between the end parts of the adjoining fastener stringers so that the opening part thereof will confront the rear sides of the end parts of the fastener stringers and the gap between the end parts of the fastener stringers is sealed by filling the empty space in the backup member with a wet sealing material. Appropriately, the framework of the cladding unit is provided on each of the outer lateral surfaces thereof with two parallel elongate ribs extended in the direction of length of the surfaces as raised therefrom so that the longitudinal edge part of the fastener stringer opposite the engaging part thereof will be press fit preferably with a linear retaining member into a groove which is formed by the two ribs. The face member of the cladding



REPLACEMENT SHEET

13 OCT 1997

- 24 -

WHAT IS CLAIMED IS:

1. A seal structure for joints between adjoining cladding units attached to a backing member of a building,

5 said cladding units each comprising a cladding member comprised of a framework and a face member attached to one side face of the framework and fastener stringers of a waterproof slide fastener attached severally to outer lateral parts of said cladding member, said fastener stringers each comprising a waterproof tape and an engaging part having a plurality of
10 coupling elements attached to said waterproof tape and spaced at fixed intervals along one longitudinal edge of the tape;

said joints being sealed by the coupling of said engaging parts of opposed fastener stringers of said adjoining cladding units;

15 a boxlike backup member being disposed between the end parts of said fastener stringers and said backing member of the building; and

gaps between end parts of said fastener stringers and/or gaps between said end parts of the fastener stringers and said
20 backing member of said building being sealed by filling said gaps with a wet sealing material and gaps between the end parts of said fastener strings and said backing member being sealed with a wet sealing material packed in an empty space of said backup member.

25 2. The seal structure according to claim 1, wherein said backup member is provided with projecting parts thrusting out between the end parts of said fastener stringers and said backing member of the building, assuming a cross section



13 OCT 1997

- 25 -

substantially of the shape of three sides of a square, and having an opening disposed so as to confront the rear sides of the end parts of the relevant fastener stringers.

5 3. The seal structure according to claim 1 or 2, wherein said backup member has a notch substantially in the shape of letter V formed in an upper edge thereof.

10 4. The seal structure according to any one of claims 1 to 3, wherein said cladding unit comprises two parallel elongate ribs raised from each of outer lateral surfaces of said framework and extended in the direction of length thereof and the longitudinal edge part of each of said fastener stringers opposite the engaging part thereof is fixed in a groove formed by said two ribs by means of a linear retaining member.

15 5. The seal structure according to claim 4, wherein said face member of said cladding unit is attached to said framework so as to have edges thereof protruding from said framework and gaps between said framework and said face member are sealed with a wet sealing material packed in the gaps formed severally between said edges and one of said ribs.

20 6. The seal structure according to any one of claims 1 to 5, wherein one-end part of said engaging part of the fastener stringer protrudes from one-end part of said waterproof tape in the longitudinal direction of the tape.

25 7. A seal structure for a cruciform joint formed by four vertically and laterally adjoining cladding units,

said cladding units each comprising a cladding member comprised of a framework and a face member attached to one side face of the framework and fastener stringers of a waterproof



REPLACEMENT SHEET

13 OCT 1997

- 26 -

slide fastener attached severally to outer lateral parts of said cladding member, said fastener stringers each comprising a waterproof tape and an engaging part having a plurality of coupling elements attached to said waterproof tape and spaced
5 at fixed intervals along one longitudinal edge of the tape;

a lateral joint being sealed by coupling the engaging parts of opposed fastener stringers of said vertically adjoining cladding units and a vertical joint being sealed by coupling the engaging parts of opposed fastener stringers of
10 said laterally adjoining cladding units;

a cruciform backup member being disposed in said cruciform joint resulting from the intersection of said lateral joint and said vertical joint so as to protrude into the rear surfaces closely to end parts of said fastener stringers; and
15 the end parts of said fastener stringers being continuously sealed with a wet sealing material packed in said cruciform backup member.

8. The seal structure according to claim 7, wherein one-end part of said engaging part of the fastener stringer
20 protrudes from one-end part of said waterproof tape in the longitudinal direction of the tape.

9. A seal structure for a T-shaped joint formed by a first and a second cladding unit arranged in an adjoining state and a third cladding unit arranged astraddle said two adjoining
25 cladding units,

said cladding units each comprising a cladding member comprised of a framework and a face member attached to one side face of the framework and fastener stringers of a waterproof



13 OCT 1997

- 27 -

slide fastener attached severally to outer lateral parts of said cladding member, said fastener stringers each comprising a waterproof tape and an engaging part having a plurality of coupling elements attached to said waterproof tape and spaced
5 at fixed intervals along one longitudinal edge of the tape;

a first joint between said first and second cladding units being sealed by coupling the engaging parts of opposed fastener stringers of said first and second cladding units in the adjoining state;

10 a second joint between said first and third cladding units and a third joint between said second and third cladding units being severally sealed by coupling said engaging parts of said fastener stringers of said first and second cladding units with the opposite engaging part of said fastener stringer of said
15 third cladding unit;

a T-shaped backup member being disposed in a T-shaped joint resulting from the intersection of said first, second, and third joints so as to protrude in the rear surfaces closely to end parts of said fastener stringers; and

20 the end parts of said fastener stringers being continuously sealed with a wet sealing material packed in said T-shaped backup member.

10. The seal structure according to claim 9, wherein one-end part of said engaging part of the fastener stringer
25 protrudes from one-end part of said waterproof tape in the longitudinal direction of the tape.

11. A seal structure for an end part joint between end parts of a first and a second cladding unit arranged in an



13 OCT 1997

- 28 -

adjoining state and an edge part of an opening of a building,

said cladding units each comprising a cladding member comprised of a framework and a face member attached to one side face of the framework and fastener stringers of a waterproof slide fastener attached severally to outer lateral parts of said cladding member, said fastener stringers each comprising a waterproof tape and an engaging part having a plurality of coupling elements attached to said waterproof tape and spaced at fixed intervals along one longitudinal edge of the tape;

10 a joint between said first and second cladding units being sealed by coupling the engaging parts of opposed fastener stringers of said first and second cladding units;

an end part backup member being disposed closely to end parts of said first and second cladding units opposed to said wall in the opening of the building so as to protrude in the rear surfaces closely to end parts of said fastener stringers;

gaps between the end parts of said first and second cladding units and gaps in the end parts of said fastener stringers being severally sealed with a wet sealing material packed in said end part backup member; and

20 a joint between said first and second cladding units and said wall of the building is sealed with a wet sealing material packed in said joint.

12. The seal structure according to claim 11, wherein said cladding unit has a waterproof tape at a lateral part of said framework opposed to the wall in the opening of the building.

13. The seal structure according to claim 11, wherein



13 OCT 1997

- 29 -

said cladding unit has no fastener stringer at a lateral part of said framework opposed to the wall in the opening of the building.

14. The seal structure according to any one of claims 11
5 to 13, wherein one-end part of said engaging part of the fastener stringer protrudes from one-end part of said waterproof tape in the longitudinal direction of the tape.

15. A seal structure for a joint formed between a first and a second cladding unit in the adjoining state and an
10 obstacle thrust from between said adjoining cladding units,

said cladding units each comprising a cladding member comprised of a framework and a face member attached to one side face of the framework and fastener stringers of a waterproof slide fastener attached severally to outer lateral parts of
15 said cladding member, said fastener stringers each comprising a waterproof tape and an engaging part having a plurality of coupling elements attached to said waterproof tape and spaced at fixed intervals along one longitudinal edge of the tape;

said first and second cladding units each having a
20 depressed part conforming to the contour of said obstacle so formed as to interrupt the continuity of the fastener stringers of said cladding units;

a wet sealing material being packed along the depressed parts;

25 joints formed on the opposite sides relative to said obstacle as the boundary being severally sealed by coupling the engaging parts of opposed fastener stringers attached to said first and second cladding units;



13 OCT 1997

- 30 -

backup members being disposed one each closely to end parts of said coupled fastener stringers opposed to said obstacle at said joints so as to protrude in the rear surfaces of said coupled fastener stringers;

- 5 said backup members being filled with a wet sealing material so as to connect said fastener stringers with said wet sealing material packed in said depressed parts; and

gaps between said wet sealing materials and said obstacle being sealed by filling said gaps with a wet sealing material.

- 10 16. The seal structure according to claim 15, wherein one-end part of said engaging part of the fastener stringer protrudes from one-end part of said waterproof tape in the longitudinal direction of the tape.