

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
16 May 2002 (16.05.2002)

PCT

(10) International Publication Number
WO 02/38954 A1

(51) International Patent Classification⁷: F03D 3/06, 3/00

(21) International Application Number: PCT/PH01/00002

(22) International Filing Date: 16 October 2001 (16 10 2001)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
1-2000-03130 13 November 2000 (13.11.2000) PH
01305525 6 26 June 2001 (26.06.2001) EP

(71) Applicant and

(72) Inventor: URSUA, Isidro, U. [PH/PH], #7 Sunrise Street,
Rimview Park, Concepcion Dos, Markina City 1811 (PH)

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,

CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, PH, PL, PT, RO, RU, SD, SE, SG, SI,
SK, SL, TJ, TM, TR, TT, TZ, UA, UG, US, UZ, VN, YU,
ZA, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZW), Eurasian
patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European
patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE,
IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF,
CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD,
TG)

Declaration under Rule 4.17:

— of inventorship (Rule 4.17(iv)) for US only

[Continued on next page]

(54) Title: VERTICAL AXIS WIND TURBINE



(57) Abstract: The present invention provides a prime mover (2) for harnessing energy from a flow of fluid, the prime mover (2) comprising a shaft (4) having a rotational axis, arranged to be rotatably mounted to a substructure, the shaft (4) comprising at least one arm (6) extending radially from the shaft (4), the or each arm (6) comprising at least one blade (8) wherein the or each blade (8) is oriented such that flow action on the blade (8) effects rotation of the shaft (4), characterized in that the or each blade (8) is movably mounted on an arm (6) and wherein each blade (8) is movable from a first position, having a first drag, to a second position, having a second drag, wherein the first drag is higher than the second drag. The prime mover (2) of the invention provides substantially reduced drag in a flow of fluid, and an increased torque output, compared to prior art prime movers.

WO 02/38954 A1

20

WO 02/38954 A1



Published:

— with international search report

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette