

Description

Mobile Climbing Robot and Service System Having a
Climbing Robot

5

Technical Area

The invention relates to a mobile climbing robot and a
10 service system having a climbing robot, which can be used
to clean a facade of a building, for example.

Background Information

15

Publication CH 670 248 A5 makes known an arrangement
comprising a vertically movable cabin for working on
structures having a curved or planar surface. The
arrangement is used in particular for working on large
20 surfaces, such as cooling towers, masonry dams, sides of
ships, and the like. The arrangement comprises a cabin
for this purpose, which is equipped with a crawler drive
having suction cups. Using the crawler drive, the cabin
can be moved along the facade of the building, wherein
25 the suction cups are used to increase the adhesion
between the crawler drive and the building facade.
However, the use of the crawler drive is limited to
smooth surfaces having a relatively small curvature. The
crawler drive is unable to overcome, or cannot easily
30 overcome stairs and steps in the facade.

Publication US 5 551 525 makes known a climbing robot
having a front leg and a rear leg. The two legs are

interconnected by way of a knee joint, and each comprises a rotatable foot joint. Although a robot of that type can overcome steps in the building facade, the use thereof for autonomous building cleaning is limited since the
5 freedom of motion thereof is inadequate.

Advantages of the Invention

10 The problem addressed by the invention is that of providing a mobile climbing robot that can climb along any type of surface, such as curved and angled surfaces, overhangs, and ceilings, for example, and can overcome stairs.

15

The problem is solved by a mobile climbing robot having the features of claim 1.

The mobile climbing robot according to the invention
20 comprises a central joint, by which a first leg is connected to a second leg. In addition, the robot comprises a first foot which is connected to the first leg by way of a first foot joint for rotation and a first foot joint for tilting. Furthermore, a second foot is
25 provided which is connected to the second leg by way of a second foot joint for rotation and a second foot joint for tilting. Finally, the mobile climbing robot comprises a mounting disposed on the first foot for attaching an implement.

30

Advantageous developments of the invention will be apparent from the features indicated in the dependent claims.

In an embodiment of the climbing robot according to the invention, the first and the second leg are offset laterally relative to one another. This has the advantage
5 that the two legs can be moved past one another, thereby resulting in the greatest possible freedom of motion.

In another embodiment of the climbing robot according to the invention, the first and/or the second foot is
10 equipped with a suction cup. The result is greater adhesion of the climbing robot on the foundation on which the climbing robot moves.

As an alternative or in addition thereto, the first
15 and/or the second foot of the climbing robot can be equipped with a magnet. This is advantageous in particular when the climbing robot is supposed to move on a metallic, magnetic surface. Using the magnet, the extent of the adhesion of the foot or feet on the
20 metallic surface can be controlled in a simple manner. To this end, the magnet is advantageously designed as a switchable electromagnet.

Furthermore, in the case of the climbing robot according
25 to the invention, the first and/or the second foot can be equipped with a claw. This is advantageous in particular when the climbing robot is supposed to move over an uneven surface, such as a heavily structured surface, for example.

30

To solve the problem it is furthermore provided that, in the case of the climbing robot according to the invention, the first and/or the second foot is equipped

with a drilling device. The robot can thus create points on the surface of the object on which it is supposed to move, so it can hold onto these points. However, the drilling device can also be used to perform work on the surface of the object. The robot can therefore drill
5 holes in the wall of the building e.g. at points of a facade of a building that are difficult to access.

According to another feature of the invention, it can be
10 improved further by equipping the climbing robot with electrical or hydraulic drives for moving the legs and/or the feet.

According to another embodiment of the climbing robot
15 according to the invention, a cleaning device is provided as the implement. Using the cleaning device, the robot can then autonomously clean e.g. the facade of the building, the hull or superstructure of a ship, or the surface of a solar or photovoltaic installation.

20 In addition, a service system is provided that comprises the above-described climbing robot for a surface of an object such as the facade of a building, for example. To this end, the service system has a supply station for
25 supplying the climbing robot. In addition, the service system includes a windlass which can be attached to the object to lower the supply station and secure the climbing robot.

30 According to a development of the service system, the supply station includes a control unit for controlling the climbing robot.

In addition, the supply station of the service system can include a supply container for cleaning agent.

According to another development of the service system,
5 the supply station includes an energy source for the drive of the climbing robot.

Finally, the service system can be equipped with a camera mounted on the climbing robot, and a display screen for
10 displaying the information delivered by the camera. In addition, the service system can be equipped with a control unit for controlling the climbing robot.

15 **Brief Description of the Drawings**

The invention is explained in greater detail in the following using a plurality of embodiments and with reference to 13 figures.

20

Figure 1 shows a first possible embodiment of the mobile climbing robot according to the invention, in a three-dimensional view.

25 Figure 2 shows a second possible embodiment of the mobile climbing robot according to the invention, in a three-dimensional view.

Figure 3 shows a first possible type of motion of the
30 climbing robot.

Figure 4 shows a second possible type of motion of the climbing robot.

Figure 5 shows the sequence of motions of the climbing robot for overcoming a step and an overhang.

5 Figure 6 shows the climbing robot when cleaning a surface without using the revolute joints on the feet.

Figure 7 shows the climbing robot once more when cleaning a surface, wherein the revolute joints on the
10 feet are used in this case.

Figure 8 shows the climbing robot when cleaning a corner and a surface.

15 Figure 9 shows the climbing robot when cleaning a larger surface.

Figure 10 shows the climbing robot once more when cleaning a corner and a larger surface.

20 Figure 11 shows another possible sequence of motions of the climbing robot for cleaning a surface.

Figure 12 shows the climbing robot together with a
25 plurality of signal transmitters for controlling the climbing robot.

Figure 13 shows the service system with the climbing robot on the facade of a building, in a three-
30 dimensional view.

Ways to Implement the Invention

A first possible embodiment of mobile climbing robot 15 according to the invention is shown in figure 1. Climbing robot 15 comprises two legs 1 and 2 which are interconnected by way of a common joint 3. Joint 3 is disposed and designed between legs 1 and 2 such that legs 1 and 2 are offset laterally relative to one another. This has the advantage that the two legs 1 and 2 can be moved past one another, thereby enabling the robot to stride forward similar to a human.

First leg 1 is connected to a first foot 8 by way of a first foot joint for tilting 4 and a first foot joint for rotation 5. Foot 8 comprises a first suction cup 8.1, a second suction cup 8.2, and a third suction cup 8.3. Suction cups 8.1, 8.2 and 8.3 are controllable and are used to provide sufficient adhesion on a planar surface so that robot 15 is securely adhered thereto. Furthermore, a pivotable device mounting 11 which carries a cleaning device 10 at one end is provided on first foot 8. Cleaning device 10 can be a suction device, for example. The suction device comprises a suction connector 10.1 which can be connected to a hose which is not depicted. Cleaning device 10 can also contain a sponge which is supplied with a cleaning agent by way of connector 10.1.

Second leg 2 is connected to a second foot 9 by way of a second foot joint for tilting 6 and a second foot joint for rotation 7. Second foot 9, similar to first foot 8, comprises a first suction cup 9.1, a second suction cup 9.2, and a third suction cup 9.3.

Electrical, hydraulic, or pneumatic drives are integrated into joints 3, 4, 5, 6 and 7.

Lines can be integrated into the housing of legs 1 and 2.

5 In the embodiment of the robot shown in figure 1, these lines are routed out of the legs with a connector 1.1 on leg 1 and a connector 2.1 on the second leg. The lines are interconnectable by way of connectors 1.1 and 2.1 and a hose which is not shown in figure 1. These lines can be
10 used as supply lines and/or drain lines. The lines can be used, for example, to carry away the material drawn up by cleaning head 10 or to supply cleaning head 10 with cleaning agent.

15 In one embodiment, suction cups 8.1 to 9.3 are designed such that they automatically adhere via suction to a planar surface when pressed thereon.

Mobile cleaning robot 15 shown in figure 2 differs from
20 the cleaning robot shown in figure 1 in that it comprises a first hose or a first tube line 13.1, a second hose or a second tube line 13.2, and a third hose or a third tube line 13.3. The drives in joints 3, 4, 5, 6 and 7 can be supplied with hydraulic fluid or compressed air by way of
25 lines 13.1, 13.2 and 13.3. The hydraulic fluid or compressed air is used to supply energy to the drives. An implement 12 designed as a wiper is fastened to mounting 11.

30 As shown in figures 1 and 2, foot 8 can be equipped with various implements 10, 12.

Cleaning robot 15 is suitable for autonomously cleaning building facades in a dry or wet manner, or for working at points of a building that are difficult to access, such as a cooling tower or a tall building. In addition,
5 cleaning robot 15 is also suitable for cleaning the hull or superstructure of a ship or the surface of a solar installation or a photovoltaic installation.

Instead of the cleaning device, a drilling device can be
10 fastened to foot 8. By way thereof, robot 15 is capable of autonomously drilling holes in the surface of the object on which it is supposed to hold itself, in order to autonomously create retaining points for itself. The retaining points can be used by the robot to increase its
15 hold on the object. The object can be a building, a bridge, or a ship, for example. The drilling device can also be used to drill holes into the masonry of the building for other reasons.

20 Two ways for robot 15 to move are depicted graphically in figure 3. In a first step 20, robot 15 rotates by way of revolute joint 7 about foot 9, and so foot 8 makes a circular motion. This motion in the plane of the drawing is depicted as first step 20 in figure 3. In a second
25 step 21, foot 9 is detached from the foundation and swiveled past first foot 8 (perpendicular to the plane of the drawing) in a 180° arc. Next, foot 9 attaches itself to the foundation once more using suction. In a third
30 step 22, foot 8 is again swiveled in a circular motion about foot 9. Revolute joint 7 is used primarily once more for this purpose.

Mobile robot 15 can also perform a sequence of motions of the type shown in figure 4. In a first step 23, the leg having foot 9 is detached from the foundation and, as shown in figure 4, is moved upwardly in the plane of the drawing, in that legs 1 and 2 are moved apart from one another. Foot 9 then attaches itself to the foundation using suction and, in a subsequent step 24, foot 8 is drawn toward it. As soon as foot 8 is securely attached to the foundation once more using suction, next step 25 takes place, which corresponds to step 23 in regard to the sequence of motions.

Figure 5 shows the sequence of motions of robot 15 when overcoming an overhang (steps 26, 27, 28 and 29) and when overcoming a step (steps 30, 31 and 32).

The radius of action of robot 15 during cleaning is shown in figure 6. In the sequence of actions shown in figure 6, foot 9 remains still and foot 8 with cleaning device 12 is moved along cleaning surface 35, e.g. in a circle, in that robot 15 rotates about foot 9 using revolute joint 7. Instead thereof, cleaning device 12 can also be moved along a straight trajectory 33. Tilting joints 4 and 6 and central joint 3 are used for this purpose. A plurality of such straight cleaning trajectories 33 can be disposed next to one another in parallel. This is indicated by straight line 32.

Figure 7 shows another pattern of motion of mobile climbing robot 15. For example, the robot can follow two straight trajectories 33.1 and 33.2 which are disposed next to one another in parallel. For this purpose, robot 15 rotates using revolute joint 7 about foot 9 and,

simultaneously, the position of foot 8 is adjusted using central joint 3 and revolute joint 5.

Various possible patterns of motion that robot 15 can perform to clean the facade of a building will be explained in the following with reference to figures 8, 9 and 10.

Figure 8 shows a corner of a building, and cleaning robot 15 is located in the vicinity of this corner. As soon as foot 9 becomes securely adhered to the building facade, the cleaning procedure can be started. For this purpose, in a first step, the robot can clean a surface 39 parallel to the lower edge of the building, and, in a second step, a surface 40 that is parallel to the vertical building edge. Next, foot 8 with cleaning device 12 is moved slightly closer to foot 9, and the horizontal and vertical cleaning of the building facade is continued. Another pattern of motion of the cleaning robot is depicted in principle further above in figure 8. As indicated, the robot can also clean circular segments 36, 37 and 38.

To clean a larger surface on the facade of a building, robot 15 - as indicated in figure 9 using arrows 45 - can be moved and thereby clean the facade using overlapping, circular motions. The special geometry of robot 15 enables it to follow circular cleaning trajectories 41, 42 and 43 and square or rectangular cleaning trajectories 44.

Figure 10 shows how the robot, once it has cleaned a corner of the facade, continues cleaning in the vicinity

of the corner using circular cleaning trajectories. The illustration to the right in figure 10 shows how individual cleaning trajectories 46 to 51 can overlap when the cleaning robot follows circular cleaning trajectories 46 to 51.

Cleaning robot 15 can also clean a square surface 60, as shown in figure 11.

As shown in figure 12, if robot 15 is situated on a large surface, such as the facade of a building, a plurality of signal transmitters 70, 71 and 72 can be provided at various points of the building to transmit control signals and position signals to robot 15.

15

A portion of a building 73 is shown in a three-dimensional view in figure 13, wherein cleaning robot 15 is part of a service system. The service system comprises a windlass 74 which is disposed in the upper region of building 73 such that it can move along the building. Windlass 74 is used to lower a supply station 76. Supply station 76 can include e.g. an energy source for the drive of robot 15 and a supply container for cleaning agent. Cable 75 is used to hold supply device 76 and as a safety cable for robot 15. Robot 15 can be additionally equipped with a camera 14, by way of which information on the position of the robot can be obtained. Camera 14 can also be used to obtain information about the state of the facade.

30

The preceding description of the embodiments according to the present invention is used merely for illustrative purposes and not for the purpose of limiting the

invention. Various changes and modifications are possible within the scope of the invention without leaving the scope of the invention and the equivalents thereof. For example, the patterns of motion explained with reference to figures 8, 9 and 10 may also be used with other objects such as ships and solar installations, for example.

List of reference characters

	1	First leg
	2	Second leg
5	3	Central joint
	4	First foot joint for tilting
	5	First foot joint for rotation
	6	Second foot joint for tilting
	7	Second foot joint for rotation
10	8	First foot
	8.1	First suction cup
	8.2	Second suction cup
	8.3	Third suction cup
	9	Second foot
15	9.1	First suction cup
	9.2	Second suction cup
	9.3	Third suction cup
	10	Cleaning device
	11	Device mounting
20	12	Wiper
	13.1	First hose
	13.2	Second hose
	13.3	Third hose
	14	Camera
25	15	Climbing robot
	20	First step
	21 - 31	Steps
	32	Baseline
	33.1	Cleaning surface
30	33.2	Cleaning surface
	34	Position of the cleaning device
	35 - 40	Cleaning surfaces
	45	Direction of motion

	46 - 51	Cleaning surfaces
	60	Cleaning surface
	70	Signal transmitter
	71	Signal transmitter
5	72	Signal transmitter
	73	Building
	74	Windlass
	75	Cable
	76	Supply station

10

Claims

1. A mobile climbing robot,
 - comprising a central joint (3), by way of which a
 - 5 first leg (1) is connected to a second leg (2),
 - comprising a first foot (8) which is connected to
 - the first leg (1) by way of a first foot joint for
 - rotation (5) and a first foot joint for tilting (4),
 - comprising a second foot (9) which is connected to
 - 10 the second leg (2) by way of a second foot joint for
 - rotation (7) and a second foot joint for tilting (6),
 - and
 - comprising a mounting (11) for attaching an
 - implement (10; 12) disposed on a first foot (8).
- 15 2. The climbing robot according to claim 1,
wherein the first leg (1) and the second leg (2) are
offset laterally relative to one another.
3. The climbing robot according to claim 1 or 2,
wherein the first and/or the second foot (8, 9) are
- 20 equipped with a suction cup (8.1, 9.1).
4. The climbing robot according to claim 1, 2 or 3,
wherein the first and/or the second foot (8, 9) are
equipped with a magnet.
5. The climbing robot according to one of the claims 1
- 25 to 4,
wherein the first and/or the second foot (8, 9) are
equipped with a claw.
6. The climbing robot according to one of the claims 1
- to 5,
- 30 wherein the first and/or the second foot (8, 9) are
equipped with a drilling device.

7. The climbing robot according to one of the claims 1 to 6,
- wherein drives are provided for moving the legs (1, 2) and the feet (8, 9), and
5 - wherein the drives are designed as electrical or hydraulic drives.
8. The climbing robot according to one of the claims 1 to 7,
wherein the implement (10; 12) is a cleaning device.
- 10 9. The use of the climbing robot according to one of the claims 1 to 8,
for cleaning an object.
10. The use of the climbing robot according to claim 9,
wherein the object is a building, a bridge, a ship,
15 or a solar installation.
11. A service system having a climbing robot according to one of the claims 1 to 10,
- comprising a supply station (76) for supplying the climbing robot (15), and
20 - comprising a windlass (74) disposed on the object (73) for lowering the supply station (76) and securing the climbing robot (15).
12. The service system according to claim 11,
wherein the supply station (76) comprises a control
25 unit for controlling the climbing robot (15).
13. The service station according to claim 11 or 12,
wherein the supply station (76) comprises a supply container for cleaning agent.
14. The service system according to one of the claims 11 to 13,
30

wherein the supply station (76) comprises an energy source for the drive of the climbing robot (15).

15. The service system according to one of the claims 11 to 14,
- 5 - comprising a camera disposed on the climbing robot (15),
- comprising a display screen for displaying the information delivered by the camera, and
- 10 - comprising a control unit for controlling the climbing robot (15).