

## DESCRIPTION

Title of Invention  
IMAGE ENCODING METHOD AND IMAGE DECODING METHOD

5

## Technical Field

Embodiments described herein relate generally to a motion information compression method, image encoding method, and image decoding method in the encoding and  
10 decoding of a moving image.

## Background Art

Recently, an image encoding method having a greatly increased encoding efficiency has been recommended as ITU-T Rec. H.264 and ISO/IEC 14496-10  
15 (referred to as H.264 hereinafter) through the cooperation of ITU-T and ISO/IEC. In H.264, a prediction process, conversion process, and entropy encoding process are performed for each rectangular block (for example, each block of  $16 \times 16$  or  $8 \times$   
20  $8$  pixels). In the prediction process, motion compensation of performing prediction in the temporal domain is performed on a rectangular block to be encoded (an encoding target block) by referring to an already encoded frame (reference frame). In this  
25 motion compensation, it is necessary to encode motion information containing a motion vector as spatial shift information between the encoding target block and a block to be referred to in the reference frame, and

transmit the encoded motion information to a decoding side. When performing motion compensation by using a plurality of reference frames, it is also necessary to encode reference frame numbers in addition to the motion information. This sometimes increases the code amount of the motion information and reference frame numbers. There are also motion information prediction methods by which predicted motion information of an encoding target block is derived by referring to motion information of a reference frame, which is stored in a motion information memory (Patent Literature 1 and Non-Patent Literature 2), and the capacity of the motion information memory for storing motion information sometimes increases.

As an example of a method of reducing the capacity of the motion information memory, representative motion information is derived in a predetermined block and only the representative motion information is stored in the motion information memory in Non-Patent Literature 2.

#### Citation List

##### Patent Literature

Patent Literature 1: Japanese Patent No. 4020789

##### Non Patent Literature

Non-Patent Literature 1: J. Jung et al, "Temporal MV Predictor Modification for MV-Comp, Skip, Direct and Merge Schemes", Joint Collaborative Team on Video

Coding (JCT-VC) of ITU-T SG16 WP3 and ISO/IEC  
JTC1/SC29/WG11 Document, JCTVC-D164, January 2011

Non-Patent Literature 2: Yeping Su et al, "CE9:  
Reduced Resolution Storage of Motion Vector Data",  
5 Joint Collaborative Team on Video Coding (JCT-VC) of  
ITU-T SG16 WP3 and ISO/IEC JTC1/SC29/WG11 Document,  
JCTVC-D072, January 2011

#### Summary of Invention

##### Technical Problem

10 There is, however, a problem that if the predicted  
motion information derivation method disclosed in  
Non-Patent Literature 1 and the representative motion  
information derivation method disclosed in Non-Patent  
Literature 2 are different, the temporal correlation of  
15 the predicted motion information reduces, and as a  
consequence the code amount of the motion information  
increases.

The present embodiment has been made to solve the  
abovementioned problem, and has as its object to  
20 provide an image encoding apparatus and image decoding  
apparatus including an information compressing device  
capable of increasing the encoding efficiency.

##### Solution to Problem

25 In general, according to one embodiment, disclosed  
is a method of dividing an input image signal into  
pixel blocks, and performing inter-prediction on the  
divided pixel blocks. This method includes selecting

predicted motion information from a motion information buffer storing motion information in an encoded region, and predicting motion information of an encoding target block by using the predicted motion information. The method further includes acquiring representative motion information from a plurality of items of motion information in an encoded region in accordance with first information indicating a method of selecting the predicted motion information, thereby obtaining only the representative motion information.

#### Brief Description of Drawings

FIG. 1 is a block diagram schematically showing the arrangement of an image encoding apparatus according to the first embodiment.

FIG. 2A is a view for explaining a pixel block predictive encoding sequence.

FIG. 2B is a view for explaining an example of a pixel block size.

FIG. 2C is a view for explaining another example of the pixel block size.

FIG. 2D is a view for explaining still another example of the pixel block size.

FIG. 3A is a view for explaining an example of a pixel block in a coding tree unit.

FIG. 3B is a view for explaining another example of the pixel block in the coding tree unit.

FIG. 3C is a view for explaining still another

example of the pixel block in the coding tree unit.

FIG. 3D is a view for explaining still another example of the pixel block in the coding tree unit.

FIG. 4 is a block diagram schematically showing the arrangement of an entropy encoder shown in FIG. 1.

FIG. 5 is a view schematically showing the arrangement of a motion information memory shown in FIG. 1.

FIG. 6A is a view for explaining an example of an inter-prediction process executed by an inter-predictor shown in FIG. 1.

FIG. 6B is a view for explaining another example of the inter-prediction process executed by the inter-predictor shown in FIG. 1.

FIG. 7A is a view for explaining an example of a prediction unit.

FIG. 7B is a view for explaining another example of the prediction unit.

FIG. 7C is a view for explaining still another example of the prediction unit.

FIG. 7D is a view for explaining still another example of the prediction unit.

FIG. 7E is a view for explaining still another example of the prediction unit.

FIG. 7F is a view for explaining still another example of the prediction unit.

FIG. 7G is a view for explaining still another

example of the prediction unit.

FIG. 8 is a view for explaining a skip mode, merge mode, and inter mode.

5 FIG. 9 is a block diagram schematically showing the arrangement of a motion information encoder shown in FIG. 4.

FIG. 10 is a view for explaining examples of the position of a predicted motion information candidate with respect to an encoding target prediction unit.

10 FIG. 11 is a view for explaining another example of the position of the predicted motion information candidate with respect to the encoding target prediction unit.

15 FIG. 12 is a view showing an example of a list indicating the relationship between the block positions and indices  $Mvpidx$  of a plurality of predicted motion information candidates.

20 FIG. 13A is a view showing an example of a reference motion information acquisition position indicating the center of an encoding target prediction unit when the size of the prediction unit is  $32 \times 32$ .

25 FIG. 13B is a view showing an example of a reference motion information acquisition position indicating the center of an encoding target prediction unit when the size of the prediction unit is  $32 \times 16$ .

FIG. 13C is a view showing an example of a reference motion information acquisition position

indicating the center of an encoding target prediction unit when the size of the prediction unit is  $16 \times 32$ .

FIG. 13D is a view showing an example of a reference motion information acquisition position  
5 indicating the center of an encoding target prediction unit when the size of the prediction unit is  $16 \times 16$ .

FIG. 13E is a view showing an example of a reference motion information acquisition position  
10 indicating the center of an encoding target prediction unit when the size of the prediction unit is  $16 \times 8$ .

FIG. 13F is a view showing an example of a reference motion information acquisition position  
indicating the center of an encoding target prediction unit when the size of the prediction unit is  $8 \times 16$ .

15 FIG. 14A is a view showing another example of the reference motion information acquisition position indicating the center of an encoding target prediction unit when the size of the prediction unit is  $32 \times 32$ .

20 FIG. 14B is a view showing another example of the reference motion information acquisition position indicating the center of an encoding target prediction unit when the size of the prediction unit is  $32 \times 16$ .

25 FIG. 14C is a view showing another example of the reference motion information acquisition position indicating the center of an encoding target prediction unit when the size of the prediction unit is  $16 \times 32$ .

FIG. 14D is a view showing another example of the

reference motion information acquisition position  
indicating the center of an encoding target prediction  
unit when the size of the prediction unit is  $16 \times 16$ .

FIG. 14E is a view showing another example of the  
5 reference motion information acquisition position  
indicating the center of an encoding target prediction  
unit when the size of the prediction unit is  $16 \times 8$ .

FIG. 14F is a view showing another example of the  
reference motion information acquisition position  
10 indicating the center of an encoding target prediction  
unit when the size of the prediction unit is  $8 \times 16$ .

FIG. 15 is a view for explaining a spatial-domain  
reference motion information memory 501 and  
temporal-domain reference motion information memory  
15 502.

FIG. 16 is a flowchart showing an example of the  
operation of a motion information compressor shown in  
FIG. 1.

FIG. 17A is a view showing an example of a  
20 reference motion information acquisition position  
indicating the upper left end of an encoding target  
prediction unit when the size of the prediction unit is  
 $32 \times 32$ .

FIG. 17B is a view showing an example of a  
25 reference motion information acquisition position  
indicating the upper left end of an encoding target  
prediction unit when the size of the prediction unit is

32 × 16.

FIG. 17C is a view showing an example of a reference motion information acquisition position indicating the upper left end of an encoding target prediction unit when the size of the prediction unit is 16 × 32.

FIG. 17D is a view showing an example of a reference motion information acquisition position indicating the upper left end of an encoding target prediction unit when the size of the prediction unit is 16 × 16.

FIG. 17E is a view showing an example of a reference motion information acquisition position indicating the upper left end of an encoding target prediction unit when the size of the prediction unit is 16 × 8.

FIG. 17F is a view showing an example of a reference motion information acquisition position indicating the upper left end of an encoding target prediction unit when the size of the prediction unit is 8 × 16.

FIG. 18A is a view showing examples of a representative motion information position.

FIG. 18B is a view showing other examples of the representative motion information position.

FIG. 19 is a view showing examples of the centers of prediction units having different prediction sizes.

FIG. 20A is a view showing examples of a representative motion information position when the barycenter of a plurality of reference motion information acquisition positions of each motion information compression block is set as the  
5 representative motion information position.

FIG. 20B is a view showing other examples of the representative motion information position when the barycenter of a plurality of reference motion  
10 information acquisition positions of each motion information compression block is set as the representative motion information position.

FIG. 21A is a view showing an example of a representative motion information position.

15 FIG. 21B is a view showing another example of the representative motion information position.

FIG. 22 is a view showing a syntax structure according to an embodiment.

20 FIG. 23A is a view showing an example of a sequence parameter set syntax according to an embodiment.

FIG. 23B is a view showing another example of the sequence parameter set syntax according to the embodiment.

25 FIG. 24 is a view showing an example of a prediction unit syntax according to an embodiment.

FIG. 25 is a block diagram schematically showing

an image decoding apparatus according to the second embodiment.

FIG. 26 is a block diagram schematically showing an entropy decoder shown in FIG. 25.

5        FIG. 27 is a block diagram schematically showing a motion information decoder shown in FIG. 26.

#### Brief Description of Embodiments

10        An image encoding apparatus and image decoding apparatus according to each embodiment will be explained in detail below with reference to the accompanying drawings. Note that in the following explanation, the term "image" can appropriately be replaced by terms such as "picture", "pixel", "image signal", and "image data". Note also that in the  
15        following embodiments, portions denoted by the same reference number perform the same operation, so a repeated explanation will be omitted.

#### (First Embodiment)

20        The first embodiment is directed to an image encoding apparatus. An image decoding apparatus corresponding to the image encoding apparatus according to this embodiment will be explained in the second embodiment. This image encoding apparatus can be implemented by hardware such as a large-scale  
25        integration (LSI) chip, digital signal processor (DSP), or field-programmable gate array (FPGA). This image encoding apparatus can also be implemented by causing a

computer to execute an image encoding program.

As shown in FIG. 1, an image encoding apparatus 100 according to this embodiment includes a subtracter 101, orthogonal transformer 102, quantizer 103, inverse quantizer 104, inverse orthogonal transformer 105, adder 106, reference image memory 107, inter-predictor 108, motion information compressor 109, motion information memory 110, and entropy encoder 112. An encoding controller 114 and output buffer 113 are normally installed outside the image encoding apparatus 100.

The image encoding apparatus 100 shown in FIG. 1 divides each frame, each field, or each slice forming an input image signal 151 into a plurality of pixel blocks, performs predictive encoding on these divided pixel blocks, and outputs encoded data 163. In the following explanation, it is assumed, for the sake of simplicity, that the predictive encoding of pixel blocks is performed from the upper left corner to the lower right corner, as shown in FIG. 2A. Referring to FIG. 2A, encoded pixel blocks p are positioned above and on the left side of an encoding target pixel block c in a frame f as an encoding target.

The pixel block is an image processing unit such as a block of  $M \times N$  pixels (N and M being natural numbers), a coding unit, a macro block, a sub-block, or one pixel. Note that the pixel block basically means a

coding unit in the following explanation, but the pixel block can also be interpreted as the above-described meanings by appropriately replacing the terms. The coding unit is typically, for example, a block of 16 × 16 pixels, as shown in FIG. 2B, but may also be a block of 32 × 32 pixels, as shown in FIG. 2C, or a block of 64 × 64 pixels, as shown in FIG. 2D. The coding unit can also be a block of 8 × 8 pixels (not shown) or a block of 4 × 4 pixels (not shown). Furthermore, the coding unit need not be square. In the following explanation, the encoding target block or coding unit of the input image signal 151 will also be referred to as a "prediction target block". In addition, the encoding unit is not limited to a pixel block such as the coding unit, and it is also possible to use a frame, field, or slice, or a combination thereof.

FIGS. 3A, 3B, 3C, and 3D are views showing practical examples of the coding unit. FIG. 3A shows an example in which the size of the coding unit is 64 × 64 pixels ( $N = 32$ ).  $N$  represents the size of the coding unit as a reference. A size when the coding unit is divided is defined as  $N$ , and that when it is not divided is defined as  $2N$ . A coding tree unit has a quadtree structure. When the coding tree unit is divided, indices are allocated to four pixel blocks in Z-scan order. FIG. 3B shows an example in which quadtree division is performed on the block of

64 × 64 pixels shown in FIG. 3A. Numbers shown in FIG. 3B represent the ordinal numbers in Z-scan. It is also possible to further perform quadtree division on one quadtree index of the coding unit. The depth of division is defined as Depth. That is, FIG. 3A shows an example in which Depth = 0. FIG. 3C shows an example of a coding unit having a size of 32 × 32 pixels (N = 16) when Depth = 1. The largest unit of a coding tree unit like this is called a large coding tree unit or tree block, and the input image signal is encoded in raster scan order by using this unit, as shown in FIG. 2A.

On the basis of an encoding parameter input from the encoding controller 114, the image encoding apparatus 100 shown in FIG. 1 performs inter-prediction (also called inter-image prediction, inter-frame prediction, or motion compensation prediction) or intra-prediction (also called intra-image prediction or intra-frame prediction) (not shown) on the pixel block, thereby generating a predicted image signal 159. The image encoding apparatus 100 orthogonally transforms and quantizes a prediction error signal 152 between the pixel block (input image signal 151) and predicted image signal 159, generates the encoded data 163 by performing entropy encoding, and outputs the encoded data 163.

The image encoding apparatus 100 shown in FIG. 1

performs encoding by selectively applying a plurality of prediction modes having different block sizes and different methods of generating the predicted image signal 159. The methods of generating the predicted image signal 159 are roughly classified into two types: intra-prediction that performs prediction within an encoding target frame; and inter-prediction that performs prediction by using one reference frame or a plurality of temporally different reference frames.

Each element included in the image encoding apparatus 100 shown in FIG. 1 will be explained below.

The subtracter 101 obtains the prediction error signal 152 by subtracting, from the encoding target block of the input image signal 151, the predicted image signal 159 corresponding to the encoding target block. The subtracter 101 inputs the prediction error signal 152 to the orthogonal transformer 102.

The orthogonal transformer 102 obtains a transform coefficient 153 by performing orthogonal transformation such as a discrete cosine transform (DCT) on the prediction error signal 152 from the subtracter 101. The orthogonal transformer 102 outputs the transform coefficient 153 to the quantizer 103.

The quantizer 103 obtains a quantized transform coefficient 154 by quantizing the transform coefficient 153 from the orthogonal transformer 102. More specifically, the quantizer 103 performs quantization

in accordance with quantization information such as a quantization parameter and quantization matrix designated by the encoding controller 114. The quantization parameter indicates the fineness of quantization. The quantization matrix is used to weigh the quantization fineness for each component of the transform coefficient, but whether to use the quantization matrix is not essential to the embodiment. The quantizer 103 outputs the quantized transform coefficient 154 to the entropy encoder 112 and inverse quantizer 104.

The entropy encoder 112 performs entropy encoding (for example, Huffman encoding or arithmetic encoding) on various encoding parameters such as the quantized transform coefficient 154 from the quantizer 103, motion information 160 from the inter-predictor 108, prediction information 165 designated by the encoding controller 114, reference position information 164 from the encoding controller 114, and the quantization information, thereby generating the encoded data 163. Note that the encoding parameters are parameters necessary for decoding, such as the prediction information 165, information of the transform coefficient, and information of quantization. For example, the encoding controller 114 includes an internal memory (not shown), and this memory stores the encoding parameters. When encoding a prediction target

block, the encoding parameters of an already encoded pixel block adjacent to the prediction target block are used.

More specifically, as shown in FIG. 4, the entropy encoder 112 includes a parameter encoder 401, transform coefficient encoder 402, motion information encoder 403, and multiplexer 404. The parameter encoder 401 generates encoded data 451A by encoding the encoding parameters such as the prediction information 165 received from the encoding controller 114. The transform coefficient encoder 402 generates encoded data 451B by encoding the quantized transform coefficient 154 received from the quantizer 103.

The motion information encoder 403 encodes the motion information 160 received from the inter-predictor 108 by referring to reference motion information 166 received from the motion information memory 110 and reference position information 164 received from the encoding controller 114, thereby generating encoded data 451C. Details of the motion information encoder 403 will be described later.

The multiplexer 404 generates the encoded data 163 by multiplexing the encoded data 451A, 451B, and 451C. The generated encoded data 163 contains all parameters necessary for decoding, such as the information of the transform coefficient and the information of quantization, in addition to the motion information 160

and prediction information 165.

The encoded data 163 generated by the entropy encoder 112 is temporarily stored in the output buffer 113 after, for example, multiplication, and output at a proper output timing managed by the encoding controller 114. The encoded data 163 is output to, for example, a storage system (storage medium) (not shown) or a transmission system (communication line) (not shown).

The inverse quantizer 104 obtains a restored transform coefficient 155 by inversely quantizing the quantized transform coefficient 154 from the quantizer 103. More specifically, the inverse quantizer 104 performs inverse quantization in accordance with the quantization information used in the quantizer 103. The quantization information used in the quantizer 103 is loaded from the internal memory of the encoding controller 114. The inverse quantizer 104 outputs the restored transform coefficient 155 to the inverse orthogonal transformer 105.

The inverse orthogonal transformer 105 performs, on the restored transform coefficient 155 from the inverse quantizer 104, inverse orthogonal transformation such as an inverse discrete cosine transform corresponding to the orthogonal transformation performed in the orthogonal transformer 102, thereby obtaining a restored prediction error signal 156. The inverse orthogonal transformer 105

outputs the restored prediction error signal 156 to the adder 106.

5       The adder 106 generates a local decoded image signal 157 by adding the restored prediction error signal 156 and corresponding predicted image signal 159. The decoded image signal 157 is input to the reference image memory 107 through a deblocking filter or Wiener filter (not shown).

10       The reference image memory 107 stores a locally decoded filtered image signal 158. The inter-predictor 108 refers to the filtered image signal 158 as a reference image signal 158 when generating a predicted image as needed.

15       The inter-predictor 108 performs inter-prediction by using the reference image signal 158 saved in the reference image memory 107. More specifically, the inter-predictor 108 derives a motion difference (motion vector) by performing a block matching process between the prediction target block and reference image signal 20       158. Based on this motion vector, the inter-predictor 108 generates an inter-predicted image by performing motion compensation (interpolation for a motion at decimal precision). In H.264, interpolation can be performed up to 1/4-pixel precision. The derived 25       motion vector is entropically encoded as a part of the motion information 160.

      The motion information memory 110 includes the

motion information compressor 109. The motion  
information memory 110 reduces the information amount  
of the motion information 160 by appropriately  
performing a compression process, and temporarily  
5 stores the compressed motion information as the  
reference motion information 166. As shown in FIG. 5,  
the motion information memory 110 is stored for each  
frame (or slice), and the motion information memory 110  
further includes a spatial-domain reference motion  
10 information memory 501 for storing the motion  
information 160 on the same frame as the reference  
motion information 166, and a temporal-domain reference  
motion information memory 502 for storing the motion  
information 160 of an already encoded frame as the  
15 reference motion information 166. The motion  
information memory 110 can also include a plurality of  
temporal-domain reference motion information memories  
502 in accordance with the number of reference frames  
to be used by the encoding target frame for prediction.

20 Also, the spatial-domain reference motion  
information memory 501 and temporal-domain reference  
motion information memory 502 can be obtained by  
logically splitting a physically single memory.  
Furthermore, the spatial-domain reference motion  
25 information memory 501 can store only spatial-domain  
motion information necessary for a frame currently  
being encoded, and items of spatial-domain motion

information that are no longer necessary as reference information can sequentially be compressed and stored in the temporal-domain reference motion information memory 502.

5           The reference motion information 166 is stored for each predetermined region (for example, each 4 × 4 pixel block) in the spatial-domain reference motion information memory 501 and temporal-domain reference motion information memory 502. The reference motion  
10 information 166 further contains information indicating whether the region is encoded by inter-prediction (to be described later) or intra-prediction (to be described later). Also, even when a coding unit (or prediction unit) is inter-predicted by using the motion  
15 information 160 predicted from an encoded region without encoding the value of the motion vector in the motion information 160, such as in a skip mode or direct mode defined by H.264 or in a merge mode (to be described later), motion information of the coding unit  
20 (or prediction unit) is stored as the reference motion information 166.

          When the process of encoding the encoding target frame or slice is complete, the handling of the spatial-domain reference motion information memory 501  
25 of the frame is changed to that of the temporal-domain reference motion information memory 502 for a frame to be encoded next. In this step, to reduce the memory

capacity of the temporal-domain reference motion  
 information memory 502, the motion information 160  
 compressed by the motion information compressor 109 (to  
 be described later) is stored in the temporal-domain  
 5 reference motion information memory 502.

The prediction information 165 complies with a  
 prediction mode controlled by the encoding controller  
 114. As described above, it is possible to select  
 inter-prediction, or intra-prediction (not shown) or  
 10 inter-prediction in order to generate the predicted  
 image signal 159. It is also possible to further  
 select a plurality of modes for each of  
 intra-prediction and inter-prediction. The encoding  
 controller 114 determines one of the plurality of  
 15 prediction modes of intra-prediction and  
 inter-prediction as an optimum prediction mode, and  
 sets the prediction information 165.

For example, the encoding controller 114  
 determines an optimum prediction mode by using a cost  
 20 function indicated by equation (1) below:

$$K = SAD + \lambda \times OH \quad (1)$$

In equation (1) (to be called a simplified  
 encoding cost hereinafter), OH indicates the code  
 25 amount of the prediction information 160 (for example,  
 motion vector information or predicted block size  
 information), and SAD indicates a difference absolute  
 value sum (i.e., the cumulative sum of the absolute

values of the prediction error signal 152) between the prediction target block and predicted image signal 159. Also,  $\lambda$  indicates a Lagrange undetermined multiplier to be determined based on the value of the quantization information (quantization parameter), and K indicates the encoding cost. When using equation (1), a prediction mode that minimizes the encoding cost K is determined as an optimum prediction mode from the viewpoints of the generated code amount and prediction error. As a variation of equation (1), it is also possible to estimate the encoding cost from only the OH or SAD, or estimate the encoding cost by using a value obtained by performing a Hadamard transform on the SAD or an approximation of the value.

Furthermore, an optimum prediction mode can be determined by using a temporary encoding unit (not shown). For example, the encoding controller 114 determines an optimum prediction mode by using a cost function indicated by equation (2) below:

$$J = D + \lambda \times R \quad (2)$$

In equation (2), D indicates a square error sum (i.e., encoding distortion) between a prediction target block and locally decoded image, R indicates a code amount estimated by temporary encoding for a prediction error between the prediction target block and the predicted image signal 159 of the prediction mode, and J indicates the encoding cost. When calculating the

encoding cost  $J$  (to be called a detailed encoding cost hereinafter) of equation (2), a temporary encoding process and local decoding process are necessary for each prediction mode, so the circuit scale or  
5 calculation amount increases. On the other hand, the encoding cost  $J$  is calculated based on a more accurate encoding distortion and more accurate code amount.

This facilitates maintaining a high encoding efficiency by accurately determining an optimum prediction mode.  
10 Note that as a variation of equation (2), it is also possible to estimate the encoding cost from only the  $R$  or  $D$ , or estimate the encoding cost by using an approximate value of the  $R$  or  $D$ . Furthermore, a hierarchical use of these costs is also possible. The  
15 encoding controller 114 can also previously decrease the number of candidates of prediction modes for performing determination using equation (1) or (2), based on information (for example, prediction modes of surrounding pixel blocks or the result of image  
20 analysis) preobtained for a prediction target block.

As a modification of this embodiment, it is possible to further reduce the number of prediction mode candidates while maintaining the encoding performance, by performing two-step mode determination  
25 combining equations (1) and (2). The simplified encoding cost indicated by equation (1) requires no local decoding process unlike equation (2), and hence

can be calculated at high speed. The image encoding apparatus of this embodiment has more prediction modes than those of H.264, so mode determination using the detailed encoding cost is unrealistic. As a first  
5 step, therefore, mode determination using the simplified encoding cost is performed on prediction modes usable for the corresponding pixel block, thereby deriving prediction mode candidates.

Since the correlation between the simplified  
10 encoding cost and detailed encoding cost increases as the value of the quantization parameter defining the roughness of quantization increases, the number of prediction mode candidates is changed by using this property.

15 Next, the prediction process of the image encoding apparatus 100 will be explained.

Although not shown, a plurality of prediction modes are prepared for the image encoding apparatus 100 shown in FIG. 1, and the method of generating the  
20 predicted image signal 159 and the motion compensation block size change from one prediction mode to another. The methods by which the predictor 108 generates the predicted image signal 159 are roughly classified into intra-prediction (intra-frame prediction) that  
25 generates a predicted image by using the reference image signal 158 of the encoding target frame (or field), and inter-prediction (inter-frame prediction)

that generates a predicted image by using the reference image signal 158 of one or more encoded reference frames (or reference fields). The predictor 108 generates the predicted image signal 159 of the encoding target block by selectively switching intra-prediction and inter-prediction.

FIG. 6A shows an example of inter-prediction. Inter-prediction is typically executed for each prediction unit, and each prediction unit can have unique motion information 160. In inter-prediction, as shown in FIG. 6A, the predicted image signal 159 is generated by using the reference image signal 158 of a block 602 in a position spatially shifted, in accordance with the motion vector contained in the motion information 160, from a block 601 which is a pixel block in an already encoded reference frame (for example, an immediately preceding encoded frame) and exists in the same position as that of an encoding target prediction unit. That is, the predicted image signal 159 is generated by using the reference image signal 158 of the block 602 in the reference frame, which is specified by the position (coordinates) of the encoding target block and the motion vector contained in the motion information 160.

In inter-prediction, motion compensation at small-number-of-pixel precision (for example, 1/2-pixel precision or 1/4-pixel precision) is possible, and the

value of an interpolating pixel is generated by filtering the reference image signal 158. For example, an interpolation process of up to 1/4-pixel precision can be performed on a luminance signal in H.264. This interpolation process can be executed by using arbitrary filtering instead of filtering defined by H.264.

Note that in inter-prediction, it is possible to use not only an immediately preceding reference frame, as shown in FIG. 6A, but also any already encoded reference frame, as shown in FIG. 6B. When the reference image signals 158 of a plurality of reference frames having different time positions are stored, information indicating the time position of the reference image signal 158 from which the predicted image signal 159 is generated is represented by a reference frame number. The motion information 160 contains this reference frame number. The reference frame number can be changed for each region (for example, each picture, slice, or block). That is, different reference frames can be used for different prediction units. As an example, when an immediately preceding encoded reference frame is used in prediction, the reference frame number of this region is set to zero. When an encoded reference frame two frames before an encoding target frame is used in prediction, the reference frame number of this region

is set to 1. As another example, when the reference image signal 158 of only one frame is stored in the reference image memory 107 (when only one reference frame is stored), the reference frame number is always set to zero.

In addition, it is possible to selectively use a size suitable for an encoding target block from a plurality of prepared prediction unit sizes. For example, motion compensation can be performed for each prediction unit obtained by dividing coding tree units, as shown in FIGS. 7A, 7B, 7C, 7D, 7E, 7F, and 7G. It is also possible to perform motion compensation for each prediction unit divided into a shape other than a square, as shown in FIG. 7F or 7G.

As described previously, the motion information 160 of an encoded pixel block (for example, a block of  $4 \times 4$  pixels) in an encoding target frame to be used in inter-prediction is stored as the reference motion information 166. Therefore, the shape and motion vector of an optimum motion compensation block and the reference frame number can be used in accordance with the local property of the input image signal 151. It is also possible to freely combine coding units and prediction units. When the coding unit is a block of  $64 \times 64$  pixels, each of four coding tree units (blocks of  $32 \times 32$  pixels) obtained by dividing the block of  $64 \times 64$  pixels can further be divided into four blocks.

This makes it possible to hierarchically use blocks of 16 × 16 pixels from the block of 64 × 64 pixels. It is similarly possible to hierarchically use blocks of 8 × 8 pixels from the block of 64 × 64 pixels. When the  
5 prediction unit is obtained by dividing the coding tree unit into four blocks, it is possible to execute a hierarchical motion compensation process from a block of 64 × 64 pixels to blocks of 4 × 4 pixels.

Furthermore, in inter-prediction, bidirectional  
10 prediction using two kinds of motion compensation can be executed on an encoding target pixel block. In H.264, a new predicted image signal (not shown) is obtained by performing two kinds of motion compensation on an encoding target pixel block, and calculating the  
15 weighted average of two kinds of predicted image signals. In this bidirectional prediction, the two kinds of motion compensation will be referred to as list 0 prediction and list 1 prediction.

<Explanation of Skip Mode, Merge Mode, and Inter Mode>

20 The image encoding apparatus 100 according to this embodiment uses a plurality of prediction modes having different encoding processes, as shown in FIG. 8. Referring to FIG. 8, the skip mode is a mode in which only the syntax of a predicted motion information  
25 position 954 (described later) is encoded, and other syntaxes are not encoded. The merge mode is a mode in which only the syntax of the predicted motion

information position 954 and the transform coefficient information 153 are encoded, and other syntaxes are not encoded. The inter mode is a mode in which the syntax of the predicted motion information position 954,  
5 differential motion information 953 (to be described later), and the transform coefficient information 153 are encoded. These modes are switched by the prediction information 165 controlled by the encoding controller 114.

10 <Motion Information Encoder 403>

The motion information encoder 403 will be explained below with reference to FIG. 9.

The motion information encoder 403 includes a reference motion vector acquisition unit 901, predicted  
15 motion vector selection switch (to be also referred to as a predicted motion information selection switch) 902, subtracter 903, differential motion information encoder 904, predicted motion information position encoder 905, and multiplexer 906.

20 The reference motion vector acquisition unit 901 receives the reference motion information 166 and reference position information 164, and generates at least one predicted motion information candidate (also referred to as a predicted motion vector candidate) 951  
25 (951A, 951B, . . .). FIGS. 10 and 11 illustrate examples of the position of the predicted motion information candidate 951 with respect to a target

prediction unit. FIG. 10 shows the positions of prediction units spatially adjacent to the target prediction unit. AX ( $X = 0$  to  $nA-1$ ) indicates an adjacent prediction unit on the left side of the target prediction unit, BY ( $Y = 0$  to  $nB-1$ ) indicates an adjacent prediction unit above the target prediction unit, and C, D, and E respectively indicate adjacent prediction units at the upper right corner, upper left corner, and lower left corner of the target prediction unit. FIG. 11 shows the position of a prediction unit in an already encoded reference frame with respect to the encoding target prediction unit. In FIG. 11, Col indicates a prediction unit, which exists in the same position as that of the encoding target prediction unit, in the reference frame. FIG. 12 shows an example of a list indicating the relationship between the block positions and indices Mvpidx of a plurality of predicted motion information candidates 951. Indices 0 to 2 of Mvpidx indicate the predicted motion vector candidates 951 positioned in the spatial domain, and index 3 of Mvpidx indicates the predicted motion vector candidate 951 positioned in the temporal domain. Prediction unit position A is the position of a prediction unit of inter-prediction, i.e., a prediction unit having the reference motion information 166, in AX, as shown in FIG. 10, and the value of X is smallest at prediction unit position A. Prediction unit

position B is the position of a prediction unit of inter-prediction, i.e., a prediction unit having the reference motion information 166, in BY, as shown in FIG. 10, and the value of Y is smallest in prediction unit position B. When prediction unit position C is not inter-prediction, the reference motion information 166 in prediction unit position D is replaced with the reference motion information 166 in prediction unit position C. When prediction unit positions C and D are not inter-prediction, the reference motion information 166 in prediction unit position E is replaced with reference motion information 166 in prediction unit position C.

If the size of the encoding target prediction unit is larger than that of the smallest prediction unit, prediction unit position Col may store a plurality of items of reference motion information 166 in the temporal-domain reference motion information memory 502. In this case, the reference motion information 166 in the prediction unit at position Col is acquired in accordance with the reference position information 164. The acquisition position of the reference motion information 166 in the prediction unit at position Col will be referred to as a reference motion information acquisition position hereinafter. FIGS. 13A, 13B, 13C, 13D, 13E, and 13F illustrate examples of the reference motion information acquisition position for each

encoding target prediction unit size ( $32 \times 32$  to  $16 \times 16$ ) when the reference position information 164 indicates the center of the prediction unit in position Col. In FIGS. 13A, 13B, 13C, 13D, 13E, and 13F, each block indicates a  $4 \times 4$  prediction unit, and a circle indicates the position of a  $4 \times 4$  prediction unit to be acquired as the predicted motion information candidate 951. FIGS. 14A, 14B, 14C, 14D, 14E, and 14F illustrate other examples of the reference motion information acquisition position. Referring to FIGS. 14A, 14B, 14C, 14D, 14E, and 14F, no  $4 \times 4$  prediction unit exists in the position of a circle, so the predicted motion information candidate 951 is generated by a predetermined method such as the average or median of the reference motion information 166 in four  $4 \times 4$  prediction units adjacent to the circle. As still another example of the reference motion information acquisition position, the reference motion information 166 of a  $4 \times 4$  prediction unit positioned at the upper left corner of the prediction unit in position Col may also be used as the predicted motion information candidate 951. In a case other than the abovementioned examples, it is possible to generate the predicted motion information candidate 951 by using any position and any method, provided that the method is a predetermined method.

Note that if no reference motion information 166

exists, the motion information 160 having a zero vector is output as the predicted motion information candidate 951.

5 By the processing described above, at least one predicted motion information candidate 951 is output from the reference motion block. If the reference frame number of the aforementioned predicted motion information candidate 951 is different from that of the encoding target prediction unit, the predicted motion  
10 information candidate 951 can be scaled by using the reference frame number of the predicted motion information candidate 951 and that of the encoding target prediction unit.

The predicted motion information selection switch  
15 902 selects one of the plurality of predicted motion information candidates 951 in accordance with a command from the encoding controller 114, and outputs the predicted motion information 952. The predicted motion information selection switch 902 may also output the  
20 predicted motion information position information 954 (to be described later). The abovementioned selection can be performed by using an evaluation function such as equation (1) or (2). The subtracter 903 subtracts the predicted motion vector information 952 from the  
25 motion information 160, and outputs the differential motion information 953 to the differential motion information encoder 904. The differential motion

information encoder 904 encodes the differential motion information 953, and outputs encoded data 960A. Note that in the skip mode and merge mode, the differential motion information encoder 904 need not encode the differential motion information 953.

The predicted motion information position encoder 905 encodes the predicted motion information position information 954 (Mvpidx) indicating which predicted motion information candidate 951 is selected from the list shown in FIG. 12, and outputs encoded data 960B. The predicted motion information position information 954 is encoded by using fixed-length encoding or variable-length encoding generated from the total number of predicted motion information candidates 951. Variable-length encoding may also be performed using the correlation with adjacent blocks. Furthermore, if a plurality of predicted motion information candidates 951 have identical information, it is also possible to encode the predicted motion information position information 954 by forming a code table from the total number of predicted motion information candidates 951 from which the identical predicted motion information candidates 951 are deleted. Also, if the total number of predicted motion information candidates 951 is 1, it is determined that the corresponding predicted motion information candidate 951 is the predicted motion information 952, so the predicted motion information

position information 954 need not be encoded.

In addition, in the skip mode, merge mode, and inter mode, the methods of deriving the predicted motion information candidate 951 need not be the same, and it is possible to independently set the methods of deriving the predicted motion information candidate 951. This embodiment will be explained by assuming that the same method of deriving the predicted motion information candidate 951 is used in the skip mode and merge mode, and a different method of deriving the predicted motion information candidate 951 is used in the merge mode.

<Details of Motion Information Compressor 109>

First, the motion information compression process will be explained with reference to FIG. 15. In FIG. 15, the reference motion information 166 of the spatial-domain reference motion information memory 501 is compressed and stored in the temporal-domain reference motion information memory 502. The reference motion information 166 which is stored in the representative motion information position for each motion information compression block (in FIG. 15, a block of  $16 \times 16$  pixels) in the spatial-domain reference motion information memory 501 is stored in the temporal-domain reference motion information memory 502. When performing the above-described motion information encoding process, the reference motion

information 166 stored in the above-described reference motion information acquisition position is set as the predicted motion information candidate 951. In this case, it is also possible to assume that the motion information compression block virtually has the same reference motion information 166, and set the reference motion information 166 stored in the above-described reference motion information position as the predicted motion information candidate 951 (the same predicted motion information candidate 951 is derived).

Next, the motion information compressor 109 will be explained with reference to the flowchart shown in FIG. 16. When the process of encoding a frame (or an arbitrary unit such as a slice or coding unit) is complete, the motion information compression 109 compresses the motion information 160 and stores the motion information 160 in the temporal-domain reference motion information memory 502.

First, the reference position information 164 is acquired from the encoding controller 114 (step S1601), and a frame is divided into motion information compression blocks as compression units of the motion information 160 (step S1602). The motion information compression block is a pixel block larger than a unit (typically, a block of  $4 \times 4$  pixels) by which the motion information 160 is stored by the motion compensation process, and is typically a block of

16 × 16 pixels. The motion information compression block may also be a block of 64 × 64 pixels, a block of 32 × 32 pixels, a block of 8 × 8 pixels, a rectangular pixel block, or a pixel region having an arbitrary shape.

Then, a representative motion information position is generated in accordance with the reference position information 164 (step S1603). As an example of generating a representative motion information position, when the motion information compression block is a block of 16 × 16 pixels, the reference motion information acquisition position when the prediction unit size is 16 × 16, as shown in FIGS. 13D, 14D, and 17D, is set as the representative motion information position. Subsequently, the reference motion information 166 of the generated representative motion information position is set as representative motion information (step S1604), and the representative motion information is stored in the temporal-domain reference motion information memory (step S1605). Steps S1604 and S1605 described above are executed for all motion information compression blocks.

When the unit for storing the motion information 160 is an  $M \times M$  block and the size of the motion information compression block is  $N \times N$  ( $N$  is a multiple of  $M$ ), the capacity of the reference motion information memory can be reduced to  $(M \times M)/(N \times N)$  by executing

the aforementioned motion information compression process.

<Other Embodiments of Representative motion information Position>

5           As another example of generating a representative motion information position, the central position of a plurality of reference motion information acquisition positions may also be used as the representative motion information position. FIGS. 18A and 18B show the  
10           representative motion information position of each motion compression block having a size of  $16 \times 16$ .

FIG. 18A shows representative motion information positions when reference motion information acquisition positions are the positions shown in FIG. 13D.  
15           Likewise, FIG. 18B shows representative motion information positions when reference motion information acquisition positions are the positions shown in FIG. 17D. Symbols ● in FIGS. 18A and 18B indicate reference motion information acquisition positions when  
20           a prediction unit is a  $16 \times 16$  block. A representative motion information position indicated by × is placed in the central position (also called the barycentric position) of four reference motion information acquisition positions.

25           As still another example of generating a representative motion information position, it is also possible to use a reference motion information

acquisition position for each size of a plurality of prediction units as the reference position information 164, and generate a representative motion information position from a plurality of reference motion information acquisition positions.

As an example of generating a representative motion information position, it is also possible to use a reference motion information acquisition position for each size of a plurality of prediction units as the reference position information 164, and generate a representative motion information position from a plurality of reference motion information acquisition positions. FIG. 19 shows the center (reference motion information acquisition position) of each prediction unit having a prediction unit size of  $16 \times 16$  or more, when a tree block is a block of  $64 \times 64$  pixels.

As another example of generating a representative motion information position, a representative motion information position can also be set by using a reference motion information acquisition position set for each motion information compression block.

FIG. 20A shows an example when the barycenter of a plurality of reference motion information acquisition positions in each motion information compression block is set as a representative motion information position. If the barycentric position does not match the position of a  $4 \times 4$  block, it is possible to set the nearest

4 × 4 block as a representative motion information position, or generate the reference motion vector 166 of the barycentric position by using interpolation such as bi-linear interpolation.

5           FIG. 20B shows an example in which one of a plurality of reference motion information acquisition positions is selected for each motion information compression block, and set as a representative motion information position.

10           Furthermore, FIGS. 21A and 21B illustrate examples when motion information compression blocks have the same reference motion information acquisition position in a tree block. Since all motion information compression blocks have the same representative motion  
15           information position, representative motion information positions need not be switched in accordance with a position in the tree block. The representative motion information position need not be those shown in  
FIGS. 21A and 21B, and can be any position such as the  
20           upper left corner or upper right corner in the motion information compression block.

          As an example of generating a representative motion information position, a representative motion information position may also be indicated by using  
25           BlkIdx indicating positions of 4 × 4 blocks in a motion information compression block in Z-scan order. When the size of the motion information compression block is

16 × 16, the representative motion information position shown in FIG. 21A is equivalent to the position of BlkIdx = 12. Also, the representative motion information position shown in FIG. 21B is equivalent to the position of BlkIdx = 15.

As another example of the motion information compression process, the motion information compression process may also include reference frame numbers in order to reduce the memory capacity for reference frame numbers. In this case, a reference frame number stored in a representative motion information position is stored in the memory capacity for reference frame numbers. Accordingly, the spatial-domain reference motion information memory 501 and temporal-domain reference motion information memory 502 shown in FIG. 5 store reference frame numbers in addition to the motion vector information.

As still another example of the motion information compression process, when the motion information compression process does not include any reference frame number, motion vector information in motion information in a representative motion information position can be scaled by using a reference frame number, and stored in the motion information memory 110. A typical example of the scaling process is a linear scaling process based on reference frame number zero. That is, if the reference frame number is not

zero, the linear scaling process is performed such that the motion vector information refers to a reference frame corresponding to reference frame number zero.

The basis of the above-described scaling process may also be a value other than reference frame number zero. If division occurs when performing the above-described linear scaling process, this division can be implemented by looking up a division process table formed beforehand.

When the size of the motion information compression block is not a  $16 \times 16$  block, a representative motion information position is generated by using the same processing as described above. As an example, when the size of the motion information compression block is  $64 \times 64$ , a reference motion information acquisition position in a  $64 \times 64$  prediction unit is set as a representative motion information position. As another example, a representative motion information position in the  $16 \times 16$  motion information compression block shown in, for example, FIGS. 21A and 21B can be scaled in the horizontal and vertical directions in accordance with the motion information compression block size, and the scaled position can be set as a representative motion information position.

If no reference motion information exists because a representative motion information position is outside

a picture or slice, a position where reference motion information can be acquired in a motion information compression block, for example, the upper left corner of the motion information compression block can be set  
5 as a new representative motion information position. Also, if no reference motion information exists because a representative motion information position is a region to which intra-prediction is applied, a new representative motion information position can be set  
10 by executing the same processing.

#### <Syntax Configuration>

The syntax used by the image encoding apparatus  
100 shown in FIG. 1 will be explained below.

The syntax indicates the structure of encoded data  
15 (for example, the encoded data 163 shown in FIG. 1) obtained when the image encoding apparatus encodes moving image data. When decoding this encoded data, an image decoding apparatus interprets the syntax by referring to the same syntax structure. FIG. 22 shows  
20 an example of a syntax 2200 used by the image encoding apparatus shown in FIG. 1.

The syntax 2200 includes three parts, i.e., a high level syntax 2201, slice level syntax 2202, and coding tree level syntax 2203. The high level syntax 2201  
25 contains syntax information of layers higher than a slice. The slice is a rectangular region or continuous region included in a frame or field. The slice level

syntax 2202 contains information necessary to decode each slice. The coding tree level syntax 2203 contains information necessary to decode each coding tree (i.e., each coding tree unit). These parts each further  
5 include detailed syntaxes.

The high level syntax 2201 includes sequence and picture level syntaxes such as a sequence parameter set syntax 2204 and picture parameter set syntax 2205. The slice level syntax 2202 includes a slice header syntax  
10 2206 and slice data syntax 2207. The coding tree level syntax 2203 includes a coding tree unit syntax 2208, transform unit syntax 2209, and prediction unit syntax 2210.

The coding tree unit syntax 2208 can have a  
15 quadtree structure. More specifically, the coding tree unit syntax 2208 can recursively be called as a syntax element of the coding tree unit syntax 2208. That is, one coding tree unit can be subdivided by a quadtree. Also, the coding tree unit syntax 2208 includes the  
20 transform unit syntax 2209 and prediction unit syntax 2210. The transform unit syntax 2209 and prediction unit syntax 2210 are called in each coding tree unit syntax 2208 at the endmost portion of the quadtree. Information of prediction is described in the  
25 prediction unit syntax 2210. Information of inverse orthogonal transformation and quantization is described in the transform unit syntax 2209.

FIG. 23 shows examples of the sequence parameter set syntax 2204 according to this embodiment. The flag `motion_vector_buffer_comp_flag` shown in FIGS. 23A and 23B is a syntax indicating whether motion information compression according to this embodiment is valid/invalid for the sequence. If `motion_vector_buffer_comp_flag` is 0, motion information compression according to this embodiment is invalid for the sequence. Accordingly, the processing of the motion information compressor shown in FIG. 1 is skipped. As an example, if `motion_vector_buffer_comp_flag` is 1, motion information compression according to this embodiment is valid for the sequence. The value `motion_vector_buffer_comp_ratio_log2` shown in FIGS. 23A and 23B is information indicating the unit of the motion information compression process, and is shown when `motion_vector_buffer_comp_flag` is 1. For example, `motion_vector_buffer_comp_ratio_log2` indicates information of the size of the motion information compression block according to this embodiment, and a value obtained by multiplying the smallest unit of motion compensation by  $2^{(\text{motion\_vector\_buffer\_comp\_ratio\_log2})}$  is the size of the motion information compression block. An example in which the smallest unit of motion compensation is a block of  $4 \times 4$  pixels, i.e., the reference motion

information memory is stored for each block of  $4 \times 4$  pixels, will be described below. When motion\_vector\_buffer\_comp\_ratio\_log2 is 1, the size of the motion information compression block according to this embodiment is a block of  $8 \times 8$  pixels. Similarly, when motion\_vector\_buffer\_comp\_ratio\_log2 is 2, the size of the motion information compression block according to this embodiment is a block of  $16 \times 16$  pixels. The value motion\_vector\_buffer\_comp\_position shown in FIG. 23B is information indicating a representative motion information position in the motion information compression block, and is shown when motion\_vector\_buffer\_comp\_flag is 1. For example, motion\_vector\_buffer\_comp\_position may also indicate a reference motion information position in the motion information compression block, as shown in FIGS. 21A and 21B, or indicate a reference motion information position in each motion information compression block, as shown in FIGS. 20A and 20B. Also, motion\_vector\_buffer\_comp\_position can further indicate the center of a plurality of blocks.

As another example, the validity/invalidity of prediction according to this embodiment may also be defined for each local region inside the slice in syntaxes of layers (for example, the picture parameter syntax, slice level syntax, coding tree unit, and

transform unit) below motion\_vector\_buffer\_comp\_flag,  
 motion\_vector\_buffer\_comp\_ratio\_log2, and  
 motion\_vector\_buffer\_comp\_position.

FIG. 24 shows an example of the prediction unit  
 5 syntax. The flag skip\_flag shown in FIG. 24 indicates  
 whether the prediction mode of a coding unit to which  
 the prediction unit syntax belongs is the skip mode.  
 If skip\_flag is 1, it indicates that syntaxes (the  
 coding unit syntax, prediction unit syntax, and  
 10 transform unit syntax) other than the prediction motion  
 information position information 954 are not encoded.  
 NumMVPCand(L0) and NumMVPCand(L1) respectively indicate  
 the numbers of predicted motion information candidates  
 951 in list 0 prediction and list 1 prediction. If the  
 15 predicted motion information candidate 951 exists  
 (NumMVPCand(LX) > 0, X = 0 or 1), mvp\_idx\_IX indicating  
 the predicted motion information position information  
 954 is encoded.

If skip\_flag is 0, it indicates that the  
 20 prediction mode of a coding unit to which the  
 prediction unit syntax belongs is not the skip mode.  
 NumMergeCandidates indicates the number of predicted  
 motion information candidates 951 derived in FIG. 12 or  
 the like. If the predicted motion information  
 25 candidate 951 exists (NumMergeCandidates > 0),  
 merge\_flag as a flag indicating whether the prediction  
 unit is the merge mode is encoded. When the value of

merge\_flag is 1, the flag indicates that the prediction unit is the merge mode. If the value is 0, the flag indicates that the prediction unit uses the inter mode. If merge\_flag is 1 and two or more predicted motion information candidates 951 exist (NumMergeCandidates > 1), merge\_idx as the predicted motion information 952 indicating a block of the predicted motion information candidates 951 from which merge is started is encoded.

If merge\_flag is 1, prediction unit syntaxes other than merge\_flag and merge\_idx need not be encoded.

If merge\_flag is 0, it indicates that the prediction unit is the inter mode. In the inter mode, mvd\_IX (X = 0 or 1) indicating differential motion vector information contained in the differential motion information 953 and reference frame number ref\_idx\_IX are encoded, and, in the case of a B slice, inter\_pred\_idc indicating whether the prediction unit is unidirectional prediction (list 0 or list 1) or bidirectional prediction is encoded. In addition, NumMVPCand(L0) and NumMVPCand(L1) are acquired as in the slip mode. If the predicted motion information candidate 951 exists (NumMVPCand(LX) > 0, X = 0 or 1), mvp\_idx\_IX indicating the predicted motion information position information 954 is encoded.

The foregoing is the syntax configuration according to this embodiment.

(Second Embodiment)

The second embodiment is directed to an image decoding apparatus. The image encoding apparatus corresponding to the image decoding apparatus according to this embodiment is explained in the first embodiment. That is, the image decoding apparatus according to this embodiment decodes, for example, encoded data generated by the image encoding apparatus according to the first embodiment.

As shown in FIG. 25, the image decoding apparatus according to this embodiment includes an entropy decoder 2501, inverse quantizer 2502, inverse orthogonal transformer 2503, adder 2504, reference image memory 2505, inter-predictor 2506, reference motion information memory 2507, reference motion information compressor 2508, and decoding controller 2510.

The image decoding apparatus shown in FIG. 25 decodes encoded data 2550, stores a decoded image signal 2554 in an output buffer 2511, and outputs the decoded image signal 2554 as an output image. The encoded data 2550 is output from, for example, the image encoding apparatus shown in FIG. 1, and input to an image decoding apparatus 2500 through a storage system (not shown) or transmission system (not shown).

The entropy decoder 2501 performs decryption based on syntaxes in order to decode the encoded data 2550.

The entropy decoder 2501 sequentially entropically decodes a code sequence of each syntax, and reproduces encoding parameters, such as motion information 2559 and a quantized transform coefficient 2551, of an encoding target block. The encoding parameters are parameters necessary to decode, for example, prediction information, information of a transform coefficient, and information of quantization.

More specifically, as shown in FIG. 26, the entropy decoder 2501 includes a separator 2601, parameter decoder 2602, transform coefficient decoder 2603, and motion information decoder 2604. The separator 2601 separates the encoded data 2550, and outputs encoded data 2651A of a parameter to the parameter decoder 2602, encoded data 2651B of a transform coefficient to the transform coefficient decoder 2603, and encoded data 2651C of motion information to the motion information decoder 2604. The parameter decoder 2602 decodes an encoding parameter 2651A such as prediction information and outputs the encoding parameter 2570 to the decoding controller 2510. The transform coefficient decoder 2603 receives the encoded data 2651B, decodes the transform coefficient information 2551, and outputs the decoded information to the inverse quantizer 2502.

The motion information decoder 2604 receives the encoded data 2651C from the separator 2601, reference

position information 2560 from the decoding controller 2510, and reference motion information 2558 from the reference motion information memory 2507, and outputs the motion information 2559. The output motion  
5 information 2559 is input to the inter-predictor 2506.

As shown in FIG. 27, the motion information decoder 2604 includes a separator 2701, a differential motion information decoder 2702, predicted motion information position decoder 2703, reference motion  
10 information acquisition unit 2704, predicted motion information selection switch 2705, and adder 2706.

The encoded data 2651C of motion information is input to the separator 2701, and separated into encoded data 2751 of differential motion information and  
15 encoded data 2752 of a predicted motion information position. The differential motion information encoder 2702 receives the encoded data 2751 of differential motion information, and decodes differential motion information 2753. The adder 2706 adds the differential  
20 motion information 2753 to predicted motion information 2756 (to be described later), and outputs motion information 2759. The predicted motion information position decoder 2703 receives the encoded data 2752 of a predicted motion information position, and decodes a  
25 predicted motion information position 2754.

The predicted motion information selection switch 2705 receives the predicted motion information position

2754, and selects the predicted motion information 2756 from predicted motion information candidates 2755. The predicted motion information position information 2560 is decoded by using fixed-length decoding or  
5 variable-length decoding generated from the number of predicted motion information candidates 2755. Variable-length decoding may also be performed using the correlation with adjacent blocks. Furthermore, if a plurality of predicted motion information candidates  
10 2755 are identical, the predicted motion information position information 2560 can be decoded based on a code table generated from the total number of predicted motion information candidates 2755 from which the identical candidates are deleted. In addition, if the  
15 total number of predicted motion information candidates 2755 is 1, the corresponding predicted motion information candidate 2755 is determined as the predicted motion information 2556, so the predicted motion information position information 2754 need not  
20 be decoded.

The arrangement and processing contents of the predicted motion information acquisition unit 2704 are the same as those of the predicted motion information acquisition unit 901 explained in the first embodiment.

25 The reference motion information acquisition unit 2704 receives the reference motion information 2558 and reference position information 2560, and generates at

least one predicted motion information candidate 2755  
2755A, 2755B, . . .). FIGS. 10 and 11 illustrate  
examples of the position of the predicted motion  
information candidate 2755 with respect to a decoding  
5 target prediction unit. FIG. 10 shows the positions of  
prediction units spatially adjacent to the decoding  
target prediction unit. AX ( $X = 0$  to  $nA-1$ ) indicates  
an adjacent prediction unit on the left side of the  
target prediction unit, BY ( $Y = 0$  to  $nB-1$ ) indicates an  
10 adjacent prediction unit above the target prediction  
unit, and C, D, and E respectively indicate adjacent  
prediction units at the upper right corner, upper left  
corner, and lower left corner of the target prediction  
unit. FIG. 11 shows the position of a prediction unit  
15 in an already decoded reference frame with respect to  
the decoding target prediction unit. In FIG. 11, Col  
indicates a prediction unit, which exists in the same  
position as that of the decoding target prediction  
unit, in the reference frame. FIG. 12 shows an example  
20 of a list indicating the relationship between the block  
positions and indices Mvpidx of a plurality of  
predicted motion information candidates 2755. Indices  
0 to 2 of Mvpidx indicate the predicted motion vector  
candidates 2755 positioned in the spatial domain, and  
25 index 3 of Mvpidx indicates the predicted motion vector  
candidate 2755 positioned in the temporal domain.  
Prediction unit position A is the position of a

prediction unit of inter-prediction, i.e., a prediction unit having the reference motion information 2558, in AX, as shown in FIG. 10, and the value of X is smallest at prediction unit position A. Prediction unit position B is the position of a prediction unit of inter-prediction, i.e., a prediction unit having the reference motion information 2558, in BY, as shown in FIG. 10, and the value of Y is smallest in prediction unit position B. When prediction unit position C is not inter-prediction, the reference motion information 2558 in prediction unit position D is replaced with the reference motion information 2558 in prediction unit position C. When prediction unit positions C and D are not inter-prediction, the reference motion information 2558 in prediction unit position E is replaced with reference motion information 2558 in prediction unit position C.

If the size of the encoding target prediction unit is larger than that of the smallest prediction unit, prediction unit position Col may store a plurality of items of reference motion information 2558 in the temporal-domain reference motion information memory 2507. In this case, the reference motion information 2558 in the prediction unit at position Col is acquired in accordance with the reference position information 2560. The acquisition position of the reference motion information 2558 in the prediction unit at position Col

will be referred to as a reference motion information acquisition position hereinafter. FIGS. 13A, 13B, 13C, 13D, 13E, and 13F illustrate examples of the reference motion information acquisition position for each encoding target prediction unit size ( $32 \times 32$  to  $16 \times 16$ ) when the reference position information 2560 indicates the center of the prediction unit in position Col. In FIGS. 13A, 13B, 13C, 13D, 13E, and 13F, each block indicates a  $4 \times 4$  prediction unit, and a circle indicates the position of a  $4 \times 4$  prediction unit to be acquired as the predicted motion information candidate 2755. FIGS. 14A, 14B, 14C, 14D, 14E, and 14F illustrate other examples of the reference motion information acquisition position. Referring to FIGS. 14A, 14B, 14C, 14D, 14E, and 14F, no  $4 \times 4$  prediction unit exists in the position of a circle, so the predicted motion information candidate 2755 is generated by a predetermined method such as the average or median of the reference motion information 2558 in four  $4 \times 4$  prediction units adjacent to the circle. As still another example of the reference motion information acquisition position, the reference motion information 2558 of a  $4 \times 4$  prediction unit positioned at the upper left corner of the prediction unit in position Col may also be used as the predicted motion information candidate 2755. In a case other than the abovementioned examples, it is possible to generate the

predicted motion information candidate 2755 by using any position and any method, provided that the method is a predetermined method.

Note that if no reference motion information 2558 exists, the motion information 2559 having a zero vector is output as the predicted motion information candidate 2755.

By the processing described above, at least one predicted motion information candidate 2755 is output from the reference motion block. If the reference frame number of the aforementioned predicted motion information candidate 2755 is different from that of the encoding target prediction unit, the predicted motion information candidate 2755 can be scaled by using the reference frame number of the predicted motion information candidate 2755 and that of the encoding target prediction unit. The predicted motion information selection switch 2705 selects one of the plurality of predicted motion information candidates 2755 in accordance with the predicted motion information position 2754, and outputs the predicted motion information 952.

The inverse quantizer 2502 obtains a restored transform coefficient 2552 by inversely quantizing the quantized transform coefficient 2551 from the entropy decoder 2501. More specifically, the inverse quantizer 2502 performs inverse quantization in accordance with

the information of quantization decoded by the entropy decoder 2501. The inverse quantizer 2502 outputs the restored transform coefficient 2552 to the inverse orthogonal transformer 2503.

5           The inverse orthogonal transformer 2503 performs, on the restored transform coefficient 2552 from the inverse quantizer 2502, inverse orthogonal transformation corresponding to orthogonal transformation performed on the encoding side, thereby  
10 obtaining a restored prediction error signal 2553. The inverse orthogonal transformer 2503 inputs the restored prediction error signal 2553 to the adder 2504.

          The adder 2504 generates the decoded image signal 2554 by adding the restored prediction error signal  
15 2553 to the corresponding predicted image signal 2556. The decoded image signal 2554 is processed by a deblocking filter (not shown) or Wiener filter (not shown), temporarily stored in the output buffer 2511 for an output image, and also saved in the reference  
20 image memory 2505 for a reference image signal 2555. The decoded image signal 2554 saved in the reference image memory 2505 is referred to, as the reference image signal 2555, for each frame or each field as needed by the inter-predictor 2506. The decoded image  
25 signal 2554 temporarily stored in the output buffer 2511 is output in accordance with an output timing managed by the decoding controller 2510.

The inter-predictor 2506 performs inter-prediction by using the reference image signal 2555 saved in the reference image memory 2505. More specifically, the inter-predictor 2506 acquires the motion information 2559 containing a motion difference (motion vector) between the prediction target block and reference image signal 2555 from the entropy decoder 2501, and generates an inter-predicted image by performing interpolation (motion compensation) based on this motion vector. The generation of the inter-predicted image is the same as that in the first embodiment, so a repeated explanation will be omitted.

The decoding controller 2510 controls each element of the image decoding apparatus shown in FIG. 25. More specifically, the decoding controller 2510 outputs the reference position information 2560 (to be described later) to the entropy decoder 2501, and performs various kinds of control for the decoding process including the above-described operations.

<Explanation of Skip Mode, Merge Mode, and Inter Mode>

The image decoding apparatus 2500 according to this embodiment uses a plurality of prediction modes using different decoding processes, as shown in FIG. 8. Referring to FIG. 8, the skip mode is a mode that decodes only a syntax pertaining to the predicted motion information position 2754 (to be described later), and does not decode any other syntaxes. The

merge mode is a mode that decodes only a syntax  
pertaining to the predicted motion information position  
2754 and the transform coefficient information 2551,  
and does not decode any other syntaxes. The inter mode  
5 is a mode that decodes a syntax pertaining to the  
predicted motion information position 2754, the  
differential motion information 2753 (to be described  
later), and the transform coefficient information 2551.  
These modes are switched by the prediction information  
10 2571 controlled by the decoding controller 2510.

Also, the image decoding apparatus shown in  
FIG. 25 uses syntaxes that are the same as or similar  
to the syntaxes explained with reference to FIG. 22, so  
a detailed explanation thereof will be omitted.

15 <Details of Motion Information Compressor 2508>

Next, the motion information compressor 2508 will  
be explained with reference to the flowchart shown in  
FIG. 16. When a process of decoding a frame (or an  
arbitrary unit such as a slice or coding unit) is  
20 complete, the motion information compressor 2508  
compresses the motion information 2559 and stores the  
motion information 2559 in the temporal-domain  
reference motion information memory 502.

First, the reference position information 2560 is  
25 acquired from the decoding controller 2510 (step  
S1601), and a frame is divided into motion information  
compression blocks as compression units of the motion

information 2559 (step S1602). The motion information compression block is a pixel block larger than a unit (typically, a block of  $4 \times 4$  pixels) by which the motion information 2559 is stored by the motion compensation process, and is typically a block of  $16 \times 16$  pixels. The motion information compression block may also be a block of  $32 \times 32$  pixels, a block of  $8 \times 8$  pixels, a rectangular pixel block, or a pixel region having an arbitrary shape.

Then, a representative motion information position is generated in accordance with the reference position information 2560 (step S1603). As an example of generating a representative motion information position, when the motion information compression block is a block of  $16 \times 16$  pixels, the reference motion information acquisition position when the prediction unit size is  $16 \times 16$ , as shown in FIGS. 13D, 14D, and 17D, is set as the representative motion information position. Subsequently, the reference motion information 2558 of the generated representative motion information position is set as representative motion information (step S1604), and the representative motion information is stored in the temporal-domain reference motion information memory (step S1605). Steps S1604 and S1605 described above are executed for all motion information compression blocks.

When the unit for storing the motion information

2559 is an  $M \times M$  block and the size of the motion information compression block is  $N \times N$  ( $N$  is a multiple of  $M$ ), the capacity of the reference motion information memory can be reduced to  $(M \times M)/(N \times N)$  by executing the aforementioned motion information compression process.

<Other Embodiments of Representative motion information Position>

As another example of generating a representative motion information position, the central position of a plurality of reference motion information acquisition positions may also be used as the representative motion information position. FIGS. 18A and 18B show the representative motion information position of each motion compression block having a size of  $16 \times 16$ . FIG. 18A shows representative motion information positions when reference motion information acquisition positions are the positions shown in FIG. 13D. Likewise, FIG. 18B shows representative motion information positions when reference motion information acquisition positions are the positions shown in FIG. 17D. Symbols  $\bullet$  in FIGS. 18A and 18B indicate reference motion information acquisition positions when a prediction unit is a  $16 \times 16$  block. A representative motion information position indicated by  $\times$  is placed in the central position (also called the barycentric position) of four reference motion information

acquisition positions.

As still another example of generating a representative motion information position, it is also possible to use a reference motion information acquisition position for each size of a plurality of prediction units as the reference position information 2560, and generate a representative motion information position from a plurality of reference motion information acquisition positions. FIG. 19 shows the center (reference motion information acquisition position) of each prediction unit having a prediction unit size of  $16 \times 16$  or more when a tree block is a block of  $64 \times 64$  pixels.

As another example of generating a representative motion information position, a representative motion information position can also be set by using a reference motion information acquisition position set for each motion information compression block. FIG. 20A shows an example when the barycenter of a plurality of reference motion information acquisition positions in each motion information compression block is set as a representative motion information position. If the barycentric position does not match the position of a  $4 \times 4$  block, it is possible to set the nearest  $4 \times 4$  block as a representative motion information position, or generate the reference motion vector 166 of the barycentric position by using interpolation such

as bi-linear interpolation.

FIG. 20B shows an example in which one of a plurality of reference motion information acquisition positions is selected for each motion information compression block, and set as a representative motion information position.

Furthermore, FIGS. 21A and 21B illustrate examples when motion information compression blocks have the same reference motion information acquisition position in a tree block. Since all motion information compression blocks have the same representative motion information position, representative motion information positions need not be switched in accordance with a position in the tree block. The representative motion information position need not be any of those shown in FIGS. 21A and 21B. The representative motion information position can be any position such as the upper left corner or upper right corner in the motion information compression block.

As an example of generating a representative motion information position, a representative motion information position may also be indicated by using BlkIdx indicating positions of  $4 \times 4$  blocks in a motion information compression block in Z-scan order. When the size of the motion information compression block is  $16 \times 16$ , the representative motion information position, as shown in FIG. 21A, is equivalent to the

position of BlkIdx = 12. Also, the representative motion information position, as shown in FIG. 21B, is equivalent to the position of BlkIdx = 15.

As another example of the motion information compression process, the motion information compression process may also include reference frame numbers in order to reduce the memory capacity for reference frame numbers. In this case, a reference frame number stored in a representative motion information position is stored in the memory capacity for reference frame numbers. Accordingly, the spatial-domain reference motion information memory 501 and spatial-domain reference motion information memory 502 shown in FIG. 5 store reference frame numbers in addition to the motion vector information.

As still another example of the motion information compression process, when the motion information compression process does not include any reference frame number, motion vector information in motion information in a representative motion information position can be scaled by using a reference frame number, and stored in the motion information memory 110. A typical example of the scaling process is a linear scaling process based on reference frame number zero. That is, if the reference frame number is not zero, the linear scaling process is performed such that the motion vector information refers to a reference

frame corresponding to reference frame number zero.  
The basis of the above-described scaling process may  
also be a value other than reference frame number zero.  
If division occurs when performing the above-described  
5 linear scaling process, this division can be  
implemented by looking up a division process table  
formed beforehand.

When the motion information compression block is  
not a  $16 \times 16$  block, a representative motion  
10 information position is generated by using the same  
processing as described above. As an example, when the  
size of the motion information compression block is  $64$   
 $\times 64$ , a reference motion information acquisition  
position in a  $64 \times 64$  prediction unit is set as a  
15 representative motion information position. As another  
example, a representative motion information position  
in the  $16 \times 16$  motion information compression block  
shown in, for example, FIGS. 21A and 21B can be scaled  
in the horizontal and vertical directions in accordance  
20 with the motion information compression block size, and  
the scaled position can be set as a representative  
motion information position.

If no reference motion information exists because  
a representative motion information position is outside  
25 a picture or slice, a position where reference motion  
information can be acquired in a motion information  
compression block, for example, the upper left corner

of the motion information compression block can be set as a new representative motion information position. Also, if no reference motion information exists because a representative motion information position is a region to which intra-prediction is applied, a new representative motion information position can be set by executing the same processing.

Modifications of each embodiment will be explained below.

In each of the first and second embodiments, an example in which a frame is divided into rectangular blocks having a size of, for example,  $16 \times 16$  pixels and encoding or decoding is performed in order from the upper left block to the lower right block on a screen has been explained (see FIG. 2A). However, the encoding order and decoding order are not limited to this example. For example, encoding and decoding may also be performed in order from the lower right block to the upper left block, or spirally performed from the center to the edges of a screen. Furthermore, encoding and decoding may also be performed in order from the upper right block to the lower left block, or spirally performed from the edges to the center of a screen.

The first and second embodiments have been explained by showing prediction target block sizes such as a block of  $4 \times 4$  pixels, a block of  $8 \times 8$  pixels, and a block of  $16 \times 16$  pixels as examples, but a

prediction target block need not have a uniform block shape. For example, the prediction target block (prediction unit) size can also be a block of  $16 \times 8$  pixels, a block of  $8 \times 16$  pixels, a block of  $8 \times 4$  pixels, or a block of  $4 \times 8$  pixels. Also, all block sizes need not be the same in one coding tree unit, and a plurality of different block sizes can coexist. When a plurality of different block sizes coexist in one coding tree unit, a code amount for encoding or decoding division information increases as the number of divided blocks increases. Therefore, a block size is desirably selected by taking account of the balance between the code amount of division information and the quality of a locally decoded image or decoded image.

In the first and second embodiments, a comprehensive explanation has been described for color signal components without distinguishing between a luminance signal and color difference signals for the sake of simplicity. However, when different prediction processes are used for a luminance signal and color difference signals, it is possible to use the same prediction method or different prediction methods. When different prediction methods are used for a luminance signal and color difference signals, a prediction method selected for the color difference signals can be encoded or decoded by the same method as that for the luminance signal.

In the first and second embodiments, a comprehensive explanation has been described for color signal components without distinguishing between a luminance signal and color difference signals for the sake of simplicity. However, when different orthogonal transformation processes are used for a luminance signal and color difference signals, it is possible to use the same orthogonal transformation method or different orthogonal transformation methods. When different orthogonal transformation methods are used for a luminance signal and color difference signals, an orthogonal transformation method selected for the color difference signals can be encoded or decoded by the same method as that for the luminance signal.

In the first and second embodiments, a syntax element not defined in the embodiments can be inserted between lines of the table indicating the syntax configuration, or another description pertaining to conditional branch may also be included. It is also possible to divide the syntax table into a plurality of tables, or integrate a plurality of tables into one table. Furthermore, it is not always necessary to use the same language, and freely change the language in accordance with a use form.

As has been explained above, each embodiment can implement efficient orthogonal transformation and inverse orthogonal transformation while reducing the

complexity in a hardware package and software package. Accordingly, each embodiment increases the encoding efficiency and improves the subjective image quality.

Also, the instructions indicated by the procedures explained in the above-described embodiments can be executed based on a program as software. A general-purpose computer system can obtain effects similar to those of the image encoding apparatus and image decoding apparatus of the above-described embodiments by prestoring the program and reading it. The instructions described in the abovementioned embodiments are recorded, as a program executable by a computer, on a magnetic disk (for example, a flexible disk or hard disk), an optical disk (for example, a CD-ROM, CD-R, CD-RW, DVD-ROM, DVD±R, or DVD±RW), a semiconductor memory, or a recording medium of this kind. The storage format of the recording medium can take any form, provided that the medium can be read by a computer or an embedded system. The computer can implement the same operations as those of the image encoding apparatus and image decoding apparatus of the above-described embodiments by reading the program from the recording medium, and causing a CPU to execute, based on the program, the instructions described in the program. The computer can, of course, also acquire or read the program across a network.

In addition, based on the instructions of the

program installed in the computer or embedded system from the recording medium, an operating system (OS) running on the computer, database management software, or middleware (MW) of the network or the like can  
5 execute a part of each processing for implementing the embodiments.

Furthermore, the recording medium according to the embodiments is not limited to a medium independent of the computer or embedded system, and includes a  
10 recording medium storing or temporarily storing the program transmitted across a LAN or the Internet and downloaded. It is also possible to store the program for implementing the process of each embodiment in a computer (server) connected to a network such as the  
15 Internet, and download the program to a computer (client) across the network.

Also, the recording medium is not restricted to one. Even when the process of each embodiment is executed from a plurality of media, these media are  
20 included in the recording medium according to the embodiments, and the media can take any form.

Note that the computer or embedded system according to the embodiments is used to execute each process of the embodiments based on the program stored  
25 in the recording medium, and can be, for example, a single apparatus such as a personal computer or microcomputer, or a system obtained by connecting a

plurality of apparatuses across a network.

Note also that the computer according to the embodiments is not limited to a personal computer, and includes a processing unit or microcomputer  
5 incorporated into an information processing apparatus. That is, the computer is a general term of an apparatus and device capable of implementing the functions of the embodiments based on the program.

While certain embodiments have been described,  
10 these embodiments have been presented by way of example only, and are not intended to limit the scope of the inventions. Indeed, the novel embodiments described herein may be embodied in a variety of other forms; furthermore, various omissions, substitutions and  
15 changes in the form of the embodiments described herein may be made without departing from the spirit of the inventions. The accompanying claims and their equivalents are intended to cover such forms or modifications as would fall within the scope and spirit  
20 of the inventions.

## CLAIMS

1. A method comprising:  
inputting encoded data comprising at least a target  
5 block in a first frame;  
decoding a merge flag specifying whether at least a  
motion vector of an inter prediction mode is inferred from  
a merging block;  
deriving a first candidate motion vector from at  
10 least one neighboring block of the target block, when the  
merge flag specifies that at least the motion vector of  
the inter prediction mode is inferred from the merging  
block;  
deriving a second candidate motion vector from a  
15 representative motion vector of a collocated block in a  
second frame different from the first frame, the  
collocated block being determined according to a first  
position of the target block, when the merge flag  
specifies that at least the motion vector of the inter  
20 prediction mode is inferred from the merging block,  
wherein the representative motion vector is derived from  
one of representative positions determined according to  
both a second position of the collocated block and a size  
of the collocated block, and the representative positions  
25 include at least a center of the collocated block;  
decoding a merge index specifying the merging block  
from the at least one neighboring block and the collocated  
block; and  
deriving a first motion vector for the target block  
30 from any one of the first candidate motion vector and the  
second candidate motion vector according to the merge  
index.

2. The method of claim 1, further comprising:  
deriving a reference image according to the first  
motion vector; and

generating a prediction image according to the inter-  
5 prediction mode by using the reference image.

3. The method of claim 2, further comprising:  
decoding a transform coefficient from the encoded  
data;

10 deriving a prediction error value by using at least  
an inverse transform of the transform coefficient; and

deriving a decoded image by at least adding the  
prediction error value and the prediction image.

15 4. The method of claim 1, wherein  
the at least one neighboring block of the target  
block comprises at least one of (1) a block on bottom left  
side of the target block, (2) a block on left side of the  
target block, (3) a block on upper right side of the  
20 target block, (4) a block on upper side of the target  
block, and (5) a block on upper left side of the target  
block.

5. The method of claim 1, wherein  
25 a first number of the merge index specifying the  
first candidate motion vector as the merging block is less  
than a second number of the merge index specifying the  
second candidate motion vector as the merging block.

30 6. The method of claim 1, wherein  
the collocated block comprises a position determined  
according to a position of the target block.

7. The method of claim 1, wherein  
the representative positions include not only the  
center of the collocated block but also a position  
determined according to a corner of the collocated block.

5

8. The method of claim 1, further comprising:  
receiving the encoded data via a communication link;  
storing temporarily at least part of the encoded data  
in a buffer;

10 reading, by an electronic circuitry, at least part of  
the encoded data from the buffer; and

deriving, by the electronic circuitry, the first  
motion vector from the encoded data,

wherein the electronic circuitry is a Central  
15 Processing Unit (CPU).

9. The method of claim 1, further comprising:  
receiving the encoded data via a communication link;  
storing temporarily at least part of the encoded data  
20 in a buffer;

reading, by an electronic circuitry, at least part of  
the encoded data from the buffer; and

deriving, by the electronic circuitry, the first  
motion vector from the encoded data,

25 wherein the electronic circuitry is a field  
programmable gate array (FPGA) or a digital signal  
processor (DSP).

10. An electronic apparatus comprising:  
30 a decoder configured to:

input encoded data comprising at least a target  
block in a first frame;

decode a merge flag specifying whether at least a motion vector of an inter prediction mode is inferred from a merging block;

5       derive a first candidate motion vector from at least one neighboring block of the target block, when the merge flag specifies that at least the motion vector of the inter prediction mode is inferred from the merging block;

10       derive a second candidate motion vector from a representative motion vector of a collocated block in a second frame different from the first frame, the collocated block being determined according to a first position of the target block, when the merge flag specifies that at least the motion vector of the  
15       inter prediction mode is inferred from the merging block, wherein the representative positions include at least a center of the collocated block;

20       decode a merge index specifying the merging block from the at least one neighboring block and the collocated block; and

25       derive a first motion vector for the target block from any one of the first candidate motion vector and the second candidate motion vector according to the merge index.

11. The electronic apparatus of claim 10, wherein the decoder is further configured to:

derive a reference image according to the first motion vector; and

30       generate a prediction image according to the inter-prediction mode by using the reference image.

12. The electronic apparatus of claim 11, wherein the decoder is further configured to:

decode a transform coefficient from the encoded data;  
derive a prediction error value by using at least an  
5 inverse transform of the transform coefficient; and  
derive a decoded image by at least adding the prediction error value and the prediction image.

13. The electronic apparatus of claim 10, wherein  
10 the at least one neighboring block of the target block comprises at least one of (1) a block on bottom left side of the target block, (2) a block on left side of the target block, (3) a block on upper right side of the target block, (4) a block on upper side of the target  
15 block, and (5) a block on upper left side of the target block.

14. The electronic apparatus of claim 10, wherein  
a first number of the merge index specifying the  
20 first candidate motion vector as the merging block is less than a second number of the merge index specifying the second candidate motion vector as the merging block.

15. The electronic apparatus of claim 10, wherein  
25 the collocated block comprises a position determined according to a position of the target block.

16. The electronic apparatus of claim 10, wherein  
the representative positions include not only the  
30 center of the collocated block but also a position determined according to a corner of the collocated block.

17. The electronic apparatus of claim 10, further comprising:

communication circuitry configured to receive the encoded data via a communication link; and

5 a buffer configured to store temporarily at least part of the encoded data,

wherein the decoder is further configured to:

read at least part of the encoded data from the buffer; and

10 derive the first motion vector from the encoded data,

wherein the decoder is a Central Processing Unit (CPU).

18. The electronic apparatus of claim 10, further comprising:

communication circuitry configured to receive the encoded data via a communication link; and

a buffer configured to store temporarily at least part of the encoded data,

20 wherein the decoder is further configured to:

read at least part of the encoded data from the buffer; and

derive the first motion vector from the encoded data,

25 wherein the decoder is a field programmable gate array (FPGA) or a digital signal processor (DSP).

19. A method comprising:

encoding a merge flag specifying whether at least a motion vector of an inter prediction mode is inferred from a merging block;

30

specifying a first candidate motion vector from at least one neighboring block of a target block in a first frame;

5 specifying a second candidate motion vector from a representative motion vector of a collocated block in a second frame different from the first frame, the collocated block being determined according to a first position of the target block, wherein the representative motion vector is derived from one of representative positions determined  
10 according to both a second position of the collocated block and a size of the collocated block, and the representative positions include at least a center of the collocated block;  
and

encoding a merge index specifying the merging block  
15 from the at least one neighboring block and the collocated block, wherein a first motion vector for the target block is one of the first candidate motion vector and the second candidate motion vector corresponding to the merging block specified by the merge index.