

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 September 2003 (18.09.2003)


PCT

(10) International Publication Number
WO 03/077621 A1

- (51) International Patent Classification⁷: **H05K 3/30**,
H01L 23/02
- (21) International Application Number: PCT/US03/07017
- (22) International Filing Date: 7 March 2003 (07.03.2003)
- (25) Filing Language: English
- (26) Publication Language: English
- (30) Priority Data:
10/092,459 7 March 2002 (07.03.2002) US
- (71) Applicant (*for all designated States except US*):
KULICKE AND SOFFA INVESTMENTS, INC.
[US/US]; Suite 3165, 2751 Centerville Road, Little Falls
Center Two, Wilmington, DE 19808 (US).
- (72) Inventor; and
(75) Inventor/Applicant (*for US only*): **RUTISER, Claire**
[US/US]; 102 Cameron Road, Willow Grove, PA 19090
(US).
- (74) Agents: **NACCARELLA, Theodore** et al.; Synnvestvedt
& Lechner LLP, 2600 Aramark Tower, 1101 Market Street,
Philadelphia, PA 19107-2950 (US).
- (81) Designated States (*national*): AE, AG, AL, AM, AT, AU,
AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU,
CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH,
GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC,
LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW,
MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SC, SD, SE,
SG, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ,
VC, VN, YU, ZA, ZM, ZW.
- (84) Designated States (*regional*): ARIPO patent (GH, GM,
KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR ENCAPSULATING SEMICONDUCTOR DEVICE



(57) Abstract: The invention is a method and apparatus for encapsulating semiconductor dies (16) via stencil printing in which, after the dies have been stencil printed with encapsulant and prior to removal of the stencil from the dies (16), the edges of the encapsulating material are partially cured in order to prevent or minimize slump of the encapsulant in the time period between removal of the stencil (10) and full curing of the encapsulant. In particular, the stencil (10) can be provided with a plurality of light pipes that terminate at the edges of the apertures (12) within which the dies (16) are placed. Ultraviolet (UV) or other curing light is provided through the light pipes (201) to the edges of the encapsulating material. Some general or localized heating can be provided to enhance or accelerate the light curing of the edges of the encapsulant, but without substantially curing the remainder of the encapsulating material.



WO 03/077621 A1



Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM),
European patent (AT, BE, BG, CH, CY, CZ, DE, DK, EE,
ES, FI, FR, GB, GR, HU, IE, IT, LU, MC, NL, PT, RO,
SE, SI, SK, TR), OAPI patent (BF, BJ, CF, CG, CI, CM,
GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.

Published:

— *with international search report*