



INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(51) International Patent Classification ⁶ : H05K 5/00	A2	(11) International Publication Number: WO 99/09796 (43) International Publication Date: 25 February 1999 (25.02.99)
(21) International Application Number: PCT/US98/16806 (22) International Filing Date: 12 August 1998 (12.08.98) (30) Priority Data: 60/055,284 13 August 1997 (13.08.97) US 60/058,818 15 September 1997 (15.09.97) US 08/999,312 29 December 1997 (29.12.97) US (71) Applicant (for all designated States except US): BERG TECHNOLOGY, INC. [US/US]; One East First Street, Reno, NV 89501 (US). (72) Inventors; and (75) Inventors/Applicants (for US only): GERRITS, Antonius, H., J. [NL/NL]; Wijkelderweg 2, NL-5741 ND Beek en Donk (NL). PIGMANS, Paulus, J., M. [NL/NL]; Grevelingen 37, NL-5032 TC Tilburg (NL). VAN ALST, Wim [NL/NL]; Koninginnelaan 104, NL-5491 JX St. Oedenrode (NL). POTTERS, Paul, J., M. [NL/NL]; Needestraat 8, NL-5651 EG Eindhoven (NL). (74) Agents: LONG, Daniel, J. et al.; 825 Old Trail Road, Eiters, PA 17319 (US).	(81) Designated States: CN, JP, KR, SG, US, European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE). Published <i>Without international search report and to be republished upon receipt of that report.</i>	

(54) Title: **ELECTRONIC CARD**

(57) Abstract

Disclosed is an electronic card comprising a printed circuit board interposed between card shields having edges. Tabs on an edge of one shield engage recesses on the edge of the other shield. The jointed shields of the card provided high levels of rigidity, sufficient to exceed applicable bending and torsional resistance specification. Adequate rigidity is thereby provided. Also included is an I/O connector grounded without a separate ground contact and shielded over its length. The tabs include an arcuate member having a medial oblique projection which engages a ledge of the other shield near the recess. The electronic card of the invention also comprises a printed circuit board interposed between card shields having edges. Tabs on the edges of one shield engage recesses on the edge of the other shield. Adequate rigidity is thereby provided. A frame bar is interposed between the shields. Also included is an I/O connector grounded without a separate ground contact and shielded over its length. Also included in an "oil can" resistant shield in which a deep-draw recess is peripherally surrounded by a groove.

