

(12) INTERNATIONAL APPLICATION PUBLISHED UNDER THE PATENT COOPERATION TREATY (PCT)

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
18 August 2011 (18.08.2011)

(10) International Publication Number
WO 2011/100337 A2

PCT

(51) International Patent Classification:

F01N 3/36 (2006.01) *F01N 3/24* (2006.01)
F01N 3/28 (2006.01) *F01N 3/08* (2006.01)
B01D 53/94 (2006.01)

(21) International Application Number:

PCT/US2011/024208

(22) International Filing Date:

9 February 2011 (09.02.2011)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/303,146 10 February 2010 (10.02.2010) US
13/023,870 9 February 2011 (09.02.2011) US

(71) Applicant (for all designated States except US): **TENNECO AUTOMOTIVE OPERATING COMPANY INC.** [US/US]; 500 North Field Drive, Lake Forest, Illinois 60045 (US).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **OLIVIER, Keith** [US/US]; 7227 Fairmont Drive, Jackson, Michigan 49201 (US). **THOMAS, Stephen** [US/US]; 6206 W. Grandriver Road, Laingsburg, Michigan 48848 (US). **LOWRY, John** [US/US]; 11883 Dearmyer Road, Brooklyn, Michigan 49230 (US).

(74) Agents: **FERRARI, Mark D.** et al.; HARNESS, DICK-EY & PIERCE, P.L.C., P.O. Box 828, Bloomfield Hills, Michigan 48303 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: PRESSURE SWIRL FLOW INJECTOR WITH REDUCED FLOW VARIABILITY AND RETURN FLOW

(57) Abstract: A reagent injector with a cartridge design has a body with a reagent inlet, outlet, and a swirl chamber, which has an exit orifice that may be covered and uncovered by a solid, movable pintle. Reagent flows through the injector when the exit orifice is covered and uncovered to cool the injector. An insulator may be disposed between the injector body and a mounting flange connectable to an exhaust system. A flow path ensures cooling of an electromagnetic actuator. Reagent may bypass an orifice swirl chamber when the pintle blocks the exit orifice. Fluid may flow between an outside diameter of a pole piece and an inside diameter of an electromagnetic actuator, through an orifice chamber and return through a central bore housing a solid pintle, around which fluid may flow. Different inner injector body passages may direct fluid into an orifice distribution chamber and out to the solid pintle.



WO 2011/100337 A2