

COIL ASSEMBLY FOR MAGNETIC RESONANCE IMAGING

RELATED APPLICATIONS

This application claims priority to U.S. Provisional Application 61/879,050,
5 filed on September 17, 2013, the entire contents of which are incorporated herein
by reference.

BACKGROUND

The present disclosure relates to magnetic resonance imaging.
10

SUMMARY

In one aspect, some implementations provide a magnetic resonance
imaging system that includes: a solenoid magnet configured to generate a static
magnetic field; and an annular coil assembly housed within at least a portion of
15 the solenoid magnet, the coil assembly including a gradient coil, wherein the
annular coil assembly has an aperture formed therein.

Implementations may include one or more of the following features. The
annular coil assembly and the magnet may be non-rotatable relative to each
other such that a position of the aperture within the magnet is fixed. The annular
20 coil assembly and the magnet may be rotatable relative to each other such that a
position of the aperture within the magnet is variable.

The magnetic resonance imaging system may further include a rotating
mechanism configured to rotate the annular coil relative to the magnet; and a

locking mechanism configured to lock the annular coil such that the coil is not rotatable relative to the magnet.

A length of aperture may be shorter than a longitudinal length of the annular coil assembly. A length of the aperture may be about the same as the
5 longitudinal length of the annular coil assembly.

The magnetic resonance imaging system may further include a patient table slidable within the annular coil assembly.

The aperture may extend along a longitudinal direction of the annular coil assembly. The aperture may be located in the upper hemisphere of the annular
10 coil assembly. The aperture may be located in the lower hemisphere of the annular coil assembly. The aperture may open one or more of the 'x', 'y', or 'z' axes of an annular coil assembly. For example, the aperture may be an opening in the 'x' and 'y' axes (and shields) while the 'z' axis (and shield) continues to form a complete cylinder. The aperture may be sized to house at least a portion
15 of a breathing apparatus, an intra-operative device, an infusion apparatus, a display device, a projection screen, or a camera. The magnetic resonance imaging system may further include a display device, a projection screen, or a camera located within the aperture.

The annular coil assembly may further include a transmit coil. The
20 annular coil assembly may also include a receive coil. The magnetic resonance imaging system may further include a radio-frequency coil sized to encompass a subject's head, wherein the radio-frequency coil is configured to receive radio-frequency signals emitted from within the subject's head, and wherein coil

assembly is sized to house the radio-frequency coil.

The gradient coil of the annular coil assembly may be configured to provide a gradient variation to the static magnetic field in more than one spatial direction, and wherein none of the more than one spatial direction are directed at
5 the aperture of the annular coil assembly. The main magnet may be a portable magnet transportable on a cart.

In another aspect, some implementations provide a method for imaging a subject, the method including: placing a portion of the subject in an annular coil assembly housed within at least a portion of a solenoid magnet that is configured
10 to generate a static magnetic field, wherein the annular coil assembly has an aperture formed therein; and initiating an imaging sequence to image the subject using the annular coil assembly and the solenoid magnet.

Implementations may include one or more of the following features. The method may further include rotating the annular coil assembly relative to the
15 solenoid magnet such that a portion of the subject is aligned with an apparatus, wherein at least a portion of the apparatus is housed within the aperture of the annular coil assembly. The method may additionally include fixing the annular coil assembly relative to the magnet before initiating the imaging sequence.

The method may further include loading the patient on a slidable table;
20 and sliding the table into an inner bore of the solenoid magnet.

The method may further include passing a breathing tube through the aperture of the annular coil assembly to the subject's face that is aligned with the

aperture; and providing anesthesia to the subject through the breathing tube while the subject is being imaged.

The method may further include inserting a radio-frequency (RF) receiver coil into the aperture of the annular coil assembly before initiating the imaging
5 sequence.

The method may further include rotating the annular coil assembly relative to the magnet causes the radio-frequency receiver coil to be placed at an access port on the subject's head through which an interventional procedure is being performed; and initiating the imaging sequence further includes using the radio-
10 frequency receiver coil to image the subject during the interventional procedure based on the access port.

The method may further include communicating with the subject while the subject is being imaged using a display device or projection screen housed within the aperture of the annular coil assembly.

15 The method may further include monitoring the subject while the subject is being imaged using a camera device housed within the aperture of the annular coil assembly.

BRIEF DESCRIPTION OF THE DRAWINGS

Embodiments will now be described, by way of example only, with
20 reference to the drawings, in which:

Figure 1A shows an example magnetic resonance imaging system in which the transmit coil and gradient coil are rotatably provided within a solenoid magnet, and where an aperture is provided within the transmit and gradient coils.

Figure 1B shows an example implementation of a rotatable coil assembly including the transmit and gradient coils.

Figures 2A illustrates the use of the aperture within the rotatable transmit and gradient coil assembly for accommodating additional medical devices or
5 equipment.

Figure 2B provides a longitudinal view of the example illustration shown in Figure 2A, shown as a cross-section taken along line A-A of Figure 2A.

Figure 2C is an illustration of an example embodiment showing the rotation of the aperture to accommodate a patient oriented in a prone position.

10 **Figure 2D** is an illustration showing the rotation of the aperture to accommodate medical devices associated with a neurological interventional procedure.

Figure 3A shows a top view of a patient residing within an example MRI scanner according to one implementation, showing the close proximity of the coil
15 assembly relative to the patient head.

Figures 3B and 3C show example embodiments in which the aperture is employed to allow the patient to view an image or video.

Figure 3D shows an example embodiment illustrating the insertion of patient, wearing a head coil, into a magnetic resonance imaging system having a
20 coil assembly with an aperture formed therein.

Figure 3E is an illustration showing an example embodiment in which a camera is positioned inside the solenoid and attached to the rotating coil assembly, so that the patient can be visually monitored while inside the MRI

scanner at multiple orientations.

Figure 4A is a photograph illustrating a wooden prototype of an example system including a rotatable coil assembly recessed within a MRI magnet.

Figures 4B and 4C show examples of a portable magnetic resonance
5 imaging system according to an embodiment in which the rotatable coil assembly is recessed within the magnet bore, showing (a) a front view and (b) a rear view.

Figure 5A shows an example of a mechanism for supporting or facilitating the rotation of the coil assembly within the magnet bore.

Figure 5B is an illustration showing an example embodiment in which a
10 handle is attached to the rotatable coil assembly, in order to provide manual or automated rotation actuation.

Figure 5C is an illustration showing another example embodiment in which dual handles are attached to the rotatable coil assembly, in order to provide manual or automated rotation actuation.

15 **Figure 5D** is an illustration showing an example implementation of a locking mechanism that enables the angular orientation of the rotatable coil assembly to be locked at a plurality of configurations.

Figure 5E is an illustration of an example implementation of a magnetic resonance imaging system including a rotatable coil assembly, at least one
20 rotation mechanism (such as the handle as shown), and an optional locking mechanism (such as the insertable locking member as shown).

Figure 5F shows an example implementation of a locking mechanism in which a plurality of spring-loaded rods may be provided at the outer surface of

coil assembly, which may be removably received in corresponding holes within the solenoid for locking a given angular orientation.

Figures 6A and 6B show example configurations of the gradient coil according to two example implementations.

5 **Figure 6C** is an illustration of an example implementation of gradient coils according to the embodiment shown in Figure 6B, showing the example X and Y coil configurations.

DETAILED DESCRIPTION

10 Various embodiments and aspects of the disclosure will be described with reference to details discussed below. The following description and drawings are illustrative of the disclosure and are not to be construed as limiting the disclosure. Numerous specific details are described to provide a thorough understanding of various embodiments of the present disclosure. However, in certain instances,
15 well-known or conventional details are not described in order to provide a concise discussion of embodiments of the present disclosure.

As used herein, the terms “comprises” and “comprising” are to be construed as being inclusive and open ended, and not exclusive. Specifically, when used in the specification and claims, the terms “comprises” and
20 “comprising” and variations thereof mean the specified features, steps or components are included. These terms are not to be interpreted to exclude the presence of other features, steps or components.

As used herein, the term “exemplary” means “serving as an example,

instance, or illustration,” and should not be construed as preferred or advantageous over other configurations disclosed herein.

As used herein, the terms “about” and “approximately” are meant to cover variations that may exist in the upper and lower limits of the ranges of values, such as variations in properties, parameters, and dimensions. In one non-limiting example, the terms “about” and “approximately” mean plus or minus 10 percent or less.

According to selected embodiments of the present disclosure, magnetic resonance imaging systems and devices are provided in which an aperture (e.g. a gap, opening, cavity or window) is formed within a coil assembly including the gradient and transmit coils (and optionally a receive coil). In some implementations, the coil assembly can be rotated relative to an axis within the bore of the main solenoid magnet. In some implementations, the coil assembly may not rotate and the aperture can be fixed.

As described in further detail below, the rotatable aperture may be employed to provide access and/or visibility to a patient who is being imaged. The aperture may be employed to create a window or portal for medical staff to view and monitor the patient. The aperture may also provide a spatial region for medical equipment or devices to be accommodate or housed during a magnetic resonance imaging scan. In some implementations, the aperture may be located in the upper half, for example, on top, of the inner surface of the coil assembly. These implementations may facilitate, for example, functional MR imaging of the brain, intra-operative imaging of neurological interventions. In some

implementations, the aperture may be in the lower half, for example, at the bottom, of the inner surface of the coil assembly. These implementations may accommodate, for example, a mammography application, an MR-guided breast biopsy procedure, etc. As shown in several examples below, the aperture can be

5 rotated within the solenoid magnet to accommodate various patient positions, and can be located as needed for desired accessibility. For example, typically, the gradients and RF transmit coils are built as cylinders around the same axis as the solenoid magnet used to generate the main field. By opening up an aperture in the gradient coils and RF transmit coil, it is possible to generate extra

10 space inside the MRI without sacrificing performance. By then rotating these gradients and RF coils, it is possible to locate the area of extra space where it would be of most use during a surgical procedure, for example, to allow more room for an intubated patient with anesthesia equipment, or to allow an insert imaging device such as a port coil to be used. This rotating is possible because

15 all of MRI relies on the use of orthogonal planes. As the main magnetic field (B_0) remains constant in the 'z' direction, as long as the directions of the gradients and RF remain substantially orthogonal then performance may be maintained.

Referring now to Figure 1A, an example magnetic resonance imaging system is shown in which a coil assembly 135, including transmit coil 130 and

20 gradient coil 120, is rotatably provided within solenoid magnet 110. Aperture 125 is provided within the coil assembly, forming an opening or a gap in the coil assembly 135. Coil assembly 135 may generally be shaped as an annular structure and housed within the inner bore of solenoid magnet 110. Under

rotation of coil assembly 135 relative to central axis 150, as shown at 140, aperture 125 may be positioned at various angular locations within the inner bore of the solenoid magnet. The gradient, transmit, and receive coil system may rotate either automatically or manually. In some implementations, annular coil assembly 135 only includes gradient coil 120. In these implementations, annular coil assembly does not include transmit coil 130 or any receiver coil. For these implementations, radio-frequency (RF) signals are, for example, transmitted by local coils for imaging a subject. In one instance, a head coil in a birdcage configuration is used for both transmitting and receiving RF signals for imaging the subject. In another instance, a surface coil is used for transmitting an RF signal into the subject and a phased array coil configuration is used for receiving MR signals in response. The embodiments provided herein may be adapted for intraoperative MRI, and MRI systems for use in an emergency room setting.

Figure 1B shows a detailed view of an example implementation of the coil assembly 135, in which the aperture 125 is provided as an opening formed along the longitudinal direction of the coil assembly 135. In one instance, the aperture 125 may only extend over a portion of the full longitudinal extent of the coil assembly 135. In other instances, two or more apertures may be provided at various axial and/or azimuthal positions of the coil assembly 135. In fact, a variety of apertures with varying angular ranges may be formed on coil assembly 135.

Referring now to Figure 2A, an example implementation illustrates the use of the aperture within the rotatable transmit and gradient coil assembly for

accommodating additional medical devices or equipment. This axial view illustrates an example of providing an anesthetic mask for an intubated patient. In this example, patient 160 is positioned on patient support 180. Patient support 180 may include a slidable patient table. An anesthetic mask 170 and
5 associated tubing 175 are provided on intubated patient 160. Aperture 125 is oriented to provide additional room to house tubing 175, without comprising valuable space within coil assembly 135 between transmit coil 130 and patient 160.

Figure 2B provides a longitudinal view of the example illustration shown in
10 Figure 2A, shown as a cross-section taken along line A-A of Figure 2A. This longitudinal view shows how tubing 175 is received within the aperture that would have otherwise been occupied by gradient coil 120 and transmit coil 130. As illustrated, tubing 175 takes up space towards the top of the inner bore of the solenoid magnet 110. This space overlaps with coil assembly 135 if coil
15 assembly is a full annular coil assembly. The aperture 125 on coil assembly 135 provides the space for tubing 175 without compromising gradient coil 120 and transmit coil 130.

Figure 2C illustrates how the rotatable aspect of coil assembly 135 may be employed to accommodate a patient 160 oriented in a prone position. Since
20 aperture 125 rotates with coil assembly 135, the additional medical hardware or devices associated with the patient (in this case, tubing 175) may be accommodated in more than one angular position.

Figure 2D illustrates an example of rotating aperture 125 to accommodate

medical devices associated with a neurological interventional procedure, illustrating the example case of a patient 160 having an access port 200 inserted within his head. As shown in Figure 2D, the rotatable aperture 125 need not be positioned over the patients face, and the extra space afforded by aperture 125
5 may be employed to position a local MRI receiver 210 (e.g., implemented as a RF receiver coil) at the relevant surgical or diagnostic location. This may prove advantageous during port-based neurological surgical and diagnostic procedures in allowing for magnetic resonance images to be obtained intra-operatively without having to remove the access port prior to imaging. For example, the
10 close proximity of the local MRI receiver 210 may provide superior signal-to-noise performance to improve sensitivity or to increase frame rate of an intraoperative MRI imaging procedure.

Figure 3A shows a top-down view of a patient positioned within a magnetic resonance imaging system according to one embodiment of the
15 present disclosure, in which the coil assembly 135 is recessed within solenoid magnet 110. This example shows the close proximity that can be achieved between the coil assembly and the patient's head 160, while still providing ample room for other portions of the patient's body that are not necessarily being imaged. The dimensions provided in this figure are example ranges and are not
20 intended to be limiting.

Accordingly, embodiments of the present disclosure may enable a reduction in size of a magnetic resonance imaging system, as the presence of the rotatable aperture may enable a patient to be accommodated in a bore with a

smaller diameter. For example, as described elsewhere in the present disclosure, the rotatable aperture may be employed to accommodate one or more additional devices, such as diagnostic, therapeutic, imaging or communications devices, without requiring an associated increase in the bore diameter. In other

5 embodiments, the rotatable aperture may be employed to provide the patient with the perception of additional room within the scanner by providing additional room in the vicinity of the patient's face (for example, within a small annular segment associated with the size of the patient's face), while still maintaining close proximity between the coil assembly elsewhere.

10 This ability to perform magnetic resonance imaging within a smaller bore system can lead to advantages in performance and/or cost. A typical magnetic resonance imaging system may have a central bore (within the transmit coil) diameter of approximately 60 cm. A wide-bore system may have a diameter of approximately 70 cm. The cost of such a system is governed in part by the radius
15 of the bore, because the radius affects the stored energy in the solenoid magnet. The stored energy varies as the cube of the radius. As such, reducing the size of the bore is advantageous as it allows for cost reduction and/or an increase of the achievable primary magnetic field.

 Similarly, the performance of the gradient coil is also strongly dependent
20 on the radius, because the magnetic field from a wire drops according to an inverse square law. Accordingly, a size reduction in the gradient coil radius allows one to achieve a given performance with less current, thereby reducing the system cost and complexity (and reducing associated heating and cooling

requirements).

Accordingly, in some embodiments, the diameter of the transmit coil may be reduced from the typical values noted above. In some example implementations, the inner diameter of the transmit coil may be reduced to a value that accommodates the insertion of a head, but is, for example, less than approximately 60 cm, less than approximately 50 cm, less than approximately 45 cm, less than approximately 40 cm, and less than approximately 35 cm. As shown in Figures 2A and 2B, 3D and 5E, the coil assembly may be recessed within the solenoid magnet, such that the patient body (e.g. the shoulders) may be inserted within a broader diameter region (for example, having a diameter of approximately 60 cm) associated with the coil assembly, while inserting the head within a narrower diameter region associated with the coil assembly. For example, in one example implementation, shown in Figure 5E, the solenoid magnet may have a longitudinal (axial) length of approximately 1 m, while the region associated with the coil assembly (the gradient and transmit coils) may have a longitudinal (axial) length of approximately 0.5 m.

Figures 3B and 3C show example embodiments in which the aperture is employed to allow patient 160 to view an image or video, for example, via an MRI-compatible display device or projection screen 250 located in aperture 125 within the inside of the solenoid magnet. As shown in the Figures, the display or projection device 250 may be attached to the coil assembly, for example via member 255. Figures 3B and 3C shown in two different angular orientations, illustrating how patient 160 may view and/or interact with the display or projection

device 250 at multiple orientations.

According, in some embodiments, an MRI with a video screen or image projection may be embedded within the mechanism to facilitate communication with the patient. This screen can be used to provide scan information to the
5 patient (such as instructions to not move, or to count down the scan time remaining) or provide visual cues during scanning, for example fMRI studies. Alternatively, this screen may be used to provide entertainment during the scanning procedure. If an MR-compatible camera is added, this screen or image projection may be used for two-way communications between a patient in the
10 scanner and another individual. The screen or image projection and camera can also potentially be mounted to the rotating items such that the patient remains visible regardless of the aperture orientation.

In one example embodiment, a timer may be visible to the patient inside of the scanner. This timer would allow the patient to see an indication of time
15 remaining or time elapsed for their current scan, and could better hold still, leading to fewer image artifacts. If a general screen or area for image projection was available to the patient, the timer could be displayed here, along with instructions to stay still, and soothing images, or other entertainment. The screen or image projection could be used for fMRI studies. If the screen or
20 image projection were combined with a camera, two way visual contact could be achieved between the patient in the scanner and the operator. This contact could be used to allow medical staff to watch a medically distressed patient, or a child to be in visual contact with their caregiver. The medical staff could explain

the time to the patient, leading to a less confusing and isolating experience.

Figure 3D shows an example embodiment illustrating the insertion of patient 160, supported by a table or stretcher 180, and wearing a head coil 230, into a magnetic resonance imaging system having a coil assembly with an aperture formed therein. In one instance, head coil 230 can be configured as a radio-frequency receiver coil as a local coil. In this instance, head coil 230 is configured to receive radio-frequency signals emitted from within the subject's head and in response to excitation radio frequency pulses sent from the transmit coil 130 within the annular coil assembly 135. In another instance, head coil 230 can be configured as a radio-frequency transmit and receiver coil. In the example embodiment shown, the aperture includes a display device, screen and/or camera 252. The coil assembly and associated aperture may be rotatable to accommodate multiple patient orientations. The system includes an initial gap region 240 configured to accommodate the patient's shoulders and torso. The receiving coil may be positioned about the patient with the aperture as desired prior to installing them within the magnet. In this embodiment, the rotating coil assembly 135 includes the gradient coil 120 and transmitting coil 130.

Figure 3E is an illustration showing an example embodiment in which a camera 275 is positioned inside aperture 125 and attached to rotating coil assembly 135 (for example, via attachment member 270), so that patient 160 can be visually monitored while inside the scanner at multiple orientations. Such an embodiment may be optionally combined with the embodiment shown in Figures 3B and 3C to provide a display mechanism in addition to a camera, for example,

to allow two-way visual communication or interaction between a patient in the scanner and another individual. By positioning an MR compatible camera (e.g., for eye-tracking in fMRI studies) on the rotating element, it is possible for the anesthetist to maintain visual contact with the patient regardless of their
5 orientation.

Figure 4A is a photograph illustrating a wooden prototype of an example system including a rotatable coil assembly 135 recessed within a MRI magnet 110. The rotatable coil assembly 135 had an aperture 125. Figures 4B and 4C show examples of a portable magnetic resonance imaging system 280 according
10 to an embodiment in which the rotatable coil assembly is recessed within the magnet bore, showing (a) a front view and (b) a rear view. In some instances, the magnet is portable in that it can travel within a room or between rooms, and may be mounted on wheels, with or without a motorized base. The magnet may have a tether cable attaching it to an equipment room. .

15 In some embodiments, support structures may be provided to support the weight of the coil assembly in order to assist with, and/or guide, rotation of the coil assembly. Referring now to Figure 5A, an example mechanism is provided for supporting or facilitating the rotation of the coil assembly (including gradient coil 120 and transmit coil 130) within the bore magnet 110. In the example
20 shown, a plurality of rotatable supports 300, such as rods, wheels, or bearings (which may be configured to be shock absorbing) are provided at various azimuthal positions. Such supports may be retained by a suitable mechanism, such as lateral retention mechanism 305. In some embodiments, such supports

may be provided only in the vicinity of the lower portion of the system, where the weight of the coil assembly is received. Alternatively, pneumatic or air-bearing mechanisms may be employed.

A wide variety of mechanisms and means, both manual and automated,
5 may be employed to achieve or actuate rotation of the rotatable insert. In one illustration, an MRI-compatible motor may be employed to produce rotation of the rotatable coil assembly. A floating cable may be employed that extends out the back of the magnet and is of sufficient length to support rotation.

Figure 5B is an illustration showing an example embodiment in which a
10 handle 350 is attached to the rotatable coil assembly, in order to provide manual or automated rotation actuation and relative positioning of aperture 125. Figure 5C is an illustration showing another example embodiment in which dual handles 360 and 365 are attached to the rotatable coil assembly, in order to provide manual or automated rotation actuation and relative positioning of aperture 125.
15 The handles may be connected to an automated mechanism, such as an external motor, to automatically control the rotation of the coil assembly. In some embodiments, the handles are provided at the rear of the system, such that they do not interfere with the body of the patient (e.g. the patient's shoulders).

Figure 5D is an illustration showing an example implementation of a
20 locking mechanism that enables the angular orientation of the rotatable coil assembly to be locked at a plurality of configurations. End portions 132 and 115 are provided on coil assembly 135 and solenoid 110, respectively. End portion 132 includes a plurality of first holes 410, and end portion 115 includes a plurality

of second holes 400. As coil assembly 135 is rotated, first holes 410 and second holes 400 align at different angular positions. A locking member 420 can be inserted to lock an angular position at a location where holes align, such as at location 415. Figure 5E is an illustration of an example implementation of a magnetic resonance imaging system including a rotatable coil assembly 135, at least one rotation mechanism, such as handle 350, and an optional locking mechanism, such as the insertable locking member 420.

In another embodiment, shown in Figure 5F, a plurality of spring-loaded rods 430 may be provided at the outer surface of coil assembly, which may be removably received in corresponding holes within the solenoid for locking a given angular orientation. The rods may be disengaged by a suitable mechanism. In another embodiment, the rods may be received at a sufficiently shallow depth that they may be disengaged by applying a sufficient torque to the coil assembly.

Figures 6A and 6B show example configurations of the gradient coil 130 according to two example implementations. In Figure 6A, the Y gradient axis 505 is directed towards the aperture on coil assembly 350, and the presence of the aperture leads to a performance degradation of the Y-gradient relative to that of the X-gradient.

Figure 6B illustrates another configuration in which the X and Y orientations are rotated relative to those shown in Figure 14(a), thereby improving the relative performance of the Y gradient. In one example implementation, the X and Y axes are rotated such that they are angled at approximately 45 degrees relative to the normal defined by the aperture and

neither X nor Y axis is directed towards the aperture of coil assembly 130.

Figure 6C provides an illustration of an example implementation of gradient coils according to the embodiment shown in Figure 6B, showing the example X (520 and 525) and Y (530 and 535) coil configurations. The reoriented
5 coil configurations improve the Y gradient at the expense of the X gradient. The Y gradient improves in performance because there is available continuous surface area for current to flow on either side of the newly defined Y axis (Y') in Figure 6B, while in Figure 6A there is only continuous surface area for current flow on one side of the Y axis (the lower half). Likewise, the X gradient will suffer
10 slightly in performance because in Figure 6A there is ample surface area for current to flow on either side of the X axis, while in Figure 6B the surface area on one side of the X' axis has been diminished. A variation on this approach allows for the 'z' axis to remain a complete cylinder (to achieve full performance) while the 'x' and 'y' axes are rotated about the aperture. In this approach, a substantial
15 aperture is formed without sacrificing gradient performance.

The various embodiments described above may provide one or more of the following advantages. For example, various embodiments may provide for a smaller head-only MRI system that fits closely around a patient's head, and meets the requirement to fit anesthesia equipment, other MRI imaging coils such
20 as a port coil, or to accommodate the variety of patient positions possible during, for example, neurosurgery (or spine surgery). Such embodiments may lower costs (relative to larger size MRI systems), reduce difficulty in siting, and reduce difficulty in moving the device, all of which are linked to the size of an MRI.

More generally, embodiments may make an MRI a less uncomfortable experience. Embodiments may make the patient feel less isolated within the scanner with a greater ability to communicate with the outside world. Once the scan starts, the patient can be provided with knowledge of how much time
5 remains in some embodiments. The reduced feeling of isolation, greater ability to communicate, and/or knowledge of how much time remains can decrease fidgeting, which may prevent some degradation of image quality. This may be particularly advantageous with respect to children, as they have a tendency to move about once isolated in the scanner. Similarly, this may be advantageous
10 for patients in medical distress, as it is difficult to have them be isolated and away from medical attention for the duration of their time in the scanner.

Furthermore, during an interventional neurosurgical procedure, it is advantageous for the anesthetist to have visual access to the patient's face. For an intra-operative procedure to maintain this visual access, prone and other
15 patient positions can be challenging, but embodiments described above can reduce or eliminate these challenges.

The specific embodiments described above have been shown by way of example, and it should be understood that these embodiments may be susceptible to various modifications and alternative forms. It should be further
20 understood that the claims are not intended to be limited to the particular forms disclosed, but rather to cover all modifications, equivalents, and alternatives falling within the spirit and scope of this disclosure.

WHAT IS CLAIMED IS:

1. A magnetic resonance imaging system comprising:
a solenoid magnet configured to generate a static magnetic field; and
an annular coil assembly housed within at least a portion of the solenoid magnet, the coil assembly comprising a gradient coil,
wherein the annular coil assembly has an aperture formed therein, and
wherein the annular coil assembly and the magnet are rotatable relative to each other such that a position of the aperture within the magnet is variable.
- 5 2. The magnetic resonance imaging system according to any of the preceding claims, further comprising:
a rotating mechanism configured to rotate the annular coil assembly relative to the magnet; and
a locking mechanism configured to lock the annular coil assembly such
10 that the coil is not rotatable relative to the magnet.
3. The magnetic resonance imaging system according to any one of the preceding claims wherein a length of the aperture is shorter than a longitudinal length of the annular coil assembly.
- 15 4. The magnetic resonance imaging system according to claim 1, wherein the

aperture is formed in one or more of the 'x', 'y', or 'z' axes or shields.

5. The magnetic resonance imaging system according to any one of claims 1 and 2 wherein a length of the aperture is about the same as the longitudinal length of the annular coil assembly.

5

6. The magnetic resonance imaging system according to any one of preceding claims further comprising a patient table slidable within the annular coil assembly.

10 7. The magnetic resonance imaging system according to any one of the preceding claims, wherein the aperture extends along a longitudinal direction of the annular coil assembly,

8. The magnetic resonance imaging system according to any one of claims 1
15 to 7, wherein the aperture is located in the upper hemisphere of the annular coil assembly.

9. The magnetic resonance imaging system according to any one of claims 1
to 7, wherein the aperture is located in the lower hemisphere of the annular coil
20 assembly.

10. The magnetic resonance imaging system according to any one of the preceding claims, wherein the aperture is sized to house at least a portion of a breathing apparatus, an intra-operative device, an infusion apparatus, a display device, a projection screen, or a camera.

5

11. The magnetic resonance imaging system of claim 9 further comprising a display device, a projection screen, or a camera located within the aperture.

12. The magnetic resonance imaging system according to any one of the preceding claims, wherein the annular coil assembly further comprises a transmit coil.

13 The magnetic resonance imaging system according to any one of the preceding claims, further comprising:

15 a radio-frequency coil sized to encompass a subject's head,
wherein the radio-frequency coil is configured to receive radio-frequency signals emitted from within the subject's head, and
wherein coil assembly is sized to house the radio-frequency coil.

20 14. The MR imaging system according to any one of the preceding claims,
wherein the gradient coil of the annular coil assembly is configured to provide a gradient variation to the static magnetic field in more than one spatial direction, and

wherein none of the more than one spatial direction are directed at the aperture of the annular coil assembly.

15. The MR imaging system according to any one of the preceding claims,
5 wherein the main magnet is a portable magnet transportable.

16. A method for imaging a subject, comprising:
placing a portion of the subject in an annular coil assembly housed within
at least a portion of a solenoid magnet that is configured to generate a static
10 magnetic field, wherein the annular coil assembly has an aperture formed
therein; and
initiating an imaging sequence to image the subject using the annular coil
assembly and the solenoid magnet.

15 17. The method of claim 16, further comprising:
rotating the annular coil assembly relative to the solenoid magnet such
that a portion of the subject is aligned with an apparatus, wherein at least a
portion of the apparatus is housed within the aperture of the annular coil
assembly.

20

18. The method of claim 17, further comprising:
fixing the annular coil assembly relative to the magnet before initiating the
imaging sequence.

19. The method of any of the preceding claims 16 to 18, further comprising:
loading the patient on a slidable table; and
sliding the table into an inner bore of the solenoid magnet.
- 5
20. The method of any of the preceding claims 16 to 19, further comprising:
passing a breathing tube through the aperture of the annular coil assembly
to the subject's face that is aligned with the aperture; and
providing anesthesia to the subject through the breathing tube while the
10 subject is being imaged.
21. The method of any of the preceding claims 17 to 20, further comprising:
inserting a radio-frequency (RF) receiver coil into the aperture of the
annular coil assembly before initiating the imaging sequence.
- 15
22. The method of claim 21, wherein
rotating the annular coil assembly relative to the magnet causes the radio-
frequency receiver coil to be placed at an access port on the subject's head
through which an interventional procedure is being performed; and
20 initiating the imaging sequence further includes using the radio-frequency
receiver coil to image the subject during the interventional procedure based on
the access port.

23. The method of any of the preceding claims 17 to 22, further comprising communicating with the subject while the subject is being imaged using a display device or projection screen housed within the aperture of the annular coil assembly.

5

24. The method of any of the preceding claims 17 to 22, further comprising:
monitoring the subject while the subject is being imaged using a camera device housed within the aperture of the annular coil assembly.

10