



(51) International Patent Classification:
H04L 5/00 (2006.01)

(21) International Application Number:
PCT/SE2010/051069

(22) International Filing Date:
4 October 2010 (04.10.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
61/248,661 5 October 2009 (05.10.2009) US

(71) Applicant (for all designated States except US): **TELEFONAKTIEBOLAGET L M ERICSSON (PUBL)** [SE/SE]; S-164 83 Stockholm (SE).

(72) Inventors; and

(75) Inventors/Applicants (for US only): **BALDEMAIR, Robert** [AT/SE]; Ängkärrsgatan 3, S-171 70 Solna (SE). **GERSTENBERGER, Dirk** [DE/SE]; Birger Jarlsgatan 113 C, S-113 56 Stockholm (SE). **LARSSON, Daniel** [SE/SE]; Storgatan 50, S-171 52 Solna (SE). **LINDBOM, Lars** [SE/SE]; Fogdegatan 7, S-654 62 Karlstad (SE). **PARKVALL, Stefan** [SE/SE]; Västmannagatan 53, S-113 25 Stockholm (SE). **ASTELY, David** [SE/SE]; Stobaeusvägen 22, S-168 56 Bromma (SE).

(74) Agent: **HASSELGREN, Joakim**; Ericsson AB, Patent Unit LTE, Torshamnsgatan 23, S-164 80 Stockholm (SE).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report (Rule 48.2(g))

(54) Title: PUCCH RESOURCE ALLOCATION FOR CARRIER AGGREGATION IN LTE-ADVANCED

(57) Abstract: The invention is a method and apparatus for signaling uplink control information in a mobile communication network using carrier aggregation. The signaling mechanism allows the transmission, on a single uplink component carrier, of control information associated with a downlink transmission on multiple aggregated downlink component carriers. Semi-statically reserved resources for the transmission of control information on the uplink component carrier may be dynamically shared by user terminals that are assigned multiple downlink component carriers for downlink transmissions. Implicit or explicit resource indication can be used in combination with dynamic resource indication.

