

Description**FIELD OF THE INVENTION AND RELATED ART**

5 The present invention relates to an image forming apparatus wherein an ambient condition or conditions are measured, in response to which an image forming condition or conditions are controlled.

It is conventional in an electrophotographic image forming apparatus that in order to maintain a constant density of the formed image, a potential of a charged photosensitive drum, a developing bias potential applied to a developing device or the like is adjusted so as to control the image forming conditions influential to a contrast potential of an image or a foggy background preventing potential or the like. Particularly, in a multi-color copying machine, an image forming condition is determined in response to the properties of the respective color developers so as to provide substantially the same image density for all colors, as disclosed in U.S. Serial No. 330,551.

However, although the adjustment of the image forming conditions for the respective colors is performed in such conventional machines, no consideration is made to the variation of the image density resulting from variations in the ambient conditions under which the developers are placed. Particularly, the variation in the image density resulting from the variation in the ambient humidity is remarkable. Additionally, the degrees of the density changes resulting from moisture absorption are different if the colors of the developers are different, with the result that the density difference can be conspicuous.

20 U.S. Serial No. 087,918 and Japanese Patent Application 86465/1980 propose in the field of ink jet printers that temperature or humidity is detected, in response to which the image signal is controlled for each colors in a reference value of an A/D conversion, a gain of an amplifier, a coefficient of color correction or the like. However, the control of the image signal requires a high speed processing of the signal, which results in an expensive circuit.

25 In an ordinary copying machine using black toner, the method of maintaining a constant surface potential of the photosensitive member is changed in accordance with a humidity, as disclosed in U.S. Patent No. 4,573,788. However, in this U.S. Patent, the surface potential is stabilized using a predetermined operational expression within a predetermined humidity range, but in the other range, the operational expression is not used, and measurement of the actual surface potential of the photosensitive member and adjustment of the charger and exposure amount are repeated so that the potential approaches the target potential, and therefore, the time required for reaching the target potential is very long as the case (humidity) may be.

SUMMARY OF THE INVENTION

35 According to the present invention an image forming apparatus comprises image forming means (3,4,9) for forming images on a recording medium (3), said image forming means being capable of forming the images in different colors; and

means (19) for detecting an ambient condition;

40 characterised in that there are:

means (4, 4a, 4b) for determining a contrast voltage to be given to said recording medium (3) in accordance with both the ambient condition detected by said detecting means (19) and a colour in which the image is to be formed; and

control means (18) for controlling an operating condition of said image forming means in accordance with the contrast determined by said determining means.

45 How the invention may be carried out will now be described, by way of example only, with reference to the accompanying drawings in which:

BRIEF DESCRIPTION OF THE DRAWINGS

50 Figure 1 is a sectional view of an image forming apparatus according to an embodiment of the present invention.

Figure 2 is a block diagram for the control of Figure 1 apparatus.

Figure 3 is a graph showing a relationship between an grid bias voltage and a drum surface potential.

Figure 4 is a graph showing a density change by humidity change for each color developer.

55 Figures 5A, 5B, 5C and 5D are flow charts illustrating a process of setting image forming conditions in Figure 1 apparatus.

Figure 6 is a graph showing a relationship between the humidity and a set contrast potential.

Figures 7 and 8 are block diagram for the control of an image forming apparatus according to another embodiment of the present invention.

Figure 9 is a graph showing a contrast potential changed by a changing means.

5 DETAILED DESCRIPTION OF THE PREFERRED EMBODIMENTS

Referring to Figure 1, there is shown an image forming apparatus according to an embodiment of the present invention. The image forming apparatus comprising a rotary type developing device 1 having a rotor carrying an yellow developing device 1Y, a magenta developing device 1M, a cyan developing device
10 1C and a black developing device 1BK. The apparatus further includes a developer (toner) supplying device for supplying the developer to the developing device 1. The supplying device 2 includes a yellow hopper 2Y, a magenta hopper 2M, a cyan hopper 2C and a black hopper 2BK.

The description will first be made as to a general operation of the color image forming apparatus, taking as an example a full-color mode operation. A photosensitive drum 3 is rotatable in the direction indicated by an arrow, and a surface thereof is uniformly charged by a charger 4. An unshown original is exposed to light, and an yellow image signal is obtained by a proper photo-electric conversion. A laser beam E is modulated in accordance with the yellow image signal and is projected onto the surface of the charged
15 photosensitive drum 3, so that an electrostatic latent image is formed on the photosensitive drum 3. Then, the yellow developing device 1Y situated beforehand to its developing position develops the electrostatic latent image. Which one of the developing devices 1Y, 1M, 1C and 1BK is placed at the developing position is discriminated by unshown microswitches.

A transfer sheet for receiving an image is transported through a sheet guide 5a, a sheet feeding roller 6 and a sheet guide 5b and is held by a gripper 7. The sheet is electrostatically wrapped around a transfer drum 9 by a contact roller 8 and an opposite electrode. The transfer drum 9 is rotated in the direction
25 indicated by an arrow in synchronism with the photosensitive drum 3. The image developed and visualized by the yellow developing device 1Y is transferred to the transfer sheet at the transfer station provided with a transfer charger 10. The transfer drum 9 continues to rotate while holding the transfer sheet to be prepared for the image transfer in the next color, more particularly, a magenta image in the example of Figure 1 embodiment.

On the other hand, the photosensitive drum 3 is discharged by a discharger 11 and is then cleaned by a cleaning member 12. The photosensitive drum 3 is again charged by a charger 4 and is exposed to the laser beam which is then modulated in accordance with a magenta image signal. During this, the rotary developing device 1 rotates to place the magenta developing device 1M at a predetermined developing position to perform a developing operation in the magenta color. Subsequently, the above-described steps
35 are repeated for each of the cyan and black colors. When the transfer operations for four colors are completed, the visualized four color image on the transfer sheet is discharged by dischargers 13 and 14. The transfer sheet is released from the gripper 7 and is separated from the transfer drum 9 by a separation pawl 15 and is transported to an image fixing device 17 by a conveying belt 16. Thus, a series of full color printing operations is completed to provide a full-color print image.

Further, in this embodiment, there is provided in addition to the above-described structures with an ambience sensor 19 including a humidity sensor and a temperature sensor disposed at a position where the moisture absorption of the toner is properly reflected, such as a neighborhood of a toner hopper or the neighborhood of the developing device.

Figure 2 is a block diagram of the control system for Figure 1 apparatus.

The primary charger 4 is supplied with a high voltage from a high voltage source 4a. The primary charger 4 is provided with a grid for controlling an amount of charge applied to the photosensitive drum 3, the grid being supplied with electric power from a grid bias source 4b. A developing bias source provides a developing bias in the form of a combined AC and DC voltages. The outputs of the power sources are controlled by a microcomputer 18 or the like. The control means 18 is also connected to the ambience
45 sensor 19 and a potential sensor 20.

Next, the operation of this embodiment will be described.

Referring to Figure 3, there is shown a relationship between a grid bias voltage and a surface potential of the photosensitive drum 3. In this Figure, V_D is a surface potential of the area not exposed to the light beam, while V_L is a surface potential of the area exposed to the light beam. As will be understood from this
55 Figure, the surface potential V_D , that is, the amount of charge is proportional to the grid bias V_G . The surface potential V_L after the light exposure has a similar tendency. However, a ratio of change of V_D with respect to a change of the grid bias V_G , is larger than that for V_L , that is, $\alpha > \beta$. In consideration of this, the control means 18, before execution of the printing sequences, measures the potentials V_D and V_L using a

potential sensor 20 for predetermined grid voltages V_{G1} and V_{G2} , so that charging curves for the potentials V_D and V_L with respect to a grid voltage as shown in Figure 3 is assumed on the basis of data by the potential sensor 20. Subsequently, when the image forming operation is actually executed, a grid voltage which provides a predetermined image contrast, that is, a difference between a DC component of a developing bias which will be described hereinafter and a surface potential V_L after image exposure, or $V_D - V_L$ is determined on the basis of the charging curve. The grid voltage is determined in this manner, and the grid bias source 4b is controlled to provide the voltage. Further, a developing bias D_B is determined to be lower than the potential V_D by a predetermined voltage (V_B) so as to prevent deposition of the toner onto the area corresponding to the background of the image, that is, the area corresponding to V_D in this case since a reversal development is effected, and the developing bias source 1' is controlled, accordingly.

Figure 4 is a graph showing influence of humidity to the image density when the printing is effected under the same image forming conditions. As will be understood from this graph, the density decreases with the humidity under the same image forming conditions, and it increases with the increase of the humidity. Therefore, the humidity is detected, and a contrast potential V_{cont} corresponding to a humidity is determined. On the basis of the value, the image forming condition or conditions are set, whereby a stabilized image can be obtained irrespective of variation of the ambient conditions. Also understood from this figure is that the image density is different if the color of the developer is different even in the same humidity. Therefore, the image forming condition or conditions are made variable for the respective colors, whereby the image density variation depending on the color of the developer can be corrected.

Referring to Figures 5A, 5B and 5C which are flow charts, operations of the control means 18 in this embodiment will be described. The processing shown in those flow charts is programmed in a ROM 23.

First, a processing A will be described referring to Figure 5A. The ambience sensor 19 measures the temperature and the relative humidity every 30 minutes, for example, or several times in every 30 minutes, and an average value is determined. The ambience sensor 19 is operative irrespective of the state of a main switch supplying power to the image forming apparatus, by an interruption function using a timer 21. The data are stored in a buffer area in a memory 22 capable of storing data for 8 hours, for example. At step 1, an absolute humidity or a value corresponding thereto (a mixture ratio, for example) is determined on the basis of the stored data. This is done because the image density is proportional to the absolute humidity, that is, an amount of water in the air. The humidity sensor in this embodiment is a relative humidity sensor having a strong temperature dependence. Since it is non-linear, a relative humidity h is determined on the basis of the temperature data and the humidity data using a high-quarter polynomial approximation, and thereafter, the absolute humidity (mixture ratio) r is obtained by the following equations:

$$e = h \times e_s / 100$$

$$r = 0.622 e / (p - e)$$

wherein

e_s : saturated vapour pressure

p : pressure

In the equations, e_s has a temperature dependence property, and therefore temperature data are required to obtain the absolute humidity (mixture ratio). Therefore, the ROM stores a table for every 1 °C, and a table search is performed for the determination. At step 2, a discrimination is made as to whether or not the absolute humidity (mixture ratio) calculations have been executed for the eight hour period, and if so, at step 3, average values x , y and z are determined for the latest 2 hours, 4 hours and 8 hours, respectively. The averages x , y and z are parameters when the contrast is determined. By the steps 4 - 7, the humidity change is discriminated. At step 4, the discrimination is made as to whether or not the two hours average x of the mixture ratio is 16.5 g or larger, and if so a flag is set to CONT1. In this case, it is discriminated that the high humidity condition continues for not less than two hours. If not, at step 5, the discrimination is made as to whether or not the current mixture ratio w is 16.5 g or larger, and if so, the flag is set to CONT2. Here, the current mixture ratio w is represented by the latest humidity data. The flag CONT2 corresponds to the discrimination that the low humidity condition continued for the past two hours, but the humidity is increasing now. If not, at step 6, the discrimination is made as to whether or not the eight hours average z is 9 g or larger, and if so, the flag is set to CONT3. This means that the humidity has been middle (middle between the high humidity and the low humidity) for 8 hours or longer. If not, at step 7, the discrimination is made as to whether or not the four hours average y is 9 g or larger, and if so, the flag is set to CONT4. It is now discriminated that the humidity is changing from the low humidity condition to an intermediate or middle humidity condition. If not, that is, the four hours average is less than 9 g, the low humidity condition is discriminated so that the flag is set to CONT5.

The above described method of discrimination is performed because the speeds of the moisture absorption and dehumidification of the toner are different between when the humidity is changing from the low humidity condition to the high humidity condition and when it is changing from the high humidity condition to the low humidity condition. Generally, the speed of the dehumidification when the humidity is changing from the high humidity condition to the low humidity condition is lower than the speed of the moisture absorption when the humidity is changing from the low humidity condition to the high humidity condition. It is true that the image density is influenced by the absolute moisture, but, more particularly, the influence is determined not by the humidity of the ambience but by the moisture absorption by the toner. This is the reason for executing the above-described discrimination steps.

At step 8 a variable H for the contrast calculation is determined on the basis of the contrast flag. For example, when the CONT1 is selected, it means that the toner is completely influenced by the high humidity condition, and therefore, the variable H corresponds to the two hours average x. When the CONT2 is selected, that is, it is between the low humidity condition and the high humidity condition, the variable H is an average of the two hours average x and the current value w, that is, $(x + w)/2$.

Further, by the contrast flag and color information representing the color of the developer, a coefficient of calculation is searched and read out of the table in the memory 23. A general equation of the calculation is

$$V_{\text{cont}} = A_n - B_n \times H_n$$

Vcont: contrast potential
 H_n : variable
 A_n and B_n : coefficients
 n: number of CONT flag.

The following is a Table giving A_n , B_n and H_n for the respective CONTs.

Table 1

DEVELOPER	CONT	a_n	b_n	H_n
Y	1	a_{1Y}	b_{1Y}	x
	2	a_{2Y}	b_{2Y}	$(x+w)/2$
	3	a_{3Y}	b_{3Y}	$(x+z+w)/3$
	4	a_{4Y}	b_{4Y}	$(y+z)/2$
	5	a_{5Y}	b_{5Y}	y

M	1	a_{1M}	b_{1M}	x
	2	a_{2M}	b_{2M}	$(x+w)/2$
	3	a_{3M}	b_{3M}	$(x+z+w)/3$
	4	a_{4M}	b_{4M}	$(y+z)/2$
	5	a_{5M}	b_{5M}	y

C	1	a_{1C}	b_{1C}	x
	2	a_{2C}	b_{2C}	$(x+w)/2$
	3	a_{3C}	b_{3C}	$(x+z+w)/3$
	4	a_{4C}	b_{4C}	$(y+z)/2$
	5	a_{5C}	b_{5C}	y

BK	1	a_{1BK}	b_{1BK}	x
	2	a_{2BK}	b_{2BK}	$(x+w)/2$
	3	a_{3BK}	b_{3BK}	$(x+z+w)/3$
	4	a_{4BK}	b_{4BK}	$(y+z)/2$
	5	a_{5BK}	b_{5BK}	y

On the basis of the coefficients A_n and B_n and the variable H_n , the contrast potential V_{cont} is calculated, and at step 9, it is stored in the memory. This is repeated for four colors.

As described in the foregoing, one of CONT1 -CONT5 is selected on the basis of the average humidity data x, y and z and the current value w. If the flag of CONT3 is selected, a type of the variable H and the coefficient a_3 and b_3 are obtained from the table stored in the memory ROM23, thus determining the calculation equation. Using the equation, the contrast potential V_{cont} is determined using the actual values for the variation H.

Figure 6 is a plot of contrast potentials with respect to humidities for respective colors of the developer. As will be understood from this Figure, the coefficients are changed for the respective colors, the difference in the density variation depending on the colors can be accommodated and can be properly corrected.

Referring to Figure 5B, the description will be made as to the processing B. First, similarly to the usual copying sequence, the photosensitive drum is rotated, and the primary high voltage source 4a is energized. At steps 11 and 12, the grid bias is set to a predetermined level V_{G1} , and a surface potential of the photosensitive drum in the dark area V_{D1} is measured and stored in the memory. Next, the laser is actuated, and the drum is exposed to the maximum amount of the laser beam. At step 13, the light surface potential V_{L1} after the light exposure is measured, and the data is stored in the memory. At steps 14 and 15, the grid bias is set to another predetermined level V_{G2} , and the surface potential V_{L2} is measured, and then, the laser is deactivated. At step 16, the surface potential V_{D2} is measured, and the data is stored in the memory 22. By this, data required for the calculation which will be described hereinafter have been obtained.

The order of V_D and V_L measurements with the laser actuation and deactivation and the order of setting V_{G1} and V_{G2} may be changed for the convenience of the sequential operation. The processings A and B are independent from each other, and either will go first, and it is not necessary that the processings are performed simultaneously.

Referring to Figure 5C, the description will be made as to the processing C. The processing C has to be performed after the processings A and B are performed.

At step 21, the inclinations α and β for the potentials V_D and V_L and the difference D between α - β are calculated from V_{G1} , V_{G2} , data V_{D1} , V_{D2} , V_{L1} and V_{L2} by the following equations:

$$\alpha = (V_{D2} - V_{D1}) / (V_{G2} - V_{G1}),$$

$$\beta = (V_{L2} - V_{L1}) / (V_{G2} - V_{G1}).$$

At step 22, the above described fog preventing voltage V_B and the contrast voltage V_{cont} obtained by the processing A are read out of the buffer area. At step 23, the grid bias V_G is set so that $V_D - V_L$ equals to $V_{cont} + V_B$. More particularly, the following calculation is performed:

$$V_G = \{V_{cont} + V_B - (V_{D1} - V_{L1})\}(\alpha - \beta) + V_{G1}$$

After the grid voltage is determined at step 24, the potential V_D is obtained by the following equation:

$$V_D = \alpha(V_G - V_{G1}) + V_{D1}$$

Further, at step 25, the DC component (DB) of the developing bias is obtained at step 25 by the following equation:

$$DB = V_D - V_B$$

At step 26, if it is discriminated that the above processing is completed for four colors, the processing terminates.

By the above described steps, the grid bias control value V_G and the developing bias control value DB have been obtained. Then, the image forming operation is performed using the grid bias voltage V_G and the developing bias DB obtained in the manner described above. Since those values are determined not only on the basis of the humidity condition under which the developer has been placed but also on the basis of the property difference among the developers having different colors, an extremely stabilized proper density image can be obtained.

As described in the foregoing, the present invention takes as an important factor for determining the image forming condition or conditions the history of the humidity. Therefore, it is required that the apparatus is always energized to allow the temperature data and the relative humidity data to be taken. However, when, for example, the apparatus is initially installed or when the ambience sensor is failed, the buffer area does not contain any data or it contains false data. Therefore, the proper image forming conditions would not be provided immediately after the repairing or the like.

Referring to Figure 7, an embodiment of the present invention to obviate this inconvenience will be described. The apparatus of Figure 7 is provided in addition to Figure 1 apparatus with a rewriting means 24 for rewriting the humidity data stored in the memory 22. In this apparatus, following process is executed.

Referring to Figure 5D, at step 32, the temperature and humidity are measured immediately after the apparatus is energized. At step 33, the data are stored in the entirety of the 8 hours buffer area of the memory, assuming that the measured temperature and humidity are constantly continued for 8 hours. At step 34, the above-described processings A, B and C are executed. At step 35, an expert service man or the like takes a copy using a normal copying sequence to take a sample of an image. At step 36, the image density is checked. The image density is not always proper. For example, if the humidity is high at the time of installation of the apparatus, the eight hours humidity data are all high humidity data, and therefore, the contrast potential is determined on the data. However, the toner supplied into the apparatus at the time of installation is mainly influenced by the moisture under the ambience sealed in the plant, which might be completely different from the ambience of the installation. In view of this, in the present embodiment, when the image density is discriminated as being not proper at steps 38 and 39, the humidity data is rewritten by a humidity data rewriting means 24 using a servicing mode. In this mode, the humidity data are rewritten all at once. In this embodiment, the humidity data rewriting means 24 includes two keys, one of which can rewrite toward the low humidity side, and the other of which rewrites toward the high humidity side. By depressing the switch, the humidity data is changed by an amount corresponding to one contrast change. In this embodiment, the one contrast change corresponds to 50 V of the drum surface potential.

By the initial setting through the above process, the proper image can be provided from the start. Furthermore, with elapse of the time, the temperature and humidity data are accumulated so that the proper images can be provided.

However, the property of the developer can be extremely different from lot to lot. On such an occasion, if the coefficient of the contrast calculation is fixed, a proper image density can not be obtained as the case may be.

Referring to Figure 8, there is shown an embodiment which can provide a proper image even if that case. The apparatus of this embodiment is provided in addition to Figure 1 apparatus with memory means 22' which can keep the memory even if the power supply is stopped. As an example, the memory means 22' includes a RAM and a back-up battery or includes EPROM. The memory means 22' stores the data to be added at the time of the contrast calculation for each of the colors. The contents thereof can be rewritten by a changing means 25 in a servicing mode, so that proper adjustment can be effected, checking the image samples.

The above-described contrast calculation can be expressed by:

$$V_{cont} = V_{off} + a_n - b_n H_n$$

That is, at step 9 in Figure 5A, the contrast is changed, and the contrast is stored in the memory at step 10. Further, the humidity-contrast curve of Figure 6 becomes as shown in Figure 9. In Figure 9, the solid line curve is a curve at the time of initial setting, and when, for example, the image density is lower than the initial setting, V_{off} is positive, and the broken line curve is used. If the density is high, V_{off} becomes negative as shown in chain lines.

In place of adding or reducing V_{off} , a RAM 22' may store coefficients a_n and b_n and variable H_n , and the coefficients a_n and b_n may be rewritten by the changing means 25 for each of the CONT1 - CONT5 and for each color. By this, further proper contrast value can be provided.

By the above described processing, which changes the contrast potential, a proper image density can be provided in the case that the properties of the developer are significantly different.

The foregoing description has been made as to a multi-color image forming apparatus. However, the present invention is applicable to usual monochromatic image forming apparatus. Also, the present invention is applicable to the apparatus wherein an image of an original is directly projected on the photosensitive member, and the image thereof is formed.

In the foregoing description, the ambient detecting means detects the absolute humidity. However, the image density may be controlled on the basis of the measurement of a factor or factors influential to the developer such as temperature other than the humidity to control the image density.

In the foregoing, the image forming condition is determined on the basis of the charge potential on the photosensitive drum, the potential after the light application and the potential of the developing bias. However, other condition or conditions may be controlled such as charged potential of the developer or amount of light application or the like. When the light amount is controlled, it is increased when the humidity is low, while it is decreased when the humidity is high. In the foregoing description, the contrast levels are

divided into five levels (CONT1 -CONT5). However, the number of division may be increased further.

While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth and this application is intended to cover such modifications or changes as may come within the scope of the following claims.

Claims

1. An image forming apparatus, (1) comprising image forming means (3,4,9) for forming images on a recording medium (3), said image forming means being capable of forming the images in different colors; and
means (19) for detecting an ambient condition;
characterised in that there are:
means (4, 4a, 4b) for determining a contrast voltage to be given to said recording medium (3) in accordance with both the ambient condition detected by said detecting means (19) and a colour in which the image is to be formed; and
control means (18) for controlling an operating condition of said image forming means (3,4,9) in accordance with the contrast determined by said determining means.
2. An apparatus according to Claim 1, wherein said detecting means (19) detects humidity in said apparatus.
3. An apparatus according to Claim 2, wherein said detecting means (19) detects absolute humidity.
4. An apparatus according to Claim 1, wherein said image forming means (3,4,9) includes means (4) for charging the recording medium (3), and wherein said control means (18) controls the degree of charging by said charging means (4).
5. An apparatus according to Claim 4, wherein said image forming means includes plural developing means (1Y,1M,1C,1BK) containing different color developers, and wherein said control means (18) controls a developing bias voltage of said developing means.
6. An apparatus according to Claim 4, wherein said charging means (4) includes a grid electrode (4B).
7. An apparatus according to Claim 6, wherein said control means (18) controls a voltage applied to said grid electrode (4B) in accordance with the contrast voltage.
8. An apparatus according to Claim 1, wherein said image forming means includes means for exposing the recording medium in accordance with an image signal (4B).
9. An apparatus according to Claim 1, further comprising means (19) for detecting temperature, wherein said control means (18) corrects its output in accordance with the temperature detected by said temperature detecting means (19) to control said image forming means (3,4,9) with the corrected output.
10. An apparatus according to Claim 1, wherein said image forming means (3,4,9) includes plural developing means (1Y,1M,1C,1BK) containing different color developers.

Patentansprüche

1. Bilderzeugungsgerät (1) mit einer Bilderzeugungseinrichtung (3,4,9) zum Erzeugen von Bildern auf einem Aufzeichnungsträger (3), die zum Erzeugen der Bilder in verschiedenen Farben geeignet ist, und mit einer Einrichtung (19) zum Erfassen eines Umgebungszustandes,
gekennzeichnet durch
eine Einrichtung (4,4a,4b) zum Bestimmen einer auf den Aufzeichnungsträger (3) aufzubringenden Kontrastspannung entsprechend sowohl dem mittels der Fassungseinrichtung (19) erfaßten Umgebungszustand auch einer Farbe, in der das Bild zu erzeugen ist, und
eine Steuereinrichtung (18) zum Steuern eines Betriebszustands der Bilderzeugungseinrichtung (3,4,9) entsprechend dem durch die Bestimmungseinrichtung bestimmten Kontrast.



divided into five levels (CONT1 -CONT5). However, the number of division may be increased further.

While the invention has been described with reference to the structures disclosed herein, it is not confined to the details set forth and this application is intended to cover such modifications or changes as may come within the scope of the following claims.

5

Claims

1. An image forming apparatus, (1) comprising image forming means (3,4,9) for forming images on a recording medium (3), said image forming means being capable of forming the images in different colors; and
 means (19) for detecting an ambient condition;
 characterised in that there are:
 means (4, 4a, 4b) for determining a contrast voltage to be given to said recording medium (3) in accordance with both the ambient condition detected by said detecting means (19) and a colour in which the image is to be formed; and
 control means (18) for controlling an operating condition of said image forming means (3,4,9) in accordance with the contrast determined by said determining means.
2. An apparatus according to Claim 1, wherein said detecting means (19) detects humidity in said apparatus.
3. An apparatus according to Claim 2, wherein said detecting means (19) detects absolute humidity.
4. An apparatus according to Claim 1, wherein said image forming means (3,4,9) includes means (4) for charging the recording medium (3), and wherein said control means (18) controls the degree of charging by said charging means (4).
5. An apparatus according to Claim 4, wherein said image forming means includes plural developing means (1Y,1M,1C,1BK) containing different color developers, and wherein said control means (18) controls a developing bias voltage of said developing means.
6. An apparatus according to Claim 4, wherein said charging means (4) includes a grid electrode (4B).
7. An apparatus according to Claim 6, wherein said control means (18) controls a voltage applied to said grid electrode (4B) in accordance with the contrast voltage.
8. An apparatus according to Claim 1, wherein said image forming means includes means for exposing the recording medium in accordance with an image signal (4B).
9. An apparatus according to Claim 1, further comprising means (19) for detecting temperature, wherein said control means (18) corrects its output in accordance with the temperature detected by said temperature detecting means (19) to control said image forming means (3,4,9) with the corrected output.
10. An apparatus according to Claim 1, wherein said image forming means (3,4,9) includes plural developing means (1Y,1M,1C,1BK) containing different color developers.

Patentansprüche

1. Bilderzeugungsgerät (1) mit einer Bilderzeugungseinrichtung (3,4,9) zum Erzeugen von Bildern auf einem Aufzeichnungsträger (3), die zum Erzeugen der Bilder in verschiedenen Farben geeignet ist, und mit einer Einrichtung (19) zum Erfassen eines Umgebungszustandes, gekennzeichnet durch
 eine Einrichtung (4,4a,4b) zum Bestimmen einer auf den Aufzeichnungsträger (3) aufzubringenden Kontrastspannung entsprechend sowohl dem mittels der Fassungseinrichtung (19) erfaßten Umgebungszustand auch einer Farbe, in der das Bild zu erzeugen ist, und
 eine Steuereinrichtung (18) zum Steuern eines Betriebszustands der Bilderzeugungseinrichtung (3,4,9) entsprechend dem durch die Bestimmungseinrichtung bestimmten Kontrast.



2. Gerät nach Anspruch 1, in dem die Erfassungseinrichtung (19) die Feuchtigkeit in dem Gerät erfasst.
3. Gerät nach Anspruch 2, in dem die Erfassungseinrichtung (19) die absolute Feuchtigkeit erfasst.
- 5 4. Gerät nach Anspruch 1, in dem Bilderzeugungseinrichtung (3,4,9) eine Vorrichtung (4) zum Laden des Aufzeichnungsträgers (3) aufweist und in dem die Steuereinrichtung (18) das Ausmaß des Ladens durch die Ladevorrichtung (4) steuert.
- 10 5. Gerät nach Anspruch 4, in dem die Bilderzeugungseinrichtung mehrere Entwicklungsvorrichtungen (1Y, 1M, 1C, 1BK) aufweist, die unterschiedliche Farbentwickler enthalten, und in dem die Steuereinrichtung (18) eine Entwicklungsvorspannung der Entwicklungsvorrichtungen steuert.
6. Gerät nach Anspruch 4, in dem die Ladevorrichtung (4) eine Gitterelektrode (4B) enthält.
- 15 7. Gerät nach Anspruch 6, in dem die Steuereinrichtung (18) eine an die Gitterelektrode (4B) angelegte Spannung entsprechend der Kontrastspannung steuert.
8. Gerät nach Anspruch 1, in dem Bilderzeugungseinrichtung eine Einrichtung zum Belichten des Aufzeichnungsträgers entsprechend einem Bildsignal (4B) aufweist.
- 20 9. Gerät nach Anspruch 1, das ferner eine Vorrichtung (19) zum Messen der Temperatur aufweist, wobei die Steuereinrichtung (18) ihr Ausgangssignal entsprechend der durch die Temperaturmeßvorrichtung (19) gemessenen Temperatur korrigiert, um die Bilderzeugungseinrichtung (3,4,9) mit dem korrigierten Ausgangssignal zu steuern.
- 25 10. Gerät nach Anspruch 1, in dem die Bilderzeugungseinrichtung (3,4,9) mehrere Entwicklungsvorrichtungen (1Y, 1M, 1C, 1BK) aufweist, die unterschiedliche Farbentwickler enthalten.

Revendications

- 30 1. Appareil (1) de formation d'images comportant des moyens (3, 4, 9) de formation d'images destinés à former des images sur un support d'enregistrement (3), lesdits moyens de formation d'images étant capables de former les images dans des couleurs différentes ; et
des moyens (19) destinés à détecter une condition ambiante ;
35 caractérisé en ce qu'il comporte :
des moyens (4, 4a, 4b) destinés à déterminer une tension de contraste devant être appliquée audit support (3) d'enregistrement en fonction à la fois de la condition ambiante détectée par lesdits moyens de détection (19) et d'une couleur dans laquelle l'image doit être formée ; et
des moyens de commande (18) destinés à commander une condition de fonctionnement desdits
40 moyens (3, 4, 9) de formation d'images en fonction du contraste déterminé par lesdits moyens de détermination.
2. Appareil selon la revendication 1, dans lequel lesdits moyens (19) de détection détectent l'humidité dans ledit appareil.
- 45 3. Appareil selon la revendication 2, dans lequel lesdits moyens (19) de détection détectent l'humidité absolue.
4. Appareil selon la revendication 1, dans lequel lesdits moyens (3, 4, 9) de formation d'images comprennent un moyen (4) destiné à charger le support d'enregistrement (3), et dans lequel lesdits
50 moyens de commande (18) commandent le degré de charge par ledit moyen de charge (4).
5. Appareil selon la revendication 4, dans lequel lesdits moyens de formation d'images comprennent plusieurs moyens de développement (1Y, 1M, 1C, 1BK) contenant différents développeurs en couleur, et dans lequel lesdits moyens de commande (18) commandent une tension de polarisation de
55 développement desdits moyens de développement.



6. Appareil selon la revendication 4, dans lequel ledit moyen de charge (4) comprend une électrode de grille (4B).
- 5 7. Appareil selon la revendication 6, dans lequel lesdits moyens de commande (18) commandent une tension appliquée à ladite électrode de grille (4B) en fonction de la tension de contraste.
8. Appareil selon la revendication 1, dans lequel lesdits moyens de formation d'images comprennent des moyens destinés à exposer le support d'enregistrement en fonction d'un signal d'images (4B).
- 10 9. Appareil selon la revendication 1, comportant en outre des moyens (19) destinés à détecter une température, dans lequel lesdits moyens de commande (18) corrigent leur signal de sortie en fonction de la température détectée par lesdits moyens (19) de détection de température afin de commander lesdits moyens (3, 4, 9) de formation d'images avec le signal de sortie corrigé.
- 15 10. Appareil selon la revendication 1, dans lequel lesdits moyens (3, 4, 9) de formation d'images comprennent plusieurs moyens de développement (1Y, 1M, 1C, 1BK) contenant des développeurs de couleurs différentes.

20

25

30

35

40

45

50

55