

TECHNIQUES FOR ACCESSING LOGICAL NETWORKS VIA A PROGRAMMATIC SERVICE CALL

[0001] This application claims priority to co-pending U.S. non-provisional application entitled "TECHNIQUES FOR ACCESSING LOGICAL NETWORKS VIA A PROGRAMMATIC SERVICE CALL," assigned Serial Number 13/252,604 and filed October 4, 2011, the entirety of which is hereby incorporated by reference herein.

BACKGROUND

[0002] People use computing devices to communicate with other computing devices and with each other. Sometimes people are dispersed to remote and/or different locations, but still need to communicate as if they were centrally located.

SUMMARY OF INVENTION

[0002a] In a first aspect, there is provided a system, comprising: at least one computing device; and a logical network configuration manager executable in the at least one computing device, wherein upon execution, the logical network configuration manager causes the at least one computing device to at least: receive, via a logical network gateway operated by a computing service provider, at least one programmatic service call from a client device associated with a customer of the computing service provider to connect to a logical network operated by the computing service provider; create, responsive to receipt of the at least one programmatic service call from the client device, a plurality of customer accounts associated with the logical network, individual ones of the plurality of customer accounts associated with respective ones of a plurality of clients; create, responsive to receipt of the at least one programmatic service call from the client device, a plurality of accountings of usage of the logical network, individual ones of the plurality of accountings

of usage associated with respective ones of the plurality of customer accounts; create, responsive to receipt of the at least one programmatic service call from the client device, a programmatic configuration of the logical network comprising the logical network gateway and the plurality of customer accounts; create, responsive to receipt of the at least one programmatic service call from the client device, a plurality of permissions associated with the logical network, *individual ones of the plurality of permissions associated with the* respective ones of the plurality of customer accounts; create, responsive to receipt of the at least one programmatic service call from the client device, a logical network tunnel between the client device and a plurality of virtual computers attached to the logical network according to the programmatic configuration, wherein the virtual computers are associated with network addresses specified by the customer and wherein the computing service provider operates a plurality of logical networks for the plurality of customer accounts associated with the computing service provider; and send confirmation data associated with creation of the logical network tunnel to the client device.

[0002b] In a second aspect, there is provided a method, comprising: creating, by a computing service provider via at least one computing device, a logical network for a customer within an environment provided by the computing service provider, wherein the logical network includes one or more virtual computers associated with a plurality of network addresses specified by the customer; creating, by the at least one computing device, *a plurality of customer accounts associated with the logical network responsive to* receipt of at least one programmatic service call from a client device, *individual ones of the* plurality of customer accounts associated with respective ones of a plurality of clients;

creating, by the at least one computing device, a plurality of accountings of usage responsive to receipt of the at least one programmatic service call from the client device, individual ones of the plurality of accountings of usage associated with respective ones of the plurality of customer accounts; creating, by the at least one computing device, a plurality of permissions associated with the logical network responsive to receipt of at least one programmatic service call from the client device, individual ones of the plurality of permissions associated with the respective ones of the plurality of customer accounts; creating, by the at least one computing device, a programmatic configuration of the logical network comprising a logical network gateway and the plurality of customer accounts responsive to receipt of the at least one programmatic service call from the client device; creating, by the at least one computing device, a logical network tunnel between the client device and the logical network in response to receipt of the at least one programmatic service call from the client device such that the client device appears as being present in the logical network; and transmitting, by the at least one computing device, confirmation data associated with the creation of the logical network tunnel to the client device.

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] Many aspects of the present disclosure can be better understood with reference to the following drawings. The components in the drawings are not necessarily to scale, emphasis instead being placed upon clearly illustrating the principles of the disclosure. Moreover, in the drawings, like reference numerals designate corresponding parts throughout the several views.

[0004] FIG. 1 is a drawing of a networked environment according to various embodiments of the present disclosure.

[0005] FIG. 2 is a flowchart illustrating one example of functionality implemented as portions of a logical network application executed in a client computing device in the networked environment of FIG. 1 according to various embodiments of the present disclosure.

[0006] FIGS. 3A and 3B are flowcharts illustrating one example of functionality implemented as portions of a logical network configuration manager executed in a

computing device in the networked environment of FIG. 1 according to various embodiments of the present disclosure.

[0007] FIG. 4 is a flowchart illustrating one example of functionality implemented as portions of a logical network gateway service executed in a computing device in the networked environment of FIG. 1 according to various embodiments of the present disclosure.

[0008] FIG. 5 is a flowchart illustrating another example of functionality implemented as portions of a logical network configuration manager executed in a computing device in the networked environment of FIG. 1 according to various embodiments of the present disclosure.

[0009] FIG. 6 is a schematic block diagram that provides one example illustration of a computing device employed in the networked environment of FIG. 1 according to various embodiments of the present disclosure.

[0010] FIG. 7 is a schematic block diagram that provides one example illustration of a client computing device employed in the networked environment of FIG. 1 according to various embodiments of the present disclosure.

DETAILED DESCRIPTION

[0011] The present disclosure relates to programmatically configuring a logical network through which one or more client devices may communicate with other computing devices within the logical network. The users connect to the logical network by establishing a logical network tunnel between the client device and the logical network gateway service on the computing device. The logical network gateway service is configured with information about the users who may establish logical network tunnels and the one or more logical networks to which the users may connect. In the following discussion, a general

description of the system and its components is provided, followed by a discussion of the operation of the same.

[0012] With reference to FIG. 1, shown is a networked environment 100 according to various embodiments. The networked environment 100 includes one or more computing devices 103, one or more client devices 106 and one or more computing device 143 communicating by way of a network 109. The network 109 includes, for example, the Internet, intranets, extranets, wide area networks (WANs), local area networks (LANs), wired networks, wireless networks, or other suitable networks, *etc.*, or any combination of two or more such networks.

[0013] Each computing device 103 may be operated by a cloud computing service provider or other provider. The computing device 103 may comprise, for example, a server computer or any other system providing computing capability. Alternatively, a plurality of computing devices 103 may be employed that are arranged, for example, in one or more server banks or computer banks or other arrangements. A plurality of computing devices 103 together may comprise, for example, a cloud computing resource, a grid computing resource, and/or any other distributed computing arrangement. Such computing devices 103 may be located in a single installation or may be distributed among many different geographical locations. For purposes of convenience, the computing device 103 is referred to herein in the singular. Even though each computing device 103 is referred to in the singular, it is understood that a plurality may be employed in the various arrangements as described above.

[0014] The logical network 141 is a logical network created and operated by the computing device 103. The logical network 141 may include various virtual or actual devices, such as one or more computing devices 143 and/or client devices 106. The logical network 141 facilitates the appearance of an exclusive network and/or internetwork

through which devices within the logical network 141 may communicate with other devices located inside and potentially outside the logical network 141.

[0015] The computing device 143 may comprise one or more virtual computers operated on the computing device 103, or the computing device 143 may comprise, for example, a server computer or any other system providing computing capability. Alternatively, a plurality of computing devices 143 may be employed that are arranged, for example, in one or more server banks or computer banks or other arrangements. A plurality of computing devices 143 together may comprise, for example, a cloud computing resource, a grid computing resource, and/or any other distributed computing arrangement. Such computing devices 143 may be located in a single installation or may be distributed among many different geographical locations. Furthermore, in various embodiments, the computing device 143 may or may not be logically present in the logical network 141. For purposes of convenience, the computing device 143 is referred to herein in the singular. Even though each computing device 143 is referred to in the singular, it is understood that a plurality may be employed in the various arrangements as described above.

[0016] Various applications and/or other functionality may be executed in the computing device 143 according to various embodiments. The components executed on the computing device 143, for example, may include the user AAA service 147. The user AAA service 147 may additionally provide authentication, authorization and/or accounting (AAA) services to the logical network 141, logical network gateway service 145 and/or other services and devices. The services may be offered using protocols such as Terminal Access Controller Access-Control System Plus (TACACS+), Remote Authentication Dial In User Service (RADIUS), Diameter or other protocols as can be appreciated.

[0017] Various applications and/or other functionality may be executed in the computing device 103 according to various embodiments. Also, various data is stored in a

data store 112 that is accessible to the computing device 103. The data store 112 may be representative of a plurality of data stores as can be appreciated. The data stored in the data store 112, for example, is associated with the operation of the various applications and/or functional entities described below.

[0018] The components executed on the computing device 103, for example, include a logical network configuration manager 121, a logical network user manager 123 and a logical network gateway service 145. The components executed on the computing device 103 may also include other applications, services, processes, systems, engines, or functionality not discussed in detail herein. The data stored in the data store 112 includes data that may be accessed by the applications, for example, logical network configuration data 131 and user accounts 134, as well as potentially other data.

[0019] In various embodiments, the components executed on the computing device 103 may utilize any type of middleware framework to communicate with a client application executing on a client device 106 or with other applications executing on the computing device 103. Examples of such frameworks include remote procedure calls, service-oriented architecture protocol (SOAP), representational state transfer (REST), Windows Communication Foundation, and other frameworks.

[0020] The logical network configuration manager 121 may be executed to provide an interface to facilitate the creation and configuration of a logical network 141 via a programmatic service call. To this end, the logical network configuration manager 121 may be executed to install one or more computing devices 143 into the logical network 141, associate a logical network 141 with a logical network gateway service 145 and configure the logical network gateway service 145. In one embodiment, the interface provided by the logical network configuration manager 121 may include electronic content, such as web pages or other types of network content, that are provided to a client device 106. In

another embodiment, the logical network configuration manager 121 may provide a middleware framework to communicate with a client application executing on a client device 106.

[0021] The logical network user manager 123 may be executed to provide an interface to facilitate management of user accounts for at least the logical network 141 and logical network gateway service 145 via a programmatic service call. In carrying out this role, the logical network user manager 123 may enable the creation, removal, importation, exportation and editing of user and group accounts, as well as the permissions associated with the accounts. As a non-limiting example, the permissions for the user/group accounts may include whether the account may establish a tunnel, the logical network(s) to which the account may connect, the network(s) and/or device(s) to which the account may connect, etc.

[0022] In one embodiment, the interface provided by the logical network user manager 123 may include electronic content, such as web pages or other types of network content, that are provided to a client device 106. In another embodiment, the logical network user manager 123 may provide a middleware framework to communicate with a client application executing on a client device 106.

[0023] The logical network user manager 123 may additionally provide authentication, authorization and/or accounting (AAA) services to the logical network 141 and logical network gateway service 145. The services may be offered using protocols such as Terminal Access Controller Access-Control System Plus (TACACS+), Remote Authentication Dial In User Service (RADIUS), Diameter or other protocols as can be appreciated.

[0024] The logical network gateway service 145 may be executed to provide the client device 106 with access to the logical network 141 via a logical network tunnel 149. The

logical network tunnels 149 facilitate the appearance of the client device 106 being present in the logical network 141 while connecting remotely from another network, such as the Internet. Additionally, the logical network tunnel 149 may further support methods of ensuring confidentiality, integrity and authentication of the communications across the logical network tunnel 149. To this end, the logical network tunnels 149 may be established using Internet Protocol Security (IPsec), Layer 2 Tunneling Protocol (L2TP), Secure Socket Layer/ Transport Layer Security (SSL/TLS) and/or other protocols as can be appreciated. The logical network gateway service 145 may use authentication, authorization and/or accounting (AAA) services related to establishing logical network tunnels 149 with client devices 106. The services may be received using protocols such as TACACS+, RADIUS, Diameter or other protocols as can be appreciated.

[0025] The data stored in the data store 112 may include, for example, logical network configuration data 131, user accounts 134 and potentially other data. The logical network configuration data 131 may include configuration information related to the logical network 141 such as a logical network identifier, the network configuration, the computing device(s) 143 installed in the logical network 141, the logical network gateway service 145 configuration, the AAA configuration for the logical network gateway service 145, etc.

[0026] Each user account 134 may be associated with a respective user of the logical network 141 and may include information such as a full name, user identifier, password, membership in one or more user groups, user/group permissions, usage logs and/or other data related to the user and AAA services. As a non-limiting example, the usage logs may include the total time each account maintained a logical network tunnel 149, the number of logical network tunnels 149, total bandwidth used, etc.

[0027] The client device 106 is representative of a plurality of devices that are associated with various customers. The client device 106 may be coupled to the network

109 and may further communicate on the logical network 141 via a logical network tunnel 149. The client device 106 may comprise, for example, a processor-based system such as a computer system. Such a computer system may be embodied in the form of a desktop computer, a laptop computer, a personal digital assistant, a cellular telephone, a set-top box, a music player, a video player, a media player, a web pad, a tablet computer system, a game console, or other devices with like capabilities. The client 106 may include a display 157. The display 157 may comprise, for example, one or more devices such as cathode ray tubes (CRTs), liquid crystal display (LCD) screens, gas plasma-based flat panel displays, LCD projectors, or other types of display devices, etc.

[0028] The client device 106 may be configured to execute various applications such as a logical network application 169, a browser 161, and/or other applications. The logical network application 169 may be executed in the client device 106 to facilitate establishing one or more logical network tunnels 149 to the logical network gateway service 145 of the computing device 103. The logical network application 169 may further be executed to manage configuration of the logical network 141, as well as access to the logical network 141 via the logical network gateway service 145. The browser 161 may be executed in the client device 106, for example, to access and render network pages, such as web pages, or other network content served up by the computing device 103 and/or other servers, thereby rendering a user interface 166 on the display 157. The browser 161 may further be executed in the client device 106 to facilitate establishing a logical network tunnel 149 to the logical network gateway service 145 on the computing device 103. The client device 106 may be configured to execute applications beyond the logical network application 169 and the browser 161, such as, for example, email applications, instant message applications, and/or other applications.

[0029] Next, a general description of the operation of the various components of the networked environment 100 is provided. To begin, the client device 106 makes a request to the logical network configuration manager 121 to create a logical network 141. The request from the client device 106 to the logical network configuration manager 121 may be made via the browser 161, the logical network application 169 or another application capable of making a programmatic service request. The client device 106 may further configure the logical network 141 to include one or more network address allocations, such as a range of Internet Protocol (IP) addresses, which may be used for devices communicating on the logical network 141. Additionally, the client device 106 may further configure the logical network 141 to include one or more computing devices 143 within the logical network 141.

[0030] Furthermore, the client device 106 makes a programmatic service request to the logical network configuration manager 121 to associate a logical network gateway service 145 with the logical network 141. The logical network gateway service 145 will permit users to communicate within the logical network 141 through the use of logical network tunnels 149. In one embodiment, users of the logical network gateway service 145 and their associated permissions are managed by the logical network user manager 123. In this embodiment, the client device 106 may request to the logical network user manager 123 for operations such as adding, importing, editing or removing users and/or permissions from the list of users of the logical network gateway service 145. The request from the client device 106 to the logical network user manager 123 may be made via the browser 161, the logical network application 169 or another application capable of making a programmatic service request.

[0031] In a second embodiment, users of the logical network gateway service 145 and their associated permissions are managed by the user AAA service 147 on the computing

device 143 or another computing device accessible to the logical network gateway service 145. In a third embodiment, management of the users of the logical network gateway service 145 may be separated from the management of the user permissions related to the logical network gateway service 145.

[0032] Once the logical network configuration manager 121 receives the necessary configuration data via one or more programmatic service requests from the client device 106, the logical network configuration manager 121 creates the logical network 141, provisions any computing devices 143 and configures the logical network gateway service 145 via a programmatic service request.

[0033] Referring next to FIG. 2, shown is a flowchart that provides one example of the operation of a portion of the logical network application 169 (FIG. 1) according to various embodiments. It is understood that the flowchart of FIG. 2 provides merely an example of the many different types of functional arrangements that may be employed to implement the operation of the portion of the logical network application 169 as described herein. As an alternative, the flowchart of FIG. 2 may be viewed as depicting an example of steps of a method implemented in the client device 106 (FIG. 1) according to one or more embodiments.

[0034] Beginning with box 203, the logical network application 169 makes a service call to the logical network configuration manager 121 (FIG. 1) to create a logical network 141. The request from the client device 106 to the logical network configuration manager 121 may be made via the browser 161, the logical network application 169 or another application capable of making a programmatic service request. The request from the client device 106 may further configure the logical network 141 to include one or more network address allocations, such as a range of Internet Protocol (IP) addresses, which may be used for devices participating within the logical network 141.

[0035] Next, at box 204, the logical network application 169 makes a service call to the logical network configuration manager 121 to include one or more computing devices 143 within the logical network 141. As a non-limiting example, the computing device(s) 143 may be a cloud computing device(s), virtual computing device(s) or any computing device(s) capable of being included within the logical network 141. In various embodiments, the computing device(s) 143 may only be able to communicate within the logical network 141 or with devices on other networks such as the Internet or other logical networks 141.

[0036] Subsequently, at box 206 the logical network application 169 makes a service call to the logical network configuration manager 121 to associate the logical network gateway service 145 with the logical network 141. The logical network gateway service 145 will permit users of remote devices to communicate within the logical network 141 through the use of logical network tunnels 149. The logical network tunnels 149 may be established using IPsec, L2TP, SSL/TLS or other protocols as can be appreciated.

[0037] Moving on, in box 209, the logical network application 169 makes a service call to the logical network configuration manager 121 to configure the logical network gateway service 145 for authenticating users. The authentication function is carried out to positively identify users and may use one or more techniques such as username/password, digital certificates, hardware tokens, biometrics and/or other techniques. The logical network gateway service 145 may authenticate users locally in the logical network gateway service 145, or it may rely in whole or in part on other devices to perform this function. If the logical network gateway service 145 relies upon other devices to perform these functions, the logical network gateway service 145 may communicate with these other devices using TACACS+, RADIUS, Diameter or other similar protocols as can be appreciated. In one embodiment, the function of authenticating users of the logical network gateway service

145 may be carried out by the logical network user manager 123. In an alternate embodiment, the functions of authenticating the users of the logical network gateway service 145 may be carried out by the computing device 143 or another computing device accessible to the logical network gateway service 145.

[0038] Next, in box 212, the logical network application 169 makes a service call to the logical network configuration manager 121 to configure the user/group permissions of the logical network gateway service 145. The authorization function may be carried out to determine the permissions assigned to a user/group. As non-limiting examples, the permissions for the user/group accounts may include whether the account may establish a logical network tunnel 149, the logical network(s) 141 accessible to the account, the network(s) and/or device(s) accessible to the account, *etc.* The logical network gateway service 145 may determine the authorization of users locally in the logical network gateway service 145, or it may rely in whole or in part on other devices to perform this function. If the logical network gateway service 145 relies upon other devices to perform these functions, the logical network gateway service 145 may communicate with these other devices using TACACS+, RADIUS, Diameter or other similar protocols as can be appreciated. In one embodiment, the function of authorizing users of the logical network gateway service 145 may be carried out by the logical network user manager 123. In an alternate embodiment, the functions of authenticating the users of the logical network gateway service 145 may be carried out by the computing device 143 or another computing device accessible to the logical network gateway service 145.

[0039] Subsequently, in box 215, the logical network application 169 makes a service call to the logical network configuration manager 121 to configure an accounting of usage for each user. As non-limiting examples, an accounting of usage may include connection time, bandwidth used, the number of logical network tunnels 149 established and other

metrics as can be appreciated. The logical network gateway service 145 may store the accounting of usage locally in the logical network gateway service 145, or it may rely in whole or in part on other devices to perform this function. If the logical network gateway service 145 relies upon other devices to perform these functions, the logical network gateway service 145 may communicate with these other devices using TACACS+, RADIUS, Diameter or other similar protocols as can be appreciated. In one embodiment, the function of accounting of usage for the logical network gateway service 145 may be carried out by the logical network user manager 123. In an alternate embodiment, the functions of accounting of usage for the logical network gateway service 145 may be carried out by the computing device 143 or another computing device accessible to the logical network gateway service 145.

[0040] Furthermore, the logical network gateway service 145 may be configured such that the authentication, authorization and accounting functions discussed in boxes 209-215 may be carried out by different devices. As a non-limiting example, the authentication function may be performed using a Lightweight Directory Access Protocol (LDAP) server accessible over the Internet, the authorization function may be performed by the logical network user manager 123 using the TACACS+ protocol, and the accounting of usage function may be performed using a computing device 143 using the Diameter protocol.

[0041] Next, in box 218, if the logical network application 169 receives a return code from the logical network configuration manager 121 indicating a failure occurred while creating and configuring the logical network 141, in box 220, the logical network application 169 may provide notice of the failure. Thereafter, execution of the portion of the logical network application 169 may end as shown. Alternatively, if the logical network application 169 receives a return code from the logical network configuration manager 121 indicating the logical network 141 was successfully created and configured, in box 221, the logical

network application 169 may provide notice of the success. Instead of or in addition to receiving a successful return code from the logical network configuration manager 121, the logical network application 169 may receive configuration data necessary for the client device 106 to establish a logical network tunnel 149 to the logical network gateway service 145. Thereafter, execution of the portion of the logical network application 169 may end as shown.

[0042] The configuration data may be in the form of a document to be read by a user, a file that may be interpreted by the logical network application 169 or other application on the client device 106 or another form as may be appreciated. The configuration data may include instructions to establish the logical network tunnel 149, the types of logical network tunnels 149 supported by the logical network gateway service 145, the network address(es) of the logical network gateway(s) 145, *etc.* Thereafter, execution of the portion of the logical network application 169 ends as shown.

[0043] Turning now to FIGS. 3A and 3B, shown is a flowchart that provides one example of the operation of a portion of the logical network configuration manager 121 (FIG. 1) according to various embodiments. It is understood that the flowcharts of FIGS. 3A and 3B provides merely an example of the many different types of functional arrangements that may be employed to implement the operation of the portion of the logical network configuration manager 121 as described herein. As an alternative, the flowcharts of FIGS. 3A and 3B may be viewed as depicting an example of steps of a method implemented in the computing device 103 (FIG. 1) according to one or more embodiments.

[0044] Beginning with box 303, the logical network configuration manager 121 creates a data structure for a logical network 141 after receiving a service call from the client device 106 (FIG. 1) to create a logical network 141. The request to the logical network configuration manager 121 from the client device 106 may be made using various

protocols, such as Hypertext Transfer Protocol (HTTP), Secure HTTP (HTTPS) and/or middle frameworks including remote procedure calls, SOAP, REST, Windows Communication Foundation, and other frameworks. The service call from the client device 106 may further configure the data structure of the logical network 141 to include one or more network address allocations, such as a range of IP addresses, which may be used for devices participating within the logical network 141.

[0045] Next, at box 304, the logical network configuration manager 121 creates a data structure to include one or more computing devices 143 within the logical network 141 after receiving a service call from the client device 106 to include one or more computing devices 143 within the logical network 141. As a non-limiting example, the computing device(s) 143 may be cloud computing device(s), virtual computing device(s) or any computing device(s) capable of being included within the logical network 141. In various embodiments, the computing device(s) 143 may only be able to communicate within the logical network 141 or with devices on other networks such as the Internet or other logical networks 141.

[0046] Subsequently, at box 306, the logical network configuration manager 121 creates a data structure to associate a logical network gateway service 145 with the logical network 141 upon receiving a service call from the client 106 to associate a logical network gateway service 145 with the logical network 141. The logical network gateway service 145 will permit users of remote devices to communicate within the logical network 141 through the use of logical network tunnels 149. The logical network tunnels 149 may be established using IPsec, L2TP, SSL/TLS or other protocols as can be appreciated.

[0047] Moving on, in box 309, the logical network configuration manager 121 creates a data structure to configure the logical network gateway service 145 for authenticating users after receiving a service call from the client 106 to configure the logical network gateway service 145 for authenticating users. The authentication function is carried out to positively

identify users and the logical network gateway service 145 may authenticate users locally in the logical network gateway service 145, or it may rely in whole or in part on other devices to perform this function. If the logical network gateway service 145 relies upon other devices to perform these functions, the logical network gateway service 145 may communicate with these other devices using TACACS+, RADIUS, Diameter or other similar protocols as can be appreciated. In one embodiment, the function of authenticating users of the logical network gateway service 145 may be carried out by the logical network user manager 123. In another embodiment, the functions of authenticating the users of the logical network gateway service 145 may be carried out by the computing device 143 or another computing device accessible to the logical network gateway service 145.

[0048] Next, in box 312, the logical network configuration manager 121 creates a data structure to configure the user permissions of the logical network gateway service 145 upon receiving a service call from the client 106 to configure the user permissions of the logical network gateway service 145. The authorization function may be carried out to determine the permissions assigned to a user. The logical network gateway service 145 may determine the authorization of users locally in the logical network gateway service 145, or it may rely in whole or in part on other devices to perform this function. If the logical network gateway service 145 relies upon other devices to perform these functions, the logical network gateway service 145 may communicate with these other devices using TACACS+, RADIUS, Diameter or other similar protocols as can be appreciated. In one embodiment, the function of authorizing users of the logical network gateway service 145 may be carried out by the logical network user manager 123. In another embodiment, the functions of authenticating the users of the logical network gateway service 145 may be carried out by the computing device 143 or another computing device accessible to the logical network gateway service 145.

[0049] Subsequently, in box 315, the logical network configuration manager 121 creates a data structure to configure an accounting of usage for each user after receiving a service call from the client 106 to configure an accounting of usage for each user. As non-limiting examples, an accounting of usage may include connection time, bandwidth used, the number of logical network tunnels 149 established and other metrics as can be appreciated. The logical network gateway service 145 may store the accounting of usage locally in the logical network gateway service 145, or it may rely in whole or in part on other devices to perform this function. If the logical network gateway service 145 relies upon other devices to perform these functions, the logical network gateway service 145 may communicate with these other devices using TACACS+, RADIUS, Diameter or other similar protocols as can be appreciated. In one embodiment, the function of accounting of usage for the logical network gateway service 145 may be carried out by the logical network user manager 123. In another embodiment, the functions of accounting of usage for the logical network gateway service 145 may be carried out by the computing device 143 or another computing device accessible to the logical network gateway service 145.

[0050] Furthermore, the data structures corresponding to the authentication, authorization and accounting functions of the logical network gateway service 145 discussed in boxes 309-315 may be configured such that they may be carried out by different devices. As a non-limiting example, the authentication function may be performed using an LDAP server accessible over the Internet, and the authorization function may be performed by the logical network user manager 123 using the TACACS+ protocol. Continuing with the example, the accounting of usage function may be performed using a computing device 143 using the Diameter protocol.

[0051] Next, in box 318, the logical network configuration manager 121 creates the logical network 141, provisions any computing devices 143 and configures the logical

network gateway service 145 via a programmatic service request. The service call may include the data structures created at least from the service calls received from the client device 106. Subsequently, in box 319, if the computing resources currently allocated to the operation of the logical network 141 and logical network gateway service 145 have reached a maximum threshold, then, in box 320, the logical network configuration manager 121 or another service may allocate additional computing resources as needed.

[0052] Moving on, in box 321, if the logical network configuration manager 121 fails to create the logical network 141 and/or receives a return code from the logical network gateway service 145 indicating a failure, or fails to receive any return code within a timeout period, in box 324, the logical network configuration manager 121 may notify the client device 106 of the failure. Thereafter, execution of the portion of the logical network configuration manager 121 ends as shown.

[0053] Alternatively, in box 327, the logical network configuration manager 121 may transmit a return code indicating the logical network 141 was successfully created and configured, and/or the logical network configuration manager 121 may transmit the configuration data necessary for the client device 106 to establish a logical network tunnel 149 to the logical network gateway service 145. The configuration data may be in the form of a document to be read by a user, a file that may be interpreted by the logical network application 169 or other application on the client device 106 or another form as may be appreciated. The configuration data may include instructions to establish the logical network tunnel 149, the types of logical network tunnels 149 supported by the logical network gateway service 145, the network address(es) of the logical network gateway(s) 145, *etc.* Thereafter, execution of the portion of the logical network configuration manager 121 ends as shown.

[0054] Moving on to FIG. 4, shown is a flowchart that provides one example of the operation of a portion of the logical network gateway service 145 (FIG. 1) according to various embodiments. It is understood that the flowchart of FIG. 4 provides merely an example of the many different types of functional arrangements that may be employed to implement the operation of the portion of the logical network gateway service 145 as described herein. As an alternative, the flowchart of FIG. 4 may be viewed as depicting an example of steps of a method implemented in the computing device 103 (FIG. 1) according to one or more embodiments.

[0055] Beginning with box 403, the logical network gateway service 145 receives a request from a client device 106 to establish a logical network tunnel 149 (FIG. 1). In response, the logical network gateway service 145 may request authentication credentials from the client device 106. The initial client request may be accomplished using Internet Security Association and Key Management Protocol (ISAKMP), an SSL/TLS handshake or through other techniques as can be appreciated. Next, in box 406, the logical network gateway service 145 may receive and authenticate credentials from the client device 106 using the logical network user manager 123, the user AAA service 147 on a computing device 143 or another authentication service. To this end, the authentication may be carried out using TACACS+, RADIUS, Diameter or other similar protocols as can be appreciated.

[0056] If, in box 409, the client authentication fails or no response is received within a timeout period, in box 430, the logical network gateway service 145 transmits a failure code to the client and execution of this portion of the logical network gateway service 145 ends as shown. Alternatively, if the client authentication succeeds, in box 412, the logical network gateway service 145 may request permissions associated with the client using the logical network user manager 123, the user AAA service 147 on a computing device 143 or

another authorization service. To this end, the authorization may be carried out using TACACS+, RADIUS, Diameter or other similar protocols as can be appreciated.

[0057] If, in box 415, the client fails to have the necessary permissions or no response is received within a timeout period, in box 430, the logical network gateway service 145 transmits a failure code to the client and execution of this portion of the logical network gateway service 145 ends as shown. Alternatively, in box 418, if the computing resources currently allocated to the operation of the logical network 141 and the logical network gateway service 145 have reached a maximum threshold, then, in box 421, the logical network gateway service or another service may allocate additional computing resources as needed.

[0058] Next, in box 424, the logical network gateway service 145 may begin or continue negotiating the establishment of the logical network tunnel 149 using ISAKMP, an SSL/TLS handshake or through other techniques as can be appreciated. If, in box 427, the logical network tunnel 149 fails to establish, the logical network gateway service 145 may, in box 430, transmit an appropriate return code to the client and execution of this portion of the logical network gateway service 145 ends as shown. Alternatively, if the logical network tunnel 149 is successfully established, the logical network gateway service 145 may, in box 433, transmit an appropriate return code to the client and execution of this portion of the logical network gateway service 145 ends as shown.

[0059] Referring next to FIG. 5, shown is a flowchart that provides one example of the operation of a portion of the logical network configuration manager 121 (FIG. 1) according to various embodiments. It is understood that the flowchart of FIG. 5 provides merely an example of the many different types of functional arrangements that may be employed to implement the operation of the portion of the logical network configuration manager 121 as described herein. As an alternative, the flowchart of FIG. 5 may be viewed as depicting an

example of steps of a method implemented in the computing device 103 (FIG. 1) according to one or more embodiments.

[0060] Beginning with box 503, the logical network configuration manager 121 receives a request from a client device 106 to establish communications over the network 109. In response, the logical network gateway service 145 may request authentication credentials from the client device 106. The initial client request may be accomplished using HTTP, HTTPS, a middleware framework or other techniques as can be appreciated. Next, in box 506, the logical network configuration manager 121 may receive and authenticate credentials from the client device 106 using the logical network user manager 123, the user AAA service 147 on a computing device 143 or another authentication service. To this end, the authentication may be carried out using TACACS+, RADIUS, Diameter or other similar protocols as can be appreciated.

[0061] If, in box 509, the client authentication fails or no response is received within a timeout period, in box 521, the logical network configuration manager 121 transmits an appropriate failure code to the client and execution of this portion of the logical network configuration manager 121 ends as shown. Alternatively, if the client authentication succeeds, in box 512, the logical network configuration manager 121 may request permissions associated with the client using the logical network user manager 123, the user AAA service 147 on a computing device 143 or another authorization service. To this end, the authorization may be carried out using TACACS+, RADIUS, Diameter or other similar protocols as can be appreciated.

[0062] Then, in box 515, the logical network configuration manager 121 determines if the client possesses the necessary authorization to disable other user accounts. The authorization may at least in part be determined by the permissions associated with the client account as identified during the authorization action. If the client does not possess

the necessary authorization, or if no response is received within a timeout period, in box 521, the logical network configuration manager 121 transmits an appropriate failure code to the client and execution of this portion of the logical network configuration manager 121 ends as shown. Alternatively, in box 524, if the client is authorized to disable a user account, the logical network configuration manager 121 may receive input associated with disabling a user account. Such input may be related to the account identifier for the account that is to be disabled, duration for which the account is disabled, time at which the account is to be disabled, whether the account should be disconnected from a current logical network tunnel 149, *etc.* Similarly, more than one account and/or groups may also be disabled using similar techniques.

[0063] Next, in box 527, the logical network configuration manager 121 may transmit the information associated with disabling the account(s)/group(s) to the logical network gateway service 145, the logical network user manager 123, the user AAA service 147 on a computing device 143 and/or another configured authentication/authorization service, in addition to potentially other actions that may be taken. Subsequently, in box 530, if the logical network configuration manager 121 fails to receive a successful acknowledgement, or any acknowledgement within a timeout period, in box 521, the logical network configuration manager 121 transmits an appropriate failure code to the client and execution of this portion of the logical network configuration manager 121 ends as shown.

[0064] Alternatively, if the notifications sent are successfully acknowledged by the associated devices and/or service, then the logical network configuration manager 121 may, in box 533, transmit an appropriate return code to the client and execution of this portion of the logical network configuration manager 121 ends as shown.

[0065] Moving on to FIG. 6, shown is a schematic block diagram of the computing device 103 according to an embodiment of the present disclosure. The computing device

103 includes at least one processor circuit, for example, having a processor 603 and a memory 606, both of which are coupled to a local interface 609. To this end, the computing device 103 may comprise, for example, at least one server computer or like device. The local interface 609 may comprise, for example, a data bus with an accompanying address/control bus or other bus structure as can be appreciated.

[0066] Stored in the memory 606 are both data and several components that are executable by the processor 603. In particular, stored in the memory 606 and executable by the processor 603 are the logical network configuration manager 121, the logical network user manager 123, the logical network gateway service 145 and potentially other applications. Also stored in the memory 606 may be a data store 112 and other data. In addition, an operating system may be stored in the memory 606 and executable by the processor 603.

[0067] Turning now to FIG. 7, shown is a schematic block diagram of the client device 106 according to an embodiment of the present disclosure. The client device 106 includes at least one processor circuit, for example, having a processor 703 and a memory 706, both of which are coupled to a local interface 709. To this end, the client device 106 may comprise, for example, a processor-based system such as a computer system. Such a computer system may be embodied in the form of a desktop computer, a laptop computer, a personal digital assistant, a cellular telephone, a set-top box, a music player, a video player, a media player, a web pad, a tablet computer system, a game console, or other devices with like capabilities. The local interface 709 may comprise, for example, a data bus with an accompanying address/control bus or other bus structure as can be appreciated.

[0068] Stored in the memory 706 are both data and several components that are executable by the processor 703. In particular, stored in the memory 706 and executable

by the processor 703 are the logical network application 169 and potentially other applications. In addition, an operating system may be stored in the memory 706 and executable by the processor 703.

[0069] With reference to FIGS. 6 and 7, it is understood that there may be other applications that are stored in the memories 606 or 706 and are executable by the respective processors 603 or 703 as can be appreciated. Where any component discussed herein is implemented in the form of software, any one of a number of programming languages may be employed such as, for example, C, C++, C#, Objective C, Java, Javascript, Perl, PHP, Visual Basic, Python, Ruby, Delphi, Flash, or other programming languages.

[0070] A number of software components are stored in the memories 606 or 706 and are executable by the respective processors 603 or 703. In this respect, the term "executable" means a program file that is in a form that can ultimately be run by the processors 603 or 703. Examples of executable programs may be, for example, a compiled program that can be translated into machine code in a format that can be loaded into a random access portion of the memories 606 or 706 and run by the respective processors 603 or 703, source code that may be expressed in proper format such as object code that is *capable of being loaded into a random access portion of the memories 606 or 706* and executed by the respective processors 603 or 703, or source code that may be interpreted by another executable program to generate instructions in a random access portion of the memories 606 or 706 to be executed by the respective processors 603 or 703, *etc.* An executable program may be stored in any portion or component of the memories 606 or 706 including, for example, random access memory (RAM), read-only memory (ROM), hard drive, solid-state drive, USB flash drive, memory card, optical disc

such as compact disc (CD) or digital versatile disc (DVD), floppy disk, magnetic tape, or other memory components.

[0071] The memories 606 or 706 are defined herein as including both volatile and nonvolatile memory and data storage components. Volatile components are those that do not retain data values upon loss of power. Nonvolatile components are those that retain data upon a loss of power. Thus, the memories 606 or 706 may comprise, for example, random access memory (RAM), read-only memory (ROM), hard disk drives, solid-state drives, USB flash drives, memory cards accessed via a memory card reader, floppy disks accessed via an associated floppy disk drive, optical discs accessed via an optical disc drive, magnetic tapes accessed via an appropriate tape drive, and/or other memory components, or a combination of any two or more of these memory components. In addition, the RAM may comprise, for example, static random access memory (SRAM), dynamic random access memory (DRAM), or magnetic random access memory (MRAM) and other such devices. The ROM may comprise, for example, a programmable read-only memory (PROM), an erasable programmable read-only memory (EPROM), an electrically erasable programmable read-only memory (EEPROM), or other like memory device.

[0072] Also, the respective processors 603 or 703 may represent multiple processors and the respective memories 606 or 706 may represent multiple memories that operate in parallel processing circuits, respectively. In such a case, the local interfaces 609 or 709 may be an appropriate network 109 (FIG. 1) that facilitates communication between any two of the respective multiple processors 603 or 703, between any respective processors 603 or 703 and any of the respective memories 606 or 706, or between any two of the respective memories 606 or 706, etc. The local interfaces 609 or 709 may comprise additional systems designed to coordinate this communication, including, for example,

performing load balancing. The processors 603 or 703 may be of electrical or of some other available construction.

[0073] Although the logical network configuration manager 121, logical network user manager 123, logical network gateway service 145, logical network application 169 and other various systems described herein may be embodied in software or code executed by general purpose hardware as discussed above, as an alternative the same may also be embodied in dedicated hardware or a combination of software/general purpose hardware and dedicated hardware. If embodied in dedicated hardware, each can be implemented as a circuit or state machine that employs any one of or a combination of a number of technologies. These technologies may include, but are not limited to, discrete logic circuits having logic gates for implementing various logic functions upon an application of one or more data signals, application specific integrated circuits having appropriate logic gates, or other components, *etc.* Such technologies are generally well known by those skilled in the art and, consequently, are not described in detail herein.

[0074] The flowcharts of FIGS. 2-5 show the functionality and operation of an implementation of portions of the logical network configuration manager 121, logical network gateway service 145 and logical network application 169. If embodied in software, each block may represent a module, segment, or portion of code that comprises program instructions to implement the specified logical function(s). The program instructions may be embodied in the form of source code that comprises human-readable statements written in a programming language or machine code that comprises numerical instructions recognizable by a suitable execution system such as processors 603 or 703 in a computer system or other system. The machine code may be converted from the source code, *etc.* If embodied in hardware, each block may represent a circuit or a number of interconnected circuits to implement the specified logical function(s).

[0075] Although the flowcharts of FIGS. 2-5 show a specific order of execution, it is understood that the order of execution may differ from that which is depicted. For example, the order of execution of two or more blocks may be scrambled relative to the order shown. Also, two or more blocks shown in succession in FIGS. 2-5 may be executed concurrently or with partial concurrence. Further, in some embodiments, one or more of the blocks shown in FIGS. 2-5 may be skipped or omitted. In addition, any number of counters, state variables, warning semaphores, or messages might be added to the logical flow described herein, for purposes of enhanced utility, accounting, performance measurement, or providing troubleshooting aids, *etc.* It is understood that all such variations are within the scope of the present disclosure.

[0076] Also, any logic or application described herein, including the logical network configuration manager 121, logical network user manager 123, logical network gateway service 145 and logical network application 169, that comprises software or code can be embodied in any non-transitory computer-readable medium for use by or in connection with an instruction execution system such as, for example, processors 603 or 703 in a computer system or other system. In this sense, the logic may comprise, for example, statements including instructions and declarations that can be fetched from the computer-readable medium and executed by the instruction execution system. In the context of the present disclosure, a "computer-readable medium" can be any medium that can contain, store, or maintain the logic or application described herein for use by or in connection with the instruction execution system. The computer-readable medium can comprise any one of many physical media such as, for example, magnetic, optical, or semiconductor media. More specific examples of a suitable computer-readable medium would include, but are not limited to, magnetic tapes, magnetic floppy diskettes, magnetic hard drives, memory cards, solid-state drives, USB flash drives, or optical discs. Also, the computer-readable medium

may be a random access memory (RAM) including, for example, static random access memory (SRAM) and dynamic random access memory (DRAM), or magnetic random access memory (MRAM). In addition, the computer-readable medium may be a read-only memory (ROM), a programmable read-only memory (PROM), an erasable programmable read-only memory (EPROM), an electrically erasable programmable read-only memory (EEPROM), or other type of memory device.

[0077] Various example embodiments of the disclosure can be described by the following clauses:

[0078] Clause 1. A non-transitory computer-readable medium embodying a program executable in a computing device, the program comprising:

code that creates, upon receiving a first service call in at least one computing device, a data structure describing a logical network gateway;

code that transmits, in response to the first service call, a handle for the logical network gateway;

code that creates, upon receiving a second service call in the at least one computing device, a data structure describing a plurality of clients of the logical network gateway;

code that transmits, in response to the second service call, a handle for the clients;

code that creates, upon receiving a third service call in the at least one computing device, a data structure describing a plurality of permissions associated with the clients;

code that transmits, in response to the third service call, a handle for the permissions associated with the clients;

code that creates, upon receiving a fourth service call in the at least one computing device, a data structure describing an accounting of usage of the logical network gateway by the clients;

code that transmits, in response to the fourth service call, a handle for the accounting of usage of the logical network gateway by the clients;

code that creates, upon receiving a fifth service call in the at least one computing device, a logical network that includes the logical network gateway, the clients, the permissions associated with the clients and the accounting of usage of the logical network gateway by the clients;

code that transmits, in response to the fifth service call, configuration data associated with a client device establishing a connection with the logical network gateway.

[0079] Clause 2. The non-transitory computer-readable medium of Clause 1, wherein the logical network gateway further comprises a plurality of logical network gateways organized in a distributed computing configuration.

[0080] Clause 3. A system, comprising:

at least one computing device; and

a logical network configuration manager executable in the at least one computing device, the logical network configuration manager comprising:

logic that creates a logical network upon receiving a service call, wherein the logical network comprises a logical network gateway and a plurality of client accounts associated with the logical network gateway; and

logic that sends confirmation data associated with creation of the logical network.

[0081] Clause 4. The system of Clause 3, wherein the logical network gateway further comprises a plurality of logical network gateways arranged in a distributed computing configuration.

[0082] Clause 5. The system of Clause 3, wherein the client accounts associated with the logical network gateway are used to further establish a connection with the logical network gateway from a plurality of network addresses.

[0083] Clause 6. The system of Clause 3, wherein the logical network gateway facilitates communication between a client device and at least one logical network.

[0084] Clause 7. The system of Clause 3, wherein the client accounts associated with the logical network gateway are stored in at least one computing device within the logical network.

[0085] Clause 8. The system of Clause 3, further comprising a logical network user manager executable, the logical network user manager comprising:

logic that creates the client accounts upon receiving at least one service call;

logic that sends, in response to the at least one service call, confirmation data corresponding to the creation of the client accounts;

logic that associates the client accounts with the logical network gateway upon receiving the at least one service call; and

logic that sends, in response to the at least one service call, confirmation data corresponding to the association of the client accounts with the logical network gateway.

[0086] Clause 9. The system of Clause 3, wherein the logical network further comprises a plurality of permissions corresponding to the client accounts associated with the logical network gateway.

[0087] Clause 10. The system of Clause 9, wherein the permissions further comprise permissions granting, to the client accounts, network access to a plurality of network address destinations.

[0088] Clause 11. The system of Clause 9, wherein the permissions further comprise limiting network access of the client accounts from a plurality of network address destinations.

[0089] Clause 12. The system of Clause 3, wherein the logical network further comprises configuration for an accounting of usage of the logical network gateway by the client accounts associated with the logical network gateway.

[0090] Clause 13. The system of Clause 12, wherein the accounting of usage of the logical network gateway is stored on at least one computing device within the logical network.

[0091] Clause 14. The system of Clause 12, wherein the accounting of usage of the logical network gateway is stored on the at least one computing device.

[0092] Clause 15. A method, comprising the steps of:

creating, upon receiving a service call in at least one computing device, a logical network comprising a logical network gateway, a plurality of client accounts associated with the logical network gateway and a plurality of permissions corresponding to the client accounts; and

transmitting, in response to the service call to the at least one computing device, configuration data associated with a client device establishing a connection with the logical network gateway.

[0093] Clause 16. The method of Clause 15, wherein the logical network gateway further comprises a plurality of logical network gateways arranged in a distributed computing configuration.

[0094] Clause 17. The method of Clause 15, wherein the logical network further comprises at least one computing device within the logical network.

[0095] Clause 18. The method of Clause 15, wherein the client accounts further comprise data defining membership in at least one client group associated with the logical network gateway.

[0096] Clause 19. The method of Clause 18, wherein the client accounts and the at least one client group are stored on at least one computing device within the logical network.

[0097] Clause 20. The method of Clause 18, wherein the client accounts and the at least one client group are stored in the at least one computing device.

[0098] Clause 21. The method of Clause 15, wherein the permissions corresponding to the client accounts further comprise permissions granting to the client accounts network access to a plurality of network address destinations.

[0099] Clause 22. The method of Clause 15, wherein the permissions corresponding to the client accounts further comprise limiting network access of the client accounts from a plurality of network address destinations.

[00100] Clause 23. A system, comprising:

at least one computing device; and

a logical network gateway service executable in the at least one computing device,

the logical network gateway service comprising:

logic that receives a request over a network from a client to establish a logical network tunnel over the network;

logic that receives at least one credential over the network from the client associated with establishing the logical network tunnel;

logic that authenticates the client based at least in part upon the at least one credential;

logic that monitors a use of a plurality of first computing resources assigned to the logical network gateway service;

logic that allocates at least one available second computing resource to augment the first computing resources if the use meets a predefined allocation threshold; and

logic that negotiates over the network with the client to establish the logical network tunnel.

[00101] Clause 24. The system of Clause 23, wherein the logical network gateway service further comprises logic that obtains a plurality of permissions from a data store associated with the client establishing the logical network tunnel.

[00102] Clause 25. The system of Clause 23, wherein the logical network gateway service further comprises logic that releases a portion of the first computing resources if the use meets a predefined release threshold.

[00103] Clause 26. The system of Clause 23, wherein the logical network gateway service further comprises logic that terminates the logical network tunnel based at least in part upon receiving a notification from an administrator to terminate the logical network tunnel.

[00104] It should be emphasized that the above-described embodiments of the present disclosure are merely possible examples of implementations set forth for a clear understanding of the principles of the disclosure. Many variations and modifications may be made to the above-described embodiment(s) without departing substantially from the spirit and principles of the disclosure. All such modifications and variations are intended to be included herein within the scope of this disclosure and protected by the following claims.

Claims

Therefore, the following is claimed:

1. A system, comprising:
 - at least one computing device; and
 - a logical network configuration manager executable in the at least one computing device, wherein upon execution, the logical network configuration manager causes the at least one computing device to at least:
 - receive, via a logical network gateway operated by a computing service provider, at least one programmatic service call from a client device associated with a customer of the computing service provider to connect to a logical network operated by the computing service provider;
 - create, responsive to receipt of the at least one programmatic service call from the client device, a plurality of customer accounts associated with the logical network, individual ones of the plurality of customer accounts associated with respective ones of a plurality of clients;
 - create, responsive to receipt of the at least one programmatic service call from the client device, a plurality of accountings of usage of the logical network, individual ones of the plurality of accountings of usage associated with respective ones of the plurality of customer accounts;
 - create, responsive to receipt of the at least one programmatic service call from the client device, a programmatic configuration of the logical network comprising the logical network gateway and the plurality of customer accounts;
 - create, responsive to receipt of the at least one programmatic service call from the client device, a plurality of permissions associated with the logical network, individual ones of the plurality of permissions associated with the respective ones of the plurality of customer accounts;

create, responsive to receipt of the at least one programmatic service call from the client device, a logical network tunnel between the client device and a plurality of virtual computers attached to the logical network according to the programmatic configuration, wherein the virtual computers are associated with network addresses specified by the customer and wherein the computing service provider operates a plurality of logical networks for the plurality of customer accounts associated with the computing service provider; and

send confirmation data associated with creation of the logical network tunnel to the client device.

2. The system of claim 1, wherein the logical network gateway further comprises a plurality of logical network gateways arranged in a distributed computing configuration.

3. The system of claim 1, wherein the plurality of customer accounts associated with the logical network gateway are used to further establish a connection with the logical network gateway from a plurality of network addresses.

4. The system of claim 1, wherein the logical network gateway facilitates communication between the client device and at least one logical network.

5. The system of claim 1, wherein the plurality of customer accounts associated with the logical network gateway are stored in at least one computing device within the logical network.

6. The system of claim 1, further comprising a logical network user manager executable in the at least one computing device, wherein upon execution, the logical network user manager causes the at least one computing device to:

send, in response to the at least one programmatic service call, confirmation data corresponding to the creation of the plurality of customer accounts;

associate the plurality of customer accounts with the logical network gateway upon receiving the at least one programmatic service call; and

send, in response to the at least one programmatic service call, confirmation data corresponding to the association of the plurality of customer accounts with the logical network gateway.

7. The system of claim 6, wherein at least one of the plurality of permissions further comprises limiting network access of the plurality of customer accounts from a plurality of network address destinations.

8. The system of claim 1, wherein the logical network further comprises a configuration for the plurality of accounting of usages of the logical network gateway by the plurality of customer accounts associated with the logical network gateway.

9. The system of claim 1, wherein the plurality of accountings of usage comprises at least one of a connection time, bandwidth, and a number of logical network tunnels created.

10. A method, comprising:

creating, by a computing service provider via at least one computing device, a logical network for a customer within an environment provided by the computing service provider, wherein the logical network includes one or more virtual computers associated with a plurality of network addresses specified by the customer;

creating, by the at least one computing device, a plurality of customer accounts associated with the logical network responsive to receipt of at least one programmatic service call from a client device, individual ones of the plurality of customer accounts associated with respective ones of a plurality of clients;

creating, by the at least one computing device, a plurality of accountings of usage responsive to receipt of the at least one programmatic service call from the client device, individual ones of the plurality of accountings of usage associated with respective ones of the plurality of customer accounts;

creating, by the at least one computing device, a plurality of permissions associated with the logical network responsive to receipt of at least one programmatic service call from the client device, individual ones of the plurality of permissions associated with the respective ones of the plurality of customer accounts;

creating, by the at least one computing device, a programmatic configuration of the logical network comprising a logical network gateway and the plurality of customer accounts responsive to receipt of the at least one programmatic service call from the client device;

creating, by the at least one computing device, a logical network tunnel between the client device and the logical network in response to receipt of the at least one programmatic service call from the client device such that the client device appears as being present in the logical network; and

transmitting, by the at least one computing device, confirmation data associated with the creation of the logical network tunnel to the client device.

11. The method of claim 10, wherein the logical network gateway further comprises a plurality of logical network gateways arranged in a distributed computing configuration.

12. The method of claim 10, wherein the logical network further comprises at least one computing device within the logical network.

13. The method of claim 10, wherein the plurality of customer accounts further comprise data defining membership in at least one client group associated with the logical network gateway.

14. The method of claim 13, wherein the plurality of customer accounts and the at least one client group are stored on at least one computing device within the logical network.

15. The method of claim 10, wherein the plurality of permissions further comprises granting to the plurality of customer accounts network access to a plurality of network address destinations.

16. The method of claim 10, further comprising a plurality of permissions corresponding to individual ones of the plurality of customer accounts, at least one of the plurality of permissions further comprising limiting network access of the plurality of customer accounts from a plurality of network address destinations.