

1203

SPECIFICATION
GARBAGE DISPOSING DEVICE
BACKGROUND OF THE INVENTION

1. Field of the Invention

5 The present invention relates to a garbage disposing device of an energy saving type which is capable of efficiently decomposing food wastes and deodorizing unpleasant odor of a gas resulting from the decomposition.

2. Disclosure of the Prior Art

10 In the past, garbage disposing devices for decomposing food wastes by a decomposer or a microbial transformation have been known. For example, a garbage disposing device **1C** of the prior art is shown in FIG. 11. The disposing device **1C** comprises a housing **10C**, a vessel **20C** for storing therein food wastes, and a decomposer for decomposing
15 the food wastes placed in the vessel, and an ozone deodorizer unit **50C**. The housing **10C** has an air intake port **11C** and an air discharge port **12C**. The vessel **20C** has an air inlet **21C** and an air outlet **22C**, and is incorporated in the housing **10C**. Wood chips carrying thereon microbes are used as the decomposer. Numeral **90C** designates an
20 agitator for agitating a mixture of the decomposer and the food wastes in the vessel **20C**. Numeral **3C** designates a planar heater for heating the decomposer in the vessel **20C**.

 An intake passage **16C** is formed in the housing **10C** to extend from the air intake port **11C** to the air inlet **21C** for introducing a fresh
25 air into the vessel **20C**. A heater **52C** is arranged in the intake passage **16C** to warm the fresh air. The warmed fresh air is useful to activate

the microbial transformation of the food wastes. In particular, when the garbage disposing device 1C is used at an outdoor in winter season, a cold air supplied from the outside into the vessel 20C lowers an efficiency of the microbial transformation of the food wastes.

- 5 Therefore, it is necessary to warm the fresh air in the intake passage 16C before the fresh air is introduced into the vessel 20C. Numeral 9C designates a fan for sending the fresh air from the outside into the intake passage 16C. An exhaust passage 40C is formed in the housing 10C to extend from the air outlet 22C to the air discharge port 12C.
- 10 Unpleasant odor in a gas resulting from the microbial transformation of the food wastes is deodorized by the ozone deodorizer unit 50C arranged in the exhaust passage 40C. Numeral 4C designates a fan for giving a forced flow of the air exhausted from the deodorizer unit 50C to the air discharge port 12C.

15 SUMMARY OF THE INVENTION

- A primary object of the present invention is to provide a garbage disposing device of an energy saving type from the viewpoint of conservation of energy resources in recent years. That is, a garbage disposing device comprises a housing having an air intake port and an
- 20 air discharge port, and a vessel mounted within the housing to store therein food wastes. The vessel has an air inlet and an air outlet. An intake passage is formed in the housing exteriorly of the vessel, and extends from the intake port to the air inlet for introducing a fresh air into the vessel. An exhaust passage is formed within the housing
- 25 exteriorly of the vessel to extend from the air outlet to the discharge port for discharging therethrough an air containing unpleasant odor

developed in the vessel due to a decomposition of the food wastes. The garbage disposing device comprises a deodorizer unit which is formed with a catalyst for decomposing the unpleasant odor, a heater for activating the catalyst, and a case for incorporating therein the catalyst and the heater. The garbage disposing device of the present invention is characterized in that the deodorizer unit is arranged in the exhaust passage such that an outer surface of the case is exposed in the intake passage, and the fresh air in the intake passage is warmed by a contact with the outer surface of the case inevitably heated by the heater.

Therefore, it is possible to stably provide the warmed the fresh air into the vessel to enhance the decomposition of the food wastes by application of a waste heat given off from the case of the deodorizing unit without arranging an additional heater in the intake passage. In addition, since it is not necessary to take a space for arranging the additional heater in the housing, there is an advantage of small-sizing the garbage disposing device.

In a preferred embodiment of the present invention, the intake passage is formed in a clearance between the vessel and the housing to extend from first and second air-intake ports formed in a bottom of the housing to the air inlet of the vessel, and the exhaust passage is located within the clearance to locate the deodorizer unit within the intake passage for heat transfer between the case heated by the heater and the fresh air being introduced through the intake passage. The garbage disposing device includes a control unit for controlling the heater. The control unit comprises electronic components carried on a board. The first air-intake port is located below the deodorizer unit to allow a part of the fresh air to pass by the case of the deodorizer unit. The second

air-intake port is located below the control unit to allow a part of the fresh air to pass by the electronic components of the control unit. In this case, the fresh air being introduced into the vessel can be warmed more efficiently by application of a waste heat given off from the electric components in addition to the waste heat given off from the case of the deodorizer unit. According to the heat transfer between the electric components and the fresh air, it is possible to prevent an
5 overheat of the electric components.

It is preferred that a blower is arranged in the exhaust passage upstream of the deodorizer unit to give a forced flow of the air from
10 inside of the vessel to the discharge port through the deodorizer unit. In particular, it is preferred that a return path is provided to extend from the exhaust passage at a portion between the blower and the deodorizer unit into the vessel for returning a portion of the air being discharged
15 through the exhaust passage into the vessel as a forced return flow. The return flow is mixed with the fresh air supplied into the vessel from the intake passage to generate a convection of the mixed air in the vessel. As a result, it is possible to avoid the occurrence of a situation that the fresh air supplied in the vessel is instantly exhausted from the vessel
20 through the air outlet without most of the fresh air being effectively used for the decomposition of the food wastes.

It is also preferred that the heater is of a U-shaped configuration having a pair of legs, and fixed in the case of the deodorizer unit with an open top end of the U-shape oriented in an upstream direction of the exhaust passage. It is also preferred that a flow splitter is placed near
25 the open top end of the heater in order to diverge the incoming air flow into sub-flows which pass by the legs of the heater, respectively. In this

case, there is an advantage that the air containing unpleasant odor can be sufficiently heated by the U-shaped heater before reaching the catalyst.

It is further preferred that a dilution chamber is arranged in the exhaust passage downstream of the deodorizer unit. The dilution chamber is provided with a diluting fan which introduces a fresh air directly from outside of the housing for diluting an air emerging out of the deodorizer unit by the fresh air. In addition, it is preferred that the dilution chamber extends in a lengthwise direction crossing with a direction of the air flow emerging out of the deodorizer unit and is formed at opposite ends of the lengthwise direction respectively with the discharge port and an air hole introducing the fresh air into the dilution chamber. Moreover, it is preferred that a baffle is provided at juncture of the deodorizer unit and the dilution chamber for directing the air emerging out of the deodorizer unit towards the discharge port, and the diluting fan is placed between the baffle and the air hole for introducing the fresh air into the dilution chamber and merging it with the air emerging out of the deodorizer unit.

In another preferred embodiment of the preset invention, the heater is of a U-shaped configuration having an open top end and a closed bottom end, and fixed in the deodorizer unit with the open top end oriented upstream of the exhaust passage and with the closed bottom end directed to the catalyst. A blower is provided in the exhaust passage upstream of the U-shaped heater to give a forced flow of the air from inside of the vessel through the deodorizer unit. A first temperature sensor is provided adjacent the closed bottom of the U-shaped heater upstream of the catalyst to give a heater temperature, and

a second temperature sensor is provided adjacent downstream of the catalyst to give a catalyst temperature. A control unit is provided to compare the catalyst temperature with the heater temperature for recognizing an abnormal condition when the catalyst temperature is
5 lower than the heater temperature, At the abnormal condition, the control unit stops a supply of electric current to the U-shaped heater and the blower.

These and still other objects and advantages will become apparent from the following description of the preferred embodiments of the
10 invention when taken in conjunction with the attached drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a perspective view of a garbage disposing device of the present invention;

FIG. 2 is a cross section of the garbage disposing device;

15 FIG. 3 is a cross section of the garbage disposing device;

FIG. 4 is a cross section of an intake passage of the garbage disposing device;

In FIGS. 5A to 5C, FIG. 5A is a cross-sectional view of a deodorizer unit of the garbage disposing device, FIG. 5B is a temperature curve at
20 a normal condition of the deodorizer unit, and FIG. 5C is a temperature curve at an abnormal condition of the deodorizer unit;

FIG. 6 is a cross section of an exhaust passage of the garbage disposing device;

FIG. 7 is a partially bottom view of the garbage disposing device;

25 FIG. 8 is schematic diagram of a control unit of the garbage disposing device;

FIG. 9 is a cross-sectional view of a return path of the garbage disposing device;

FIG. 10 is a partially cross-sectional view showing an exhaust extension tube connected to a diluting duct of the garbage disposing device; and

FIG. 11 is a perspective view of a garbage disposing device of the prior art.

DETAILED DESCRIPTION OF PREFERRED EMBODIMENTS

As shown in FIGS. 1 to 3, a garbage disposing device **1** comprises

10 a housing **10** having a lid **11**, and a vessel **20** mounted within the housing to store therein food wastes. The housing **10** has an air intake port **12** and an air discharge port **13**. The vessel **20** has an air inlet **21** and an air outlet **22**. A decomposer **2** capable of providing a microbial transformation of the food wastes is placed in the vessel **20**. The

15 microbial transformation means that organic compounds contained in the food wastes are transformed by the help of microbe's enzymes. For example, a sawdust carrying thereon microbes may be used as the decomposer **2**. In addition, a decomposer disclosed in Japanese Patent Publication [KOKOKU] No. 2-30760 can be used. An agitator **90** is

20 arranged in the vessel **20** to uniformly mix the food wastes with the decomposer **2**. The agitator **90** is formed with a horizontal shaft **91** rotatably supported about its axis to the housing **10**, a plurality of agitating rods **92** projecting from the horizontal shaft, and a drive unit **93** for rotating the horizontal shaft through a chain **94**. Numeral **3**

25 designates a planar heater attached to an outer surface of the vessel **20** to heat the decomposer **2**.

A moisture sensor 70 is attached to an inner surface of the vessel 20 to measure a moisture content of the decomposer 2. According to the moisture content, the planar heater 3, agitator 90, and a blower 4 explained below, can be controlled by a control unit 5, as shown in FIG.

5 8. Numeral 6 designates a supplemental heater arranged at an upper portion of a side wall of the vessel 20. The supplemental heater 6 is useful to prevent the occurrence of dew in the vessel 20 and enhance the microbial transformation of the food wastes. The air outlet 22 and the air inlet 21 are positioned behind a depending wall 14 of the housing 10
10 which extends along the circumference of a top opening of the vessel 20, as shown in FIG. 4. Therefore, a fresh air is introduced into the vessel 20 from the air inlet 21 through a clearance 15 between the depending wall 14 and the vessel, as shown by the arrow of FIG. 4. An air containing unpleasant odor resulting from the microbial transformation
15 of the food wastes is exhausted from the air outlet 22 through the clearance 15, as shown in FIG. 2.

A main intake passage is formed within the housing 10 exteriorly of the vessel 20 to extend from the air intake port 12 to the air inlet 21 for introducing a fresh air into the vessel. An exhaust passage is formed
20 in the housing 10 with a duct 40 extending from the air outlet 22 to the air discharge port 13 for discharging therethrough the air containing unpleasant odor. In this garbage disposing device 1, a clearance 30 formed between a side wall of the vessel 20 and the duct 40 of the exhaust passage and between a side wall of the housing 10 and the duct
25 is defined as the intake passage, as shown in FIG. 2. A deodorizer unit 50 is mounted in the exhaust passage. The deodorizer unit 50 comprises

a catalyst **51** for removing the unpleasant odor of the air to be discharged through the air discharge port **13**, and a U-shaped heater **52** arranged at the upstream of the catalyst to heat the catalyst and the air containing the unpleasant odor. The catalyst **51** is formed with a
5 honeycomb structure made of a ceramic material and platinum deposited on the honeycomb structure.

The catalyst **51** and the U-shaped heater **52** are placed in a heater case **56** having top and bottom openings for allowing the air being discharged to pass through the U-shaped heater case. The U-shaped
10 heater **52** has a pair of legs **53** and an arcuate portion **54** therebetween, and fixed in the heater case **56** with an open top end of the U-shape configuration oriented in an upstream direction of the exhaust passage, and with the arcuate portion **54** directed to the catalyst **51**, as shown in FIG. 6. Numeral **55** designates a flow splitter placed near the open top
15 end of the U-shaped heater **52** in order to diverge the incoming air flow into sub-flows which pass by the legs **53** of the U-shaped heater, respectively. The sub flows diverged by the flow splitter **55** are uniformly heated by the legs **53** of the U-shaped heater **52**. The heater case **56** is disposed such that an outer surface of the heater case is
20 exposed in the intake passage, and the fresh air in the intake passage is warmed by a contact with the outer surface of the heater case inevitably heated by the U-shaped heater **52**. In other words, the outer surface of the heater case **56** exposed in the intake passage effects as a waste-heat recover section. Alternatively, the intake passage may be formed by
25 an intake duct extending from the air intake port **12** to the air inlet **21** such that an outer surface of the heater case **56** is exposed in the intake

duct.

The control unit 5 carries thereon electric components for controlling the U-shaped heater 52. An additional air-intake port 16 is formed in the bottom of the housing 10. A clearance 31 formed
5 between the electric components and a side wall of the housing is defined as a supplemental intake passage. A fresh air introduced in the supplemental intake passage is exposed to the electric components, and warmed by a waste heat resulting from the electric components during an operation of the garbage disposing device 1. The warmed fresh air in
10 the supplemental intake passage is joined with the fresh air flowing in the main intake passage, and then introduced into the vessel 20. Since the electric components are air-cooled by the air flow in the supplemental intake passage, it is possible to prevent an overheat of the control unit 5.

15 The blower 4 is arranged at the upstream of the deodorizer unit 50 in the duct 40 of the exhaust passage to give a forced flow of the air containing unpleasant odor to the deodorizer unit 50. The blower 4 is controlled to have a discharge rate within a range of 20 to 100 liter/min. For example, when the discharge rate is 20 liter/min, the blower 4 is
20 capable of removing the moisture at a rate of about 800 to 900 g/day. Numeral 7 designates a filter for preventing an intrusion of the decomposer 2 into the duct 40. Numeral 17 designates an opening for returning the decomposer caught by the filter to the vessel 20.

A return path 41 is provided to extend from the duct 40 of the
25 exhaust passage at a portion between the blower 4 and the deodorizer unit 50 into the vessel 20 for returning a part of the air being discharged

through the exhaust passage into the vessel as a forced return flow. The air flowing into the vessel **20** through the return path **41** is mixed with the fresh air introduced into the vessel **20** through the air inlet **21** to generate a convection of the mixed air in the vessel. The return path **41** is useful to avoid a situation that the fresh air introduced in the vessel **20** is instantly exhausted from the air outlet **22** without being effectively used for the microbial transformation of the food wastes.

The garbage disposing device **1** has a diluting duct **60** extending from a second-air intake port **18** formed in the bottom of the housing **10**, as shown in FIG. 7, to the air discharge port **13**. A diluting fan **61** is disposed in the diluting duct **60** to introduce a fresh air directly from outside of the housing **10** through the second air-intake port **18** for diluting the air emerging out of the deodorizer unit **50** by the fresh air. The duct **40** of the exhaust passage is joined with the diluting duct **60**, at the downstream of the deodorizer unit **50** and between the diluting fan **61** and the air discharge port **13**. For example, when a hot air of 250 °C emerging out of the deodorizer unit **50** flows into the diluting duct **60** at a discharge rate of 20 liter/min of the blower **4**, and a fresh air of 30 °C is introduced into the diluting duct at a rate of 200 liter/min by the diluting fan **61**, it has been confirmed that the hot air of 250 °C is mixed with the fresh air of 30 °C, and a mixed air of about 50 °C is discharged through the discharge port **13** at a discharge rate of 220 liter/min. Thus, it is preferred that the diluting fan **61** and the blower **4** are controlled by the control unit **5** such that an amount of the air flow produced by the diluting fan is greater than that of the air flow produced by the blower. In FIG. 7, numeral **19** designates a waterproof wall

formed on the bottom surface of the housing **10** to prevent the intrusion of water, e.g., rain water, into the diluting duct **60** through the second air-intake port **18**.

A first temperature sensor **71** is disposed at the inside of the
5 arcuate portion **54** of the U-shaped heater **52**, as shown in FIG. 5A, to measure a temperature of the U-shaped heater. A supply of electric current to the U-shaped heater **52** is controlled by the control unit **5** according to a temperature value measured by the first temperature sensor **71**. A second temperature sensor **72** is disposed adjacent the
10 catalyst **51** in the deodorizer unit **50** to measure a temperature of the catalyst. The catalyst temperature measured by the second temperature sensor **72** is compared with the heater temperature measured by the first temperature sensor **71** at the control unit **5**. When the catalyst
temperature is higher than the heater temperature, as shown in FIG. 5B,
15 it is regarded as a normal condition of the deodorizer unit **50**. On the other hand, when the heater temperature is higher than the catalyst temperature due to an accident such as a clogging of the filter **7**, as shown in FIG. 5C, it is regarded as an abnormal condition of the deodorizer unit **50**. At the abnormal condition, the control unit **5**
20 responds to stop the supply of electric current to the U-shaped heater **52** and the blower **4**. Numeral **57** designates a temperature fuse responding to an abnormal condition of the U-shaped heater **52**. For example, the temperature fuse **57** will operate at a temperature of 390 °C.

A third temperature sensor **73** is arranged at the upstream of the
25 diluting fan **61** in the diluting duct **60** to measure a temperature of the outside air. When a temperature value measured by the third

temperature 73 is lower than a predetermined temperature value, the supplemental heater 6 may be turned on, or a supply of electric current to the supplemental heater is increased. Alternatively, the discharge rate of the blower 4 may be reduced when the temperature of the outside
5 air is low. On the other hand, when the temperature value measured by the third temperature sensor 73 is higher than a predetermined temperature value, it is assumed that the diluting fan 61 stops for some reason, or the air discharge port 13 is closed for some reason. In this case, the control unit 5 stops the supply of electric current to the U-
10 shaped heater 52, the blower 4 and the diluting fan 61 to provide a safe operation of the garbage disposing device 1.

In FIG. 6, numeral 62 designates a baffle provided at juncture of the duct 40 of the exhaust passage and the diluting duct 60 for directing the air emerging out of the deodorizer unit 50 towards the air
15 discharge port 13. Numeral 63 designates an air vent formed in the diluting duct 60 adjacent to the third temperature sensor 73 and between the second air-intake port 18 and the diluting fan 61. For example, when the diluting fan 61 stops for some reason, there is a possibility of causing a back flow of the discharge gas in the diluting duct 60. In this
20 case, a portion of the back flow will be exhausted from the air vent 63 after passing by the third temperature sensor 73. Therefore, a high temperature of the back flow can be detected by the third temperature sensor 73. According to an output of the third temperature sensor 73 informing the unusual state in the diluting duct 60, the supply of electric
25 current to the U-shaped heater 52 is stopped by the control unit 5.

The garbage disposing device 1 has a switch 8 for selectively

operating the device at a low deodorizing mode and a high deodorizing mode. At the low deodorizing mode, the U-shaped heater 52 is heated at a first temperature, e.g., 150 °C. In case of using platinum as the catalyst 51, about 90 % of sulfur and about 30 % of ammonia in the air containing unpleasant odor being discharged from the vessel 20 can be removed by the heated catalyst 51 at the low deodorizing mode. At the high deodorizing mode, the U-shaped heater 52 is heated at a second temperature higher than the first temperature, e.g., 250 °C. About 90 % of sulfur and about 90 % of ammonia in the air containing unpleasant odor can be removed by the heated catalyst 51 at the high deodorizing mode. When the high deodorizing mode is adopted, it is preferred that the high deodorizing mode is automatically turned off after the elapse of a predetermined time period, e.g., 48 hours. If necessary, an ammonia content in the gas being exhausted from the vessel 20 may be detected by an ammonia sensor (not shown), and the low and high deodorizing modes may be automatically switched according to the ammonia content.

The blower 4 can be controlled by the control unit 5 according to the following manner. When the catalyst temperature measured by the second temperature sensor 72 is smaller than a predetermined temperature, the blower 4 is controlled to increase a discharge rate for a constant time period. When the catalyst temperature measured by the second temperature sensor 72 does not reach the predetermined temperature within the time period, the supply of electric current to the U-shaped heater 52 and the blower 4 is stopped by the control unit 5. For example, when the discharge port 13 is accidentally closed by an

obstacle such as a leaves, there is a possibility that a mixture gas of the fresh air introduced by the diluting fan 61 and the gas emerging out of the deodorizer unit 50 flows backward in the duct 40 of the exhaust passage to reduce the catalyst temperature. In such a case, an amount of
5 air flow produced by the blower 4 is increased for the time period to blow off the leaves. However, if the obstacle is not removed by the increased air flow within the time period, the supply of electric current to the U-shaped heater 52 and the blower 4 is stopped for a safe operation of the garbage disposing device 1. Alternatively, the supply
10 of electric current to the U-shaped heater 52 and the blower 4 may be stopped immediately when the catalyst temperature detected by the second temperature sensor 72 is smaller than a predetermined temperature. The control unit 5 operates not to respond to the detected temperature until after an elapse of a predetermined time from the start
15 of the garbage disposing device 1.

In addition, it is preferred that the control unit 5 samples the catalyst temperature detected by the second temperature sensor 72 at an interval of several minutes and determines an abnormal condition to stop operating the U-shaped heater 52, the blower 4, and the diluting fan
20 61, only when all of some successively detected temperatures, e.g., five successively detected temperatures, are smaller than a predetermined temperature. Therefore, even when two or three successively detected temperatures are smaller than the predetermined temperature due to the influence of a gust of wind, the control unit 5 will not regard the
25 situation as the abnormal condition. It is also preferred that when the catalyst temperature detected by the second temperature sensor 72 is

lower than a predetermined temperature, e.g., 100 °C, even after the elapse of a prescribed time duration, e.g., 10 minutes, from the start of the garbage disposing device 1, the control unit 5 stops the supply of electric current to the U-shaped heater 52.

5 In general, there is a difference between temperatures of the outside air detected at daily night and noon. According to this temperature difference, it is possible to self-check whether the third temperature sensor 73 is normally operating. That is, the control unit 5 obtains a digital value converted from an analogue value of the
10 temperature detected at each of daily night and noon by the third temperature sensor 73. The control unit 5 provides a difference between two successively obtained digital values. When the difference is equal to or greater than a predetermined value, the control unit 5 regards that the third temperature sensor 73 normally operates.
15 However, when the difference is less than the predetermined value, the control unit 5 determines that the third temperature sensor 73 is in an unusual state, and stops the supplies of electric current to the U-shaped heater 52, the blower 4, and the diluting fan 61. Thus, the self-diagnosis of determining a failure of the third temperature sensor 73
20 will promise a safe operation of the garbage disposing device 1.

 The U-shaped heater 52 can be controlled by the control unit 5 such that the supply of electric current to the U-shaped heater is stopped when a temperature value except for a predetermined temperature range is detected by at least one of the first and second temperature sensors
25 (71 and 72). In addition, it is preferred that the supply of electric current to the U-shaped heater 52 is stopped by the control unit 5 when

a duty ratio is not within a predetermined range. For example, when an amount of air flow produced by the blower 4 is reduced as a result of an accident such as a clogging of the filter 7, the temperature value detected by the first or second temperature sensor (71 or 72) comes to be higher, so that the duty ratio, i.e., a supply rate of electric current, will be less than a lower limit of the predetermined range. Since such a low duty ratio is regarded as unusual, the supply of electric current to the U-shaped heater 52 is stopped by the control unit 5. On the other hand, when the amount of air flow produced by the blower 4 is increased as a result of an accident such as a back flow of the discharge gas or a failure of the blower, the temperature value detected by the first or second temperature sensor (71 or 72) comes to be lower, so that the duty ratio will be higher than an upper limit of the predetermined range. Since such a high duty ratio is regarded as unusual, the supply of electric current to the U-shaped heater 52 is stopped by the control unit 5.

If necessary, a flow regulator 45 may be mounted at juncture of the duct 40 of the exhaust passage and the return path 41, as shown in FIG. 9. The flow regulator 45 is biased by a spring (not shown). When an amount of air flow produced by the blower 4 is decreased, the flow regulator 45 is moved by the spring such that an amount of air flow introduced into the return path 41 is kept constant. On the contrary, when the amount of air flow produced by the blower 4 is increased, the flow regulator 45 is moved against the spring bias by the air flow so that the amount of air flow introduced into the return path 41 is kept constant.

An extension exhaust tube **80** may be detachably connected to the discharge port **13** through an adapter **81**, as shown in FIG. 10. It is preferred that an additional blower **82** is arranged in the adapter **81** to prevent the occurrence of a back flow of the discharge gas. By the use
5 of the exhaust tube **80**, the garbage disposing device **1** may be placed and used in a house.



What is claimed is:

1. A garbage disposing device which comprises:
 - a housing having an air intake port and an air discharge port;
 - 5 a vessel mounted within said housing to store therein food wastes, said vessel having an air inlet and an air outlet;
 - an intake passage formed in said housing exteriorly of said vessel and extending from said intake port to said air inlet for introducing a fresh air into said vessel;
 - 10 an exhaust passage formed within said housing exteriorly of said vessel to extend from said air outlet to said discharge port of said housing for discharging therethrough an air containing unpleasant odor developed in said vessel due to a decomposition of said food wastes;
 - 15 a deodorizer unit comprising a catalyst which decomposes said unpleasant odor contained in the air being discharged, a heater for activating said catalyst, and a case for incorporating therein said catalyst and said heater;
 - wherein said deodorizer unit is arranged in said exhaust passage such
 - 20 that an outer surface of said case is exposed in said intake passage, and the fresh air in said intake passage is warmed by a contact with the outer surface of said case inevitably heated by said heater to enhance the decomposition of said food wastes.

25

2. The garbage disposing device as set forth in claim 1, wherein said



intake passage is formed in a clearance between said vessel and said housing to extend from first and second air-intake ports formed in a bottom of said housing to said air inlet, and wherein said exhaust passage is located within said clearance to locate said deodorizer unit
5 within said intake passage for heat transfer between said case heated by said heater and the fresh air being introduced through said intake passage, said device including a control unit for controlling said heater, said control unit comprising electronic components carried on a board, said first air-intake port being located below said deodorizer unit to
10 allow a part of the fresh air being introduced to pass by said case of said deodorizer unit, said second air-intake port located below said control unit to allow a part of the fresh air to pass by said electronic components of said control unit.

15

3. The garbage disposing apparatus as set forth in claim 1, wherein said vessel is provided at its upper portion with an auxiliary heater for heating the air inside of said vessel.

20

4. The garbage disposing device as set forth in claim 1, further including a blower arranged in said exhaust passage upstream of said
25 deodorizer unit to give a forced flow of the air from inside of said vessel through said deodorizer unit.



5. The garbage disposing device as set forth in claim 4, wherein a return path is provided to extend from said exhaust passage at a portion between said blower and said deodorizer unit into said vessel for returning a portion of the air being discharged through said exhaust
5 passage into said vessel as a forced return flow.

6. The garbage disposing device as set forth in claim 1, wherein said
10 heater is of a U-shaped configuration having a pair of legs and is fixed in said deodorizer unit with an open top end of the U-shape oriented in an upstream direction of said exhaust passage, a flow splitter means being placed near said open top end of said heater in order to diverge the incoming air flow into sub-flows which pass by said legs of said
15 heater, respectively.

7. The garbage disposing device as set forth in claim 1, further
20 including a switch for selectively operating said device at a high deodorizing mode and a low deodorizing mode.

25 8. The garbage disposing device as set forth in claim 7, wherein said heater is controlled to heat said catalyst to high and low temperatures respectively in said high and low deodorizing modes, a



temperature sensor being provided near said catalyst to control said heater.

5

9. The garbage disposing device as set forth in claim 4, further including a dilution chamber arranged in said exhaust passage downstream of said deodorizer unit, said dilution chamber provided with a diluting fan which introduces a fresh air directly from outside of the housing for diluting the air emerging out of said deodorizer unit by the fresh air.

15 10. The garbage disposing device as set forth in claim 9, wherein said dilution chamber is provided with a temperature sensor upstream of said diluting fan to give a temperature of the fresh air being introduced in said dilution chamber.

20

11. The garbage disposing device as set forth in claim 9, wherein said dilution chamber extends in a lengthwise direction crossing with a direction of the air flow emerging out of said deodorizer unit and is formed at opposite ends of said lengthwise direction respectively with said discharge port and an air hole introducing the fresh air into said dilution chamber, a baffle being provided at conjuncture of said

25



deodorizer unit and said dilution chamber for directing the air emerging out of said deodorizer unit towards said discharge port, said diluting fan being placed between said baffle and said air hole for introducing the fresh air into said dilution chamber and merging it with said air
5 emerging out of said deodorizer unit.

12. The garbage disposing device as set forth in claim 10, wherein said
10 dilution chamber is provided with an additional air hole opposite of said discharge port and adjacent to said temperature sensor fixed between said diluting fan and said air hole.

15

13. The garbage disposing device as set forth in claim 1, further including an extension exhaust tube connected to and extending from said discharge port, said extension exhaust tube incorporating an additional blower for discharging the air out therethrough.

20

14. The garbage disposing device as set forth in claim 1, wherein a temperature sensor is provided adjacent to said catalyst of said
25 deodorizing unit to give a detected temperature of said catalyst, and a control unit being provided for controlling to stop operating said heater when the detected temperature does not reaches a predetermined



temperature within a prescribed time duration from the start of said device.

5

15. The garbage disposing device as set forth in claim 14, wherein said control unit operates to vary a duty ratio of electric current being fed to said heater for controlling the temperature of said catalyst in response to said detected temperature, said control unit stopping to operate said
10 heater when said duty ratio goes beyond a predetermined range.

16. The garbage disposing device as set forth in claim 9, wherein a
15 control unit is provided to give an amount of the air flow produced by said diluting fan greater than that of the air flow produced by said blower.

20

17. The garbage disposing device as set forth in claim 16, wherein a temperature sensor is provided adjacent to said catalyst of said deodorizing unit to give a detected temperature of said catalyst, and a control unit being provided to increase the amount of the air flow
25 produced by said blower for a prescribed time duration when the detected temperature is less than a predetermined temperature, and stop operating said heater when the detected temperature does not reach the



predetermined temperature within said prescribed time duration.

- 5 18. The garbage disposing device as set forth in claim 14, wherein said control unit operates not to respond to the detected temperature until after an elapse of a predetermined time from the start of said device.

10

19. The garbage disposing device as set forth in claim 17, wherein said control unit samples the detected temperature at an interval of several minutes and determining an abnormal condition to stop operating said heater, said blower, and said diluting fan only when all of some
15 successively detected temperatures do not exceed a predetermined temperature.

- 20 20. The garbage disposing device as set forth in claim 10, further including a control unit which obtains a digital value converted from an analogue value of the temperature detected at said temperature sensor at each of daily night and noon as indicative of the temperature of the outside air, said control units giving a difference between two
25 successively obtained digital values and making a self-diagnosis of determining a failure of said temperature sensor to stop operating said heater, said blower, and said diluting fan when said difference is less



than a predetermined value

5 21. The garbage disposing device as set forth in claim 1, wherein said
heater being of a U-shaped configuration having an open top end and a
closed bottom end and fixed in said deodorizer unit with said open top
end oriented upstream of said exhaust passage and with said closed
bottom end directed to said catalyst, a blower being provided in said
10 exhaust passage upstream of said deodorizer unit to give a forced flow
of the air from inside of said vessel through said deodorizer unit, a first
temperature sensor provided adjacent said closed bottom of said heater
upstream of said catalyst to give a heater temperature, a second
temperature sensor being provided adjacent downstream of said catalyst
15 to give a catalyst temperature, a control unit being provided to compare
said catalyst temperature with said heater temperature for recognizing
an abnormal condition when said catalyst temperature is lower than said
heater temperature, said control unit responding to said abnormal
condition for stopping said heater and said blower.

20

22. The garbage disposing device as set forth in claim 1, wherein a
decomposer capable of providing a microbial transformation of said
food wastes is placed in said vessel.

25