

TIME-LOCKED NETWORK AND NODES FOR EXCHANGING SECURE DATA PACKETS

BACKGROUND INFORMATION

5

1. Field:

[0001] The present disclosure relates generally to managing a network and, in particular, to managing the exchange of data between nodes within a network. Still
10 more particularly, the disclosure relates to a configuration for a node in a network that allows secure data to be received and transmitted based on a predetermined schedule.

15 2. Background:

[0002] Networks are frequently used to exchange data between hardware devices such as, for example, computers, servers, user devices, and other types of devices. As used herein, a "network" may be comprised of one or more
20 computer networks that are interconnected. This type of network may also be referred to as an "internetwork". A "computer network", as used herein, is a collection of computers and/or processors that are interconnected by communications channels that allow data to be exchanged.
25 The Internet is an example of a network comprised of multiple interconnected computer networks.

[0003] The data exchanged between hardware devices in a network may take the form of, for example, data streams. Each data stream may be comprised of data
30 packets. Data packets may also be referred to as network packets in some cases. Exchanging data may include receiving data packets and/or sending data packets.

[0004] Data may be transmitted from a source device in a network to a destination device in the network using

one or more nodes in the network. As used herein, a "node" includes any hardware equipment that may be used to receive data packets, process these data packets, and then send these data packets to one or more other nodes in the network and/or to a destination device. The data packets received at the node may be received from a source device and/or from one or more nodes in the network.

[0005] The hardware equipment that forms a node may include, for example, without limitation, any number of routing devices, switching devices, buffers, control lines, gateways, and/or other types of equipment. The different nodes in a network form a node network within the network.

[0006] In some situations, an undesired inconsistency may occur during the exchange of data within a network. The undesired inconsistency may be, for example, without limitation, a buffer overflow, a denial of service event, a server crash, a loss of data packets, or some other type of undesired event that occurs during the exchange of data. Various solutions for reducing the possibility of an undesired inconsistency during the exchanging of data within a network are currently available. However, some of these currently available solutions may not be as effective as desired.

[0007] For example, some currently available solutions may be able to prevent only certain types of undesired inconsistencies and not others. For example, some currently available methods for preventing buffer overflow use software addressing or memory techniques. However, these techniques may be unable to protect against heap overflows as well as stack-based overflows.

[0008] As another example, some currently available methods for preventing denial of service events may try

to stop the flow of data packets received from
unauthorized source devices by denying data packets
received from certain ports, data packets received from
certain internet protocol (IP) addresses, and/or data
5 packets received based on certain communications
protocols. However, these methods may be unable to
protect against unauthorized source devices that use for
example, without limitation, protocol spoofing, internet
protocol address spoofing, and/or other types of
10 techniques. Therefore, it would be desirable to have a
method and apparatus that takes into account at least
some of the issues discussed above, as well as other
possible issues.

15 SUMMARY

[0009] In one illustrative embodiment, a method for
transmitting secure data packets through a node network
is provided. Unsecure data packets are received at a set
20 of unsecure inputs and secure data packets are received
at a number of secure inputs in a node in the node
network. The secure data packets are authorized to be
sent to a number of secure destination devices. The
unsecure data packets are not authorized to be sent to
25 the number of secure destination devices. The secure
data packets and the unsecure data packets are integrated
to form a number of output data streams based on a
predetermined schedule. The number of output data
streams is sent to a number of next nodes in the node
30 network.

[0010] In another illustrative embodiment, a method
for transmitting secure data packets to a number of
secure destination devices is provided. A number of
input data streams are received at a node in a node

network. The secure data packets are separated from
unsecure data packets received in the number of input
data streams based on a predetermined schedule. The
secure data packets are authorized to be sent to the
5 number of secure destination devices. The unsecure data
packets are not authorized to be sent to the number of
secure destination devices. The secure data packets are
sent to the number of secure destination devices as a
number of secure output data streams from a number of
10 secure outputs in the node.

[0011] In yet another illustrative embodiment, a node
in a node network comprises a number of secure inputs, a
set of unsecure inputs, a timing controller, and a number
of outputs. The number of secure inputs is configured to
15 receive secure data packets. The secure data packets are
authorized to be sent to a number of secure destination
devices. The set of unsecure inputs is configured to
receive unsecure data packets. The unsecure data packets
are not authorized to be sent to the number of secure
20 destination devices. The timing controller is configured
to control integration of the secure data packets and the
unsecure data packets into a number of output data
streams based on a predetermined schedule. The number of
outputs is configured to send the number of output data
25 streams to a number of next nodes in the node network.

[0012] In still yet another illustrative embodiment, a
node in a node network comprises an number of inputs, a
timing controller, and number of secure outputs. The
number of inputs is configured to receive a number of
30 input data streams from a number of previous nodes in the
node network. The timing controller is configured to
separate secure data packets from unsecure data packets
received in the number of input data streams based on a
predetermined schedule. The secure data packets are

authorized to be sent to a number of secure destination devices. The unsecure data packets are not authorized to be sent to the number of secure destination devices. The number of secure outputs is configured to send the secure data packets to the number of secure destination devices as a number of secure output data streams.

[0013] The features and functions can be achieved independently in various embodiments of the present disclosure or may be combined in yet other embodiments in which further details can be seen with reference to the following description and drawings.

BRIEF DESCRIPTION OF THE DRAWINGS

[0014] The novel features believed characteristic of the illustrative embodiments are set forth in the appended claims. The illustrative embodiments, however, as well as a preferred mode of use, further objectives and features thereof, will best be understood by reference to the following detailed description of an illustrative embodiment of the present disclosure when read in conjunction with the accompanying drawings, wherein:

[0015] **Figure 1** is an illustration of a network in the form of a block diagram in accordance with an illustrative embodiment;

[0016] **Figure 2** is an illustration of an ingress node in the form of a block diagram in accordance with an illustrative embodiment;

[0017] **Figure 3** is an illustration of an egress node in the form of a block diagram in accordance with an illustrative embodiment;

[0018] **Figure 4** is an illustration of a node network in accordance with an illustrative embodiment;

[0019] **Figure 5** is an illustration of data packets being exchanged across a node network in accordance with an illustrative embodiment;

5 [0020] **Figure 6** is an illustration of data packets being exchanged across a node network in accordance with an illustrative embodiment;

10 [0021] **Figure 7** is an illustration of a node functioning as an ingress node is in accordance with an illustrative embodiment;

15 [0022] **Figure 8** is an illustration of a node functioning as an egress node is in accordance with an illustrative embodiment;

20 [0023] **Figure 9** is an illustration of output data streams being sent to destination devices in accordance with an illustrative embodiment;

25 [0024] **Figure 10** is an illustration of a process for transmitting secure data packets through a node network in the form of a flowchart in accordance with an illustrative embodiment;

30 [0025] **Figure 11** is an illustration of a process for transmitting secure data packets to a number of secure destination devices in the form of a flowchart in accordance with an illustrative embodiment; and

35 [0026] **Figure 12** is an illustration of a data processing system in the form of a block diagram in accordance with an illustrative embodiment.

DETAILED DESCRIPTION

[0027] The different illustrative embodiments recognize and take into account a number of different
5 considerations. For example, the illustrative
embodiments recognize and take into account that some
currently available solutions for reducing the
possibility of undesired inconsistencies occurring during
the transmission of data over a network may not be as
10 effective as desired. In particular, solutions that
include, for example, bounds checking, canary values,
tagging, and/or other techniques may be unable to protect
against as wide a range of undesired inconsistencies as
desired.

15 [0028] For example, some currently available solutions
may be unable to prevent a potential hacker from
introducing an undesired inconsistency into a data stream
of secure data packets. As used herein, "secure data
packets" may include data packets that are both
20 authorized for transmission through the network and/or
authorized to reach a secure destination device for the
data packets. These data packets, for example, may be
encrypted, may be password-protected, and/or may meet
selected authentication criteria. Further, "unsecure
25 data packets" may include data packets that may or may
not be authorized for transmission through the network
but that are not authorized to reach the secure
destination device.

[0029] The illustrative embodiments recognize and take
30 into account that it may be desirable to transmit secure
data packets from a source device across a node network
to a destination device using a predetermined node
pathway and a predetermined schedule. The predetermined
node pathway may identify the ingress node at which the

secure data packets may enter the node network from the source device and the egress node at which the secure data packets may exit the node network to the destination device. Further, the predetermined node pathway may
5 identify any nodes through which the secure data packets may pass between the ingress node and the egress node.

[0030] The predetermined schedule may identify the specific times at which each node along the predetermined node pathway may transmit the secure data packets. In
10 particular, each secure data packet may be required to be transmitted from a node at a specified time. This type of node network across which secure data packets may be transmitted may be referred to as a time-locked node network.

15 **[0031]** The illustrative embodiments recognize and take into account that a time-locked node network may be capable of providing a desired level of protection against unauthorized users and unauthorized devices attempting to cause undesired inconsistencies to occur
20 during the transmission of secure data packets. With a time-locked node network, an unauthorized user or unauthorized device may need to know the specific times at which secure data packets are to be transmitted from a particular node as well as the particular nodes that are
25 part of the predetermined node pathway to be able to cause undesired inconsistencies to occur during the transmission of the secure data packets.

[0032] The illustrative embodiments recognize and take into account that a time-locked node network may provide
30 a wider range of protection and a greater level of protection against undesired inconsistencies as compared to some currently available solutions. Further, the illustrative embodiments recognize and take into account that the ingress node and the egress node in a

predetermined node pathway for the transmission of secure data packets may need to have configurations capable of controlling the processing and transmission of the secure data packets based on the predetermined schedule.

5 **[0033]** Thus, the illustrative embodiments provide a configuration for an ingress node and a configuration for an egress node. In one illustrative embodiment, a method for transmitting secure data packets through a node network is provided. Unsecure data packets are received
10 from a set of unsecure source devices and secure data packets from a number of secure source devices at a node in the node network. The secure data packets are authorized to be sent to a number of secure destination devices. The unsecure data packets are not authorized to
15 be sent to the number of secure destination devices. The secure data packets and the unsecure data packets are integrated to form a number of output data streams based on a predetermined schedule. The number of output data streams is sent to a number of next nodes in the node
20 network.

[0034] In another illustrative embodiment, a method for transmitting secure data packets to a number of secure destination devices is provided. A number of input data streams is received. The secure data packets
25 are separated from unsecure data packets received in the number of input data streams based on a predetermined schedule. The secure data packets are authorized to be sent to the number of secure destination devices. The unsecure data packets are not authorized to be sent to
30 the number of secure destination devices. The secure data packets are sent to the number of secure destination devices as a number of secure output data streams.

[0035] With reference now to **Figure 1**, an illustration of a network in the form of a block diagram is depicted

in accordance with an illustrative embodiment. In **Figure 1**, network **100** may be comprised of devices **101** that are interconnected. A device, such as one of devices **101**, may be a hardware device that comprises hardware and, in some cases, software. In these illustrative examples, the operations, functions, and/or processes described as being performed by a device may be performed by the hardware and/or software within the device.

[0036] In one illustrative example, devices **101** may include computers and, in some cases, other hardware components. As used herein, a "computer" may be any type of programmable device configured to send and/or receive data over a communications channel. For example, a computer in devices **101** may take the form of a microcomputer, a desktop computer, a laptop computer, a tablet computer, a smartphone, a personal digital assistant (PDA), a workstation, a server computer, a Web server, a client computer, a mainframe computer, a supercomputer, a processor, a microprocessor, or some other type of data processing system.

[0037] Devices **101** may be configured to exchange data with each other using node network **102** within network **100**. Node network **102** is formed by plurality of nodes **104** that are interconnected. As one illustrative example, one of devices **101** may send data to another one of devices **101** using at least a portion of plurality of nodes **104**. The device sending the data may be referred to as the source device, while the device receiving the data may be referred to as the destination device. In some cases, a node in plurality of nodes **104** may be one of devices **101**.

[0038] In these illustrative examples, data may be sent from a source device to a destination device across node network **102** in the form of data streams comprised of

data packets. In one illustrative example, without limitation, number of source devices **105** may send input data streams into node network **102**. Further, number of destination devices **106** may be configured to receive
5 output data streams from node network **102**.

[0039] As used herein, a “number of” items means one or more items. For example, number of source devices **105** may be one or more source devices. Further, number of destination devices **106** may be one or more destination
10 devices.

[0040] As depicted, number of source devices **105** may include set of unsecure source devices **108** and number of secure source devices **109**. Further, number of destination devices **106** may include set of unsecure
15 destination devices **110** and number of secure destination devices **111**. As used herein, a “set of” items may be zero or more items. In this manner, a set of items may be an empty or null set in some cases. For example, set of unsecure source devices **108** may be zero, one, two,
20 four, or some other set of unsecure source devices **108**.

[0041] An “unsecure source device”, such as one of set of unsecure source devices **108**, may be a device that is authorized to send data through node network **102** but that is not authorized to send data to one or more secure
25 destination devices. The type of data sent from an unsecure source device may be “unsecure data packets”. A “secure source device”, such as one of number of secure source devices **109**, may be a device that is both authorized to send data through node network **102** and
30 authorized to send data to one or more secure destination devices. The type of data sent from a secure source device may be “secure data packets”.

[0042] Further, an “unsecure destination device”, such as one of set of unsecure destination devices **110**, may be

a device that is not authorized to receive secure data packets through node network **102**. A "secure destination device", such as one of number of secure destination devices **111**, may be a device that is authorized to

5 receive secure data packets through node network **102**. For example, without limitation, secure destination device may be a secure server, a secure end-node, a secure end-device, or a secure Web server.

[0043] In these illustrative examples, data packets

10 may enter node network **102** through ingress node **112**. These data packets may then be transmitted from ingress node **112** through set of nodes **114** to egress node **116**. Data packets may leave node network **102** through egress node **116**.

15 **[0044]** As one illustrative example, a source device in number of source devices **105** may send data packets into node network **102** through ingress node **112**. These data packets may then be transmitted from ingress node **112** to egress node **116** through set of nodes **114**. The data

20 packets may then be sent to a destination device in number of destination devices **106** from egress node **116**.

[0045] Node **120** is an example of one of plurality of nodes **104** in node network **102**. Node **120** may be implemented such that node **120** may be capable of

25 functioning as ingress node **112**, one of set of nodes **114**, and/or egress node **116**.

[0046] As depicted, node **120** may include number of inputs **122**, number of outputs **124**, first networking device **126**, second networking device **128**, and timing

30 controller **130**. Number of inputs **122** may comprise any number of switches, buffers, and/or other types of hardware equipment and/or software configured to receive data. Number of outputs **124** may comprise any number of

switches, buffers, and/or other types of hardware equipment and/or software configured to send data.

[0047] Further, first networking device **126** and second networking device **128** may comprise hardware equipment and/or software configured to process the data received by number of inputs **122** and send this data to number of outputs **124**. First networking device **126** and second networking device **128** may have switching and/or routing capabilities. Timing controller **130** may be configured to control the receiving, processing, and sending of data to or from node **120** based on a specified timing.

[0048] Potential configurations for a node functioning as ingress node **112** are described in **Figure 2** below. Potential configurations for a node functioning as egress node **116** are described in **Figure 3** below.

[0049] With reference now to **Figure 2**, an illustration of an ingress node in the form of a block diagram is depicted in accordance with an illustrative embodiment. As depicted, ingress node **112** includes number of inputs **202**, number of outputs **204**, first networking device **206**, second networking device **208**, and timing controller **210**.

[0050] In this illustrative example, number of inputs **202** may be configured to receive number of input data streams **212** from number of source devices **105** in **Figure 1**. Number of inputs **202** may include set of unsecure inputs **203** and number of secure inputs **205**. These inputs may be, for example, ports. An unsecure input is an input that has not been designated to receive secure data packets. A secure input is an input that has been designated to receive secure data packets. In some cases, a secure input may be designated to only receive secure data packets. However, in other examples, a secure input may be designated to receive a combination of both secure data packets and unsecure data packets.

[0051] As depicted, set of unsecure inputs **203** is configured to receive set of unsecure input data streams **214** and number of secure inputs **205** is configured to receive number of secure input data streams **216**. Each of
5 set of unsecure input data streams **214** may be comprised of unsecure data packets, while each of number of secure input data streams **216** may be comprised of secure data packets. Ingress node **112** may be configured to receive number of input data streams **212**, process the data
10 packets in number of input data streams **212**, and send out these data packets in the form of number of output data streams **220**.

[0052] As depicted, number of inputs **202** may include set of switches **222** and set of buffers **224** in any order.
15 Set of unsecure inputs **203** may process set of unsecure input data streams **214** using at least a portion of set of switches **222** and set of buffers **224** in any order and send the unsecure data packets in set of unsecure input data streams **214** to first networking device **206**. Further,
20 number of secure inputs **205** may process number of secure input data streams **216** using at least a portion of set of switches **222** and set of buffers **224** in any order and send the secure data packets in number of secure input data streams **216** to second networking device **208**.

[0053] In some cases, the portion of set of switches **222** used to send the secure data packets to second networking device **208** may be controlled by timing controller **210**. Timing controller **210** may determine when each of these secure data packets is to be sent to number
25 of outputs **204**.
30

[0054] In this illustrative example, first networking device **206** may comprise set of switches **230**, set of routers **232**, set of buffers **234**, and/or other types of hardware and/or software equipment. Further, second

networking device **208** may comprise set of switches **236**, set of routers **238**, set of buffers **240**, and/or other types of hardware and/or software equipment. Timing controller **210** may control first networking device **206** and/or second networking device **208** depending on the implementation. Timing controller **210** may determine the times at which unsecure data packets and secure data packets are to be sent to number of outputs **204**.

[0055] As depicted, number of outputs **204** may include set of switches **242** and set of buffers **244** in any order. Number of outputs **204** may be configured to integrate the unsecure data packets received from first networking device **206** and the secure data packets received from second networking device **208** to form number of output data streams **220**. In particular, timing controller **210** may determine the times at which each of the secure data packets is inserted into an output data stream in number of output data streams **220**. Number of outputs **204** may send number of output data streams to a number of next nodes within node network **102** in **Figure 1**.

[0056] With reference now to **Figure 3**, an illustration of an egress node in the form of a block diagram is depicted in accordance with an illustrative embodiment. As depicted, egress node **116** includes number of inputs **302**, number of outputs **304**, first networking device **306**, second networking device **308**, and timing controller **310**.

[0057] In this illustrative example, number of inputs **302** may be configured to receive number of input data streams **312** from a number of previous nodes in node network **102** in **Figure 1**. Egress node **116** may be configured to receive number of input data streams **312**, process the data packets in number of input data streams **312**, and send out these data packets to number of

destination devices **106** in **Figure 1** in the form of number of output data streams **316**.

[0058] Number of output data streams **316** may include set of unsecure output data streams **318** and number of
5 secure output data streams **320**. Each of set of unsecure output data streams **318** may be comprised of unsecure data packets, while each of number of secure output data streams **320** may be comprised of secure data packets.

[0059] As depicted, number of inputs **302** may include
10 set of switches **322** and set of buffers **324** in any order. Number of inputs **302** may process number of input data streams **312** using set of switches **322** and set of buffers **324**. Number of inputs **302** may send the unsecure data packets in number of input data streams **312** to first
15 networking device **306**. Further, number of inputs **302** may send the secure data packets in number of input data streams **312** to second networking device **308**.

[0060] In some cases, set of switches **322** may be controlled by timing controller **310**. Timing controller
20 **310** may use the times at which each data packet is received at number of inputs **302** to determine whether the data packet is a secure data packet or an unsecure data packet. For example, a data packet may be identified as a secure data packet based on the specific time the data
25 packet was received based on a predetermined schedule.

[0061] In this illustrative example, first networking device **306** may comprise set of switches **326**, set of routers **328**, set of buffers **330**, and/or other types of hardware equipment and/or software. Further, second
30 networking device **308** may comprise set of switches **332**, set of routers **334**, set of buffers **336**, and/or other types of hardware equipment and/or software. Timing controller **310** may control first networking device **306** and/or second networking device **308** depending on the

implementation. Timing controller **310** may determine the times at which unsecure data packets and secure data packets are to be sent to number of outputs **304**.

[0062] Number of outputs **304** may include set of unsecure outputs **311** and number of secure outputs **313**. These outputs may be, for example, ports. An unsecure output is an output that has not been designated to send out secure data packets. A secure output is an output that has been designated to send out secure data packets.

10 In some cases, a secure output may be designated to only send out secure data packets. However, in other examples, a secure output may be designated to send out a combination of both secure data packets and unsecure data packets.

15 **[0063]** As depicted, number of outputs **304** may include set of switches **338** and set of buffers **340** in any order. Set of unsecure outputs **311** may be configured to send the unsecure data packets to set of unsecure destination devices **110** in **Figure 1** in the form of set of unsecure output data streams **318**. Further, number of secure outputs **313** may be configured to send the secure data packets to number of secure destination devices **111** in **Figure 1** in the form of number of secure output data streams **320**.

25 **[0064]** In this manner, egress node **116** may separate secure data packets from unsecure data packets and may ensure that only secure data packets are sent to number of secure destination devices **111** in **Figure 1**. Egress node **116** may ensure that unsecure data packets do not reach number of secure destination devices **111** in **Figure 1**.

[0065] The illustrations of network **100** in **Figure 1**, ingress node **112** in **Figure 2**, and egress node **116** in **Figure 3** are not meant to imply physical or architectural

limitations to the manner in which an illustrative embodiment may be implemented. Other components in addition to or in place of the ones illustrated may be used. Some components may be optional. Also, the blocks
5 are presented to illustrate some functional components. One or more of these blocks may be combined, divided, or combined and divided into different blocks when implemented in an illustrative embodiment.

[0066] With reference now to **Figure 4**, an illustration
10 of a node network is depicted in accordance with an illustrative embodiment. In **Figure 4**, node network **400** may be an example of one implementation for node network **102** in **Figure 1**. As depicted, node network **400** includes nodes **402**, **404**, **406**, **408**, **410**, **412**, **414**, **416**, **418**, **420**,
15 and **424**. These nodes may be configured to communicate using communications links **426**. Communications links **426** may include, for example, any number of wireless communications links, wired communications links, optical communications links, and/or other types of
20 communications links.

[0067] In this illustrative example, node pathway **428** may be a pathway through node network **400** that has been preselected for use in sending data through node network **400**. Node pathway **428** includes node **402**, node **408**, node
25 **410**, node **416**, and node **418** in this example. Node **402** may be the ingress node in node pathway **428**, while node **418** may be the egress node in node pathway **428**.

[0068] Data may be sent along node pathway **428** based on a predetermined schedule. For example, without
30 limitation, the different nodes in node network **400** may all be configured to receive timing signals from clock **430**. Clock **430** may be, for example, without limitation, a satellite clock, a global positioning system satellite clock, or some other type of clock either common,

coupled, or separate and/or either in-band or out-of-band.

[0069] Each node along node pathway **428** may be configured to use the timing signals received from clock **430** to determine the specific times at which secure data packets are to be received and sent from each node. Further, each node along node pathway **428** may be configured to take into account the propagation delay between nodes. For example, without limitation, propagation delays **432**, **434**, **436**, and **438** may be taken into account when determining the times at which each node along node pathway **428** is scheduled to receive secure data packets and send out secure data packets.

[0070] With reference now to **Figure 5**, an illustration of data packets being exchanged across a node network is depicted in accordance with an illustrative embodiment. In this illustrative example, data packets **502** are being exchanged across node network **400** from **Figure 4**. Secure data packets may be authorized to be transmitted across node network **400** along node pathway **428**.

[0071] As the ingress node, node **402** may receive unsecure input data stream **504**, unsecure input data stream **506**, and secure input data stream **508**. These input data streams may be configured to be sent through node network **400** along node pathway **428**. Unsecure input data stream **504** and unsecure input data stream **506** may be received from unsecure source devices. However, secure input data stream **508** may be received from a secure source device. The secure data packets in secure input data stream **508** may be configured to be sent through node network **400** along node pathway **428** at scheduled time slots **510**.

[0072] As the egress node, node **418** may send out unsecure output data stream **512**, unsecure output data

stream **514**, and secure output data stream **516**. Unsecure output data stream **512** and unsecure output data stream **514** may be sent to unsecure destination devices.

However, secure output data stream **516** may be sent to a
5 secure destination device. Secure output data stream **516** comprises the secure data packets received in secure input data stream **508** at node **402**. Node **418** is configured to ensure that only secure data packets and not unsecure data packets reach secure destination
10 devices.

[**0073**] With reference now to **Figure 6**, an illustration of data packets being exchanged across a node network is depicted in accordance with an illustrative embodiment. In this illustrative example, data packets **502** being
15 exchanged across node network **400** from **Figures 4-5** may include unsecure authorized data packets **600**, unsecure unauthorized data packets **602**, and secure data packets **604**.

[**0074**] Unsecure authorized data packets **600** may
20 include data packets that may have been authorized for transmission through node network **400** but that have not been authorized to be sent to any secure destination devices. Unsecure unauthorized data packets **602** may include data packets that may not have been authorized
25 for transmission through node network **400** and that have not been authorized to be sent to any secure destination devices. Unsecure unauthorized data packets **602** may pose information security issues and/or undesired inconsistency issues. Secure data packets **604** may
30 include data packets that may have been authorized for transmission through node network **400** and that have been authorized to be sent to one or more secure destination devices.

[0075] The predetermined schedule established for the transmission of data packets along node pathway **428** may ensure that only secure data packets are sent to secure destination devices. For example, secure output data stream **516** sent out by node **418** may not include any unsecure authorized data packets or any unsecure unauthorized data packets.

[0076] With reference now to **Figure 7**, an illustration of a node functioning as an ingress node is depicted in accordance with an illustrative embodiment. As depicted, node **402** from **Figures 4-6** may function as ingress node **700**. Ingress node **700** may be an example of one implementation for ingress node **112** in **Figure 2**.

[0077] Ingress node **700** may include number of inputs **702**, number of outputs **704**, first networking device **706**, second networking device **708**, and timing controller **710**. Number of inputs **702** includes switch array **712**, buffer array **714**, and switch array **716**. Number of outputs **704** includes switch array **718**, buffer array **720**, and switch array **722**.

[0078] In this illustrative example, an unsecure input in number of inputs **702** receives unsecure input data stream **724**. In particular, this unsecure input processes unsecure input data stream **724** using switch **726** in switch array **712**, buffer **728** in buffer array **714**, and switch **730** in switch array **716**. Further, another unsecure input in number of inputs **702** receives unsecure input data stream **732**. This other unsecure input processes unsecure input data stream **732** using switch **734** in switch array **712**, buffer **736** in buffer array **714**, and switch **738** in switch array **716**.

[0079] These two unsecure inputs send the unsecure data packets in unsecure input data stream **724** and in unsecure input data stream **732** to first networking device

706. In this illustrative example, timing controller **710** does not control the times at which these unsecure inputs send unsecure data packets to first networking device **706**.

5 **[0080]** Further, a secure input in number of inputs **702** receives secure input data stream **740**. This secure input processes secure input data stream **740** using switch **742** in switch array **712**, buffer **744** in buffer array **714**, and switch **746** in switch array **716**. In this illustrative
10 example, switch **742**, buffer **744**, and switch **746** may be controlled by timing controller **710**.

[0081] Timing controller **710** may determine the times at which secure data packets in secure input data stream **740** are sent from the secure input to second networking
15 device **708**. Further, timing controller **710** determines when second networking device **708** is to send a secure data packet to each of switch **748**, switch **750**, and switch **752** in switch array **718** in number of outputs **704**. These switches also may be controlled by timing controller **710**.

20 **[0082]** An output in number of outputs **704** uses switch **748**, buffer **754** in buffer array **720**, and switch **756** in switch array **722** to form output data stream **758**. In particular, a portion of the unsecure data packets processed by first networking device **706** may be sent into
25 buffer **754**. Timing controller **710** may control switch **748**, switch **756**, first networking device **706**, and second networking device **708** to determine when unsecure data packets and when secure data packets are put into output data stream **758**.

30 **[0083]** Similarly, another output in number of outputs **704** uses switch **750**, buffer **760** in buffer array **720**, and switch **762** in switch array **722** to form output data stream **764**. In particular, a portion of the unsecure data packets processed by first networking device **706** may be

sent into buffer **760**. Timing controller **710** may control switch **750**, switch **762**, first networking device **706**, and second networking device **708** to determine when unsecure data packets and when secure data packets are put into
5 output data stream **764**.

[0084] Yet another output in number of outputs **704** uses switch **752**, buffer **766** in buffer array **720**, and switch **768** in switch array **722** to form output data stream **770**. In particular, a portion of the unsecure data
10 packets processed by first networking device **706** may be sent into buffer **766**. Timing controller **710** may control switch **752**, switch **768**, first networking device **706**, and second networking device **708** to determine when unsecure data packets and when secure data packets are put into
15 output data stream **770**.

[0085] With reference now to **Figure 8**, an illustration of a node functioning as an egress node is depicted in accordance with an illustrative embodiment. As depicted, node **418** from **Figures 4-6** may function as egress node
20 **800**. Egress node **800** may be an example of one implementation for egress node **116** in **Figure 3**. Egress node **800** may include number of inputs **802**, number of outputs **804**, first networking device **806**, second networking device **808**, and timing controller **810**.

[0086] In this illustrative example, number of inputs **802** includes switch array **812**, buffer array **814**, and switch array **816**. Number of outputs **804** includes switch array **818**, buffer array **820**, and switch array **822**.

[0087] As depicted, an input in number of inputs **802**
30 is configured to receive input data stream **824**. This input processes input data stream **824** using switch **826** in switch array **812**, buffer **828** in buffer array **814**, and switch **830** in switch array **816**. Timing controller **810** may control switch **826** and switch **830**. In particular,

timing controller **810** may be used to determine which data packets in input data stream **824** are secure data packets and which data packets are unsecure data packets based on the times at which these data packets are received at the
5 input.

[0088] The input sends the unsecure data packets to first networking device **806**. First networking device **806** sends the unsecure data packets to an unsecure output in number of outputs **804**. In this illustrative example, the
10 unsecure output processes the unsecure data packets using switch **832** in switch array **818**, buffer **834** in buffer array **820**, and switch **836** in switch array **822**. The unsecure output forms unsecure output data stream **838** using these unsecure data packets. In this illustrative
15 example, unsecure output data stream **838** does not include any secure data packets. Unsecure output data stream **838** may be sent out to an unsecure destination device.

[0089] Further, the input sends the secure data packets to second networking device **808**. Second
20 networking device **808** sends the secure data packets to a secure output in number of outputs **804**. The secure output processes these secure data packets using switch **840** in switch array **818**, buffer **842** in buffer array **820**, and switch **844** in switch array **822**. The secure output
25 forms secure output data stream **846** using the secure data packets. In this illustrative example, secure output data stream **846** does not include any unsecure data packets. The secure output may send secure output data stream **846** to a secure destination device.

30 [0090] With reference now to **Figure 9**, an illustration of output data streams being sent to destination devices is depicted in accordance with an illustrative embodiment. In this illustrative example, unsecure output data stream **838** from **Figure 8** may be sent to

unsecure destination device **900**, while secure output data stream **846** may be sent to secure destination device **902**.

[0091] As depicted, unsecure destination device **900** takes the form of unsecure web server **904**, while secure destination device **902** takes the form of secure web server **906**. Unsecure web server **904** includes input buffer **908**, processor **910**, and data structure **912**.

[0092] Input buffer **908** is configured to receive the unsecure data packets in unsecure output data stream **838**

and store these unsecure data packets in data structure **912**. Unsecure output data stream **838** may include

unsecure authorized data packets and/or unsecure unauthorized data packets. These unsecure data packets in unsecure output stream **838** may have undesired

inconsistencies which may cause for example, without limitation, buffer overflow, denial of service events, server crashes, and/or other undesired events. Because these unsecure data packets in unsecure output stream **838** are sent to unsecure destination device **900**, the

undesired inconsistencies and/or other undesired events will occur in unsecure destination device **900**.

Consequently, the data stored in data structure **912** may be considered compromised data **914**.

[0093] Secure web server **906** may include input buffer **916**, processor **918**, and data structure **920**. Input buffer **916** is configured to receive the secure data packets in secure output data stream **846** and store these secure data packets in data structure **920**. Because secure output data stream **846** does not include any unsecure data

packets, the data stored in data structure **920** may be considered non-compromised data **922**. Because secure output data stream **846** only includes secure data packets, undesired inconsistencies such as, for example, without limitation, buffer overflow, denial of service events,

server crashes, and/or other undesired events may not occur in secure destination device **902**.

[0094] The illustrations of node network **400** in **Figures 4-6**, ingress node **700** in **Figure 7**, egress node **800** in **Figure 8**, and unsecure destination device **900** and secure destination device **902** in **Figure 9** are not meant to imply physical or architectural limitations to the manner in which an illustrative embodiment may be implemented. Other components in addition to or in place of the ones illustrated may be used. Some components may be optional.

[0095] The different components shown in **Figures 4-9** may be illustrative examples of how components shown in block form in **Figures 1-3** may be implemented as physical structures. Additionally, the components shown in **Figures 4-9** may be combined with components in **Figure 1**, used with components in **Figure 1**, or a combination of the two.

[0096] With reference now to **Figure 10**, an illustration of a process for transmitting secure data packets through a node network in the form of a flowchart is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 10** may be implemented by, for example, without limitation, ingress node **112** in **Figure 2**.

[0097] The process may begin by receiving unsecure data packets at a set of unsecure inputs and secure data packets at a number of secure inputs in a node in the node network (operation **1000**). The secure data packets may be authorized to be sent to a number of secure destination devices. However, the unsecure data packets may not be authorized to be sent to the number of secure destination devices.

[0098] Thereafter, the secure data packets and the unsecure data packets may be integrated to form a number of output data streams based on a predetermined schedule (operation **1002**). The number of output data streams may
5 then be sent to a number of next nodes in the node network (**1004**), with the process terminating thereafter.

[0099] With reference now to **Figure 11**, an illustration of a process for transmitting secure data packets to a number of secure destination devices in the
10 form of a flowchart is depicted in accordance with an illustrative embodiment. The process illustrated in **Figure 11** may be implemented by, for example, without limitation, egress node **116** in **Figure 3**.

[00100] The process may begin by receiving a number of
15 input data streams at a node in a node network (operation **1100**). Thereafter, secure data packets may be separated from unsecure data packets received in the number of input data streams based on a predetermined schedule (operation **1102**). The secure data packets may be
20 authorized to be sent to a number of secure destination devices. However, the unsecure data packets may not be authorized to be sent to the number of secure destination devices.

[00101] The secure data packets may then be sent to the
25 number of secure destination devices as a number of secure output data streams from a number of secure outputs (**1104**), with the process terminating thereafter. Further, in operation **1104**, the set of unsecure data packets may be sent to a set of unsecure destination
30 devices as a set of unsecure output data streams.

[00102] The flowcharts and block diagrams in the different depicted embodiments illustrate the architecture, functionality, and operation of some possible implementations of apparatus and methods in an

illustrative embodiment. In this regard, each block in the flowcharts or block diagrams may represent a module, a segment, a function, and/or a portion of an operation or step. For example, one or more of the blocks may be implemented as program code, in hardware, or a combination of the program code and hardware. When implemented in hardware, the hardware may, for example, take the form of integrated circuits that are manufactured or configured to perform one or more operations in the flowcharts or block diagrams.

[00103] In some alternative implementations of an illustrative embodiment, the function or functions noted in the blocks may occur out of the order noted in the figures. For example, in some cases, two blocks shown in succession may be executed substantially concurrently, or the blocks may sometimes be performed in the reverse order, depending upon the functionality involved. Also, other blocks may be added in addition to the illustrated blocks in a flowchart or block diagram.

[00104] Turning now to **Figure 12**, an illustration of a data processing system in the form of a block diagram is depicted in accordance with an illustrative embodiment. In this illustrative example, data processing system **1200** may be used to implement any one of number of source devices **105**, plurality of nodes **104**, and/or number of destination devices **106** in devices **101** in **Figure 1**. Further, data processing system **1200** may be used to implement any component within a node in plurality of nodes **104**.

[00105] In this illustrative example, data processing system **1200** includes communications framework **1202**, which provides communications between processor unit **1204**, memory **1206**, persistent storage **1208**, communications unit **1210**, input/output unit **1212**, and display **1214**.

Communications framework **1202** may be implemented as a bus system in some examples.

[00106] Processor unit **1204** serves to execute instructions for software that is loaded into memory **1206** to perform a number of operations. Processor unit **1204** may be a number of processors, a multi-processor core, or some other type of processor, depending on the particular implementation. In some cases, processor unit **1204** may take the form of a hardware unit, such as a circuit system, an application specific integrated circuit (ASIC), a programmable logic device, or some other suitable type of hardware.

[00107] Memory **1206** and persistent storage **1208** are examples of storage devices **1216**. Storage devices **1216** may be in communication with processor unit **1204** through communications framework **1202**. A storage device, also referred to as a computer readable storage device, is any piece of hardware capable of storing information such as, for example, without limitation, data, program code in functional form, and/or other suitable information either on a temporary basis and/or a permanent basis. Memory **1206** may be, for example, a random access memory or any other suitable volatile or non-volatile storage device.

[00108] Persistent storage **1208** may take various forms and comprise any number of components or devices, depending on the particular implementation. For example, persistent storage **1208** may be a hard drive, a flash memory, a rewritable optical disk, a rewritable magnetic tape, or some combination of the above. Depending on the implementation, the media used by persistent storage **1208** may or may not be removable.

[00109] Communications unit **1210**, in these examples, provides for communications with other data processing systems or devices. Communications unit **1210** may provide

communications through the use of either or both physical and wireless communications links.

[00110] Input/output unit **1212** allows for input and output of data with other devices that may be connected to data processing system **1200**. For example, input/output unit **1212** may provide a connection for user input through a keyboard, a mouse, and/or some other suitable input device and/or may send output to a printer. Display **1214** provides a mechanism to display information to a user.

[00111] Instructions for the operating system, applications, and/or programs may be located in storage devices **1216**. The processes of the different embodiments may be performed by processor unit **1204** using computer-implemented instructions. These instructions are referred to as program code, computer usable program code, or computer readable program code and may be read and executed by one or more processors in processor unit **1204**.

[00112] In these examples, program code **1218** is located in a functional form on computer readable media **1220** that is selectively removable and may be loaded onto or transferred to data processing system **1200** for execution by processor unit **1204**. Program code **1218** and computer readable media **1220** form computer program product **1222** in these examples. Computer readable media **1220** may take the form of computer readable storage media **1224** or computer readable signal media **1226**.

[00113] Computer readable storage media **1224** is a physical or tangible storage device used to store program code **1218** rather than a medium that propagates or transmits program code **1218**. Computer readable storage media **1224** may take the form of, for example, without limitation, an optical or magnetic disk or a persistent

storage device that is connected to data processing system **1200**.

[00114] Alternatively, program code **1218** may be transferred to data processing system **1200** using computer
5 readable signal media **1226**. Computer readable signal media **1226** may be, for example, without limitation, a propagated data signal containing program code **1218**. This data signal may be an electromagnetic signal, an optical signal, and/or some other suitable type of signal
10 that may be transmitted over communications links that are physical, optical, and/or wireless.

[00115] The different components illustrated for data processing system **1200** are not meant to provide architectural limitations to the manner in which
15 different embodiments may be implemented. The different illustrative embodiments may be implemented in a data processing system including components in addition to or in place of those illustrated for data processing system **1200**. Other components shown in **Figure 12** can be varied
20 from the illustrative examples shown. The different embodiments may be implemented using any hardware device or system capable of running program code. As one example, the data processing system may include organic components integrated with inorganic components and/or
25 may be comprised entirely of organic components excluding a human being. For example, a storage device may be comprised of an organic semiconductor.

[00116] Thus, the illustrative embodiments provide configurations for nodes in a node network that allow
30 secure data packets to be sent to secure destination devices. Using the node network described by the illustrative embodiments, the possibility of undesired inconsistencies occurring during the transmission of data

through the node network may be reduced to within selected tolerances.

[00117] The description of the different illustrative embodiments has been presented for purposes of
5 illustration and description, and is not intended to be exhaustive or limited to the embodiments in the form disclosed. Many modifications and variations will be apparent to those of ordinary skill in the art. Further, different illustrative embodiments may provide different
10 features as compared to other illustrative embodiments. The embodiment or embodiments selected are chosen and described in order to best explain the principles of the embodiments, the practical application, and to enable others of ordinary skill in the art to understand the
15 disclosure for various embodiments with various modifications as are suited to the particular use contemplated.

CLAIMS:

What is claimed is:

- 5 1. A method for transmitting secure data packets through a node network, the method comprising:
receiving unsecure data packets at a set of unsecure inputs and secure data packets at a number of secure inputs in a node in the node network,
10 wherein the secure data packets are authorized to be sent to a number of secure destination devices; and
wherein the unsecure data packets are not authorized to be sent to the number of secure
15 destination devices;
integrating the secure data packets and the unsecure data packets to form a number of output data streams based on a predetermined schedule; and
sending the number of output data streams to a
20 number of next nodes in the node network.
2. The method of claim 1, wherein the step of integrating the secure data packets and the unsecure data packets to form the number of output data streams based
25 on the predetermined schedule comprises:
forming the number of output data streams using the unsecure data packets; and
inserting each of the secure data packets into a corresponding output data stream in the number of output
30 data streams based on the predetermined schedule.
3. The method of claim 2, wherein the step of inserting the each of the secure data packets into the corresponding output data stream in the number of output

data streams based on the predetermined schedule
comprises:

5 inserting the each of the secure data packets into
the corresponding output data stream in the number of
output data streams based on a corresponding time at
which the each of the secure data packets is to be sent
to a next node in the number of next nodes.

4. A method for transmitting secure data packets to a
10 number of secure destination devices, the method
comprising:

receiving a number of input data streams at a node
in a node network;

15 separating the secure data packets from unsecure
data packets received in the number of input data streams
based on a predetermined schedule,

wherein the secure data packets are authorized
to be sent to the number of secure destination
devices; and

20 wherein the unsecure data packets are not
authorized to be sent to the number of secure
destination devices; and

sending the secure data packets to the number of
secure destination devices as a number of secure output
25 data streams from a number of secure outputs in the node.

5. The method of claim 4, wherein the step of
separating the secure data packets from the unsecure data
packets received in the number of input data streams
30 based on the predetermined schedule comprises:

identifying data packets in the number of input data
streams received at specified times indicated in the
predetermined schedule as the secure data packets.

6. The method of claim 4, wherein the step of sending the secure data packets to the number of secure destination devices as the number of secure output data streams comprises:

5 sending the secure data packets to the number of secure destination devices as the number of secure output data streams from the number of secure outputs in the node, wherein the number of secure destination devices includes at least one of a secure server, a secure end-
10 node, a secure end-device, and a secure Web server.

7. The method of claim 4 further comprising:

15 sending the unsecure data packets to a set of unsecure destination devices as a set of unsecure output data streams from a set of unsecure outputs in the node, wherein the unsecure data packets include at least one of unsecure authorized data packets and unsecure unauthorized data packets.

20 8. A node in a node network, the node comprising:
a number of secure inputs configured to receive secure data packets, wherein the secure data packets are authorized to be sent to a number of secure destination devices;

25 a set of unsecure inputs configured to receive unsecure data packets, wherein the unsecure data packets are not authorized to be sent to the number of secure destination devices;

a timing controller configured to control
30 integration of the secure data packets and the unsecure data packets into a number of output data streams based on a predetermined schedule; and

a number of outputs configured to send the number of output data streams to a number of next nodes in the node network.

5 9. The node of claim 8 further comprising:

a first networking device configured to receive the unsecure data packets from the set of unsecure inputs and send the unsecure data packets to the number of outputs; and

10 a second networking device configured to receive the secure data packets from the number of secure inputs and send the secure data packets to the number of outputs.

10. The node of claim 9, wherein the timing controller
15 is configured to control at least one of the number of secure inputs, the set of unsecure inputs, the number of outputs, the first networking device, and the second networking device using the predetermined schedule.

20 11. The node of claim 9, wherein the first networking device comprises:

a set of buffers.

12. The node of claim 9, wherein the second networking
25 device comprises:

a set of buffers.

13. The node of claim 8, wherein the set of unsecure
inputs is not designated to receive any secure data
30 packets.

14. The node of claim 8, wherein the set of unsecure inputs is configured to receive the unsecure data packets from a set of unsecure source devices and wherein the

number of secure inputs is configured to receive the secure data packets from a number of secure source devices.

5 15. The node of claim 8, wherein the unsecure data packets include at least one of unsecure authorized data packets and unsecure unauthorized data packets.

16. A node in a node network, the node comprising:
10 a number of inputs configured to receive a number of input data streams from a number of previous nodes in the node network;

a timing controller configured to separate secure data packets from unsecure data packets received in the
15 number of input data streams based on a predetermined schedule,

wherein the secure data packets are authorized to be sent to a number of secure destination devices; and

20 wherein the unsecure data packets are not authorized to be sent to the number of secure destination devices; and

a number of secure outputs configured to send the secure data packets to the number of secure destination
25 devices as a number of secure output data streams.

17. The node of claim 16 further comprising:

a set of unsecure outputs configured to send the unsecure data packets to a set of unsecure destination
30 devices as a set of unsecure output data streams.

18. The node of claim 17 further comprising:

a first networking device configured to receive the unsecure data packets from the number of inputs and send

the unsecure data packets to the set of unsecure outputs;
and

5 a second networking device configured to receive the
secure data packets from the number of inputs and send
the secure data packets to the number of secure outputs.

19. The node of claim 18, wherein the timing controller
is configured to control at least one of the number of
inputs, the number of secure outputs, the set of unsecure
10 outputs, the first networking device, and the second
networking device using the predetermined schedule.

20. The node of claim 16, wherein the unsecure data
packets include at least one of unsecure authorized data
15 packets and unsecure unauthorized data packets.