

ADJUSTABLE FLOW NOZZLE SYSTEM

FIELD

[0001] The present disclosure relates to an adjustable flow nozzle system and in particular to an adjustable flow nozzle system that adjusts the cross-sectional area of the overall opening formed by each adjustable flow nozzle by selective rotation of at least two openings in overlapping arrangement with respect to each other for establishing between a non-zero minimum flow rate to a maximum flow rate by each individual flow nozzle.

BACKGROUND

[0002] Semiconductor processing involves selective removal of polymers or metals from the surface of silicon wafers. This is accomplished through spraying various chemicals – acids or solvents – on a batch of wafers. One of the many factors that influence the removal rate is the flow rate and volume of liquid through the spray nozzles. Currently, the adjustment of flow through each spray nozzle is done at the “macro” level by adjusting the flow to all of the spray nozzles in the manifold at once. Individual spray nozzles can be changed as described, but this individual adjustment of each spray nozzle is both time consuming and may not precisely adjust the flow of liquid through each respective spray nozzle.

BRIEF DESCRIPTION OF THE DRAWINGS

[0003] FIG. 1 is a perspective view of an adjustable flow nozzle system showing an adjustable flow manifold, according to one aspect of the present disclosure;

[0004] FIG. 2 is a perspective view of the adjustable flow manifold showing the adjustable flow nozzle in an exploded view, according to one aspect of the present disclosure;

[0005] FIG. 3 is a side view of the adjustable flow manifold, according to one aspect of the present disclosure;

[0006] FIG. 4 is a top view of the adjustable flow manifold showing a plurality of plugs that seal respective access openings, according to one aspect of the present disclosure;

[0007] FIG. 5 is a cross-sectional view of the adjustable flow manifold along line 5-5 of FIG. 3 showing one of the plurality of adjustable flow nozzles, according to one aspect of the present disclosure;

[0008] FIG. 6 is a perspective view of a manifold body for the adjustable flow manifold, according to one aspect of the present disclosure;

[0009] FIG. 7 is an end view of the manifold body of FIG. 6;

[0010] FIG. 8 is a cross-sectional view of the manifold body taken along line 8-8 of FIG. 7, according to one aspect of the present disclosure;

[0011] FIG. 9 is a bottom view of the manifold body, according to one aspect of the present disclosure;

[0012] FIG. 10 is a top view of the manifold body, according to one aspect of the present disclosure;

[0013] FIG. 11 is an enlarged cross-sectional view taken along line 11-11 of FIG. 8, according to one aspect of the present disclosure;

[0014] FIG. 12 is a perspective view of a nozzle retainer, according to one aspect of the present disclosure;

[0015] FIG. 13 is an opposite perspective view of the nozzle retainer shown in FIG. 12, according to one aspect of the present disclosure;

[0016] FIG. 14 is a side view of the nozzle retainer showing the channel in phantom line, according to one aspect of the present disclosure;

[0017] FIG. 15 a partial cross-sectional view of the nozzle retainer, according to one aspect of the present disclosure;

[0018] FIG. 16 a top plan view of the nozzle retainer, according to one aspect of the present disclosure;

[0019] FIG. 17 is a perspective view of a retainer orifice insert for the adjustable flow nozzle, according to one aspect of the present disclosure;

[0020] FIG. 18 is a front view of the retainer orifice insert, according to one aspect of the present disclosure;

[0021] FIG. 19 is a side view of the retainer orifice insert, according to one aspect of the present disclosure;

[0022] FIG. 20 a perspective view of a manifold orifice insert for the adjustable flow nozzle, according to one aspect of the present disclosure;

[0023] FIG. 21 is a front view of the manifold orifice insert, according to one aspect of the present disclosure;

[0024] FIG. **22** is a side view of the manifold orifice insert, according to one aspect of the present disclosure;

[0025] FIG. **23** is an enlarged cross-sectional view of the manifold orifice insert taken along line **23-23** of FIG. **22**, according to one aspect of the present disclosure;

[0026] FIG. **24** is a perspective view of a plug used to seal the access opening of the manifold body, according to one aspect of the present disclosure;

[0027] FIG. **25** is a side view of the plug of FIG. **24**, according to one aspect of the present disclosure;

[0028] FIG. **26** is another side view of the plug of FIG. **24**, according to one aspect of the present disclosure;

[0029] FIG. **27** is a top plan view of the plug of FIG. **24**, according to one aspect of the present disclosure;

[0030] FIG. **28** is perspective view of an adjustment key for adjusting the flow rate of the adjustable flow nozzle, according to one aspect of the present disclosure;

[0031] FIG. **29** is a side view of the adjustment key of FIG. **28**, according to one aspect of the present disclosure;

[0032] FIG. **30** is an end view of the adjustment key showing a first and second key elements, according to one aspect of the present disclosure;

[0033] FIG. **31** is a side view of the adjustment key showing a first recess in phantom line configured to receive the first key element, according to one aspect of the present disclosure;

[0034] FIG. **32** is a side view of the adjustment key showing first and second recesses in phantom line configured to receive the first and second key elements, respectively, according to one aspect of the present disclosure;

[0035] FIG. **33** is an end view of the adjustment key showing a notch, according to one aspect of the present disclosure;

[0036] FIG. **34** is an opposite end view of the adjustment key shown in FIG. **33**, according to one aspect of the present disclosure;

[0037] FIG. **35** is a perspective view of the first key element, according to one aspect of the present disclosure;

[0038] FIG. 36 is a top view of the first key element of FIG. 35, according to one aspect of the present disclosure;

[0039] FIG. 37 is a cross-sectional view of the first key element of FIG. 35, according to one aspect of the present disclosure;

[0040] FIGS. 38A-38K show the sequence of rotation of the manifold orifice insert relative to the retainer orifice insert for the adjustable flow nozzle, according to one aspect of the present disclosure;

[0041] FIG. 39 is a cross-sectional view of the adjustable flow manifold showing the access opening to the adjustable flow nozzle sealed by the plug, according to one aspect of the present disclosure;

[0042] FIG. 40 is a cross-sectional view of the adjustable flow manifold showing the adjustment key engaged to the adjustable flow nozzle, according to one aspect of the present disclosure;

[0043] FIG. 41 is a perspective view of the adjustable flow manifold showing the flow of liquid through the manifold body, according to one aspect of the present disclosure;

[0044] FIG. 42 is a table showing the percentage opening of the adjustable flow nozzle and concurrent reduction in the opening area for each angle of rotation of the manifold orifice insert relative to the retainer orifice insert, according to one aspect of the present disclosure;

[0045] FIG. 43 is a chart illustrating the values for angle, reduction of opening area, and opening percentage shown in the table of FIG. 39, according to one aspect of the present disclosure;

[0046] FIG. 44 is an enlarged view of FIG. 10 showing the setting indicia used to adjust the manifold orifice insert, according to one aspect of the present disclosure;

[0047] FIG. 45 is a perspective view of the manifold body shown in FIG. 8, according to one aspect of the present disclosure;

[0048] FIG. 46 is an opposite perspective view of the nozzle component, according to one aspect of the present disclosure;

[0049] FIG. 47 is an end view of the nozzle component, according to one aspect of the present disclosure;

[0050] FIG. 48 is an opposite end view of the nozzle component, according to one aspect of the present disclosure;

[0051] FIG. **49** is a side view of the nozzle component, according to one aspect\ of the present disclosure;

[0052] FIG. **50** is an opposite side view of the nozzle component, according to one aspect of the present disclosure; and

[0053] FIG. **51** is a cross-sectional view of the nozzle component taken along line **51-51** of FIG. **50**, according to one aspect of the present disclosure.

[0054] Corresponding reference characters indicate corresponding elements among the view of the drawings. The headings used in the figures do not limit the scope of the claims.

DETAILED DESCRIPTION

[0055] Various embodiments for an adjustable flow nozzle system having a manifold with a plurality of adjustable flow nozzles in which the flow rate of each adjustable flow nozzle may be individually adjusted are described herein. In some embodiments, the adjustable flow nozzle system may be used for semiconductor processing through the spraying of various solvents or acids through a plurality of individually adjustable flow nozzles on a batch of silicon wafers at various flow rates. In some embodiments, each adjustable flow rate nozzle includes a manifold orifice insert that defines at least one opening in overlapping relation with a retainer orifice insert that defines at least one opening in which the overlapping openings are aligned along a common axis of rotation for defining a collective opening that controls the flow rate of fluid through the adjustable fluid nozzle. In some embodiments, adjusting the cross-sectional area of the collective opening as the manifold orifice insert is rotated relative to the retainer orifice insert adjusts the flow rate through the adjustable flow nozzle. In some embodiments, the flow rate of each adjustable flow nozzle is adjusted through the selective overlap of the openings such that each adjustable flow nozzle is adjustable between a non-zero minimum flow rate when minimum overlap between the overlapped openings occurs and a maximum flow rate when maximum overlap between the overlapped openings occurs. In some embodiments, the flow rate of each adjustable flow nozzles may be individually adjusted using an adjustment key that engages and rotates the manifold orifice insert relative to the fixed retainer orifice insert. Referring to the drawings, various embodiments of an adjustable flow nozzle system are illustrated and generally indicated as **100** in FIGS. **1-43**.

[0056] Referring to FIGS. **1-4**, the adjustable flow nozzle system **100** includes an adjustable flow manifold **102** having a plurality of adjustable flow nozzles **104** positioned in series along an elongated manifold body **106**. In some embodiments, each of the adjustable flow nozzles **104** may be manually adjusted to a particular flow rate. In some embodiments, each adjustable flow nozzle **104** may be accessed through the interior of the manifold body **106** using an adjustment key **166** to manually adjust the flow rate of each adjustable flow nozzle **104** without requiring each adjustable flow nozzle **104** to be disassembled or require disengagement of the adjustable flow nozzle **104** from the manifold body **106** to adjust the flow rate.

[0057] As shown in FIGS. **6-11**, the manifold body **106** is collectively defined by a top side **122**, a bottom side **124**, a front side **126** and rear side **128** having a distal end portion **130** and an opposite proximal end portion **132** that collectively define the elongated rectangular-shaped manifold body **106**. Referring to FIGS. **6** and **8-10**, the manifold body **106** defines a plurality of access openings **134** arranged in series along the top side **122** of the manifold body **106** and configured to be sealed by a respective plug **108** (FIG. **4**).

[0058] Referring to FIGS. **24-27**, each plug **108** is configured to seal a respective access opening **134** during operation of the nozzle flow system **100**. In some embodiments, the plug **108** includes a cap portion **160** and a base portion **161** that extends axially from the cap portion **160**. As shown in FIG. **39**, the base portion **161** is configured to engage and seal off the access cavity **139**, while the cap portion **160** seals off the access opening **134** for establishing a water-tight seal between the plug **108** and the manifold body **106**.

[0059] As shown in FIGS. **6** and **8**, the manifold body **106** further defines a plurality of apertures **135** arranged in series along the bottom side **124** of the manifold body **106** and configured to be engaged to a respective adjustable flow nozzle **104**. As shown in FIG. **11**, each access opening **134** communicates with a respective access cavity **139** and each aperture **135** communicates with a respective nozzle cavity **138**. The nozzle cavity **138** is configured to receive the adjustable flow nozzle **104**. In some embodiments, each respective access opening **134** is located directly opposite a respective aperture **135** such that the adjustable flow nozzle **104** may be accessed through the access opening **134** to manually adjust the flow rate of the adjustable flow nozzle **104** as shall be described in greater detail below. As shown in FIGS. **10** and **44**, in some embodiments a setting indicia **117** may be engraved or placed around each respective access hole **134** to provide a visual indicator of flow rate for a user when manually adjusting the flow rate desired for each respective adjustable flow nozzle **104**. As shown in FIG. **10**, a respective setting indicia **117A-117I** may be associated with each adjustable flow nozzle **104**. In some embodiments, the setting indicia **117** may be preset numbers, lines, visual indicators or a combination thereof that provide the user with a visual indication of flow rate being applied to each respective adjustable flow nozzle **104**.

[0060] As further shown in FIG. **11**, the proximal end portion **132** of the manifold body **106** defines a proximal opening **141** and the distal end portion **130** of

the manifold body **106** defines a distal opening **140**. The manifold body **106** further defines an axial channel **136** in communication with the distal opening **140** at one end and proximal opening **141** at the opposite end of the axial channel **136**. As noted above, each access opening **134** is configured to be engaged to a plug **108** to seal access to the axial channel **136** as well as the rear portion of the adjustable flow nozzle **104**. In addition, each aperture **135** is configured to be engaged to a respective adjustable flow nozzle **104** positioned opposite a respective plug **108**.

[0061] FIG. **41** illustrates the fluid pathway through the adjustable flow manifold **102**. As shown, inlet flow **A** enters the axial channel **136** through the distal opening **140** of the manifold body **106** and inlet flow **B** enters the opposite end of the axial channel **136** through the proximal opening **141** of the manifold body **106**. In one aspect, each adjustable flow nozzle **104** may be manually adjusted to allow a respective outlet flow **C1** through outlet flow **C9** having the same or different flow rates.

[0062] As shown in FIG. **5**, in some embodiments each adjustable flow nozzle **104** includes an adjustable nozzle component **110** that is manually and individually adjusted to modify the cross-sectional area of a collective opening **158** such that the flow rate for that particular adjustable flow nozzle **104** may be changed to a desired flow rate. As such, each adjustable flow nozzle **104** can be individually adjusted to provide a flow rate that is either the same or different than the other adjustable flow nozzles **104** of the adjustable flow manifold **102**.

[0063] Referring to FIGS. **2** and **5**, each adjustable flow nozzle **104** includes a retainer orifice insert **114** stacked in overlapping fashion with a manifold orifice insert **116** that is manually rotated relative to the retainer orifice insert **114** to individually adjust the flow rate of the adjustable flow nozzle **104**. In assembly, the retainer orifice insert **114** is fixed in position and engaged with the manifold orifice insert **116**. In operation, the manifold orifice insert **116** may be manually rotated relative to the stationary retainer orifice insert **114** using the adjustment key **166** to adjust flow rate as shall be described in greater detail below. In some embodiments, each adjustable flow nozzle **104** further includes a nozzle component **110** which is engaged to the retainer orifice insert **114** and functions as a nozzle arrangement for the release of fluid at a predetermined flow rate in a spraying action. In some embodiments, the nozzle component **110** defines a circumferential groove configured to receive an O-ring **118** for establishing a fluid tight seal between the

adjustable flow nozzle **104** and the manifold body **106**. In addition, the adjustable flow nozzle **104** may include an O-ring **121** that forms part of the assembly for the adjustable flow nozzle **104**. As further shown, the plug **108** may include an O-ring **120** that establishes a fluid-tight seal between the plug **108** and the access opening **134**.

[0064] As shown in FIGS. **5** and **45-51**, in some embodiments the nozzle component **110** includes a nozzle body **180** defining a distal end portion **190** forming a nozzle head **181** and a proximal end portion **191** forming a proximal opening **184**. The nozzle head **181** defines a nozzle opening **182** configured to provide a spraying action. As shown in FIG. **51**, a conduit **183** is defined through the nozzle body **180** and is in fluid flow communication between the nozzle opening **182** and the proximal opening **184** for establishing fluid flow communication through the nozzle component **110**. As shown, the nozzle body **180** forms a middle flange **185** and a proximal flange **186** that collectively define groove **187** configured to receive O-ring **118** (FIG. **5**). As further shown, in some embodiments a bayonet mount **189** may be formed adjacent the proximal opening **184** configured to engage the nozzle component **110** to the nozzle retainer **112**.

[0065] In some embodiments, the adjustable flow nozzle **104** further includes a nozzle retainer **112** engaged to the nozzle component **110** such that the nozzle component **110** extends through the nozzle retainer **112** and is retained to the manifold body **105**. As shown in FIGS. **12-14**, in some embodiments the nozzle retainer **112** defines a cap portion **142** and a tubular portion **143** that extends axially from the cap portion **142**. The nozzle retainer **112** forms an axial channel **144** in communication with a first axial opening **145** defined through the tubular portion **143** and a second axial opening **149** defined through the cap portion **142**. The axial channel **144** is configured to receive the nozzle component **110** such that the nozzle component **110** extends through first and second axial openings **145** and **149** as shown in FIG. **5**. In addition, the nozzle retainer **112** forms a peripheral edge **146** defining first and second flat portions **147** and **148** defined opposite of each other as illustrated in FIG. **16**. The first and second flat portions **147** and **148** act as gripping surfaces configured to be engaged by the thumb and forefinger for permitting an individual to grip the nozzle retainer **112** when engaging the retainer nozzle **112** to the nozzle component **110** and manifold body **106** during assembly of the adjustable flow nozzle **104**.

[0066] As shown in FIGS. 17-19, the retainer orifice insert **114** defines a generally disc-shaped body **151** with a central opening **150** formed through the retainer orifice insert **114**. In some embodiments, the retainer orifice insert **114** defines a pair of opposing first and second curved slots **162** and **163** formed through the disc body **151** that form a part of the collective opening **158** (FIGS. 38A-38K) with the manifold orifice retainer **116** that establishes fluid flow rate through each adjustable flow nozzle **104** as shall be discussed in greater detail below. In addition, the retainer orifice insert **114** defines a substantially circular-shaped peripheral edge that forms a key portion **152** that extends outwardly from the peripheral edge of the retainer orifice body **114**. The key portion **152** is configured to align and fix the retainer orifice insert **114** in position between the nozzle component **110** and the manifold orifice insert **116** during assembly of the adjustable flow nozzle **104**.

[0067] As shown in FIGS. 20-23, the manifold orifice insert **116** defines a generally disc-shaped body **157** with a central opening **154** formed through the manifold orifice insert **116**. In some embodiments, the manifold orifice insert **116** defines a pair of opposing first and second curved slots **164** and **165** formed through the manifold orifice insert **116** that are identical in configuration to first and second slots **162** and **163** of the retainer orifice insert **114** that collectively form a part of the collective opening **158** (FIGS. 38A-38K) when aligned with the first and second curved slots **164** and **165** of the manifold orifice insert **116** to establish a rate of fluid flow through each adjustable flow nozzle **104** as shall be discussed in greater detail below. In addition, the manifold orifice insert **116** defines a substantially similar circular-shaped peripheral edge having a configuration that is substantially similar or identical to the retainer orifice insert **114**. In some embodiments, the central opening **154** of the manifold orifice insert **116** has an identical configuration as the central opening **150** of the retainer orifice insert **114** and is co-axial alignment with the central opening **150** for establishing a non-zero minimum flow rate through the adjustable flow nozzle **104** when flow rate through the first curved slots **162/164** and second curved slots **163/165** is prevented (FIG. 38K) Referring to FIGS. 22 and 23, first and second key receptacles **155** and **156** are formed through the rear surface **185** of the manifold orifice insert **116** which are configured to engage the adjustment key **166** when adjusting the flow rate of the adjustable flow nozzle **104** as shall be described in greater detail below.

[0068] As noted above, the rotation of the manifold orifice insert **116** relative to the stationary retainer orifice insert **114** causes the cross-sectional area of the collective opening **158** defined by the overlapping arrangement between the rotated first and second curved slots **164/165** of the manifold orifice insert **116** relative to the stationary first and second slots **162/163** of the retainer orifice insert **114** to change which adjusts the flow rate through the adjustable flow nozzle **104**. In one aspect, the adjustable flow nozzle **104** is adjusted through the selective overlap between the aligned first curved slots **162/164** and aligned second curved slots **163/165** as the manifold orifice insert **116** is rotated about a common axis **204** (FIGS. **38A-38K**) relative to the retainer orifice insert **114** which remains in a fixed position. As noted above, in some embodiments, the first and second curved slots **162** and **163** of the retainer orifice insert **114** and the first and second curved slots **164** and **165** of the manifold orifice insert **116** each define identical curved slots, although in other embodiments the first and second curved slots **162** and **163** and the first and second curved slots **164** and **165** may each define identical or differently shaped openings, such as semi-circular shaped opening, a rectangular-shaped opening, an irregular-shaped opening, an angular-shaped opening, and/or square-shaped opening other than a circular-shaped opening since rotation of a pair of circular-shaped openings along the same axis would not produce a change in cross-sectional area of the opening collectively defined by the overlapping arrangement. This overlapping arrangement between the first and second curved slots **162** and **163** with respective first and second curved slots **164** and **165** also allows the flow rate of the adjustable flow nozzle **104** to be manually adjusted in range between a non-zero minimum flow rate and a maximum flow rate. In particular, a non-zero minimum flow rate is achieved through the adjustable flow nozzle **104** since there will always be some degree of minimum fluid flow by virtue of the fluid flow communication through the central openings **150** and **154** despite the fact that the first and second curved slots **162** and **163** and the first and second curved slots **164** and **165** may be oriented such that the collective opening **158** is closed off to fluid flow communication as shown in FIG. **38K**. In other embodiments in which there are no aligned central openings **150/154**, the first and second curved slots **162** and **163** of the retainer orifice insert **114** and the first and second curved slots **164** and **165** of the manifold orifice insert **116** may be in an overlapping arrangement to establish a

non-zero minimum flow rate through the adjustable flow nozzle **104** as shown in FIG. **38J**.

[0069] Referring to FIGS. **28-37** and **40**, as described above the flow rate of the adjustable flow nozzle **104** may be adjusted by rotating the manifold orifice insert **116** using the adjustment key **166** in the direction indicated by the setting indicia **117** (FIG. **44**) until the adjustable flow nozzle **104** is adjusted to the desired flow rate indicated by the setting indicia **117**. In some embodiments, the adjustment key **166** includes an elongated key body **167** defining a distal portion **172** and a proximal portion **173** that is of sufficient length to allow the distal portion **172** to access the adjustable flow nozzle **104** through the channel **136**. In some embodiments, first and second key elements **168** and **169** extend from the distal portion **172** of the elongated key body **167** which are configured to be received within the respective first and second key receptacles **155** and **156** of the manifold orifice insert **116**. As shown in FIGS. **30-32**, first and second pockets **176** and **177** are formed within the elongated key body **167** adjacent the distal portion **172** of the adjustment key **166** and are configured to receive a respective first key element **168** and second key element **169** in a tight engagement sufficient to prevent inadvertent disengagement of the first and second key elements **168** and **169**. In other embodiments, the adjustment key **166** may include first and second key elements **168** and **169** which are formed integral with the distal portion **172** of the elongated key body **167**. In some embodiments, the adjustment key **166** may define a channel **171** formed through the proximal portion **173** of the elongated key body **167**. In some embodiments, a notch **170** may be defined along the proximal portion **173** of the elongated key body **167**.

[0070] As shown in FIGS. **35-37**, the first key element **168**, which has an identical configuration as the second key element **169**, may define an end portion **174** and a body portion **175**. The end portion **175** forms a pointed shape configured to engage either the first or second key receptacles **155** and **156** of the manifold orifice insert **116** as shown in FIG. **40** and a body portion **175** configured to be disposed within either the first pocket **176** or the second pocket **177** of the elongated key body **167** such that the end portion **174** extends outwardly from the distal portion **172** of the adjustment key **166**. In some embodiments, the end portion **175** may have a configuration similar to a conventional screw driver or a Phillips screw driver.

[0071] FIGS. **38A-38K** illustrate a sequence of rotation of the manifold orifice insert **116** relative to the stationary retainer orifice insert **114** as the manifold orifice insert **116** is rotated by the adjustment key **166** to individually change the flow rate of each of the respective adjustable flow nozzles **104** along the adjustable flow manifold **102**. Referring to FIG. **38A**, the manifold orifice insert **116** and the retainer orifice insert **114** are aligned in an overlapping arrangement such that the longitudinal axis **200** of the first and second curved slots **162** and **163** of the retainer orifice insert **114** are aligned along the same orientation as the longitudinal axis **202** of the first and second curved slots **164** and **165** of the manifold orifice insert **116**. In this orientation, the respective collective openings **158** formed by the overlapping relationship between aligned first curved slots **162/164** and the aligned second curved slots **163/165** each define the maximum cross-sectional area that can be defined by each respective collective opening **158**. Referring to FIGS. **38B-38K**, rotation of the manifold orifice insert **116** about central axis **204** in a clockwise direction (or counter-clockwise direction in an alternative embodiment) will gradually reduce the cross-sectional area of each respective collective opening **158** as the first and second curved slots **164** and **165** of the manifold orifice insert **116** are rotated relative to the stationary first and second curved slots **162** and **163** of the retainer orifice insert **114**. Conversely, rotation of the manifold orifice insert **116** in a counter-clockwise direction (or clockwise direction in the alternative embodiment) will gradually increase the cross-sectional area of the collective opening **158**. As shown in FIG. **38K**, the manifold orifice insert **116** may be rotated such that the longitudinal axis **202** of the manifold orifice insert **116** is at a perpendicular relation relative to the longitudinal axis **200** of the retainer orifice insert **114**. In this overlapping arrangement, the collective openings **158** are closed off to fluid flow communication such that the non-minimum flow rate is achieved by fluid flow through the aligned central opening **150/154**.

[0072] As shown in FIG. **42**, the table illustrates the reduction in cross-sectional area (sq. mm) of the collective opening **158** and the percentage that the collective opening **158** is reduced as the angle between the first and second longitudinal axes **200** and **202** increases. FIG. **43** is a graph that illustrates the relationship between the angles formed between the first and second longitudinal axes **200** and **202**, the gradual reduction of the cross-sectional area of the collective opening **158** for each angle formed between the first and second longitudinal axes

200 and **202**, and the percentage the collective opening **158** is reduced with each angle formed between the first and second longitudinal axes **200** and **202**.

[0073] It should be understood from the foregoing that, while particular embodiments have been illustrated and described, various modifications can be made thereto without departing from the spirit and scope of the invention as will be apparent to those skilled in the art. Such changes and modifications are within the scope and teachings of this invention as defined in the claims appended hereto.

CLAIMS

1. An adjustable flow nozzle system comprising:
 - an adjustable flow manifold comprising a manifold body defining an axial channel that extends between a distal end portion defining a distal opening and a proximal end portion defining a proximal opening, a plurality of access openings formed along one side of the manifold body and a plurality of apertures formed on the opposite side of the manifold body, wherein the plurality of access openings and apertures communicate with the axial channel, and
 - a plurality adjustable flow nozzles coupled to a respective one of the plurality of apertures, each of the plurality of adjustable flow nozzles comprising:
 - a nozzle component configured for providing a fluid pathway for a fluid exiting the nozzle component;
 - a retainer orifice insert engaged to the nozzle component, the retainer orifice insert defining at least one opening; and
 - a manifold orifice insert engaged to the retainer orifice insert, the manifold orifice insert defining at least one opening in a co-axial relation with the at least one opening of the retainer orifice insert in an overlapping arrangement such that a collective opening between the at least one opening of the manifold orifice insert and the at least one opening of the retainer orifice insert, wherein the manifold orifice insert is operable to rotate relative to the retainer orifice insert such that a cross-sectional area of the collective opening is adjusted, wherein adjusting the cross-sectional area of the collective opening gradually adjusts a flow rate through each of the plurality of adjustable flow

nozzles, and wherein each of the plurality of adjustable flow nozzles is operable for individual adjustment independent of other adjustable flow nozzles of the plurality of adjustable flow nozzles.

2. The adjustable flow nozzle system of claim 1, wherein the manifold orifice insert defines first and second key receptacles for providing respective engagement points to rotate the manifold orifice insert relative to the retainer orifice insert.
3. The adjustable flow nozzle system of claim 1, wherein the retainer orifice insert is fixed in position relative to the manifold orifice insert.
4. The adjustable flow nozzle system of claim 1, wherein the flow rate exiting each of the plurality of adjustable flow nozzles is in a range between a minimum flow rate and a maximum flow rate.
5. The adjustable flow nozzle system of claim 1, wherein the flow rate of each of the plurality of adjustable flow nozzles is incrementally adjusted through the overlapping arrangement of the at least one opening of the manifold orifice insert with the at least one opening of the retainer orifice insert such that each of the plurality of adjustable flow nozzles is incrementally adjustable between a minimum flow rate when minimum overlap between the first and second apertures occurs and a maximum flow rate when maximum overlap between the at least one opening of the manifold retainer insert and the at least one opening of the retainer orifice insert occurs.
6. The adjustable flow nozzle system of claim 1, wherein each of the plurality of adjustable flow nozzles further comprises a nozzle retainer engaged to the nozzle component for coupling each of the plurality of adjustable flow nozzles to the adjustable flow manifold.
7. The adjustable flow nozzle system of claim 1, further comprising:
a plurality of plugs configured to seal a respective one of the plurality of access openings.

8. The adjustable flow nozzle system of claim 1, wherein the retainer orifice insert defines an outwardly extending key portion for aligning the retainer orifice insert relative to the manifold orifice insert.
9. The adjustable flow nozzle system of claim 1, further comprising:
 - an adjustment key having an elongated key body defining a proximal portion and a distal portion, at least one key element extending from the proximal portion of the elongated key body, the at least one key element being configured to engage a respective key receptacle formed along the manifold orifice insert for rotating the manifold orifice insert relative to the retainer orifice insert.
10. The adjustable flow nozzle system of claim 1, wherein the manifold orifice insert further defines a first central opening and the retainer orifice insert further defines a second central opening; and wherein the first central opening is in a co-axial alignment with the second central opening in a maximum overlap arrangement to establish a minimum flow rate through each of the plurality of adjustable nozzles.