

**DESCRIPTION**

CONTENT PLAYBACK APPARATUS, METHOD, AND PROGRAM, AND

KEY MANAGEMENT APPARATUS AND SYSTEM

5 Technical Field

 This invention relates to a broadcast reception system in
which only such playback apparatuses that are owned by users authorized
to view digital broadcast contents are able to play back contents
properly (hereafter, referred to as the "conditional access system"),
10 and particularly to a technique for updating master keys that are
needed at times of playing back the contents.

Background Art

 In MPEG-2 Systems (ISO/IEC13818-1), which is a standard
conditional access system, the distributor transmits contents
15 including images and audio after scrambling them with a scrambling
key K_s . The receiver plays back the contents after descrambling them
with a scrambling key K_s . At this time, the distributor and the
receiver each need to have the same scrambling key K_s .

 The distributor therefore stores the scrambling key K_s into
20 a piece of information called ECM (Entitlement Control Messages),
and transmits the ECM after encrypting them with a work key K_w . Further,



the distributor stores the work key K_w into a piece of information called EMM (Entitlement Management Messages), and transmits the EMM after encrypting them with a master key K_m which is unique to each playback apparatus.

5 The receiver decrypts the EMM using the master key K_m that is of its own to obtain the work key K_w , and then decrypts the ECM using the work key K_w to obtain the scrambling key K_s . This way, the distributor and the receiver each have the same scrambling key K_s .

10 FIG. 1 shows the general structure of the conditional access system.

 The broadcast apparatus 101 multiplexes and transmits to the playback apparatus 102 by broadcast, various kinds of information including scrambled contents, ECM, EMM. The playback apparatus 102
15 descrambles/decrypts the information and displays it on a display monitor 103. At this time, the playback apparatus 102 performs decryption with use of an ID and a master key K_m stored in the playback apparatus itself, and then descrambles the scrambled contents. A
different ID is assigned to each playback apparatus, each manufacturer,
20 or else, as necessary. Also, a different master key K_m is assigned to each playback apparatus, each manufacturer, or else, as necessary.

The master keys correspond one-to-one with the IDs.

FIG. 2 shows the structure of the playback apparatus in the conditional access system.

In the playback apparatus 201, the receiving unit 202 receives
5 various kinds of information including scrambled contents, ECM, EMM,
and the type judging unit 203 judges the types of information. The
type judging unit 203 transfers information to different units
depending on what type of information it is; for example, it transfers
scrambled contents to the content descrambling unit 211, ECM to the
10 ECM decrypting unit 208, and EMM to the EMM decrypting unit 205.

The ID/Km storing unit 204 stores an ID and a master key that
are unique to the playback apparatus 201. The EMM decrypting unit
205 decrypts EMM with the master key Km, and inputs, to the Kw updating
unit 206, a work key Kw which has been a part of the decrypted EMM.
15 The Kw updating unit 206 obtains the work key Kw from the EMM decrypting
unit 205 and updates the existing work key Kw. The Kw storing unit
207 stores the work key Kw that has been updated by the Kw updating
unit 206.

There is also another example where, in order to update an
20 existing work key, a new work key is obtained through a bi-directional
communication system. (e.g. see Japanese Unexamined Patent

Application Publication No. 2002-16901)

The ECM decrypting unit 208 decrypts ECM with the work key Kw, and inputs, to the Ks updating unit 209, a scrambling key Ks which has been a part of the decrypted ECM. The Ks updating unit 209 obtains
5 the scrambling key Ks from the ECM decrypting unit 208 and updates the existing scrambling key Ks.

Here, updating of the work key Kw and the scrambling key Ks usually means to overwrite them; however, it is acceptable to make additions to the work key and the scrambling key.

10 The Ks storing unit 210 stores the scrambling key Ks that has been updated by the Ks updating unit 209. The content descrambling unit 211 descrambles the scrambled contents using the scrambling key Ks, and inputs the descrambled contents to the content outputting unit 212. The content outputting unit 212 transmits the contents
15 to the display monitor.

FIG. 3 shows the operation of the playback apparatus in the conditional access system.

The playback apparatus receives EMM from the broadcast apparatus (S301). The EMM include (i) an ID of a playback apparatus
20 that is to receive the EMM and (ii) an encrypted work key $E(Kw, Km)$ which is a work key Kw encrypted with a master key Km that corresponds

to the ID. Here and hereafter, $E(X, Y)$ denotes "information X encrypted with the key Y" or "information X scrambled with the key Y".

The playback apparatus decrypts $E(K_w, K_m)$ using a K_m stored in the playback apparatus itself, if the ID included in EMM coincides with the ID stored in the playback apparatus itself. As a result,
5 the playback apparatus obtains the work key K_w (S302).

Next, the playback apparatus receives ECM from the broadcast apparatus (S303). The ECM include an encrypted scrambling key $E(K_s, K_w)$ which is a scrambling key K_s encrypted with a work key K_w .

10 The playback apparatus decrypts $E(K_s, K_w)$ using the work key K_w stored in the playback apparatus itself. As a result, the playback apparatus obtains the scrambling key K_s (S304).

Further, the playback apparatus receives a scrambled content $E(\text{Content}, K_s)$ from the broadcast apparatus (S305).

15 The playback apparatus descrambles $E(\text{Content}, K_s)$ using the scrambling key K_s stored in the playback apparatus itself. As a result, the playback apparatus obtains the content (S306) and the user is able to view the content.

FIG. 4 shows the general structure of the conditional access system in which there are a plurality of playback apparatuses.
20

The playback apparatus 1 and the playback apparatus 2 receive

various kinds of information transmitted from the broadcast apparatus 101. A display monitor is omitted from the drawing. The ID1 and the ID2 are assigned to each of the playback apparatuses respectively and are different from each other. Since IDs correspond one-to-one with master keys Kms, Km1 and Km2 are different from each other as well. Here, a different ID is assigned to each playback apparatus, but it is also acceptable if a different ID is assigned to each manufacturer, each model of playback apparatuses, each production lot, or each specific group. In such cases, a plurality of playback apparatuses within a group have the same IDs and master keys Kms, but those IDs and master keys are different from IDs and master keys owned by playback apparatuses in another group.

FIG. 5 shows the operation of the plurality of playback apparatus in the conditional access system.

The playback apparatus 1 selectively receives EMM 1 from the broadcast apparatus (S501). EMM 1 includes the ID1 and an encrypted work key $E(Kw, Km1)$ which is a work key Kw encrypted with the master key Km1 that corresponds to the ID1. Because of the ID1 included in EMM 1, the playback apparatus 1 is able to identify that this particular set of EMM is addressed to the playback apparatus 1 itself.

The playback apparatus 1 decrypts $E(Kw, Km1)$ using the Km1

stored in the playback apparatus 1 itself. As a result, the playback apparatus 1 obtains the work key K_w (S502).

The playback apparatus 2 selectively receives EMM 2 from the broadcast apparatus (S503). EMM 2 include ID2 and an encrypted work key $E(K_w, K_{m2})$ which is the work key K_w encrypted with the master key K_{m2} that corresponds to ID2. Because of the ID2 included in EMM 2, the playback apparatus 2 is able to identify that this particular set of EMM is addressed to the playback apparatus 2 itself.

The playback apparatus 2 decrypts $E(K_w, K_{m2})$ using the K_{m2} stored in the playback apparatus 2 itself. As a result, the playback apparatus 2 obtains the work key K_w (S504).

This is how the playback apparatus 1 and the playback apparatus 2 each obtain the work key K_w . The procedure after this is the same as the one described in FIG. 3; therefore, explanation will be omitted.

The following describe a method of preventing an unauthorized apparatus from playing back contents, when there is one.

FIG. 6 shows the general structure of the conditional access system in which there is an unauthorized apparatus.

The unauthorized playback apparatus is a playback apparatus that disguises itself as the playback apparatus 2 with ID2 and the master Key K_{m2} having been obtained in an unauthorized fashion. In

this situation, the unauthorized apparatus is able to pretend as if it was the playback apparatus 2 and play back the contents, by the same procedure of operations shown in FIG. 5.

Here is a method by which the broadcast apparatus does not
5 transmit EMM that include the ID2 so that it is possible to prevent unauthorized playback of contents when it has been learned that an unauthorized apparatus exists.

FIG. 7 shows the operation of the playback apparatuses at times of preventing an unauthorized apparatus from performing
10 unauthorized playback of contents.

FIG. 7 differs from FIG. 5 in that the broadcast apparatus transmits only EMM 1 intended for the playback apparatus 1 (S501), and does not transmit EMM2 which are intended for the playback apparatus 2. This way, the unauthorized apparatus is not able to obtain the
15 work key Kw. As a result, the unauthorized playback apparatus is not able to obtain a scrambling key Ks (S701), and is not able to receive the contents, either (S702).

There is, however, a problem in this method since the broadcast apparatus does not transmit EMM that include the ID2. --- The playback
20 apparatus 2, being an authorized apparatus, will not be able to play back the contents, either.

The first object of the present invention, therefore, is to provide a technique that makes it possible to eliminate content playback by unauthorized playback apparatus, and enable only authorized playback apparatuses to play back contents properly.

5 The second object of the present invention is to provide a technique that enables only authorized playback apparatus to play back contents properly by utilizing the channel through which the contents are transmitted.

Disclosure of the Invention

10 The present invention provides a content playback apparatus comprising: a storing unit that has a secret key stored therein; a key information decrypting unit operable to (i) obtain encrypted key information that has been encrypted by a first secret-key encrypting method, and (ii) decrypt the encrypted key information into key
15 information using the stored secret key, the key information being either a decryption key used for decrypting a content key or key-updating information used for updating the secret key; a content playback unit operable to, when the decrypted key information is the decryption key, (i) decrypt an encrypted content key that has been
20 encrypted by a second secret-key encrypting method, using the decryption key, (ii) descramble a scrambled content that has been

scrambled by a scramble encrypting method, using the decrypted content key, and (iii) play back the descrambled content; and an updating unit operable to, when the decrypted key information is the key-updating information, update the secret key according to the key-updating information.

With this arrangement, the content playback apparatus obtains key information and (a) when the key information is key-updating information, updates the secret key, and (b) when the key information is a decryption key, plays back contents using the decryption key. By updating the secret key according to the key-updating information in this fashion, when obtaining key information that has been encrypted with use of the updated secret key, the content playback apparatus will be able to properly decrypt this encrypted key information.

Accordingly, after the secret key is updated, only authorized content playback apparatuses are able to play back contents, and it is therefore possible to eliminate content playback by unauthorized content playback apparatus.

The content playback apparatus may have an arrangement wherein, the key information has an identifier attached thereto for identifying the key information as either the decryption key or the key-updating information, and the content playback apparatus further comprises

a judging unit operable to judge, according to the identifier, whether the key information is the decryption key or the key-updating information.

With this arrangement, the content playback apparatus is able to judge from the identifier whether the key information is a decryption key or key-updating information.

The content playback apparatus may have an arrangement wherein the key information is included in EMM, EMM denoting Entitlement Management Messages, and the content playback apparatus further comprises a broadcast receiving unit operable to receive broadcast data which includes encrypted EMM that have been encrypted with use of the secret key and thereby obtain the encrypted key information, and the key information decrypting unit obtains the encrypted key information received by the broadcast receiving unit.

One of the ways to update a secret key is that a manager of the secret keys sends, to each authorized user, a portable medium on which a new secret key is recorded. In this method, it takes a considerable number of days before each authorized user receives the portable medium, and there is a possibility that the authorized users suffer a loss of privilege to view the contents meanwhile. Also, from the viewpoint of the manager of the secret keys, it is necessary

to send a portable medium to each of the users when secret keys of a plurality of content playback apparatuses need to be updated, and the costs that the manager needs to bear would be very high.

With the aforementioned arrangement, however, the content playback apparatus is able to obtain the key-updating information by receiving the broadcast data. Since the key-updating information is transmitted by broadcast, it is possible to update the secret key instantly.

This way, the authorized users will not suffer a loss as mentioned above. Besides, it is possible to notify a plurality of content playback apparatuses of updating of the secret keys at the same time by transmitting the key-updating information by broadcast.

Thus, the manager of the secret keys is able to reduce the costs mentioned above.

The content playback apparatus may have an arrangement wherein the updating unit updates the secret key by generating a new secret key according to a conversion unique to each content playback apparatus, each production lot of content playback apparatuses, each model of content playback apparatuses, or each manufacturer of content playback apparatuses.

With this arrangement, since the secret key is updated

according to a conversion that is unique to each content playback apparatus, each production lot of content playback apparatuses, each model of content playback apparatuses, or each manufacturer of content playback apparatuses, there will only be a limited number of content playback apparatuses for which measures need to be taken, even if a content playback apparatus is reverse-engineered and the conversion method of the secret key has leaked out.

The content playback apparatus may have an arrangement wherein the key-updating information includes seed information from which a new secret key is to be generated, and the updating unit updates the secret key by converting the seed information into the new secret key.

With this arrangement, since the key-updating information includes seed information, the content playback apparatus is able to obtain the seed information and generate a new secret key by converting the seed information.

The content playback apparatus may have an arrangement wherein the key-updating information is trigger information which instructs that the secret key should be updated, and the updating unit further includes: a transmitting subunit operable to transmit, in response to the trigger information, a request signal requesting seed

information from which a new secret key is to be generated, to a key management apparatus that manages one or more secret keys; and a seed information receiving subunit operable to receive the seed information transmitted by the key management apparatus in response to the request signal, and the updating unit updates the secret key by converting the received seed information into the new secret key.

With this arrangement, the content playback apparatus obtains trigger information and realizes that the secret key needs to be updated due to the trigger information. Then, the content playback apparatus transmits a request for seed information to the key management apparatus, receives the seed information, and obtains a new secret key by converting the seed information. Communicating with the key management apparatus after receiving the key-updating information has two advantages as follows:

One is that the key management apparatus is able to determine from which content playback apparatus the unauthorized content playback apparatus has derived. For example, if it has been arranged so that content playback apparatuses need to transmit their own IDs as a requesting signal and there is an unauthorized content playback apparatus, then the same ID will be transmitted to the key management apparatus more than once. Then, the key management apparatus is able

to judge that the content playback apparatus having this particular ID is the one from which the unauthorized content playback apparatus has derived.

The other advantage is that the key management apparatus is able to find out that the content playback apparatus is updating a master key. For example, in a case where only seed information is transmitted by broadcast, the key management apparatus is not able to find out that the content playback apparatus is updating a master key. With the aforementioned arrangement, however, the key management apparatus is able to confirm at least that the content playback apparatus has received the key-updating information because there is communication from the content playback apparatus.

The content playback apparatus may have an arrangement wherein the key-updating information includes seed information from which a new secret key is to be generated, and the updating unit further includes an outputting subunit operable to output event information that is different every time of output or once in every certain number of times of output, the updating unit updates the secret key by converting the seed information and the event information into the new secret key, and the content playback apparatus further comprises a transmitting unit operable to transmit the event information

outputted by the outputting subunit to a key management apparatus that manages one or more secret keys.

With this arrangement, the content playback apparatus generates a new secret key from the seed information and the event
5 information, and also transmits the event information in order to let the key management apparatus have the same new secret key. Communicating with the key management apparatus after receiving the key-updating information has two advantages as follows:

One is that the key management apparatus is able to determine
10 from which content playback apparatus the unauthorized content playback apparatus has derived. For example, if it has been arranged so that content playback apparatuses need to transmit their own IDs as a requesting signal and there is an unauthorized content playback apparatus, then the same ID will be transmitted to the key management
15 apparatus more than once. Then, the key management apparatus is able to judge that the content playback apparatus having this particular ID is the one from which the unauthorized content playback apparatus has derived.

The other advantage is that the key management apparatus is
20 able to find out that the content playback apparatus is updating a master key. For example, in a case where only seed information is

transmitted by broadcast, the key management apparatus is not able to find out that the content playback apparatus is updating a master key. With the aforementioned arrangement, however, the key management apparatus is able to confirm at least that the content
5 playback apparatus has received the key-updating information because there is communication from the content playback apparatus.

The content playback apparatus may have an arrangement wherein the secret key stored in the storing unit is unique to each content playback apparatus, each production lot of content playback
10 apparatuses, each model of content playback apparatuses, or each manufacturer of content playback apparatuses.

With this arrangement, since the secret key is unique to each content playback apparatus, each production lot of content playback apparatuses, each model of content playback apparatuses, or each
15 manufacturer of content playback apparatuses, there will only be a limited number of content playback apparatuses for which measures need to be taken, even if a content playback apparatus is reverse-engineered and the conversion method of the secret key has leaked out.

20 The content playback apparatus may further have an ID that is unique to each content playback apparatus, each production lot

of content playback apparatuses, each model of content playback apparatuses, or each manufacturer of content playback apparatuses, wherein the updating unit updates the secret key by converting the ID and seed information into a new secret key, the seed information
5 being information from which the new secret key is to be generated.

With this arrangement, since the ID is unique to each content playback apparatus, each production lot of content playback apparatuses, each model of content playback apparatuses, or each manufacturer of content playback apparatuses, there will only be a
10 limited number of content playback apparatuses for which measures need to be taken, even if a content playback apparatus is reverse-engineered and the conversion method of the secret key has leaked out.

The present invention further provides a content playback
15 method to be used in a content playback apparatus which includes a storing unit that has a secret key stored therein, the content playback method comprising: a key information decrypting step of (i) obtaining encrypted key information that has been encrypted by a first secret-key encrypting method, and (ii) decrypting the encrypted key information
20 into key information using the stored secret key, the key information being either a decryption key used for decrypting a content key or

key-updating information used for updating the secret key; a content playback step of, when the decrypted key information is the decryption key, (i) decrypting an encrypted content key that has been encrypted by a second secret-key encrypting method, using the decryption key, (ii) descrambling a scrambled content that has been scrambled by a scramble encrypting method, using the decrypted content key, and (iii) playing back the descrambled content; and an updating step of, when the decrypted key information is the key-updating information, updating the secret key according to the key-updating information.

With this arrangement, the content playback apparatus obtains key information and (a) when the key information is key-updating information, updates the secret key, and (b) when the key information is a decryption key, plays back contents using the decryption key. By updating the secret key according to the key-updating information in this fashion, when obtaining key information that has been encrypted with use of the updated secret key, the content playback apparatus will be able to properly decrypt this encrypted key information.

Accordingly, after the secret key is updated, only authorized content playback apparatuses are able to play back contents, and it is therefore possible to eliminate content playback by unauthorized content playback apparatus.

The present invention further provides a program that instructs a computer to play back contents, the computer including a storing unit that has a secret key stored therein, the program comprising: a key information decrypting step of (i) obtaining encrypted key information that has been encrypted by a first secret-key encrypting method, and (ii) decrypting the encrypted key information into key information using the stored secret key, the key information being either a decryption key used for decrypting a content key or key-updating information used for updating the secret key; a content playback step of, when the decrypted key information is the decryption key, (i) decrypting an encrypted content key that has been encrypted by a second secret-key encrypting method, using the decryption key, (ii) descrambling a scrambled content that has been scrambled by a scramble encrypting method, using the decrypted content key, and (iii) playing back the descrambled content; and an updating step of, when the decrypted key information is the key-updating information, updating the secret key according to the key-updating information.

With this arrangement, the computer obtains key information and (a) when the key information is key-updating information, updates the secret key, and (b) when the key information is a decryption key, plays back contents using the decryption key. By updating the secret

key according to the key-updating information in this fashion, when obtaining key information that has been encrypted with use of the updated secret key, the content playback apparatus will be able to properly decrypt this encrypted key information.

5 Accordingly, after the secret key is updated, only authorized content playback apparatuses are able to play back contents, and it is therefore possible to eliminate content playback by unauthorized content playback apparatus.

10 The present invention further provides a key management apparatus that manages a secret key used in a secret-key encrypting method, comprising: a key-updating information generating unit operable to generate key-updating information used for updating the secret key; a transmitting unit operable to encrypt key information using the secret key and transmit the encrypted key information to
15 a playback apparatus, the key information being either a decryption key for playing back contents or the key-updating information; and a secret key updating unit operable to update the secret key according to the key-updating information.

20 With this arrangement, since the key management apparatus transmits encrypted key information to the content playback apparatus, the key management apparatus and the content playback apparatus each

will be able to have the same key information. Also, the key management apparatus is able to update the secret key according to key-updating information included in the key information. Consequently, after the secret key is updated, only authorized content playback apparatuses are able to playback contents, and it is therefore possible to eliminate content playback by unauthorized content playback apparatus.

The key management apparatus may have an arrangement wherein the transmitting unit attaches, to the key information, an identifier for identifying the key information as either the decryption key or the key-updating information, before transmitting the key information.

With this arrangement, the key management apparatus is able to transmit, in one form, two kinds of information such as a decryption key and key-updating information.

The key management apparatus may have an arrangement wherein the key information is included in EMM, EMM denoting Entitlement Management Messages, and the transmitting unit transmits the key information to the playback apparatus by broadcast.

With this arrangement, the key management apparatus is able to transmit the key-updating information by broadcast. Since the

key-updating information is transmitted by broadcast, it is possible to update the secret keys instantly.

The key management apparatus may have an arrangement wherein the key-updating information includes seed information from which a new secret key is to be generated, and the secret key updating unit
5 updates the secret key by converting the seed information into the new secret key.

With this arrangement, since the key-updating information includes seed information, the key management apparatus is able to
10 generate the seed information and also to generate a new secret key by converting the seed information.

The key management apparatus may have an arrangement wherein the key-updating information is trigger information which instructs that the secret key should be updated, and the secret key updating
15 unit further includes: a seed information generating subunit operable to generate seed information from which a new secret key is to be generated; and a transferring subunit operable to receive a request signal transmitted by the playback apparatus that has obtained the trigger information, and transfer the generated seed information to
20 the playback apparatus in response to the request signal, and the secret key updating unit updates the secret key by converting the

seed information into the new secret key.

With this arrangement, the key management apparatus generates trigger information and notifies the content playback apparatus, with use of the trigger information, that the secret key needs to be updated.

5 Then, the key management apparatus receives from the content playback apparatus a request signal requesting seed information, transmits the seed information to the content playback apparatus in response to the request signal, and obtains a new secret key by converting the seed information. Communicating with the content playback
10 apparatus after transmitting the key-updating information has two advantages as follows:

One is that the key management apparatus is able to determine from which content playback apparatus the unauthorized content playback apparatus has derived. For example, if it has been arranged
15 so that content playback apparatuses need to transmit their own IDs as a requesting signal and there is an unauthorized content playback apparatus, then the same ID will be transmitted to the key management apparatus more than once. Then, the key management apparatus is able to judge that the content playback apparatus having this particular
20 ID is the one from which the unauthorized content playback apparatus has derived.

The other advantage is that the key management apparatus is able to find out that the content playback apparatus is updating a master key. For example, in a case where only seed information is transmitted by broadcast, the key management apparatus is not able to find out that the content playback apparatus is updating a master key. With the aforementioned arrangement, however, the key management apparatus is able to confirm at least that the content playback apparatus has received the key-updating information because there is communication from the content playback apparatus.

The key management apparatus may have an arrangement wherein the key-updating information includes seed information from which a new secret key is to be generated, and the secret key updating unit further includes a receiving subunit operable to receive event information transmitted by the playback apparatus that has obtained the seed information, the event information being different every time of transmission or once in every certain number of times of transmission, and the secret key updating unit updates the secret key by converting the seed information and the event information into the new secret key.

With this arrangement, the key management apparatus receives the event information from the content playback apparatus and

generates a new secret key from the seed information and the event information. Communicating with the content playback apparatus after transmitting the key-updating information has two advantages as follows:

5 One is that the key management apparatus is able to determine from which content playback apparatus the unauthorized content playback apparatus has derived. For example, if it has been arranged so that content playback apparatuses need to transmit their own IDs as a requesting signal and there is an unauthorized content playback
10 apparatus, then the same ID will be transmitted to the key management apparatus more than once. Then, the key management apparatus is able to judge that the content playback apparatus having this particular ID is the one from which the unauthorized content playback apparatus has derived.

15 The other advantage is that the key management apparatus is able to find out that the content playback apparatus is updating a master key. For example, in a case where only seed information is transmitted by broadcast, the key management apparatus is not able to find out that the content playback apparatus is updating a master
20 key. With the aforementioned arrangement, however, the key management apparatus is able to confirm at least that the content

playback apparatus has received the key-updating information because there is communication from the content playback apparatus.

The present invention further provides a key management system made up of (i) a content playback apparatus and (ii) a key management apparatus that manages one or more secret keys used in a secret-key
5 encrypting method for the content playback apparatus, the key management system comprising: a key-updating information generating unit that is included in the key management apparatus and is operable to generate key-updating information used for updating each secret
10 key; a transmitting unit operable to encrypt key information using a first secret key, and transmit the encrypted key information to the content playback apparatus, the key information being either a decryption key for playing back contents or the key-updating information; a key information decrypting unit that is included in
15 the content playback apparatus and is operable to obtain the encrypted key information transmitted by the transmitting unit and decrypt the encrypted key information into key information using a second secret key, the second secret key being stored in the content playback apparatus; a first updating unit that is included in the key management
20 apparatus and is operable to update the first secret key according to the key-updating information; and a second updating unit that is

included in the content playback apparatus and is operable to, when the decrypted key information is key-updating information used for updating the second secret key, update the second secret key according to the key-updating information.

5 With this arrangement, the content playback apparatus and the key management apparatus each obtain key information and (a) when the key information is key-updating information, update the secret key, and (b) when the key information is a decryption key, play back contents using the decryption key. By updating the secret keys according to the key-updating information in this fashion, when
10 obtaining key information that has been encrypted with use of the updated secret key, the content playback apparatus and the key management apparatus each will be able to properly decrypt this encrypted key information.

15 Accordingly, after the secret keys are updated, only authorized content playback apparatuses are able to play back contents, and it is therefore possible to eliminate content playback by unauthorized content playback apparatus.

Brief Description of The Drawings

20 FIG. 1 shows the general structure of a conditional access system;

FIG. 2 shows the structure of a playback apparatus in the conditional access system;

FIG. 3 shows the operation of the playback apparatus in the conditional access system;

5 FIG. 4 shows the general structure of the conditional access system in which there are a plurality of playback apparatuses;

FIG. 5 shows the operation of the plurality of playback apparatus in the conditional access system;

10 FIG. 6 shows the general structure of the conditional access system in which there is an unauthorized apparatus;

FIG. 7 shows the operation of the playback apparatuses at times of preventing an unauthorized apparatus from performing unauthorized playback of contents;

15 FIG. 8 shows the general structure of the conditional access system of the first embodiment;

FIG. 9 shows the structure of the playback apparatus in the conditional access system;

FIG. 10 shows the detailed structure of the Km updating unit in the first embodiment;

20 FIG. 11 shows the data structure of normal EMM;

FIG. 12 shows the data structure of EMM for updating a master

key Km;

FIGs. 13A and 13B show examples of algorithms used in the Km generating unit;

FIG. 14 shows the operation of the playback apparatus in the conditional access system;

FIG. 15 shows the structure of the key management apparatus in the conditional access system;

FIG. 16 shows an example of management of IDs and master keys Kms by the key management apparatus;

FIG. 17 shows the operation of the key management apparatus in the conditional access system;

FIG. 18 shows the operation of the playback apparatuses at times of eliminating unauthorized content viewing by an unauthorized apparatus;

FIG. 19 shows the general structure of the conditional access system of the second embodiment;

FIG. 20 shows the detailed structure of the Km updating unit in the second embodiment;

FIG. 21 shows the data structure of EMM for updating a master key Km;

FIG. 22 shows the structure of the key management apparatus

in the conditional access system;

FIG. 23 shows the general structure of the conditional access system of the third embodiment;

FIG. 24 shows the detailed structure of the Km updating unit
5 in the third embodiment;

FIG. 25 shows the structure of the key management apparatus in the conditional access system; and

FIG. 26 shows the structure of a DVD playback apparatus.

Best Mode for Carrying Out the Invention

10 First Embodiment

General Structure of the Conditional Access System

FIG. 8 shows the general structure of the conditional access system of the first embodiment.

The conditional access system of the first embodiment comprises
15 a key management apparatus 801, a manufacturing machine 802, a playback apparatus 803, and a broadcast apparatus 804.

Firstly, explanation is provided on how the key management apparatus 801 and the playback apparatus 803 each get to have the same ID and the same master key Km.

20 The key management apparatus 801 assigns an ID and a master key that are both unique to each playback apparatus, each production

lot, each model, or each manufacturer, as necessary, and provides them for the manufacturing machines 802.

The manufacturing machine 802, which manufactures the playback apparatus 803, assembles the ID and the master key Km that have been
5 assigned by the key management apparatus 801 into the playback apparatus 803, and then provides the playback apparatus 803 for a user.

This way, the key management apparatus 801 and the playback apparatus 803 each get to have the same ID and the same master key
10 Km.

Secondly, explanation is provided on the procedure by which a user views a desired content. Here, it is assumed that, as an example, the user's playback apparatus 803 stores an ID "00000001" and a master key Km "27832529" therein.

15 The user makes a request for content viewing to the broadcast apparatus 804 that broadcasts the desired content. At this time, the user informs the broadcast apparatus 804 of the ID "00000001" stored in his/her playback apparatus 803.

The broadcast apparatus 804 receives the request from the
20 user and stores the ID "00000001" and the work key Kw for the playback apparatus 803 into EMM and sends the EMM to the key management apparatus

801.

Here, the work key Kw is a key which only such playback apparatuses that are owned by users authorized to view contents are able to obtain.

5 The key management apparatus 801 receives the EMM from the broadcast 804, and extracts the ID "00000001" stored in the EMM. Then, the key management apparatus 801 identifies that a master key Km "27832529" corresponds to this ID and encrypts the EMM with the master key Km "27832529", before transmitting the EMM to the broadcast
10 apparatus 804.

The broadcast apparatus 804 broadcasts the encrypted EMM.

The playback apparatus 803 selectively receives the EMM, judging from the ID stored in the EMM that this particular set of EMM has been addressed to the playback apparatus itself. In this
15 case, the ID stored in the EMM is the ID "00000001"; therefore, the playback apparatus 803 judges that this set of EMM is addressed to the playback apparatus 803 itself. Subsequently, the playback apparatus 803 decrypts the EMM with the master key Km "27832529" and obtains a work key Kw.

20 This is how the broadcast apparatus 804 and the playback apparatus 803 each get to have the same work key Kw.

In addition to EMM, the broadcast apparatus 804 also broadcasts ECM that include a scrambling key K_s as well as contents scrambled by a scrambling key K_s . The playback apparatus 803 is able to obtain a scramble key K_s by decrypting ECM using the work key K_w , and is
5 able to obtain a content by descrambling a scrambled content that has been scrambled by the scrambling key K_s .

The following explains updating of a master key K_m , which is one of the characteristics of the present embodiment.

A master key K_m does not need to be updated in principle;
10 however, if the ID "00000001" and the master key K_m "27832529" of the playback apparatus 803 leak to an unauthorized user, for example, then by copying and registering these ID and master key K_m into his/her playback apparatus, this unauthorized user will be able to view, in an unauthorized fashion, the contents which the user of the playback
15 apparatus 803 has been authorized to view. In this case, Updating of the master key K_m becomes necessary.

Thus, the broadcast apparatus 804 stores in EMM (i) an ID of the playback apparatus that needs an update of the master key and (ii) seed information from which a new master key is to be generated
20 and broadcasts the EMM. Then, the playback apparatus in need of an updated master key generates a new master key from the seed information.

Here, the algorithm used to generate a new master key from seed information is determined at the time of manufacturing a playback apparatus and is assembled into the playback apparatus in a secure state. The same algorithm has also been assembled into a key management apparatus in a secure state. It means that since only the key management apparatus and the playback apparatus of an authorized user store the same algorithms, only the key management apparatus and the playback apparatus of the authorized user are able to have the same new master keys.

Accordingly, the conditional access system of the present embodiment is able to eliminate unauthorized viewing of contents by unauthorized users after the master keys are updated.

The following explains in detail the playback apparatus and the key management apparatus which are used to actualize such a conditional access system.

Structure of Playback Apparatus

FIG. 9 shows the structure of the playback apparatus in the conditional access system.

The playback apparatus 901 comprises a receiving unit 902, a type judging unit 903, an ID/Km storing unit 904, an EMM decrypting unit 905, an updating information judging unit 906, a Kw updating

unit 907, a Kw storing unit 908, an ECM decrypting unit 909, a Ks updating unit 910, a Ks storing unit 911, a content descrambling unit 912, a content outputting unit 913, and a Km updating unit 914.

5 The receiving unit 902 receives various kinds of information including scrambled contents, ECM and EMM from the broadcast apparatus.

The type judging unit 903 transfers information to different units depending on what type of information it is, for example, it transfers scrambled contents to the content descrambling unit 912, ECM to the ECM decrypting unit 909, and EMM to the EMM decrypting unit 905.

10 The ID/Km storing unit 904 stores an ID and a master key that are unique to the playback apparatus 901, and inputs the master key Km to the EMM decrypting unit 905, as necessary. The initial value of the master key Km is the one that has been assembled into the playback apparatus by the manufacturer and gets updated by the Km updating unit 914, as necessary.

15 The EMM decrypting unit 905 decrypts EMM using the master key Km and inputs the decrypted EMM to the updating information judging unit 906.

20 The updating information judging unit 906, according to the

identifier included in the EMM, judges whether the EMM stores seed information for updating the master key K_m or a new work key for updating the work key. The identifier will be explained later.

When a work key K_w is stored, the updating information judging unit 906 inputs the work key K_w to the K_w updating unit 907. When seed information is stored, the updating information judging unit 906 inputs the seed information to the K_m updating unit 914.

The K_w updating unit 907 obtains the work key K_w from the updating information judging unit 906 and updates the existing work key. A work key is usually updated by being overwritten; however, it is also acceptable to update a work key by making an addition to it.

The K_w storing unit 908 stores the work key K_w updated by the K_w updating unit 907, and inputs the work key K_w to the ECM decrypting unit 909, as necessary.

The ECM decrypting unit 909 decrypts ECM using the work key K_w and inputs a new scrambling key K_s stored in the ECM to the K_s updating unit 910.

The K_s updating unit 910 obtains the scrambling key K_s from the ECM decrypting unit 909 and updates the existing scrambling key K_s . A scrambling key is usually updated by being overwritten; however,

it is also acceptable to update a scrambling key by making an addition to it.

The Ks storing unit 911 stores the scrambling key Ks updated by the Ks updating unit 910 and inputs the scrambling key Ks to the content descrambling unit 912, as necessary.

The content descrambling unit 912 descrambles scrambled contents using the scrambling key Ks and inputs the descrambled contents to the content outputting unit 913.

The content outputting unit 913 transmits the content to the display monitor.

The Km updating unit 914 obtains the seed information from the updating information judging unit 906 and updates the master key Km using the seed information. A master key is usually updated by being overwritten; however, it is also acceptable to update a master key by making an addition to it. When an addition is made to a master key, the ID/Km storing unit 904 will be able to store all master keys that are there prior to updates as well as the current master key. Thus, in case the current master key is unusable due to an error, it will be possible to use one of the master keys prior to updates instead. It is further acceptable if the ID/Km storing unit 904 stores only the initial master key in addition to the current master key.

Furthermore, it is also acceptable to update the master key and the ID at the same time. It is also acceptable to use part of an ID as a generation number and update the generation of a combination of an ID and a master key. In such a case, the ID may be updated
5 by being overwritten or by having an addition made to it.

FIG. 10 shows the detailed structure of the Km updating unit in the first embodiment.

The Km updating unit 914 comprises a seed information obtaining unit 1001, a Km generating unit 1002, and a Km retaining unit 1003.

10 The seed information obtaining unit 1001 obtains the seed information from the updating information judging unit and inputs the seed information to the Km generating unit 1002 as an argument in the algorithm used for generating a master key.

The Km generating unit 1002 generates a new master key Km' using the algorithm having been assembled into the Km generating unit
15 1002 itself. The algorithm is unique to each playback apparatus, each production lot, each model, or each manufacturer. The same algorithm is also stored in the key management apparatus.

The Km retaining unit 1003 retains the master key Km in a form in which the ID/Km storing unit 904 will be able to store it.
20

This way, the playback apparatus 901 is able to update the

master key Km using the EMM broadcasted from the broadcast apparatus.

The Km updating unit 914 has two possibilities as will be mentioned below depending on at which point of time a new master key is generated, and it could be either way.

5 The first possibility is that a new master key is generated as soon as the seed information is obtained.

 The second possibility is that the seed information is obtained and stored till it is necessary to generate a new master key. In this case, a new master key may be generated, for example, after EMM
10 are inputted to the EMM decrypting unit, and then a signal transmitted from the EMM decrypting unit is received.

 The following explains the data structure of EMM.

 FIG. 11 shows the data structure of normal EMM.

 EMM are made up of an ID segment and a data segment. The ID
15 segment stores an ID of the playback apparatus that is to receive this particular set of EMM. The playback apparatus is therefore able to selectively decrypt only EMM in which the ID of the playback apparatus is stored, among different sets of EMM broadcasted from the broadcast apparatus.

20 The data segment stores an identifier and key information. The identifier identifies the key information stored in the data

segment as either a work key or seed information. For instance, it could be arranged so that when the identifier is "0x01", a work key is stored, and when the identifier is "0x02", seed information is stored.

5 The data segment also stores other items such as an information length, a protocol number, an expiration date, but explanation on these items will be omitted.

FIG. 12 shows the data structure of EMM for updating a master key Km.

10 A set of EMM for updating a master key Km is also made up of an ID segment and a data segment like the normal EMM.

The data segment stores an identifier and seed information.

The seed information is information from which a new master key is to be generated and could be, for example, a generation number of the master key, random numbers, or a combination of these.

15

FIGs. 13A and 13B show examples of algorithms used in the Km generating unit.

FIG. 13A indicates a method where a master key is obtained from the ID and the generation number of the playback apparatus, with use of an original hash function.

20

FIG. 13B indicates a method where a master key is obtained

by encrypting random numbers generated in the key management apparatus with use of an original encrypting function.

Methods for generating a new master key is not limited to the ones mentioned here as long as the playback apparatus and the key management apparatus are each able to own a new master key securely. It is acceptable, for example, to generate a new master key by inputting the ID, the generation number and the seed information into an original hash function that is unique to each manufacturer.

Operation of Playback Apparatus

FIG. 14 shows the operation of the playback apparatus in the conditional access system.

The playback apparatus receives various kinds of information including scrambled contents, ECM, and EMM from the broadcast apparatus. The following explains only a case where EMM are received.

When the playback apparatus receives EMM, it is judged whether a work key is included or seed information is included from the identifier stored in the EMM (S1401).

If seed information is included in the EMM (S1402, Y) the playback apparatus obtains the seed information included in the EMM (S1403).

The playback apparatus then generates a new master key from

the seed information (S1404).

The playback apparatus stores the master key generated in Step S1404 and uses it starting from the next occasion (S1405).

If a work key is included in the EMM at Step S1402 (S1402,
5 N), the playback apparatus obtains the work key (S1406).

The playback apparatus stores the work key decrypted in Step S1406 so that it can be used starting from the next occasion of receiving ECM (S1407).

So far, explanation is provided as to the structure and the
10 operation of the playback apparatus that is able to generate a new master key from the seed information stored in EMM. The following explains how a key management apparatus is able to have the same new master key as the playback apparatus does.

Structure of the Key Management Apparatus

15 FIG. 15 shows the structure of the key management apparatus in the conditional access system.

The key management apparatus 1501 comprises an EMM receiving unit 1502, a key-updating judging unit 1503, a seed information generating and inserting unit 1504, a Km updating unit 1505, an ID/Km
20 storing unit 1506, an EMM encrypting unit 1507, and an encrypted EMM transmitting unit 1508.

The EMM receiving unit 1502 receives EMM transmitted from the broadcast apparatus and inputs the EMM to the key-updating judging unit 1503.

5 The key-updating judging unit 1503 judges if the EMM include some information which indicates that the master key needs to be updated. More specifically, if it is arranged so that an identifier "0x02" means "the master key needs to be updated", then the key-updating judging unit 1503 checks if the identifier is "0x02" or not. When the identifier is "0x02", the key-updating judging unit notifies the
10 seed information generating and inserting unit 1504 of the fact. The EMM will be inputted to the EMM encrypting unit 1507.

 The seed information generating and inserting unit 1504 receives the notification from the key-updating judging unit 1503, generates seed information, inserts it into the EMM, and also inputs
15 the seed information to the Km updating unit 1505. The seed information is information from which a new master key is to be generated and could be, for example, a generation number of the master key or random numbers.

 The Km updating unit 1505 obtains the seed information from
20 the seed information generating and inserting unit 1504 and updates the master key Km using the seed information. Here, the algorithm

used to generate the new master key from the seed information is stored in the playback apparatus as well.

The ID/Km storing unit 1506 stores an ID and a master key Km that are unique to each playback apparatus, each production lot, each model, or manufacturer, and inputs the master key Km to the EMM
5 encrypting unit 1507, as necessary. The initial value of the master key Km is the one that has been assembled into the playback apparatus at the time of manufacturing, and gets updated by the Km updating unit 1505, as necessary.

10 The EMM encrypting unit 1507 encrypts the EMM using the master key Km and inputs the encrypted EMM to the encrypted EMM transmitting unit 1508.

The encrypted EMM transmitting unit 1508 transmits the encrypted EMM to the broadcast apparatus.

15 The EMM for transmitting seed information therein gets encrypted with use of the old master key before being updated. The new master key after the update will be used starting from the next occasion of encrypting EMM.

As so far explained, the keymanagement apparatus (i) generates
20 seed information and inserts it into the EMM, (ii) transmits the seed information to the playback apparatus via the broadcast apparatus,

and (iii) updates the master key K_m with use of the seed information. The playback apparatus, on the other hand, updates the master key with use of the seed information having been transmitted. Here, since the key management apparatus and the playback apparatus each own the same algorithm that is used to generate a master key from seed information, the key management apparatus and the playback apparatus each get to own the same new master key.

FIG. 16 shows an example of management of IDs and master keys K_m s by the key management apparatus.

The key management apparatus manages all IDs and master keys K_m s together at the ID/ K_m storing unit using a management table shown in FIG. 16. In the management table, different IDs are arranged in the row direction, and different generations of the master keys K_m s are arranged in the column direction.

When the key management apparatus assigns an ID and a master key to a manufacturing machine, these ID and master key K_m are added to this management table. At first, a master key is added to the column of the first generation, and every time the master key is updated, a new master key is added to the next column, starting with the column of the second generation and then to the column of the third generation.

The reason that all master keys including the ones in the

past are stored can be explained as follows:

When a same ID is assigned to each playback apparatus of the same model, all the playback apparatuses will not necessarily be successful in updating their master keys after the first transmission of updating information. It is therefore necessary to transmit, to those playback apparatuses that have not been successful in updating their master keys, updating information that has been encrypted with use of a master key from the past.

Operation of the Key Management Apparatus

FIG. 17 shows the operation of the key management apparatus in the conditional access system.

When receiving EMM from the broadcast apparatus, the key management apparatus judges whether a secret key needs to be updated or not from the identifier included in the EMM (S1701).

If the master key needs to be updated (S1702, Y), the key management apparatus generates seed information (S1703), and inserts the seed information into the EMM (S1704).

The key management apparatus obtains the master key stored in the ID/Km storing unit (S1705), and encrypts the EMM using the master key (S1706).

Then, the key management apparatus transmits the encrypted

EMM to the broadcast apparatus (S1707).

After transmitting the encrypted EMM to the broadcast apparatus in Step S1707, the key management apparatus generates a new master key using the seed information generated in Step S1703 (S1708).

5 The key management apparatus stores the new master key generated in Step S1708 and uses the new master key starting from the next occasion (S1709).

 If the master key does not need to be updated in Step S1702 (S1702, N), the key management apparatus obtains the master key stored
10 in the ID/Km storing unit (S1710), and encrypts the EMM using the master key (S1711).

 Then, the key management apparatus transmits the encrypted EMM to the broadcast apparatus (S1712).

Operation of the Conditional Access System

15 The following describes the operation of the conditional access system that includes the playback apparatus and the key management apparatus mentioned above. This embodiment is characterized with the operation by which it is possible to eliminate
content viewing by an unauthorized playback apparatus, when it has
20 been learned that there is an unauthorized playback apparatus which disguises itself as an authorized playback apparatus. The following

explains this particular operation.

FIG. 18 shows the operation of the playback apparatuses at times of eliminating unauthorized content viewing by an unauthorized apparatus.

5 The playback apparatus 1 is owned by the user 1 authorized to view contents and stores ID1 and a master key Km1. In the same manner, the playback apparatus 2 is owned by the user 2 authorized to view contents and stores ID2 and a master key Km2. The unauthorized playback apparatus is disguising itself as the playback apparatus
10 2 and stores ID2 and a master key Km2.

The following explains the procedure in which the broadcast apparatus finds out that there is an unauthorized playback apparatus and eliminates the content viewing by the unauthorized playback apparatus.

15 The broadcast apparatus transmits EMM 1 to the playback apparatus 1 (S1801).

 Generally speaking, EMM include (i) the ID of a playback apparatus that is to receive this particular set of EMM and (ii) an encrypted work key $E(K_w, K_m)$ which is a work key K_w encrypted with
20 a master key K_m . Accordingly, EMM 1 include the ID1 and an encrypted work key $E(K_w, K_{m1})$.

The playback apparatus 1 judges that this particular set of EMM is addressed to the playback apparatus 1 itself from the ID1 included in the EMM 1, and decrypts $E(Kw, Km1)$ using the $Km1$ stored in the playback apparatus 1 itself. As a result, the playback apparatus
5 1 obtains the work key Kw (S1802).

The broadcast apparatus transmits EMM 2 to the playback apparatus 2 (S1803).

The EMM 2 include the ID2 and encrypted seed information $E(\text{Seed}, Km2)$. The encrypted seed information $E(\text{Seed}, Km2)$ is seed information
10 "Seed" that has been encrypted using the master key $Km2$.

The playback apparatus 2 judges that this particular set of EMM is addressed to the playback apparatus 2 itself from the ID2 included in the EMM 2, and decrypts $E(\text{Seed}, Km2)$ using the $Km2$ stored in the playback apparatus 2 itself. As a result, the playback apparatus
15 2 obtains the seed information "Seed" (S1804).

The unauthorized playback apparatus also judges that this particular set of EMM is addressed to the unauthorized playback apparatus itself from the ID2 included in the EMM 2 and decrypts $E(\text{Seed}, Km2)$ using the $Km2$ stored in the unauthorized playback apparatus itself.
20 As a result, the unauthorized playback apparatus obtains the seed information "Seed" (S1805).

The playback apparatus 2 generates a new master key $Km2'$ from the seed information "Seed" (S1806). The algorithm used to generate the master key $Km2'$ from the seed information "Seed" is unique to each playback apparatus, each production lot, each model, or each manufacturer. As storing the same algorithm, the key management apparatus is also able to generate the master key $Km2'$ from the seed information "Seed". Consequently, the playback apparatus 2 and the key management apparatus are each able to own the same new master key $Km2'$.

On the other hand, the unauthorized playback apparatus does not have the algorithm used to generate the master key $Km2'$ from the seed information "Seed", and is therefore not able to generate a master key $Km2'$ (S1807).

The broadcast apparatus transmits $EMM2'$ to the playback apparatus 2 (S1808).

Here the $EMM2'$ include ID2 and an encrypted work key $E(Kw, Km2')$.

The playback apparatus 2 judges that this particular set of EMM is addressed to the playback apparatus 2 itself from the ID2 included in the EMM 2, and decrypts $E(Kw, Km2')$ using the $Km2'$ stored in the playback apparatus 2 itself. As a result, the playback apparatus

2 obtains a work key K_w (S1809).

On the other hand, the unauthorized playback apparatus also judges that this particular set of EMM is addressed to the unauthorized playback apparatus itself from the ID2 included in the EMM 2, but
5 is not able to obtain a work key K_w because the unauthorized playback apparatus does not store the master key K_{m2}' (S1810).

The broadcast apparatus transmits ECM to both the playback apparatus 1 and the playback apparatus 2. (S1811).

ECM include an encrypted scrambling key $E(K_s, K_w)$ which is
10 a scrambling key K_s encrypted with a work key K_w .

The playback apparatus 1 receives the ECM and decrypts $E(K_s, K_w)$ using the work key K_w obtained in Step S1802. As a result, the playback apparatus 1 obtains the scrambling key K_s (S1812).

The playback apparatus 2 receives the ECM and decrypts $E(K_s, K_w)$ using the work key K_w obtained in Step S1809. As a result, the
15 playback apparatus 2 obtains the scrambling key K_s (S1813).

On the other hand, the unauthorized playback apparatus is not able to obtain the work key K_w in Step S1810, and is therefore not able to obtain the scrambling key K_s , either (S1814).

20 The broadcast apparatus transmits a scrambled content to each of the playback apparatus 1 and the playback apparatus 2 (S1815).

The scrambled content $E(\text{Content}, K_s)$ is a content scrambled with a scrambling key K_s .

The playback apparatus 1 descrambles $E(\text{Content}, K_s)$ using the scrambling key K_s obtained in Step S1812. As a result, the playback
5 apparatus 1 obtains the content (S1816).

The playback apparatus 2 descrambles $E(\text{Content}, K_s)$ using the scrambling key K_s obtained in Step S1813. As a result, the playback apparatus 2 obtains the content (S1817).

On the other hand, the unauthorized playback apparatus is
10 not able to obtain the scrambling key K_s in Step S1814, and is therefore not able to obtain the content, either (S1818).

In this manner, when it is learned that there is an unauthorized playback apparatus which disguises itself as an authorized playback apparatus, the broadcast apparatus updates the master keys owned by
15 both the key management apparatus and the playback apparatuses, and is therefore able to eliminate the content viewing by the unauthorized playback apparatus.

Also, in this embodiment, since the master keys are updated with use of EMM that are transmitted by broadcast, it takes fewer
20 days to update the master keys than in the case where portable media such as IC cards are used for the transmission. Accordingly, an

authorized user will not suffer a loss of privilege to view desirable contents that may be caused before the portable medium arrives.

Further, the key management apparatus does not need to bear the cost of sending a portable medium to all playback apparatuses that need one, even if an ID and a master key K_m are assigned to each production lot, each model, or each manufacturer, instead of to each playback apparatus.

Second Embodiment

General Structure of the Conditional Access System

FIG. 19 shows the general structure of the conditional access system of the second embodiment.

The conditional access system of the second embodiment comprises a key management apparatus 1901, a manufacturing machine 1902, a playback apparatus 1903, and a broadcast apparatus 1904.

The procedure in which both the key management apparatus 1901 and the playback apparatus 1903 each own the same ID and the same master key K_m and the procedure in which the playback apparatus 1903 obtains a work key K_w are the same as in the first embodiment.

The second embodiment differs from the first embodiment in the method of updating the master key K_m .

In the second embodiment, the master key K_m is updated in

the following manner:

The broadcast apparatus 1904 stores in EMM (i) an ID of the playback apparatus that needs an update of the master key and (ii) trigger information which indicates that the master key needs to be updated, and broadcasts the EMM. Then, the playback apparatus in need of an updated master key realizes that the master key K_m needs to be updated due to the updating information and transmits apparatus information such as its own ID to the key management apparatus 1901. The key management apparatus 1901 transmits to the playback apparatus seed information from which a new master key is to be generated. The playback apparatus updates the master key K_m using the seed information.

Here, since only the key management apparatus and the playback apparatuses of the authorized users store the same algorithms used to generate the new master key K_m 's from the seed information, only the key management apparatus and the playback apparatuses of the authorized users are able to have the same new master keys K_m 's. Accordingly, the conditional access system of the present embodiment is able to eliminate unauthorized viewing of contents by unauthorized users after the master keys are updated.

In the first embodiment, seed information is stored in EMM,

and the EMM get transmitted. The second embodiment is different from the first embodiment in that EMM transmitted stores trigger information that merely initiates the update of the master key, and seed information is transmitted in some other way than in EMM.

5 The following explains in detail a playback apparatus that actualizes such a conditional access system.

Structure of the Playback Apparatus

 The playback apparatus of the second embodiment is different from the playback apparatus of the first embodiment in only the Km
10 updating unit. Thus, only the Km updating unit will be explained, and explanation on other parts of the structure will be omitted.

 FIG. 20 shows the detailed structure of the Km updating unit in the second embodiment.

 The Km updating unit comprises an apparatus information storing
15 unit 2001, an apparatus information transmitting unit 2002, a seed information receiving unit 2003, a Km generating unit 2004, and a Km retaining unit 2005.

 The apparatus information storing unit 2001 stores apparatus
information that is unique to the playback apparatus such as an ID,
20 and inputs the apparatus information to the apparatus information transmitting unit 2002 according to the notification from the updating

information judging unit.

The apparatus information transmitting unit 2002 transmits the apparatus information stored in the apparatus information storing unit 2001 to the key management apparatus as a request signal requesting seed information. In response to the apparatus information having been received, the key management apparatus transmits seed information in return.

The seed information receiving unit 2003 receives the seed information and inputs the seed information to the Km generating unit 2004 as an argument in the algorithm used for generating a master key. Here, the apparatus information and the seed information are transferred via a telephone line.

The Km generating unit 2004 generates a new master key Km' using the algorithm having been assembled into the Km generating unit 2004 itself. The algorithm is unique to each playback apparatus, each production lot, each model, or each manufacturer. The same algorithm is also stored in the key management apparatus.

The Km retaining unit 2005 retains the master key Km.

In this embodiment again, there are two possibilities as will be mentioned below depending on at which point of time a new master key is generated, and it could be either way.

The first possibility is that a new master key is generated as soon as the seed information is obtained.

The second possibility is that the seed information is obtained and stored till it is necessary to generate a new master key. In this case, a new master key may be generated, for example, after EMM are inputted to the EMM decrypting unit, and then a signal transmitted from the EMM decrypting unit is received.

FIG. 21 shows the data structure of EMM for updating a master key Km.

In this embodiment, an identifier is stored in the data segment, and this identifier itself is trigger information.

Structure of Key Management Apparatus

FIG. 22 shows the structure of the key management apparatus in the conditional access system.

The key management apparatus 2201 comprises an EMM receiving unit 2202, a key-updating judging unit 2203, a seed information generating unit 2204, a Km updating unit 2205, an ID/Km storing unit 2206, an EMM encrypting unit 2207, an encrypted EMM transmitting unit 2208, apparatus information receiving unit 2209 and seed information transmitting unit 2210.

The key management apparatus in the second embodiment is

different from the one in the first embodiment in the seed information generating unit 2204, the apparatus information receiving unit 2209, and the seed information transmitting unit 2210. Thus, only these different parts of the structure will be explained, and explanation
5 on the same structure will be omitted.

The seed information generating unit 2204 receives notification from the key-updating judging unit 2203, generates seed information, and inputs the seed information to the Km updating unit 2205 as well as to the seed information transmitting unit 2210. The
10 seed information is information from which a new master key is to be generated, and could be, for example, a generation number of the master key Km or random numbers.

The apparatus information receiving unit 2209 receives apparatus information such as an ID from a playback apparatus, and
15 identifies the particular playback apparatus that has transmitted this apparatus information.

The seed information transmitting unit 2210 transmits the seed information to the playback apparatus identified by the apparatus information receiving unit 2209.

20 This way, the key management apparatus in this embodiment transmits the seed information according to the request for seed

information made by the playback apparatus. The playback apparatus realizes that the master key needs to be updated due to the trigger information included in the EMM, and transmits a request for seed information to the key management apparatus.

5 Accordingly, the playback apparatus and the key management apparatus each obtain the same seed information, and each of them will generate a new master key from the seed information with use of the same algorithm.

 In this embodiment, the playback apparatus needs to communicate
10 with the key management apparatus when updating the master key; therefore, the key management apparatus is able to identify a playback apparatus from which an unauthorized playback apparatus has derived.

 For example, if it has been arranged so that playback
 apparatuses need to transmit their own IDs as a requesting signal
15 and there is an unauthorized playback apparatus, then the same ID will be transmitted to the key management apparatus more than once. This way, the key management apparatus is able to judge that the playback apparatus having this particular ID is the one from which the unauthorized playback apparatus has derived.

20 It should be noted that the apparatus information and the seed information are transmitted via a telephone line in this

embodiment; however, the transmission is not limited to this and they could be transmitted off line. The seed information may be also transmitted with use of EMM.

Third Embodiment

5 General Structure of the Conditional Access System

FIG. 23 shows the general structure of the conditional access system of the third embodiment.

The conditional access system of the third embodiment comprises, a key management apparatus 2301, a manufacturing machine 2302, a
10 playback apparatus 2303, and a broadcast apparatus 2304.

The procedure in which both the key management apparatus 2301 and the playback apparatus 2303 each own the same ID and the same master key K_m , and the procedure in which the playback apparatus 2303 obtains a work key K_w are the same as in the first embodiment.

15 The third embodiment differs from the first embodiment in the method for updating the master key K_m .

In the third embodiment, the master key K_m is updated in the following manner:

The broadcast apparatus 2304 stores in EMM (i) an ID of the
20 playback apparatus 2303 that needs an update of the master key and (ii) seed information from which a new master key K_m' is to be generated,

and broadcasts the EMM.

The playback apparatus 2303 realizes that the master key needs to be updated due to the seed information, generates event information, and generates a new master key K_m' from both the seed information and the event information. Here, the event information denotes information that has a different value for each update. In this embodiment, random numbers are used as event information.

The playback apparatus 2303 then transmits apparatus information which includes the ID of the playback apparatus 2303 itself and random numbers to the key management apparatus 2301. The key management apparatus 2301 updates the master key using both the seed information and the random numbers.

Here, since only the key management apparatus and the playback apparatus of an authorized user store the same algorithms used to generate new master keys K_m' s from the seed information and the random numbers, only the key management apparatus and the playback apparatus of the authorized user are able to have the same new master keys K_m' s.

Accordingly, the conditional access system of the present embodiment is able to eliminate unauthorized viewing of contents by unauthorized users after the master keys are updated.

The following explains in detail the playback apparatus which

is used to actualize such a conditional access system.

Structure of Playback Apparatus

The playback apparatus of the third embodiment is different from the playback apparatus of the first embodiment in only the Km updating unit. Thus, only the Km updating unit will be explained, and explanation on other parts of the structure will be omitted.

FIG. 24 shows the detailed structure of the Km updating unit in the third embodiment.

The Km updating unit comprises a seed information obtaining unit 2401, an apparatus information generating unit 2402, a Km generating unit 2403, a Km retaining unit 2404, and an apparatus information transmitting unit 2405.

The seed information obtaining unit 2401 obtains seed information from the updating information judging unit and inputs the seed information to the Km generating unit 2403 as an argument in the algorithm used for generating a master key.

The apparatus information generating unit 2402 generates random numbers in response to the notification from the updating information judging unit, combines the random numbers with an ID having already been stored in the apparatus information generating unit 2402 itself, and generates apparatus information unique to the playback

apparatus. The apparatus information gets inputted to both the Km generating unit 2403 and the apparatus information transmitting unit 2405.

The Km generating unit 2403 generates a new master key Km' using an algorithm having been assembled into the Km generating unit 2403 itself. The algorithm is unique to each playback apparatus, each production lot, each model, or each manufacturer. The same algorithm is also stored in the key management apparatus.

The Km retaining unit 2404 retains the master key Km.

The apparatus information transmitting unit 2405 transmits the apparatus information generated by the apparatus information generating unit 2402 to the key management apparatus. Here, the apparatus information is transmitted via a telephone line.

In this embodiment again, there are two possibilities as will be mentioned below depending on at which point of time a new master key is generated, and it could be either way.

The first possibility is that a new master key is generated as soon as the seed information is obtained.

The second possibility is that the seed information is obtained and stored till it is necessary to generate a new master key. In this case, a new master key may be generated, for example, after EMM

are inputted to the EMM decrypting unit, and then a signal transmitted from the EMM decrypting unit is received.

Structure of Key Management Apparatus

FIG. 25 shows the structure of the key management apparatus in the conditional access system.

The key management apparatus in the third embodiment is different from the one in the first embodiment in the apparatus information receiving unit 2505 and the Km updating unit 2506. Accordingly, only the apparatus information receiving unit will be explained, and explanation on other parts of the structure will be omitted.

The apparatus information receiving unit 2505 receives apparatus information from the playback apparatus. The apparatus information is made up of an ID of the playback apparatus and random numbers generated in the playback apparatus. The apparatus information receiving unit 2505 identifies the particular playback apparatus that has transmitted this apparatus information, using the ID included therein.

The Km updating unit 2506 updates the master key using both seed information generated by the seed information generating and inserting unit 2504 and random numbers received by the apparatus

information receiving unit 2505.

The new master key is generated with use of the same algorithm as the one stored in the playback apparatus.

This way, the key management apparatus in the third embodiment
5 stores seed information in EMM and transmits the EMM to the playback apparatus, and receives random numbers from the playback apparatus. The playback apparatus realizes that the master key needs to be updated due to the seed information, and transmits the random numbers that are generated to the key management apparatus.

10 Accordingly, the playback apparatus and the key management apparatus each obtain the same seed information and the same random numbers, and each get to generate a new master key from the seed information and the random numbers with use of the same algorithms.

In this embodiment, the playback apparatus needs to communicate
15 with the key management apparatus when updating the master key; therefore, the key management apparatus is able to identify a playback apparatus from which an unauthorized playback apparatus has derived.

For example, if it has been arranged so that playback
apparatuses need to transmit their own IDs as a requesting signal
20 and there is an unauthorized playback apparatus, then the same ID will be transmitted to the key management apparatus more than once.

This way, the key management apparatus is able to judge that the playback apparatus having this particular ID is the one from which the unauthorized playback apparatus has derived.

It should be noted that the apparatus information is transmitted via a telephone line in this embodiment; however, the transmission is not limited to this and they could be transmitted off line.

In all the embodiments so far, the playback apparatus and the key management apparatus update only the master keys; however it is also acceptable that the IDs are updated as well as the master keys. The master keys and the IDs may be updated by being overwritten, or it may be arranged so that some of the IDs are stored and these stored IDs are valid, or all of the IDs are stored and all these IDs are valid.

In all the embodiments so far, the algorithm used to generate a new master key is managed by the key management apparatus; however, the invention is not limited to this as long as a secure state is provided. For instance, when there are more than one manufacturer and each manufacturer manages algorithms for the playback apparatuses of its own, there is a favorable effect of being able to disperse the risk because the plurality of algorithms are managed separately.

In the first embodiment, the method for updating the master keys is applied only to the playback apparatus in a conditional access system; however, it is also possible to apply the method for updating the master keys to other apparatuses that have keys corresponding to IDs in order to protect various kinds of information, e.g. SD cards and DVD playback apparatuses. The following explains an example in which the updating method is applied to a DVD playback apparatus.

FIG. 26 shows the structure of a DVD apparatus.

The playback apparatus 2601 comprises a reading unit 2602, a type judging unit 2603, a device key storing unit 2604, a media key decrypting unit 2605, an updating information judging unit 2606, a content key decrypting unit 2607, a content descrambling unit 2608, and a content playback unit 2609. The reading unit 2602 reads various kinds of information from a DVD, and the type judging unit 2603 transfers information to different destinations depending on what type of information it is.

The media key decrypting unit 2605 decrypts the data using a device key stored in the device key storing unit 2604 and inputs it to the updating information judging unit 2606.

The updating information judging unit 2606 inputs the data to the device key updating unit 2610, if the data includes updating

information, and inputs the data to the content key decrypting unit 2607, if the data does not include updating information.

The device key updating unit 2610 generates a new device key using the updating information and updates the device key stored in the device key storing unit 2604.

This way, the playback apparatus 2601 is able to update the device key with use of the updating information judging unit 2606 and the device key updating unit 2610.

Industrial Applicability

The present invention is applicable to a digital tuner used in a conditional access system. With the present invention, master keys are properly updated only in authorized digital tuners, and not in unauthorized digital tuners. Consequently, it is possible to eliminate content viewing by unauthorized digital tuners. In addition, it is easy and inexpensive to update the master keys since the master keys are updated with use of broadcast.

CLAIMS

1. A content playback apparatus comprising:

a storing unit that has a secret key stored therein;

5 a key information decrypting unit operable to (i) obtain encrypted key information that has been encrypted by a first secret-key encrypting method, and (ii) decrypt the encrypted key information into key information using the stored secret key, the key information being either a decryption key used for decrypting a content key or
10 key-updating information used for updating the secret key;

a content playback unit operable to, when the decrypted key information is the decryption key, (i) decrypt an encrypted content key that has been encrypted by a second secret-key encrypting method, using the decryption key, (ii) descramble a scrambled content that
15 has been scrambled by a scramble encrypting method, using the decrypted content key, and (iii) play back the descrambled content; and

an updating unit operable to, when the decrypted key information is the key-updating information, update the secret key according to the key-updating information.

20 2. The content playback apparatus of Claim 1, wherein

the key information has an identifier attached thereto
for identifying the key information as either the decryption key or
the key-updating information, and

the content playback apparatus further comprises

5 a judging unit operable to judge, according to the identifier,
whether the key information is the decryption key or the key-updating
information.

3. The content playback apparatus of Claim 2, wherein

10 the key information is included in EMM, EMM denoting
Entitlement Management Messages, and

the content playback apparatus further comprises

a broadcast receiving unit operable to receive broadcast data
which includes encrypted EMM that have been encrypted with use of
15 the secret key and thereby obtain the encrypted key information, and

the key information decrypting unit obtains the encrypted
key information received by the broadcast receiving unit.

4. The content playback apparatus of Claim 1, wherein

20 the updating unit updates the secret key by generating a new
secret key according to a conversion unique to each content playback

apparatus, each production lot of content playback apparatuses, each model of content playback apparatuses, or each manufacturer of content playback apparatuses.

5 5. The content playback apparatus of Claim 1, wherein
 the key-updating information includes seed information from
 which a new secret key is to be generated, and
 the updating unit updates the secret key by converting the
 seed information into the new secret key.

10 6. The content playback apparatus of Claim 1, wherein
 the key-updating information is trigger information which
 instructs that the secret key should be updated, and
 the updating unit further includes:

15 a transmitting subunit operable to transmit, in
 response to the trigger information, a request signal requesting seed
 information from which a new secret key is to be generated, to a key
 management apparatus that manages one or more secret keys; and

20 a seed information receiving subunit operable to
 receive the seed information transmitted by the key management
 apparatus in response to the request signal, and

the updating unit updates the secret key by converting the received seed information into the new secret key.

7. The content playback apparatus of Claim 1, wherein

5 the key-updating information includes seed information from which a new secret key is to be generated, and

the updating unit further includes

an outputting subunit operable to output event information that is different every time of output or once in every
10 certain number of times of output,

the updating unit updates the secret key by converting the seed information and the event information into the new secret key, and

the content playback apparatus further comprises

15 a transmitting unit operable to transmit the event information outputted by the outputting subunit to a key management apparatus that manages one or more secret keys.

8. The content playback apparatus of Claim 1, wherein

20 the secret key stored in the storing unit is unique to each content playback apparatus, each production lot of content playback

apparatuses, each model of content playback apparatuses, or each manufacturer of content playback apparatuses.

9. The content playback apparatus of Claim 1, further having
5 an ID that is unique to each content playback apparatus, each production lot of content playback apparatuses, each model of content playback apparatuses, or each manufacturer of content playback apparatuses, wherein

the updating unit updates the secret key by converting the
10 ID and seed information into a new secret key, the seed information being information from which the new secret key is to be generated.

10. A content playback method to be used in a content playback apparatus which includes a storing unit that has a secret key stored
15 therein, the content playback method comprising:

a key information decrypting step of (i) obtaining encrypted key information that has been encrypted by a first secret-key encrypting method, and (ii) decrypting the encrypted key information into key information using the stored secret key, the key information
20 being either a decryption key used for decrypting a content key or key-updating information used for updating the secret key;

a content playback step of, when the decrypted key information is the decryption key, (i) decrypting an encrypted content key that has been encrypted by a second secret-key encrypting method, using the decryption key, (ii) descrambling a scrambled content that has been scrambled by a scramble encrypting method, using the decrypted content key, and (iii) playing back the descrambled content; and

an updating step of, when the decrypted key information is the key-updating information, updating the secret key according to the key-updating information.

11. A program that instructs a computer to play back contents, the computer including a storing unit that has a secret key stored therein, the program comprising:

a key information decrypting step of (i) obtaining encrypted key information that has been encrypted by a first secret-key encrypting method, and (ii) decrypting the encrypted key information into key information using the stored secret key, the key information being either a decryption key used for decrypting a content key or key-updating information used for updating the secret key;

a content playback step of, when the decrypted key information

is the decryption key, (i) decrypting an encrypted content key that has been encrypted by a second secret-key encrypting method, using the decryption key, (ii) descrambling a scrambled content that has been scrambled by a scramble encrypting method, using the decrypted content key, and (iii) playing back the descrambled content; and

an updating step of, when the decrypted key information is the key-updating information, updating the secret key according to the key-updating information.

12. A key management apparatus that manages a secret key used in a secret-key encrypting method, comprising:

a key-updating information generating unit operable to generate key-updating information used for updating the secret key;

a transmitting unit operable to encrypt key information using the secret key and transmit the encrypted key information to a playback apparatus, the key information being either a decryption key for playing back contents or the key-updating information; and

a secret key updating unit operable to update the secret key according to the key-updating information.

13. The key management apparatus of Claim 12, wherein

the transmitting unit attaches, to the key information, an identifier for identifying the key information as either the decryption key or the key-updating information, before transmitting the key information.

5

14. The key management apparatus of Claim 13, wherein the key information is included in EMM, EMM denoting Entitlement Management Messages, and

the transmitting unit transmits the key information to the playback apparatus by broadcast.

10

15. The key management apparatus of Claim 12, wherein the key-updating information includes seed information from which a new secret key is to be generated, and

the secret key updating unit updates the secret key by converting the seed information into the new secret key.

15

16. The key management apparatus of Claim 12, wherein the key-updating information is trigger information which instructs that the secret key should be updated, and the secret key updating unit further includes:

20

a seed information generating subunit operable to generate seed information from which a new secret key is to be generated; and

a transferring subunit operable to receive a request signal transmitted by the playback apparatus that has obtained the trigger information, and transfer the generated seed information to the playback apparatus in response to the request signal, and

the secret key updating unit updates the secret key by converting the seed information into the new secret key.

10

17. The key management apparatus of Claim 12, wherein

the key-updating information includes seed information from which a new secret key is to be generated, and

the secret key updating unit further includes

15

a receiving subunit operable to receive event information transmitted by the playback apparatus that has obtained the seed information, the event information being different every time of transmission or once in every certain number of times of transmission, and

20

the secret key updating unit updates the secret key by converting the seed information and the event information into the

new secret key.

18. A key management system made up of (i) a content playback apparatus and (ii) a key management apparatus that manages one or
5 more secret keys used in a secret-key encrypting method for the content playback apparatus, the key management system comprising:

a key-updating information generating unit that is included in the key management apparatus and is operable to generate key-updating information used for updating each secret key;

10 a transmitting unit operable to encrypt key information using a first secret key, and transmit the encrypted key information to the content playback apparatus, the key information being either a decryption key for playing back contents or the key-updating information;

15 a key information decrypting unit that is included in the content playback apparatus and is operable to obtain the encrypted key information transmitted by the transmitting unit and decrypt the encrypted key information into key information using a second secret key, the second secret key being stored in the content playback
20 apparatus;

a first updating unit that is included in the key management

apparatus and is operable to update the first secret key according to the key-updating information; and

a second updating unit that is included in the content playback apparatus and is operable to, when the decrypted key information is key-updating information used for updating the second secret key,
5 update the second secret key according to the key-updating information.