



(51) International Patent Classification:  
*A43B 7/12* (2006.01) *A43B 7/06* (2006.01)

(21) International Application Number:  
PCT/EP2010/061355

(22) International Filing Date:  
4 August 2010 (04.08.2010)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:  
09425336.6 28 August 2009 (28.08.2009) EP

(71) Applicant (for all designated States except US): **GEOX S.P.A.** [IT/IT]; Via Feltrina Centro, 16, I-31044 MONTEBELLUNA, Località Biadene - (Treviso) (IT).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **POLEGATO MORETTI, Mario** [IT/IT]; Via Fantin, 96, I-31035 Crocetta Del Montello (IT).

(74) Agent: **MODIANO, Micaela**; Modiano & Partners, Via Meravigli, 16, I-20123 Milano (IT).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM,


AO, AT, AU, AZ, BA, BB, BG, BH, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PE, PG, PH, PL, PT, RO, RS, RU, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

- with international search report (Art. 21(3))
- with amended claims (Art. 19(1))

(54) Title: INSERT FOR VAPOR-PERMEABLE AND WATERPROOF SOLES



(57) Abstract: An insert for vapor-permeable and waterproof soles, which has a monolithic sheet-like structure, made of a polymeric material that is impermeable to water in the liquid state and permeable to water vapor. At least one functional portion of the insert for soles (10) has such a thickness as to give it a penetration resistance of more than approximately 10 N, assessed according to the method presented in chapter 5.8.2 of the ISO 20344-2004 standard.