



(51) International Patent Classification:

F28F 21/08 (2006.01) C22C 21/10 (2006.01)
C22C 21/00 (2006.01) F28D 1/04 (2006.01)
C22C 21/06 (2006.01)

(21) International Application Number:

PCT/US2013/036324

(22) International Filing Date:

12 April 2013 (12.04.2013)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

61/623,386 12 April 2012 (12.04.2012) US

(71) Applicant: CARRIER CORPORATION [US/US]; 1
Carrier Place, Farmington, Connecticut 06034 (US).

(72) Inventors: HUANG, Ruoshuang; One Carrier Place,
Farmington, Connecticut 06034 (US). LOMBARDO,
Mary Teresa; One Carrier Place, Farmington, Connecticut
06034 (US).

(74) Agent: MARSHALL, Paul L.; Cantor Colburn LLP, 20
Church Street, 22nd Floor, Hartford, Connecticut 06103
(US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY,
BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM,
DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT,
HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP,
KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD,
ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI,
NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU,
RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ,
TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA,
ZM, ZW.


(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ,
UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ,
TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK,
EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV,
MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM,
TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW,
ML, MR, NE, SN, TD, TG).

Declarations under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a
patent (Rule 4.17(ii))

[Continued on next page]

(54) Title: ALUMINUM ALLOY TUBE-FIN HEAT EXCHANGER



(57) Abstract: A heat exchanger includes a tube comprising a first aluminum alloy; and a plurality of fins in thermally conductive contact with the exterior of the tube, the fins including a second aluminum alloy such as AA1100, AA8006, and AA8011 and zinc or magnesium in an amount sufficient to provide the second aluminum alloy with an electrochemical solution potential of at least 10 mV more negative than the electrochemical solution potential of the first aluminum alloy.



-
- *as to the applicant's entitlement to claim the priority of the earlier application (Rule 4.17(iii))* — *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*
- *of inventorship (Rule 4.17(iv))*

Published:

(88) Date of publication of the international search report:

12 December 2013

- *with international search report (Art. 21(3))*