

Description

The invention relates to an apparatus and a process for the catalytic conversion of a hydrocarbon feed material to a hydrocarbon product material having smaller molecules in the presence of a catalytic composition of matter.

An apparatus for the continuous cracking of hydrocarbons in a thermal manner is disclosed in U.S. Patent 3,215,505, wherein an upflow regenerator acts to recondition heat transfer particles, such as sand in an elongated pneumatic elevator for passage, after separation, with vapors into a thermal cracking reactor. The inlet channel for the heat carrier material discharges into the top of a pyrolytic reactor having an internal baffle structure to overcome problems of gas bubbles propelling the heat transfer material in an upward direction.

Another apparatus for the conversion of liquid hydrocarbons in the presence of a solid material, which may be a catalyst, is disclosed in U.S. Patent 2,458,162. In Figure 2, a downflow reactor is exemplified with solid particles derived from a dense phase surmounted bed in contact with a liquid charge entered approximately mid-way in the converter column after a control acts on the amount of catalytic material admitted to the converter unit. The amount of descending catalyst is controlled to provide an adequate level of a relatively dense phase of catalyst in the bottom of the reactor. The spent catalyst is reconverted to fresh catalyst in a catalyst reconditioner and then charged to the dense phase catalyst hopper surmounting the converter via a conveyor.

U.S. patents 2,420,632 and 2,411,603 demonstrate the use of a reaction zone having a serpentine flow pattern defined by intermittent baffle sections.

A downflow catalytic cracking reactor in communication with an upflow regenerator is disclosed in U.S. patent 4,514,285. The reactor discharges the reactant products and catalysts from the reaction zone axially downward directly into the upper portion of an unobstructed ballistic separation zone having a cross sectional area within the range of 20 to 30 times the cross sectional area of the reaction zone. While there will be less coke formed during this type of downflow reaction wherein the catalyst moves with the aid of gravity, coke will still be formed in relatively large quantities. To permit this type of discharge into an unobstructed zone from the bottom of the downflow reactor invites serious "after cracking" pursuant to the extended contact time of the catalyst with the hydrocarbon material.

In U.S. Patent 3,835,029, a downflow concurrent catalytic cracking operation is disclosed having increased yield by introducing vaporous hydrocarbon feed into downflow contact with a zeolite-type catalyst and steam for a period of time of 0.2 to 5 seconds. A conventional stripper and separator receive the catalyst and hydrocarbon products and require an additional vertical-situated cyclone separator to efficiently segregate the vapours from the solid particles.

In EP-A-0,171,330 an apparatus is described which comprises a downflow reactor communicating with a series of two regeneration zones. A primary separation zone receives the catalyst and hydrocarbon products and at least one secondary separation zone is required to obtain a sufficient separation of catalyst and hydrocarbon products.

The present invention concerns an apparatus and process for an integral hydrocarbon catalytic cracking conversion utilizing at least three interrelated vessels inclusive of: (1) an upflow riser regenerator, (2) a downflow hydrocarbon conversion reactor, and (3) a horizontal cyclone separator connecting the bottom (inlet) of the upflow riser regenerator and the bottom (outlet) of the downflow reactor.

The interconnection of the top of the regenerator (outlet) and top of the reactor (inlet) is accomplished by means of a pressure leg seal of a bed of freshly regenerated catalyst to insure that the catalytic hydrocarbon conversion occurs in the downflow reactor at a relatively low pressure drop relative to a riser reactor. In order to establish a viable operation of this integral catalytic conversion system, the catalyst is actually "blown down" by the velocity of the vapour in dispersion with the hydrocarbon reactant feed stream and, if desired, diluent steam. One important advantage of this system is a reduction of 5 to 10 times the amount of catalyst inventory necessary for conversion of the same throughput of hydrocarbonaceous feed stock.

The present invention, therefore, relates to an integral hydrocarbon catalytic cracking conversion apparatus for the catalytic conversion of a hydrocarbon feed material to a hydrocarbon product material having smaller molecules which comprises:

a) a substantially vertically extending catalytic downflow reactor having a top and bottom portion comprising a hydrocarbon feed inlet at a position juxtaposed to the top portion of the downflow reactor, a regenerated catalyst inlet at a position juxtaposed to the top portion of the downflow reactor and a product and spent catalyst withdrawal outlet at a position juxtaposed to the bottom portion of the downflow reactor;

b) a substantially vertically extending upflow catalytic riser regenerator having a top and bottom portion for regeneration of spent catalyst passed from the catalytic downflow reactor having a spent catalyst inlet at a position juxtaposed to the bottom portion of the regenerator, a regeneration gas inlet means for entry of an oxygen-containing gas at a position juxtaposed to the bottom portion of the regenerator and a regenerated catalyst and vapour phase outlet at a position juxtaposed to the top portion of the regenerator, the outlet having a means suitable to remove regenerated catalyst and vapours

resultant from the oxidation of coke, present on the spent catalyst, with the oxygen-containing regeneration gas;

c) a horizontal cyclonic separation means for separating spent catalyst from hydrocarbon product material, the horizontal cyclone separation means being in communication with the bottom portion of the catalytic downflow reactor and the bottom part of the riser regenerator;

d) a connection separation means communicating with the top of the upflow riser regenerator and the top of the catalytic downflow reactor to separate regenerated catalyst, derived from the upflow riser regenerator, from spent oxidation gases; wherein said horizontal cyclone separation means interconnects the respective bottoms of the downflow reactor and the upflow riser regenerator, the connection separation means provides a relatively dense phase of catalyst intermediate the top of the upflow regenerator and the top of the catalytic downflow reactor, and the apparatus further comprises:

e) a pressure reduction means for obtaining of a higher pressure in the relatively dense phase above the pressure reduction means than the pressure in the top portion of the catalytic downflow reactor.

The horizontal separation means suitably comprises:

i) a horizontal substantially cylindrical vessel having a body comprising a top having an aperture to the catalytic downflow reactor, a first imperforate end wall, a bottom and a perforate second end wall for penetration of a hydrocarbon product outlet withdrawal conduit, wherein the aperture is located off center with respect to the longitudinal axis of the top of the cylindrical vessel in horizontal direction, the aperture is sufficient to provide passage of an admixture of spent catalyst and hydrocarbon products in a downward direction into the vessel;

ii) a downcomer in the form of a relatively vertically extending conduit interconnecting the vessel bottom at a place relatively opposite to the aperture in the top of the vessel for passage downward through the downcomer of a relatively minor amount of spent catalyst;

iii) a hydrocarbon product withdrawal conduit situated in the, perforate second end wall of the vessel, in vertical direction below the aperture and in horizontal direction towards the aperture, for the continuous removal of the hydrocarbon product after a secondary centrifugal separation from spent catalyst;

iv) an inclined slot solid dropout means interconnecting the bottom of the vessel at a position at least 90° separated from the catalytic downflow reactor point of communication with the top of the vessel as measured by the angle around the circumference of the vessel where 360° equal one complete revolution around the circumference, the dropout means receiving spent catalyst by primary mass separation of spent catalysts from the hydrocarbon product by centrifugal acceleration of spent catalyst about the angle of at least 90 degrees in the horizontal vessel, wherein spent catalyst is accelerated against the surface of the cylindrical vessel to cause primary mass flow separation and to thereby pass the majority of spent catalyst through the inclined solid dropout means to the downcomer;

v) wherein the diameter of the hydrocarbon product withdrawal conduit is smaller than the diameter of the horizontal vessel and the off center ingress of said admixture of the hydrocarbon product and spent catalyst develops during operation a swirl ratio of greater than 0.2 defined by the tangential velocity of the hydrocarbon product across the cross section of the catalytic downflow reactor divided by the superficial axial velocity of the fluid through the cross section of the hydrocarbon product withdrawal conduit to produce a vortex of the hydrocarbon product with entrained minor quantities of spent catalyst in a helical path extending from the imperforate wall opposite the hydrocarbon product withdrawal conduit to cause the secondary centrifugal separation and disengagement of the minor amount of the entrained spent catalyst from the helical hydrocarbon product and thereby passage of the disengaged minor amount of the disentrained spent catalyst to the point of interconnection of the vessel with the downcomer to pass the disengaged and separated spent catalyst through the downcomer to a stripping zone; and

vi) a stripping zone communicating with the downcomer and the bottom portion of the upflow riser regenerator, the stripping zone comprising during operation a dense bed of spent catalyst received from both 1) the primary mass flow separation via the inclined slot solid dropout means and 2) the secondary centrifugal separation via the downcomer, wherein during operation stripping gas is passed to the stripping zone by means of a stripping gas inlet means and wherein the helical flow path of the hydrocarbon product material extending from the second end wall to the hydrocarbon product material withdrawal outlet prohibits at least a portion of the stripping gas from passing upward through the downcomer and into the horizontal vessel.

As shown in Figures 1, 2 and 3, hereinafter discussed in more detail, a relatively small low-residence time dense bed of catalyst is situated in a position surmounted with respect to the top of the downflow reactor. This small low-residence time dense bed of catalyst acts to provide a viable leg seal to insure that the pressure above the top of the downflow reactor is higher as compared to the pressure in the downflow reactor itself. This orientation of downflow reactor and dense bed leg seal requires the presence of a special pressure differential means to insure proper dispersion of the reactant hydrocarbon feed material with the passage of the catalyst down the reactor. Various vendors and suppliers for valves that can perform this function include, among others, Kubota American Corporation, Chapman Engineers, Inc. or Tapco International, Inc. These pressure differential valves provide and insure presence of a desired amount of catalyst to achieve the desired hydrocarbon conversion in the downflow reactor. Other means such as a flow restriction pipe may also be used to attain the proper pressure differentials.

The leg seal dense bed of catalyst above the pressure differential means situated atop of the downflow

reactor can be supplied by a horizontal cyclone separator interconnecting the exit of an upflow riser regenerator and the inlet to the downflow hydrocarbon catalytic reactor. This separatory vessel is similar to the after-described horizontal cyclone separator which interconnects the respective bottoms of the downflow reactor and riser regenerator.

In a specific embodiment of this invention, some regeneration may occur or be affirmatively undertaken in the leg seal dense bed of catalyst above the pressure differential means situated atop of the downflow reactor.

The process parameters existent in the downflow reactor are a very low pressure drop, i.e. of near zero, a pressure of from 4 to 5 bar, although 1 to 50 bar is contemplated, a residence time of 0.2 to 5 seconds and a temperature of from 260 to 649°C. The pressure differential existent in the downflow reactor vis-a-vis the pressure in the dense phase leg seal (surmounting the downflow reactor) is more than 34.5 mbar. This will permit and aid in the downflow of all applicable material such as steam, hydrocarbon reactant and catalyst in a well dispersed phase at the near zero pressure drop.

Both the cracking reactor and riser regenerator operate under fast fluidizing conditions which transpire when the entraining velocity of the vapor exceeds the terminal velocity of the mass of the catalyst. The entrainment velocity can be as great as 3—100 times the individual particle terminal velocity because the dense catalyst flows as groups of particles, i.e. streamers. The minimum velocity for fast fluidizing conditions occurs when the entraining velocity of the vapor exceeds the terminal velocity of the mass of catalyst. The minimum velocity for fast fluidization of the catalyst particles is about one meter/sec at typical densities.

The pressure drop through a fast fluidized system increases with the velocity head ($\frac{1}{2} \rho V_{\text{a}}^2$) whereas the pressure drop through a fluidized bed is relatively constant with respect to the velocity head or flow rate.

Small scale mixing in fast fluidized systems is very efficient because of the turbulence of the flow, however large scale backmixing is much less than in a fluidized bed. The riser regenerator can burn to lower carbon on catalyst with less air consumption than a fluidized bed. In fact, fluidized bed reaction rates are only about 10% of the theoretical burning rate whereas risers could achieve nearly 100%. High efficiencies of that type are required in order to succeed in a riser regenerator.

The downflow reactor is also fast-fluidized despite its downward orientation. The vapor velocity (magnitude) exceeds the catalyst terminal velocity. The vapor entrains the solids down the reactor as opposed to having the solids fall freely. The bottom of the downflow reactor must be minimally obstructed to provide rapid separation of reacted vapor and to prevent backup of solids. This is accomplished by discharging directly into the unique horizontal cyclone separator hereinafter described. The catalyst holdup in the downflow reactor is expected to be about half of that of the holdup in a riser reactor with typical vapor velocities. This is largely due to fast fluidized (turbulent entrainment) conditions. The catalyst contact time becomes one third to one half as long; subsequent regeneration is therefore much easier in this system.

The hydrocarbon feed material can be added to the downflow reactor at a point juxtaposed to entry of the regenerated catalysts intermixed with steam through the above discussed pressure differential means. The hydrocarbon feed will usually have a boiling point of between 93 and 427°C and will be charged as a partial vapor and a partial liquid to the upper part of the downflow reactor or in the dense phase of catalyst surmounted thereto. Applicable hydrocarbonaceous reactants which are modified to hydrocarbonaceous products having smaller molecules are those normally derived from natural crude oils and synthetic crude oils. Specific examples of these hydrocarbonaceous reactants are distillates boiling within the vacuum gas oil range, atmospheric distillation underflow distillate, kerosene boiling hydrocarbonaceous material or naphtha. It is also contemplated that asphaltene materials could be utilized as the hydrocarbon reactant although not necessarily with equivalent cracking results in light of the low quantity of hydrogen present therein.

In light of the very rapid deactivation observed in the preferred catalyst of this invention (hereinafter discussed), short contact time between the catalyst particles and the hydrocarbonaceous reactant are actually desired. For this reason, multiple reactant feed entry points may be employed along the downflow reactor to, maximize or minimize the amount of time the active catalyst actually contacts the hydrocarbonaceous reactants. Once the catalyst becomes deactivated, which can happen relatively fast, contact of the catalyst with the hydrocarbonaceous reactant is simply non-productive. The hydrocarbonaceous products, having smaller molecules than the hydrocarbonaceous feed stream reactants, are preferably gasoline used for internal combustion engines or other fuels such as jet fuel, diesel fuel and heating oils.

The downflow reactor interconnects with an upflow riser regenerator; bottom to bottom, top to top. This interconnection is accomplished by a quick separation means, especially in the bottom to bottom interconnection. It is contemplated that this quick separation means in the top to top connection may comprise a horizontal cyclone separator, a vertical cyclone separator, a reverse flow separator, or an elbow separator having an inlet dimension equal to less than four times the diameter or sixteen times the cross section of the reaction zone. The spent catalyst separation time downstream of the downflow reactor bottom, with this unique horizontal cyclone, will be from 0.2 to 2.0 seconds in contrast to the unobstructed separation time of U.S. Patent 4,514,285 of between 8 seconds and 1 minute. It is therefore necessary for

the quick separation means in the bottom to bottom connection to comprise at least one horizontal cyclone separator, preferably commensurate with that described herein.

The horizontal cyclone separator communicates preferably with the bottommost portion of the downflow reactor (outlet) and the bottommost portion of the upflow riser regenerator (inlet). This horizontal cyclone separator will have an offset inlet in the bottom of the horizontal cyclone separator to charge spent catalyst and hydrocarbon product to the separator at an angular acceleration substantially greater than gravity to force the spent catalyst against the side walls of the horizontal cyclone separator and thereby separate the same by primary mass separation using angular acceleration and centrifugal force.

The horizontal cyclone separator can be equipped with a vortex stabilizer which acts to form a helical flow of vapors from one end of the cyclone separator to the hydrocarbon product outlet end of the same. This vortex acts as a secondary spent catalyst and hydrocarbon product phase separation means to eliminate any entrained spent catalyst from the hydrocarbon product material. The horizontal cyclone separator is equipped with a special solid slot dropout means which interconnects the bottom portion of the horizontal cyclone separator juxtaposed to the inlet of the spent catalyst and hydrocarbon product (gasiform phase) and a downcomer, which itself interconnects the opposite extreme of the horizontal cyclone separator. With this preferred embodiment, spent catalyst is very quickly separated from the hydrocarbonaceous material and thereby after-cracking or excessive coke formation is eliminated or at least mitigated. This horizontal cyclone separator in functional operation with the downflow reactor and the riser regenerator results in a process with more flexibility and better coke formation handling than was previously recognized, especially in the aforementioned U.S. Patent 4,514,285. It is preferred, however, that a stripping zone interconnect the bottom of the horizontal cyclone separator and the bottom of the riser regenerator. In the stripping zone, a stripping medium, most preferably steam or a flue gas, is closely contacted with the catalytic composition of matter having deactivating coke deposited thereon to an extent of from 0.1% by weight carbon to 5.0% by weight carbon to remove adsorbed and interstitial hydrocarbonaceous material from the spent catalyst. The stripping vessel may take the form of a conventional vertical stripping vessel having a dense phase of spent catalyst in the bottom thereof, or the stripping vessel may be a horizontal stripping vessel having a dip leg funneling catalyst to a holding chamber composed almost entirely of the dense phase of spent catalysts and unoccupied space. The stripping vessel, regardless of which configuration is used, is normally maintained at about the same temperature as the downflow reactor, usually in a range of from 427 to 649°C. The preferred stripping gas, usually steam or nitrogen, is introduced at a pressure usually in the range of 0.7 to 2.4 bar in sufficient quantities to effect substantially complete removal of volatile components from the spent catalyst. The downflow side of the stripping zone interconnects with a moveable valve means communicating with the upflow riser regenerator system.

The riser regenerator can comprise many configurations to regenerate the spent catalyst to activity levels of nearly fresh catalyst. The principle idea for the riser regenerator is to operate in a dense, fast fluidized mode over the entire length of the regenerator. In order to initiate coke combustion at the bottom of the riser regenerator the temperature must be elevated with respect to the temperature of the stripped spent catalyst charged to the bottom of the riser regenerator. Several means of elevating this temperature involve back mixing actual heat of combustion (i.e., coke to CO oxidation) to the bottom of the riser regenerator. These means include the presence of a dense bed of catalyst, recycle of regenerated catalyst, countercurrent flow of heat transfer agents and an enlarged back mixing section. For example, a dense bed of catalyst may be situated near the bottom of the regenerator but should preferably be minimized to reduce catalyst inventory. Advantages derivative of such a reduction in inventory are capital cost savings, catalyst deactivation mitigation and a reduction in catalyst attrition. Where backmixing of the catalyst occurs the temperature in the bottom of the riser regenerator will increase to a point around the combustion take off temperature, i.e. where the carbon rate is limited by mass transfer and not oxidation kinetics. This raise in temperature may be 55.6—166.7°C higher than the indigenous temperature of the incoming stripped spent catalyst. This backmixing section may be referred to as a dense recirculating zone which is necessary for said temperature rise.

In one embodiment of this invention, the upflow riser regenerator comprises a riser regenerator having a dense phase of spent and regenerating catalyst (first dense bed) in the bottom thereof and a dilute phase of catalyst thereabove entering into a second separator, preferably a horizontal cyclone stripper. Spent, but stripped, catalyst from the stripping zone is charged to the bottom of the riser regenerator, which may have present therein a dense bed of catalyst to achieve the temperature of the carbon burning rate. And when such a dense bed of catalyst is used its inventory should be minimized compared to conventional riser regenerators. If desired, a recycle means can be provided, with or without cyclone separators, to recycle regenerated catalyst back to the dense bed of catalyst either internally or externally of the regenerator to attain the carbon burning rate temperature. This quantity of recycled regenerated catalyst can best be regulated by surveying a temperature within the dense phase of the riser regenerator and modifying the quantity of recycle catalyst accordingly. It is also within the scope of this invention that the catalyst recycle itself possess a fluidizing means therein for fluidizing the regenerated recycled catalyst. The extent of fluidization in the recycle conduit can be effected in response to a temperature in the regenerator system to better control the temperature in the dense phase of catalyst in the bottom of the riser regenerator.

The dense phase of the catalyst in the regenerator is fluidized via a fluidizing gas useful for oxidizing

the coke contained on the spent catalyst to carbon monoxide and then to carbon dioxide, which is eventually removed from the process or utilized to generate power in a power recovery system downstream of the riser regenerator. The most preferred fluidizing gas is air which is preferably present in a slight stoichiometric excess (based on oxygen) necessary to undertake coke oxidation. The excess oxygen may vary from .1 to 25%, of that theoretically necessary for the coke oxidation in order to acquire the most active catalyst via regeneration.

Temperature control in an FCC unit is a prime consideration and therefore temperature in the regenerator must be closely monitored. The technical obstacles to an upflow riser regenerator are low inlet temperature and low residence time. In order to mitigate these difficulties a refiner may wish to adopt one of three not mutually exclusive pathways. First, heat transfer pellets may be dropped down through the riser to backmix heat, increase catalyst holdup time, or maximize mass transfer coefficients. Proper pneumatic elevation means can be used to circulate the pellets from the bottom of the riser to the top of the riser if it is desired to recirculate the pellets. Second, regenerated catalyst can be recirculated back to the bottom of the riser to backmix the heat. Third, an expansion section can be installed at the bottom of the riser to backmix heat in the entry zone of the riser regenerator.

The catalyst undergoes regeneration in the riser and can be nearly fully regenerated in the dense phase of catalyst. The reaction conditions established (if necessary by the initial burning of torch oil) and maintained in the riser regenerator is a temperature in the range of from 621 to 768 °C and a pressure in the range of from 0.35 to 3.5 bar. If desired, a secondary oxygen containing gas can be added to the dilute phase at a point downstream of the dense bed of catalyst. It is most preferable to add this secondary source of oxidation gas at a point immediately above the dense phase of catalyst if one exists in the bottom of the regenerator. It may also be desirable to incorporate a combustion promoter in order to more closely regulate the temperature and reduce the amount of coke on the catalyst. U.S. Patents 4,341,623 and 4,341,660 represent a description of contemplated regeneration combustion promoters, all of the teachings of which are herein incorporated by reference.

In the embodiment where the riser regenerator is maintained with a dense bed of catalyst in the bottom, the regenerating catalyst exits the dense phase and is then passed to a dilute phase zone which is maintained at a temperature in the range of from 649 to 815°C. Again, there must always be struck a relationship of temperature in the regeneration zone necessary to supply hot regenerated catalysts to the reaction zone to minimize heat consumption in the overall process. It is imperative to recognize that the catalyst inventory is going to be greatly reduced vis-a-vis a standard upflow riser reactor and thus a more precise balance of the temperatures in the downflow reactor and upflow regenerator can be struck and maintained. It is also contemplated that the riser regenerator can have a dilute phase of catalyst passed into a disengagement chamber, wherein a second dense bed of catalyst in the regenerator is maintained in the bottom for accumulation and passage through a regenerated catalyst recycle means to the dense phase bed of catalyst in the bottom of the riser regenerator.

It is also contemplated within the scope of this invention that chosen known solid particle heat transfer materials, such as spherical metal balls, phase change materials, heat exchange pellets or other low coke-like solids, be interspersed with the catalyst. In this preferred embodiment, the heat sink particles act to maintain elevated temperatures at the bottom of the regenerator riser and are generically inert to the actual function of the catalyst and desired conversion of the hydrocarbonaceous reactant materials. Notwithstanding the presence of the heat transfer materials, it is preferred that the quantity of carbon on the regenerated catalyst be held to less than .5 wt% and preferably less than .02 wt% coke.

The catalyst employed in this invention comprises catalytically active crystalline aluminosilicates having initially high activity relative to conversion of the hydrocarbonaceous material. A preferred catalyst comprises a zeolite dispersed in an alumina matrix. It is also contemplated that a silica-alumina composition of matter be utilized. Other refractory metal oxides such as magnesium or zirconium may also be employed but are usually not as efficient as the silica-alumina catalyst. Suitable molecular sieves may also be employed, with or without incorporation to an alumina matrix, such as faujasite, chabazite, X-type and Y-type aluminosilicate materials, and ultra stable large pore crystalline aluminosilicate materials, such as a ZSM-5 or a ZSM-8 catalyst. The metal ions of these materials should be exchanged for ammonium or hydrogen prior to use. It is preferred that only a very small quantity, if any at all, of the alkali or alkaline earth metals be present.

In an overall view of the instant process, the riser regenerator will be longer than the downflow catalytic reactor. The reason for this size variation in this configuration resides in the rapid loss of catalyst activity in the downflow reactor. It is preferred that the downflow catalytic reactor be not more than one half the length of the riser regenerator.

The invention further relates to a process for the continuous cracking of a hydrocarbonaceous feed material to a hydrocarbonaceous product material having smaller molecules in a downflow catalytic reactor which comprises:

a) passing the hydrocarbonaceous feed material into the top portion of a substantially vertically extending downflow reactor in the presence of a catalytic cracking composition of matter at a temperature of from 260 to 815°C, a pressure of from 1 bar to 50 bars and a pressure drop of near zero to crack the molecules of the hydrocarbonaceous feed material to smaller molecules during a residence time of from about 0.2 sec to 5 sec. while the hydrocarbonaceous feed material flows in a downward direction towards

the outlet of the reactor;

b) withdrawing a hydrocarbonaceous product material and spent catalyst having coke deposited thereon from the outlet of the reactor after the above-mentioned residence time and discharging them directly into an horizontal cyclone separator;

5 c) separating the hydrocarbonaceous product material from spent catalyst in said horizontal cyclone separator and withdrawing the hydrocarbonaceous product material from the process as product material;

d) passing spent catalyst with coke deposited thereon to a riser upflow regenerator in addition to added regeneration gas comprising an oxygen-containing gas;

10 e) raising the temperature in the bottom of the regenerator by a temperature elevation means to arrive at the carbon burning rate and maintaining in the riser regenerator a relatively dense fast fluidizing bed of regenerating catalyst over nearly the entire length of the upflow riser regenerator to produce regenerated catalyst and a spent regeneration gas vapour phase;

f) passing the regenerated catalyst and a vapour phase formed from the oxidation of the coke in the presence of the oxygen-containing gas to a centrifugal separator;

15 g) separating the regenerated catalyst from the vapour phase in the horizontal cyclone separator and withdrawing the vapour phase from the process;

h) passing the separated regenerated catalyst from the centrifugal separator to a dense bed of catalyst maintained at a temperature of from 537 to 982°C, and a pressure of from 1 bar to 50 bars wherein said catalyst resides in said dense bed for a residence time of from 2 sec to 600 sec; and

20 i) passing regenerated catalyst from the dense bed to the top portion of the downflow reactor for contact with the hydrocarbonaceous feed material entering the top portion of the downflow reactor, wherein the pressure in the dense bed of catalyst is at least 34.5 mbar greater than the pressure in the downflow reactor, and wherein spent catalyst with coke deposited thereon from the horizontal cyclone separator is stripped and subsequently directly passed without any other regeneration zone to the upflow

25 regenerator.
The relatively dense fast fluidizing bed of regenerating catalyst over nearly the entire length of the upflow riser regenerator may have a temperature of 593 to 982°C and a pressure of from 1 bar to 50 bars (atmospheres), wherein the catalyst resides in the upflow regenerator for a residence time of from 30 sec to 300 sec.

30 Figure 1 is an overall view of the instant process.

Figure 2 is an in depth view of the horizontal cyclone separator interconnecting the riser regenerator and downflow reactor.

Figure 3 is a process flow view of the instant process with preferred embodiments contained therein concerning particulate catalyst recovery.

35 Figure 1 shows downflow reactor 1 in communication with riser regenerator 3 via horizontal cyclone separator 2. Hydrocarbonaceous feed is added to the flow scheme via conduit 5 and control valve 6 at or near the top of downflow reactor 1. It is preferred that this feed be entered through a manifold system (not shown) to disperse completely the feed throughout the top of the downflow reactor for movement downward in the presence of the regenerated catalyst. The feed addition is most preferably made about 2
40 meters below the pressure differential means, here shown as a valve, to permit acceleration and dispersion of the catalyst. The regenerated catalyst is added to downflow reactor 1 through pressure differential valve means 7 to insure that the pressure above the top of downflow reactor 1 (denoted as 8) is higher than the pressure in the downflow reactor (denoted as 10). It is most preferred that this pressure differential be greater than 34.5 mbar in order to have a viable dispersion of the catalyst throughout the downflow reactor
45 during the relatively short residence time.

The temperature conditions in the downflow reactor will most preferably be 427 to 815°C with a pressure of 4 to 5 bar. The downflow reactor should operate at a temperature hotter than the average riser temperature to reduce the quantity of dispersion steam and to thereby make the catalyst to oil ratio higher. As one salient advantage of this invention, the pressure drop throughout the downflow catalytic reactor
50 will be near zero. If desired, steam can be added at a point juxtaposed to the feed stream or most preferably the steam may be added by means of conduit 9 and valve 11 into second dense phase bed of catalyst 12. This second dense bed of catalyst 12 is necessary to insure the proper pressure differential in the downflow reactor. It is preferred that the catalyst reside in this second dense phase bed of catalyst for only as long as it takes to insure a proper leg seal between the above two entities. It is preferred that the residence time in the dip leg be no more than 5 minutes and preferably less than 30 seconds.

55 Downflow reactor 1 communicates with riser regenerator 3 by means of horizontal cyclone separator 2 and stripping zone 14. Spent catalyst and hydrocarbon product material pass from the bottom of downflow reactor 1 into horizontal cyclone 2 at a spot off-center with respect to the horizontal body of the cyclone. The entry of the different solid and fluid phases undergoes angular forces (usually 270°) which separates the phases by primary mass flow separation. The solid particles pass directly to downcomer 15 by means
60 of a solid slot dropout means 16, (not seen from the side view) which can be supported by a fastening and securement means 17. A minor portion of the solid spent catalyst will remain entrained in the hydrocarbonaceous fluid product. The horizontal cyclone 2 is configured such that the tangential velocity of the fluid passing into the vessel (Ui) divided by the axial velocity of fluid passing through product withdrawal conduit 18 (Vi) is greater than 0.2 as defined by:

EP 0 254 333 B1

$$\text{Swirl Ratio} = \frac{U_i}{V_i} = \frac{R_e}{R_i} \times \frac{1}{F}$$

wherein

- 5 Re = radius of the downflow reactor 1;
 Ri = radius of the withdrawal conduit 18; and
 F = the cross section area of the tubular reactor divided by the crosssectional area of the fluid withdrawal conduit.

10 Satisfaction of this relationship develops a helical or swirl flow path of the fluid at 19 in a horizontal axis beginning with an optional vortex stabilizer 20 and continuing through hydrocarbon product outlet 18. This creates disentrainment of the minor portion of the solid spent catalyst which passes to stripper 14 via downcomer 15.

15 Stripper 14 possesses a third dense bed of catalyst 21 (spent) which is immediately contacted with a stripping agent, preferably air or steam, through a stripping gas inlet conduit 22 and control valve 23. After a small residence time in stripper 14 sufficient to excise a portion of the absorbed hydrocarbons from the surface of the catalyst, preferably 10—100 seconds, the spent and stripped catalyst is passed to the first dense phase of catalyst 24 by means of connection conduit 25 and flow control device 26. The third dense phase bed of catalyst 21 will usually have a temperature of 260 to 537°C.

20 The first dense phase bed of catalyst 24 is maintained on a specially sized grate (not shown) to permit the upflow of vapor through the grate and the downflow of spent catalyst from the dense phase of catalyst. A suitable fluidizing agent is an oxygen-containing gas, which is also used for the oxidation of coke on the catalyst to carbon monoxide and carbon dioxide. The oxygen-containing gas is supplied via conduit 29 and distribution manifold 31. It is within the scope of this invention that the amount of fluidizing gas added to
 25 regenerator 3 can be regulated as per the temperature in the combustion zone or the quantity or level of catalyst in first dense bed of catalyst 24. If desired, a regenerated catalyst recycle stream 27 can be provided to recycle regenerated catalyst from the upper portion of the dilute phase of riser regenerator 3 through, conduit 27 containing flow control valve 28, which may also be regulated as per the temperature in the dilute phase of the regeneration zone. This catalyst recycle stream, while shown as being external to the
 30 riser regenerator may also be placed in an internal position to insure that the catalyst being recycled is not overly cooled in its passage to first dense phase catalyst bed 24. It is also contemplated that conduit 27 can intersect conduit 25 and that a "salt and pepper" mixture of regenerated and spent catalyst be concomitantly added to the first dense phase of catalyst 24 through conduit 25.

35 Regenerated catalysts and vapor effluent derivative of the oxidation of the coke with oxygen are passed from a dilute phase of catalyst 33 to a separation means, preferably a horizontal cyclone separator but other equivalent separators such as a vertical cyclone separator can also be used. Again, it is contemplated that more than one cyclonic separator be put in service in a series or parallel flow passage scheme. The upflow of regenerated catalysts is removed from the vapors, which contain usually less than
 40 1000 ppm CO through conduit 41 and can be removed from the process in conduit 43 or passed to a power recovery unit 45 or a carbon monoxide boiler unit (not shown). The cyclonic communication conduit 47 acts to excise the catalyst particles from any unwanted vapors and insure passage of regenerated catalyst to the second dense phase of catalyst 12 which provides the leg seal surmounted to the downflow reactor.

Figure 2 shows in more detail the instant horizontal cyclone separator 2 designed for removal of spent catalyst and hydrocarbon product from the downflow reactor to the stripper and ultimately the first dense
 45 phase of catalyst in the upflow riser regenerator.

Figure 3 demonstrates a more sophisticated apparatus and flow scheme of this invention with downflow reactor 101 and riser regenerator 103 interconnected by means of overhead horizontal cyclone separator 102. The lower portion of riser regenerator 103, is supplied with an oxygen-containing gas by means of conduit 105 and manifold 107. A selectively perforated grate 109 is supplied to maintain the
 50 bottom of the fluidized bed of catalyst. It is possible that no grate is necessary where the dense phase of catalyst is very small, i.e., 2.44 m in diameter. A dense phase of catalyst 111 is maintained at suitable regeneration-affecting conditions, i.e. a temperature of 649 to 815°C, to diminish the coke on the catalyst to .05 wt.% coke or less. Catalyst having undergone regeneration in riser regenerator 103 enter dilute phase 113 having in the bottom thereof the ability to add a combustion promoter by means of conduit 115 and/or
 55 a secondary air supply means of conduit 117. The amount of air is usually regulated so that the oxygen content is more than stoichiometrically sufficient to burn the nefarious coke to carbon monoxide and then convert some or all of same to carbon dioxide. The regenerated catalyst is entrained upwards through the dilute phase maintained at the conditions hereinbefore depicted and will either enter horizontal cyclone separator 102 or will be recycled to the dense phase of regenerating catalyst 111 by means of recycle
 60 conduit 121 and control valve means 123 situated in conduit 121. Again, this recycle stream is shown as being external to the regenerator but could be also internal and contain various process flow control devices such as a level indicator or a temperature sensing and regulating device to regulate temperatures as a function of the conditions existent in dilute phase 113. The combustion products, usually predominantly carbon dioxide, nitrogen, and water exit horizontal cyclone separator 102 through vortex
 65 exhaust conduit 131. The vortex exhaust conduit establishes a helical flow of catalyst 135 across the

horizontal cyclone separator in a direction substantially perpendicular to riser regenerator 103. This helical flow of catalyst preferably totally surrounds flow deflecting conical device 137 for passage of the particulate catalyst in a downward direction to dense phase leg seal 139. Interconnecting conduit 141 may be a further extension of the horizontal cyclone separator or it can simply be a catalyst transfer conduit from same.

5 Feed is added by conduit 145 downstream of pressure reduction valve 147. Steam, if desired, may also be added by means of conduit 149 or 151 or both. Pressure differential valve 147 is existent to insure that no hydrocarbons flow upward through the seal leg of catalyst. In this manner solids, such as the catalyst particles, are blown down by the velocity of the descending vapors, which provide good dispersion of catalyst-hydrocarbon reactant-steam. All three of these entities pass downward in reactor 101 to form the sought after hydrocarbon products. In this embodiment, a second horizontal cyclone separator is provided

10 at the bottom of the downflow reactor 101. Vapors can exit on either side of the downcomer although in this embodiment vapors exit through vortex exhaust conduit 167 connected to conventional vertical cyclone separator 157. In the latter vertical cyclone separator, gases are withdrawn from the process in conduit 159 while solid catalyst extracted from the vapors are passed by means of dip leg 161 to another dense phase of catalyst 163 existent in steam stripping zone 165. The vortex exhaust conduit 167, also

15 creates a second helical flow path of spent catalyst 169 for passage to stripper dense bed 163 via vortex stabilizer 171. It is contemplated that a dense phase of catalyst 163 may also be provided with a dip leg 173 providing catalysts for yet another dense phase of catalyst 175 existent in the bottom of the stripper column. The latter is provided with two sources of steam in conduits 177 and 179. Stripped, yet spent

20 catalysts, is withdrawn from the bottom of stripper unit 165 via conduit 181 and passed to dense phase bed 111 of riser regenerator 103 via slide control valve 183.

The flow of hot vapors is removed from the horizontal cyclone separator 102 in flow conduit 131. The same is then passed to a conventional vertical catalyst cyclone separator 201 having vapor outlet means 203 and catalyst dip leg 205 for passage of recovered regenerated catalyst back to dense phase 111. The

25 vertical separator 201 passes the off gases to a third horizontal cyclone separator 207 similar in configuration to horizontal cyclone separator 102. Again regenerated catalyst is recovered from hot vapors and recycled in recycle conduit 209 to dense phase catalyst bed 111. The off-gases are predominantly free of solid material in conduit 211, are withdrawn from the horizontal cyclone separator 207 and passed to a power recovery means comprising very broadly a turbine 215 to provide the power in electric motor

30 generator 221 to run other parts of the process for other parts of the refinery or to sell to the public in a power cogeneration scheme and is then passed to compressor 213.

Claims

1. An integral hydrocarbon catalytic cracking conversion apparatus for the catalytic conversion of a hydrocarbon feed material to a hydrocarbon product material having smaller molecules which comprises:
 - a) a substantially vertically extending catalytic downflow reactor comprising a hydrocarbon feed inlet at a position juxtaposed to the top portion of the downflow reactor, a regenerated catalyst inlet at a position juxtaposed to the top portion of the downflow reactor and a product and spent catalyst withdrawal outlet at a position juxtaposed to the bottom portion of the downflow reactor;
 - b) a substantially vertically extending upflow catalytic riser regenerator for regeneration of spent catalyst passed from the catalytic downflow reactor having a spent catalyst inlet at a position juxtaposed to the bottom portion of the regenerator, a regeneration gas inlet means for entry of an oxygen-containing gas at a position juxtaposed to the bottom portion of the regenerator and a regenerated catalyst and vapour phase outlet at a position juxtaposed to the top portion of the regenerator, the outlet having a means suitable to remove regenerated catalyst and vapours resultant from the oxidation of coke, present on spent catalyst, with the oxygen-containing regeneration gas;
 - c) a horizontal cyclonic separation means for separating spent catalyst from hydrocarbon product material, said horizontal cyclone separation means being in communication with the bottom portion of the catalytic downflow reactor and the bottom part of the riser regenerator;
 - d) a connection separation means communicating with the top of the upflow riser regenerator and the top of the catalytic downflow reactor to separate regenerated catalyst, derived from the upflow riser regenerator, from spent oxidation gases, characterized in that the horizontal cyclone separation means (2) interconnects the respective bottoms of the downflow reactor and the upflow riser regenerator (3), the connection separation means (47) provides a relatively dense phase of catalyst intermediate the top of the upflow regenerator and the top of the catalytic downflow reactor, and the apparatus further comprises:
 - e) a pressure reduction means (7) for obtention of a higher pressure in the relatively dense phase (12) above the pressure reduction means (7) than the pressure in the top portion of the catalytic downflow reactor.
2. The apparatus of Claim 1 wherein the horizontal separation means (2) comprises.
 - i) a horizontal substantially cylindrical vessel having a body comprising a top having an aperture to the catalytic downflow reactor, a first imperforate end wall, a bottom and a perforate second end wall for penetration of a hydrocarbon product outlet withdrawal conduit (18), wherein said aperture is located off center with respect to the longitudinal axis of the top of the cylindrical vessel in horizontal direction, the aperture being sufficient to provide passage of an admixture of spent catalyst and hydrocarbon products in
 - a downward direction into the vessel;



EP 0 254 333 B1

horizontal cyclone separator in a direction substantially perpendicular to riser regenerator 103. This helical flow of catalyst preferably totally surrounds flow deflecting conical device 137 for passage of the particulate catalyst in a downward direction to dense phase leg seal 139. Interconnecting conduit 141 may be a further extension of the horizontal cyclone separator or it can simply be a catalyst transfer conduit from same.

5 Feed is added by conduit 145 downstream of pressure reduction valve 147. Steam, if desired, may also be added by means of conduit 149 or 151 or both. Pressure differential valve 147 is existent to insure that no hydrocarbons flow upward through the seal leg of catalyst. In this manner solids, such as the catalyst particles, are blown down by the velocity of the descending vapors, which provide good dispersion of catalyst-hydrocarbon reactant-steam. All three of these entities pass downward in reactor 101 to form the

10 sought after hydrocarbon products. In this embodiment, a second horizontal cyclone separator is provided at the bottom of the downflow reactor 101. Vapors can exit on either side of the downcomer although in this embodiment vapors exit through vortex exhaust conduit 167 connected to conventional vertical cyclone separator 157. In the latter vertical cyclone separator, gases are withdrawn from the process in conduit 159 while solid catalyst extracted from the vapors are passed by means of dip leg 161 to another

15 dense phase of catalyst 163 existent in steam stripping zone 165. The vortex exhaust conduit 167, also creates a second helical flow path of spent catalyst 169 for passage to stripper dense bed 163 via vortex stabilizer 171. It is contemplated that a dense phase of catalyst 163 may also be provided with a dip leg 173 providing catalysts for yet another dense phase of catalyst 175 existent in the bottom of the stripper column. The latter is provided with two sources of steam in conduits 177 and 179. Stripped, yet spent

20 catalysts, is withdrawn from the bottom of stripper unit 165 via conduit 181 and passed to dense phase bed 111 of riser regenerator 103 via slide control valve 183.

The flow of hot vapors is removed from the horizontal cyclone separator 102 in flow conduit 131. The same is then passed to a conventional vertical catalyst cyclone separator 201 having vapor outlet means 203 and catalyst dip leg 205 for passage of recovered regenerated catalyst back to dense phase 111. The

25 vertical separator 201 passes the off gases to a third horizontal cyclone separator 207 similar in configuration to horizontal cyclone separator 102. Again regenerated catalyst is recovered from hot vapors and recycled in recycle conduit 209 to dense phase catalyst bed 111. The off-gases are predominantly free of solid material in conduit 211, are withdrawn from the horizontal cyclone separator 207 and passed to a power recovery means comprising very broadly a turbine 215 to provide the power in electric motor generator 221 to run other parts of the process for other parts of the refinery or to sell to the public in a

30 power cogeneration scheme and is then passed to compressor 213.

Claims

1. An integral hydrocarbon catalytic cracking conversion apparatus for the catalytic conversion of a hydrocarbon feed material to a hydrocarbon product material having smaller molecules which comprises:
 - 35 a) a substantially vertically extending catalytic downflow reactor comprising a hydrocarbon feed inlet at a position juxtaposed to the top portion of the downflow reactor, a regenerated catalyst inlet at a position juxtaposed to the top portion of the downflow reactor and a product and spent catalyst withdrawal outlet at a position juxtaposed to the bottom portion of the downflow reactor;
 - 40 b) a substantially vertically extending upflow catalytic riser regenerator for regeneration of spent catalyst passed from the catalytic downflow reactor having a spent catalyst inlet at a position juxtaposed to the bottom portion of the regenerator, a regeneration gas inlet means for entry of an oxygen-containing gas at a position juxtaposed to the bottom portion of the regenerator and a regenerated catalyst and vapour phase outlet at a position juxtaposed to the top portion of the regenerator, the outlet having a
 - 45 means suitable to remove regenerated catalyst and vapours resultant from the oxidation of coke, present on spent catalyst, with the oxygen-containing regeneration gas;
 - c) a horizontal cyclonic separation means for separating spent catalyst from hydrocarbon product material, said horizontal cyclone separation means being in communication with the bottom portion of the catalytic downflow reactor and the bottom part of the riser regenerator;
 - 50 d) a connection separation means communicating with the top of the upflow riser regenerator and the top of the catalytic downflow reactor to separate regenerated catalyst, derived from the upflow riser regenerator, from spent oxidation gases, characterized in that the horizontal cyclone separation means (2) interconnects the respective bottoms of the downflow reactor and the upflow riser regenerator (3), the connection separation means (47) provides a relatively dense phase of catalyst intermediate the top of the
 - 55 upflow regenerator and the top of the catalytic downflow reactor, and the apparatus further comprises:
 - e) a pressure reduction means (7) for obtention of a higher pressure in the relatively dense phase (12) above the pressure reduction means (7) than the pressure in the top portion of the catalytic downflow reactor.
2. The apparatus of Claim 1 wherein the horizontal separation means (2) comprises.
 - 60 i) a horizontal substantially cylindrical vessel having a body comprising a top having an aperture to the catalytic downflow reactor, a first imperforate end wall, a bottom and a perforate second end wall for penetration of a hydrocarbon product outlet withdrawal conduit (18), wherein said aperture is located off center with respect to the longitudinal axis of the top of the cylindrical vessel in horizontal direction, the aperture being sufficient to provide passage of an admixture of spent catalyst and hydrocarbon products in
 - 65 a downward direction into the vessel;



ii) a downcomer (15) in the form of a relatively vertically extending conduit interconnecting the vessel bottom at a place relatively opposite to the aperture in the top of the vessel for passage downward through the downcomer of a relatively minor amount of spent catalyst;

iii) a hydrocarbon product withdrawal conduit (18) situated in the perforate second end wall of the vessel, in vertical direction below the aperture and in horizontal direction towards the aperture, for the continuous removal of the hydrocarbon product after a secondary centrifugal separation from spent catalyst;

iv) an inclined slot solid dropout means (16) interconnecting the bottom of the vessel at a position at least 90° separated from the catalytic downflow reactor point of communication with the top of the vessel as measured by the angle around the circumference of the vessel where 360° equal one complete revolution around the circumference, the dropout means (16) receiving spent catalyst by primary mass separation of spent catalysts from the hydrocarbon product by centrifugal acceleration of spent catalyst about the angle of at least 90° in the horizontal vessel, wherein spent catalyst is accelerated against the surface of the cylindrical vessel to cause primary mass flow separation and to thereby pass the majority of spent catalyst through the inclined solid dropout means (16) to the downcomer (15);

v) wherein the diameter of the hydrocarbon product withdrawal, conduit (18) is smaller than the diameter of the horizontal vessel and the off center ingress of the admixture of the hydrocarbon product and spent catalyst develops during operation a swirl ratio of greater than 0.2 defined by the tangential velocity of the hydrocarbon product across the cross section of the catalytic downflow reactor divided by the superficial axial velocity of the fluid through the cross section of the hydrocarbon product withdrawal conduit to produce a vortex of the hydrocarbon product with entrained minor quantities of spent catalyst in a helical path extending from the imperforate wall opposite the hydrocarbon product withdrawal conduit (18) to cause the secondary centrifugal separation and disengagement of the minor amount of the entrained spent catalyst from the helical hydrocarbon product and thereby passage of the disengaged minor amount of the disentrained spent catalyst to the point of interconnection of the vessel with the downcomer (15) to pass the disengaged and separated spent catalyst through the downcomer (15) to a stripping zone (14); and

vi) a stripping zone (14) communicating with the downcomer (15) and the bottom portion of the upflow riser regenerator, the stripping zone (14) comprising during operation a dense bed of spent catalyst received from both 1) the primary mass flow separation via the inclined slot solid dropout means (16) and 2) the secondary centrifugal separation via the downcomer (15), wherein during operation stripping gas is passed to the stripping zone by means of a stripping gas inlet means (22) and wherein the helical flow path of the hydrocarbon product material extending from the second end wall to the hydrocarbon product material withdrawal outlet (18) prohibits at least a portion of the stripping gas from passing upward through the downcomer (15) and into the horizontal vessel.

3. The apparatus of Claim 1 wherein a uniform bed of regenerating catalyst in the regenerator comprises a first relatively dense bed of catalyst (24) in the bottom portion of the regenerator and a relatively dilute phase of catalyst in the top portion of the regenerator.

4. The apparatus of Claim 1 wherein the hydrocarbon feed inlet (5) is positioned at a point directly below the pressure reduction means (7).

5. The apparatus of Claim 1 wherein the connection separation means (141) communicating with the top of the upflow riser regenerator (3) and the top of catalytic downflow reactor (1) comprises:

i) an inlet means communicating with the top of the upflow riser regenerator (3);

ii) a vortex exhaust tube (131) for separating regenerated catalyst from the spent oxidation gas, wherein the regenerated catalyst is accelerated in a substantially horizontal direction in a helical flow path.

iii) a spent oxidation gas exit means (133) for withdrawal of the spent oxidation gas in the vortex exhaust tube (131);

iv) a conical flow control means (137) comprising a vortex stabilizer located at a position in the separation means opposite the extreme end of placement of the vortex exhaust tube (131) and so situated to provide the helical flow path of the spent oxidation gas encompasses the conical shape of the conical flow control means (137); and

v) an outlet means communicating with the second relatively dense phase of regenerated catalyst to pass regenerated catalyst from the connection separation means (141) to the second relatively dense phase of catalyst (135).

6. The apparatus of Claim 1 wherein the relatively dense phase of regenerated catalyst (139) surmounted to the catalytic downflow reactor possesses a steam inlet means (149), to add steam with the catalyst to the catalytic downflow reactor.

7. A process for the continuous cracking of a hydrocarbonaceous feed material to a hydrocarbonaceous product material having smaller molecules in a downflow catalytic reactor which comprises:

a) passing the hydrocarbonaceous feed material into the top portion of a substantially vertically extending downflow reactor in the presence of a catalytic cracking composition of matter at a temperature of from 260 to 815°C, a pressure of from 1 to 50 bar and a pressure drop of near zero to crack the molecules of the hydrocarbonaceous feed material to smaller molecules during a residence time of from 0.2 sec to 5



sec while the hydrocarbonaceous feed material flows in downward direction towards the outlet of the reactor;

b) withdrawing hydrocarbonaceous product material and spent catalyst having coke deposited thereon from the outlet of the reactor after the above-mentioned residence time and discharging them directly into an horizontal cyclone separator;

c) separating the hydrocarbonaceous product material from spent catalyst in said horizontal cyclone separator and withdrawing the hydrocarbonaceous product material from the process as product material;

d) passing spent catalyst with coke deposited thereon from the horizontal cyclone separator to a riser upflow regenerator in addition to added regeneration gas comprising an oxygen-containing gas;

e) raising the temperature in the bottom of the regenerator by a temperature elevation means to arrive at a carbon burning rate temperature and maintaining in the riser regenerator a relatively dense fast fluidizing bed of regenerating catalyst over the near entire length of the upflow riser regenerator to produce regenerated catalyst and a spent regeneration gas vapour phase;

f) passing the regenerated catalyst and a vapour phase formed from the oxidation of the coke in the presence of the oxygen-containing gas to a centrifugal separator;

g) separating the regenerated catalyst from the vapour phase in the centrifugal separator and withdrawing the vapour phase from the process, characterized in that the process further comprises:

h) passing the separated regenerated catalyst from the centrifugal separator to a dense bed of catalyst maintained at a temperature of from 537 to 982°C, and a pressure of from 1 bar to 50 bars, wherein the catalyst resides in the dense bed for a residence time from 2 sec to 600 sec; and

i) passing regenerated catalyst from the dense bed to the top portion of the downflow reactor for contact with hydrocarbonaceous feed material entering the top portion of the downflow reactor, wherein the pressure in the dense bed of catalyst is more than 34.5 mbar compared with the pressure in the downflow reactor, and wherein spent catalyst with coke deposited thereon from the horizontal cyclone separator is stripped and subsequently directly passed without any other regeneration zone to the riser upflow regenerator.

Patentansprüche

1. Integrale Vorrichtung zur Kohlenwasserstoffumwandlung durch katalytisches Kracken für die katalytische Umwandlung eines Kohlenwasserstoff-Ausgangsmaterials in ein Kohlenwasserstoff-Produktmaterial mit kleineren Molekülen, die aufweist:

a) einen sich im wesentlichen vertikal erstreckenden katalytischen Fallreaktor mit einem Kohlenwasserstoff-Ausgangsmaterialeinlaß an einer Stelle nahe dem Oberteil des Fallreaktors, einem Einlaß für regenerierten Katalysator an einer Stelle nahe dem Oberteil des Fallreaktors und einem Auslaß für den Abzug des Produktes und verbrauchten Katalysator an einer Stelle nahe dem Unterteil des Fallreaktors;

b) einen sich im wesentlichen vertikal erstreckenden katalytischen Steigregenerator zum Regenerieren von verbrauchtem Katalysator, der vom katalytischen Fallreaktor zugeleitet wird, mit einem Einlaß für verbrauchten Katalysator an einer Stelle nahe dem Unterteil des Regenerators, einer Regenerationsgas-Einlaßeinrichtung für den Eintritt eines sauerstoffhaltigen Gases an einer Stelle nahe dem Unterteil des Regenerators und einem Auslaß für regenerierten Katalysator und Dampfphase an einer Stelle nahe dem Oberteil des Regenerators, wobei der Auslaß Mittel aufweist, die zum Entfernen des regenerierten Katalysators und der Dämpfe geeignet sind, welche sich aus der Oxidation von an verbrauchten Katalysator vorhandenen Koks mit dem sauerstoffhaltigen Regenerationsgas ergeben;

c) eine horizontale Zyklonabscheideeinrichtung zum Abscheiden des verbrauchten Katalysators vom Kohlenwasserstoff-Produktmaterial, wobei die horizontale Zyklonabscheideeinrichtung in Verbindung mit dem Unterteil des katalytischen Fallreaktors und dem Unterteil des Steigregenerators steht;

d) eine Anschluß-Abscheideeinrichtung, die mit dem Oberteil des Steigregenerators und dem Oberteil des katalytischen Fallreaktors in Verbindung steht, um regenerierten Katalysator, der aus dem Steigregenerator erhalten wird, von verbrauchten Oxidationsgasen abzuscheiden, dadurch gekennzeichnet, daß die horizontale Zyklonabscheideeinrichtung (2) die entsprechenden Unterteile des Fallreaktors und des Steigregenerators (3) verbindet, wobei die Anschluß-Abscheideeinrichtung (47) eine relativ dichte Phase des Katalysators zwischen dem Oberteil des Steigregenerators und dem Oberteil des katalytischen Fallreaktors bildet, und die Vorrichtung ferner aufweist:

e) Druckreduziermittel (7) zur Erzielung eines höheren Druckes in der relativ dichten Phase (12) oberhalb der Druckreduziermittel (7) im Vergleich zum Druck im Oberteil des katalytischen Fallreaktors.

2. Vorrichtung nach Anspruch 1, bei welcher die horizontale Abscheideeinrichtung (2) umfaßt:

i) ein horizontales, im wesentlichen zylindrisches Gefäß mit einem Körper, der einen Oberteil mit einer Öffnung zum katalytischen Fallreaktor hat, eine erste ungelochte Endwand, einen Unterteil und eine gelochte zweite Endwand für den Durchtritt einer Kohlenwasserstoffprodukt-Auslaßabzugsleitung (18), wobei die Öffnung bezüglich der Längsachse des Oberteiles des zylindrischen Gefäßes in horizontaler Richtung exzentrisch angeordnet ist, und wobei die Öffnung ausreicht, um einen Strom des Gemenges aus verbrauchtem Katalysator und Kohlenwasserstoffprodukten in Richtung nach unten in das Gefäß zu leiten;

ii) ein Fallrohr (15) in Form einer sich relativ vertikal erstreckenden Leitung, welche an den



Gefäßunterteil an einer der Öffnung im Oberteil des Gefäßes relativ gegenüberliegenden Stelle anschließt, um eine relativ kleine Menge des verbrauchten Katalysators nach unten zur Strömung durch das Fallrohr zu leiten;

iii) eine Kohlenwasserstoffprodukt-Abzugsleitung (18), die in der gelochten zweiten Endwand des Gefäßes angeordnet ist, in vertikaler Richtung unterhalb der Öffnung und in horizontaler Richtung gegen die Öffnung zu, zum kontinuierlichen Abziehen des Kohlenwasserstoffproduktes nach einer Sekundärzentrifugalabscheidung vom verbrauchten Katalysator;

iv) eine geneigte schlitzförmige Feststoffausfalleinrichtung (16), welche an den Unterteil des Gefäßes an einer Stelle anschließt, die um zumindest 90° vom Anschlußpunkt des katalytischen Fallreaktors an den Oberteil des Gefäßes getrennt ist, gemessen in einem Winkel um den Umfang des Gefäßes, wobei 360° einen vollständigen Umlauf um den Umfang darstellen, wobei die Ausfalleinrichtung (16) verbrauchten Katalysator durch die Hauptmassenabscheidung des verbrauchten Katalysators vom Kohlenwasserstoffprodukt durch Zentrifugalbeschleunigung des verbrauchten Katalysators über den Winkel von zumindest 90° im horizontalen Gefäß erhält, wobei verbrauchter Katalysator gegen die Fläche des zylindrischen Gefäßes beschleunigt wird, um eine Hauptmassenstromabscheidung zu bewirken und dadurch den Hauptteil des verbrauchten Katalysators durch die geneigte-Feststoffausfalleinrichtung (16) in das Fallrohr (15) zu leiten;

v) wobei der Durchmesser der Kohlenwasserstoff-Produkt-Abzugsleitung (18) kleiner als der Durchmesser des horizontalen Gefäßes ist und der exzentrische Einlaß für das Gemenge aus Kohlenwasserstoffprodukt und verbrauchtem Katalysator während des Betriebes ein Verwirbelungsverhältnis von größer als 0,2 entwickelt, definiert durch die Tangentialgeschwindigkeit des Kohlenwasserstoffproduktes über den Querschnitt des katalytischen Fallreaktors dividiert durch die Oberflächen-Axialgeschwindigkeit des Fluids durch den Querschnitt der Kohlenwasserstoffprodukt-Abzugsleitung, um einen Wirbel des Kohlenwasserstoffproduktes mit mitgerissenen kleineren Mengen an verbrauchtem Katalysator auf einem wendelförmigen Weg zu erzeugen, der sich von der ungelochten Wand gegenüber der Kohlenwasserstoffprodukt-Abzugsleitung (18) wegerstreckt, um eine Sekundärzentrifugalabscheidung und ein Abscheiden der kleineren Menge des mitgerissenen verbrauchten Katalysators vom wendelförmig strömenden Kohlenwasserstoffprodukt zu bewirken und dadurch die abgeschiedene kleinere Menge des nicht mitgerissenen verbrauchten Katalysators zum Anschlußpunkt des Gefäßes an das Fallrohr (15), um den gelösten und abgeschiedenen verbrauchten Katalysator durch das Fallrohr (15) zu einer Strippzone (14) zu leiten; und

vi) eine Strippzone (14), die mit dem Fallrohr (15) und dem Unterteil des Steigregenerators in Verbindung steht, wobei die Strippzone (14) im Betrieb ein dichtes Bett aus verbrauchtem Katalysator aufweist, der sowohl 1) von der Hauptmassenstromabscheidung über die geneigte schlitzförmige Feststoffausfalleinrichtung (16) und 2) der Sekundärzentrifugalabscheidung über das Fallrohr (15) erhalten wird, wobei während des Betriebes Strippgas der Strippzone mittels einer Strippgaseinlaßeinrichtung (22) zugeleitet wird und wobei der wendelförmige Strömungsweg des Kohlenwasserstoff-Produktmaterials, der sich von der zweiten Endwand zum Kohlenwasserstoff-Produktmaterial-Abzugsauslaß (18) erstreckt, zumindest einen Teil des Strippgases daran hindert nach oben durch das Fallrohr (15) und in das horizontale Gefäß zu strömen.

3. Vorrichtung nach Anspruch 1, bei welcher ein einheitliches Bett des regenerierten Katalysators im Separator ein erstes, relativ dichtes Katalysatorbett (24) im Unterteil des Regenerators und eine relativ verdünnte Phase des Katalysators im Oberteil des Regenerators aufweist.

4. Vorrichtung nach Anspruch 1, bei welcher der Kohlenwasserstoff-Ausgangsmaterialeinlaß (5) an einem Punkt direkt unterhalb der Druckreduziereinrichtung (7) angeordnet ist.

5. Vorrichtung nach Anspruch 1, bei welcher die Anschluß-Abscheideeinrichtung (141), die mit der Oberseite des Steigregenerators (3) und der Oberseite des katalytischen Fallreaktors (1) in Verbindung steht, aufweist:

i) eine Einlaßeinrichtung, die mit der Oberseite des Steigregenerators (3) in Verbindung steht;

ii) ein Wirbelabzugsrohr (131) zum Abscheiden des regenerierten Katalysators vom verbrauchten Oxidationsgas, wobei der regenerierte Katalysator im wesentlichen in horizontaler Richtung auf einem wendelförmigen Strömungsweg beschleunigt wird;

iii) eine Austrittseinrichtung (133) für verbrauchtes Oxidationsgas zum Abzug des verbrauchten Oxidationsgases im Wirbelauslaßrohr (131);

iv) eine konische Strömungssteuereinrichtung (137), die einen Wirbelstabilisator aufweist, der an einer Stelle in der Abscheideeinrichtung gegenüber dem Ende des Wirbelauslaßrohres (131) liegt und so angeordnet ist, daß sie einen wendelförmigen Strömungsweg des verbrauchten Oxidationsgases bildet, welcher die konische Gestalt der konischen Strömungssteuereinrichtung (137) umgibt; und

v) eine Auslaßeinrichtung, die mit der zweiten, relativ dichten Phase des regenerierten Katalysators in Verbindung steht, um regenerierten Katalysator von der Anschluß-Abscheideeinrichtung (141) zum zweiten, relativ dichten Katalysatorbett (135) zu leiten.

6. Vorrichtung nach Anspruch 1, bei welcher die relativ dichte Phase des regenerierten Katalysators (139), welche über dem katalytischen Fallreaktor liegt, eine Dampfeinlaßeinrichtung (149) aufweist, um dem katalytischen Fallreaktor Dampf mit dem Katalysator zuzusetzen.

7. Verfahren zum kontinuierlichen Kracken eines kohlenwasserstoffhaltigen Ausgangsmaterials in ein



kohlenwasserstoffhaltiges Produktmaterial mit kleineren Molekülen in einem katalytischen Fallreaktor, welches umfaßt:

- a) Einleiten des kohlenwasserstoffhaltigen Ausgangsmaterials in den Oberteil eines sich im wesentlichen vertikal erstreckenden Fallreaktors in Gegenwart einer katalytischen Krack-Materialzusammensetzung bei einer Temperatur von 260 bis 815°C, einem Druck von 1 bar bis 50 bar und einem Druckabfall von nahezu Null, um die Moleküle des kohlenwasserstoffhaltigen Ausgangsmaterials in kleinere Moleküle zu kracken während einer Verweilzeit von 0,2 bis 5 s, während das kohlenwasserstoffhaltige Ausgangsmaterial in Richtung nach unten gegen den Auslaß des Reaktors strömt;
- b) Abziehen des kohlenwasserstoffhaltigen Produktmaterials und des verbrauchten Katalysators, auf dem Koks abgelagert ist, aus dem Auslaß des Reaktors nach der vorerwähnten Verweilzeit und direkte Aufgabe derselben in einen horizontalen Zyklonseparator;
- c) Abscheiden des kohlenwasserstoffhaltigen Produktmaterials vom verbrauchten Katalysator im horizontalen Zyklonseparator und Abziehen des kohlenwasserstoffhaltigen Produktmaterials aus dem Verfahren als Produktmaterial;
- d) Überleiten des verbrauchten Katalysators mit auf diesem abgelagerten Koks aus dem horizontalen Zyklonseparator in einen Steigregenerator, zusätzlich zu hinzugefügtem Regenerationsgas, das ein sauerstoffhaltiges Gas enthält;
- e) Anheben der Temperatur im Unterteil des Regenerators durch Temperatursteigerungsmittel, um zu einer Kohlenstoffverbrennungstemperatur zu gelangen, und Aufrechterhalten eines relativ dichten Schnellfluidisierbettes aus regeneriertem Katalysator im Steigregenerator über nahezu die gesamte Länge des Steigregenerators, um regenerierten Katalysator und eine Dampfphase verbrauchten Regenerationsgases zu erzeugen;
- f) Überleiten des regenerierten Katalysators und einer Dampfphase, die aus der Oxidation des Koks in Gegenwart des sauerstoffhaltigen Gases gebildet wird, in einen Zentrifugalseparator;
- g) Abscheiden des regenerierten Katalysators aus der Dampfphase im Zentrifugalseparator und Abziehen der Dampfphase aus dem Verfahren, dadurch gekennzeichnet, daß das Verfahren ferner umfaßt:
 - h) Einleiten des abgesonderten regenerierten Katalysators aus dem Zentrifugalseparator in ein dichtes Katalysatorbett, das auf einer Temperatur von 537 bis 982°C und einem Druck von 1 bar bis 50 bar gehalten wird, wobei der Katalysator im dichten Bett während einer Verweilzeit von 2 bis 600 s verbleibt; und
 - i) Überführen des regenerierten Katalysators aus dem dichten Bett zum Oberteil des Fallreaktors zum Kontakt mit kohlenwasserstoffhaltigem Ausgangsmaterial, das in den Oberteil des Fallreaktors eintritt, wobei der Druck im dichten Katalysatorbett um zumindest 34,5 mbar höher als der Druck im Fallreaktor ist, und wobei der verbrauchte Katalysator mit auf diesem abgelagerten Koks aus dem horizontalen Zyklonseparator gestrippt und nachfolgend direkt ohne irgendeine andere Regenerationszone dem Steigregenerator aufgegeben wird.

Revendications

1. Dispositif pour la conversion intégrale, par craquage catalytique, d'hydrocarbures pour la conversion catalytique d'une matière d'alimentation hydrocarbonée en une matière de produits hydrocarbonés ayant des molécules plus petites, ledit dispositif comportant:
 - a) un réacteur catalytique à écoulement descendant s'étendant essentiellement dans le sens vertical, ledit réacteur comportant une entrée pour une alimentation d'hydrocarbures à une position juxtaposée à la partie supérieure du réacteur à écoulement descendant, une entrée de catalyseur régénéré, à une position juxtaposée à la partie supérieure du réacteur à écoulement descendant, et une sortie pour l'évacuation de produit et de catalyseur usé, à une position juxtaposée à la partie inférieure du réacteur à écoulement descendant;
 - b) un régénérateur catalytique ascendant à riser s'étendant essentiellement dans le sens vertical pour la régénération de catalyseur usé provenant du réacteur catalytique à écoulement descendant, ayant une entrée de catalyseur usé à une position juxtaposée à la portion inférieure du régénérateur, des moyens d'entrée d'un gaz de régénération, pour introduire un gaz contenant de l'oxygène à une position juxtaposée à la partie inférieure du régénérateur, et une sortie pour le catalyseur régénéré et pour une phase de vapeur, à une position juxtaposée à la partie supérieure du régénérateur, la sortie ayant des moyens adaptés pour enlever le catalyseur régénéré et les vapeurs résultant de l'oxydation du coke, présent sur le catalyseur usé, avec le gaz de régénération contenant de l'oxygène;
 - c) des moyens horizontaux de séparation cycloniques pour séparer le catalyseur usé de la matière de produit hydrocarboné, lesdits moyens horizontaux cycloniques de séparation étant en communication avec la partie inférieure du réacteur catalytique à écoulement descendant, et avec la partie inférieure du régénérateur à riser;
 - d) des moyens de connexion et de séparation communiquant avec le sommet du régénérateur ascendant à riser et avec le sommet du réacteur catalytique à écoulement descendant pour séparer le catalyseur régénéré, dérivé du régénérateur ascendant à riser, des gaz d'oxydation usés, ledit dispositif étant caractérisé en ce que les moyens horizontaux cycloniques de séparation (2) relient les fonds respectifs du réacteur à écoulement descendant et du régénérateur ascendant à riser (3), les moyens de



connexion et de séparation (47) fournissent une phase relativement dense de catalyseur entre le sommet du régénérateur à écoulement ascendant et le sommet du réacteur catalytique à écoulement descendant, et le dispositif comportant en outre:

- e) des moyens pour réduire la pression (7) de façon à obtenir une pression plus élevée, dans la phase relativement dense (12), audessus des moyens de réduction de pression (7), que la pression dans la partie supérieure du réacteur catalytique à écoulement descendant.

2. Dispositif selon la revendication 1, caractérisé en ce que les moyens (2) horizontaux de séparation comportent:

- i) un récipient horizontal essentiellement cylindrique ayant un corps comportant un sommet avec une ouverture vers le réacteur catalytique à écoulement descendant, une première paroi d'extrémité non perforée, un sommet, et une deuxième paroi d'extrémité perforée pour la pénétration d'un conduit (18) pour l'évacuation d'un produit hydrocarboné, où ladite ouverture est localisée excentrée par rapport à l'axe longitudinal du sommet du récipient cylindrique, dans la direction horizontale, l'ouverture étant suffisante pour permettre le passage d'un mélange de catalyseur usé et de produits hydrocarbonés, en direction descendante dans le récipient;

ii) un déversoir (downcomer) (15) sous forme d'un conduit qui s'étend relativement verticalement et qui est relié au fond du récipient à un endroit relativement opposé à l'ouverture, dans le sommet du récipient, pour le passage vers le bas, à travers le déversoir, d'une quantité relativement faible de catalyseur usé;

- iii) un conduit (18) pour enlever les produits hydrocarbonés, ce conduit étant situé dans la deuxième paroi perforée d'extrémité du récipient, dans une direction verticale sous l'ouverture, et dans une direction horizontale vers l'ouverture, pour enlever de façon continue le produit hydrocarboné après une séparation centrifuge secondaire à partir du catalyseur usé;

iv) des moyens (16), avec fente inclinée, pour descente de solide, qui sont reliés au fond du récipient, à une position séparée d'au moins 90° du point de communication du réacteur catalytique à écoulement descendant avec le sommet du réservoir, la mesure étant faite par l'angle autour de la circonférence du récipient, où 360° est égal à une révolution complète autour de la circonférence, les moyens (16) de descente recevant le catalyseur usé par une séparation primaire de masse des catalyseurs usés à partir du produit hydrocarboné par accélération centrifuge de catalyseur usé d'un angle d'au moins 90° dans le récipient horizontal, de telle sorte que le catalyseur usé soit accéléré contre la surface du récipient cylindrique pour provoquer une séparation primaire de l'écoulement de masse et pour faire ainsi passer la plus grande partie du catalyseur usé à travers les moyens (16) inclinés pour descente de solide, vers le déversoir (15);

v) le dispositif étant tel que le diamètre du conduit (18) pour enlever le produit hydrocarboné soit plus petit que le diamètre du récipient horizontal, et que l'entrée excentrée du mélange de produit hydrocarboné et de catalyseur usé développe pendant l'opération un taux de turbulence supérieur à 0,2 défini par la vitesse tangentielle du produit hydrocarboné à travers la section transversale du réacteur catalytique à écoulement descendant divisée par la vitesse superficielle axiale du fluide à travers la section transversale du conduit pour enlever le produit hydrocarboné, de façon à provoquer un vortex du produit hydrocarboné avec de faibles quantités entraînées de catalyseur usé dans un trajet hélicoïdal qui s'étend depuis la paroi non perforée, à l'opposé du conduit (18) pour enlever le produit hydrocarboné, pour provoquer la séparation centrifuge secondaire et la séparation de la faible quantité de catalyseur usé entraîné, à partir du produit hydrocarboné en hélice, et donc le passage de la faible quantité séparée du catalyseur usé qui n'est donc plus entraînée, vers le point de connexion du récipient avec le déversoir (15) pour faire passer le catalyseur usé séparé et non entraîné, par le déversoir (15), vers une zone de rectification (14); et

vi) une zone de rectification (14) qui communique avec le déversoir (15) et la partie inférieure du régénérateur ascendant à riser, la zone de rectification (14) comportant, pendant l'opération, un lit dense de catalyseur usé provenant à la fois de 1) la séparation primaire d'écoulement massique, par les moyens (16) à fente inclinée, pour descente de solide, et 2) la séparation secondaire centrifuge, par l'intermédiaire du déversoir (15), de telle sorte que, pendant l'opération, on fasse passer un gaz de rectification vers la zone de rectification, grâce à des moyens (22) pour l'entrée d'un gaz de rectification, et de telle sorte que le trajet d'écoulement hélicoïdal de la matière de produit hydrocarboné, qui s'étend depuis la seconde paroi d'extrémité vers la sortie (18) pour enlever la matière à produit hydrocarbonée, empêche qu'au moins une portion du gaz de rectification pénètre vers le haut à travers le déversoir (15) et dans le récipient horizontal.

3. Dispositif selon la revendication 1, où un lit uniforme de catalyseur en régénération dans le régénérateur comporte un premier lit relativement dense de catalyseur (24) dans la partie inférieure du régénérateur, et une phase relativement diluée de catalyseur dans la partie supérieure du régénérateur.

4. Dispositif selon la revendication 1, où l'entrée (5) pour l'alimentation en hydrocarbures est située en un point directement au-dessous des moyens (7) pour réduire la pression.

5. Dispositif selon la revendication 1, dans lequel les moyens de connexion et de séparation (141) communiquant avec le sommet du régénérateur (3) ascendant à riser et le sommet du réacteur catalytique (1) à écoulement descendant comportent:

- i) des moyens d'introduction communiquant avec le sommet du régénérateur (3) ascendant à riser;
ii) un tube (131) de sortie à vortex pour séparer le catalyseur régénéré du gaz d'oxydation usé, où le



catalyseur régénéré est accéléré dans une direction essentiellement horizontale, avec un trajet d'écoulement hélicoïdal;

iii) des moyens (133) pour la sortie du gaz d'oxydation usé, permettant d'évacuer le gaz d'oxydation usé dans le tube (131) d'évacuation à vortex;

5 iv) des moyens (137) coniques pour le contrôle de l'écoulement, comportant un stabilisateur de vortex situé à une position dans les moyens de séparation opposée à l'extrémité finale de placement du tube (131) de sortie à vortex et disposé de façon à permettre le trajet d'écoulement en hélice du gaz d'oxydation usé de telle sorte que cet écoulement en hélice entoure la forme conique des moyens de contrôle (137) coniques d'écoulement; et

10 v) des moyens de sortie communiquant avec la deuxième phase relativement dense de catalyseur régénéré pour faire passer le catalyseur régénéré depuis les moyens (141) de connexion et de séparation vers la deuxième phase relativement dense (135) de catalyseur.

6. Dispositif selon la revendication 1, où la phase relativement dense (139) de catalyseur régénéré qui surmonte le réacteur catalytique à écoulement descendant possède des moyens (149) d'introduction de 15 vapeur d'eau, pour ajouter de la vapeur avec le catalyseur au réacteur catalytique à écoulement descendant.

7. procédé pour le craquage en continu d'une matière d'alimentation hydrocarbonée de façon à obtenir une matière de produits hydrocarbonés ayant de plus petites molécules, dans un réacteur catalytique à écoulement descendant, ledit procédé comportant les points suivants:

20 a) on fait passer la matière d'alimentation hydrocarbonée dans la partie supérieure d'un réacteur à écoulement descendant qui s'étend essentiellement verticalement, en présence d'une composition de matière catalytique de craquage, à une température de 260 à 815°C, une pression de 1 à 50 bars et une baisse de pression voisine de zéro, pour craquer les molécules de la matière d'alimentation hydrocarbonée, de façon à obtenir des molécules plus petites pendant un temps de séjour de 0,2 secondes 25 à 5 secondes, alors que la matière d'alimentation hydrocarbonée s'écoule en direction du bas, vers la sortie du réacteur;

b) on enlève la matière de produits hydrocarbonés et le catalyseur usé sur lequel se trouve déposé du coke, de la sortie du réacteur, après le temps de séjour mentionné ci-dessus, et on les décharge directement dans un séparateur à cyclone horizontal;

30 c) on sépare la matière de produits hydrocarbonés du catalyseur usé dans ledit séparateur à cyclone horizontal, et on enlève du processus la matière de produits hydrocarbonés comme matière produit;

d) on fait passer le catalyseur usé, sur lequel se trouve déposé du coke, depuis le séparateur horizontal à cyclone vers un régénérateur ascendant à riser, avec en plus un gaz de régénération ajouté, comportant un gaz contenant de l'oxygène;

35 e) on élève la température dans le fond du régénérateur avec des moyens pour élever la température, de façon à parvenir à une température pour taux de combustion du carbone, et on maintient dans le régénérateur à riser un lit relativement dense à fluidisation rapide de catalyseur en régénération, sur pratiquement toute la longueur du régénérateur ascendant à riser pour produire le catalyseur régénéré et une phase vapeur de gaz de régénération usé;

40 f) on fait passer le catalyseur régénéré et une phase vapeur, formée par l'oxydation du coke, en présence du gaz contenant de l'oxygène, vers un séparateur centrifuge;

g) on sépare le catalyseur régénéré de la phase vapeur dans le séparateur centrifuge, et on retire du processus la phase vapeur, ledit procédé étant caractérisé en outre par les points suivants:

45 h) on fait passer le catalyseur régénéré séparé depuis le séparateur centrifuge vers un lit dense de catalyseur maintenu à une température de 537 à 982°C, et une pression de 1 bar à 50 bars, de telle sorte que le catalyseur séjourne dans le lit dense pendant un temps de séjour de 2 secondes à 600 secondes; et

50 i) on fait passer le catalyseur régénéré depuis le lit dense vers la partie supérieure du réacteur descendant pour qu'il soit au contact de la matière d'alimentation hydrocarbonée qui entre dans la partie supérieure du réacteur descendant, la pression dans le lit dense de catalyseur est supérieure de plus de 34,5 mbars à la pression dans le réacteur descendant, et le catalyseur usé, sur lequel se trouve déposé du coke, en provenance du séparateur horizontal à cyclone, étant rectifié et introduit ensuite directement, sans autre zone de régénération, dans le régénérateur ascendant à riser.

55

60

65