

CONFIGURATION INFORMATION PUSH METHOD AND DEVICE

TECHNICAL FIELD

The present invention relates to the communications field, and in particular, to a configuration information push method and device.

BACKGROUND

In a process in which an application system executes a program, to flexibly cope with a requirement change, some configurations that are often changed are settled into a file. In different deployment and application scenarios, different configurations need to be changed before deployment is performed. When a configuration is changed, based on a real-time configuration push system, the application system can have the configuration change that immediately takes effect without restarting a program. For example, a database cluster is used in a transaction platform, and when a program is started, a connection is established to a database by using a group of database connection parameters. When a peak hour for use of the transaction platform arrives, some database connection parameters need to be switched. In this case, based on the real-time configuration push system, an application on the transaction platform can immediately take effect without restarting the application, so that execution of a service is not affected as much as possible. The real-time configuration push system needs to efficiently find that a new configuration value of a server is inconsistent with an original configuration value of a client, and pushes the new configuration value to the client in real time.

In the existing technology, a client interacts with a server by using a Hypertext Transfer Protocol (HTTP) short connection, and the client periodically initiates a short connection to perform polling on the server. However, in a currently used manner of periodically performing polling on the server, duration of each polling is short, and a wait time for polling is long. Consequently, real-time performance of configuration pushing cannot be ensured.

SUMMARY

The present invention provides a configuration information push method and device, to resolve a problem that when an existing client periodically performs polling on a server, real-time performance of configuration pushing cannot be ensured due to short polling

duration.

To achieve the foregoing objective, the present invention provides a configuration information push method, including:

- obtaining a polling request sent by a client, where the polling request includes configuration information of configuration items;

- determining whether the configuration information of the configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items;

- keeping a short connection to the client within preset polling duration if a determining result is yes; and

- pushing, if, in the duration of the short connection, current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, the current configuration information of the target configuration item to the client, so that the client updates a configuration of the target configuration item to the current configuration information.

To achieve the foregoing objective, the present invention provides a configuration information push method, including:

- sending a polling request to a server, so that the server determines whether configuration information of configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items, where

 - the polling request includes the configuration information of the configuration items;

- receiving a connection keeping request for keeping a short connection to the server within preset polling duration that is sent by the server, where the connection keeping request is sent by the server when the server determines that the configuration information of the configuration items in the polling request is respectively consistent with the current configuration information of the corresponding local configuration items;

- receiving, from the server, a push message used to push current configuration information of a target configuration item, where the push message is sent by the server when the server determines, in the duration of the short connection, that current configuration information of at least one target configuration item is inconsistent with configuration information of a corresponding configuration item in the polling request, and the target configuration item is a configuration item in the local configuration items; and

 - updating a configuration of the target configuration item to the current configuration

information.

To achieve the foregoing objective, the present invention provides a configuration information push device, including:

- an obtaining module, configured to obtain a polling request sent by a client, where the polling request includes configuration information of configuration items;

- a determining module, configured to determine whether the configuration information of the configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items;

- a connection keeping module, configured to keep a short connection to the client within preset polling duration if a determining result is yes; and

- a push module, configured to push, if, in the duration of the short connection, current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, the current configuration information of the target configuration item to the client, so that the client updates a configuration of the target configuration item to the current configuration information.

To achieve the foregoing objective, the present invention provides a configuration information push device, including:

- a sending module, configured to send a polling request to a server, so that the server determines whether configuration information of configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items, where

- the polling request includes the configuration information of the configuration items;

- a first receiving module, configured to receive a connection keeping request for keeping a short connection to the server within preset polling duration that is sent by the server, where the connection keeping request is sent by the server when the server determines that the configuration information of the configuration items in the polling request is respectively consistent with the current configuration information of the corresponding local configuration items;

- a second receiving module, configured to receive, from the server, a push message used to push current configuration information of a target configuration item, where the push message is sent by the server when the server determines, in the duration of the short connection, that current configuration information of at least one target configuration item is inconsistent with configuration information of a corresponding configuration item in the

polling request, and the target configuration item is a configuration item in the local configuration items; and

an update module, configured to update a configuration of the target configuration item to the current configuration information.

According to the configuration information push method and device that are provided in the present invention, a polling request sent by a client is obtained; whether configuration information of configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items is determined; if yes, a short connection to the client is kept within preset polling duration; and if, in the duration of the short connection, current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, the current configuration information of the target configuration item is pushed to the client, so that the client updates a configuration of the target configuration item to the current configuration information. In embodiments, when configuration information of a configuration item is not updated, a short connection needs to be kept within preset polling duration, so that the polling duration is correspondingly extended, and a change in the configuration information of the configuration item can be sensed in time, thereby ensuring real-time performance of configuration information pushing.

BRIEF DESCRIPTION OF THE DRAWINGS

FIG. 1 is a schematic flowchart of a configuration information push method according to Embodiment 1 of the present invention;

FIG. 2 is a schematic flowchart of a configuration information push method according to Embodiment 2 of the present invention;

FIG. 3 is a schematic application diagram of the configuration information push method according to Embodiment 2 of the present invention;

FIG. 4 is a schematic structural diagram of a configuration information push device according to Embodiment 3 of the present invention;

FIG. 5 is a schematic structural diagram of a configuration information push device according to Embodiment 4 of the present invention; and

FIG. 6 is a schematic structural diagram of a configuration information push system according to Embodiment 5 of the present invention.

DETAILED DESCRIPTION OF THE INVENTION

The following describes in detail a configuration information push method and device that are provided in embodiments of the present invention with reference to the accompanying drawings.

Embodiment 1

As shown in FIG. 1, FIG. 1 is a schematic flowchart of a configuration information push method according to Embodiment 1 of the present invention. This embodiment is performed by a server. The configuration information push method includes the following steps.

S101: Obtain a polling request sent by a client.

The polling request includes configuration information of configuration items.

A short connection is established between the client and the server. In this embodiment, the server establishes the short connection to the client based on the HTTP. Since the HTTP communication protocol is a text protocol, cross-language pushing of configuration information can be implemented.

After the short connection is established, the server may continually receive the polling request that is sent by the client by using the short connection, to perform polling on a configuration change state of each configuration item in the server. The polling request includes the configuration information of the configuration items, and the configuration information is information configured by the server for the configuration item last time. Configuration information is a configuration value of a configuration item.

S102: Determine whether the configuration information of the configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items.

After receiving the polling request, the server determines whether the current configuration information of the locally stored configuration items is respectively consistent with the configuration information of the corresponding configuration items that is sent by the client. The locally stored configuration items are completely the same as the configuration items in the client, but configuration information of a local configuration item may be different from configuration information of a configuration item in the client. For example, the configuration items include a configuration item 1, a configuration item 2, and a configuration item 3, and in the polling request, configuration information of the configuration item 1 is data 1, configuration information of the configuration item 2 is data 2, and configuration information of the configuration item 3 is data 3. When configuration

information of a locally stored configuration item 1 to a locally stored configuration item 3 is respectively the data 1 to the data 3, current configuration information of the locally stored configuration items is respectively consistent with the configuration information of the corresponding configuration items that is sent by the client. That is, the determining result is yes, and step S103 is performed. If configuration information of the locally stored configuration item 2 is data 4, the current configuration information of the locally stored configuration items is not consistent with the configuration information of the corresponding configuration items that is sent by the client. That is, the determining result is no, and step S105 is performed.

S103: Keep a short connection to the client within preset polling duration.

When it is determined that the current configuration information of the locally stored configuration items is consistent with the configuration information of the corresponding configuration items that is sent by the client, that is, configuration information of a configuration item in the client is not updated, the server may keep the short connection to the client within the preset polling duration. Specifically, the server sends an asynchronous processing request to the client. The asynchronous processing request instructs the client to keep the short connection to the server within the preset polling duration. For example, the short connection to the client may be kept by using an asynchronous Servlet.

S104: Push, in the duration of the short connection, if current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, the current configuration information of the target configuration item to the client, so that the client updates a configuration of the target configuration item to the current configuration information.

When the duration of the short connection to the client has not reached the preset polling duration, when current configuration information of at least one target configuration item in the locally stored configuration items in the server is inconsistent with configuration information of a corresponding configuration item in the polling request, that is, configuration information of the target configuration item in the server is changed, the server may push the current configuration information of the target configuration item to the client.

For example, the server may send, to the client, a polling response indicating a configuration change. The polling response includes the current configuration information of the target configuration item. For example, when the target configuration item is the configuration item 2; the polling response is: configuration item 2, data 4. Correspondingly,

after receiving the current configuration information of the target configuration item, the client needs to update the configuration of the target configuration item to the current configuration information.

In this embodiment, when the target configuration item is obtained, the target configuration item and the current configuration information of the target configuration item are directly sent to the client, thereby reducing a processing time of a polling result, and improving real-time performance of configuration information pushing.

Optionally, after obtaining the target configuration item, the server may first add the target configuration item to the polling response and send the polling response to the client, and after receiving a configuration information request message sent by the client, the server sends a configuration value of the target configuration item to the client. Although a processing time of a polling result is extended, when the client does not need to update the configuration item, a waste of resources can be reduced.

Further, after the duration of the short connection to the client reaches the preset polling duration, if the current configuration information of the locally stored configuration items in the server is respectively consistent with the configuration information of the corresponding configuration items in the polling request, the server may send, to the client, a polling response indicating no configuration change. The polling response is null.

In this embodiment, the short connection to the client may be kept until a preset polling time is reached and may be broken after that. When the short connection is kept within the preset polling time, if the server detects that current configuration information of at least one target configuration item in the local configuration items is inconsistent with previous configuration information of a corresponding configuration item that is sent to the client, the server may deliver the current configuration information of the target configuration item to the client, so that configuration information of the configuration item in the client is consistent with the configuration information of the corresponding configuration item in the server.

Alternatively, in the duration of the short connection, after a user corresponding to the client actively changes configuration information of at least one configuration item in the polling request, the configuration information is added to the polling request and sent to the server. The server can also detect that current configuration information of at least one target configuration item in the local configuration items is different from the changed configuration information of the configuration item in the polling request, and the server may deliver the current configuration information of the target configuration item to the client, so

that the client reconfigures the target configuration item of the client with the configuration information delivered by the server.

Optionally, in the duration of the short connection, when inconsistency between current configuration information of at least one target configuration item in the local configuration items and configuration information of a corresponding configuration item in the polling request occurs the first time, the server pushes the current configuration information of the target configuration item to the client, and then, immediately breaks the short connection to the client. After the current configuration information of the target configuration item is sent, it indicates that a configuration in the client is already the newest configuration. To continue to update the configuration in the client in real time, the short connection to the client needs to be immediately broken. When the short connection to the client is broken, after a next preset time interval is reached, a polling request sent by the client can continue to be received, so as to continue to update the configuration item in the client in real time.

To improve real-time performance of configuration updating for the client, a time interval for performing polling on the server can be shortened, so that after configuration information of a configuration item in the server is updated, information about a corresponding configuration item can be updated in the client more quickly.

S105: Obtain a target configuration item from the local configuration items.

If it is determined that configuration information of at least one configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, it indicates that current configuration information of the at least one configuration item whose configuration information is changed needs to be sent to the client, and the at least one configuration item whose configuration information is changed is obtained. In this embodiment, the at least one configuration item whose configuration information is inconsistent with the configuration information of the corresponding configuration item in the polling request is referred to as the target configuration item.

S106: Push current configuration information of the target configuration item to the client, so that the client updates a configuration of the target configuration item to the current configuration information.

After obtaining the target configuration item, the server pushes the current configuration information of the target configuration item to the client. For example, the server may send, to the client, a polling response indicating a configuration change. The polling response includes the current configuration information of the target configuration item.

Correspondingly, after receiving the current configuration information of the target configuration item, the client needs to update the configuration of the target configuration item to the current configuration information. After the current configuration information of the target configuration item is pushed, the short connection to the client is broken, so that after a next preset time interval is reached, a polling request sent by the client continues to be received, so as to update the configuration item in the client in real time.

According to the configuration information push method provided in this embodiment, a polling request sent by a client is obtained; whether configuration information of configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items is determined; if yes, a short connection to the client is kept within preset polling duration; and if in the duration of the short connection, current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, the current configuration information of the target configuration item is pushed to the client, so that the client updates a configuration of the target configuration item to the current configuration information. In this embodiment, when configuration information of a configuration item is not updated, a short connection needs to be kept within preset polling duration, so that the polling duration is correspondingly extended, and a change in the configuration information of the configuration item can be sensed in time, thereby ensuring real-time performance of configuration information pushing.

Embodiment 2

As shown in FIG. 2, FIG. 2 is a schematic flowchart of a configuration information push method according to Embodiment 2 of the present invention. This embodiment is executed by a client. The configuration information push method includes the following steps.

S201: Send a polling request to a server, so that the server determines whether configuration information of configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items.

The polling request includes configuration information of configuration items.

In this embodiment, before sending the polling request to the server, the client needs to establish a short connection to the server based on the HTTP. The HTTP communication protocol is a text protocol, so that cross-language pushing of configuration information can be implemented.

After the connection is established, the client sends the polling request to the server

through the short connection, to performing polling on a configuration change state of each configuration item in the server. The polling request includes the configuration information of the configuration items, and the configuration information is information configured by the server for the configuration last time. Configuration information is a configuration value of a configuration item.

Correspondingly, after receiving the polling request, the server determines whether current configuration information of locally stored configuration items is respectively consistent with configuration information of corresponding configuration items that is sent by the client. The locally stored configuration items are all the same as the configuration items in the client, but configuration information of a local configuration item may be different from configuration information of a configuration item in the client.

S202: Receive a connection keeping request for keeping a short connection to the server within preset polling duration that is sent by the server, where the connection keeping request is sent by the server when the server determines that the configuration information of the configuration items in the polling request is respectively consistent with the current configuration information of the corresponding local configuration items.

When the server determines that the current configuration information of the locally stored configuration items is consistent with the configuration information of the corresponding configuration items that is sent by the client, it indicates that the configuration information of the configuration items in the client is not updated. In this case, the client receives the connection keeping request for keeping the short connection to the server within the preset polling duration that is sent by the server, and after receiving the connection keeping request, the client continues keeping the short connection within the preset polling duration.

Further, the connection keeping request is an asynchronous processing request used to instruct to keep the short connection to the server within the preset polling duration. For example, the short connection to the server may be kept within the preset polling duration by using an asynchronous Servlet.

S203: Receive, from the server, a push message used to push current configuration information of a target configuration item, where the push message is sent by the server when the server determines, in the duration of the short connection, that current configuration information of at least one target configuration item is inconsistent with configuration information of a corresponding configuration item in the polling request, and the target configuration item is a configuration item in the local configuration items.

In the duration of the short connection to the client within the preset polling duration, if current configuration information of at least one target configuration item in the locally stored configuration items in the server is inconsistent with configuration information of a corresponding configuration item in the polling request, that is, configuration information of the target configuration item of the server is changed, the client receives the push message sent by the server. The push message includes the current configuration information of the target configuration item.

Optionally, the client receives a polling response indicating a configuration change and sent by the server. The polling response includes the target configuration item. After receiving the polling response, the client sends a configuration request message to the server, to request the server to deliver the current configuration information of the target configuration item to the client.

Further, after the short connection to the client reaches the preset polling duration, if the current configuration information of the locally stored configuration items in the server is respectively consistent with the configuration information of the corresponding configuration items in the polling request, the client receives a polling response indicating no configuration change and sent by the server, where the polling response is null; and the client senses that the server breaks the short connection to the client. Specifically, the client may obtain an indication message indicating that the short connection is broken, and after receiving the indication message, after a next preset time interval is reached, the client may continue to send a polling request to the server, so as to update the configuration item in real time.

S204: Update a configuration of the target configuration item to the current configuration information.

Correspondingly, after receiving the current configuration information of the target configuration item, the client needs to update the configuration of the target configuration item to the current configuration information.

During actual application, after sending the push message, the server immediately breaks the short connection to the client. Correspondingly, after the server breaks the short connection, the client can immediately sense that the short connection is broken. To keep updating the configuration item in the client in real time, the client needs to start timing immediately according to a preset time interval, and after a next time interval is reached, re-sends a polling request to the server. In this embodiment, a time interval for performing polling on the server can be shortened, so that after configuration information of a configuration item in the server is updated, information of a corresponding configuration item

can be updated in the client more quickly, thereby improving real-time performance of configuration updating in the client.

According to the configuration information push method provided in this embodiment, a polling request is sent to a server, so that the server determines whether configuration information of configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items; if yes, a short connection to the server is kept within preset polling duration; and if, in the duration of the short connection, current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, a client receives a push message including the current configuration information of the target configuration item, and the client updates a configuration of the target configuration item to the current configuration information. In this embodiment, when configuration information of a configuration item is not updated, a short connection needs to be kept within preset polling duration, so that the polling duration is correspondingly extended, and a change in the configuration information of the configuration item can be sensed in time, thereby ensuring real-time performance of configuration information pushing.

As shown in FIG. 3, FIG. 3 shows a specific application example of the foregoing embodiment of the present invention, and is used to explain and describe the foregoing embodiment. In this example, a client interacts with a server by using an HTTP short connection, and the client periodically initiates a polling request based on the short connection, to perform polling on the server.

S301: A client sends a polling request to a server.

Two configuration items: a configuration item 1 and a configuration item 2 are subscribed to in the polling request. A configuration value of the configuration item is dataid1 group1, and a configuration value of the configuration item 2 is dataid2 group2.

Assuming that at a moment of 0.0s, the client sends the polling request to the server, to perform polling on a change state of configuration information of a configuration item. Generally, the configuration information of the configuration item is a configuration value of the configuration item.

S302: After receiving the polling request, the server determines whether configuration values of locally stored configuration items are consistent with configuration values of corresponding configuration items in the polling request.

If yes, step S303 is performed.

S303: The server keeps the short connection to the client within preset polling duration based on an asynchronous Servlet technology.

If yes, it indicates that the server does not update the configuration values of the configuration items, that is, a polling result is no change. The server keeps the short connection to the client within the preset polling duration based on the asynchronous Servlet technology. In this example, the preset polling duration is 5s.

S304: The server sends a polling response to the client.

The polling response includes null.

In this example, the preset polling duration is 5s, and the server waits for reaching of the polling duration of 5s, that is, a moment at the 5.0s. In this example, within a time of 5s within which the short connection is kept, the configuration information of the configuration item 1 and the configuration item 2 is not changed in the server, so that the server sends, to the client, a polling response indicating no configuration change, where the polling response includes null, and breaks the short connection.

S305: After a preset time interval is reached, the client re-sends a polling request to the server.

After the client senses that the short connection to the server is broken, when a next preset time interval is reached, the client re-sends a polling request to the server, to perform polling on a configuration change state. In this example, the preset time interval is 1 ms, that is, a moment of 5.001s. A polling request is re-sent to the server. A configuration item and configuration information of the configuration item are subscribed to in the polling request. In this example, the configuration items that are subscribed to are the configuration item 1 and the configuration item 2. After the previous polling, polling results of the configuration item 1 and the configuration item 2 are no change, so that the configuration value of the configuration item is still dataid1 group1, and the configuration value of the configuration item 2 is still dataid2 group2.

S306: The server determines whether configuration values of locally stored configuration items are consistent with configuration values of corresponding configuration items in the polling request.

If yes, step S307 is performed.

S307: The server keeps a short connection to the client within preset polling duration based on an asynchronous Servlet technology.

S308: When the short connection is kept within the polling duration, when the configuration value of the configuration item 2 is changed, the server sends, to the client, a

polling response indicating a configuration change, where the polling response carries the configuration item 2.

If yes, it indicates that the server does not update the configuration values of the configuration items, that is, the polling result is no change, in the duration of the short connection within the polling duration, the configuration item 2: dataid2 group2 is changed 1s after the client sends the polling response indicating no configuration change, that is, at a moment of 6.0s, and the polling response indicating a configuration change is sent to the client. The polling response includes the configuration item 2, and the configuration item 2 is the target configuration item. Assuming that the time for obtaining the information on the change obtained through polling is 3 ms, the polling response indicating a configuration change is sent to the client at a moment of 6.003s. That is, at the moment of 6.003s, the client senses the configuration change, and the moment of 6.003s is close to a time at which the configuration is changed, that is, the moment of 6.0s, so that it may be considered that the client senses the configuration change in real time.

S309: The client sends a configuration value request to the server.

Specifically, after receiving, at the moment of 6.003s, the polling response indicating a configuration change, the client sends the configuration value request to the server at 6.004s, to request to configure the configuration item 2 as the newest configuration value in the server. The newest configuration value is a current configuration value of the configuration item 2.

S310: The server sends newest configuration value of the configuration item 2 to the client.

After receiving the configuration value request, the server sends the newest configuration value of the configuration item 2 to the client at a moment of 6.005s. Correspondingly, after receiving the newest configuration value, the client updates the configuration value of the configuration item 2 to the newest configuration value, and breaks the short connection.

S311: The client updates the configuration value of the configuration item 2 to the newest configuration value.

Specifically, after receiving the newest configuration value at the moment of 6.005s, the client updates the configuration value of the configuration item 2 to the newest current configuration value of the configuration item 2 in the polling response.

Optionally, in step S308, the polling response indicating a configuration change and sent by the server to the client carries both the configuration item 2 and the newest configuration value of the configuration item 2. The newest configuration value of the configuration item 2

is dataid2%02%group2. After receiving the polling response, the client updates the configuration value of the configuration item 2 to the newest configuration value.

Herein, it should be noted that, although the preset polling duration is 5s, for a case in which a configuration is changed when the short connection is kept within the polling duration, it takes only approximately 1s for the client to update the configuration value of the corresponding configuration item to the newest configuration value. To improve real-time performance of updating a configuration of a configuration item by the client, after the configuration is updated, the short connection needs to be broken immediately, so that the client sends a next polling request as soon as possible, so as to perform polling on a configuration change state, thereby pushing information to the client in real time.

S312: After a preset time interval is reached, the client re-sends a polling request to the server.

After sensing that the short connection to the server is broken, the client re-sends a polling request to the server at next 1 ms, that is, a moment of 6.006s, to performing polling on a configuration change state. The polling request includes the configuration item 1 and the configuration item 2 and respective configuration values. In this step, the configuration value of the configuration item 1 is dataid1 group1, and the configuration value of the configuration item 2 is dataid2%02%group2.

In this example, when configuration information of a configuration item is not updated, a short connection is kept within preset polling duration, which is equivalent to that the polling duration is extended, and a change in the configuration information of the configuration item can be sensed in time, thereby ensuring real-time performance of configuration information pushing.

Embodiment 3

As shown in FIG. 4, FIG. 4 is a schematic structural diagram of a configuration information push device according to Embodiment 3 of the present invention. The configuration information push device includes an obtaining module 11, a determining module 12, a connection keeping module 13, a push module 14, and a breaking module 15.

The obtaining module 11 is configured to obtain a polling request sent by a client, where the polling request includes configuration information of configuration items.

The determining module 12 is configured to determine whether the configuration information of the configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items.

The connection keeping module 13 is configured to keep a short connection to the client

within preset polling duration if a determining result is yes.

The push module 14 is configured to push, if in the duration of the short connection, current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, the current configuration information of the target configuration item to the client, so that the client updates a configuration of the target configuration item to the current configuration information.

The breaking module 15 is configured to break the short connection to the client.

The breaking module 15 is specifically configured to: push if in the duration of the short connection, inconsistency between current configuration information of at least one target configuration item in the local configuration items and configuration information of a corresponding configuration item in the polling request occurs the first time, the current configuration information of the target configuration item to the client, so that the client updates a configuration of the target configuration item to the current configuration information; and then break the short connection to the client.

The breaking module 15 is further specifically configured to: when the preset polling duration is reached, break the short connection to the client.

Further, the push module 14 is further configured to: when the determining result of the determining module 12 is no, obtain the target configuration item from the local configuration items; and push the current configuration information of the target configuration item to the client, so that the client updates the configuration of the target configuration item to the current configuration information.

Further, the push module 14 is specifically configured to: send a polling response to the client, where the polling response includes the target configuration item; receive a configuration information request sent by the client; and send the current configuration information of the target configuration item to the client, so that the client updates the configuration of the target configuration item to the current configuration information.

Further, the obtaining module 11 is further configured to: after the breaking module 15 breaks the short connection to the client, after a preset time interval is reached, re-obtain a polling request sent by the client.

Further, the connection keeping module 13 is specifically configured to: when the determining result of the determining module is yes, send an asynchronous processing request to the client, so that the client keeps the short connection within the preset polling duration.

According to the configuration information push device provided in this embodiment, a polling request sent by a client is obtained; whether configuration information of configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items is determined; if yes, a short connection to the client is kept within preset polling duration; and if, in the duration of the short connection, current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, the current configuration information of the target configuration item is pushed to the client, so that the client updates a configuration of the target configuration item to the current configuration information. In this embodiment, when configuration information of a configuration item is not updated, a short connection needs to be kept within preset polling duration, so that the polling duration is correspondingly extended, and a change in the configuration information of the configuration item can be sensed in time, thereby ensuring real-time performance of configuration information pushing.

Embodiment 4

As shown in FIG. 5, FIG. 5 is a schematic structural diagram of a configuration information push device according to Embodiment 4 of the present invention. The configuration information push device includes a sending module 21, a first receiving module 22, a second receiving module 23, and an update module 24.

The sending module 21 is configured to send a polling request to a server, so that the server determines whether configuration information of configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items.

The polling request includes the configuration information of the configuration items.

The first receiving module 22 is configured to receive a connection keeping request for keeping a short connection to the server within preset polling duration that is sent by the server.

The connection keeping request is sent by the server when the server determines that the configuration information of the configuration items in the polling request is consistent with the current configuration information of the corresponding local configuration items.

The second receiving module 23 is configured to receive, from the server, a push message used to push current configuration information of a target configuration item.

The push message is sent by the server when the server determines, in the duration of the

short connection, that current configuration information of at least one target configuration item is inconsistent with configuration information of a corresponding configuration item in the polling request, and the target configuration item is a configuration item in the local configuration items.

The update module 24 is configured to update a configuration of the target configuration item to the current configuration information.

Further, the sending module 21 is further configured to: before the second receiving module receives, from the server, the push message used to push the current configuration information of the target configuration item, send a configuration information request to the server, where the configuration information request is used to request the server to deliver the current configuration information of the target configuration item.

Further, the first receiving module 22 is further configured to receive an indication message for breaking the short connection that is sent by the server.

The indication message is sent by the server after the preset polling duration is reached and before the server sends the push message.

Further, the sending module 21 is further configured to: after the short connection to the server is broken, re-send a polling request to the server after a preset time interval is reached.

Further, the connection keeping request is an asynchronous processing request used to instruct to keep the short connection to the server within the preset polling duration.

Further, the sending module 21 is further configured to: after the update module 24 updates the configuration of the target configuration item to the current configuration information, re-send a polling request to the server after a preset time interval is reached.

According to the configuration information push device provided in this embodiment, a polling request is sent to a server, so that the server determines whether configuration information of configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items; if yes, a short connection to the server is kept within preset polling duration; and if, in the duration of the short connection, current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, a client receives a push message including the current configuration information of the target configuration item, and the client updates a configuration of the target configuration item to the current configuration information. In this embodiment, when configuration information of a configuration item is not updated, a short connection needs to be kept within preset polling duration, so that the

polling duration is correspondingly extended, and a change in the configuration information of the configuration item can be sensed in time, thereby ensuring real-time performance of configuration information pushing.

Embodiment 5

As shown in FIG. 6, FIG. 6 is a schematic structural diagram of a configuration information push system according to Embodiment 5 of the present invention. The configuration information push system includes a server 1 and a client 2. For a structure implementation and a processing process of the server 1, refer to descriptions in Embodiment 3 and FIG. 4 in this specification, and details are not described herein again. For a structure implementation and a processing process of the client 2, refer to descriptions in Embodiment 4 and FIG. 5 in this specification, and details are not described herein again.

In this embodiment, when configuration information of a configuration item is not updated, a short connection needs to be kept within preset polling duration, so that the polling duration is correspondingly extended, and a change in the configuration information of the configuration item can be sensed in time, thereby ensuring real-time performance of configuration information pushing.

Persons of ordinary skill in the art may understand that all or some of the steps of the method embodiments may be implemented by a program instructing relevant hardware. The program may be stored in a computer-readable storage medium. When the program is executed, the steps of the method embodiments are performed. The foregoing storage medium includes: any medium that can store program code, such as a ROM, a RAM, a magnetic disk, or an optical disc.

Finally, it should be noted that the foregoing embodiments are merely intended for describing the technical solutions of the present invention, but not for limiting the present invention. Although the present invention is described in detail with reference to the foregoing embodiments, persons of ordinary skill in the art should understand that they may still make modifications to the technical solutions described in the foregoing embodiments or make equivalent replacements to some or all technical features thereof, without departing from the scope of the technical solutions of the embodiments of the present invention.

CLAIMS

What is claimed is:

1. A configuration information push method, comprising:
 - obtaining a polling request sent by a client, wherein the polling request comprises configuration information of configuration items;
 - determining whether the configuration information of the configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items;
 - keeping a short connection to the client within preset polling duration if a determining result is yes; and
 - pushing, if, in the duration of the short connection, current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, the current configuration information of the target configuration item to the client, so that the client updates a configuration of the target configuration item to the current configuration information.
2. The method according to claim 1, further comprising:
 - if the determining result is no, obtaining the target configuration item from the local configuration items;
 - pushing the current configuration information of the target configuration item to the client, so that the client updates the configuration of the target configuration item to the current configuration information; and
 - breaking the short connection to the client.
3. The method according to claim 1, wherein the pushing, if, in the duration of the short connection, current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, the current configuration information of the target configuration item to the client, so that the client updates a configuration of the target configuration item to the current configuration information comprises:
 - sending a polling response to the client, wherein the polling response comprises the target configuration item;
 - receiving a configuration information request sent by the client; and
 - sending the current configuration information of the target configuration item to the

client, so that the client updates the configuration of the target configuration item to the current configuration information.

4. The method according to claim 1, wherein the pushing, if in the duration of the short connection, current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, the current configuration information of the target configuration item to the client, so that the client updates a configuration of the target configuration item to the current configuration information comprises:

pushing, if, in the duration of the short connection, inconsistency between current configuration information of at least one target configuration item in the local configuration items and configuration information of a corresponding configuration item in the polling request occurs the first time, the current configuration information of the target configuration item to the client, so that the client updates a configuration of the target configuration item to the current configuration information; and

breaking the short connection to the client.

5. The method according to claim 3, wherein after the pushing, if, in the duration of the short connection, current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, the current configuration information of the target configuration item to the client, so that the client updates a configuration of the target configuration item to the current configuration information, the method comprises:

when the preset polling duration is reached, breaking the short connection to the client.

6. The method according to claim 4 or 5, wherein after the breaking the short connection to the client, the method comprises:

after a preset time interval is reached, re-obtaining a polling request sent by the client.

7. The method according to claim 1, wherein the keeping a short connection to the client within preset polling duration if a determining result is yes comprises:

sending an asynchronous processing request to the client, so that the client keeps the short connection within the preset polling duration.

8. A configuration information push method, comprising:

sending a polling request to a server, so that the server determines whether configuration information of configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items, wherein the polling request comprises the configuration information of the configuration items;

receiving a connection keeping request for keeping a short connection to the server within preset polling duration that is sent by the server, wherein the connection keeping request is sent by the server when the server determines that the configuration information of the configuration items in the polling request is respectively consistent with the current configuration information of the corresponding local configuration items;

receiving, from the server, a push message used to push current configuration information of a target configuration item, wherein the push message is sent by the server when the server determines, in the duration of the short connection, that current configuration information of at least one target configuration item is inconsistent with configuration information of a corresponding configuration item in the polling request, and the target configuration item is a configuration item in the local configuration items; and

updating a configuration of the target configuration item to the current configuration information.

9. The method according to claim 8, wherein before the receiving, from the server, a push message used to push current configuration information of a target configuration item, the method comprises:

sending a configuration information request to the server, wherein the configuration information request is used to request the server to deliver the current configuration information of the target configuration item.

10. The method according to claim 8, further comprising:

receiving an indication message for breaking the short connection that is sent by the server, wherein the indication message is sent by the server after the preset polling duration is reached and before the server sends the push message; and

after a preset time interval is reached, re-sending a polling request to the server.

11. The method according to any one of claims 8 to 10, wherein the connection keeping request is an asynchronous processing request used to instruct to keep the short connection to the server within the preset polling duration.

12. The method according to claim 8 or 9, wherein after the updating a configuration of the target configuration item to the current configuration information, the method further comprises:

after a preset time interval is reached, re-sending a polling request to the server.

13. A configuration information push device, comprising:

an obtaining module, configured to obtain a polling request sent by a client, wherein the polling request comprises configuration information of configuration items;

a determining module, configured to determine whether the configuration information of the configuration items in the polling request is respectively consistent with current configuration information of corresponding local configuration items;

a connection keeping module, configured to keep a short connection to the client within preset polling duration if a determining result is yes; and

a push module, configured to push, if, in the duration of the short connection, current configuration information of at least one target configuration item in the local configuration items is inconsistent with configuration information of a corresponding configuration item in the polling request, the current configuration information of the target configuration item to the client, so that the client updates a configuration of the target configuration item to the current configuration information.

14. The device according to claim 13, wherein the push module is further configured to: when the determining result of the determining module is no, obtain the target configuration item from the local configuration items; and push the current configuration information of the target configuration item to the client, so that the client updates the configuration of the target configuration item to the current configuration information.

15. The device according to claim 13, wherein the push module is specifically configured to: send a polling response to the client, wherein the polling response comprises the target configuration item; receive a configuration information request sent by the client; and send the current configuration information of the target configuration item to the client, so that the client updates the configuration of the target configuration item to the current configuration information.

16. The device according to claim 15, further comprising:

a breaking module, configured to: push, if, in the duration of the short connection, inconsistency between current configuration information of at least one target configuration item in the local configuration items and configuration information of a corresponding configuration item in the polling request occurs the first time, the current configuration information of the target configuration item to the client, so that the client updates a configuration of the target configuration item to the current configuration information; and then break the short connection to the client.

17. The device according to claim 15, wherein the breaking module is further configured to: when the preset polling duration is reached, break the short connection to the client.

18. The device according to claim 16 or 17, wherein the obtaining module is further configured to: after the breaking module breaks the short connection to the client, after a

preset time interval is reached, re-obtain a polling request sent by the client.

19. The device according to claim 13, wherein the connection keeping module is specifically configured to: when the determining result of the determining module is yes, send an asynchronous processing request to the client, so that the client keeps the short connection within the preset polling duration.

20. A configuration information push device, comprising:

a sending module, configured to send a polling request to a server, so that the server determines whether configuration information of configuration items in the polling request is consistent with current configuration information of corresponding local configuration items, wherein the polling request comprises the configuration information of the configuration items;

a first receiving module, configured to receive a connection keeping request for keeping a short connection to the server within preset polling duration that is sent by the server, wherein the connection keeping request is sent by the server when the server determines that the configuration information of the configuration items in the polling request is respectively consistent with the current configuration information of the corresponding local configuration items;

a second receiving module, configured to receive, from the server, a push message used to push current configuration information of a target configuration item, wherein the push message is sent by the server when the server determines, in the duration of the short connection, that current configuration information of at least one target configuration item is inconsistent with configuration information of a corresponding configuration item in the polling request, and the target configuration item is a configuration item in the local configuration items; and

an update module, configured to update a configuration of the target configuration item to the current configuration information.

21. The device according to claim 20, wherein the sending module is further configured to: before the second receiving module receives, from the server, the push message used to push the current configuration information of the target configuration item, send a configuration information request to the server, wherein the configuration information request is used to request the server to deliver the current configuration information of the target configuration item.

22. The device according to claim 21, wherein the first receiving module is further configured to receive an indication message for breaking the short connection that is sent by

the server, wherein the indication message is sent by the server after the preset polling duration is reached and before the server sends the push message; and

the sending module is further configured to: after the short connection to the server is broken, re-send a polling request to the server after a preset time interval is reached.

23. The device according to any one of claims 20 to 22, wherein the connection keeping request is an asynchronous processing request used to instruct to keep the short connection to the server within the preset polling duration.

24. The device according to claim 20 or 21, wherein the sending module is further configured to: after the update module updates the configuration of the target configuration item to the current configuration information, re-send a polling request to the server after a preset time interval is reached.