



(51) International Patent Classification:

H02J 5/00 (2006.01) *H01F 38/14* (2006.01)
B60L 5/00 (2006.01)

(21) International Application Number:

PCT/EP2012/071770

(22) International Filing Date:

2 November 2012 (02.11.2012)

(25) Filing Language:

English

(26) Publication Language:

English

(30) Priority Data:

1119152.5 4 November 2011 (04.11.2011) GB

(71) Applicant: **BOMBARDIER TRANSPORTATION GMBH** [DE/DE]; Schöneberger Ufer 1, 10785 Berlin (DE).(72) Inventors: **CZAINSKI, Robert**; Waldsassener Str. 65, 12279 Berlin (DE). **WORONOWICZ, Konrad**; 5029 Fox Run Place, Kingston, Ontario K7P 0E4 (CA).(74) Agent: **BRESSEL UND PARTNER**; Potsdamer Platz10, 10785 Berlin (DE).

(81) **Designated States** (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AO, AT, AU, AZ, BA, BB, BG, BH, BN, BR, BW, BY, BZ, CA, CH, CL, CN, CO, CR, CU, CZ, DE, DK, DM, DO, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, GT, HN, HR, HU, ID, IL, IN, IS, JP, KE, KG, KM, KN, KP, KR, KZ, LA, LC, LK, LR, LS, LT, LU, LY, MA, MD, ME, MG, MK, MN, MW, MX, MY, MZ, NA, NG, NI, NO, NZ, OM, PA, PE, PG, PH, PL, PT, QA, RO, RS, RU, RW, SC, SD, SE, SG, SK, SL, SM, ST, SV, SY, TH, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, ZA, ZM, ZW.

(84) **Designated States** (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LR, LS, MW, MZ, NA, RW, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, RU, TJ, TM), European (AL, AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HR, HU, IE, IS, IT, LT, LU, LV, MC, MK, MT, NL, NO, PL, PT, RO, RS, SE, SI, SK, SM, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).


Declarations under Rule 4.17:

— of inventorship (Rule 4.17(iv))

[Continued on next page]

(54) **Title:** PROVIDING A VEHICLE WITH ELECTRIC ENERGY USING A RECEIVING DEVICE ADAPTED TO RECEIVE AN ALTERNATING ELECTROMAGNETIC FIELD

Fig. 1



(57) **Abstract:** The invention relates to an arrangement for providing a vehicle (81) with electric energy, wherein the arrangement comprises a receiving device (85) adapted to receive an alternating electromagnetic field and to produce an alternating electric current by magnetic induction, wherein the receiving device (85) comprises a plurality of phase lines, each phase line being adapted to carry a different one of a plurality of phase currents of the alternating electric current, wherein each phase line forms at least two coils (C), each coil (C) consists of at least one turn of the phase line, if any one of the coils (C) consists of one turn, the turn is turning around a central axis of the coil, if any one of the coils (C) consists of more than one turn, the turns are consecutive sections of the phase line turning around a central axis of the coil (C), the at least two coils (C) of each phase line are located next to each other so as to form a sequence (G, R, B) of coils (GCL, GCM1, GCM2, GCR; RCL, RCM1, RCM2, RCR; BCL, BCM1, BCM2, BCR) which covers an effective area in a plane that extends perpendicularly to the central axes of the coils (C), so that there are a first (GCL; RCL; BCL) and a second (GCR; RCR; BCR) end coil at the opposite ends of the sequence and optionally, in the case of three or more coils, at least one middle coil in between the end coils of the sequence, for at least one of the phase lines (9, 10, 11), the number of turns per coil of the sequence (G, R, B) of coils (GCL, GCM1, GCM2, GCR; RCL, RCM1, RCM2, RCR; BCL, BCM1, BCM2, BCR) differs.

**Published:****(88) Date of publication of the international search report:**

20 March 2014

- *with international search report (Art. 21(3))*
- *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments (Rule 48.2(h))*