

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
7 July 2005 (07.07.2005)

PCT

(10) International Publication Number
WO 2005/060720 A3

(51) International Patent Classification:
F16K 15/00 (2006.01)

(21) International Application Number:
PCT/US2004/044067

(22) International Filing Date:
16 December 2004 (16.12.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
10/741,566 19 December 2003 (19.12.2003) US

(71) Applicant (for all designated States except US): **QUALITROL CORPORATION** [US/US]; 1385 Fairport Road, Fairport, NY 14450-1309 (US).

(72) Inventor: **HERZ, Joshua, J.**; 281 Barrington Street, Rochester, NY 14607 (US).

(74) Agents: **SALAI, Stephen, B.** et al.; Harter, Secrest & Emery LLP, 1600 Bausch & Lomb Place, Rochester, NY 14604-2711 (US).

(81) Designated States (unless otherwise indicated, for every kind of national protection available): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,

CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG, PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SM, SY, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM, ZW.

(84) Designated States (unless otherwise indicated, for every kind of regional protection available): ARIPO (BW, GH, GM, KE, LS, MW, MZ, NA, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR, GB, GR, HU, IE, IS, IT, LT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Declaration under Rule 4.17:

— as to applicant's entitlement to apply for and be granted a patent (Rule 4.17(ii))

Published:


— with international search report
— before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments

(88) Date of publication of the international search report:

1 June 2006

[Continued on next page]

(54) Title: PRESSURE RELIEF DEVICE WITH INCREASED FLOW RATE



(57) Abstract: A pressure relief device (50) for electrical equipment housing (52), includes a valve body (70) having a pedestal (72) that projects above a mounting flange (56) and a table (74) on the pedestal (72) that supports a two-stage valve assembly (82) that can be sized in diameter independently of the working area (62) of the flange (56) beneath the table (74). The design is particularly applicable to retrofit applications for large power distribution equipment with the footprint of the pressure relief device fixed by the design of the equipment housings. The first-stage valve opening (96) can be sized substantially as large as vent openings (54) in the housings (52) and the second-stage valve openings (98) can be sized in the desired relationship with the first-stage opening (96) for optimizing valve performance independently of the constraints imposed by the footprint of the device.

WO 2005/060720 A3



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.