Error correction encoding a data stream of information.

This Sheet Has Been Replaced

The invention relates to an apparatus for error correction encoding a data stream of information into blocks of error correction encoded information, the apparatus comprising:
- input means for receiving the data stream of information,
- error correction encoding means for carrying out an error correction encoding step on portions of said data stream of information so as to obtain said blocks of error correction encoded information, a block of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word and a portion of said error correction encoded information, where n is a positive integer larger than 3,
- output means for supplying said blocks of error correction encoded information. Such an apparatus is known from WO 96/31880.

The known apparatus discloses the generation of different sync words for the sync blocks in a block of error correction encoded information. This enables the identification of the position of a sync block within a block of error correction encoded information. In spite of this, errors occur after receiving the error correction encoded information that can not be corrected for in the error correction step normally available in the receiver.

The invention aims at improving the error correction capability.

In accordance with the invention, the apparatus as defined in the introductory paragraph is characterized in that the error correction encoding means are adapted to supply one of m mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that the sequence of two sync words of two subsequent sync blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of error correction encoded information, m being an integer for which holds $2 < m < n$.

The invention is based on the following recognition. Sync words used for identifying the sync blocks are generally unique bit patterns that do not occur elsewhere in the

serial data stream of information. A further aim is to uniquely identify the exact position of a sync block in the array of n sync blocks in the blocks of error correction encoded information. This requires a plurality of mutually different sync words. It should further be noted that the error correction capability increases for increasing size of the blocks of error correction encoded information: that means for an increasing number of sync blocks in a block of error correction encoded information. Identifying each sync block separately would mean as many sync words as there are sync blocks in a block of error correction encoded information. In accordance with the invention, with the requirement that the sequence of two sync words of two subsequent sync blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of error correction encoded information, less mutually different sync words are needed, so that more words are available for the information itself, whilst moreover improving the error correction capability.

The apparatus as defined in the opening paragraph may also be characterized in that the error correction encoding means are adapted to supply one of m mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by one sync block is unique for each group of two sync blocks in the block of error correction encoded information, said two sync blocks being separated from each other by one sync block, m being an integer for which holds $2 < m < n$. This enables a reliable determination of the position of the sync block detected, even in the case that the sync word of this sync block was missed.

The apparatus as defined in the opening paragraph may also be characterized in that the error correction encoding means are adapted to supply one of m mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks is unique for each group of two sync blocks in the block of error correction encoded information, said two sync blocks being separated from each other by two sync blocks, m being an integer for which holds $3 < m < n$.. This enables a reliable determination of the position of the sync block detected, even in the case that the sync word of this sync block and the sync word of the preceding or the next sync block was missed.

This Sheet Has Been Replaced

These and other aspects of the invention will be apparent from and further elucidated with respect to embodiments described in the following figure description, in which

figure 1 shows a block of error correction encoded information, including sync blocks of information,

figure 2 shows an embodiment of the error correction encoding apparatus, and figure 3 shows an embodiment of an error correction apparatus.

Figure 1 shows a block 10 of error correction encoded information obtained from carrying out an error correction encoding step, generally known in the art, on a portion of the incoming data stream of information. The block 10 comprises n sync blocks, denoted SB_1, SB_2, ..., SB_{n-1}, SB_n. Each sync block comprises a sync word, included in the first part FP1 in each of the sync blocks and the remaining part FP2 of the sync blocks is used for storing portions of the error correction encoded information in. A limited number of m mutually different sync words are used for incorporation into the first parts FP1 of each of the sync blocks.

In an embodiment of the block of error correction encoded information, it is assumed that n=31 and that 7 mutually different sync words are used for incorporation in the first parts FP1 of the 31 sync blocks.

In the table given below, the sync words for the 31sync blocks of the block of error correction encoded information are given for four different embodiments. In all embodiments, 7 mutually different sync words are available, sw0 to sw6. As can be seen, in each embodiment, the sync word sw0 is used for the first sync block of the block of error correction encoded information. The other sync words are used to identify the sync blocks numbered 2 to 31 in the block of error correction encoded information.

This Sheet Has Been Replaced




Table 1: various sequences of sync words

Sync block sequence no.	Sync word 1st embodiment	Sync word 2nd embodiment	Sync word 3rd embodiment	Sync word 4th embodiment
1	sw0	sw0	sw0	sw0
2	sw1	sw1	sw1	sw1
3	sw1	sw2	sw2	sw2
4	sw2	sw2	sw3	sw3
5	sw3	sw3	sw2	sw3
6	sw2	sw1	sw4	sw1
7	sw4	sw3	sw4	sw4
8	sw5	sw4	sw2	sw1
9	sw5	sw4	sw5	sw5
10	sw4	sw5	sw3	sw5
11	sw3	sw3	sw5	sw4
12	sw4	sw5	sw6	sw3
13	sw6	sw1	sw6	sw4
14	sw2	sw1	sw5	sw6
15	sw2	sw6	sw4	sw6
16	sw6	sw5	sw3	sw3
17	sw3	sw6	sw4	sw5
18	sw6	sw3	sw1	sw3
19	sw1	sw3	sw1	sw2
20	sw4	sw2	sw4	sw2
21	sw4	sw6	sw6	sw5
22	sw1	sw2	sw3	sw6
23	sw3	sw5	sw6	sw5
24	sw1	sw5	sw2	sw1
25	sw5	sw4	sw2	sw1
26	sw6	sw2	sw6	sw6
27	sw6	sw4	sw1	sw2
28	sw5	sw6	sw3	sw6
29	sw3	sw6	sw1	sw4
30	sw5	sw1	sw5	sw4
31	sw2	sw4	sw5	sw2

It is submitted that the apparatus of the invention generates the blocks of error correction encoded information in accordance with the array of sync words in one of the columns given below.

From the examples given above, it is clear that the array of sync words satisfy the following rules:

1. A sequence of two sync words of two subsequent sync blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of

error correction encoded information. An example: in the first embodiment, the sync words of the sync blocks SB_{27} and SB_{28} are sw6 and sw5. This sequence of two sync words occurs only once in the sequence of 31 sync words. Further, preferably, also the sequence of the last sync word in a block of error correction encoded information and the first sync word in the next block of error correction encoded information is unique.

2. Each time two sync words of two sync blocks in the block of error correction encoded information being separated from each other by one sync block is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by one sync block. An example: in the second embodiment, the sync words of the sync blocks SB_{13} and SB_{15} are sw1 and sw6. This sequence of two sync words occurs only once for sync words of sync blocks being separated from each other by one sync block in the block of error correction encoded information. This requirement is preferably also valid across the boundary between two subsequent blocks of error correction encoded information.

3. Each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks. An example: in the third embodiment, the sync words of the sync blocks SB_2 and SB_5 are sw1 and sw2. This sequence of two sync words occurs only once for sync words of sync blocks separated from each other by two sync blocks in the block of error correction encoded information.

This requirement is preferably also valid across the boundary between two subsequent blocks of error correction encoded information.

4. Each time two sync words of two sync blocks in the block of error correction encoded information being separated from each other by three sync blocks is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by three sync blocks. An example: in the fourth embodiment, the sync words of the sync blocks SB_{20} and SB_{24} are sw2 and sw1. This sequence of two sync words occurs only once for sync words of sync blocks separated from each other by three sync blocks in the block of error correction encoded information. This requirement is preferably also valid across the boundary between two subsequent blocks of error correction encoded information.

During reception of a data stream comprising an array of blocks of error correction encoded information, subsequent sync blocks of information are received. Three subsequent sync blocks, defined as SB_{i-2}, SB_{i-1}, SB_i , SB_{i+1} and SB_{i+2}, have sync words defined as sw_a, sw_b, sw_c, sw_d and sw_e, respectively.

This Sheet Has Been Replaced

Suppose that, upon reception, the sync word of the sync block SB_i is distorted and cannot be identified. Assuming that the sync words sw_b and sw_d equal both sw2, and further assuming that the sync words satisfy the array of sync words in accordance with the first embodiment, it can be established that the distorted sync word was sw3, and that the sync block of this distorted sync word was the sync block SB5. It is now possible to store the data included in this sync block in the correct position in an error correction memory included in a receiver, so that an error correction step can be carried out on the data stored in the memory.

Suppose that, upon reception, the sync words of the sync blocks SB_i and SB_{i+1} are distorted and cannot be identified. Assuming that the sync words sw_b and sw_e equal sw3 and sw1, and further assuming that the sync words satisfy the array of sync words in accordance with the second embodiment, it can be established that the distorted sync words were sw5 and sw1 and that the sync blocks of the distorted sync words were the sync blocks SB12 and SB13, respectively. It is now possible to store the data included in these sync blocks in the correct position in an error correction memory included in a receiver, so that an error correction step can be carried out on the data stored in the memory.

Suppose that, upon reception, the sync words of the sync blocks SB_{i-1}, SB_i and SB_{i+1} are distorted and cannot be identified. Assuming that the sync words sw_a and sw_e equal sw1 and sw5, and further assuming that the sync words satisfy the array of sync words in accordance with the third embodiment, it can be established that the distorted sync words were sw3, sw1 and sw5 and that the sync blocks of the distorted sync words were the sync blocks SB28, SB29 and SB30, respectively. It is now possible to store the data included in these sync blocks in the correct position in an error correction memory included in a receiver, so that an error correction step can be carried out on the data stored in the memory.

It will be clear that, where necessary, this can be extended in order to correct for more than three distorted sync words.

Figure 2 shows schematically an embodiment of the apparatus in accordance with the invention. The apparatus for error correction encoding a data stream of information into blocks of error correction encoded information, comprises an input terminal 20 for receiving the data stream of information. The input terminal 20 is coupled to an input of a signal processing unit 22. The unit 22 is capable of carrying out an error correction encoding step, well known in the art, on the incoming data stream. Further, the unit 22 may be capable of carrying out a channel encoding step, well known in the art, either prior to, but generally after, the error correction encoding step, on the incoming data stream. An error correction encoded data stream of information is supplied to an output terminal 24. Further, a generator

This Sheet Has Been Replaced



unit 26 is available for supplying the plurality of m mutually different sync words. The unit 26 could be in the form of a memory in which the m mutually different sync words are stored. Generation of a sync word can be realized by addressing a memory location in the memory by means of an address signal generated by a microprocessor unit 28 and supplied via the line 30. The unit 28 further supplies a control signal via the line 32 to the processing unit 22 to control the functioning of the unit 22.

The error correction encoding unit 22 generates blocks of error correction encoded information in response to said error correction encoding step carried out a portions of said data stream of information. As an example, a block of v times w data words of the serial data stream of information is subjected to an error correction encoding step, resulting in the generation of 'horizontal' parity words and 'vertical' parity words. The parity words are arranged such that bocks of error correction encoded data are created comprising n times m data words. The n arrays of m data words each fit in the right hand portion of figure 1, indicated by FP2 for each of the n sync blocks. Each sync block further comprises a sync word. n is a positive integer larger than 3.

The error correction encoding unit 22 is further adapted to supply one of the m mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that the sequence of two sync words of two subsequent sync blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of error correction encoded information, m being an integer for which holds $2 < m < n$.

In another embodiment, the error correction encoding unit 22 is further adapted to supply one of the m mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information being separated one sync block apart from each other is unique for each group of two sync blocks in the block of error correction encoded information being separated one sync block apart, m being an integer for which holds $2 < m < n$.

In again another embodiment, the error correction encoding unit 22 is further adapted to supply one of m mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated two sync blocks apart from each other is unique for each group of two sync blocks in the block of error correction

This Sheet Has Been Replaced



encoded information separated two sync blocks apart from each other, m being an integer for which holds $3 < m < n$. n should be larger than 4 in this case.

All above requirements could also be valid across the boundary between two subsequent blocks of error correction encoded information.

It should further be noted that the apparatus may be provided with a channel encoding unit 40 for carrying out a channel encoding step on the information prior to eg. recording the error correction encoded data on a record carrier 44, such as a magnetic record carrier, or an optical record carrier 46. The channel encoding step is well known in the art. The step of adding the sync words may be carried out in the channel encoding unit 40, instead of in the error correction encoding unit 22.

It should be noted here that the various requirements described above for the application of the mutually different sync words to the various sync blocks could be combined into one and the same embodiment of the apparatus in accordance with the invention.

Figure 3 shows an error correction apparatus, provided with an input terminal 50 for receiving the blocks of error correction encoded information. Those blocks of error correction encoded information may have been obtained from reading information from a record carrier, such as the magnetic record carrier 44 or the optical record carrier 46, by means of a reading unit and after having carried out a channel decoding step on the information read from the record carrier in a channel decoding unit 52.

An error correction unit 56 is available for carrying out an error correction step on blocks of error correction encoded information included in the signal supplied via the terminal 50, so as to obtain blocks of error corrected information. The blocks of error corrected information are supplied to an output terminal 58 as a serial data stream of information. The apparatus is provided with a detection unit 60 for detecting m mutually different sync words, where m is an integer smaller than n. More specifically, the detection unit 60 is adapted to detect two sync words in the blocks of error correction encoded information, said two sync words being the sync words of the i^{th} and j^{th} sync block in a block of error correction encoded information. The sync words detected are stored in a memory 62. This memory has at least three memory locations for storing the sync words detected for three subsequent sync blocks in a block of error correction encoded information. When having detected two subsequent sync words of two subsequent sync blocks i and j in a block of information, the apparatus is capable of identifying the position of the said i^{th} and j^{th} sync block in said block of error correction encoded information. This is realized by means of a converter unit 64, which is capable of converting the sequence of two directly successive sync

This Sheet Has Been Replaced



words into a position information, indicating the position of the two sync blocks in the block of error correction encoded information.

The memory 62 has p memory locations for storing the sync words of p subsequent sync blocks, where p equals 3 or larger. In the case of p=3, the sync word in the second memory location may be erroneous, or could not be detected at all. Again the position of this central sync block of the three successive sync blocks corresponding to the three sync words in the memory 62 can be established in the converter unit 64, using the sync words in the first and third memory location of the memory 62.

In the case of p=4, the sync words in the second and/or third memory location of the memory 62 may be erroneous, or could not be detected at all. Again the position of this second and/or third sync block of the four successive sync blocks corresponding to the four sync words in the memory 62 can be established in the converter unit 64, using the sync words in the first and fourth memory location of the memory 62.

In the case of p=5, the sync words in the second and/or third and/or fourth memory location of the memory 62 may be erroneous, or could not be detected at all. Again the position of this second and/or third and/or fourth sync block of the five successive sync blocks corresponding to the five sync words in the memory 62 can be established in the converter unit 64, using the sync words in the first and fifth memory location of the memory 62.

Next, a different approach for determining the row number within a block from the sync numbers will be given. Use will be made of the sequence of sync words as listed in embodiment 4 in the previous table 1.

- Suppose two sync numbers S_R and S_{R-d} have been detected, where R is the unknown row number and d is the (known) distance between the syncs.
- It appears to be convenient to remap the sync numbers (see columns 4 and 5 of table 2) and to divide the total block of 31 sync blocks into 6 sub blocks of 5 rows and row 0. Now the sync numbers show a regular structure (as shown in column 6 of table 2). Sync S0 disturbs the regular structure, which has to be accounted for (dark gray areas in columns 8 to 10 in table 2). Note that all additions in table 2 are done modulo 6.

Next, follows the procedure to determine the row number in the total block from two sync numbers and their distance:

1. Check for special cases: $S_R = 0$ (before remapping)
   $S_R = 2$ and $S_{R-4} = 5$ (after remapping, only when $d = 4$)
2. Calculate the difference $\Delta = S_R - S_{R-d}$ (modulo 6)

This Sheet Has Been Replaced

3. Determine the relative row number r with the appropriate lookup table (see table 3)

4. Calculate n_b. This is also the sub block number b

5. Calculate the absolute row number: $R = 5*b + r + 1$

With a brute force lookup table one would need 8 input bits (2 x 3 bits for the sync numbers and 2 bits for the distance) and 5 output bits. When this table is implemented in a ROM 1280 bits are required.

With the method described above 5 lookup tables (4 shown in table 3 and one to do the remapping of the sync numbers) with 3 input bits and 3 output bits are necessary. This requires 135 ROM bits plus some additional logic.

This Sheet Has Been Replaced

Table 2: Overview

sub block number	Absolute row number	relative row number	Sync number	Remapped Sync number		Difference $\Delta = S_R - S_{R-d}$ Distance (d)			
b	R	r	S_R		n_b	1	2	3	4
	0		0	5					
0	1	0	1	0	$n_0 = 0$	1	0	5	5
	2	1	2	5	n_0+5	5	0	0	4
	3	2	3	2	n_0+2	3	2	3	3
	4	3	3	2	n_0+2	0	3	2	3
	5	4	1	0	n_0	4	4	1	0
1	6	0	4	1	$n_1 = 1$	1	5	5	2
	7	1	1	0	n_1+5	5	0	4	4
	8	2	5	3	n_1+2	3	2	3	1
	9	3	5	3	n_1+2	0	3	2	3
	10	4	4	1	n_1	4	4	1	0
2	11	0	3	2	$n_2 = 2$	1	5	5	2
	12	1	4	1	n_2+5	5	0	4	4
	13	2	6	4	n_2+2	3	2	3	1
	14	3	6	4	n_2+2	0	3	2	3
	15	4	3	2	n_2	4	4	1	0
3	16	0	5	3	$n_3 = 3$	1	5	5	2
	17	1	3	2	n_3+5	5	0	4	4
	18	2	2	5	n_3+2	3	2	3	1
	19	3	2	5	n_3+2	0	3	2	3
	20	4	5	3	n_3	4	4	1	0
4	21	0	6	4	$n_4 = 4$	1	5	5	2
	22	1	5	3	n_4+5	5	0	4	4
	23	2	1	0	n_4+2	3	2	3	1
	24	3	1	0	n_4+2	0	3	2	3
	25	4	6	4	n_4	4	4	1	0
5	26	0	2	5	$n_5 = 5$	1	5	5	2
	27	1	6	4	n_5+5	5	0	4	4
	28	2	4	1	n_5+2	3	2	3	1
	29	3	4	1	n_5+2	0	3	2	3
	30	4	2	5	n_5	4	4	1	0

This Sheet Has Been Replaced

Table 3 : Lookup tables that map the difference Δ to the relative row number r

d = 1	
r	Δ
0	1
1	5
2	3
3	0
4	4

(a)

d = 2	
r	Δ
0	5, 1
1	0
2	2
3	3
4	4

(b)

d = 3	
r	Δ
0	5
1	4, 0
2	3
3	2
4	1

(c)

d = 4	
r	Δ
0	2, 5
1	4
2	1
3	3
4	1

(d)

Whilst the invention has been described with reference to preferred embodiments thereof, it is to be understood that these are not limitative examples. Thus, various modifications may become apparent to those skilled in the art, without departing from the scope of the invention, as defined by the claims. Further, any reference signs do not limit the scope of the claims. The invention, as far as incorporated in the error correction encoding apparatus, can be implemented by means of both hardware and software, and several "means" may be represented by the same item of hardware. The word 'comprising' does not exclude the presence of other elements or steps than those listed in a claim. Also, the word "a" or "an" preceding an element does not exclude the presence of a plurality of such elements. In addition, the invention lies in each and every novel feature or combination of features.

This Sheet Has Been Replaced

CLAIMS:

This Sheet Has Been Replaced

1. Apparatus for error correction encoding a data stream of information into blocks of error correction encoded information, the apparatus comprising:
- input means for receiving the data stream of information,
- error correction encoding means for carrying out an error correction encoding step on portions of said data stream of information so as to obtain said blocks of error correction encoded information, a block of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word and a portion of said error correction encoded information, where n is a positive integer larger than 3,
- output means for supplying said blocks of error correction encoded information,
characterized in that the error correction encoding means are adapted to supply one of m mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that the sequence of two sync words of two subsequent sync blocks in the block of error correction encoded information is unique for each two subsequent sync blocks in the block of error correction encoded information, m being an integer for which holds $2 < m < n$.

2. Apparatus for error correction encoding a data stream of information into blocks of error correction encoded information, the apparatus comprising:
- input means for receiving the data stream of information,
- error correction encoding means for carrying out an error correction encoding step on portions of said data stream of information so as to obtain said blocks of error correction encoded information, a block of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word and a portion of said error correction encoded information, where n is a positive integer larger than 3,
- output means for supplying said blocks of error correction encoded information,
characterized in that the error correction encoding means are adapted to supply one of m mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by one sync block is unique

for each group of two sync blocks in the block of error correction encoded information, said two sync blocks being separated from each other by one sync block, m being an integer for which holds $2 < m < n$.

3. Apparatus as claimed in claim 1, characterized in that the error correction encoding means are further adapted to supply sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by one sync block is unique for each group of two sync blocks in the block of error correction encoded information, said two sync blocks being separated from each other by one sync block.

4. Apparatus for error correction encoding a data stream of information into blocks of error correction encoded information, the apparatus comprising:
- input means for receiving the data stream of information,
- error correction encoding means for carrying out an error correction encoding step on portions of said data stream of information so as to obtain said blocks of error correction encoded information, a block of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word and a portion of said error correction encoded information, where n is a positive integer larger than 4,
- output means for supplying said blocks of error correction encoded information, characterized in that the error correction encoding means are adapted to supply one of m mutually different sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks is unique for each group of two sync blocks in the block of error correction encoded information, said two sync blocks being separated from each other by two sync blocks, m being an integer for which holds $3 < m < n$.

5. Apparatus as claimed in claim 1 or 2, characterized in that the error correction encoding means are further adapted to supply sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by two sync blocks.

This Sheet Has Been Replaced

6. Apparatus as claimed in claim 1, characterized in that the error correction encoding means are further adapted to supply sync words to each of said n sync blocks in said block of error correction encoded information, such that each time two sync words of two sync blocks in the block of error correction encoded information separated from each other by p sync blocks is unique for each group of two sync blocks in the block of error correction encoded information separated from each other by p sync blocks apart from each other, where p is an integer larger than 2.

7. Apparatus as claimed in claim 1, 2 or 4, characterized in that the error correction encoding means are further adapted to supply a specific one of said m sync words only to the first sync block of said n sync blocks in each of said blocks of error correction encoded information.

8. Apparatus as claimed in claim 1, 2 or 4, characterized in that the error correction encoding means are further adapted to carry out a channel encoding step on either the data stream of information or on the error correction encoded data stream of information.

9. Apparatus as claimed in claim 1, 2 or 4, characterized in that it further comprises means for writing said blocks of error correction encoded information on a record carrier.

10. Apparatus as claimed in claim 1, 2 or 4, characterized in that in that the error correction encoding means are adapted to supply a sync word to each of said n sync blocks in said block of error correction encoded information, such that the sequence of two sync words of the last sync block in the block of error correction encoded information and the first sync block in the next block of error correction encoded information is unique for each two subsequent sync blocks in the said two blocks of error correction encoded information.

11. Apparatus as claimed in claim 1, 2 or 4, characterized in that the error correction encoding means are adapted to supply a sync word to each of said n sync blocks in said block of error correction encoded information, such that a group of two sync words, one sync block in the block of error correction encoded information and the other in the next block of error correction encoded information and being separated by q sync blocks is unique for

This Sheet Has Been Replaced

each group of two sync blocks in the two blocks of error correction encoded information, said two sync blocks being separated from each other by q sync blocks, where q is an integer larger than 1.

12. Method for carrying out the error correction encoding in the apparatus as claimed in claim 1, 2, 4, 8 or 9.

13. Record carrier having blocks of error correction encoded information recorded in a track on said record carrier, obtained with the apparatus as claimed in claim 9.

14. Apparatus for error correcting blocks of error correction encoded information into a serial data stream of information, a block of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word and a portion of said error correction encoded information, where n is a positive integer larger than 3, the apparatus comprising:

- input means for receiving the blocks of error correction encoded information,
- error correction means for carrying out an error correction step on said blocks of error correction encoded information so as to obtain blocks of error corrected information,
- output means for supplying said blocks of error corrected information as a serial data stream of information,

characterized in that said error correction means is adapted to detect m mutually different sync words, where m is an integer smaller than n, the error correction means comprising detection means for detecting two sync words in the blocks of error correction encoded information, said two sync words being the sync words of the i^{th} and j^{th} sync block in a block of error correction encoded information, so as to identify the position of the said i^{th} and j^{th} sync block in said block of error correction encoded information.

15. Apparatus for error correcting blocks of error correction encoded information into a serial data stream of information, a block of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word and a portion of said error correction encoded information, where n is a positive integer larger than 3, the apparatus comprising:

- input means for receiving the blocks of error correction encoded information,

This Sheet Has Been Replaced





- error correction means for carrying out an error correction step on said blocks of error correction encoded information so as to obtain blocks of error corrected information,
- output means for supplying said blocks of error corrected information as a serial data stream of information,

characterized in that said error correction means is adapted to detect m mutually different sync words, where m is an integer smaller than n, the error correction means comprising detection means for detecting p sync words of p subsequent sync blocks in a block of error correction encoded information, where p is an integer larger than 2, the detection means being adapted to identify the position of the at least one central sync block of said p subsequent sync blocks using the detected sync words of the first and last sync blocks of the said p subsequent sync blocks in said block of error correction encoded information.

16. Apparatus for error correcting blocks of error correction encoded information into a serial data stream of information, a block of error correction encoded information comprising a plurality of n sync blocks, each sync block comprising a sync word and a portion of said error correction encoded information, where n is a positive integer larger than 3, the apparatus comprising:

- input means for receiving the blocks of error correction encoded information,
- error correction means for carrying out an error correction step on said blocks of error correction encoded information so as to obtain blocks of error corrected information,
- output means for supplying said blocks of error corrected information as a serial data stream of information,

characterized in that said error correction means is adapted to detect m mutually different sync words, where m is an integer smaller than n, the error correction means comprising detection means for detecting two sync words in the blocks of error correction encoded information and the distance between said two sync words, expressed in numbers of sync blocks, said two sync words being the sync words of the i^{th} and j^{th} sync block in a block of error correction encoded information, so as to identify the position of the said i^{th} and j^{th} sync block in said block of error correction encoded information, using said two sync words detected and said distance.

17. Apparatus as claimed in claim 16, characterized in that said identifying step for identifying said position makes use of a conversion table.

This Sheet Has Been Replaced



