

REPEATING METHOD OF WIRELESS REPEATING DEVICE, AND WIRELESS REPEATING DEVICE

FIELD OF THE INVENTION

[0001] The present invention relates to the field of communications technologies, and in particular, to a repeating method of a wireless repeating device, and a wireless repeating device.

BACKGROUND OF THE INVENTION

[0002] With the rapid development of wireless broadband Internet access services, wireless home gateway products develop rapidly. However, a physical layout of high-power wireless local area network (Wireless Local Area Network, WLAN) devices has certain limitations and a penetration capability of wireless broadband (wireless fidelity, WIFI) signals is weak, which result in that there are certain blind areas in WIFI signal coverage, and therefore, development opportunities are brought to a WLAN signal repeating device WLAN Repeater. A WLAN Repeater includes a WLAN access point side (Access Point, AP) and a WLAN client side Client, where the WLAN AP side of the WLAN Repeater may receive access of a station (Station, STA) device, and the WLAN Client side may be used an STA to connect to another AP, which is as a good extension of WIFI signals, to effectively solve a coverage problem of the WIFI signals. Currently, for a WLAN Repeater product on the market, when data transmission is performed by a downstream interface (a WLAN AP interface) and an upstream interface (a WLAN Client interface), a wireless STA MAC address attached to a WLAN AP side is replaced with a MAC address of a WLAN Client side of the Repeater itself. Therefore, an existing Repeater product is not a WIFI signal repeater in a real sense.

[0003] However, in a scenario of WLAN coverage based on MAC address authentication/accounting, for example, in a scenario of enterprise-level WLAN (AP/AC) coverage based on AAA authentication and accounting or portal authentication, if the existing WLAN Repeater is adopted, an accounting party or an authentication party can perform accounting for an address of a WLAN Client of the WLAN Repeater only, and cannot perform accounting for an STA MAC address of each attached STA separately. Therefore, the existing WLAN Repeater cannot meet a requirement of unified authentication/accounting based on a MAC address.

SUMMARY OF THE INVENTION

[0004] An objective of embodiments of the present invention is to provide a repeating method of a wireless repeating device, so as to solve a problem that a WLAN Repeater in the prior art cannot meet a requirement of unified authentication/accounting based on a MAC address.

5 **[0005]** An embodiment of the present invention is implemented in this manner: a repeating method of a wireless repeating device, where the method includes the following steps:

synchronizing network connection information of an upstream AP to a downstream WLAN AP interface of the wireless repeating device after the wireless repeating device establishes a connection with the upstream AP;

10 obtaining, according to the downstream WLAN AP interface corresponding to the synchronized upstream AP, downstream wireless STA MAC address information, and establishing an upstream WLAN Client interface which is in a mapping relationship with an STA MAC address; and

performing, according to the mapping relationship between the STA MAC address and
15 the established upstream WLAN Client interface, management on data forwarded between the upstream AP and a downstream wireless STA.

[0006] An embodiment of the present invention further provides a wireless repeating device, where the wireless repeating device includes:

a synchronizing unit, configured to, synchronize network connection information of an
20 upstream AP to a downstream WLAN AP interface of the wireless repeating device after the wireless repeating device establishes a connection with the upstream AP;

a mapping unit, configured to obtain, according to the downstream WLAN AP interface corresponding to the synchronized upstream AP, downstream wireless STA MAC address information, and establish an upstream WLAN Client interface which is in a mapping relationship
25 with an STA MAC address; and

a data management unit, configured to perform, according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, management on data forwarded between the upstream AP and a downstream wireless STA.

[0007] In the embodiments, the network connection information of the upstream AP is
30 synchronized to the downstream WLAN AP interface, and the upstream WLAN Client interface in the mapping relationship with the STA MAC address is established; and based on the foregoing mapping relationship, the management is performed on the data forwarded between the upstream AP and the downstream wireless STA, thereby implementing effective transparent transmission of

an attached wireless STA MAC address. Therefore, for corresponding actions of authentication and accounting performed by an upstream AAA authentication party or accounting party on the upstream WLAN Client interface through the upstream AP, all the corresponding actions may be performed by a downstream WLAN AP interface proxy corresponding to the upstream AP, and a certain downstream STA. In this manner, it is achieved that the authentication or accounting party may perform accounting on an STA MAC address of each attached STA separately, thereby meeting the requirement of the unified authentication/accounting based on the MAC address.

BRIEF DESCRIPTION OF THE DRAWINGS

[0008] In order to illustrate the technical solutions in embodiments of the present invention more clearly, accompanying drawings required for describing the embodiments or the prior art are briefly introduced below. Obviously, the accompanying drawings in the following description are only some embodiments of the present invention, and persons of ordinary skill in the art may further obtain other drawings according to the accompanying drawings without creative efforts.

[0009] FIG. 1 is a structural diagram of a system in an application scenario according to Embodiment 1 of the present invention;

[0010] FIG. 2 is a flowchart of implementing a repeating method of a wireless repeating device according to Embodiment 1 of the present invention;

[0011] FIG. 3 is a flowchart of implementing a repeating method of a wireless repeating device according to Embodiment 2 of the present invention;

[0012] FIG. 4 is an implementation flowchart of an implementation example of the repeating method of the wireless repeating device according to Embodiment 2 of the present invention;

[0013] FIG. 5 is a structural diagram of a wireless repeating device according to Embodiment 3 of the present invention; and

[0014] FIG. 6 is a structural diagram of a wireless repeating device according to Embodiment 4 of the present invention.

DETAILED DESCRIPTION OF THE EMBODIMENTS

[0015] To make the objective, technical solutions, and advantages of the present invention clearer, the following further describes the present invention in detail with reference to the accompanying drawings and embodiments. It should be understandable that the specific embodiments to be described are only used to explain the present invention and are not intended to

limit the present invention.

[0016] In the embodiments, by synchronizing network connection information of an upstream AP to a downstream WLAN AP interface of a wireless repeating device and establishing an upstream WLAN Client interface which is in a mapping relationship with an STA MAC address of a downstream STA, effective transparent transmission of an attached wireless STA MAC address is implemented.

[0017] An embodiment of the present invention provides a repeating method of a wireless repeating device, where the method includes the following steps:

synchronizing network connection information of an upstream AP to a downstream WLAN AP interface of the wireless repeating device after the wireless repeating device establishes a connection with the upstream AP;

obtaining, according to the downstream WLAN AP interface corresponding to the synchronized upstream AP, downstream wireless STA MAC address information, and establishing an upstream WLAN Client interface which is in a mapping relationship with an STA MAC address; and

performing, according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, management on data forwarded between the upstream AP and a downstream wireless STA, where the data is management action data or service data.

[0018] An embodiment of the present invention further provides a wireless repeating device, where the wireless repeating device includes:

a synchronizing unit, configured to, synchronize network connection information of an upstream AP to a downstream WLAN AP interface of the wireless repeating device after the wireless repeating device establishes a connection with the upstream AP;

a mapping unit, configured to obtain, according to the downstream WLAN AP interface corresponding to the synchronized upstream AP, downstream wireless STA MAC address information, and establish an upstream WLAN Client interface which is in a mapping relationship with an STA MAC address; and

a data management unit, configured to perform, according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, management on data forwarded between the upstream AP and a downstream wireless STA, where the data is management action data or service data.

[0019] The implementation of the present invention is described below in detail with reference to specific embodiments.

Embodiment 1

[0020] A structural diagram of a system in an application scenario of the present invention is as shown in FIG. 1. The system includes multiple upstream APs: AP1, AP2, AP3, ..., APn, multiple downstream wireless stations: STA1, STA2, STA3, ..., STAm, where both m and n are nonzero positive integers, and a wireless repeating device. The wireless repeating device may include multiple virtual upstream WLAN Client interfaces and multiple virtual downstream WLAN AP interfaces, where the wireless repeating device accesses an upstream AP through an upstream WLAN Client interface, a downstream STA establishes a connection with a downstream WLAN AP interface of the wireless repeating device, and the wireless repeating device may implement transparent transmission of an attached STA MAC address and forwarding of a management flow and data flow between multiple virtual upstream and downstream interfaces. A working process of the wireless repeating device specifically includes: initialization of multiple SSIDs, wireless STA MAC mapping, dynamic management of upstream and downstream interfaces, and forwarding of service data flows of upstream and downstream interfaces. A repeating method of the wireless repeating device is described below through an embodiment, FIG. 2 is a flowchart of implementing a repeating method of a wireless repeating device according to Embodiment 1 of the present invention, and details are described below:

[0021] In step S201, network connection information of an upstream AP is synchronized to a downstream WLAN AP interface of the wireless repeating device after the wireless repeating device establishes a connection with the upstream AP.

[0022] In this embodiment, when the number of the upstream APs is one, network connection information of the one upstream AP is synchronized to one downstream WLAN AP interface; when the number of the upstream APs is multiple, network connection information of the multiple upstream APs is synchronized to multiple downstream WLAN AP interfaces, where the upstream APs may be multiple APs in different encryption/authentication modes.

[0023] In step S202, downstream wireless STA MAC address information is obtained according to the downstream WLAN AP interface corresponding to the synchronized upstream AP, and an upstream WLAN Client interface in a mapping relationship with an STA MAC address is established.

[0024] In this embodiment, the mapping relationship between the STA MAC address and the established upstream WLAN Client interface is a reversible single mapping relationship.

[0025] In step S203, management is performed, according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, on data forwarded

between the upstream AP and a downstream wireless STA, where the data is management action data or service data.

[0026] In this embodiment, management actions may be associate (Associate), authenticate (Authenticate), disassociate notify (Disassociate notify), deauthenticate notify (Deauthenticate notify), and reassociate (Reassociate).

[0027] In this embodiment, the network connection information of the upstream AP is synchronized to the downstream WLAN AP interface, and the upstream WLAN Client interface in the mapping relationship with the STA MAC address is established; based on the foregoing mapping relationship, for actions of operations performed on a data flow or management flow between the upstream AP and the upstream WLAN Client interface, all the actions may be performed by a downstream WLAN AP interface proxy corresponding to the upstream AP interface, and a certain downstream STA, where the downstream STA may be searched for through the mapping relationship between the STA MAC address and the upstream WLAN Client interface, thereby achieving effective transparent transmission of the attached wireless STA MAC address.

Therefore, for corresponding actions of authentication and accounting performed by an upstream AAA authentication party or accounting party on the upstream WLAN Client interface through the upstream AP, all the corresponding actions may be performed by a downstream WLAN AP interface proxy corresponding to the upstream AP, and a certain downstream STA. In this manner, it is achieved that the AAA authentication or accounting party may perform accounting on an STA MAC address of each attached STA separately, thereby meeting a requirement of unified authentication/accounting based on a MAC address. Meanwhile, when a WLAN Repeater is interconnected with some upstream gateway devices with enabled DHCP spoofing/flooding functions, a DHCP Server of an upstream device may still implement normal functions such as IP address assignment or lease renewing, and an STA at a WLAN Client side may obtain a corresponding IP address and continue with Internet access.

Embodiment 2

[0028] FIG. 3 is a flowchart of implementing a repeating method of a wireless repeating device according to Embodiment 2 of the present invention. Details are described below:

[0029] In step S301, a WIFI connection is established between an initialized upstream WLAN Client interface of a wireless repeating device and an upstream AP.

[0030] In this embodiment, initializing a WLAN Client interface of an upstream wireless repeating device may be initialing one upstream WLAN Client interface, and may also be

initializing multiple upstream WLAN Client interfaces, which is not used to limit the present invention here.

[0031] In step S302, network connection information of the upstream AP is obtained, and the network connection information of the upstream AP is synchronized to a downstream WLAN AP interface.

[0032] In this embodiment, the network connection information may include an encryption mode of a network connection, password information of a network connection, service set identifier (Service Set Identifier, SSID) information, an authentication manner, a physical working channel, and so on.

[0033] In step S303, the initialized upstream WLAN Client interface is deregistered.

[0034] In this embodiment, when the synchronization is completed, the initialized upstream WLAN Client interface is deregistered, to prevent an interface which is not deregistered from occupying a system resource.

[0035] In step S304, a connection is established between a downstream wireless STA and the downstream WLAN AP interface that is corresponding to the synchronized upstream AP.

[0036] In this embodiment, a network connection may be established between a downstream wireless STA and a downstream WLAN AP interface, and network connections may also be established between multiple downstream wireless STAs and a same downstream WLAN AP interface.

[0037] In step S305, if the downstream wireless STA and the downstream WLAN AP interface that is corresponding to the synchronized upstream AP are connected successfully, STA MAC address information is obtained.

[0038] In this embodiment, if the downstream wireless STA and the downstream WLAN AP interface that is corresponding to the synchronized upstream AP are connected successfully, STA MAC address information corresponding to the STA is obtained; if the downstream wireless STA and the downstream WLAN AP interface that is corresponding to the synchronized upstream AP are not connected successfully, the network connection continues to be performed.

[0039] In step S306, an upstream WLAN Client interface in a mapping relationship with an STA MAC address is established.

[0040] In this embodiment, by establishing the upstream WLAN Client interface which is in the mapping relationship with the STA MAC address, automatic mapping from the STA MAC address to the upstream WLAN Client interface is completed.

[0041] In step S307, management is performed, according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, on data forwarded

between the upstream AP and the downstream wireless STA, where the data is management action data or service data.

[0042] In this embodiment, management actions may be associate (Associate), authenticate (Authenticate), disassociate notify (Disassociate notify), deauthenticate notify (Deauthenticate notify), and reassociate (Reassociate).

[0043] Optionally, when the data is management action data and an action initiator is the upstream AP, step S307 specifically is:

1. Through the upstream WLAN Client interface, management action data sent by the upstream AP is received, and a management action is completed; and

2. According to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, a downstream wireless STA corresponding to the upstream WLAN Client interface is searched for, and the management action is completed between a downstream WLAN AP interface corresponding to the upstream AP interface, and the downstream wireless STA.

[0044] When the management action is deauthenticate notify, after step 2, the following step is further included:

deregistering a downstream WLAN AP interface corresponding to the STA, and the upstream WLAN Client interface.

[0045] Optionally, when the data is management action data and an action initiator is the downstream wireless STA, step S307 specifically is:

1. Through the downstream WLAN AP interface, management action data sent by the downstream wireless STA is received, and a management action is completed; and

2. According to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, an upstream WLAN Client interface corresponding to the downstream wireless STA is searched for, and the management action is completed between the upstream WLAN Client interface found by searching and an upstream AP corresponding to the downstream WLAN AP interface.

[0046] When the management action is Deauthenticate notify, after step 2, the following step is further included:

deregistering a downstream WLAN AP interface corresponding to the STA, and the upstream WLAN Client interface.

[0047] For ease of understanding, an implementation process in which a WLAN Repeater performs association is illustrated below by using a specific implementation example, but the present invention is not limited to the implementation process of the implementation example. It is

assumed that the upstream AP is a single AP and downstream stations are STA1, STA2, ..., STAN.

A working flow of the WLAN Repeater is as shown in FIG. 4:

1. Associate an upstream AP and synchronize information;
2. An STA1 completes association;
- 5 3. A Repeater proxy completes association;
4. An STA2 completes association;
5. The Repeater proxy completes association;
- ...
6. An STAN completes association;
- 10 7. The Repeater proxy completes association;
8. The STA1 disassociates;
9. The Repeater proxy completes disassociation;
- ...

[0048] In this implementation example, the upstream AP attempts to be associated with the STA1. In this case, the upstream AP first sends an association management action to the WLAN Repeater, the WLAN Repeater synchronizes information of the downstream WLAN AP interface corresponding to the upstream AP, and by using the synchronization information, a WLAN Repeater proxy is associated with the STA1, so that the STA1 completes the association. Similarly, the upstream AP may be associated with other stations: STA2, STA3, ..., STAN. Contrariwise, when a certain station needs disassociation, the WLAN Repeater proxy may complete the disassociation.

[0049] Optionally, when the data is service data and the service data is from an upstream AP to a downstream wireless STA, step S307 specifically is:

- 25 1) Through the upstream WLAN Client interface, service data sent by the upstream AP is received;
- 2) According to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, a downstream wireless STA corresponding to the upstream WLAN Client interface is searched for, and a destination address corresponding to the service data is mapped into an STA MAC address corresponding to the downstream wireless STA;
- 30 and
- 3) Through the downstream WLAN AP interface, the mapped service data is sent to the downstream wireless STA.

[0050] Optionally, when the data is service data and the service data is from a downstream wireless STA to the upstream AP, step S307 specifically is:

1) Through the downstream WLAN AP interface, service data sent by the downstream wireless STA is received;

2) According to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, an upstream WLAN Client interface corresponding to the downstream wireless STA is searched for, and a source address of the service data is mapped into a WLAN Client address corresponding to the upstream WLAN Client interface; and

3) Through the upstream WLAN Client interface found by searching, the mapped service data is sent to an upstream AP corresponding to the downstream WLAN AP interface.

Embodiment 3

10 **[0051]** FIG. 5 is a structural diagram of a wireless repeating device according to Embodiment 3 of the present invention; and for ease of illustration, only parts related to the embodiment of the present invention are shown.

[0052] The wireless repeating device includes a synchronizing unit 51, a mapping unit 52, and a data management unit 53.

15 **[0053]** The synchronizing unit 51 is configured to synchronize network connection information of an upstream AP to a downstream WLAN AP interface of the wireless repeating device after the connection between a wireless repeating device and the upstream AP is established.

[0054] The mapping unit 52 is configured to obtain, according to the downstream WLAN AP interface corresponding to the synchronized upstream AP, downstream wireless STA MAC address information, and establish an upstream WLAN Client interface which is in a mapping relationship with an STA MAC address.

20 **[0055]** The data management unit 53 is configured to perform, according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, management on data forwarded between the upstream AP and a downstream wireless STA, where the data is management action data or service data.

[0056] The wireless repeating device according to this embodiment of the present invention may be used in Embodiment 1 of the foregoing corresponding method. Reference may be made to the foregoing description of Embodiment 1 for details, which are not repeatedly described here.

30 **[0057]** In this embodiment, the wireless repeating device establishes the upstream WLAN Client interface which is in the mapping relationship with the STA MAC address by synchronizing the network connection information of the upstream AP to the downstream WLAN AP interface; based on the foregoing mapping relationship, for actions of operations performed on a data flow or

management flow between the upstream AP and the upstream WLAN Client interface, all the actions may be performed by a downstream WLAN AP interface proxy corresponding to the upstream AP interface, and a certain downstream STA, where the downstream STA may be searched for through the mapping relationship between the STA MAC address and the upstream
5 WLAN Client interface, thereby achieving effective transparent transmission of an attached wireless STA MAC address. Therefore, for corresponding actions of authentication and accounting performed by an upstream AAA authentication party or accounting party on the upstream WLAN Client interface through the upstream AP, all the corresponding actions may be performed by a downstream WLAN AP interface proxy corresponding to the upstream AP, and a certain
10 downstream STA. In this manner, it is achieved that the authentication or accounting party may perform accounting on an STA MAC address of each attached STA separately, thereby meeting a requirement of unified authentication/accounting based on a MAC address. Meanwhile, when a WLAN Repeater is interconnected with some upstream gateway devices with enabled DHCP spoofing/flooding functions, a DHCP Server of an upstream device may still implement normal
15 functions such as IP address assignment or lease renewing, and an STA at a WLAN Client side may obtain a corresponding IP address and continue with Internet access.

Embodiment 4

[0058] FIG. 6 is a structural diagram of a wireless repeating device according to Embodiment 4 of the present invention; and for ease of illustration, only parts related to the embodiment of the
20 present invention are shown.

[0059] The wireless repeating device includes a synchronizing unit 61, a mapping unit 62, and a data management unit 63.

[0060] A difference between this embodiment and Embodiment 3 is that the synchronizing unit 61 specifically includes a first connection module 611, a synchronizing module 612, and a
25 deregistration module 613.

[0061] The first connection module 611 is configured to establish a WIFI connection between an initialized upstream WLAN Client interface of the wireless repeating device and an upstream AP.

[0062] The synchronizing module 612 is configured to obtain network connection information of the upstream AP, and synchronize the network connection information of the upstream AP to a
30 downstream WLAN AP interface.

[0063] The deregistration module 613 is configured to deregister the initialized upstream

WLAN Client interface.

[0064] Furthermore, the mapping unit 62 specifically includes a second connection module 621, an obtaining module 622, and a mapping establishment module 623.

5 **[0065]** The second connection module 621 is configured to establish a connection between a downstream wireless STA and the downstream WLAN AP interface that is corresponding to the synchronized upstream AP.

[0066] The obtaining module 622 is configured to, if the downstream wireless STA and the downstream WLAN AP interface that is corresponding to the synchronized upstream AP are connected successfully, obtain STA MAC address information.

10 **[0067]** The mapping establishment module 623 is configured to establish a WLAN Client interface which is in a reversible single mapping relationship with an STA MAC address.

[0068] In this embodiment, the mapping relationship between the STA MAC address and the established upstream WLAN Client interface is the reversible single mapping relationship.

15 **[0069]** Furthermore, when the data is management action data and an action initiator is the upstream AP, the data management unit 63 is specifically configured to:

through the upstream WLAN Client interface, receive management action data sent by the upstream AP, and complete a management action; and

according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, search for a downstream wireless STA corresponding to the upstream WLAN Client interface, and complete a management action between a downstream WLAN AP interface corresponding to an upstream AP interface, and the downstream wireless STA.

20

[0070] Furthermore, when the data is management action data and an action initiator is the downstream wireless STA, the data management unit 63 is specifically configured to:

25 through the downstream WLAN AP interface, receive management action data sent by the downstream wireless STA, and complete a management action; and

according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, search for an upstream WLAN Client interface corresponding to the downstream wireless STA, and complete a management action between the upstream WLAN Client interface found by searching and an upstream AP corresponding to the downstream WLAN AP interface.

30

[0071] In this embodiment, management actions may specifically be associate Associate, authenticate Authenticate, disassociate notify Disassociate notify, deauthenticate notify Deauthenticate notify, and reassociate Reassociate.

[0072] When the management action is Deauthenticate notify, the data management unit 63 is

further configured to deregister a downstream WLAN AP interface corresponding to the STA, and the upstream WLAN Client interface.

[0073] Furthermore, when the data is service data and the service data is from an upstream AP to a downstream wireless STA, the data management unit 63 is specifically configured to:

5 through the upstream WLAN Client interface, receive service data sent by the upstream AP;

according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, search for a downstream wireless STA corresponding to the upstream WLAN Client interface, map a destination address corresponding to the service data
10 into an STA MAC address corresponding to the downstream wireless STA; and

through the downstream WLAN AP interface, send the mapped service data to the downstream wireless STA.

[0074] Furthermore, when the data is service data and the service data is from a downstream wireless STA to an upstream AP, the data management unit 63 is specifically configured to:

15 through the downstream WLAN AP interface, receive service data sent by the downstream wireless STA;

according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, search for an upstream WLAN Client interface corresponding to the downstream wireless STA, and map a source address of the service data into a
20 WLAN Client address corresponding to the upstream WLAN Client interface; and

through the upstream WLAN Client interface found by searching, send the mapped service data to an upstream AP corresponding to the downstream WLAN AP interface.

[0075] The wireless repeating device according to this embodiment of the present invention may be used in Embodiment 2 of the foregoing corresponding method. Reference may be made to
25 the description of Embodiment 2 for details, which are not repeatedly described here.

[0076] It should be noted that in the foregoing embodiments of apparatus and system, the included units are classified according to function logic, but the present invention is not limited to the foregoing classification, as long as corresponding functions can be realized. In addition, specific names of the functional units are also only for ease of differentiation, and are not intended to limit
30 the protection scope of the present invention.

[0077] Moreover, persons of ordinary skill in the art may understand that all or part of the steps in the method of the foregoing embodiments of the present invention may be implemented by a program instructing relevant hardware. The program may be stored in a computer readable storage medium, where the storage medium may be a ROM/RAM, a magnetic disk, or an optical disk, and

so on.

[0078] The foregoing is merely exemplary embodiments of the present invention, and is not intended to limit the present invention. Any modification, equivalent replacement, and improvement made without departing from the spirit and principle of the present invention shall fall

5 within the protection scope of the present invention.

CLAIMS

What is claimed is:

1. A repeating method of a wireless repeating device, wherein the method comprises the following steps:

5 synchronizing network connection information of an upstream AP to a downstream WLAN AP interface of the wireless repeating device after the wireless repeating device establishes a connection with the upstream AP;

 obtaining, according to the downstream WLAN AP interface corresponding to the synchronized upstream AP, downstream wireless STA MAC address information, and establishing
10 an upstream WLAN Client interface which is in a mapping relationship with an STA MAC address;
 and

 performing, according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, management on data forwarded between the upstream AP and a downstream wireless STA.

15 2. The method according to claim 1, wherein the step of synchronizing the network connection information of the upstream AP to the downstream WLAN AP interface of the wireless repeating device after the wireless repeating device establishes the connection with the upstream AP specifically is:

 establishing a WIFI connection between an initialized upstream WLAN Client interface of the
20 wireless repeating device and the upstream AP;

 obtaining the network connection information of the upstream AP, and synchronizing the network connection information of the upstream AP to the downstream WLAN AP interface; and

 deregistering the initialized upstream WLAN Client interface.

25 3. The method according to claim 1, wherein the step of obtaining, according to the downstream WLAN AP interface corresponding to the synchronized upstream AP, the downstream wireless STA MAC address information, and establishing the upstream WLAN Client interface which is in the mapping relationship with the STA MAC address specifically is:

 establishing a connection between the downstream wireless STA and the downstream WLAN AP interface that is corresponding to the synchronized upstream AP;

30 if the downstream wireless STA and the downstream WLAN AP interface that is corresponding to the synchronized upstream AP are connected successfully, obtaining STA MAC address information; and

establishing a WLAN Client interface which is in a mapping relationship with the STA MAC address.

4. The method according to any one of claims 1 to 3, wherein the mapping relationship between the STA MAC address and the established upstream WLAN Client interface is a reversible single mapping relationship.

5. The method according to claim 1, wherein when the data is management action data and an action initiator is the upstream AP, the step of performing, according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, the management on the data forwarded between the upstream AP and the downstream wireless STA specifically is:

through the upstream WLAN Client interface, receiving management action data sent by the upstream AP, and completing a management action; and

according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, searching for a downstream wireless STA corresponding to the upstream WLAN Client interface, and completing a management action between a downstream WLAN AP interface corresponding to an upstream AP interface, and the downstream wireless STA.

6. The method according to claim 1, wherein when the data is management action data and an action initiator is the downstream wireless STA, the step of performing, according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, the management on the data forwarded between the upstream AP and the downstream wireless STA specifically is:

through the downstream WLAN AP interface, receiving management action data sent by the downstream wireless STA, and completing a management action; and

according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, searching for an upstream WLAN Client interface corresponding to the downstream wireless STA, and completing a management action between the upstream WLAN Client interface found by searching and an upstream AP that is corresponding to the downstream WLAN AP interface.

7. The method according to claim 5 or 6, wherein management actions specifically are: associate Associate, authenticate Authenticate, disassociate notify Disassociate notify, deauthenticate notify Deauthenticate notify, and reassociate Reassociate; wherein when the management action is deauthenticate notify, the method further comprises the following step:

deregistering a downstream WLAN AP interface corresponding to the STA, and the upstream WLAN Client interface.

8. The method according to claim 1, wherein when the data is service data and the service data is from the upstream AP to the downstream wireless STA, the step of performing, according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, the management on the data forwarded between the upstream AP and the downstream

5 wireless STA specifically is:

through the upstream WLAN Client interface, receiving service data sent by the upstream AP;

according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, searching for a downstream wireless STA corresponding to the upstream WLAN Client interface, and mapping a destination address corresponding to the service
10 data into an STA MAC address corresponding to the downstream wireless STA; and

through the downstream WLAN AP interface, sending the mapped service data to the downstream wireless STA.

9. The method according to claim 1, wherein when the data is service data and the service data is from the downstream wireless STA to the upstream AP, the step of performing, according to the
15 mapping relationship between the STA MAC address and the established upstream WLAN Client interface, the management on the data forwarded between the upstream AP and the downstream wireless STA specifically is:

through the downstream WLAN AP interface, receiving service data sent by the downstream wireless STA;

20 according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, searching for an upstream WLAN Client interface corresponding to the downstream wireless STA, and mapping a source address of the service data into a WLAN Client address corresponding to the upstream WLAN Client interface; and

through the upstream WLAN Client interface found by searching, sending the mapped service
25 data to an upstream AP corresponding to the downstream WLAN AP interface.

10. A wireless repeating device, comprising:

a synchronizing unit, configured to synchronize network connection information of an upstream AP to a downstream WLAN AP interface of the wireless repeating device after a connection between the wireless repeating device and the upstream AP is established;

30 a mapping unit, configured to obtain, according to the downstream WLAN AP interface corresponding to the synchronized upstream AP, downstream wireless STA MAC address information, and establish an upstream WLAN Client interface which is in a mapping relationship with an STA MAC address; and

a data management unit, configured to perform, according to the mapping relationship between

the STA MAC address and the established upstream WLAN Client interface, management on data forwarded between the upstream AP and a downstream wireless STA.

11. The wireless repeating device according to claim 10, wherein the synchronizing unit comprises:

5 a first connection module, configured to establish a WIFI connection between an initialized upstream WLAN Client interface of the wireless repeating device and the upstream AP;

a synchronizing module, configured to obtain the network connection information of the upstream AP, and synchronize the network connection information of the upstream AP to the downstream WLAN AP interface; and

10 a deregistration module, configured to deregister the initialized upstream WLAN Client interface.

12. The wireless repeating device according to claim 10, wherein the mapping unit specifically comprises:

15 a second connection module, configured to establish a connection between the downstream wireless STA and the downstream WLAN AP interface that is corresponding to the synchronized upstream AP;

an obtaining module, configured to, if the downstream wireless STA and the downstream WLAN AP interface that is corresponding to the synchronized upstream AP are connected successfully, obtain STA MAC address information; and

20 a mapping establishment module, configured to establish a WLAN Client interface which is in a reversible single mapping relationship with the STA MAC address.

13. The wireless repeating device according to any one of claims 10 to 12, wherein the mapping relationship between the STA MAC address and the established upstream WLAN Client interface is a reversible single mapping relationship.

25 14. The wireless repeating device according to claim 10, wherein when the data is management action data and an action initiator is the upstream AP, the data management unit is specifically configured to:

through the upstream WLAN Client interface, receive management action data sent by the upstream AP, and complete a management action; and

30 according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, search for a downstream wireless STA corresponding to the upstream WLAN Client interface, and complete a management action between a downstream WLAN AP interface corresponding to an upstream AP interface and the downstream wireless STA.

15. The wireless repeating device according to claim 10, wherein when the data is management

action data and an action initiator is the downstream wireless STA, the data management unit is specifically configured to:

through the downstream WLAN AP interface, receive management action data sent by the downstream wireless STA, and complete a management action; and

5 according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, search for an upstream WLAN Client interface corresponding to the downstream wireless STA, and complete a management action between the upstream WLAN Client interface found by searching and an upstream AP that is corresponding to the downstream WLAN AP interface.

10 16. The wireless repeating device according to claim 14 or 15, wherein management actions specifically are associate Associate, authenticate Authenticate, disassociate notify Disassociate notify, deauthenticate notify Deauthenticate notify, and reassociate Reassociate;

when the management action is deauthenticate notify, the data management unit is further configured to deregister a downstream WLAN AP interface corresponding to the STA, and the
15 upstream WLAN Client interface.

17. The wireless repeating device according to claim 10, wherein when the data is service data and the service data is from the upstream AP to the downstream wireless STA, the data forwarding unit is specifically configured to:

through the upstream WLAN Client interface, receive service data sent by the upstream AP;

20 according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, search for a downstream wireless STA corresponding to the upstream WLAN Client interface, and map a destination address corresponding to the service data into an STA MAC address corresponding to the downstream wireless STA; and

through the downstream WLAN AP interface, send the mapped service data to the downstream
25 wireless STA.

18. The wireless repeating device according to claim 10, wherein when the data is service data and the service data is from the downstream wireless STA to the upstream AP, the data forwarding unit is specifically configured to:

30 through the downstream WLAN AP interface, receive service data sent by the downstream wireless STA;

according to the mapping relationship between the STA MAC address and the established upstream WLAN Client interface, search for an upstream WLAN Client interface corresponding to the downstream wireless STA, and map a source address of the service data into a WLAN Client address corresponding to the upstream WLAN Client interface; and

through the upstream WLAN Client interface found by searching, send the mapped service data to an upstream AP corresponding to the downstream WLAN AP interface.