

(19) World Intellectual Property Organization
International Bureau



(43) International Publication Date
26 September 2002 (26.09.2002)

PCT

(10) International Publication Number
WO 02/075906 A2

(51) International Patent Classification⁷: **H02K 49/04**

(74) Agents: **COSTANZA, Kevin, S.** et al.; Seed Intellectual Property Law Group PLLC, Suite 6300, 701 Fifth Avenue, Seattle, WA 98104-7092 (US).

(21) International Application Number: PCT/US02/08401

(22) International Filing Date: 13 March 2002 (13.03.2002)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
09/811,343 15 March 2001 (15.03.2001) US
09/898,917 3 July 2001 (03.07.2001) US

(71) Applicant (for all designated States except US): **MAGNADRIVE CORPORATION** [US/US]; 1177 Fairview Avenue North, Seattle, WA 98109-4418 (US).

(72) Inventor; and

(75) Inventor/Applicant (for US only): **KILLEN, Richard** [US/US]; 24427 236th Court SE, Maple Valley, WA 98038 (US).

(81) Designated States (*national*): AE, AG, AL, AM, AT, AU, AZ, BA, BB, BG, BR, BY, BZ, CA, CH, CN, CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, ES, FI, GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE, KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD, MG, MK, MN, MW, MX, MZ, NO, NZ, OM, PH, PL, PT, RO, RU, SD, SE, SG, SI, SK, SL, TJ, TM, TN, TR, TT, TZ, UA, UG, US, UZ, VN, YU, ZA, ZM, ZW.


(84) Designated States (*regional*): ARIPO patent (GH, GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW), Eurasian patent (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), European patent (AT, BE, CH, CY, DE, DK, ES, FI, FR, GB, GR, IE, IT, LU, MC, NL, PT, SE, TR), OAPI patent (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

Published:

— without international search report and to be republished upon receipt of that report

[Continued on next page]

(54) Title: **ADJUSTABLE MAGNETIC COUPLER**



(57) Abstract: An adjustable coupler has a group of magnet rotors with permanent magnets on a first shaft separated by air gaps from non-ferrous conductor rotors on a second shaft presented by a group of conductor rotors. In one embodiment, the first and second shafts are coupled together at a spherical bearing that permits relative rotation between the shafts, but that limits relative lateral movement between the shafts. In the same or other embodiments, the group of magnet rotors are coupled together by pivoting linkages, and/or one of the magnet rotors is coupled to the outside of a hub for moving axially along the first shaft.



WO 02/075906 A2



For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.