

(19) World Intellectual Property
Organization
International Bureau



(43) International Publication Date
11 November 2004 (11.11.2004)

PCT

(10) International Publication Number
WO 2004/096428 A1

(51) International Patent Classification⁷: **B01J 8/00**, 8/06

(21) International Application Number:
PCT/US2004/012390

(22) International Filing Date: 21 April 2004 (21.04.2004)

(25) Filing Language: English

(26) Publication Language: English

(30) Priority Data:
60/465,171 24 April 2003 (24.04.2003) US

(71) Applicant (for all designated States except US): **CAT
TECH, INC.** [US/US]; 1149 Ellsworth, Suite 327,
Pasadena, TX 77506 (US).

(71) Applicant and

(72) Inventor: **BRENNOM, Stephen** [US/US]; 1149
Ellsworth, Suite 327, Pasadena, TX 77506 (US).


(74) Agents: **PATTERSON, William, B.** et al.; Moser, Patter-
son & Sheridan, L.L.P., 3040 Post Oak Boulevard, Suite
1500, Houston, TX 77056 (US).

(81) Designated States (unless otherwise indicated, for every
kind of national protection available): AE, AG, AL, AM,
AT, AU, AZ, BA, BB, BG, BR, BW, BY, BZ, CA, CH, CN,
CO, CR, CU, CZ, DE, DK, DM, DZ, EC, EE, EG, ES, FI,
GB, GD, GE, GH, GM, HR, HU, ID, IL, IN, IS, JP, KE,
KG, KP, KR, KZ, LC, LK, LR, LS, LT, LU, LV, MA, MD,
MG, MK, MN, MW, MX, MZ, NA, NI, NO, NZ, OM, PG,
PH, PL, PT, RO, RU, SC, SD, SE, SG, SK, SL, SY, TJ, TM,
TN, TR, TT, TZ, UA, UG, US, UZ, VC, VN, YU, ZA, ZM,
ZW.

(84) Designated States (unless otherwise indicated, for every
kind of regional protection available): ARIPO (BW, GH,
GM, KE, LS, MW, MZ, SD, SL, SZ, TZ, UG, ZM, ZW),
Eurasian (AM, AZ, BY, KG, KZ, MD, RU, TJ, TM), Euro-
pean (AT, BE, BG, CH, CY, CZ, DE, DK, EE, ES, FI, FR,

[Continued on next page]

(54) Title: METHOD AND APPARATUS FOR LOADING CATALYST



(57) Abstract: Methods and apparatus are disclosed for filling solid particles into a vertical tube by conveying the particles downwardly into the tube along a loading tool that softens the fall of the particles and provides even filling of the tube. The loading tool includes a center member and a plurality of damper members that can be adapted in particular cases to the actual type of particles and the tube diameter. The damper members can be stiff or flexible since they do not occupy a substantial portion of the cross section of the tube at any particular axial location. In operation, the center member can be jerked during the filling operation while simultaneously being lifted up gradually as the tube fills or it can be sequentially lifted. The damper members reduce the falling velocity of the particles and divert the particles from falling in straight downward paths. This avoids bridge formation and breakage of the particles during filling.



GB, GR, HU, IE, IT, LU, MC, NL, PL, PT, RO, SE, SI, SK, TR), OAPI (BF, BJ, CF, CG, CI, CM, GA, GN, GQ, GW, ML, MR, NE, SN, TD, TG).

— *before the expiration of the time limit for amending the claims and to be republished in the event of receipt of amendments*

Published:

— *with international search report*

For two-letter codes and other abbreviations, refer to the "Guidance Notes on Codes and Abbreviations" appearing at the beginning of each regular issue of the PCT Gazette.